

Description

The present invention relates to a so-called engagement profile or a beam of the type defined in more detail in the preamble of claim 1 and disclosed in FI-B-73284 or FI-B-66453.

A beam according to the invention is preferably made of thin steel plate by bending in a manner that the beam comprises one or several web plates extending lengthwise of the beam substantially at a constant distance from each other and are perpendicular or inclined relative to the fastening plane of the beam. These web members are interconnected by members of the same sheet material. Thus, the beam is preferably made of a single sheet blank. For fastening it to its underlying bed, the beam further comprises one or several fastening strips, which are preferably integral parts of the web members and whereby the beam is fastened to a level supported by said beam. Such a supported level can be made e.g. of wood, such as boards, woodboard, plywood, blockboard, chipboard, fiberboard, gypsum board or the like, into which the engagement profiles formed in a per se known manner on fastening strips sink and engage as the strips are clamped against the level e.g. by means of a suitable press. The beam can also be used for supporting and reinforcing a concrete slab, whereby it is placed on top of a concrete slab during its casting prior to the setting of concrete, the studs engaging in concrete. Thus, in a particularly preferred case, the studs are designed so that the blade side of said studs is provided with a transverse toothing or roughening, as disclosed in the Applicants' earlier Patent No. 65643.

A drawback with the above type of beam is, however, a relatively weak strength under major stresses as the sheet material of such beam is thin, the sheet thicknesses being e.g. 1—1,5 mm. Such a thin sheet material begins to fracture quite easily because of buckling. In order to provide a beam with greater strength, it can of course be made of a thicker sheet material. However, manufacturing will be more difficult and costs will be higher because the raw material is more expensive and working is more difficult. Especially, the preparation of engagement studs will be more difficult with thicker sheet material.

When studying tensions in the above type of beam it can be noted, especially as far as bending is concerned, that the greatest stresses occur in the upper and lower portions of the beam cross-section while in the mid-portion, in a so-called neutral plane, the stress is zero. In the upper edge of the cross-section, i.e. in fastening strips, there prevails a compression stress while in the lower edge there is accordingly a tensile stress. Some of the stresses in the fastening strips is naturally taken up by the plate or board which is supported by the beam, but if this plate is weak, the stress on the strips may become too great, especially since such strips are weakened by the reduction in the amount of basic material as a result of stamping of the studs.

The basic idea and object of the invention is thus to provide a solution to the above problems and to improve the strength of an engagement beam without substantially increasing the actual material thickness of a beam so as not to unduly increase the weight and manufacturing costs of a beam.

The invention is mainly characterized by what is set forth in the characterizing clause of the main claim.

The invention will now be described in more detail with reference to made to the accompanying drawings which illustrate a few preferred embodiments of the invention and their details and advantages. In the drawings

Fig. 1 is a perspective view of one preferred embodiment of a beam of the invention as seen obliquely from the front,

Figs. 2—5 are perspective partial views showing mainly diagrammatically different embodiments of the fastening strips for a beam of the invention,

Fig. 6 is another perspective view showing an embodiment of the invention in which the main reinforcement strip comprises a flat steel strip,

Fig. 7 is a partial view of the reinforcement strip of the preceding embodiment,

Fig. 8 is a partial view of one modification of the embodiment shown in Fig. 6,

Fig. 9 shows an embodiment in which the reinforcement strips include studs the same way as fastening strips,

Fig. 10 shows one modification of the embodiment shown in Fig. 9,

Fig. 11 shows an embodiment in which the reinforcement strip comprises a steel bar and

Fig. 12 shows yet another embodiment of the beam.

A beam shown in the embodiment of Fig. 1 comprises a sheet blank, e.g. a blank of 1—2 mm thick, galvanized or black steel sheet, which is bent either by means of a bending press or by rolling into a shaped list having the shape of a flat-bottomed V, wherein sides 1 serve as web portions interconnected by an intermediate strip 2. Joined to the ends of sides 1 are fastening strips 3, formed in a per se known manner with fastening studs or teeth 4 for fastening the beam to a sheet blank or a boarding to be supported or reinforced e.g. by compressing with an appropriate press so that studs 4 are tightened in a sheet blank. Stud 4 are preferably fitted with a transverse roughening or teeth for securing them more firmly than smooth studs. The beam can also be used for reinforcing concrete slabs, especially rather thin slabs, the beams being placed on top of a concrete slab inside a casting mould during the casting of concrete so as to set the studs completely inside the concrete. After the concrete is set, the result is a firm and relatively rigid, but still rather light concrete slab element, which is suitable for a wall or floor element. Of course, the concrete can be further reinforced e.g. with a steel-wire mesh. According to the invention, the beam is reinforced by fitting the most stress-

laden parts thereof with reinforcement strips 5, 6, 7, extending lengthwise of the beam and preferably made of the same material as the beam itself. The first reinforcement strip 5 is thus placed at intermediate strip 2 outside and/or inside extending crosswise slightly on top of the web portions. In addition, further reinforcement strips 6, 7 are placed upon fastening strips 3, i.e. on the opposite side of studs 4, and those too extend slightly on top of the web portions. The reinforcement strips of this embodiment are preferably secured by means of e.g. resistance welding, such as disc welding, the jointing proceeding lengthwise of the beam.

The reinforcement of fastening strips 3 can also be achieved preferably by making the fastening strips originally somewhat wider and then, after punching out the studs, by bending the extra width e.g. into a round hem (Fig. 2), a single hem (Fig. 3), a double hem (Fig. 4) or an open fold (Fig. 5). The reinforcement of fastening strips prevents them from buckling under major stresses, especially if the basic material, i.e. the building slab to be supported, has a poor bearing strength or if the question is about a boarding structure with a gap between individual boards.

Fig. 6 illustrates another embodiment of the invention, wherein the cross-section of a beam is substantially in the shape of a flat-bottomed V, the same way as in the preceding embodiment shown in Fig. 1. In this embodiment, the main reinforcement is provided by a flat reinforcement strip 5 which is preferably fastened in contact with the inner beam surface upon the intermediate strip 2. The fastening can be made even more effective in one of the following manners. The connection between sides 1 and intermediate strip 2 of a profiled beam can be rounded so as partially surround the edge of reinforcement strip 5. The width of reinforcement strip 5 is selected to slightly exceed the internal width of where it is mounted on a profiled beam. Furthermore, the side edges of a reinforcement strip can be provided with roughenings or ribs 8 (Fig. 7), which secure firmly to the walls of its mounting spot as said reinforcement strip 5 is forced in position e.g. in a press by means of a suitable tool and back stop or by rolling.

Fig. 8 discloses a modification of the embodiment shown in Fig. 6, wherein the fastening of a reinforcement strip 5 is secured with a profiled strip, designed so that its bent side portions clamp the side edges of intermediate strip 2 of the beam for locking reinforcement strip 5 in position. Profiled strip 9 is dimensioned so that the distance of its side portions from each other is slightly less than the width of intermediate strip 2 of the beam so, when clamping it in position, there will be a stress caused by deflection which clamps said reinforcement strip 5 firmly in position. Profiled strip 9 can also be provided with studs for fastening two boards with a beam.

According to one embodiment of the invention (Fig. 8), the reinforcement of a beam can also be provided in a manner that said fastening strips 3

comprise base strips 3', which are smooth, i.e. without studs 4, and join with sides 1, as well as reinforcement strips 6, 7 formed with studs 4. Reinforcement strips 6 and 7 are secured to base strips 3' e.g. by means of integrally formed welts 6', 7' by compressing or rolling the welts closed after pushing reinforcement strips 6, 7 into position on top of base strips 3'. For this engagement, the upper edge of sides 1 of the beam and the junction of base strips 3' are appropriately shaped so as to produce a bead 1' for securing the edge of the welt of a reinforcement strip therebelow.

In the embodiment shown in Fig. 9, said fastening strips 3 are provided with studs 4. In addition to that, said reinforcement strips 6, 7 are also provided with studs 4', whose spacing is at least roughly the same as that of the former studs. Such reinforcement strips are intended to be fastened in position after securing a beam firmly to a slab to be strengthened, whereby the reinforcement strips are compressed into position so that their studs 4' pass through the stud holes in fastening strip 3.

In the embodiment of Fig. 9, the reinforcement strip is made of round, so-called ribbed steel bar. Therefore, the lowest part of a beam cross-section is designed as a tube 10 for inserting a round ribbed steel bar 11 therein. After this, said ribbed bar 11 is secured even more firmly by shaping a tube 10 e.g. by lateral pressing to make it conform to the shape of a ribbed steel bar.

It is also possible to have several tubular members 10 as well as ribbed steel bars 11 serving as a reinforcement strip. Tube 10 can be made of sides 1 or it can be made separately and attached to a web plate.

The embodiment shown in Fig. 10 is in a way a combination of the embodiments shown in Figs. 8 and 9. In this embodiment, a fastening strip 3 consists of smooth cover strips 3'', joining with sides 1 and provided with holes 13, as well as of reinforcement strips or lists 6, 7 fitted with studs 4' the same way as in the embodiment of Fig. 9. These studs have the same spacing as holes 13 in cover strips 3''. When it is secured, the beam is first pressed against an engagement level so that cover strips 3'' come against the engagement level, whereafter the actual fastening is effected by pressing reinforcement lists 6, 7 in, so that their studs 4' penetrate into the engagement level through holes 13 in cover strips 3''.

In a very simple embodiment shown in Fig. 11, a beam of the invention only comprises a single side 1 and a single studded fastening strip 3, bent to an angle of circa 90° relative to a web plate. The lower edge of a web plate is provided with a tubular member 10, into which is fitted and secured a ribbed steel bar 11 serving as a reinforcement list the same way as above. Side 1 can be corrugated in longitudinal direction to provide a required rigidity.

In the above embodiments, a beam of the invention has been considered to have an equal height over its entire length. It is within the invention, however, to make a beam converging

at both ends, thus reducing the height of a profile towards the ends. Fig. 12 shows such a beam diagrammatically in side view. The ends of side 1 can be further provided with means 12 for locking the ends of ribbed steel bars 11. Thus, it is also possible to give the reinforcing steels a per se known prestress to increase the bearing capacity of a beam. The beam shown in Fig. 12 may have e.g. a V-shaped cross-section.

A beam as shown in Fig. 12 can be preferably manufactured by deep drawing technique, whereby the cross-section of a beam is substantially in the shape of a flat-bottomed V the same way as in Fig. 7. The reinforcement list can thus be a flat steel strip 5, fixed in position in a conventional manner. The design shown in Fig. 12 offers the advantage that even the gable edges of a beam will be provided with fastening studs, whereby the beam does not easily disengage from its position under varying loads over a longer period of time.

The above describes but a few examples of beam embodiments within the scope of the invention. It is obvious that the structures of these embodiments can still be arbitrarily combined with each other to create further embodiments which can thus be considered as part of the invention. It should also be noted that in certain cases a beam may have several sides 1 and fastening strips 3 as well as intermediate strips 2, whereby the cross-section of a beam can be e.g. in the shape of W. The beam can be manufactured by using either galvanized or black steel sheet. In the latter case, a finished, reinforced beam can be subjected to hot-dip galvanizing in a conventional manner. In certain cases, this might even improve the fastening of a reinforcement list, the galvanizing having the same effect as soldering. The cross-sectional shape of a beam may have a variety of alternatives in different embodiments. One and the same beam can be provided with one or a plurality of reinforcement lists 5 or 11.

Claims

1. A beam or the like substantially manufactured from rather thin sheet metal, the cross-sectional shape of said beam being substantially flat-bottomed V, said beam comprising two sides (1), two fastening strips (3), each joined at the edge of the same in an angular position to the first edge of respective side (1), and intermediate strip (2) joining the second edges of said sides (1) together and at least one reinforcement element extending lengthwise of said beam, said fastening strips (3) being provided with fastening means, such as studs (4) or the like, characterized in that said reinforcement element (5) is mounted in connection with the inner surface of said beam on said intermediate strip (2), substantially across said intermediate strip (2) to reach the joints between said sides (1) and said intermediate strip (2).

2. Beam as set forth in claim 1, characterized in that said joints between the sides (1) and the

intermediate strip (2) are rounded to surround at least partially the edges of reinforcement element (5).

3. Beam as set forth in claims 1 and 2, characterized in that the edges of said reinforcement element (5) are provided with a roughening or ribs (8).

4. Beam as set forth in claims 1 and 2, characterized in that the attachment of said reinforcement element (5) is secured by means of a shaped list (9), which is placed outside the beam and whose bent side edges are adapted to press the beam sides (1) from outside.

5. Beam as set forth in claim 4, characterized in that said shaped list (9) is provided with fastening means, such as arrays of studs.

6. Beam as set forth in claim 1, characterized in that said reinforcement element (5) comprises at least one ribbed bar-like steel element (11).

7. Beam as set forth in claim 1, characterized in that said ribbed bar-like steel element (11) is inserted in a tubular member forming at least a part of said intermediate strip (2).

Patentansprüche

1. Ein Balken oder dergleichen, der im wesentlichen aus ziemlich dünnem Blech hergestellt ist, die Querschnittsform des Balkens im wesentlichen ein mit flachem Boden versehenes V ist, der Balken zwei Seiten (1) umfasst, zwei Befestigungsbänder (3), wovon jedes an seiner Kante in einer Winkelposition mit der ersten Kante der jeweiligen Seite (1) verbunden ist, und ein Zwischenband (2) die zweiten Kanten der Seiten (1) miteinander verbindet und mindestens ein Verstärkungselement sich in Längsrichtung des Balkens erstreckt, und die Befestigungsbänder (3) mit einer Befestigungseinrichtung, wie beispielsweise Stiften (4) oder dergleichen ausgestattet sind, dadurch gekennzeichnet, dass das Verstärkungselement (5) mit der Innenfläche des Balkens auf dem Zwischenband (2) befestigt ist und sich im wesentlichen über das Zwischenband (2) erstreckt, um die Verbindungsstellen zwischen den Seiten (1) und dem Zwischenband (2) zu erreichen.

2. Balken nach Anspruch 1, dadurch gekennzeichnet, dass die Verbindungsstellen zwischen den Seiten (1) und dem Zwischenband (2) abgerundet sind, um zumindest teilweise die Kanten des Verstärkungselementes (5) zu umgeben.

3. Balken nach den Ansprüchen 1 und 2, dadurch gekennzeichnet, dass die Kanten des Verstärkungselementes (5) mit einer Aufrauhung oder mit Rippen (8) versehen sind.

4. Balken nach den Ansprüchen 1 und 2, dadurch gekennzeichnet, dass die Befestigung des Verstärkungselementes (5) mittels einer geformten Tafel (9) erfolgt, die an der Aussenseite des Kastens angebracht ist und deren umgebogene Seitenkanten geeignet sind, die Balkenseiten (1) von aussen anzudrücken.

5. Balken nach Anspruch 4, dadurch gekennzeichnet, dass die geformte Tafel (9) mit einer



at both ends, thus reducing the height of a profile towards the ends. Fig. 12 shows such a beam diagrammatically in side view. The ends of side 1 can be further provided with means 12 for locking the ends of ribbed steel bars 11. Thus, it is also possible to give the reinforcing steels a per se known prestress to increase the bearing capacity of a beam. The beam shown in Fig. 12 may have e.g. a V-shaped cross-section.

A beam as shown in Fig. 12 can be preferably manufactured by deep drawing technique, whereby the cross-section of a beam is substantially in the shape of a flat-bottomed V the same way as in Fig. 7. The reinforcement list can thus be a flat steel strip 5, fixed in position in a conventional manner. The design shown in Fig. 12 offers the advantage that even the gable edges of a beam will be provided with fastening studs, whereby the beam does not easily disengage from its position under varying loads over a longer period of time.

The above describes but a few examples of beam embodiments within the scope of the invention. It is obvious that the structures of these embodiments can still be arbitrarily combined with each other to create further embodiments which can thus be considered as part of the invention. It should also be noted that in certain cases a beam may have several sides 1 and fastening strips 3 as well as intermediate strips 2, whereby the cross-section of a beam can be e.g. in the shape of W. The beam can be manufactured by using either galvanized or black steel sheet. In the latter case, a finished, reinforced beam can be subjected to hot-dip galvanizing in a conventional manner. In certain cases, this might even improve the fastening of a reinforcement list, the galvanizing having the same effect as soldering. The cross-sectional shape of a beam may have a variety of alternatives in different embodiments. One and the same beam can be provided with one or a plurality of reinforcement lists 5 or 11.

Claims

1. A beam or the like substantially manufactured from rather thin sheet metal, the cross-sectional shape of said beam being substantially flat-bottomed V, said beam comprising two sides (1), two fastening strips (3), each joined at the edge of the same in an angular position to the first edge of respective side (1), and intermediate strip (2) joining the second edges of said sides (1) together and at least one reinforcement element extending lengthwise of said beam, said fastening strips (3) being provided with fastening means, such as studs (4) or the like, characterized in that said reinforcement element (5) is mounted in connection with the inner surface of said beam on said intermediate strip (2), substantially across said intermediate strip (2) to reach the joints between said sides (1) and said intermediate strip (2).

2. Beam as set forth in claim 1, characterized in that said joints between the sides (1) and the

intermediate strip (2) are rounded to surround at least partially the edges of reinforcement element (5).

3. Beam as set forth in claims 1 and 2, characterized in that the edges of said reinforcement element (5) are provided with a roughening or ribs (8).

4. Beam as set forth in claims 1 and 2, characterized in that the attachment of said reinforcement element (5) is secured by means of a shaped list (9), which is placed outside the beam and whose bent side edges are adapted to press the beam sides (1) from outside.

5. Beam as set forth in claim 4, characterized in that said shaped list (9) is provided with fastening means, such as arrays of studs.

6. Beam as set forth in claim 1, characterized in that said reinforcement element (5) comprises at least one ribbed bar-like steel element (11).

7. Beam as set forth in claim 1, characterized in that said ribbed bar-like steel element (11) is inserted in a tubular member forming at least a part of said intermediate strip (2).

Patentansprüche

1. Ein Balken oder dergleichen, der im wesentlichen aus ziemlich dünnem Blech hergestellt ist, die Querschnittsform des Balkens im wesentlichen ein mit flachem Boden versehenes V ist, der Balken zwei Seiten (1) umfasst, zwei Befestigungsbänder (3), wovon jedes an seiner Kante in einer Winkelposition mit der ersten Kante der jeweiligen Seite (1) verbunden ist, und ein Zwischenband (2) die zweiten Kanten der Seiten (1) miteinander verbindet und mindestens ein Verstärkungselement sich in Längsrichtung des Balkens erstreckt, und die Befestigungsbänder (3) mit einer Befestigungseinrichtung, wie beispielsweise Stiften (4) oder dergleichen ausgestattet sind, dadurch gekennzeichnet, dass das Verstärkungselement (5) mit der Innenfläche des Balkens auf dem Zwischenband (2) befestigt ist und sich im wesentlichen über das Zwischenband (2) erstreckt, um die Verbindungsstellen zwischen den Seiten (1) und dem Zwischenband (2) zu erreichen.

2. Balken nach Anspruch 1, dadurch gekennzeichnet, dass die Verbindungsstellen zwischen den Seiten (1) und dem Zwischenband (2) abgerundet sind, um zumindest teilweise die Kanten des Verstärkungselementes (5) zu umgeben.

3. Balken nach den Ansprüchen 1 und 2, dadurch gekennzeichnet, dass die Kanten des Verstärkungselementes (5) mit einer Aufrauung oder mit Rippen (8) versehen sind.

4. Balken nach den Ansprüchen 1 und 2, dadurch gekennzeichnet, dass die Befestigung des Verstärkungselementes (5) mittels einer geformten Tafel (9) erfolgt, die an der Aussenseite des Kastens angebracht ist und deren umgebogene Seitenkanten geeignet sind, die Balkenseiten (1) von aussen anzudrücken.

5. Balken nach Anspruch 4, dadurch gekennzeichnet, dass die geformte Tafel (9) mit einer



Befestigungseinrichtung, wie einer Reihe von Stiften, versehen ist.

6. Balken nach Anspruch 1, dadurch gekennzeichnet, dass das Verstärkungselement (5) mindestens ein geripptes, stabartiges Stahlelement (11) umfasst.

7. Balken nach Anspruch 1, dadurch gekennzeichnet, dass das gerippte, stabartige Stahlelement (11) in ein Rohrelement eingesetzt ist, das zumindest einen Teil des Zwischenbandes (2) bildet.

Revendications

1. Poutre ou pièce similaire fabriquée essentiellement en tôle relativement mince, la forme en coupe transversale de cette poutre étant essentiellement celle d'un V à fond plat, ladite poutre comprenant deux flancs (1), deux bandes de fixation (3) dont chacune est unie par son bord, en position angulaire, au premier bord du flanc (1) respectif, une bande intermédiaire (2) joignant ensemble les seconds bords desdits flancs (1) et au moins un élément de renfort s'étendant dans la direction longitudinale de ladite poutre, lesdites bandes de fixation (3) étant munies de moyens de fixation tels que des pointes (4) ou similaires, caractérisée en ce que ledit élément de renfort (5) est monté en rapport avec la surface interne de la poutre sur ladite bande intermédiaire (2), s'étendant sensiblement en travers de ladite bande intermédiaire (2) de manière à atteindre les joints

entre lesdits flancs (1) et ladite bande intermédiaire (2).

2. Poutre selon la revendication 1, caractérisée en ce que lesdits joints entre les flancs (1) et la bande intermédiaire (2) sont arrondis de façon à entourer au moins partiellement les bords de l'élément de renfort (5).

3. Poutre selon les revendications 1 et 2, caractérisée en ce que les bords dudit élément de renfort (5) sont pourvus d'une rugosité ou de nervures (8).

4. Poutre selon les revendications 1 et 2, caractérisée en ce que la fixation dudit élément de renfort (5) est assurée au moyen d'une lame profilée (9) qui est placée à l'extérieur de la poutre et dont les bords latéraux recourbés sont agencés de façon à presser les flancs (1) de la poutre par l'extérieur.

5. Poutre selon la revendication 4, caractérisée en ce que ladite lame profilée (9) est pourvue de moyens de fixation, tels que des rangées de pointes.

6. Poutre selon la revendication 1, caractérisée en ce que ledit élément de renfort (5) comprend au moins un élément en forme de barre d'acier nervurée (11).

7. Poutre selon la revendication 1, caractérisée en ce que ledit élément en forme de barre d'acier nervurée (11) est inséré dans un élément tubulaire qui constitue au moins une partie de ladite bande intermédiaire (2).