Description

The present invention pertains to systems in which tow or more data processors, or computers, are arranged together in a network. More particularly, the present invention relates to protocols of application programming interfaces utilised in computer networks.

Data processing systems, or computers such as personal computers (PCs) may be arranged in a local area network (LAN) for mutual communication. Typical available LANs may accommodate hundreds of thousands of PCs, and extend for several thousand metres, depending on the load that is placed on the network by the PCs. LANs may be configured in a variety of forms. For example, multiple PCs may be connected to a common bus, or connected to a ring, such as the token-ring network of International Business Machines Corporation (IBM). Another form of LAN connects the PCs in a multi-branch configuration ray be selected in accordance with the requirements of the given application.

In each case, a PC is incorporated in a LAN within a node, which includes the PC, a network adapter and pertinent software providing an interface between the PC and the physical adapter. The adapter in turn is connected to other nodes to form the network. The network adapters provide the physical interfaces for the corresponding PCs to communicate with each other over the network.

The associated software utilising the LAN includes various protocols that are effectively rules to govern communication over the network. Such rules, or protocols, are needed because multiple PCs in a network are sharing a common cable medium, and must communicate with each other over the cable medium reliably without interference from one another. In general, the protocols aid in such reliable communication, provide addressing for all computers on the network, and control the flow of data travelling between computers on the network. Typically, the protocols include such functions as data transmission, reception and acknowledgment over the cable.

The interface software utilised to operate a PC, or other computer, in a network may be considered to be structured in layers. An example of a LAN, or a portion of a LAN, is shown generally at 10 in Fig. 1, and includes two nodes designated as A and B. In node A, a PC A is indicated as being equipped with an adapter A including an adapter card, which is the physical layer 12 of the adapter A and which connects directly to the PC A. The necessary cable connections to the remainder of the network are made to the adapter card. The PC A may be equipped with application programming 14, which is the highest level software and is accessible by the user of the PC. At the other extreme of the layered software of node A is a low level link layer 16. The link layer software 16 is the communicating control software, the remainder of the LAN 10 by way of the adapter card physical layer 12. The link layer 16 is generally largely responsible for assembling bits into data units for transmission by the physical layer 12, or for checking and assembling bits received from elsewhere in the network by the adapter A. When information is to be transmitted by node A, the link layer 16 puts the data into the correct format and detects any errors that might occur.

It will be appreciated from Fig. 1 that the link layer 16 of adapter A is provided with the adapter physical layer 12. Additional interface software may be input directly into the PC A. Such software includes an adapter support interface 18, for example. Such an adapter support interface 18 may be provided to allow the application program 14 to use the adapter card by providing control blocks in the PC memory and calling the adapter support interface with an interrupt instruction.

An additional interface software layer may be utilised to provide the command functions for communication on the LAN. By 1985, IBM had provided what may be considered an industry standard for an application programming interface in the form of a network basic input/output system (NETBIOS). PC A is shown equipped with NETBIOS 20 as the highest level of interface software in communication with the application programming 14.

Node B includes a PC B to which is connected an adapter B as the physical interface between the PC B and the remainder of the network. A wiring system 22 is shown as connecting the two nodes A and B in the LAN 10 through their respective adapters.

As in the case of node A, node B includes several layers of software, the highest layer being application programming 24 to which the user of node B has access. NETBIOS 26 is provided for the command functions, and communicates through the adapter support interface to the link layer software 30, which is provided with a physical layer adapter card 32 in the adapter B.

The various interface software layers may be provided either as incorporated in the adapter card or resident in the PC memory. It will be appreciated that additional software layers and features may be included in a network node. Further, additional details of the software layers indicated in Fig. 1 are known in the industry and need not be described in detail herein, nor referred to for an explanation and understanding of the present invention.

In the NETBIOS version heretofore available, there exists a protocol generally identified by the command SEND, which is utilised in sending a message between two nodes in a LAN, once a NETBIOS session has been established between the two nodes. For example, a message to be send form PC A of node A to PC B of node B is input through the application programming 14 at PC A along with the com-

mand SEND. The message is then appropriately prepared by NETBIOS 20, and transmission is effected through the adapter A by the link layer software 16. When the message is received at the link layer software 30 of node B, through the corresponding adapter B, a link level acknowledgment is transmitted from node B to node A to indicate that a message has been received. This link level acknowledgment is itself then received as a message by the link level software 16 of node A.

If the message originally sent to node B is appropriately processed and communicated in its entirety to the user at PC B through the layers of node B software, an acknowledgment indicating that fact is originated by NETBIOS 26 of node B and sent, via the cable 22, to NETBIOS 20 of node A where such acknowledgment can be communicated to the PC A user through the application programming 14. If however, the message originally sent to node B is not received, or not completely received, at the application level 24 of PC B, a response message to that effect will be transmitted by NETBIOS 26 of node B to NETBIOS 20 of node A for communication to the user at PC A. In either case, the acknowledgment regarding the receipt of the message at the application level 24 of PC B is originated after the message is processed by NETBIOS 26 and attempted to be conveyed to the user at PC B. Additionally, this acknowledgment is originated at a higher software level at NETBIOS 26 than the link level 30, and is more sophisticated than a link level acknowledgment which simply indicates that a transmission has been received at the node without giving details of the reception. Following the higher level NETBIOS acknowledgment to node A, node A sends a link layer acknowledgment to node B that the higher level acknowledgment has been received at node A.

A control flow diagram of the SEND function of NETBIOS is shown generally at 40 in Fig. 2. Starting at block 42, the user of the PC wanting to send a message inputs the message and initiates the SEND command. The SEND function is processed in the NETBIOS, as indicated in block 44, and is then transmitted by the adapter over the network cable, as indicated at block 46. The message initiating node must pause until transmission of the SEND message along the network to the receiving node is complete, as indicated by block 48. The link level acknowledgment that a transmission has been received at the link level of the receiving node signals completion of the transmission. When the transmission of the message is complete, the initiating mode must await receipt of an acknowledgment indicating whether the transmitted message has been received by the PC user of the receiving node, as shown by block 50. As discussed hereinabove, the SEND function employs two additional al acknowledgments. One such acknowledgment is a high level NETBIOS acknowledgment initiated by the receiving node to indicate whether all, a part, or none of the message was actually received by the application level of the receiving node. The other acknowledgment is sent by the link level software of the node which initiated the original message, to signal receipt of the high level acknowledgment from the message receiving node. Upon receipt of the complete acknowledgment called for in block 50, indicating receipt of the full message at the node B application level and including the link level response, the SEND command function is complete at block 52, and control is returned to the user of the message transmitting node in block 54 for further commands.

The control flow diagram 40 of Fig. 2 illustrates the operation of the SEND function in a circumstance where the message is received at the application level of the receiving node PC. If, for some reason, the message is not received at the PC application level, or is only partially received there, an appropriate high level NETBIOS response indicating same will be received by the message initiating node, which will respond with the link level acknowledgment, as the acknowledgments at block 50. Then, control will be returned to the user at block 54, when the session is ended, or some other action is taken.

It will be appreciated that the transmission and receipt of the higher level NETBIOS acknowledgment signal and the following link level acknowledgment described above require time, and therefore extend the time that the network is dedicated to communication between the nodes A and B actually for the original message from node A. During the time that the network is being used to complete the communication of the original message from node A to node B, including the aforementioned two acknowledgments, other messages are not being sent on that session between the two nodes A and B. For example, a simple request message sent from nod A to node B seeking information may consume approximately 25 milliseconds. Each of the acknowledgments may typically account for 2.5 milliseconds of that time. It is advantageous and desirable from an efficiently standpoint as well as an economic one to minimise the protocols necessary for communication between nodes over the network. The present invention provides such an improvement by eliminating the last two acknowledgment signals while allowing complete use of the network as before.

According to the invention, there is provided a computer network comprising a plurality of interconnected nodes, each node including a computer, a network adapter connecting the node into the network and stored interface software including means for processing messages at the computer at the node for transmission to another computer in the network and means for completing a message transmission command for effecting transmission of a message to another node without acknowledgement from that node

on completion of reception of the message for initiating a subsequent command, or for terminating the subsequent command on receipt of an indication, generated by the other mode, of no, or incomplete, reception of the message by the other mode.

There is also provided a method of operating a computer network comprising a plurality of nodes, each including a computer-and a network adapter connecting the computer into the network, comprising the steps of at a first of the nodes, initiating a message for a second node; commanding transmission of the message, transmitting the message to the second node; ending the command for initiation of a further command at the end of the transmission without waiting for an acknowledgement from the second mode; and on receipt of a response from the second node indicating no, or incomplete, reception of the message, terminating processing of the further command.

An embodiment of the invention will now be described, by way of example, with reference to the accompanying drawings, in which:-

Fig. 1 is a schematic illustration of a LAN or LAN portion, including two PC nodes incorporating NETBIOS;

Fig. 2 is a control flow diagram illustrating the operating of the SEND function of NETBIOS as heretofore available; and

Fig. 3 is a control flow diagram illustrating the operation of the SEND.NO.ACK. function of the present invention.

Although the present invention may be applicable to any computer network, it will be described herein for purposes of illustration as applied to a LAN utilising NETBIOS. Consequently, a NETBIOS LAN or LAN portion, as generally illustrated at 10 in Fig. 1, may be considered for purposes of discussion as employing the present invention wherein functions of the present invention are either added to the heretofore available NETBIOS, or used to replace functions of the heretofore available NETBIOS. For example, rather than the SEND function discussed hereinabove and whose control flow diagram is illustrated in Fig. 2, the present invention provides a function which may be named SEND.NO.ACK. for purposes of disclosing the present invention the NETBIOS software 20 and 26 may be considered to be so improved by the present invention, rather than the heretofore available NETBIOS as discussed above.

The SEND.NO.ACK. function operates to transmit a message from one node to another node with minimal acknowledgment response. For example, if a message is to be sent from PC A to PC B of the LAN 10 of Fig. 1, the PC A user may send the message by commanding the SEND.NO.ACK. function in improved NETBIOS 20. The message is appropriately processed by the improved NETBIOS 20, and with the necessary addressing information included, is conveyed to the adapter physical layer 12 by the link level software 16 for transmission along the cable 32 to the software 16 for transmission along the cable 32 to the adapter 32 of node B. When the message is conveyed to the link level software 30 of node B, a link level acknowledgment is send back to node A to indicate that a message has been received at a node B. Node A is thus notified that the message transmission has been completed to the link layer 30. It will be appreciated that this link level acknowledgment in the case of the SEND.NO.ACK. function is transmitted upon completion of the receipt of the original message at the node B link layer without any delay due to processing of that message at node B, or a determination of whether the message may be conveyed to the PC B application layer 24.

Fig. 3. illustrates generally at 60 a control flow diagram for the function SEND.NO.ACK. To send a message from PC A of node A, for example, to PC B of node B in Fig. 1, using improved NETBIOS software 20 and 26, a user may input the message to PC A and command the SEND.NO.ACK. function, as indicated in block 62 of Fig. 3. Thereupon the improved NETBIOS software 20 processes the SEND.NO.ACK. command and accompanying message, adding appropriate address information, as indicated at box 64. The link level software 16 of the improved NETBIOS conveys the message in appropriate form to the adapter physical layer 12 for transmission along the cable 22 to the adapter of node B, as shown by block 66. Receipt of the message at the link level software 30 of node B causes initiation of a link level acknowledgment from node B back to node A to indicate that the message has been received at the node B link layer. From the point of view of the control flow diagram of the function at node A, illustrated in Fig. 3, the receipt of the link level acknowledgment from node B to so indicate transmission of the message to the node B link level software 30 is indicated by the query diamond 68. It will be appreciated, however, that the wait indicated associated with block 68 is extended only by the approximately 2.5 milliseconds needed for the link level acknowledgment to be send to node A in response to the original message being transmitted to node B. Thereupon, node A may assume a configuration indicative of the function SEND.NO.ACK. being completed, as indicated by block 70, and return control of the PC A to the user, as at 72.

At the receiving node B, several possibilities may occur. The PC B may or may not be in a condition for receiving a message at the application layer 24 through its corresponding improved NETBIOS 26. If the PC B is so configured to receive a message, then it may receive all or part of the message initiated by node A, depending, for example, on the capacity of the receive buffer of the PC B. If the receive buffer of PC B has sufficient capacity to receive the entire message initiated by node A, then the message will

be completely received at the application layer 24. During the time of receiving of the message, or data, by PC B from node A, PC B is in a "receive" configuration. When the message from node A is completely received at the application layer of PC B, that PC will then assume its own "function receive complete" configuration, and return to the control of its user, thus indicating that the complete message has been received from node A.

If PC B is not in a "receive configuration", when the message from node A is transmitted to node B, a negative response, or negative acknowledgment, will be transmitted by the improved NETBIOS 26 of node B to node A. Similarly , if the receive buffer of PC B does not have sufficient capacity to accommodate the message initiated by node A, a negative response will be transmitted to node A. Other circumstances at node B which would prevent the complete conveyance of the message from node A to the application level of PC B would similarly initiate a negative response from node B to indicate that the message was not received at all, or was not entirely received, by PC B at the application level.

These negative responses are not acknowledgments in the sense of an acknowledgment initiated by NETBIOS as heretofore available and as described hereinabove in relation to box 50 in Fig. 2, for example. Rather, as indicated in Fig. 3, the SEND.NO.ACK. function utilised by node A according to the present invention does not wait for any such acknowledgment. However, the next command issued during that data transport session between nodes A and B by node A will either proceed forthwith, if there has been no negative response from node B, in the case of complete reception at the application level of PC B of the initial SEND.NO.ACK. message from node A, or, in the event of a negative response from node B, the next command from node A will terminate. Termination of this next command will indicate to node A and its user that some or all of the previous message sent via SEND.NO.ACK, was not received by PC B at its highest level.

The negative responses are not perceived by the user of the node initiating the original message to be transmitted until another command is attempted at that node, and then only if such a negative response had been sent. Further, the termination of a subsequently attempted command be a negative response simply indicates to the user at the transmitting node that the message was not entirely received at the application level of the other node, without indicating how much, if any, of the message was received at that level.

It will be appreciated that the form of function of the present invention, illustrated by SEND.NO.ACK. herein, is applicable to other command functions. For example, NETBIOS as heretofore available also provides a CHAIN SEND function which differs from the SEND function in that the latter utilises a single buffer from which to assemble the message to be sent, whereas the CHAIN SEND command utilises a plurality of buffers. Thus, a CHAINED.SEND.NO.ACK. function, for example, operates as the SEND.NO.ACK. described herein with the difference that the former function may draw from more than one buffer to assemble data for transmission. In general, the present invention provides function capability without waiting for high software level acknowledgments of data received, but instead may rely on the lack of a negative response, or the receipt of one, to interpret the accomplishment or failure, respectively, of complete reception at the highest software level of data transmitted to a PC in the network.

Claims

1. A computer network comprising a plurality of interconnected nodes, each node including a computer, a network adapter connecting the node into the network and stored interface software including means for processing messages at the computer at the node for transmission to another computer in the network and means for completing a message transmission command for effecting transmission of a message to another node; characterised in that
said latter means end the command for initiation of a further command at the end of the transmission without waiting for an acknowledgement from the second mode; and
on receipt of a response from the second node indicating no, or incomplete, reception of the message, terminate processing of the further command.

2. A computer network according to claim 1 comprising a local area network.

3. A network according to claim 1 or claim 2, in which said stored interface software includes a network basic input/output system application program interface.

4. A method of operating a computer network comprising a plurality of nodes, each including a computer and a network adapter connecting the computer into the network, comprising the steps of:
at a first of the nodes, initiating a message for a second node;
commanding transmission of the message,
transmitting the message to the second node;
characterised by the further steps of:
ending the command for initiation of a fur-

be completely received at the application layer 24. During the time of receiving of the message, or data, by PC B from node A, PC B is in a "receive" configuration. When the message from node A is completely received at the application layer of PC B, that PC will then assume its own "function receive complete" configuration, and return to the control of its user, thus indicating that the complete message has been received from node A.

If PC B is not in a "receive configuration", when the message from node A is transmitted to node B, a negative response, or negative acknowledgment, will be transmitted by the improved NETBIOS 26 of node B to node A. Similarly , if the receive buffer of PC B does not have sufficient capacity to accommodate the message initiated by node A, a negative response will be transmitted to node A. Other circumstances at node B which would prevent the complete conveyance of the message from node A to the application level of PC B would similarly initiate a negative response from node B to indicate that the message was not received at all, or was not entirely received, by PC B at the application level.

These negative responses are not acknowledgments in the sense of an acknowledgment initiated by NETBIOS as heretofore available and as described hereinabove in relation to box 50 in Fig. 2, for example. Rather, as indicated in Fig. 3, the SEND.NO.ACK. function utilised by node A according to the present invention does not wait for any such acknowledgment. However, the next command issued during that data transport session between nodes A and B by node A will either proceed forthwith, if there has been no negative response from node B, in the case of complete reception at the application level of PC B of the initial SEND.NO.ACK. message from node A, or, in the event of a negative response from node B, the next command from node A will terminate. Termination of this next command will indicate to node A and its user that some or all of the previous message sent via SEND.NO.ACK, was not received by PC B at its highest level.

The negative responses are not perceived by the user of the node initiating the original message to be transmitted until another command is attempted at that node, and then only if such a negative response had been sent. Further, the termination of a subsequently attempted command be a negative response simply indicates to the user at the transmitting node that the message was not entirely received at the application level of the other node, without indicating how much, if any, of the message was received at that level.

It will be appreciated that the form of function of the present invention, illustrated by SEND.NO.ACK. herein, is applicable to other command functions. For example, NETBIOS as heretofore available also provides a CHAIN SEND function which differs from the SEND function in that the latter utilises a single buffer from which to assemble the message to be sent, whereas the CHAIN SEND command utilises a plurality of buffers. Thus, a CHAINED.SEND.NO.ACK. function, for example, operates as the SEND.NO.ACK. described herein with the difference that the former function may draw from more than one buffer to assemble data for transmission. In general, the present invention provides function capability without waiting for high software level acknowledgments of data received, but instead may rely on the lack of a negative response, or the receipt of one, to interpret the accomplishment or failure, respectively, of complete reception at the highest software level of data transmitted to a PC in the network.

Claims

1. A computer network comprising a plurality of interconnected nodes, each node including a computer, a network adapter connecting the node into the network and stored interface software including means for processing messages at the computer at the node for transmission to another computer in the network and means for completing a message transmission command for effecting transmission of a message to another node; characterised in that
said latter means end the command for initiation of a further command at the end of the transmission without waiting for an acknowledgement from the second mode; and
on receipt of a response from the second node indicating no, or incomplete, reception of the message, terminate processing of the further command.

2. A computer network according to claim 1 comprising a local area network.

3. A network according to claim 1 or claim 2, in which said stored interface software includes a network basic input/output system application program interface.

4. A method of operating a computer network comprising a plurality of nodes, each including a computer and a network adapter connecting the computer into the network, comprising the steps of:
at a first of the nodes, initiating a message for a second node;
commanding transmission of the message,
transmitting the message to the second node;
characterised by the further steps of:
ending the command for initiation of a fur-

* C L M S *

ther command at the end of the transmission without waiting for an acknowledgement from the seconde node; and

on receipt of a response from the second node indicating no, or incomplete, reception of the message, terminating processing of the further command.

5. A method according to claim 4 in which each message includes data stored in a plurality of buffers in the computer in first node and including the step of:

chaining the data from the buffers to transmit the message.

Patentansprüche

1. Ein Computernetzwerk, das eine Vielzahl untereinander verbundener Knoten umfaßt, wobei jeder Knoten einen Computer, einen Netzwerkadapter zur Anbindung des Knotens an das Netzwerk und gespeicherte Schnittstellensoftware einschließlich Mittel zum Verarbeiten von Nachrichten im Computer am Knoten zur Übertragung an einen anderen Computer im Netzwerk und Mittel zur vollständigen Ausführung eines Nachrichtenübertragungsbefehls zur Durchführung der Übertragung einer Nachricht an einen anderen Knoten einschließt; dadurch gekennzeichnet, daß:
Das zuletzt genannte Mittel den Befehl zur Einleitung eines nachfolgenden Befehls am Ende der Übertragung beendet, ohne auf eine Bestätigung von dem zweiten Knoten zu warten; und
bei Empfang einer Antwort von dem zweiten Knoten, die den nicht erfolgten oder unvollständigen Empfang der Nachricht signalisiert, Beendigung der Verarbeitung des nachfolgenden Befehls.

2. Ein Computernetzwerk gemäß Patentanspruch 1, das ein lokales Netzwerk umfaßt.

3. Ein Netzwerk gemäß Patentanspruch 1 oder Patentanspruch 2, in dem die gespeicherte Schnittstellensoftware eine Anwendungsprogrammschnittstelle mit einem Basic Input/Output System (BIOS) für ein Netzwerk einschließt.

4. Ein Verfahren zum Betreiben eines Computernetzwerks, das eine Vielzahl von Knoten umfaßt, von denen jeder einen Computer und einen Netzwerkadapter zur Verbindung des Computers mit dem Netzwerk enthält, welches folgende Schritte umfaßt:
An einem ersten Knoten Einleitung einer Nachricht für einen zweiten Knoten;
Anweisung zur Übertragung der Nachricht;
Übertragung der Nachricht an den zweiten Knoten, gekennzeichnet durch die weiteren Schritte der:
Beendigung des Befehls zur Einleitung eines nachfolgenden Befehls am Ende der Übertragung, ohne auf eine Bestätigung des zweiten Knotens zu warten; und
Bei Empfang einer Antwort vom zweiten Knoten, die einen nicht erfolgten oder unvollständigen Empfang der Nachricht signalisiert, Beendigung der Verarbeitung des nachfolgenden Befehls.

5. Ein Verfahren gemäß Patentanspruch 4, in dem jede Nachricht Daten enthält, die in einer Vielzahl von Puffern im Computer im ersten Knoten gespeichert sind, und welches den folgenden Schritt umfaßt;
Verketten der Daten aus den Puffern zur Übertragung der Nachricht.

Revendications

1. Réseau d'ordinateurs comprenant une pluralité de noeuds interconnectés, chaque noeud comprenant un ordinateur, un adaptateur de réseau connectant le noeud au réseau et un logiciel d'interface mémorisé, comprenant des moyens pour traiter des messages au niveau de l'ordinateur au noeud de transmission vers un autre ordinateur du réseau, et des moyens pour effectuer une commande de transmission de message pour réaliser la transmission d'un message vers un autre noeud ;
caractérisé en ce que
lesdits derniers moyens terminent la commande pour le lancement d'une commande ultérieure à la fin de la transmission sans attendre d'accusé de réception de la part du second noeud ; et lors de la réception d'une réponse du second noeud indiquant l'absence de réception ou une réception incomplète du message, terminent le traitement de la commande ultérieure.

2. Réseau d'ordinateurs selon la revendication 1, comprenant un réseau local.

3. Réseau selon la revendication 1 ou la revendication 2, dans lequel ledit logiciel d'interface mémorisé comporte une interface entre programme d'application et système d'entrée/sortie de base du réseau.

4. Procédé d'utilisation d'un réseau d'ordinateurs comprenant une pluralité de noeuds, chaque noeud comportant un ordinateur et un adaptateur de réseau connectant l'ordinateur au réseau, comprenant les étapes consistant à :

* C L M S *

à un premier noeud, émettre un message pour un second noeud ;
commander la transmission du message ;
transmettre le message au second noeud ;
caractérisé par les étapes ultérieures suivantes :
terminer la commande d'émission d'une commande ultérieure à la fin de la transmission sans attendre d'accusé de réception de la part du second noeud ; et
lors de la réception d'une réponse de la part du second noeud indiquant l'absence de réception ou une réception incomplète du message, terminer le traitement de la commande ultérieure.

5. Procédé selon la revendication 4, dans lequel chaque message comporte des données mémorisées dans une pluralité de tampons dans l'ordinateur dans le premier noeud et comportant l'étape consistant à :
chaîner les données provenant des tampons pour transmettre le message.

* C L M S *