

Description

TECHNICAL FIELD

The present invention relates to a method of weighing a ship and analyzing the weight distribution thereof.

The invention has particular efficacy in the field of dry docking marine vessels and is described in detail herein in that context. However, the invention is applicable to a wide range of loads if they are placed on similar lifting devices and consequently should not be regarded as being limited in application merely by virtue of the specific description herein.

BACKGROUND ART

In United States patent 3,073,125 now expired, applicant for a patent for the present invention disclosed and claimed a dry dock which for operation was placed under a ship which lay between two quays, and was raised by hoist winches on the quays, along with the ship, to a height which brought the ship to quay level. The dry dock included rail mounted trolleys by means of which the ship could be moved onto the quay.

United States patent 4,087,979 also owned by applicant and still in force, discloses and claims improvement to the dry dock of 3,073,125, inter alia by way of enabling construction in module form off site, and articulating the structure at positions along its length. There are a total of one hundred and sixty eight such dry docks in operation in sixty two countries.

Both types of dry dock are operated by hoist winches which in turn are driven by a.c. synchronous motors, so as to ensure lift synchronism. Control is computerized and includes manual override.

DISCLOSURE OF THE INVENTION

It is an object of the present invention to provide a mode of operation of a dry dock of the kind disclosed and claimed in the aforementioned patents and which should be regarded as being incorporated herein by virtue of this reference thereto, which mode of operation enables the extraction of information from the apparatus which further enables design modification and/or working of a ship.

A further object of the present invention is to provide a mode of operation which enables the weight of a ship being lifted, to be observed.

A further object of the present invention is to provide a mode of operation which enables the ships center of gravity to be ascertained.

A still further object of the present invention is to provide an indication of the ships weight distribution.

The present invention is defined by the method steps of independent claims 1, 2 and 3.

The invention utilizes the output from hoist load indicating means in the load path of each hoist winch, in a system of hoist winches on opposing quays.

The load indicating means is of the kind which generates electrical signals when acted on by a said load.

Means are provided which receive and condition the signals and further means are provided which receive the conditioned signals and use them to react upon the system and thereby control it.

The further means also uses said signals to generate visual displays of load magnitudes, current magnitudes, weight distributions and total weights of gross lifted load and/or of the ship itself, as experienced by the hoist winches.

The invention will now be described, by way of example and with reference to the accompanying drawings in which:

THE DRAWINGS

Figure 1 is a diagrammatic side elevation of a dry dock incorporating the present invention.

Figure 2 is a diagrammatic view on line 2-2 of Figure 1.

Figure 3 is a pictorial view of a hoist winch of the kind utilized in the practicing of the present invention.

Figure 4 is a view in the direction of arrow 4 in Figure 1.

Figure 5 is a schematic diagram of a signal conditioning circuit incorporated in the apparatus used in practicing the modes of operation of the present invention.

Figure 6 is a dual graphic and actual numerical value display of a ships weight distribution in a hoist winch system incorporating six pairs of opposed winches of the kind depicted in Figure 3.

BEST MODE OF CARRYING OUT THE INVENTION

Referring to Figure 1. A platform 13 of the kind described in U.S. Patent 4,087,979 supports a ship 9 for vertical movement with respect to a quay 10 (Figure 2).

Referring now to Figure 2. The platform 13 includes main transverse beams 20 the ends of which lie within cutouts 17 in the opposing faces of the quays 10 (Figure 1) and 12 (Figure 4).

The ends of the beams 20 carry sheaves 18.

A hoist winch 19, one of a series of opposed pairs of hoist winches 19 as seen in Figure 4, is fixed to the quay and supports further sheaves 21 in approximately vertical alignment with the sheaves 18, and further includes a winch drum 29.

A wire rope 27 is fixed by one end to a load cell 25 which also doubles as a clevis pin and is fixed to the end of the structure of the hoist winch 19.

The rope 27 is wrapped around the sheaves 18 and 21, the remaining end finally leaving sheaves 18 and turning around the winch drum 29. A signal conditioning circuit 28 is fixed to or near the hoist winch structure 19 and is connected to the load cell clevis pin 25.

Referring now to Figure 3. Each winch drum 29 is driven by an a.c. synchronous motor 33 via a step down gear arrangement 35 and a toothed wheel 37 on the end of the drum 29.

A limit switch 41 is fastened to the structure of the hoist winch 19 and a contact pad 43 is carried by the beam 20. The limit switch is preset and when the platform 13 rises to its desired height during operation, the pad 43 contacts the limit switch 41 which then is actuated to effect halting of the platform 20.

Devices (not shown) within the system are utilized to determine the maximum desired lowered positions of the platform 13.

Referring now to Figure 4. During operation of the hoist winches 19 to raise or lower the platform 13 and its associated ship 9, the conditioning circuit 28 receives electrical signals from the load cell 25 associated with that winch 19. The circuit 28 which in Figure 4 is depicted by a box, is more explicitly illustrated in Figure 5 to which brief reference is now made. A d.c. input 60 is converted at 62 into a sinewave plus and minus d.c. voltage. The output from 62 is regulated at 64 and the resulting regulated, d.c. excitation voltage is passed to the load cell 25.

The output voltage from the load cell 25 is amplified at 66 and then converted at 68 to a current output for use in the computer, to which it is passed via a power handling MOSFET transducer 70.

Referring back to Figure 4. The computer 47 sends control signals to the ship lift control panel which can stop or allow operation of the hoist winches 19, and sends further signals to a visual display unit 49 so as to display information which has been derived from the signals concerning the operating performance of the hoist winches 19, e.g., the loads being sensed, and also the current being drawn by the winch motor 33, the weight of the vessel being lifted/lowered and other characteristics of the system. Examples of information the visual display of which is enabled by the invention,

are depicted in Figure 6 referred to hereinafter.

Figure 6 displays in both histogram and numerical form, the manner in which a particular ship's weight is distributed over the hoist winches 19. Opposed winch stations 1A and 1B are each experiencing a load of 73.8 tons. Stations 4A and 4B are each experiencing a load of 256 tons and stations 6A and 6B are each experiencing a load of 72 tons.

It should be noted, that the weights indicated from zero upwards relate to the ship. The projections of the histogram below the zero line are identical in extent, and correspond to the constant weight of the platform.

Clearly, the ability of the present invention to precisely ascertain a ship's weight distribution, also provides the ability to calculate the ships center of gravity with a magnitude of accuracy over and above methods used presently and which by comparison are virtually enumerative in both manner and result.

The foregoing description discloses the use of a load cell 25 in the form of a clevis pin. However, other forms of load cell may be used, and positioned anywhere in the load path of the loads which the hoist winches 19 experience during operation. Thus, by way of example, load cells can be positioned on the support structure 51 of the hoist winch sheaves 21, or at 53 between the hoist winches 19 and the quays 10 and 12, or at the clevis pin supports i.e., use a normal clevis pin 25 and support it on a load cell of appropriately adapted shape. Thus, a computer programme is devised which, when the signals from the load cells 25 reach the computer 47 (Figure 4), will combine those inputs, (which represent the load experienced by each hoist winch 19) with the numerical value of the spacing between winches 19, both laterally and longitudinally of the platform, and from the moment arms thus produced, calculate the actual center of gravity of the ship.

Where the ship being handled is new and unlaunched, the information as to the location of the ships center of gravity is passed to the naval architect, for consideration whether it is sufficiently near to the designed location, or that modifications should be incorporated, both in the design and the actual ship.

If the ship is docked for refurbishment, the employment of the method described herein, enables the total weight of the ship, and its distribution, to be observed during any structural alterations or repairs, and the affect, if any, such work has on the ships center of gravity. All observations and calculations derived therefrom, are transmitted via a line from the computer or other means, to the yard manager or naval architect, as appropriate, for action to counter any undesirable effects.

A further advantage obtained by the practicing of the method of the present invention, is that on dry docking a ship which is allegedly in light (empty) condition, observance of any excessive weight, of a magnitude greater than the norm, and, particularly, a center of gravity far removed from the design location for the particular ship, is a clear indication that one or more holds still contain cargo. This would provide a safety feature where the ship is a warship, and the cargo comprises ammunition, in that an opportunity is afforded to remove the ammunition prior to starting work on the ship.

Where the ship is a cargo ship, the excessive weight would apply undesirable local forces on the ship's hull, bearing in mind that the ship is no longer supported in water. The information on being passed to the yard manager, can be quickly acted upon as appropriate.

Claims

1. A method of determining and analyzing a ship's weight characteristics comprising the steps of:

a) placing the ship (9) on a dry dock comprising a number of articulately joined platforms (13), the whole being suspended from a number of opposed pairs of hoist winches (19) and with said hoist winches comprising apparatus which includes means for signalling the loads experienced by said winches, means for displaying said loads in accordance with said signals and means for controlling said hoist winches in accordance with said signals.

b) observing said loads on said display means, electronically summing them to achieve the total weight of the ship and utilizing the results by way of comparing them with the designed weight of the ship so as to enable assessment of need for design changes.

2. A method of determining and analyzing a ship's weight characteristics comprising the steps of:

a) placing the ship (9) on a dry dock comprising a number of articulately joined platforms (13), the whole being suspended from a number of opposed pairs of hoist winches (19) and with said hoist winches comprising apparatus which includes means for signalling the load experienced by each hoist winch, means for displaying said loads in accordance with said signals and means for controlling said hoist winches in accordance with said signals,

b) observing the loads being experienced by said hoist winches, and combining the

numerical values of said loads and the distances between the hoist winches so as to enable computation of the ship's actual center of gravity.

c) performing said computation and comparing the result with the design predicted center of gravity of the ship for the purpose of assessing the necessity for design changes.

3. A method of determining and analyzing a ship's weight characteristics comprising the steps of:

a) placing the ship (9) on a dry dock comprising a number of articulately joined platforms (13), the whole being suspended from a number of opposed pairs of hoist winches (19) and with said hoist winches comprising apparatus including means for signalling the loads experienced by said hoist winches, means for displaying said loads in accordance with said signals and control means for controlling said hoist winches in accordance with said signals.

b) observing on said display means the loads experienced by the hoist winches and noting if and where there exists local loads of a magnitude which is large relative to the norm of said locality in said ship when empty and,

c) where such loads exist, inspecting the holds in that or those localities and if cargo is present, unloading it prior to commencing other work on the ship.

Patentansprüche

1. Verfahren zur Feststellung und Analyse der Gewichtseigenschaften eines Schiffes, mit den Schritten:

a) Aufsetzen des Schiffes (9) auf ein Trockendock, welches eine Anzahl von gelenkig verbundenen Plattformen (13) enthält, wobei die gesamte Anordnung durch eine Anzahl gegenüberliegender Paare von Seilwinden (19) gehalten wird und wobei die Seilwinden Vorrichtungen haben, die Einrichtungen zum Signalisieren der von den Seilwinden aufgenommenen Belastungen, Einrichtungen zum Anzeigen der Belastungen gemäß dieser Signale und Einrichtungen zum Steuern der Seilwinden gemäß dieser Signale enthalten,

b) Überwachen der Belastungen auf der Anzeigeeinrichtung, elektronisches Addieren der Signale, um das Gesamtgewicht des Schiffes zu erhalten, und Verwenden der Ergebnisse, indem diese mit dem Entwurfgewicht des Schiffes verglichen werden, um so eine Bewertung der Notwendigkeit von



A further advantage obtained by the practicing of the method of the present invention, is that on dry docking a ship which is allegedly in light (empty) condition, observance of any excessive weight, of a magnitude greater than the norm, and, particularly, a center of gravity far removed from the design location for the particular ship, is a clear indication that one or more holds still contain cargo. This would provide a safety feature where the ship is a warship, and the cargo comprises ammunition, in that an opportunity is afforded to remove the ammunition prior to starting work on the ship.

Where the ship is a cargo ship, the excessive weight would apply undesirable local forces on the ship's hull, bearing in mind that the ship is no longer supported in water. The information on being passed to the yard manager, can be quickly acted upon as appropriate.

Claims

1. A method of determining and analyzing a ship's weight characteristics comprising the steps of:
 - a) placing the ship (9) on a dry dock comprising a number of articulately joined platforms (13), the whole being suspended from a number of opposed pairs of hoist winches (19) and with said hoist winches comprising apparatus which includes means for signalling the loads experienced by said winches, means for displaying said loads in accordance with said signals and means for controlling said hoist winches in accordance with said signals.
 - b) observing said loads on said display means, electronically summing them to achieve the total weight of the ship and utilizing the results by way of comparing them with the designed weight of the ship so as to enable assessment of need for design changes.
2. A method of determining and analyzing a ship's weight characteristics comprising the steps of:
 - a) placing the ship (9) on a dry dock comprising a number of articulately joined platforms (13), the whole being suspended from a number of opposed pairs of hoist winches (19) and with said hoist winches comprising apparatus which includes means for signalling the load experienced by each hoist winch, means for displaying said loads in accordance with said signals and means for controlling said hoist winches in accordance with said signals,
 - b) observing the loads being experienced by said hoist winches, and combining the

numerical values of said loads and the distances between the hoist winches so as to enable computation of the ship's actual center of gravity.

c) performing said computation and comparing the result with the design predicted center of gravity of the ship for the purpose of assessing the necessity for design changes.

3. A method of determining and analyzing a ship's weight characteristics comprising the steps of:
 - a) placing the ship (9) on a dry dock comprising a number of articulately joined platforms (13), the whole being suspended from a number of opposed pairs of hoist winches (19) and with said hoist winches comprising apparatus including means for signalling the loads experienced by said hoist winches, means for displaying said loads in accordance with said signals and control means for controlling said hoist winches in accordance with said signals.
 - b) observing on said display means the loads experienced by the hoist winches and noting if and where there exists local loads of a magnitude which is large relative to the norm of said locality in said ship when empty and,
 - c) where such loads exist, inspecting the holds in that or those localities and if cargo is present, unloading it prior to commencing other work on the ship.

Patentansprüche

1. Verfahren zur Feststellung und Analyse der Gewichtseigenschaften eines Schiffes, mit den Schritten:
 - a) Aufsetzen des Schiffes (9) auf ein Trockendock, welches eine Anzahl von gelenkig verbundenen Plattformen (13) enthält, wobei die gesamte Anordnung durch eine Anzahl gegenüberliegender Paare von Seilwinden (19) gehalten wird und wobei die Seilwinden Vorrichtungen haben, die Einrichtungen zum Signalisieren der von den Seilwinden aufgenommenen Belastungen, Einrichtungen zum Anzeigen der Belastungen gemäß dieser Signale und Einrichtungen zum Steuern der Seilwinden gemäß dieser Signale enthalten,
 - b) Überwachen der Belastungen auf der Anzeigeeinrichtung, elektronisches Addieren der Signale, um das Gesamtgewicht des Schiffes zu erhalten, und Verwenden der Ergebnisse, indem diese mit dem Entwurfs-gewicht des Schiffes verglichen werden, um so eine Bewertung der Notwendigkeit von



Konstruktionsänderungen zu erhalten.

2. Verfahren zur Feststellung und Analyse der Gewichtseigenschaften eines Schiffes, mit den Schritten:

- a) Aufsetzen des Schiffes (9) auf ein Trok-kendock, welches eine Anzahl von gelenkig verbundenen Plattformen (13) enthält, wobei die gesamte Anordnung durch eine Anzahl gegenüberliegender Paare von Seilwinden (19) gehalten wird und wobei die Seilwinden Vorrichtungen haben, die Einrichtungen zum Signalisieren der von jeder Seilwinde aufgenommenen Belastung, Einrichtungen zum Anzeigen der Belastungen gemäß dieser Signale und Einrichtungen zum Steuern der Seilwinden gemäß dieser Signale enthalten,
- b) Überwachen der Belastungen, die von den Seilwinden aufgenommen werden, und Kombinieren der numerischen Werte dieser Belastungen mit den Abständen zwischen den Seilwinden, um eine Berechnung des augenblicklichen Schwerpunktes des Schiffes durchführen zu können,
- c) Durchführen der Berechnung und Vergleichen des Ergebnisses mit dem durch den Entwurf bestimmten Mittelpunkt des Schiffes, um die Notwendigkeit von Konstruktionsänderungen zu bewerten.

3. Verfahren zur Feststellung und Analyse der Gewichtseigenschaften eines Schiffes, mit den Schritten:

- a) Aufsetzen des Schiffes (9) auf ein Trok-kendock, welches eine Anzahl von gelenkig verbundenen Plattformen (13) enthält, wobei die gesamte Anordnung durch eine Anzahl gegenüberliegender Paare von Seilwinden (19) gehalten wird und wobei die Seilwinden Vorrichtungen haben, die Einrichtungen zum Signalisieren der von den Seilwinden aufgenommenen Belastungen, Einrichtungen zum Anzeigen der Belastungen gemäß dieser Signale und Einrichtungen zum Steuern der Seilwinden gemäß dieser Signale enthalten,
- b) Überwachen der von den Seilwinden aufgenommenen Belastungen auf der Anzeigeeinrichtung und Erfassen, ob und wo lokale Belastungen eines Ausmaßes vorhanden sind, die, wenn das Schiff leer ist, gegenüber den Normalbelastungen an dieser Stelle groß sind, und
- c) wenn solche Belastungen auftreten, Untersuchen der Halterungen an dieser oder diesen Stellen und, bei Vorhandensein von Ladung, Umladen dieser Ladung, bevor auf dem Schiff mit anderen Arbeiten begonnen wird.

Revendications

1. Procédé de détermination et d'analyse des caractéristiques de poids d'un navire comprenant les étapes consistant à:

- a) placer le navire (9) sur une cale sèche qui comprend un certain nombre de plates-formes (13) assemblées de manière articulée, l'ensemble étant suspendu à un certain nombre de paires opposées de treuils de levage (19) et lesdits treuils de levage comprenant un appareillage pourvu d'un moyen de transformation en signaux des charges auxquelles sont soumis lesdits treuils, un moyen d'affichage desdites charges en fonction desdits signaux et un moyen de commande desdits treuils de levage en fonction desdits signaux.
- b) observer lesdites charges sur ledit moyen d'affichage, les sommer électroniquement pour obtenir le poids total du navire et utiliser les résultats, en les comparant au poids prévu du navire, pour permettre d'évaluer un besoin de modifications de structure.

2. Procédé de détermination et d'analyse des caractéristiques du poids d'un navire comprenant les étapes consistant à:

- a) placer le navire (9) sur une cale sèche qui comprend un certain nombre de plates-formes (13) assemblées de manière articulée, l'ensemble étant suspendu à un certain nombre de paires opposées de treuils de levage (19) et lesdits treuils de levage comprenant un appareillage pourvu d'un moyen de transformation en signaux des charges auxquelles est soumis chaque treuil, un moyen d'affichage desdites charges en fonction desdits signaux et un moyen de commande desdits treuils de levage en fonction desdits signaux.
- b) Observer les charges auxquelles sont soumis lesdits treuils de levage, et combiner les valeurs numériques desdites charges et les distances entre les treuils de levage de façon à permettre un calcul du centre de gravité réel du navire.
- c) Effectuer ledit calcul et comparer le résultat au centre de gravité prévu du navire dans le but d'évaluer la nécessité de modifications de structure.

3. Procédé de détermination et d'analyse des caractéristiques du poids d'un navire comprenant les étapes consistant à:

- a) placer le navire (9) sur une cale sèche qui comprend un certain nombre de plates-



formes (13) assemblées de manière articulée, l'ensemble étant suspendu à un certain nombre de paires opposées de treuils de levage (19) et lesdits treuils de levage comprenant un appareillage pourvu d'un moyen de transformation en signaux des charges auxquelles sont soumis lesdits treuils, un moyen d'affichage desdites charges en fonction desdits signaux et un moyen de commande pour commander lesdits treuils de levage en fonction desdits signaux.

5

10

b) observer sur ledit moyen d'affichage les charges auxquelles sont soumis les treuils de levage et noter l'existence éventuelle et les positions de charges, situées à un emplacement, dont l'amplitude est grande par rapport à la norme dudit emplacement dans ledit navire lorsqu'il est à vide et,

15

c) là où de telles charges existent, inspecter les cales à cet emplacement ou à ces emplacements et, dans le cas où un chargement est présent, le décharger avant de commencer d'autres travaux dans le navire.

20

25

30

35

40

45

50

55