

P14345

TITLE OF THE INVENTION

Motor

5

TECHNICAL FIELD

The present invention relates to a small motor for use in an information-communication apparatus, an audio-visual apparatus or the like, and a motor for use in a portable pager and a portable telephone or the like generating vibrations to be transmitted to a human body.

10

BACKGROUND ART

In order to meet the increasing needs for reducing the overall sizes, increasing the degree of precision and improving the reliability of apparatus for information-communication, audio-visual application, more and more number of brushless motors are being used in place of motors with brush. The motors with brush are also required to be compact and thin; accordingly, many of the conventional frame cases of a cylindrical shape are replaced by those of an oval shape among the core motors. Even among the coreless motors, frame cases of oval and square shapes have been developed, and motors having such frame cases are already in use in portable communication apparatus. The battery-driven motors for use in portable apparatus have to meet stringent dimensional requirements in thickness direction; in addition, the power consumption must be low in view of battery life. It has become difficult to raise the efficiency of a motor further by using a high energy-density magnet among the motors having conventional oval or cylindrical structure.

20

25

30

Motors of the above category have a structure as shown in Fig.58, Fig.61 or Fig.62. The structure is described in the following.

Fig.58 is a cross sectional view showing a conventional inner-rotor type brushless motor.

35

As shown in Fig.58, a cylindrical magnet 130 is fixed to

a shaft 131 inserted through the central hole, one end of the shaft 131 is held by a bearing 133 provided on a frame case 132 while the other end is held by a bearing 134 provided on a bracket 136; thus an inner rotor is formed which is supported at both
 5 ends. The magnet 130 fixed to the shaft 131 which is rotatably supported by bearings 133, 134 is magnetized in the N and S poles. A cylindrical core 128 is provided with three salient poles, which are wound around with a coil 129. The magnet 130 is rotated by magnetic flux generated by electricity supplied to the coil 129.

10 A circuit board 135 is mounted with electronic components. Each of the salient poles of the core 128 is wound around with coil to form a three-phase coil of phase U, phase V and phase W, respectively. The above electronic circuit controls so as the phase of induced voltage generated at each of the three
 15 phases deviates relative to one another by 120°. Thus, it is driven as a three-phase brushless motor.

Fig.61(a) is a cross sectional view showing a conventional core motor having an oval cross sectional shape for use in a portable pager, Fig.61(b) shows the motor sectioned by a
 20 plane perpendicular to the shaft.

As shown in Fig.61(a) and Fig.61(b), a core 142 made of stacked silicon steel sheets is fixed around a shaft 139, a resin insulator shaped to a same shape as the core is inserted in the core 142, and a rectifying terminal unit 144 is thrust to the
 25 shaft 139. The core 142 is wound around with a coil 143, the electric conduction point of coil 143 is aligned to a specified position of the rectifying terminal unit 144 for soldering. An armature coil assembly of a motor is thus structured. The rectifying surface of rectifying unit 144 is lapped, and then the
 30 entire assembly of armature coil is washed. A sintered bearing 140 is fixed in the centre of frame case 137. In the frame case 137 which is shaped oval, an arc-shape magnet 138 is provided at the inside of each of the two arc-shape sides of the frame case 137, the inner side of the two magnets is magnetized so as to have
 35 opposit pole relative to each other. The shaft 139 of washed armature coil assembly is inserted to the sintered bearing 140,

and a bracket 147 provided with a brush 146 and a sintered bearing 141 is affixed to the frame case 137 to complete a motor.

Magnetic flux coming out of the inner surface of one magnet 138 goes through core 142, enters into the inner surface of the other magnet 138, and returns to the initial magnet 138 via frame case 137. Namely, a magnetic circuit is formed on a plane perpendicular to the shaft 139. An imbalancing weight 148 is mounted fixed on the shaft 139.

As a result of rotation of the motor, the shaft 139 with the imbalancing weight 148 fixed thereon causes a vibration, which vibration is transmitted to the frame case 137 for the vibration of a portable pager.

Fig.62(a) is a plane view of a coreless motor having a square cross section, for use in a portable communication apparatus. Fig.62(b) is a cross sectional view of the coreless motor of Fig.62(a).

A shaft 149 is fixed to a group of coreless coils 151 via a rectifier 150. A magnet 152 of empty-cylindrical shape is fixed to a housing 153 and is disposed in a space within the group of coils 151 with a certain clearance. Frame case 154 provided with a flat portion on the outer surface fixes the housing 153 carrying thereon the magnet 152 in a space inside the group of coils 151 securing a certain clearance, at the same time forms a magnetic circuit together with the magnet 152. Bearing 155 fixed in the housing 153 holds the shaft 149 rotatable. Brush 156 is electrically coupled with the group of coils 151 via rectifier 150. Imbalancing weight 157 is fixed onto the shaft 149.

The above described conventional structure may not fully meet the increasing needs for a compact and efficient motor that satisfies the prevailing desire in the industry for making an apparatus smaller. The problems are as follows.

With an inner-rotor type brushless motor having a cylindrical core 128, as shown in Fig.58, if there is a dimensional restriction in a plane perpendicular to shaft 131 the winding work for coil 129 may face a difficulty unless a certain space is secured for the work, especially when the diameter of

magnet 130 becomes small the winding work may face an extreme difficulty.

The space factor in the above described inner-rotor type brushless motor is not quite high, by the reason described below.

5 Fig.59(a) is a cross sectional view of simplified magnetic circuit in an inner-rotor type brushless motor. Fig.59 (b) shows the motor unrolled from inside of the core. Description is made in the following with reference to these drawings. Here, the leakage of magnetic flux is ignored to make the description
10 simple.

An inverse number of the velocity shift rate μ is often used to represent the efficiency η of a motor. A following Formula 1 is generally established with respect to the velocity shift rate μ :

$$15 \quad \eta = \frac{1}{\mu} = \frac{\Phi^2 T^2}{R} \dots\dots\dots (1)$$

20 where; Φ denotes effective magnetic flux of core, T is number of coil turns, R is coil resistance.

The effective magnetic flux Φ of core is expressed in the following Formula 2.

$$25 \quad \Phi = \pi D L B_g \dots(2)$$

where; D denotes the outer diameter of rotor, L is length of rotor, B_g is the density of magnetic flux at gap.

30 The density of magnetic flux at gap B_g is expressed in the following Formula 3.

$$35 \quad B_g = \frac{B_r}{1 + \frac{\mu r}{L_m / L_g}} \dots\dots\dots (3)$$

where; B_r , μ_r are called respectively residual flux density, recoil magnetic permeability. These are the constants specific to a magnetic material.

5

L_m is thickness of magnet, L_g is air gap between magnet and core.

The relationship between the number of coil turns T and the coil resistance R is represented in Formula 4.

10

$$R = \frac{2kT^2 l}{S} \dots\dots (4)$$

15

where; k denotes electric conductivity of coil, which is a constant determined proportionate to the space factor of coil. l represents average coil length per one turn, S is cross sectional area of coil.

20

The l is represented by Formula 5, when the coil resistance is ignored.

$$l = 2 (L_c + D_c) \cong 2 \frac{L}{3} + \frac{\pi}{2} D \dots (5)$$

25

where; L_c denotes height of coil, D_c is coil width.

By substituting the Formula 2, Formula 3, Formula 4 and Formula 5 for Formula 1, the following Formula 6 is obtained:

30

$$\eta = \left[\pi DL \frac{B_r}{1 + \frac{\mu_r}{L_m / L_g}} \right]^2 \cdot \frac{S}{4k \left[\frac{L}{3} + \frac{\pi}{2} D \right]} \dots (6)$$

35

There is no component representing the coil resistance R nor the coil turn counts T contained in the above Formula. It indicates that the efficiency does not change by a change in the specifications of coil winding.

5 In the above formula, when L , D are varied so as the volume of rotor ($\pi D^2 L/4$) remains constant, with other variables fixed, the relationship between the length/diameter of rotor (L/D) and the efficiency η is as shown in Fig.60. According to Fig.60, the efficiency improves with a longer rotor, but the improvement curve saturates and
10 converges towards a certain value. So, there is a limitation, with no further improvement any more.

With regard to an inner-rotor type brushless motor as shown in Fig.58, the number of turns for a salient pole has to be increased to obtain a larger torque. This makes the salient pole
15 larger, hence a larger outer diameter of a motor, rendering it difficult to make a motor smaller. Furthermore, a core which is comprised of salient poles wound around with coil disposed at a same interval has to be provided around the inner-rotor, which makes cross sectional shape of a motor round, or almost round. It
20 is difficult to make a motor thin.

With regard to a core motor for portable pager as shown in Fig.61, the reliability is inferior to a brushless motor because of the existence of a brush. If one tries to solve the the problems by making the motor shape oval, the coil winding
25 faces a difficulty because of the small contour.

With regard to a coreless type brush motor for portable communication apparatus, as shown in Fig. 62, the reliability is inferior to a brushless motor, and an available output torque is smaller as compared with a core motor when the dimensions of a
30 motor are reduced. Namely, when diameter of a motor is reduced smaller it becomes more difficult to realize an efficient and compact coreless motor, or such a coreless motor for generating vibrations. Furthermore, coils of such a motor are required to be wound with a thin wire, e.g. as thin as 0.01 - 0.02mm, which means
35 a deteriorated production yield rate during handling of the coils. These have been some of the factors which hamper the supply of

inexpensive motors.

DISCLOSURE OF THE INVENTION

5 The present invention may implement a small motor that has a high efficiency and a thin shape, as well as a high degree of freedom when mounted on an apparatus.

10 A first exemplary device for implementing the invention comprises K pieces of (K indicating any integer greater than one) magnetic units having the N and S poles magnetized alternately in a circumferential direction which are stacked axially in K stages around a rotation shaft to form one integral body of a rotor, which rotor being held rotatable by a pair of bearings. A core is provided with salient poles wound around with coils in K stages corresponding to each of the magnetic units. The magnetized
15 position of the N and S poles in magnetic unit at each stage deviates relative to one another in a circumferential direction so as to set the phase of induced voltage generated on the salient pole wound around with the coil in each stage to a phase suitable for rotating a magnetic unit of the corresponding stage.

20 Thus the magnetic poles of a rotor magnetic unit as well as the salient poles of a core wound around with coil may be disposed splitted axially in K stages. Namely, the magnetic poles of magnetic unit and the salient poles of core wound around with coil were conventionally disposed on a same single plane; in the
25 invented motor, however, the magnetic poles of magnetic unit and the salient poles of core wound around with coil may be disposed splitted on planes axially stacked in K stages. The above structure makes it possible to present a small and thin motor that has an improved efficiency and a higher degree of freedom when
30 mounting in an apparatus.

A second exemplary device of the invention comprises a rotor which is formed with magnetic units stacked in K stages (K indicating any integer greater than one), the magnetized position of the N and S poles in magnetic unit at each stage deviating
35 relative to one another in a circumferential direction, the rotor being held rotatable by a pair of bearings, and an outer case of

an oblong shape composed of a pair of short sides facing to each other and a pair of long sides facing to each other in a cross sectional plane perpendicular to the axial direction of rotor. In which the rotor is penetrating through the outer case at the central part, and a core comprising K pieces of salient poles wound around with coil corresponding to the magnetic unit in that stage disposed on a straight line parallel to axial direction of the rotor is provided at least on one of the short sides of outer case.

With the above described structure, the magnetic poles of magnetic unit as well as the salient poles of a core wound around with coil may be disposed splitted in a direction of rotor shaft in K stages. In this way, the salient poles wound around with coil may be disposed only on the short sides of outer case. Therefore, the dimension of short side may be reduced to almost equal to outer diameter of the rotor. The above structure also makes it easier to increase the number of turns of the coil to be wound around the salient poles, to an improved efficiency of a motor. Further, because it is a brushless motor a higher operational reliability may be expected. Thus, a reliable and efficient motor may be presented in a thin configuration.

A third exemplary device of the invention comprises a rotor formed with magnetic units stacked in K stages (K indicating any integer greater than one), the magnetized position of the N and S poles in magnetic unit at each stage deviating relative to one another in a circumferential direction, the rotor being held by a pair of bearings, a core comprising salient poles wound around with coil corresponding to the magnetic unit of that stage stacked in K stages, and an outer case of an oblong shape composed of a pair of long sides facing to each other and a pair of short sides facing to each other in a cross sectional plane perpendicular to the axial direction of rotor. In which, a vibration is generated as a result of rotation of the rotor by an imbalancing weight attached thereon for rotating together.

Thus, the magnetic poles of magnetic unit as well as the salient poles of a core wound around with coil may be disposed

splitted in a direction of rotor shaft in K stages. The outer case may have reduced dimensions in the cross sectional shape, with a wide range of freedom of taking an oblong or other desired shapes. Furthermore, it becomes easier to increase the number of turns of the coil to be wound around salient poles for an improved efficiency of a motor. The above factors enable to implement a small and efficient motor for generating vibration, whose outer case having a wide range of freedom in taking a desired cross sectional shape.

10

BRIEF DESCRIPTION OF THE DRAWINGS

Fig.1(a) is a lengthwise cross sectional view of a motor in accordance with a first exemplary embodiment of the present invention. Fig.1(b) is a traversing cross sectional view of the motor. Fig.2 is a perspective view showing the magnetized state in magnetic units of the motor. Fig.3 illustrates a relationship among the magnetic units, the salient poles of core and the coils. Fig.4 is a waveform chart showing the induced voltage in the motor. Fig.5(a) is a simplified cross sectional view showing a magnetic circuit of the motor. Fig.5(b) shows the motor unfolded from inside the core. Fig 6. is a graph used to compare the motor with a conventional brushless motor in terms of efficiency. Fig.7 is a chart showing relationship among the magnetic units, the salient poles of core and the coils when magnetized position of the magnetic units deviates by 60 relative to one another. Fig.8 is an exploded perspective view of a motor which has a flat portion on the outer surface.

Fig.9 is a chart used to explain a relationship among the magnetic units, the salient poles of core and the coils of a motor in accordance with a second exemplary embodiment of the invention. Fig.10 is a chart used to explain a relationship among the magnetic units, the salient poles of core and the coils of other motor in accordance with a second exemplary embodiment of the invention.

Fig.11(a) is a lengthwise cross sectional view of a motor in accordance with a third exemplary embodiment of the

invention. Fig.11(b) is a partially cut-away top view of the motor. Fig.12 is a perspective view showing magnetized state in magnetic units of the motor. Fig.13 illustrates a relationship among the magnetic units, the salient poles of core and the coils.

5 Fig.14 is a waveform chart showing induced voltage of the motor. Fig.15(a) is a simplified cross sectional view of magnetic circuit of the motor. Fig.15(b) shows the motor unfolded from inside the core. Fig. 16. is a graph used to compare the motor with a conventional brushless motor in terms of efficiency. Fig.17 is a
10 chart showing a relationship among the magnetic units, the salient poles of core and the coils of other motor in accordance with a third exemplary embodiment of the invention.

Fig.18 is a perspective view showing the magnetized state in one example of magnetic units in a motor in accordance
15 with a fourth exemplary embodiment of the invention. Fig.19 is a perspective view showing the magnetized state in other example of magnetic units of a motor in accordance with a fourth exemplary embodiment of the invention.

Fig.20(a) is a lengthwise cross sectional view showing a
20 motor in accordance with a fifth exemplary embodiment of the invention. Fig.20(b) is a traversing cross sectional view of the motor. Fig.21 is a perspective view showing relative positioning of magnetic poles in magnetic units of the motor. Fig.22 is a model chart used to explain the quantity of imbalance in the
25 motor. Fig.23 is a perspective view of an imbalancing weight used in the motor. Fig.24(a) is a characteristics chart showing a relationship of the shift quantity in gravity centre of the weight versus the weight outer diameter/shaft diameter. Fig.24(b) is a characteristics chart showing a relationship of square measure of
30 the weight versus the weight outer diameter/shaft diameter. Fig.24(c) is a characteristics chart showing a relationship of the centrifugal force of weight versus the weight outer diameter/shaft diameter.

Fig.25 is a cross sectional magnification of a pivotal bearing of
35 the motor. Fig.26 is a characteristics chart showing a relationship between the largest surface pressure and the friction

torque in the pivotal bearing. Fig.27(a),(b) illustrate a self centering bearing; (a) is a cross sectional view at top part of a shaft, (b) is a cross sectional view at bottom end of the shaft. Fig.28 is a perspective view of an exemplary salient pole of the motor. Fig.29 is a perspective view of other salient pole of the motor. Fig.30 is a perspective view of still other salient pole of the motor. Fig.31 is an exploded perspective view of the motor. Fig.32 is charts used to explain the rotating principle of the motor.

Fig.33(a) is a lengthwise cross sectional view of a motor in accordance with a sixth exemplary embodiment of the invention. Fig.33(b) is a traversing cross sectional view of the motor. Fig.34 is a perspective view showing a relative positioning of magnetic poles in magnetic units of the motor. Fig.35 is an exploded perspective view of magnetic units of the motor used to explain the position setting of magnetic poles. Fig.36 is a perspective view of other magnetic units of the motor used to explain the position setting of magnetic poles. Fig.37 is a perspective view of an exemplary salient pole of the motor. Fig.38 is a perspective view of a salient pole of the motor wound around with coil. Fig.39 is a perspective view of a salient pole of the motor provided with a terminal board. Fig.40 is an exploded perspective view used to explain assembly of the motor.

Fig.41(a) is a lengthwise cross sectional view of a motor in accordance with a seventh exemplary embodiment of the invention. Fig.41(b) is a traversing cross sectional view of the motor. Fig.42 is a perspective view showing a rotor magnet of the motor provided with bushing. Fig.43 is a model chart used to explain the quantity of imbalance in the motor. Fig.44 is a perspective view of a salient pole of the motor wound around with coil and provided with a terminal board. Fig.45 is an exploded perspective view used to explain assembly of the motor.

Fig.46(a) is a lengthwise cross sectional view of a motor in accordance with an eighth exemplary embodiment of the invention. Fig.46(b) is a traversing cross sectional view of the motor. Fig.47(a) is a side view showing a core of the motor.

Fig.47(b) is a traversing cross sectional view showing core of the motor. Fig.48(a) is a front view showing a structure of core and resin insulator of the motor. Fig.48(b) is a side view of the same. Fig.48(c) is a plane view of the same. Fig.49 is a chart
 5 showing relationship among the core, the back yoke and the rotor magnet of the motor. Fig.50 is a graph showing relationship between the core angle α and the cogging torque in the motor. Fig.51 is a graph showing relationship between the core angle $\alpha - \beta$ and the cogging torque in the motor. Fig.52(a) is a front view showing a rotor
 10 magnet of the motor. Fig.52(b) is a bottom view of the same. Fig.53(a) is a chart showing an exemplary case of the motor wherein the gravity centre of an imbalancing weight relative to bearing is located outside an area between the two bearings. Fig.53(b) shows other case wherein the gravity centre is located between the two
 15 bearings. Fig.54 is a graph showing a relationship of the loss torque versus the distance L_1 between the bearings and the bearing to weight distance L_2 in the motor. Fig.55(a) is a chart showing load on the shaft of the motor where there is one imbalancing weight. Fig.55(b) shows load on the shaft where there are two
 20 imbalancing weights. Fig.56 is a graph showing relationship between the bending δ of shaft and the distance L_3 from bearing to weight in the motor.

Fig.57 is a cross sectional view showing a motor in accordance with a ninth embodiment of the invention.

25 Fig.58 is a cross sectional view of a conventional motor. Fig.59(a) is a cross sectional view showing a simplified magnetic circuit of the motor. Fig.59(b) is a chart showing the motor unfolded from inside the core. Fig.60 is a graph showing efficiency of the motor. Fig.61(a) is a partially cut-away cross
 30 sectional view showing other exemplary conventional motor. Fig.61(b) is a traversing cross sectional view of the same. Fig.62(a) is a plane view of other example of conventional motor. Fig.62(b) is a lengthwise cross sectional view of the same.

35 BEST MODE FOR CARRYING OUT THE INVENTION

In the following, description is made on exemplary

embodiments of the invention with reference to drawings.

Fig.1 is a cross sectional view of a motor in accordance with a first exemplary embodiment of the present invention.

As shown in Fig.1, a rotor is comprised of magnetic units 4a, 4b and 4c of empty cylindrical shape each having the magnetized N and S poles, stacked with a spacer 5 in between the units and fixed one another around a shaft 6 penetrating in the empty area, one end of the shaft 6 being supported by a bearing 9a provided on a frame case 10 while the other end by a bearing 9b provided on a bracket 8. Thus an inner-rotor structure supported at both ends is formed.

Cylindrical cores 1a, 1b and 1c having bipolar magnetic salient poles 7a - 7c are made by placing a press-formed silicon steel sheet one over another in the thrusting direction. The cores are insulated each other with resin insulators 2a, 2b and 2c. Each of the insulators 2a, 2b and 2c has a terminal pin 12 formed as an integral part of the insulator; the beginning and the end of winding of coil 3a, 3b, 3c are wound around the terminal pin 12 for several turns and soldered thereto. This makes the automatic assembly easier.

The cores 1a - 1c are serially connected together using aligning pins formed by making a part of the insulators 2a - 2c extruded, and then inserted to be fixed in the inside of the frame case 10 whose shape is cylindrical with one end closed. The terminal pins 12 are connected with coils 3a, 3b and 3c, respectively, and are fixed to a board 11 by soldering. To the open end of frame case 10, a bracket 8 having a bearing 9b fixed thereon is inserted and fixed.

Fig.2 shows a state of magnetization of rotor magnet in the above motor.

In the rotor magnet comprised of magnetic units 4a, 4b and 4c stacked in three stages, magnetized position of the N and S poles of the magnetic unit at each stage deviates relative to one another by 120° in a circumferential direction, as shown in Fig.2.

Fig.3 is charts showing the mutual relationship among

the magnetic units 4a, 4b, 4c, the cores 1a, 1b, 1c, and the coils 3a, 3b, 3c.

As shown in Fig.3 and Fig.1, the pair salient poles 7a, 7b, 7c of cores 1a, 1b, 1c are located with a same circumferential positioning, and are disposed on a straight line queue in a lengthwise direction; at each of the cores 1a, 1b, 1c, the respective pair salient poles 7a, 7b, 7c are wound around with one piece of conductive wire continually one after the other in a same winding direction, and the coils 3a, 3b, 3c are formed as shown in Fig.3.

Fig.4 is a waveform chart showing the induced voltage generated in each of the coils 3a, 3b, 3c when the magnetic units 4a, 4b, 4c are put in rotation.

As seen from the Fig.4, the phase of induced voltages Va, Vb, Vc generated at coils 3a, 3b, 3c is shifted relative to one another by 120°, reflecting the circumferential deviation of 120° in the magnetic units 4a, 4b, 4c. One coiling end of each of the coils 3a, 3b, 3c is connected together forming a common terminal called COM. The other ends of the respective coils are assigned respectively to the three phases to be electrically driven by an electronic circuit provided on the board 11 in accordance with the induced three-phase voltage. Thus a torque is generated and the magnetic units 4a, 4b, 4c are rotated, or it is driven as a three-phase brushless motor. The electronic circuit on the board 11 is supplied from a DC supply source.

Fig.5(a) is a cross sectional view of a simplified magnetic circuit in the above brushless motor. Fig.5(b) is a chart showing the motor unfolded from inside the core. For the simplification of explanation, the leakage of magnetic flux is ignored in the following description.

An inverse number of the velocity shift rate μ is often used to represent the efficiency η of a motor. A following Formula 7 is generally established with respect to the velocity shift rate μ , as already described in the background art:

$$\eta = \frac{1}{\mu} = \frac{\Phi^2 T^2}{R} \dots (7)$$

5 where; Φ denotes effective magnetic flux, T is number of coil turns, R is coil resistance.

The effective magnetic flux Φ is expressed in the following Formula 8.

$$\Phi = \pi D L B_g \dots (8)$$

10 where; D denotes the outer diameter of rotor, L is the length of rotor, B_g is the density of magnetic flux at gap.

The density of magnetic flux B_g at gap is expressed in the following Formula 9.

$$15 \quad B_g = \frac{B_r}{1 + \frac{\mu r L_m}{L_g}} \dots (9)$$

20 where; B_r , μr are called respectively residual flux density, recoil magnetic permeability. These are the constants specific to a magnetic material.

L_m is thickness of magnet, L_g is air gap between magnet and core.

25 The relationship between the number of coil turns T and the coil resistance R is represented in Formula 10.

$$30 \quad R = \frac{2kT^2 l}{S} \dots (10)$$

35 where; k denotes electric conductivity of coil, which is a constant determined proportionate to the space factor of coil. l represents average coil length per one turn, S is cross sectional area of coil.

The l is represented by Formula 11, ignoring the coil

resistance.

$$1 = 2 (L_c + D_c) \doteq 2 \frac{L}{3} + \frac{\pi}{2} D \dots (11)$$

where; L_c denotes height of coil, D_c is coil width.

By substituting the Formula 8, Formula 9, Formula 10 and Formula 11 for Formula 7, the following Formula 12 is obtained:

$$\eta = \left[\pi DL \frac{Br}{1 + \frac{\mu r}{L_m / L_g}} \right]^2 \cdot \frac{S}{4k \left[\frac{L}{3} + \frac{\pi}{2} D \right]} \dots (12)$$

There is no component representing the coil resistance R nor the number of coil turns T contained in the above Formula. It indicates that the efficiency does not change by a change in the specifications of coil winding.

In the above formula, when the rotor length L , rotor diameter D are varied so as the volume of rotor ($\pi D^2 L/4$) remains constant, with other variables fixed, the relationship between the length/diameter of rotor (L/D) and the efficiency η is as shown in Fig.6. In Fig.6, the dotted line represents a conventional inner-rotor type brushless motor. As seen from the Fig.6, efficiency of the invented motor is inferior to that of conventional brushless motor when the rotor is short, but it improves with a longer rotor; the efficiency curves cross at a certain point and the efficiency with the latter goes higher. At an ultimate convergent value, viz. $L/D = \text{infinite}$ in Formula 12, the efficiency of invented motor reaches as high as 1.5 times that the conventional motor.

In the above described exemplary embodiment, the magnetic units 4a, 4b, 4c have been magnetized respectively with

deviation of 120 relative to one another. They may be magnetized also with a deviation of 60. In the latter case, the winding direction of coils 3a, 3c has to be made inverse to that of coil 3b as shown in Fig.7, or connection of the coils be reversed while
 5 keeping the winding direction as it is; by so doing, the phase of induced voltage is shifted for 120 , making the three-phase drive possible.

Although in Fig.1 round-shape cores 1a, 1b, 1c are exemplified, they may be shaped to have a flat portion 1p at the
 10 outer circumference. With the cores of such a shape, a motor may have a good stability when mounted in an apparatus.

Although in the present embodiment the phase of induced voltage in respective three stages has been set to deviate relative to one another for 120 by shifting the direction of
 15 magnetization, the 120 deviated phase may be obtained also by shifting the direction of the salient poles 7a, 7b, 7c of cores 1a, 1b, 1c relative to one another with the direction of magnetization of the magnetic units 4a, 4b, 4c kept in one direction, or by shifting the direction of both the salient poles
 20 7a, 7b, 7c of cores 1a, 1b, 1c and the magnetic units 4a, 4b, 4c relative to one another at each stage. Under any one of the above configurations a motor may operate as a three-phase brushless motor. When both the salient poles 7a, 7b, 7c of cores 1a, 1b, 1c and the magnetic units 4a, 4b, 4c are shifted in the direction
 25 relative to one another at each stage, among other cases, it may become possible to suppress the overall height of a motor further by housing the coils of top and bottom cores 1a, 1c within a slot portion of the core 1b located in between. This may offer another step to make a motor smaller.

30 Although in the present embodiment a motor has been described to have a three-stage structure, it may also be structured in K stages($K = 2, 3, 4 \dots$). Thus the invention may be carried out generally as a K-phase brushless motor.

Now in the following, a second exemplary embodiment of
 35 the invention is described with reference to Fig.9 and Fig.10. In the second embodiment, the number of magnetized poles of a

magnetic unit is not two, but a number more than that. The structures of the motor remain the same as those of the first embodiment above, with the exceptions in the number of magnetized poles in magnetic unit, the corresponding salient poles of each core and the coils.

Fig.9 shows a relationship among magnetic units, cores and coils in a motor where magnetic units 14a, 14b, 14c have six magnetized poles, and the number of magnetic poles in salient poles 16a, 16b, 16c of cores 15a, 15b, 15c is four. A common connection terminal of each of coils 17a, 17b, 17c is represented by a symbol COM, the other end terminals by symbols U, V, W, respectively. The same applies to Fig.10.

Shown in Fig.9 are six-pole cylindrical magnetic units 14a, 14b, 14c, each having the N and S poles magnetized with a 60 angular pitch in a circumferential direction, and cores 15a, 15b, 15c, each having salient poles 16a, 16b, 16c of four magnetic poles disposed with the same angular pitch as the magnetized pitch of magnetic units 14a, 14b, 14c so as to correspond to two pairs of the magnetized poles, two poles at one side and the other two poles at the other side facing to each other as illustrated; the cores stacking up axially in three stages.

With the above structure, it turns out easy to provide the cores 15a, 15b, 15c, with a flat portion 13, as illustrated. In this way, one of the dimensions in the direction of diameter may be reduced even in a multi-slot motor. Namely, an oval-shaped motor may be designed with ease.

Fig.10 shows other exemplary configuration of the magnetic units, cores and coils in a motor comprised of six-pole magnetic units 14a, 14b, 14c and cores 15a, 15b, 15c having four-pole salient poles 16a, 16b, 16c.

Shown in Fig.10 are six-pole cylindrical magnetic units 14a, 14b, 14c, each having the N and S poles magnetized with a 60 angular pitch in a circumferential direction, and cores 15a, 15b, 15c, each having salient poles 16a, 16b, 16c of four magnetic poles disposed with the same angular pitch of magnetic units 14a,

14b, 14c so as to correspond to two pairs of the magnetized poles, the four poles of salient poles 16a, 16b, 16c being placed concentrated in one side as illustrated; the cores stacking up axially in three stages.

5 With the above structure, one dimension from axial centre of cores 15a, 15b, 15c to a side may be reduced to be smaller than the counterpart dimension, as illustrated. A motor of such configuration may be advantageous when used, for example, as the spindle motor of an optical disk device, where the mounting
10 space is limited in one of the circumferential directions; namely, within a given height, eventual size of a motor may be made larger, for a greater output.

As described in the above, a three-phase brushless motor may be implemented even if the number of poles in magnetic units
15 14a, 14b, 14c is different from that of salient poles of cores 15a, 15b, 15c; by combining three cylindrical magnetic units each having the N and S poles magnetized for $2n$ poles (n indicating any integer not smaller than one) in a circumferential direction with an equal angular pitch, and three cores each having salient poles
20 of $2m$ poles (m indicating any integer not smaller than one, $m \leq n$), disposed with a same magnetizing pitch of the magnetic units so as to correspond to m magnetized poles, stacked in axial direction for three stages, with the angle between the magnetization of magnetic unit and the core deviating by $120/n$ relative to one
25 another at each of the stages.

Although in the above exemplary embodiment a motor has been structured in three stages, it may of course take K stages ($K = 2, 3, 4, \dots$). The invention may be applied generally to any K -phase brushless motors.

30

A third exemplary embodiment of the invention is described in the following referring to Fig.11 - Fig.17.

As shown in Fig.11, a rotor is comprised of magnetic units 21a, 21b and 21c of empty cylindrical shape, stacked in three stages
35 with a spacer 22 in between and fixed around a shaft 23 penetrating through the empty area of each of the magnetic units

21a, 21b and 21c, the shaft 23 being supported at both ends by a bearing 25 attached on a frame 24. Thus an inner-rotor structure supported at both ends is formed.

Two cores 19 positioned at both sides are provided each with three salient poles 18a, 18b, 18c, being shaped out of an iron chunk by a cutting process to form a straight line queue of three, and magnetic circuits connecting the salient poles. These are insulated with an electrostatic coating. After winding coils 20a, 20b, 20c around the salient poles 18a, 18b, 18c, the cores 19 are inserted to the frame 24 at both ends, and the terminal ends of coils 20a, 20b, 20c are soldered to a board 26 on which a connection pattern is printed. A cover 27 forms a part of outer case.

Fig.12 shows the state of magnetization of magnetic units in the above motor.

As shown in Fig.12, the magnetized position of the N and S poles of the magnetic units 21a, 21b, 21c at each stage deviates relative to one another by 120° in a circumferential direction.

Fig.13 shows a relationship among the magnetic units 21a, 21b, 21c, the salient poles 18a, 18b, 18c of core 19, and the coils 20a, 20b, 20c.

As shown in Fig.13, coils 20a, 20b, 20c are coupled to form one group respectively corresponding to each of the stages of magnetic units 21a, 21b, 21c.

Fig.14 is a waveform chart showing the induced voltages generated in each of the coils by a rotating rotor. As seen from the Fig.14, the phase of induced voltages V_a , V_b , V_c generated at coils 20a, 20b, 20c is shifted relative to one another by 120°, reflecting the circumferential deviation of magnetization by 120° in the magnetic units 21a, 21b, 21c. One terminal end of each of the coils 20a, 20b, 20c is connected together forming a common terminal called COM. The other terminal ends of the respective coils are assigned respectively to the three phases to be electrically driven by an electronic circuit in accordance with the induced three-phase voltage. Thus a torque is generated and the magnetic units are rotated, or it is driven as a three-phase

brushless motor.

Fig.15(a) is a cross sectional view of a simplified magnetic circuit in the invented brushless motor. Fig.15(b) shows the motor unfolded from inside the core. For the simplification of explanation, the leakage of magnetic flux is ignored in the following description.

The efficiency of a motor η is represented, alike Embodiment 1, by:

$$\eta = \left[\frac{\pi DL \frac{Br}{\mu r}}{1 + \frac{Lm}{Lg}} \right]^2 \cdot \frac{S}{4k \left[\frac{L}{3} + \frac{\pi}{2} D \right]} \dots (12)$$

The above Formula contains no component representing the coil resistance R, nor the number of coil turns T, which indicates that the efficiency does not change by a change of specifications in the coil winding.

In the above formula, when the rotor length L, rotor diameter D are varied so as the volume of rotor ($\pi D^2 L/4$) remains constant with other variables fixed, the relationship between the length/diameter of rotor (L/D) and the efficiency η is as shown in Fig.16. In Fig.16, the dotted line represents a conventional inner-rotor type brushless motor. As seen from the Fig.16, efficiency of the invented motor is inferior to that of conventional brushless motor when the rotor is short, but it improves with a longer rotor; the efficiency curves cross at a certain point and efficiency with the latter goes higher. At an ultimate convergent value, viz. L/D = infinite in Formula 12, the efficiency of invented motor reaches as high as 1.5 times that the conventional motor.

Although in the present embodiment the core 19 having integrated salient poles 18a, 18b, 18c in three stages has been employed for two pieces, the number of cores may be q pieces (q = 1,2,3,4,...). In a case where the core 19 is employed for two pieces(or one piece) as in the present embodiment, among

others, the thickness of a motor in radius direction may be reduced to almost as thin as the diameter of magnetic units 21a, 21b, 21c. This means that magnetic units 21a, 21b, 21c having a larger diameter may be used within a given space in the thickness; output of the motor may increase accordingly.

Fig.17 shows a relationship among magnetic units, cores and coils in a motor where the magnetic units 31a, 31b, 31c have four magnetized poles, the core 29 is used for three pieces, and the number of poles in salient poles 28a, 28b, 28c is three. A common connection terminal of each of the coils 30a, 30b, 30c is represented by a symbol COM, the other end terminals by U, V, W, respectively.

Shown in Fig.17 are four-pole cylindrical magnetic units 31a, 31b, 31c, each having the N and S poles magnetized with a deviation of 90 angular pitch in a circumferential direction, and a core 29 having three-pole salient poles 28a, 28b, 28c disposed on a line parallel to the axial direction at a same pitch as the magnetizing pitch of the magnetic units 31a, 31b, 31c and magnetic circuits coupling the salient poles 28a, 28b, 28c.

A motor of the above structure may be advantageous when used, for example, as the spindle motor of an optical disk device, where the mounting space is limited in one of the circumferential directions of a motor. Namely, the eventual size of a motor may be made larger within an available height, hence a greater output.

Although in the present embodiment a motor has been described to have a three-stage structure, it may also be structured in K stages($K = 2, 3, 4, \dots$). Thus the invention may be carried out generally as a K-phase brushless motor.

Now in the following, a fourth exemplary embodiment of the invention is described with reference to Fig.18 and Fig.19.

In the above described first exemplary embodiment through third exemplary embodiment, the rotor has been comprised of three magnetic units fixed around a shaft with spacer in between the magnetic units. In the present fourth embodiment, a single rotor magnet 32 is fixed around a shaft 33, as shown in Fig.18, the rotor magnet 32 being magnetized in three stages like

the rotor of Fig.2. With the above structure, three pieces of components are integrated into a single component; which signifies the reduction in components cost and the suppressed deterioration of motor characteristics due to angular errors during assembly of the magnetic units in three stages.

In the case of Fig.18, a rotor magnet has been magnetized in three stages. However, a rotor 34 may also be magnetized in a skew configuration, as shown in Fig.19, where the magnetized area continually changes. The rotor magnet 34 produces a same effect as the one in Fig.18. A skew magnetization may present an additional advantage of reduced cogging torque, because in the skew configuration the switching of magnetic flux takes place in a smooth manner.

In the following, a fifth exemplary embodiment of the invention is described with reference to Fig.20 through Fig.32.

Fig.20(a) is a cross sectional view in the longitudinal direction showing a vibration motor for use in a pager of mobile communication apparatus. Fig.20(b) is a traversing cross sectional view of the motor.

A motor of the present embodiment has an outer case 90 whose shape is an oblong rectangle in a cross sectional plane perpendicular to the axial direction of rotor 37, the pair of shorter sides 90a, 90a forming yokes 47, 48, while the longer side pairs 90b, 90b being comprised of a printed board 51 and a sheet 53. It is also possible to make the cross sectional shape of the outer case 90 oval, or other oblong shapes. The rotor 37 is comprised of three magnetic units 38a, 38b, 38c, spacers 44a, 44b to be placed between the magnetic units, and a shaft 39.

In Fig.20, salient poles 35a, 35b, 35c, 36a, 36b, 36c are each provided with an insulation layer by means of electrostatic coating, and is wound around with coil 42 over the insulation layer. The salient poles 35a, 35b, 35c wound around with coil 42 are attached to the yoke 47 in the axial direction of shaft 39 with a certain space between one another, forming a first core(core assembly) 54. At an opposite place beyond the shaft 39 is a second core(core assembly) 55. The second core 55 is

comprised of the salient poles 36a, 36b, 36c wound around with coil 42 and attached to the yoke 48 in the axial direction of shaft 39 with a certain space between one another.

Each of the magnetic units 38a, 38b, 38c of rotor 37 is
 5 a radially anisotropic sintered magnet of an empty cylindrical shape, magnetized in the N and S poles. The three magnetic units 38a, 38b, 38c, whose magnetic position at each stage deviates relative to one another by 120° in a circumferential direction, are fixed at a certain interval around the shaft 39 inserted
 10 through the empty space of the cylindrical magnetic units, with spacers 44a, 44b provided in between the magnetic units.

A motor of the present embodiment is for use in a pager of mobile communication apparatus having a vibration call function. For obtaining a vibration, an imbalancing weight 45
 15 whose centre of gravity is off the centre of rotation (centre of shaft) is provided, and an energy stemming from centrifugal force of the weight 45 is transmitted to the stator of the motor.

In this case, the larger the radial load on bearing 41 the greater is the vibration. In order to increase the load to be
 20 exerted on bearing 41, the gravity centre of the spacers 44a, 44b is also placed off the rotating centre for creating an eccentric load. The load in radial direction to be exerted to the bearing 41 is a reaction force to an action of the imbalance force. The influence of the place of gravity centre of weight 45 and the
 25 place of gravity centre of spacers 44a, 44b on the degree of reaction force is described in the following with reference to Fig. 22.

When a substance of mass m , whose centre of gravity is
 30 eccentric to rotating axis by r , rotates around the axis at angular velocity ω , the centrifugal force F is represented by Formula 13.

$$F = m \cdot r \omega^2 \dots\dots (13)$$

35 Taking the elastic deformation ρ due to centrifugal force into consideration, the total centrifugal force F is represented by Formula

14.

$$F = m (r + \rho) \omega^2 \dots (14)$$

5 As the elastic deformation ρ is ignorable relative to r , a formula that represents the centrifugal force F is the Formula 13. When the centrifugal force F_1 , F_2 , F_3 of the weight 45 and the spacer 44a, 44b are decomposed into the directions of X axis and the Y axis, the relationship is as shown in Formula 15: where, L_1 , L_2 , L_3 indicating respectively
10 the distance from bearing 40 to weight 45, spacer 44a, spacer 44b; L indicating the distance from bearing 40 to bearing 41, the X axis representing the shaft centre, Y axis being an axis that is perpendicular to the X axis.

$$\begin{aligned} 15 \quad F_{1x} &= m_1 r_1 \omega^2 = F_1 \\ F_{1y} &= 0 \\ F_{2x} &= m_2 r_2 \omega^2 \cos \theta_2 = F_2 \cos \theta_2 \\ F_{2y} &= m_2 r_2 \omega^2 \sin \theta_2 = F_2 \sin \theta_2 \\ F_{3x} &= m_3 r_3 \omega^2 \cos \theta_3 = F_3 \cos \theta_3 \\ 20 \quad F_{3y} &= m_3 r_3 \omega^2 \sin \theta_3 = F_3 \sin \theta_3 \dots (15) \end{aligned}$$

Assuming the reactive force of bearing 41 as R , the reactive force R is also decomposed into the directions of X and Y, then the moment with the bearing 40 as fulcrum is represented in Formula 16:

$$\begin{aligned} 25 \quad L R_x &= L_1 F_{1x} + L_2 F_{2x} + L_3 F_{3x} \\ L R_y &= L_1 F_{1y} + L_2 F_{2y} + L_3 F_{3y} \dots (16) \end{aligned}$$

When component forces R_x , R_y of the reactive force R are composed:

$$\begin{aligned} 30 \quad R^2 &= R_x^2 + R_y^2 \dots (17) \end{aligned}$$

Accordingly, a square of the reactive force R is represented by Formula 18:

$$\begin{aligned} 35 \quad R^2 &= R_x^2 + R_y^2 \end{aligned}$$

$$\begin{aligned}
&= (F1x \cdot (L1/L) + F2x \cdot (L2/L) + F3x \cdot (L3/L))^2 \\
&+ (F1y \cdot (L1/L) + F2y \cdot (L2/L) + F3y \cdot (L3/L))^2 \\
&= (F1 \cdot (L1/L) + F2\cos \theta_2 \cdot (L2/L) + F3\cos \theta_3 \\
&\cdot (L3/L))^2 + (F2\sin \theta_2 \cdot (L2/L) + F3\sin \theta_3 \\
&\cdot (L3/L))^2 \dots\dots (18)
\end{aligned}$$

The reactive force R reaches maximum when R2 is the highest. In Formula 18, the angular velocity ω , mass $m1, m2, m3$, eccentricity distance $r1, r2, r3$, distance in axial direction $L1, L2, L3$ are all known values, while unknown figures are the angles θ_2, θ_3 . The reactive force R reaches maximum when $\theta_2 = \theta_3 = 0$; viz. when the direction of centrifugal force of the spacer coincides with that of the weight.

It is known from the above description that the direction of eccentricity in the spacer should preferably be in the same direction as that of weight 45, 44a, 44b. A rotor of the present embodiment has been made in conformity with the above structure. Therefore, the imbalancing load on the bearing 41 has been maximized.

As the shape of weight 45 bears a substantial influence on the vibration, a study has been made on a model weight as shown in Fig.23. The weight 45 has a fan shape having an angle semi-circle minus the angle 2α . Diameter of the outermost circle of weight 45 is represented by D, which is referred to as outer diameter of weight in the forthcoming descriptions. Fig.24(a),(b),(c) show respectively the quantity of displacement g of centre of gravity of weight 45, the square measure A of weight 45, the centrifugal force F4, with the angle α as the parameter. Here, the diameter of shaft $d = 1$, the thickness of weight 45, the specific gravity of weight 45 and a square of the revolution velocity have been assumed constant. The quantity of gravity centre displacement in the fan-shape weight 45 is in a linear equation with the ratio of weight outer diameter D versus shaft diameter d(D/d). The square measure A of weight 45 is in an equation of higher degree with the ratio of weight outer diameter D versus shaft diameter d(D/d). As the centrifugal force is represented by Formula 13, centrifugal force F4 is in proportion to the product of square measure A of weight 45 and quantity of gravity centre displacement g.

For increasing the vibration by weight 45, the outer

diameter of weight 45 should be as large as possible. This is understood from Fig.24; however, in a flat motor as illustrated in Fig.20, it may not be practical to provide a weight whose outer diameter D is larger than length of the shorter side 90a, except a very special case. The outer diameter D of weight 45 falls under the following regulations in a flat motor as shown in Fig.20.

The outer diameter D of weight 45 is:

$$0.6 \times a < D < a \dots\dots (19)$$

10

where; a represents the length of shorter side 90a(see Fig.20(b)).

Furthermore, as it is preferred for providing a motor of this type with more advantages to make the sheet 53 and the print board 51 thinner, the weight outer diameter D should ideally be determined to conform Formula 20:

15

$$0.8 \times D_m < D < 1.1 \times D_m \dots\dots (20)$$

20

where; D_m represents the outer diameter of rotor magnetic unit.

As shown in Fig.25, the bearing 40 is a cylindrical bearing which encounters a load in radial direction, while a load in thrust direction is encountered by a pivotal bearing formed by the circular arc at the tip end of shaft 39 and a thrust plate 46. A resin material of low sliding friction is used for the thrust plate 46.

25

The highest bearing pressure P_{max} and the friction torque T_p are obtainable in Formula 21:

30

$$\begin{aligned} P_{max} &= a \times r^{-2/3} \\ T_p &= b \times r^{1/3} \dots\dots (21) \end{aligned}$$

35

where, r representing the radius of tip end sphere of

shaft 39; a and b being coefficients.

Fig.26 shows a relationship between respective ratios of the highest bearing pressure P_{max} and the friction torque T_p , assuming a certain radius r_0 and friction torque T_p 1. The smaller the radius r of tip end of shaft 39 the lower is the friction torque T_p ; but the bearing pressure P_{max} goes high. When the thrust plate 46 is made of resin, too high bearing pressure might harm the reliability. On the other hand, a large radius r decreases the bearing pressure but it increases the friction torque T_p . The torque loss is converted into heat, and the reliability might be deteriorated by an increased temperature. Therefore, a pivotal bearing for a rotation faster than 2000rpm has been formed so as the radius r of tip end of shaft and the diameter d of shaft satisfy the following Formula 22:

$$10 \times d > r > 1.5 \times d/2 \dots\dots (22)$$

The thrust plate 46 has been made with a readily available high polymer material. However, a highly lubricant polyacetal resin is ideal for motors of battery-driven apparatus, in order to keep the friction torque low for a long duration. In case operation under a high temperature environment is expected, use of a heat-resistant polyimide resin, Teflon resin is recommendable.

The outer diameter D_s of thrust plate 46 and the outer diameter d of shaft have been determined to meet the following Formula 23:

$$D_s > d \dots\dots (23)$$

By so doing, the thrust plate 46 may not fall off the bearing 40 when inserting a shaft; which means an easy and stable assembly work. Even when the shaft 39 moves in the thrust direction, the thrust plate 46 does not move because it is sticking to bracket 50 with lubricating oil or oil of the bearing 40. However, the thrust plate might move in the surface

direction, therefore in some cases the move have to be regulated in order to reduce the loss in bearing. By satisfying Formula 23, the contact area is increased, the move is suppressed, and the move may be regulated by the cylinder diameter of the bearing 40.

5 A bearing satisfying the Formula 23 may be assembled by first inserting the thrust plate 46 in bracket 50, and then fixing the bearing 40.

Along with the decreasing size of a motor, the bearing loss increases relative to a generated torque. Therefore, there
10 arises an increasing need for suppressing the bearing loss. It is recommendable to use an oil-containing sintered material for the bearings 40, 41. A preferred viscosity of the oil contained in the bearing is 10cst - 50cst.

When a low-friction resin is used for the sintered material, for
15 example, when fine powder Teflon whose grain size is less than $1\ \mu\text{m}$ is mixed, the Teflon intervening in the metal gap functions as a binder. Moreover, the resin spotted on the bearing surface facing the shaft 39 contributes for further reducing the bearing loss, as compared with a bearing containing only oil. This enables low voltage starting of a motor,
20 also contributes to a longer battery life.

When the inner surface of bearing is shaped to have a circular arc in the cross section, as shown in Fig.27, the bearing loss may be reduced further. Fig.27(a) shows a state where the shaft 39 is penetrating through the bearing 41 disposed in the
25 weight-end. Fig.27(b) shows part of the bearing 40 disposed in the pivotal end. Even if the shaft 39 is not positioned in a state exactly perpendicular to bracket 49 because of, for example, twisted assembly, bent shaft 39 due to imbalance, etc., the contact of shaft 39 to bearing 41 remains as a point-contact at
30 the circular arc 41a, or the bearing 41 is provided with an automatic centering function, as illustrated in Fig.27(a).

Also in the case of Fig.27(b), the contact of shaft 39 with bearing 40 remains as a point-contact at the circular arc 40a of
35 bearing 40 even if there is a twist in the assembly or a bent shaft 39 due to imbalance. Thus the bearing loss may be reduced

by making the contact of shaft 39 with bearings 40, 41 to be a point-contact by shaping the inner surface of the bearings to have a circular arc.

Next, on a land 51a of the printed board 51 constituting
 5 a longer side 90b of the outer case 90, terminal ends of coil 42 wound around each of the salient poles 35a - 35c, 36a - 36c are electrically coupled, directly or indirectly. The printed board 51 of the present embodiment is a flexible printed board, on which an integrated circuit 52 or other electronic circuits for driving
 10 are mounted, and a land 51a is provided for connection with the power supply from an apparatus.

In a motor of the present embodiment, a flexible printed board is disposed in one of the longer sides 90b. Therefore, a board of large size relative to the thin shape of a motor is made
 15 available, which means that it is easy to mount on the board various circuit components for driving. Thus a small and thin brushless motor may be offered in accordance with the invention.

On the side opposite to printed board 51 is a sheet 53. By affixing the sheet 53, a motor is sealed against outside.
 20 Motor is protected against the invasion of dusts, so a rotor may not be retarded in its rotation by dusts that are coming from outside and staying somewhere in between rotor 37 and cores 54, 55. Namely, the sheet keeps a motor dust-free. The sheet 53 may also serve as a label for describing name of the manufacturer,
 25 serial-number, etc.

The salient poles 35a - 35c, 36a - 36c of the present embodiment are not integrated as part of the yokes 47, 48, but each of them is an independent piece component. An example of the piece component, or the salient poles 35a - 35c, 36a - 36c, is
 30 shown in Fig.28. The entire salient pole of Fig.28 is designated with a numeral 56. Surface 57a of a protruded portion 57 of the salient pole 56 facing to rotor is shaped to have a circular curvature centred at the rotating axis. The reverse surface 57b, which is other surface of the surface 57a facing to rotor, is
 35 curved, and a tooth 58 of cylindrical shape is provided thereon to be wound around with coil. Assuming the diameter of cylindrical

tooth 58 as h1, a cylindrical portion 59 whose diameter is smaller than h1 is formed at an end of the tooth 58. The cylindrical portion 59 is to be inserted to a hole of yokes 47, 48 for the mounting thereon, and a step formed by the tooth 58 of the larger diameter h1 is to provide an appropriate positioning thereof. Inserting depth to the yokes 47, 48 is regulated by the step, and the air gap between rotor and curved surface 57a at each of the salient poles 56 may be made uniform. The tip end of cylindrical portion 59 has a hollowed surface for calking/fixing at the outer circumferential edge to the yoke 47, 48 after a salient pole 56 is inserted to a hole of yoke 47, 48. Besides the above described method, the salient pole 56 may be fixed to the yoke 47, 48 by means of pressure insertion, gluing, etc.

The salient pole as a piece component may take also a shape as shown in Fig.29. The entire salient pole of Fig.29 is designated with a numeral 60. Surface 61a of a protruded portion 61 of the salient pole 60 facing to rotor is shaped to have a circular curvature centred at the rotating axis. The reverse surface 61b, which is other surface of the surface 61a facing to rotor, is curved, and a tooth 62 having a rectangular cross sectional shape is provided thereon to be wound around with coil. Assuming the length of a side of the rectangular shape perpendicular to the revolving axis as h2, that of the other side running in the same direction as the revolving axis as h3, the tooth of Fig.29 establishes following Formula 24:

$$h2 \cong h3 \dots\dots(24)$$

A cylindrical portion 63 whose diameter is smaller than length of a side of the rectangle is formed at an end of the tooth 62. The cylindrical portion 63 is to be inserted to a hole of yoke 47, 48 for the mounting thereon, and a step formed by the tooth 62 of the larger dimensions is for the purpose of providing a proper positioning. Inserting depth to the yoke 47, 48 is regulated by the step, and the air gap between rotor and curved surface 61a at each of the salient poles 60 may be made uniform.

Fig.30 shows a still other exemplary shape of the salient pole as a piece component. The entire salient pole of Fig.30 is designated with a numeral 64. Surface 65a of a protruded portion 65 of the salient pole 64 facing to rotor is shaped to have a circular curvature centred at the rotating axis. The reverse surface 65b, which is other surface of the surface 65a facing to rotor, is curved, and a tooth 66 having a rectangular cross sectional shape is provided thereon to be wound around with coil; at an end of the tooth 66 a cylindrical portion 67 having a smaller diameter is formed as integral part with the rectangular tooth 66. Assuming the length of a side of the tooth perpendicular to the revolving axis as h_4 , that of the other side running in the same direction as the revolving axis as h_5 , the tooth 66 of Fig.30 establishes following Formula 25.

$$h_4 < h_5 \dots\dots (25)$$

In a motor whose cross sectional shape is a thin rectangle, advantages in shaping a tooth 66 of salient pole 64 in a rectangle in the cross section, with which the sides running in parallel to the axial direction are made longer than the other sides as indicated by Formula 25, are as described below. Namely, with reference to Fig.28, Fig.29 and Fig.30, the length in width direction of teeth 58, 62, 66 around which coils 42 are to be wound is assumed to be equal, viz. made to fulfill Formula 26;

$$h_1 = h_2 = h_4 \dots\dots (26)$$

then, the cross sectional square measure of tooth 66 shown in Fig.30 becomes the largest as compared with those in Fig.28 and Fig.29, as indicated in Formula 27.

$$(\pi/4) h_1^2 < h_2 \cdot h_3 < h_4 \cdot h_5 \dots\dots (27)$$

Assuming a same cross sectional square measure for the teeth, the dimension of salient pole in the width direction is the

shortest with the length h_4 of Fig.30. Therefore, there is more room for making the coiling height of coil 42 higher, or there is a room for increasing the number of turns.

As the above salient poles are constituted as
 5 independent piece component, an exemplary method of manufacture is described in the following. The salient poles are formed with a mixture of powdered metal and resin by injection molding, and then it is sintered for removing the resin, a process called metal injection. As compared with those manufactured by cutting or
 10 grinding, the dimensional allowance in the curvature of the surfaces 57a, 61a, 65a facing the rotor, shown in Fig.28 through Fig.30, in the salient poles produced by the above process is kept within a targeted specification even after the salient poles undergoing the sintering process. Accordingly, the dispersion of
 15 motor characteristics may be controlled small. The above manufacturing process of salient poles fits to volume production.

Salient poles of small and complicated shapes as shown in Fig.28, Fig.29, Fig.30 may be formed to final products by the metal injection technology(also referred to as metal powder
 20 injection molding), without requiring any post finishing. An example of the powdered material for salient poles includes Fe - Si group material; the material being a one which is unfriendly to machining process steps, therefore the post processing is hardly applicable on such materials. For the salient poles requiring a
 25 calking process step during assembly, a powdered material of pure iron must be used.

Process steps of the metal injection include weighing and mixing of constituent metal powders and resin binder, each sieved for specified grain size and controlled in chemical
 30 composition by reducing reduction, kneading of the mixture to prepare a stuff material for injection molding. Injection molded with dies, the binder resin is removed after molding, and then heated to sinter the powdered metal for providing sufficient coupling between atoms to create a state in which the air sac is
 35 contained. If there are many air sacs contained, the ultimate dimensions after sintering might change. Therefore, for the

salient poles or other components where requirements in the dimensional accuracy are stringent, grain size of the powder needs to be sufficiently fine and the diameter has to be uniform for obtaining a higher density.

5 With the air sac made smaller and the density increased, a salient pole may be improved in the capability so as to be able to meet the higher magnetic flux density. In order to have resin insulation film formed on the surface of sintered metal and air sac, it is recommended to have the salient poles impregnated
10 with a resin at the final processing stage, or to have a portion of binder resin left staying. Generation of eddy current may be suppressed by an insulation film formed as an internal structure in the salient pole.

15 Other exemplary method of manufacturing a salient pole is described in the following.

 Because the salient pole has been structured as a piece component small in size, it may be manufactured in volume through a forging process using a small forging machine. In the forging process, corner edges are rounded. So, the salient poles 64 as
20 shown in Fig.30 may also be rounded at the corner edges, but the curvature of surface 65a facing the rotor magnetic unit is not affected, therefore no difference is caused in the motor characteristics that stems from the shape of salient poles, as compared with those made of powdered metal. In the forged salient
25 poles, the magnetic flux flows in a same direction as the flow of metal composition, so there is no loss of magnetic flux; but a loss arises out of distortion in crystallized grain of the metal caused by forging. In order to reduce the loss, an annealing process is applied on the salient poles for making the size of
30 crystallized grain coarse.

 Now in the following, an assembly procedure for the motor of Fig.20 is described referring to Fig.31. A first core 54 formed by a yoke 47 mounted with three salient poles wound
35 around with coil is inserted at a lower protrusion 54a in a cut 50a of bracket 50 from the axial direction, on which bracket 50

thrust plate 46 has been provided and bearing 40 is pressed into and fixed. Lower protrusion 55a of a second core 55 formed by a yoke 48 mounted with three salient poles wound around with coil is inserted in the other cut 50b of bracket 50. Magnetic units
 5 38a - 38c and a specified number of spacers are mounted and fixed around shaft 39 at a specified position to form a rotor 37. The lower end of the shaft 39 of rotor 37 is inserted to bearing 40 provided in bracket 50.

Upper protrusion 54b of the first core 54 is inserted in
 10 a cut 49a of bracket 49, and upper protrusion 55b of the second core 55 is inserted in the other cut 49b of bracket 49. Before fitting the bracket 49, upper end of shaft 39 has been put through bearing 41 of bracket 49. These components may be assembled by handling from only the axial direction to be built in. After the
 15 frame work of a motor is completed, imbalancing weight 45 is put on the shaft 39, printed board 51 having electronic components is mounted, and terminal ends of the coils are soldered to the printed board at a land 51a. And then a sheet 53 is affixed.

Now, principle of rotation in the motor of the present
 20 embodiment is described using Fig.32 as basis.

Fig.32 describes relationship among magnetic units 38a - 38c, salient poles 35a - 35c, 36a - 36c, and coil 42(designated as 43a, 43b and 43c from the top).

As illustrated in Fig.32, the salient poles 35a - 35c,
 25 36a - 36c are provided with a same circumferential orientation on respective cores 54, 55 forming a straight line queue stretching in the length direction. At each stage, coils 43a, 43b, 43c are wound continually with a single wire in a same direction around the salient poles 35a - 35c, 36a - 36c of first core 54 and second
 30 core 55. The winding direction of coils 43a, 43b, 43c at each stage remains the same, as shown in Fig.32.

When the rotor rotates with the above structure, the phase of induced voltages V_a , V_b , V_c generated at coils 43a, 43b, 43c is shifted by 120° relative to one another because the angle of magnetic units 38a,
 35 38b, 38c at each stage deviates by 120° relative to one another. The induced voltage assumes the same wave form as in the first

embodiment shown in Fig.14, so the motor of present embodiment operates under the same rotation principle.

Although in the present embodiment a motor has been described to have a three-stage structure, it may also be structured with magnetic units and salient poles in K stages (K = 2,3,4,...). Thus the invention may be carried out generally as a K-phase brushless motor.

A sixth exemplary embodiment of the invention is described hereunder with reference to Fig.33 - Fig.40.

Fig.33(a) is a cross sectional view in length direction of a motor for use in a pager having a vibration call function of mobile communication apparatus. Fig.33(b) is a traversing cross sectional view of the motor. Description on those portions identical to the fifth embodiment is omitted here; only the points of difference are described. Those having the same structure as in Fig.20 are represented in Fig.33 by using the same symbols.

As shown in Fig.33(a),(b), an outer case 90 has a thin rectangle shape in the cross section by a plane perpendicular to the axial direction of a rotor 73. The shorter sides 90a, 90a are formed with a pair of yokes 47, 48. One of the longer sides 90b, 90b is left open, while the other is formed with a plate 68 and a flexible printed board 69.

A rotor 73 is comprised of magnetic units 74a, 74b and 74c of empty cylindrical shape, each magnetized into two poles, the N and S. As shown in Fig.34, the magnetized position of the N and S poles of the magnetic units 74a, 74b, 74c at each stage deviates relative to one another in a circumferential direction by 120°, and each of the magnetic units 74a, 74b, 74c is fixed around a shaft 39 penetrating through the empty portion of the magnetic units 74a, 74b, 74c. This may be regarded as a single-body rotor 73 in which the distribution of magnetized poles is stratified in the axial direction on the surface.

In order to place the three magnetic units 74a, 74b, 74c in a correct position relative to one another so as to create a specified deviation in the polarity, each of the three magnetic units 74a, 74b, 74c is provided with protrusion/hollow 75, 76 for

correct angular orientation, as shown in Fig.35. When the magnetic units 74a, 74b, 74c are stacked with the protrusion/hollow 75, 76 engaged, the 120 deviation is automatically provided relative to one another.

5 Under the above structure, the magnetic units 74a, 74b, 74c may be magnetized respectively using the protrusion/hollow 75, 76 as the reference point; and then a certain specific arrangement of the magnetic poles is obtained by simply stacking them with the protrusion/hollow 75, 76 engaged. This makes the assembly work
10 easy. As an alternative, a position orientation gear may be incorporated in a spacer provided between magnetic units as in the fifth embodiment. One example of such structure is described in the following.

Fig.36 shows a structure which comprises three magnetic
15 units 77a, 77b, 77c and spacers 78a, 78b provided in between the magnetic units. Each of the three magnetic units 77a, 77b, 77c is provided with hollow 80, while in each of the two spacers 78a, 78b protrusion 79 is provided to be engaged with the magnetic units. The protrusion 79 on spacers 78a, 78b is provided with an angular
20 deviation 120 between the up and down protrusions. By simply assembling the magnetic units 77a, 77b, 77c having the hollow 80 engaged with the protrusion 79 of spacer 78a, 78b, the deviation of the magnetized poles relative to one another becomes 120 in a circumferential direction.

25 Under the above structure, the magnetic units 77a, 77b, 77c may be magnetized respectively using the hollow 80 as the reference point; and then stacking them by simply engaging the hollow 80 of magnetic units 77a, 77b, 77c with the protrusion 79 of spacers 78a, 78b, a certain specific arrangement of the
30 magnetized poles is obtained. This makes the assembly work easy; accordingly, the above structure may be suitable to production in volume. In addition to the function as an aligner for relative positioning among the magnetic units, the spacers 78a, 78b may also play a role of imbalancing weight, and prevent the leakage of
35 magnetic flux between the adjacent magnetic units as well.

A motor of the present embodiment is for use in a pager

of mobile communication apparatus having a vibration call function. In order to pick up a vibration to be generated by motor, an imbalancing weight 45 is provided so as the centre of gravity is off the centre of rotation (centre of shaft).

5 For increasing the vibration by weight 45, the outer diameter of weight 45 should be as large as possible. The outer diameter D of weight 45 falls under the following limitation by Formula 28, like the case with fifth embodiment. Symbol a representing the dimension of shorter side 90a of outer case
10 90(see Fig.33(b)).

$$0.6 \times a < D < a \dots\dots (28)$$

15 Although the shaft 39 is not always located at the centre of bracket 70, diameter of the weight 45 may be determined in relationship with the diameter of magnetic units 74a - 74c based on the following Formula 29, as the rotor 73 is rotating: where, Dm representing the outer diameter of magnetic units, D the outer diameter of weight.

20

$$0.8 \times Dm < D < 1.1 \times Dm \dots\dots (29)$$

The bearing portion 70a of bracket 70 is made thinner around a hole for accepting shaft, as shown in Fig.33(a), and the
25 inner surface of which is coated with a low friction resin. The shaft 39 makes contact via the coated material 81 of low friction, therefore, the bearing loss is small. Further, as the thickness of low friction coating material 81 is as thin as less than e.g. 100 μ m, which means that it works as a member of high rigidity.
30 Therefore, a force exerted to the bearing portion 70a by imbalancing weight is transmitted to a structure outside the motor without being attenuated. Examples of the low friction coating material are shown in Table 1.

35

Table 1

	Item	Molybdenum disulfide	Fluoric resin	Graphite
5	Chemical formula	MoS_2		C
	Crystal structure	Layered, Open	Complexed	Layered
	Colour	Lead	Opal	Dark gray
10	Hardness (Mohs)	1 - 1.5		1.5 - 2
	Specific gravity	4.7	2.2	2.2
15	friction coeff.	0.02	0.03	0.05
	Highest temp.(°C)	320	260	430
20	Decompose temp.(°C)	1098	727	3498

Bracket 71 is made of a low friction resin and is provided with a bearing portion 71a of a spherical hollow shape integrated therein. Because the bracket 71 is made by injection molding, complexed shapes may be formed around the bearing portion 71a.

One among the group of e.g. fluoric resin, polyacetal resin and polyimide resin may be used for the low friction resin. The fluoric resin has been widely used in many industrial fields because of its anti-chemical property, heat resisting property and non-sticking property, besides the advantage in low friction.

In a case where the bracket 71 is made of a metal material, a pivotal bearing may be formed by coating a same low-friction coating material used for the bearing 70a of bracket 70.

A flexible printed board 69 is mounted with integrated

circuits 82 and other electronic components for driving, and is affixed on the plate 68. Terminal end of coil 42 wound around each of the salient poles 35a - 35c, 36a - 36c is connected to terminal board 72, which is then electrically connected to a land
 5 on the flexible printed board 69. Where a longer side 90b is constituted with the flexible printed board 69, as in the present embodiment, it becomes relatively easier to mount driving circuit components on the flexible printed board 69 for the thin configuration of a motor. Thus, a thin and small brushless motor
 10 may be formed. The other longer side opposit to the flexible printed board 69 is left open.

Like the case with fifth embodiment, the salient poles 35a - 35c, 36a - 36c of the present embodiment are not integrated with yokes 47, 48, but each of them constitutes a piece component.
 15 Fig.37 shows an example of the salient pole as an independent piece component.

Representing the entire salient pole of Fig.37 with a numeral 83, a surface 84a of protruding portion 84 of the salient pole 83 facing to rotor 73 has a curvature whose radius is not
 20 centred at rotor axis 85 but it is located at a point further away from the rotor axis 85. Namely, if the radius of the curvature R2 is infinite the surface becomes flat.

A surface 84b of protruding portion 84, which is the reverse surface of the surface 84a facing to rotor 73, is flat,
 25 and a tooth portion 86 has a rectangular cross sectional shape. Therefore, a coil may be wound around in a flat rectangular form with an esthetic finish accompanying least displacement of winding. This is advantageous also in the view point of reliability. Fig.38 shows a salient pole of Fig.37 wound around
 30 with a coil having a flat rectangular shape in the cross section.

The shape of a hole in the yoke 47, 48 for engagement with the salient pole 83 of Fig.37 is square, not round. Accordingly, a joint portion 87 of salient pole 83 is also shaped square in the cross section. Thus, when the portions for
 35 engagement are shaped in a polygonal form other than round, the salient pole 83 and the yoke 47, 48 may be aligned to a correct

relative positioning by themselves when inserted.

Each of the salient poles 35a - 35c, 36a - 36c in Fig.33 has been insulated by an electrostatic coating process. Coil 42 is wound around over the insulation layer with the terminal board 72 affixed to a portion of salient pole provided for insertion into yoke, and terminal end of the coil 42 is pressure-connected to the terminal board 72 at a vicinity of the salient pole. Fig.39 shows a salient pole, or a piece component, attached with the terminal board 72. The terminal board 72 is formed by an insulating resin 90 and a metal plate 89 integrated therein. One salient pole 83 is provided with two metal plates 89; one for the starting end and the other for wound end of the coil. Thus, a salient pole 83 wound around with coil assumes a shape similar to a chip resistor, or a component ready to be mounted immediately with ease.

Now in the following, a process of assembling a motor of Fig.33 is described with reference to Fig.40.

Flexible printed board 69 mounted with integrated circuits 82 and other electronic components is affixed on plate 68, rotor 73 which being an assembled body of magnetic units 74a - 74c and shaft 39 is fitted to bearing portion 70a of bracket 70 and then mounted on the plate 68 from a direction perpendicular to the shaft, and then the other bracket 71 is mounted from a slightly oblique direction to be fit to the shaft. A first core 54 having salient poles 35a - 35c wound around with coil 42 with the terminal ends fixed at terminal board 72 and mounted on yoke 47 in an axial direction with gap between one another is set on the brackets 70, 71; likewise, a second core 55 having salient poles 36a - 36c, etc. mounted on yoke 48 is set.

These components may be assembled from a direction perpendicular to the axial direction to be built in. After the frame work of a motor is completed, an imbalancing weight 45 is put on the shaft 39.

A seventh exemplary embodiment of the invention is described hereunder with reference to Fig.41 through Fig.45.

Fig.41(a) is a cross sectional view in a lengthwise

direction of a motor for use in a pager having a vibration call function of mobile communication apparatus. Fig.41(b) is a traversing cross sectional view of the motor. Description on those portions identical to those of the fifth embodiment is
 5 omitted here; only the points of difference are described. Those having the same structure as in Fig.20 are represented in Fig.41 by using the same symbols.

As shown in Fig.41, a rotor magnet 91 is a magnetic body of a column shape. Rotors in the fifth and sixth embodiments have
 10 been made of three magnetic units 38a - 38c. In the present embodiment, the rotor is made of a single piece of a magnetic body. However, the rotor of present embodiment is magnetized into a same state as those of the fifth and sixth embodiments. Therefore, for the sake of easy explanation the rotor magnet 91 is
 15 described in Fig.42 splitted into three stages; as if it is made of three magnetic units each magnetized with the phase of magnetic poles deviating by 120 relative to one another. Because the rotor magnet 91 is a magnet of a single body, work steps for aligning magnetic units to a right position in relation to the
 20 magnetic pole is eliminated. At both ends of the rotor magnet 91, a ring portion 95 of a smaller diameter is provided for accepting a ring-shape bearing bush 96, 97 to be pressed in and fixed thereto.

Each of the bearing bushes 96, 97 is provided with a
 25 thick crescent portion 96a, 97a, as shown in Fig.41 or Fig.42, which is for generating an imbalancing force as a result of rotating. The bearing bush 96, 97 is provided also with a bearing hole 96b, 97b at the centre. Each of the top and bottom bearing brackets 92, 93 is provided with a bearing pin 92a, 93a at the
 30 centre for a coupling with the bearing hole 96b, 97b. The rotor magnet 91 is supported revolvable by the top and bottom bearing brackets 92, 93.

A motor of the present embodiment is for use in a pager of mobile communication apparatus having a vibration call
 35 function. In order to pick up a vibration to be generated by a motor, bearing bushes 96, 97 whose centre of gravity is off the

center of rotation (shaft centre) are provided so as the centrifugal force generated by rotation at the gravity centre of bearing bushes 96, 97 is transmitted to a stator of the motor. The larger the radial load on bearing pins 92a, 93a the greater is the vibration. The load exerted on bearing pins 92a, 93a is described referring to Fig.43, a model chart.

Representing the distances from bearing pin 93a to bearing bush 96 and to bearing bush 97 as L_5 , L_6 , respectively, the distance from bearing pin 93a to bearing pin 92a as L , the distance between gravity centre of bearing bush 96 and shaft centre as r_5 , and the distance between gravity centre of bearing bush 97 and shaft centre as r_6 ; and the shaft centre is being represented with X axis, and Y axis being perpendicular to the X axis. The centrifugal force F_5 , F_6 to be exerted on bearing bush 96, 97 decomposed in X axis and Y axis are represented in Formula 30: where; ω representing angular velocity, m_5 , m_6 are respectively the mass of bearing bush 96, bearing bush 97.

$$\begin{aligned} F_{5x} &= m_5 r_5 \omega^2 = F_5 \\ F_{5y} &= 0 \\ F_{6x} &= m_6 r_6 \omega^2 \cos \theta_6 = F_6 \cos \theta_6 \\ F_{6y} &= m_6 r_6 \omega^2 \sin \theta_6 = F_6 \sin \theta_6 \dots\dots (30) \end{aligned}$$

Assuming a reactive force at bearing pin 92a against bearing bush 96 as R_3 , the reactive force R_3 decomposed into the directions of X and Y, viz. R_{3x} , R_{3y} , are represented in terms of a momentum in Formula 31, with the bearing pin 93a of bearing bush 97 as fulcrum:

$$\begin{aligned} LR_{3x} &= L_5 F_{5x} + L_6 F_{6x} \\ LR_{3y} &= L_5 F_{5y} + L_6 F_{6y} \dots\dots (31) \end{aligned}$$

Accordingly, a square of the reactive force R_3 is represented by Formula 32:

$$\begin{aligned} R_3^2 &= R_{3x}^2 + R_{3y}^2 \\ &= (F_{5x} \cdot (L_5/L) + F_{6x} \cdot (L_6/L))^2 \\ &\quad + (F_{5y} \cdot (L_5/L) + F_{6y} \cdot (L_6/L))^2 \\ &= (F_5 \cdot (L_5/L) + F_6 \cos \theta_6 \cdot (L_6/L))^2 \\ &\quad + (F_6 \sin \theta_6 \cdot (L_6/L))^2 \dots\dots (32) \end{aligned}$$

In Formula 32, the angular velocity, mass of bearing bush, eccentricity distance, distance in axial direction are all known values for designing, while the unknown is angle θ_6 . The R_3 reaches the highest when $\theta_6 = 0$; viz. when the direction of centrifugal forces of the two bearing bushes 96, 97 coincides.

In order to maximize the imbalancing load on the bearing pin 92a corresponding to bearing bush 96, the directions of eccentricity of gravity centre in the two bearing bushes 96, 97 have to coincide. Taking a practical allowance in the accuracy of assembly into consideration, Formula 33 has to be fulfilled.

$$|\theta_6| < 30^\circ \quad \dots\dots (33)$$

Reactive force R_4 to be exerted on the bearing pin 93a corresponding to bearing bush 97, with the bearing pin 92a corresponding to bearing bush 96 as fulcrum, may be obtained through Formula 34:

$$\begin{aligned} R_4^2 &= R_{4x}^2 + R_{4y}^2 \\ &= (F_{5x} \cdot ((L - L_5) / L) + F_{6x} \cdot ((L - L_6) / L))^2 \\ &\quad + (F_{5y} \cdot ((L - L_5) / L) + F_{6y} \cdot ((L - L_6) / L))^2 \\ &= (F_5 \cdot ((L - L_5) / L) + F_6 \cos \theta_6 \cdot ((L - L_6) / L))^2 \\ &\quad + (F_6 \sin \theta_6 \cdot ((L - L_6) / L))^2 \quad \dots\dots\dots (34) \end{aligned}$$

where, R_{4x} , R_{4y} representing the components of reactive force R_4 in X,Y directions.

Formula 34 indicates that the reactive force R_4 on bearing pin 93a corresponding to bearing bush 97 is maximized when the eccentricity angles in gravity centre of bearing bushes coincide.

In order to maximize the vibration to be caused by the imbalance, a product of the imbalancing mass and the gravity centre has to be made as great as possible. The bearing bush should have a largest possible outer diameter, yet it should not touch the outer case 90 of motor. The relationship may be represented in Formula 35: where; D_m representing the outer

diameter of rotor magnet 91, D_b representing the largest outer circumferential diameter of bearing bush.

$$0.8 \times D_m < D_b < 1.1 \times D_m \dots\dots (35)$$

5

As the dimensions of imbalancing bearing bushes 96, 97 are restricted by a shorter side 90a of outer case 90, they should practically be determined so as to fulfill Formula 36: where; symbol a representing the length of shorter side 90a of outer case 90 (see Fig.41(b)), D_b representing the largest outer diameter of bearing bushes 96, 97.

10

$$0.6a < D_b < a \dots\dots (36)$$

15

Likewise the case with the fifth embodiment, the salient poles 35a - 35c, 36a - 36c are not integrated with yokes 47, 48, but each of them constitutes an independent piece component. As shown in Fig.44, each of the salient poles 35a - 35c, 36a - 36c is wound around with coil 42, at that time a terminal board formed by a resin integrated with metal pieces 98 is attached to, and end terminals of coil 42 are electrically connected to the metal pieces 98 of terminal board 99. The beginning and the ending of coil 42 are each connected to the metal piece 98 by fusing through thermal compression. A protruding portion 100 of the salient pole 35a - 35c, 36a - 36c is provided with a circular arc surface at the surface facing the rotor magnet 91. Each of the salient pole 35a - 35c, 36a - 36c is also provided with a cylindrical portion 101 to be inserted in the yoke 47, 48 for positioning.

20

25

Assembly of a motor of the present embodiment shown in Fig.41 is described in the following with reference to Fig. 45

30

As shown in Fig.45, a flexible printed board 94 is fixed on yokes 47, 48 in both sides, a certain specific number of salient poles 35a - 35c, 36a - 36c are disposed thereon with the cylindrical portions 101 inserted in holes 102 provided in the yokes 47, 48. The flexible printed board 94 is coated with a cream solder in advance and is mounted with integrated circuits

35

103 and other electronic components. Therefore, the metal piece 98 of terminal board 99 positioned on land 104 of flexible printed board 94 is soldered during a reflow furnacing for electrical conduction with the coils and electronic components.

5 After the electrical conduction is secured, each of the yokes 47, 48 mounted with the salient poles 35a - 35c, 36a - 36c is raised upright from both sides, and the rotor magnet 91 assembled with bearing bushes 96, 97 is placed between the yokes 47, 48. And then the bearing brackets 92, 93 are attached to from
10 the up, and the rotor magnet 91 is supported by the yokes 47, 48. A sheet 105 is affixed, as a result the inside of motor is kept sealed.

 The bearing brackets 92, 93 are provided respectively with bearing pins 92a, 93a. Different from those in the fifth and
15 sixth embodiments, the rotor magnet 91 of the present embodiment has an empty-cylindrical shape without shaft. Therefore, the bearing bushes 96, 97 are inserted to the rotor magnet from both ends to have bearing gear formed in engagement of the holes 96b, 97b with the bearing pins 92a, 93a of bearing brackets 92,
20 93. The bearing pin 92a, 93a may be formed by means of a coining press if the bearing bracket 92, 93 is made of a metal material.

 An eighth exemplary embodiment of the present invention is described in the following referring to Fig.46 - Fig.56.

 Fig.46(a) shows a cross sectional view in the lengthwise
25 direction of a motor for a pager of mobile communication apparatus, Fig.46(b) is a traversing cross sectional view of the motor.

 As shown in Fig.46(a), Fig.46(b), a motor of the present embodiment comprises a core 106 and a back yoke 109 facing one
30 another, with a rotor 110 disposed in between.

 It is advantageous for obtaining a good balancing to have two cores 106 disposed symmetrically with respect to rotor 110, like the cases in the fifth through seventh embodiments. In a motor where three salient poles 107a, 107b, 107c are provided,
35 however, it needs the coil 113 for six pieces, consequently twelve terminal ends of coils 113. The amounts of work for winding the

coils and handling the terminal ends are substantial. Therefore, a motor of the present exemplary embodiment comprises one core 106, and one back yoke 109 in place of the other core. Under such a constitution, only three coils are used, hence the number of terminal ends is six. This means a substantial saving of works for winding coils as well as for connecting the terminal ends; which may lead to a cost reduction.

Rotor 110 has been structured in a same arrangement as that of Fig.34; being magnetized in three stages in lengthwise direction, 120a, 120b, 120c, the magnetized position at each stage deviating relative to one another by 120°, and shaft 111 is penetrating through the empty portion of the cylindrical magnetic units 120a - 120c.

The shaft 111 is supported rotatable by bearings 112a, 112b inserted and fixed on brackets 114, 115.

The core 106, back yoke 109 and brackets 114, 115 are fixed respectively on the printed board 116, and the whole is covered with an anti-dust cover 119.

The outer case 90 is shaped to a thin rectangle shape in a cross sectional plane perpendicular to axial direction; one of the longer sides 90b is constituted with a printed board 116, while the remaining three sides, viz. the other longer side 90b and a pair of the shorter sides 90a, 90a are structured by the anti-dust cover 119.

Fig.47(a),(b) show a structure of core 106; Fig.47(a) a side view, Fig.47(b) a traversing cross section. The core 106 has been formed by combining two core components 106a, 106b of the same shape splitted into half by a plane containing the centre axis of motor and the core 106. Each of the core components 106a, 106b may be made either by stacking a plurality of silicon steel sheets or with a single sheet of metal plate.

When forming the core 106 by stacking silicon steel sheets, the efficiency is the highest, in view of the loss due to eddy current in the core, when the steel sheets are stacked in parallel with a plane in which the magnetic flux flows. In a motor having three salient poles 107a - 107c disposed in parallel

to the axial direction, the magnetic flux flows as illustrated by arrows in Fig.47(a); it flows in a radiant direction with respect to the axis within the area of salient poles 107a - 107c, and in a direction parallel to the axis within an area bridging the three
5 salient poles 107a - 107c. Accordingly, a highest efficiency may be obtained in the present embodiment when the steel sheets are stacked in a direction perpendicular to a plane formed by the axis and the core.

A core 106 of the present embodiment has been made with
10 two core components 106a, 106b overlaid together in line with the direction of magnetic flux. This structure presents a higher efficiency because of the smaller loss due to eddy current, as compared with a core formed as one single body.

As the core 106 has been formed by combining two core
15 components 106a, 106b of the same shape splitted into half by a plane containing the axis and the core 106, each of the core components may be made with ease through only bending and cutting a metal sheet, or by pressing. This means that the component may be manufactured with a comparative ease from a silicon steel
20 sheet, etc. which steel is not suitable to undergoing process steps such as contraction, forging.

Fig.48(a),(b),(c) shows structure of the above core 106 and resin insulator 108. The two core components 106a, 106b of core 106 are fixed together to form one single body by a resin
25 molded insulator 108, which at the same time forms an insulation layer for a coiling part of the core 106. On one side of the core 106 facing the printed board 116, a pin 121 is provided to be inserted in and fixed on the printed board 116.

With the above structure, binding of core components
30 106a and 106b and insulating of the core 106 are attained simultaneously; which means saving of assembly works, making it suitable for the production in volume. Further, as the resin molding process has a high degree of freedom in providing various shapes, the resin molded component may be provided with additional
35 shapes and functions.

Furthermore, because the core 106 may be fixed on the

printed board 116 by simply pushing the pin 121 in; which means that correct positioning of the core 106 on printed board 116 is done at the same time.

A motor of the present embodiment is for use in a pager of mobile communication apparatus, or a motor driven by battery. Therefore, it is a strict requirement for the motor that it can start operation without fail at a voltage as low as 1.2 - 3.3V. Among the factors related with the starting voltage of a motor are the loss at shaft, the cogging torque due to mutual attraction between core and magnet, the voltage drop in driving circuits, etc. In a motor of the present embodiment, following countermeasures, among others, have been taken for reducing the cogging torque.

Fig.49 shows relationship among the core 106, the back yoke 109 and the rotor 110. The angle α by salient pole 107a - 107c of core 106 facing the rotor 110 and the angle β by back yoke 109, shown in Fig.49, have a close relationship with cogging torque.

Fig.50 shows a relationship between the angle α and the cogging torque, when the angle α is varied under a condition $\alpha = \beta$. As seen from Fig.50, the cogging torque goes the smallest at two points, at the vicinities of 90° and 150° . Therefore, the cogging torque may be suppressed by setting the angle α at around 90° or 150° . At 90° , however, leakage of magnetic flux increases to a deteriorated magnetic efficiency; so, the angle 150° may produce a better result.

The close relationship of cogging torque with the angle α of salient pole 107a - 107c and the angle β of back yoke of core 106 has been described above. The cogging torque bears a close relationship also with the angles α and β when the α and β taking different values each other.

Fig.51 shows an exemplary case, with the $\alpha + \beta$ fixed while the $\alpha - \beta$ varied. As shown in Fig.51, cogging torque goes the smallest at around $\pm 30^\circ$, $\pm 90^\circ$. At the $\pm 90^\circ$, the magnetic efficiency is poor because of unfavourable balance at both sides. Therefore, the $\pm 30^\circ$ is superior.

In a motor of the present embodiment, a core 106 and a back yoke 109 have been used. In a case where two cores are employed, as in the fifth through seventh embodiments, a same effect may be likewise obtained by setting the difference in the angle between the two cores at $\pm 30^\circ$.

Now in the following, description is made on an imbalancing weight 117, 118.

A motor of the present embodiment is for use in a pager of mobile communication apparatus. In order to pick up a vibration to be generated by motor, weights 117, 118 whose centre of gravity is off the centre of shaft are provided so as the centrifugal force of the weights 117, 118 is transmitted to a stator of motor.

As shown in Fig.52, a rotor 110 is penetrated through by a shaft 111, and imbalancing weights 117, 118 are provided and fixed by calking at around the both ends of the shaft 111, and the weights 117, 118 are glued to the ends of the rotor 110.

Fig.53(a),(b) shows a relationship with the location of the centre of gravity of imbalancing weight 117(118) relative to bearings 112a, 112b. Fig.53(a) shows a case where the gravity centre G of imbalancing weight 117(118) is located at a point outside the region between the two bearings 112a, 112b, Fig.53(b) is a case where the gravity centre G of imbalancing weight 117(118) is located at a point between the two bearings 112a, 112b. Respective loads F_6 , F_7 by the centrifugal force F to be exerted on bearings 112a, 112b are obtainable through Formula 37: where; L_1 representing the distance between the two bearings 112a and 112b, L_2 is the axial direction from one bearing 112a to gravity centre G of weight assuming a direction towards the other bearing 112b as positive.

$$\begin{aligned} F_6 &= ((L_1 - L_2) / L_1) \cdot F \\ F_7 &= (L_2 / L_1) \cdot F \dots\dots\dots (37) \end{aligned}$$

When the gravity centre G of imbalancing weight 117(118) is placed outside of the bearings 112a, 112b, as shown in

Fig.53(a), the load F_7 turns out to be negative. This means that the direction of load is reversed.

Loss torque T_r at bearing is generally approximated in Formula 38, with a symbol f denotes a load.

5

$$T_r = T_c + k f \quad \dots\dots (38)$$

where, T_c representing a constant element independent of a load, k is a proportional constant.

10

Accordingly, the sum of loss torques at two bearings is expressed in Formula 39:

$$T_r = T_c + k (| F_6 | + | F_7 |) \quad \dots\dots (39)$$

15

Fig.54 shows a relationship of loss torque T_r with L_1 , L_2 .

As seen from Fig.54, the loss torque T_r is small when L_2 is between 0 and L_1 , viz. when the gravity centre of imbalancing weight 117(118) is placed somewhere between the two bearings 112a and 112b.

20

Taking the mechanical life of bearings into consideration, the respective loads F_6 , F_7 are preferred to be as small as possible. Both of the loads F_6 , F_7 become small when the gravity centre G of imbalancing weight 117(118) is placed at a place in fulfillment of Formula 40, viz. at the middle of the two bearings 112a and 112b. This state may be advantageous in terms of mechanical life of the bearing.

25

$$L_2 = L_1 / 2 \quad \dots\dots(40)$$

30

In Fig.53, the place of a gravity centre of imbalancing weight 117(118) has been contemplated. In a motor having two or more of imbalancing weights, as in the present embodiment, the same principle applies by assuming a centre of gravity G for the whole imbalancing weights 117(118). In a motor of the present embodiment, the centre of gravity G of the whole imbalancing

35

weights 117(118) is placed at the middle of the two bearings 112a and 112b, which means that the motor is advantageous in terms of both the bearing loss and the mechanical life.

In order to further reduce the bearing loss, it is effective to make the diameter of shaft 111 smaller. However, with a shaft of reduced diameter flexion of the shaft 111 becomes unignorable, and a problem of hitting by rotor might arise.

Fig.55(a),(b) shows the load on shaft 111 caused by the imbalancing weight 117(118). Fig.55(a) illustrates a case of one imbalancing weight 117(118), Fig.55(b) is a case of two imbalancing weights 117, 118.

Assuming the shaft 111 as a rigid body, the Fig.55(a) and the Fig.55(b) are totally identical. But, when a flexion of shaft 111 is taken into consideration, a slightly different situation is created.

The flexion δ of shaft 111 when one imbalancing weight 117(118) is used (Fig.55(a)) is represented by Formula 41:

$$\delta = F L^3 / 48 E I \dots\dots (41)$$

where, E representing the lengthwise elasticity coefficient of shaft, I is the cross sectional secondary momentum of shaft.

Likewise, the flexion δ of shaft 111 when two imbalancing weights 117 and 118 are used (Fig.55(b)) is represented by Formula 42: where, the axial distance from bearing 112a, 112b to imbalancing weight 117, 118 of the same end is designated as L3 assuming the direction towards the other bearing 112b, 112a as positive.

$$\delta = (F L^3 (L1 - L3)^2) / 3L1 EI \dots\dots (42)$$

Fig.56 shows a relationship between flexion δ and L3. In Fig.56, flexion of shaft 111 having one weight is shown in dotted line for the sake of comparison.

As seen from Fig.56, the flexion δ becomes 0 when L3 is 0. Such may be ideal, but it is unimplementable because of the existence of bearings 112a and 112b. In practice, the flexion δ may be made the smallest by placing the

imbalancing weights 117, 118 as close to bearings 112a, 112b as possible.

In a motor of the present embodiment, the imbalancing weights 117, 118 are attached at both ends of rotor 110. By so doing, the flexion δ of shaft 111 is made to be minimum, which makes it possible to use a thinner
5 shaft 111 for a reduced bearing loss.

As described above, a motor of the present embodiment uses a thin shaft 111 in order to reduce the loss at shaft. A thin shaft, however, creates a problem that the joining strength with the imbalancing weights 117, 118 and rotor 110 is inferior as compared to a case with thick shaft.

10 The relationship among pulling strength F_n , rotation torque T_n and shaft diameter d is represented by Formula 43, taking the fixing by calking, the fixing by pressurized insertion as examples representing commonly used methods of joining/fixing.

$$\begin{aligned} 15 \quad F_n &\propto d \\ T_n &\propto d^2 \dots (43) \end{aligned}$$

It is difficult to secure a thin shaft with a sufficient revolution torque T_n , among other items.

In most cases, a rotor 110 has a weaker mechanical
20 strength than that of metal; which makes it further difficult to secure the enough strength.

In order to encounter the above problems, a shaft 111 in a motor of the present embodiment is penetrating through the rotor 110, the pulling strength F_n of shaft 111 relative to rotor 110 is
25 secured by fixing and calking the imbalancing weights 117, 118 on the shaft 111 at both ends of rotor 110; in addition, the imbalancing weights 117, 118 are glued to the rotor 110 at both ends to insure the revolution torque T_n of rotor 110 relative to weights 117, 118.

30 Because the motor of present embodiment is for use as a vibration motor in a pager of mobile communication apparatus, it is not required to have a shaft extruding outside for output; what is essential for the motor is to have a sufficient pulling strength F_n with shaft 111 relative to rotor 110 and a sufficient
35 rotation torque T_n relative to imbalancing weights 117, 118. Under a structure of the present embodiment, the rotor 110 has

been provided with the minimum required pulling strength F_n relative to shaft 111, as well as revolution torque T_n relative to imbalancing weights 117, 118. The structure may be suitable to a motor for use in a pager.

5 Although a motor in accordance with the present embodiment is comprised of a core 106 and a back yoke forming a pair, the motor may be constituted with core 106 alone.

 The above described fifth embodiment through eighth embodiment have been described referring to a brushless motor for
10 generating vibration, which type of motors are superior to brush motors in terms of the reliability. The invented motors may be incorporated in portable pagers, portable telephones, etc. for generating vibrations to be transmitted to human body, in which application a high reliability in the operation is required.

15 The present invention may be embodied also in a conventional brush motor. Namely, a brush motor for generating vibration may be constituted by providing a brush and a rectifier for distributing a DC current to coils so as to set the phase of induced voltage generated on the salient pole wound around with
20 coil in each stage to a phase suitable for rotating a magnetic unit corresponding to a coil in that stage.

 Although description has been made on a brushless motor for generating a vibration in the above described fifth embodiment through eighth embodiment, the invention may of course be embodied
25 in a brushless motor without having the imbalancing weight.

 A motor in accordance with a ninth exemplary embodiment of the invention is described in the following referring to Fig.57.

30 The descriptions in the above embodiments are related to the brushless motors. The following is an embodiment of the invention in a brush motor.

 As shown in Fig.57, magnets 122a - 122c, core 123, salient poles 124a - 124c, and coils 125a - 125c are disposed in a
35 same arrangement as in the second embodiment shown in Fig.11. A brush 126 and a rectifier 127 are additionally provided to

distribute a DC current to each of the coils 125a - 125c so as to set the phase of induced voltage generated on the salient poles 124a - 124c in each stage deviates relative to one another by 120 .

5 The brush 126 has been used for three pieces, and respective brushes are positioned not to take a same rotational positioning as the rectifier in a circumferential direction. This makes it easy to distribute the electricity in each of the phases. Thus a small and thin brush motor may be presented in accordance
10 with the present invention.

INDUSTRIAL APPLICABILITY


As described in the above, a motor in accordance with the present invention comprises a rotor comprised of K pieces of
15 (K indicating any integer greater than one) magnetic units having the N and S poles magnetized alternately, a rotating shaft around which the magnetic units are stacked axially in K stages and fixed as a single body, a core having K pieces of salient poles wound around with coil corresponding to respective magnetic units, and a
20 pair of bearings for supporting the rotor rotatable; in which the magnetized position of the N and S poles of the magnetic unit at each stage deviates relative to one another in a circumferential direction so as to set the phase of induced voltage generated on the salient pole wound around with the coil in each stage to a
25 phase suitable for rotating a magnetic unit corresponding to a coil in that stage. With such a structure of the present invention, the magnetized poles of rotor, as well as the salient poles of core each wound around with coil, may be disposed splitted on planes of K stages which are perpendicular to axial
30 direction. Thus the invention enables to present a motor that has advantages in making the efficiency higher, the overall dimensions smaller and thinner, and in providing more freedom in the installation in an apparatus.

A motor in accordance with the present invention
35 comprises a rotor comprised of magnetic units stacked in K stages (K indicating any integer greater than one) the magnetized

position of the N and S poles at each stage deviating relative to one another in a circumferential direction, a core having K pieces of salient poles wound around with coil corresponding to the magnetic units disposed on a straight line that is in parallel
5 with axial direction of the rotor, a pair of bearings for supporting the rotor rotatable, and an outer case having an oblong shape in an axially perpendicular cross section consisting of a pair of long sides facing to each other and a pair of short sides facing to each other, in which the rotor is penetrating through
10 the outer case at the central part and a core is disposed in at least one of the short sides. With such a structure of the present invention, the magnetized poles of magnetic units, as well as the salient poles of core each wound around with coil, may be disposed splitted in K stages in a direction parallel to axial
15 direction of the rotor, and the salient poles wound around with coil may be provided in only the short side of the outer case. Thus the invention enables to reduce dimension of the short side to a length almost equal to outer diameter of the rotor. The invention also makes it easier to increase the number of turns of
20 the coil to be wound around the salient poles. Thus, the efficiency of a motor may be improved. Further, because it is a brushless motor a higher reliability may be expected, so a highly reliable and efficient motor may be presented in a thin configuration.

25 A motor in accordance with the present invention comprises a rotor comprised of magnetic units stacked in K stages (K indicating any integer greater than one) the magnetized position of the N and S poles at each stage deviating relative to one another in a circumferential direction, a core having K pieces
30 of salient poles wound around with coil corresponding to the magnetic units, a pair of bearings for supporting the rotor rotatable, an outer case having an oblong shape in an axially perpendicular cross section consisting of a pair of long sides facing to each other and a pair of short sides facing to each
35 other, and an imbalancing weight rotating together with the rotor for generating vibration as a result of rotation of the rotor.

With such a structure of the present invention, the magnetized poles of magnetic units, as well as the salient poles of core each wound around with coil, may be disposed splitted in K stages in the axial direction of rotor. This enables to reduce the cross sectional square measure of outer case, and makes it easy to
5 assume a desired cross sectional shape inclusive of a thin shape. Furthermore, it becomes easier to increase the number of turns of the coil to be wound around salient poles for an improved efficiency of a motor. Thus the invention offers a highly
10 efficient motor for generating vibration, whose outer case having a high degree of freedom in assuming a desired cross sectional shape in a reduced square measure.



CLAIMS

1. A motor comprising

a rotor comprised of K pieces of (K indicating any integer greater than one) magnetic units having the N and S poles magnetized alternately,

a rotating shaft around which the magnetic units are stacked axially in K stages to be fixed as a single body,

a core having salient poles wound around with coil for K stages corresponding to respective magnetic units, and

a pair of bearings for supporting the rotor rotatable; wherein

the magnetized position of the N and S poles of the magnetic unit at each stage deviates relative to one another in a circumferential direction so as to set the phase of induced voltage generated on the salient pole wound around with the coil in each stage to a phase suitable for rotating a magnetic unit corresponding to a coil in that stage.

2. A motor comprising

a rotor comprised of magnetic units stacked in K stages (K indicating any integer greater than one) the magnetized position of the N and S poles at each stage deviating relative to one another in a circumferential direction,

a core having K pieces of salient poles wound around with coil corresponding to the magnetic units disposed on a straight line that is in parallel with axial direction of the rotor,

a pair of bearings for supporting the rotor rotatable, and

an outer case having an oblong cross sectional shape in a plane perpendicular to axial direction of the rotor consisting of a pair of long sides facing to each other and a pair of short sides facing to each other; wherein

the rotor is penetrating through the outer case at the central part and a core is disposed in at least one of the short sides of the outer case.





3. A motor for generating a vibration, comprising
a rotor comprised of magnetic units stacked in K stages
(K indicating any integer greater than one) the magnetized
position of the N and S poles at each stage deviating relative to
5 one another in a circumferential direction,

a core having salient poles wound around with coil for K
stages corresponding to respective magnetic units,

a pair of bearings for supporting the rotor rotatable,
an outer case having an oblong cross sectional shape in
10 a plane perpendicular to axial direction of the rotor consisting
of a pair of long sides facing to each other and a pair of short
sides facing to each other, and

an imbalancing weight rotating together with the rotor;
wherein

15 a vibration is generated as a result of rotation of the
rotor.

4. The motor of claim 1, wherein

a core having salient poles at each stage wound around
with coil is provided splitted, a rotor formed in a splitted
20 manner and said core are combined to form a unit for each stage,
and magnetic units for each stage fixed around a rotating shaft
are assembled together in correspondence to respective stages with
the core.

5. The motor of either one claim among claims 1 through 3,
25 wherein a rotor magnet is made of a single magnetic body, being
magnetized in the N and S poles at respective stages in an
arrangement deviating relative to one another.

6. The motor of either one claim among claims 1 through 3,
wherein a rotor magnet is made of a single magnetic body, being
30 magnetized in the N and S poles in a skew arrangement.

7. The motor of either one claim among claims 1 through 6,
wherein the salient pole of respective stages wound around with
coil are disposed on a straight line running in parallel with the
rotating shaft.

35 8. The motor of either claim 2 or claim 3, wherein the core
is provided in only one of the short sides of outer case.





9. The motor of either claim 2 or claim 3, wherein the core is provided in each of the short sides of outer case.

10. The motor of either claim 2 or claim 3, wherein the core is provided in one of the short sides of outer case and a back
5 yoke is provided in the other short side of outer case.

11. The motor of either one claim among claims 1 through 6, wherein the position of salient poles wound around with coil at each stage deviates relative to one another in a circumferential direction.

10 12. The motor of either one claim among claims 1 through 6, wherein the core is provided with a flat portion in the outer circumference.

13. The motor of either one claim among claims 1 through 3, wherein the surface of salient pole facing a rotor is curved with
15 a radius index centred at the axis of rotor.

14. The motor of either one claim among claims 1 through 3, wherein the surface of salient pole facing a rotor is curved with a radius index centred at a point away from the axis of rotor.

15. The motor of either claim 2 or claim 3, wherein the outer
20 case has a rectangular cross sectional shape.

16. The motor of either one claim among claims 2, 3 and 15, wherein the outer case has dimensions the length of a short side of which is shorter than $1/2$ of a long side.


17. The motor of either one claim among claims 1 through 3,
25 wherein a core is comprised of a yoke and K pieces of salient poles coupled to the yoke.

18. The motor of claim 17, wherein the salient pole is formed by a forging process.

19. The motor of either one claim among claims 1 through 3,
30 wherein the salient pole is provided with a molded insulation resin in a portion to be wound around with coil, and the coil is insulated from the salient pole by the molded resin.

20. The motor of claim 2, wherein the surface of salient pole facing a rotor magnet has a circumferential angle either $150^\circ \pm 5^\circ$, or
35 $90^\circ \pm 5^\circ$ in terms of electrical effects.





21. The motor of claim 2, wherein the circumferential angle of the surface of salient pole facing a rotor is different between the right and the left of a pair of cores within a range $30^\circ \pm 5^\circ$ in terms of electrical effects.

5 22. The motor of claim 10, wherein the circumferential angle of the surface of salient pole of a core facing a rotor is different from that of a back yoke facing a rotor magnet within a range $30^\circ \pm 5^\circ$ in terms of electrical effects.

23. The motor of claim 3, wherein an imbalancing weight is
10 provided on the shaft at a place outside the region between a pair of bearings.

24. The motor of claim 3, wherein an imbalancing weight is provided on the shaft at a place between a pair of bearings.

25. The motor of claim 3, wherein the diameter D of the
15 largest outer circumference of an imbalancing weight, or a bearing bush functioning also as an imbalancing weight, and the dimension a of the shorter side of outer case establish a relationship $0.6a < D < a$.

26. The motor of claim 3, wherein the diameter D of the
20 largest outer circumference of an imbalancing weight, or a bearing bush functioning also as an imbalancing weight, and the diameter Dm of magnetic unit of rotor establish a relationship $0.8Dm < D < 1.1Dm$.

27. The motor of either one claim among claims 1 through 3,
25 wherein one of the bearings is formed with a thrust bearing section and a radial bearing section, and an end of the shaft contacting said thrust bearing section is spherical.


28. The motor of claim 27, wherein the radial bearing section
is made with an oil-containing sintered bearing material mixed
30 with fluoric resin.

29. The motor of claim 27, wherein the thrust bearing section is constituted with a thrust plate made of a high polymer compound.

30. The motor of claim 27, wherein the radius index r of shaft
35 end and the diameter d of shaft establish a relationship $10d > r > 1.5d/2$.



This Sheet Has Been Replaced



31. The motor of claim 27 for generating a vibration, wherein the outer dimension D_s of the thrust plate constituting the thrust bearing and the diameter d of shaft establish a relationship $D_s > d$.

32. The motor of either one claim among claims 1 through 3, wherein the bearing is formed with a bracket made of a low-friction resin.

33. The motor of either one claim among claims 1 through 3, wherein a hole for bearing is formed in a bracket constituting an end of the outer case, a bearing being formed by a circumferential edge of the hole for bearing that has been made thinner for supporting a shaft penetrating through the hole.

34. The motor of either one claim among claims 1 through 33, wherein $K = 3$.

35. The motor of either claim 2 or claim 3, wherein terminal end of the coil wound around salient pole is electrically connected on a printed board, the printed board constituting at least one of the sides of outer case, and elements of driving circuit are mounted on the printed board.

36. The motor of either claim 3 or claim 8, wherein a flexible printed board is provided for continuously covering the three sides of outer case, viz. a pair of shorter sides and one of the longer sides.

37. The motor of claim 35, wherein each salient pole is provided with a terminal board of molded resin made with a metal piece integrated to form a single body which is attached and fixed thereon, said metal piece and the printed board are electrically coupled under a state where terminal end of the coil wound around tooth portion of salient pole is being connected to said metal piece.

38. The motor of claim 37, wherein the terminal end of coil is connected with the metal piece by thermal compression.

39. The motor of either claim 37 or claim 38, wherein the metal piece is connected with the printed board by thermal



* C L M S *



compression.

40. The motor of either one claim among claims 1 through 3, wherein the tooth portion of salient pole to be wound around with coil has a rectangular shape in the cross section, a side parallel
5 to the axis of magnetic units having a length greater than that of the other side which is perpendicular to the former side.

41. The motor of either one claim among claims 1 through 40, further comprising an electronic circuit for controlling a DC current so as to provide the coil with electricity setting the
10 phase of induced voltage generated on the salient pole wound around with the coil in each stage to a phase suitable for rotating a magnetic unit in that stage, thus the motor operating as a brushless motor.

42. The motor of either one claim among claims 1, 3, 4 through
15 19, and 23 through 40, further comprising a brush and a rectifier for distributing a DC current to as to provide the coil with electricity setting the phase of induced voltage generated on the salient pole wound around with the coil in each stage to a phase suitable for rotating a magnetic unit in that stage, thus the
20 motor operating as a brush motor.

43. The motor of either claim 1, 2, 3, 41 or 42, wherein $K = 3$, comprising three pieces of magnetic units each having the N and S poles magnetized alternately in a circumferential direction for $2n$ poles (n indicating any integer not smaller than 1) at an
25 equal angular pitch, three stages of salient poles wound around with coil for $2m$ poles (m indicating any integer not smaller than 1, $m \leq n$) corresponding to each of the N and S poles of the magnetic units at each stage in m poles, wherein

the magnetized position of the magnetic poles of the
30 magnetic unit at each stage deviates relative to one another in a circumferential direction by $120/n$ degrees or $60/n$ degrees so as the phase of induced voltage generated on the three stages of salient poles wound around with the coil deviates relative to one another by 120 degrees.

35 44. A motor comprising
three magnetic units each splitted into two in a





circumferential direction and magnetized in the N and S poles,
a rotating shaft around which the three magnetic units
are stacked axially in three stages and fixed to form a single
body, and

5 a core having salient poles for three stages wound
around with coil corresponding to respective magnetic units,
wherein

the magnetized position of the N and S poles of the
magnetic unit at each stage deviates relative to one another in a
10 circumferential direction by 120 degrees so as the phase of
induced voltage generated on the salient poles wound around with
coil at each stage deviates relative to one another by 120
degrees.

45. A portable pager incorporating a motor, which motor
15 comprising

a rotor comprised of magnetic units stacked in K stages
(K indicating any integer greater than one) the magnetized
position of the N and S poles at each stage deviating relative to
one another in a circumferential direction,

20 a core having salient poles wound around with coil in K
stages corresponding to the magnetic units, and

an imbalancing weight which rotates with the rotor;
wherein

a vibration is generated as a result of rotation of the
25 motor.

46. A portable telephone unit incorporating a motor, which
motor comprising

a rotor comprised of magnetic units stacked in K stages
(K indicating any integer greater than one) the magnetized
30 position of the N and S poles at each stage deviating relative to
one another in a circumferential direction,

a core having salient poles wound around with coil in K
stages corresponding to the magnetic units, and

an imbalancing weight which rotates with the rotor;
35 wherein

a vibration is generated as a result of rotation of the



THIS SHEET HAS BEEN
REPLACED

motor.

This Sheet Has Been Replaced



* C L M S *

ABSTRACT

A small motor for use in an information-communication apparatus, an audio-visual apparatus or the like, and a motor for use in a portable pager and a portable telephone or the like for generating vibrations to be transmitted to a human body, the motors being efficient, small and thin in size, and having a high degree of freedom when mounted on an apparatus. To realize the motor as described above, K pieces of (K indicating any integer greater than one) magnetic units (4a, 4b, 4c) having N and S poles magnetized alternately are mounted on a rotor in a circumferential direction, and K magnetic units are axially stacked in K stages and integrally retained on a shaft (6), and this rotor is rotatably supported on a pair of bearings (9a, 9b). Cores (1a, 1b, 1c) each have a salient pole (7a, 7b, 7c) wound around with coils (3a, 3b, 3c) in K stages so as to correspond to each of the magnetic units. The magnetized position of the N and S poles of the magnetic unit at each stage deviates relative to one another in a circumferential direction so as to set the phase of induced voltage generated on the salient pole wound around with the coil in each stage to a phase suitable for rotating a magnet unit corresponding to a coil in that stage.

This Sheet Has Been Replaced





Fig.1

1/64

(a)



(b)




Fig.2

2/64




Fig.3

3/62




Fig.4

4/64






Fig.5

5/64

(a)



(b)



6164

Fig.6




Fig.7

7/64




Fig.8





Fig.9

9/64



10159






Fig.1 1

11/64



12/64

Fig.12





Fig.13


13/64



14/64

Fig.14

— Va
- - - Vb
- - - Vc



16/64

Fig.16




Fig.15






Fig.17

17/64



18/64

Fig.18




Fig.19

19/64




Fig.20

20/64





Fig.21

21/64





Fig.22

22/64



23/64

Fig.23




Fig.24

24/64




Fig.25

25/64




Fig.26





Fig.27

26/64

(a)



(b)




Fig.28

27/64




Fig.29




Fig.30




Fig.31

29/64






Fig.32

30/69



21/69

(a)



32/64

Fig.34




Fig.35

33/64




Fig.36

34/64




Fig.37

35/64




Fig.38




Fig.39




Fig.40





Fig.41

38/64

(a)



(b)




Fig.42




Fig.43

40/64





Fig.44



41/64

Fig.45





Fig.46

42/64 (a)



(b)





Fig.47

43/64

(a)



(b)




Fig.48




Fig.49

45/64





Fig.50



46/64

Fig.51






Fig.52

47/64



48/64

Fig. 53






Fig.54

49164



50/64

Fig.55



51/64

Fig.56





Fig.57



53/64

Fig.58






Fig.59

54/64



55/64

Fig.60




Fig.61

56/64







Fig.62

5/7/64

(a)



(b)



EXPLANATION OF MARKS

1a, 1b, 1c	Core
1p	Flat portion in the outer circumference
2a, 2b, 2c	Insulator
3a, 3b, 3c	Coil
4a, 4b, 4c	Magnetic unit
5	Spacer
6	Shaft
7a, 7b, 7c	Salient pole
8	Bracket
9a, 9b	Bearing
10	Frame case
11	Board
12	Terminal pin
13	Flat portion
14a, 14b, 14c	Magnetic unit
15a, 15b, 15c	Core
16a, 16b, 16c	Salient pole
17a, 17b, 17c	Coil
18a, 18b, 18c	Salient pole
19	Core
20a, 20b, 20c	Coil
21a, 21b, 21c	Magnetic unit
22	Spacer
23	Shaft
24	Frame

25	Bearing
26	Board
27	Cover
28a, 28b, 28c	Salient pole
29	Core
30a, 30b, 30c	Coil
31a, 31b, 31c	Magnetic unit
32	Rotor magnet
33	Shaft
34	Rotor magnet
35a, 35b, 35c	Salient pole
36a, 36b, 36c	Salient pole
37	Rotor
38a, 38b, 38c	Magnetic unit
39	Shaft
40	Bearing
40a	Circular arc
41	Bearing
41a	Circular arc
42	Coil
43a, 43b, 43c	Coil
44a, 44b	Spacer
45	Weight
46	Thrust plate
47	Yoke
48	Yoke

49	Bracket
50	Bracket
51	Printed board
51a	Land
52	Integrated circuit
53	Sheet
54	First core
55	Second core
56	Salient pole
57	Protruded portion
57a	Surface
57b	Surface
58	Tooth
59	Cylindrical portion
60	Salient pole
61	Protruded portion
61a	Surface
61b	Surface
62	Tooth
63	Cylindrical portion
64	Salient pole
65	Protruded portion
65a	Surface
65b	Surface
66	Tooth
67	Cylindrical portion

68	Plate
69	Flexible printed board
70	Bracket
70a	Bearing portion
71	Bracket
71a	Bearing portion
72	Terminal board
73	Rotor
74a, 74b, 74c	Magnetic unit
75	Hollow
76	Protrusion
77a, 77b, 77c	Magnetic unit
78a, 78b	Spacer
79	Protrusion
80	Hollow
81	Low-friction coating material
82	Integrated circuits
83	Salient pole
84	Protruding portion
84a, 84b	Surface
85	Rotor axis
86	Tooth portion
87	Joint portion
88	Coil
89	Metal plate
90	Outer case

90a	Shorter side
90b	Longer side
91	Rotor magnet
92	Bearing bracket
92a	Bearing pin
93	Bearing bracket
93a	Bearing pin
94	Flexible printed board
95	Ring portion
96	Bearing bush
96a	Crescent portion
96b	Bearing hole
97	Bearing bush
97a	Crescent portion
97b	Bearing hole
98	Metal piece
99	Terminal board
100	Protruding portion
101	Cylindrical portion
102	Hole
103	Integrated circuits
104	Land
105	Sheet
106	Core
106a, 106b	Core component
107a, 107b, 107c	Salient pole

108	Resin insulator
109	Back yoke
110	Rotor
111	Shaft
112a, 112b	Bearing
113	Coil
114	Bracket
115	Bracket
116	Printed board
117	Imbalancing weight
118	Imbalancing weight
119	Anti-dust cover
120a, 120b, 120c	Magnetic unit
121	Pin
122a, 122b, 122c	Magnetic unit
123	Core
124a, 124b, 124c	Salient pole
125a, 125b, 125c	Coil
126	Brush
127	Rectifier
128	Core of cylindrical shape
129	Coil
130	Magnet
131	Shaft
132	Frame case
133	Bearing

134	Bearing
135	Circuit board
136	Bracket
137	Frame case
138	Magnet
139	Shaft
140	Sintered bearing
141	Sintered bearing
142	Core
143	Coil
144	Rectifying terminal unit
145	Rectifier
146	Brush
147	Bracket
148	Weight
149	Shaft
150	Rectifier
151	Group of coils
152	Magnet of empty-cylindrical shape
153	Housing
154	Frame case
155	Bearing
156	Brush assembly
157	Weight

CLAIMS



1.(amended) A motor comprising
a rotor comprised of K pieces of (K indicating any
5 integer greater than one) magnetic units having the N and S poles
magnetized alternately,

a rotating shaft around which the magnetic units are
stacked axially in K stages to be fixed as a single body,

a core having salient poles wound around with coil for
10 K stages corresponding to respective magnetic units, and
a pair of bearings for supporting the rotor rotatable;
wherein

the magnetized position of the N and S poles of the
magnetic unit at each stage deviates relative to one another
15 in a circumferential direction, the phase of induced voltage
generated on the coil in each of the stages differs relative
to one another and is assigned to respective multiple phases,
thereby a motor is driven by the multiple phases.

2.(amended) A motor comprising
20 a rotor comprised of magnetic units stacked in K stages
(K indicating any integer greater than one) the magnetized
position of the N and S poles at each stage deviating relative
to one another in a circumferential direction,

a core having K pieces of salient poles wound around
25 with coil corresponding to the magnetic units disposed on a
straight line that is in parallel with axial direction of the
rotor,

a pair of bearings for supporting the rotor rotatable,
and

30 an outer case having an oblong cross sectional shape
in a plane perpendicular to axial direction of the rotor
consisting of a pair of long sides facing to each other and a
pair of short sides facing to each other; wherein

the rotor is penetrating through the outer case at the
35 central part and a core is disposed in at least one of the short
sides of the outer case, the phase of induced voltage generated

This Sheet Has Been Replaced





on the coil in each of the stages differs relative to one another and is assigned to respective multiple phases, thereby a motor is driven by the multiple phases.

3.(amended) The motor of claim 2, further comprising an
5 imbalancing weight that rotates together with the rotor, wherein

a vibration is generated as a result of rotation of the rotor.

4. The motor of claim 1, wherein
10 a core having salient poles at each stage wound around with coil is provided splitted, a rotor formed in a splitted manner and said core are combined to form a unit for each stage, and magnetic units for each stage fixed around a rotating shaft are assembled together in correspondence to respective stages
15 with the core.

5. The motor of either one claim among claims 1 through 3, wherein a rotor magnet is made of a single magnetic body, being magnetized in the N and S poles at respective stages in an arrangement deviating relative to one another.

20 6. The motor of either one claim among claims 1 through 3, wherein a rotor magnet is made of a single magnetic body, being magnetized in the N and S poles in a skew arrangement.

7. The motor of either one claim among claims 1 through 6, wherein the salient pole of respective stages wound around with
25 coil are disposed on a straight line running in parallel with the rotating shaft.

8. The motor of either claim 2 or claim 3, wherein the core is provided in only one of the short sides of outer case.

9. The motor of either claim 2 or claim 3, wherein the core
30 is provided in each of the short sides of outer case.

10. The motor of either claim 2 or claim 3, wherein the core is provided in one of the short sides of outer case and a back yoke is provided in the other short side of outer case.

11. The motor of either one claim among claims 1 through
35 6, wherein the position of salient poles wound around with coil at each stage deviates relative to one another in a

This Sheet Has Been Replaced





circumferential direction.

12. The motor of either one claim among claims 1 through 6, wherein the core is provided with a flat portion in the outer circumference.

5 13. The motor of either one claim among claims 1 through 3, wherein the surface of salient pole facing a rotor is curved with a radius index centred at the axis of rotor.

14. The motor of either one claim among claims 1 through 3, wherein the surface of salient pole facing a rotor is curved
10 with a radius index centred at a point away from the axis of rotor.

15. The motor of either claim 2 or claim 3, wherein the outer case has a rectangular cross sectional shape.

16. The motor of either one claim among claims 2, 3 and 15,
15 wherein the outer case has dimensions the length of a short side of which is shorter than $1/2$ of a long side.

17. The motor of either one claim among claims 1 through 3, wherein a core is comprised of a yoke and K pieces of salient poles coupled to the yoke.

20 18. The motor of claim 17, wherein the salient pole is formed by a forging process.


19. The motor of either one claim among claims 1 through 3, wherein the salient pole is provided with a molded insulation resin in a portion to be wound around with coil, and the coil
25 is insulated from the salient pole by the molded resin.

20. The motor of claim 2, wherein the surface of salient pole facing a rotor magnet has a circumferential angle either $150^\circ \pm 5^\circ$, or $90^\circ \pm 5^\circ$ in terms of electrical effects.

21. The motor of claim 2, wherein the circumferential angle
30 of the surface of salient pole facing a rotor is different between the right and the left of a pair of cores within a range $30^\circ \pm 5^\circ$ in terms of electrical effects.

22. The motor of claim 10, wherein the circumferential angle of the surface of salient pole of a core facing a rotor is
35 different from that of a back yoke facing a rotor magnet within a range $30^\circ \pm 5^\circ$ in terms of electrical effects.

This Sheet Has Been Replaced





23. The motor of claim 3, wherein an imbalancing weight is provided on the shaft at a place outside the region between a pair of bearings.

24. The motor of claim 3, wherein an imbalancing weight is provided on the shaft at a place between a pair of bearings.

25. The motor of claim 3, wherein the diameter D of the largest outer circumference of an imbalancing weight, or a bearing bush functioning also as an imbalancing weight, and the dimension a of the shorter side of outer case establish a relationship $0.6a < D < a$.

26. The motor of claim 3, wherein the diameter D of the largest outer circumference of an imbalancing weight, or a bearing bush functioning also as an imbalancing weight, and the diameter Dm of magnetic unit of rotor establish a relationship $0.8Dm < D < 1.1Dm$.

27. The motor of either one claim among claims 1 through 3, wherein one of the bearings is formed with a thrust bearing section and a radial bearing section, and an end of the shaft contacting said thrust bearing section is spherical.

28. The motor of claim 27, wherein the radial bearing section is made with an oil-containing sintered bearing material mixed with fluorine resin.

29. The motor of claim 27, wherein the thrust bearing section is constituted with a thrust plate made of a high polymer compound.

30. The motor of claim 27, wherein the radius index r of shaft end and the diameter d of shaft establish a relationship $10d > r > 1.5d/2$.

31. The motor of claim 27 for generating a vibration, wherein the outer dimension Ds of the thrust plate constituting the thrust bearing and the diameter d of shaft establish a relationship $Ds > d$.

32. The motor of either one claim among claims 1 through 3, wherein the bearing is formed with a bracket made of a low-friction resin.

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED



33. The motor of either one claim among claims 1 through 3, wherein a hole for bearing is formed in a bracket constituting an end of the outer case, a bearing being formed by a circumferential edge of the hole for bearing that has been made thinner for supporting a shaft penetrating through the hole.

34.(deleted)

35. The motor of either claim 2 or claim 3, wherein terminal end of the coil wound around salient pole is electrically connected on a printed board, the printed board constituting at least one of the sides of outer case, and elements of driving circuit are mounted on the printed board.

36.(amended) The motor of either claim 2 or claim 3, wherein a flexible printed board is provided for continuously covering the three sides of outer case, viz. a pair of shorter sides and one of the longer sides.

37. The motor of claim 35, wherein each salient pole is provided with a terminal board of molded resin made with a metal piece integrated to form a single body which is attached and fixed thereon, said metal piece and the printed board are electrically coupled under a state where terminal end of the coil wound around tooth portion of salient pole is being connected to said metal piece.

38. The motor of claim 37, wherein the terminal end of coil is connected with the metal piece by thermal compression.

39. The motor of either claim 37 or claim 38, wherein the metal piece is connected with the printed board by thermal compression.

40. The motor of either one claim among claims 1 through 3, wherein the tooth portion of salient pole to be wound around with coil has a rectangular shape in the cross section, a side parallel to the axis of magnetic units having a length greater than that of the other side which is perpendicular to the former side.

41. The motor of either one claim among claims 1 through 40, further comprising an electronic circuit for controlling a DC current so as to provide the coil with electricity setting



This Sheet Has Been Replaced





the phase of induced voltage generated on the salient pole wound around with the coil in each stage to a phase suitable for rotating a magnetic unit in that stage, thus the motor operating as a brushless motor.

5 42. The motor of either one claim among claims 1, 3, 4 through 19, and 23 through 40, further comprising a brush and a rectifier for distributing a DC current to as to provide the coil with electricity setting the phase of induced voltage generated on the salient pole wound around with the coil in each stage to
10 a phase suitable for rotating a magnetic unit in that stage, thus the motor operating as a brush motor.

43. The motor of either claim 1, 2, 3, 41 or 42, wherein $K = 3$, comprising three pieces of magnetic units each having the N and S poles magnetized alternately in a circumferential
15 direction for $2n$ poles (n indicating any integer not smaller than 1) at an equal angular pitch, three stages of salient poles wound around with coil for $2m$ poles (m indicating any integer not smaller than 1, $m \leq n$) corresponding to each of the N and S poles of the magnetic units at each stage in m poles, wherein
20 the magnetized position of the magnetic poles of the magnetic unit at each stage deviates relative to one another in a circumferential direction by $120/n$ degrees or $60/n$ degrees so as the phase of induced voltage generated on the three stages of salient poles wound around with the coil deviates relative
25 to one another by 120 degrees.

44. (deleted)

45. (amended) A portable pager incorporating a motor, which motor comprising

30 a rotor comprised of magnetic units stacked in K stages (K indicating any integer greater than one) the magnetized position of the N and S poles at each stage deviating relative to one another in a circumferential direction,

 a core having salient poles wound around with coil in
35 K stages corresponding to the magnetic units, and
 an imbalancing weight which rotates with the rotor,

This Sheet Has Been Replaced



wherein

the phase of induced voltage generated on the coil in each of the stages differs relative to one another and is assigned to respective multiple phases, thereby a motor is
5 driven by the multiple phases; wherein

a vibration is generated as a result of rotation of the motor.

46.(amended) A portable telephone unit incorporating a motor, which motor comprising

10 a rotor comprised of magnetic units stacked in K stages (K indicating any integer greater than one) the magnetized position of the N and S poles at each stage deviating relative to one another in a circumferential direction,

a core having salient poles wound around with coil in
15 K stages corresponding to the magnetic units, and

an imbalancing weight which rotates with the rotor, wherein


the phase of induced voltage generated on the coil in each of the stages differs relative to one another and is
20 assigned to respective multiple phases, thereby a motor is driven by the multiple phases; wherein

a vibration is generated as a result of rotation of the motor.


25



This Sheet Has Been Replaced



CLAIMS



1.(amended) A motor comprising

5 a rotor comprised of K pieces of (K indicating any integer greater than one) magnetic units having the N and S poles magnetized alternately,

a rotating shaft around which the magnetic units are stacked axially in K stages to be fixed as a single body,

10 a core having salient poles wound around with coil for K stages corresponding to respective magnetic units, and a pair of bearings for supporting the rotor rotatable; wherein

the magnetized position of the N and S poles of the magnetic unit at each stage deviates relative to one another
15 in a circumferential direction, the phase of induced voltage generated on the coil in each of the stages differs relative to one another and is assigned to respective multiple phases, thereby a motor is driven by the multiple phases.

2.(amended) A motor comprising

20 a rotor comprised of magnetic units stacked in K stages (K indicating any integer greater than one) the magnetized position of the N and S poles at each stage deviating relative to one another in a circumferential direction,


25 a core having K pieces of salient poles wound around with coil corresponding to the magnetic units disposed on a straight line that is in parallel with axial direction of the rotor,

a pair of bearings for supporting the rotor rotatable, and

30 an outer case having an oblong cross sectional shape in a plane perpendicular to axial direction of the rotor consisting of a pair of long sides facing to each other and a pair of short sides facing to each other; wherein

35 the rotor is penetrating through the outer case at the central part and a core is disposed in at least one of the short sides of the outer case, the phase of induced voltage generated





on the coil in each of the stages differs relative to one another and is assigned to respective multiple phases, thereby a motor is driven by the multiple phases.

3.(amended) The motor of claim 2, further comprising an
5 imbalancing weight that rotates together with the rotor, wherein

a vibration is generated as a result of rotation of the rotor.

4. The motor of claim 1, wherein
10 a core having salient poles at each stage wound around with coil is provided splitted, a rotor formed in a splitted manner and said core are combined to form a unit for each stage, and magnetic units for each stage fixed around a rotating shaft are assembled together in correspondence to respective stages
15 with the core.

5. The motor of either one claim among claims 1 through 3, wherein a rotor magnet is made of a single magnetic body, being magnetized in the N and S poles at respective stages in an arrangement deviating relative to one another.

20 6. The motor of either one claim among claims 1 through 3, wherein a rotor magnet is made of a single magnetic body, being magnetized in the N and S poles in a skew arrangement.

7. The motor of either one claim among claims 1 through 6, wherein the salient pole of respective stages wound around with
25 coil are disposed on a straight line running in parallel with the rotating shaft.


8. The motor of either claim 2 or claim 3, wherein the core is provided in only one of the short sides of outer case.

9. The motor of either claim 2 or claim 3, wherein the core
30 is provided in each of the short sides of outer case.

10. The motor of either claim 2 or claim 3, wherein the core is provided in one of the short sides of outer case and a back yoke is provided in the other short side of outer case.

11. The motor of either one claim among claims 1 through
35 6, wherein the position of salient poles wound around with coil at each stage deviates relative to one another in a





circumferential direction.

12. The motor of either one claim among claims 1 through 6, wherein the core is provided with a flat portion in the outer circumference.

5 13. The motor of either one claim among claims 1 through 3, wherein the surface of salient pole facing a rotor is curved with a radius index centred at the axis of rotor.

10 14. The motor of either one claim among claims 1 through 3, wherein the surface of salient pole facing a rotor is curved with a radius index centred at a point away from the axis of rotor.

15. The motor of either claim 2 or claim 3, wherein the outer case has a rectangular cross sectional shape.

15 16. The motor of either one claim among claims 2, 3 and 15, wherein the outer case has dimensions the length of a short side of which is shorter than $1/2$ of a long side.

17. The motor of either one claim among claims 1 through 3, wherein a core is comprised of a yoke and K pieces of salient poles coupled to the yoke.

20 18. The motor of claim 17, wherein the salient pole is formed by a forging process.

25 19. The motor of either one claim among claims 1 through 3, wherein the salient pole is provided with a molded insulation resin in a portion to be wound around with coil, and the coil is insulated from the salient pole by the molded resin.

20. The motor of claim 2, wherein the surface of salient pole facing a rotor magnet has a circumferential angle either $150^\circ \pm 5^\circ$, or $90^\circ \pm 5^\circ$ in terms of electrical effects.

30 21. The motor of claim 2, wherein the circumferential angle of the surface of salient pole facing a rotor is different between the right and the left of a pair of cores within a range $30^\circ \pm 5^\circ$ in terms of electrical effects.

35 22. The motor of claim 10, wherein the circumferential angle of the surface of salient pole of a core facing a rotor is different from that of a back yoke facing a rotor magnet within a range $30^\circ \pm 5^\circ$ in terms of electrical effects.



07 JUL 2001

23. The motor of claim 3, wherein an imbalancing weight is provided on the shaft at a place outside the region between a pair of bearings.

24. The motor of claim 3, wherein an imbalancing weight is provided on the shaft at a place between a pair of bearings.

25. The motor of claim 3, wherein the diameter D of the largest outer circumference of an imbalancing weight, or a bearing bush functioning also as an imbalancing weight, and the dimension a of the shorter side of outer case establish a relationship $0.6a < D < a$.

26. The motor of claim 3, wherein the diameter D of the largest outer circumference of an imbalancing weight, or a bearing bush functioning also as an imbalancing weight, and the diameter Dm of magnetic unit of rotor establish a relationship $0.8Dm < D < 1.1Dm$.

27. The motor of either one claim among claims 1 through 3, wherein one of the bearings is formed with a thrust bearing section and a radial bearing section, and an end of the shaft contacting said thrust bearing section is spherical.

28. The motor of claim 27, wherein the radial bearing section is made with an oil-containing sintered bearing material mixed with fluoric resin.

29. The motor of claim 27, wherein the thrust bearing section is constituted with a thrust plate made of a high polymer compound.

30. The motor of claim 27, wherein the radius index r of shaft end and the diameter d of shaft establish a relationship $10d > r > 1.5d/2$.

31. The motor of claim 27 for generating a vibration, wherein the outer dimension Ds of the thrust plate constituting the thrust bearing and the diameter d of shaft establish a relationship $Ds > d$.

32. The motor of either one claim among claims 1 through 3, wherein the bearing is formed with a bracket made of a low-friction resin.



07 JUL 2001

33. The motor of either one claim among claims 1 through 3, wherein a hole for bearing is formed in a bracket constituting an end of the outer case, a bearing being formed by a circumferential edge of the hole for bearing that has been made
5 thinner for supporting a shaft penetrating through the hole.

34.(deleted)

35. The motor of either claim 2 or claim 3, wherein terminal end of the coil wound around salient pole is electrically connected on a printed board, the printed board constituting
10 at least one of the sides of outer case, and elements of driving circuit are mounted on the printed board.

36.(amended) The motor of either claim 2 or claim 3, wherein a flexible printed board is provided for continuously covering the three sides of outer case, viz. a pair of shorter sides and
15 one of the longer sides.

37. The motor of claim 35, wherein each salient pole is provided with a terminal board of molded resin made with a metal piece integrated to form a single body which is attached and fixed thereon, said metal piece and the printed board are
20 electrically coupled under a state where terminal end of the coil wound around tooth portion of salient pole is being connected to said metal piece.

38. The motor of claim 37, wherein the terminal end of coil is connected with the metal piece by thermal compression.-

25 39. The motor of either claim 37 or claim 38, wherein the metal piece is connected with the printed board by thermal compression.

40. The motor of either one claim among claims 1 through 3, wherein the tooth portion of salient pole to be wound around
30 with coil has a rectangular shape in the cross section, a side parallel to the axis of magnetic units having a length greater than that of the other side which is perpendicular to the former side.

41. The motor of either one claim among claims 1 through
35 40, further comprising an electronic circuit for controlling a DC current so as to provide the coil with electricity setting



* C L H S *

07 JUL 2001

the phase of induced voltage generated on the salient pole wound around with the coil in each stage to a phase suitable for rotating a magnetic unit in that stage, thus the motor operating as a brushless motor.

5 42. The motor of either one claim among claims 1, 3, 4 through 19, and 23 through 40, further comprising a brush and a rectifier for distributing a DC current to as to provide the coil with electricity setting the phase of induced voltage generated on the salient pole wound around with the coil in each stage to
10 a phase suitable for rotating a magnetic unit in that stage, thus the motor operating as a brush motor.

43. The motor of either claim 1, 2, 3, 41 or 42, wherein $K = 3$, comprising three pieces of magnetic units each having the N and S poles magnetized alternately in a circumferential
15 direction for $2n$ poles (n indicating any integer not smaller than 1) at an equal angular pitch, three stages of salient poles wound around with coil for $2m$ poles (m indicating any integer not smaller than 1, $m \leq n$) corresponding to each of the N and S poles of the magnetic units at each stage in m poles, wherein
20 the magnetized position of the magnetic poles of the magnetic unit at each stage deviates relative to one another in a circumferential direction by $120/n$ degrees or $60/n$ degrees so as the phase of induced voltage generated on the three stages of salient poles wound around with the coil deviates relative
25 to one another by 120 degrees.


44. (deleted)

45. (amended) A portable pager incorporating a motor, which motor comprising

30 a rotor comprised of magnetic units stacked in K stages (K indicating any integer greater than one) the magnetized position of the N and S poles at each stage deviating relative to one another in a circumferential direction,

a core having salient poles wound around with coil in
35 K stages corresponding to the magnetic units, and
an imbalancing weight which rotates with the rotor,





wherein

the phase of induced voltage generated on the coil in each of the stages differs relative to one another and is assigned to respective multiple phases, thereby a motor is
5 driven by the multiple phases; wherein

a vibration is generated as a result of rotation of the motor.

46.(amended) A portable telephone unit incorporating a motor, which motor comprising

10 a rotor comprised of magnetic units stacked in K stages (K indicating any integer greater than one) the magnetized position of the N and S poles at each stage deviating relative to one another in a circumferential direction,

a core having salient poles wound around with coil in
15 K stages corresponding to the magnetic units, and

an imbalancing weight which rotates with the rotor, wherein

the phase of induced voltage generated on the coil in each of the stages differs relative to one another and is
20 assigned to respective multiple phases, thereby a motor is driven by the multiple phases; wherein

a vibration is generated as a result of rotation of the motor.

25



07 JUL 2001

ABSTRACT

A small motor for use in an information-communication apparatus, an audio-visual apparatus or the like, and a motor for use in a portable pager and a portable telephone or the like for generating vibrations to be transmitted to a human body, the motors being efficient, small and thin in size, and having a high degree of freedom when mounted on an apparatus. To realize the motor as described above, K pieces of (K indicating any integer greater than one) magnetic units (4a, 4b, 4c) having N and S poles magnetized alternately are mounted on a rotor in a circumferential direction, and K magnetic units are axially stacked in K stages and integrally retained on a shaft (6), and this rotor is rotatably supported on a pair of bearings (9a, 9b). Cores (1a, 1b, 1c) each have a salient pole (7a, 7b, 7c) wound around with coils (3a, 3b, 3c) in K stages so as to correspond to each of the magnetic units. The magnetized position of the N and S poles of the magnetic unit at each stage deviates relative to one another in a circumferential direction so as to set the phase of induced voltage generated on the salient pole wound around with the coil in each stage to a phase suitable for rotating a magnet unit corresponding to a coil in that stage.