

23 June 2004

Elevator Active Suspension System

5 This invention relates to elevators and, more particularly, improved ride quality.

Conventional elevator system suspensions can be characterized by the mechanical properties of the transmissive elements which connect three major elevator components: the car platform, the supporting frame, and
10 the guide rails. The conventional elevator car platform is typically attached to the supporting frame with hard rubber pads. The frame, in turn, runs along the guide rails, which are supported either by stiffly sprung wheels or sliding gibs at four attachment points.

15 The motion of the car platform in these conventional elevator systems is affected by forces which act directly on the car, e.g., reactive forces due to passenger motion or wind forces, and by forces which act indirectly, most particularly, by guide rail irregularities, e.g., butt
20 joint misalignments, or waviness due to settling of the building. These conventional elevator suspension systems can be classified as "passive" in the sense that no energy is provided to the suspension system to counteract the direct or rail induced forces. For such passive
25 systems, there is an inherent compromise in ride quality. Stiff transmissive elements mitigate the effects of direct car forces, while compliant (low stiffness) transmissive elements mitigate the effects of guide rail irregularities.

30 In U.S. Patent 4,899,852 issued to Salmon et al, a passive suspension configuration is disclosed with a mechanically compliant attachment between the car platform and frame. The mechanically compliant attachment is realized by suspending the car platform
35 from the frame with long steel rods. This elevator configuration, hereafter referred to as the "pendulum car" is a passive design in which the mitigation of the

23 June 2004

effects of rail irregularities is maximized at the expense of an increased sensitivity to direct car forces.

In a non-pendulum cab disclosure, U.S. Patent No. 4,754,849, Hiroshi Ando shows electromagnets disposed
5 outside the car symmetrically about guide rails in a control system using opposing forces from the electromagnets to keep the car steady using the rails as the necessary ferromagnetic mass but, rather than using the rails as a straight reference line, instead using a
10 cable stretched between the top and bottom of the hoistway. The position of the car with respect to the cable is controlled using detectors in a closed loop control system. There is serious question as to whether such a cable can be successfully used as a reliable guide
15 of straightness, especially in tall buildings.

In another non-pendulum cab disclosure, U.S. Patent No. 4,750,590, Matti Otala discloses what appears to be an essentially open loop control system with solenoid actuated guide shoes that uses the concept of memorizing
20 the out-of-straightness of the guide rails for storage in a computer memory and then sensing the position of the car in the hoistway for the purpose of recalling the corresponding information from memory and correcting the guide rail shoe positions accordingly. An acceleration
25 sensor is mentioned in claim 6 but does not appear to be otherwise disclosed as to its purpose in the specification or drawing. Perhaps it is used to determine the acceleration of the car in the hoistway. Such an acceleration signal would presumably be needed to
30 determine which data point to retrieve from memory as suggested in claim 2. Otala's approach suffers from the problem of changes in the out-of-straightness before a correction run can be effected and the accuracy with which the stored information can be made to conform to
35 the car's actual position.

A mounting arrangement for a pendulum-type or hung cab is shown in U.S. Patent 4,113,064 by Shigeta et al

23 June 2004

wherein the cab is suspended within and from the top of an outer car framework by a plurality of rods connected to the bottom of the cab. A plurality of stabilizing stoppers are shown interposed between the underside of the hung cab and the floor of the car frame. Each stopper comprises a cylinder extending downward from the underside of the hung cab surrounding a rubber torus placed on an upright rod extending from the floor of the car frame. Clearance between the cylinder and the hung cab is sufficient to permit movement but insufficient to allow the hung cab to strike the car frame. Another embodiment comprising "bolster" means having ball bearings permits movement in any direction of the horizontal plane.

Another approach is disclosed by Luinstra et al in U.S. Patent 4,660,682 wherein a pair of parallel rails are arranged horizontally in a parallelogram between the suspended cab and car frame with followers arranged to roll or slide on the rails in such a way that the hung cab can move in any horizontal direction relative to the car frame.

Both of the last two pendulum or supported cab approaches employ passive restraints on movement which by nature are reactive rather than active.

Active suspension systems are known in the automobile art. In particular, what we call "tunable shock absorbers" are used as tunable impedances. They comprise a relative displacement device made up, from a "systems" point of view, of a mechanical impedance (defined here as the frequency dependent ratio of deflection over applied force) of a stiffness in parallel with a damper. The stiffness and dampening elements are adjusted during different conditions. For example, during a cornering mode, as sensed by accelerometers, increased stiffness is desired on selected shock absorbers. Similarly, during braking, both front shocks are made stiffer. This is done in software by sensing

the displacement of the car with respect to the frame and commanding a desired displacement. In simply adjusting stiffness and damping there is a trade-off; as the mechanical impedance of the shock absorbers is increased,
5 the car becomes more sensitive to a bumpy road. Or, as the mechanical impedance of the shock absorbers is decreased, the car becomes more susceptible to direct forces, other than bumpiness.

In our study of improved ride quality for elevators,
10 we compared the frequencies of disturbances caused by rail bumpiness in a pendulum cab to the frequency manifestations of direct forces and found, at least for a pendulum cab, a critical area of between two to ten Hertz where we could not satisfy both our desire to reduce
15 mechanical impedance to cure rail bumpiness and our desire to increase mechanical impedance to mitigate direct forces. At least for a pendulum cab, this problem very significantly limits the effectiveness of the tunable impedance active suspension approach used in
20 automobiles.

Some specific examples of active suspension systems that are of interest are listed as follows:

U.S. Patent 4,809,179 to Klinger et al

25 Klinger et al discloses an acceleration sensor 26 which feeds a microprocessor which in turn appears to control an actuator for a motor vehicle suspension unit.

U.S. Patent 4,892,328 to Kurtzman et al

30 Kurtzman et al discloses an active suspension system for controlling the orientation of the chassis of a motor vehicle relative to the frame. Fig. 2 shows an accelerometer feedback signal between a strut control processor 20 and a strut assembly 10 connected between
35 each wheel 14 and the chassis, i.e., the frame 12 of a motor vehicle.

23 June 2004

U.S. Patent 4,621,833 to Soltis

Soltis discloses an acceleration sensor 16 in Fig. 2 providing a signal to a suspension control module for a multi-stable suspension unit.

5

U.S. Patent 3,939,778 to Ross et al

Ross et al discloses a lateral accelerometer 40' in Fig. 6 which shows interconnecting components insertable at the Z-Z' inputs of Fig. 4 to include lateral stability. Also, see Fig. 4 for an illustration of an electromagnetic side frame 1 and a ferromagnetic side frame 2 as part of a block diagram of a complete electrical control system comprising an active suspension for a railway truck shown in Fig. 2.

15

U.S. Patent 4,625,993 to Williams et al

Williams et al illustrates control signals that can be modified by signals representing vehicle speed and lateral and longitudinal acceleration.

20

U.S. Patent 3,871,301 to Kolm et al

Kolm et al discloses active damping of oscillations of a magnetically levitated vehicle including inertial and position sensors on the vehicle.

25

U.S. Patent 4,770,438 to Sugasawa et al

Sugasawa et al discloses an automotive suspension control system with vibration sensors for detecting road surface conditions and counteracting same.

30

U.S. Patent 4,215,403 to Pollard et al

Pollard et al discloses an active suspension for a vehicle in which an accelerometer 3 is utilized.

35

U.S. Patent 4,909,535 to Clark et al

Clark et al discloses an "active" suspension system between the body and wheel of a vehicle. A high gain

closed positional velocity servoloop is disclosed. 23 June 2004

U.S. Patent 4,898,257 to Brandstadter

Brandstadter discloses an active hydropneumatic
5 suspension system for a heavy combat vehicle wherein
vertical accelerometers 188a, 188b, 188c, 200 are
utilized, as shown in Fig. 3.

NASA Tech Briefs, July 1990 discloses "Flux-Feedback
10 Magnetic-Suspension Actuator" wherein flux density is
maintained substantially constant and hall-effect devices
are used as sensors for an electronic feedback circuit
that controls currents flowing in the electromagnetic
windings to maintain the flux linking the suspended
15 element at a substantial constant value independent of
changes in the length of the gap. Reference is made to
further information which may be found in NASA TM-100672.

An object of the present invention is to improve the
ride quality of elevators.

20 As used herein, "cab" refers to a passenger platform
suspended or movably supported within an outer frame.
"Car" refers to a passenger platform that is not free to
move within a supporting frame or on another supporting
platform, or alternately, "car" is used to refer to a
25 frame for a movably supported or suspended cab platform
(e.g., "car frame").

According to an aspect of the present invention a
platform, e.g., a suspended or supported elevator car or,
alternatively, a cab hung (pendulum cab) or supported
30 within a car frame undergoing movements in moving up and
down an elevator hoistway is controlled with respect to a
selected parameter by an actuator in a closed loop
control system responsive to a sensor for detecting the
selected or another, related parameter. Such parameters
35 may include position, velocity, acceleration, vibration
or other similar parameters, although acceleration is
preferred.

23 June 2004

In further accord with an aspect of the present invention, a control is responsive to a sensed signal to process the sensed signal to drive an actuator with a frequency response tailored to achieve a stable, high-
5 performance, drift-free system.

In still further accord with an aspect of the present invention, at least for pendulum cab embodiments, in regions where car motion is to be minimized, the loop gain is made greater than 1. At high frequencies, the
10 loop gain is rolled off to meet stability robustness requirements. At low frequencies, the loop gain is "washed-out" to reduce the effects of sensor noise and drift.

The elevator active suspension system disclosed
15 herein represents from one aspect a unique combination of a sensor, a control, and an actuator applied in one or more axes to minimize the effects of rail-induced disturbances and direct car forces.

An elevator, in going up and down a hoistway, is
20 subjected to disturbances due to rail irregularities which have a frequency content not unlike the disturbances caused by other forces, which we call direct forces. At least for a pendulum cab, unfortunately, unlike the case for automobiles, the frequency content of
25 rail-induced disturbances is in the same range of frequencies encountered at the same time in the disturbances caused by direct forces. Direct forces can be most effectively countered by high mechanical impedance, while rail irregularities can be effectively
30 countered by low mechanical impedance. In automobiles, there are well defined modes to detect, such as cornering, acceleration and deceleration, which may be effectively counteracted using the tunable impedance as previously described. In our approach, according to the
35 teachings of an aspect of our invention, we generate forces directly in response to sensed acceleration, and only the restoring force of the pendulum controls the

23 June 2004

relative displacement between the car and frame or hoistway. This same approach applies to active control of conventional elevator cars.

In still further accord with an aspect of the present invention, the actuators may be arranged, for a conventional car embodiment, so as to counteract horizontal translational forces acting on the car moving in the hoistway or, for nonconventional hung (pendulum) or supported cab embodiments, arranged to counteract horizontal forces acting on the hung or supported cab moving in the car frame as the frame moves in the hoistway. If such a concept is utilized in a conventional car application, it would require, without limitation, only four active actuators near the bottom of the car, two each for actuating rails on opposite sides of the car. Four conventional or passive guides might additionally be used near the top of the car. Such an arrangement might advantageously employ, e.g. but not limited thereto, a nonconventional "V" rail shape, e.g., a shape first suggested for other purposes by Charles R. Otis in U.S. Patent No. 134,698 (which issued on January 7, 1873). If such a concept is utilized in a pendulum or supported cab application it similarly might require, without limitation, only four actuators using a novel active actuator arrangement on or near the bottom of the cab for actuating the car frame and, also without limitation, using conventional rails for guiding the frame.

In still further accord with an aspect of the present invention, the actuators may be arranged so as to counteract rotational forces acting about vertical on the conventional car in a hoistway or a cab hung from, or supported on, a car frame. Furthermore, and without limitation, if such a concept is utilized for controlling a conventional car in a hoistway it still would only require four actuators using the same novel rail shape for active control. If such a concept is utilized in a

23 June 2004

pendulum or supported cab application, it similarly still requires only four actuators using a novel active actuator arrangement and, without limitation, using conventional rails for guiding the frame.

5 In still further accord with an aspect of the present invention, the actuators may be arranged so as to counteract rotational forces acting on a conventional car, or on a cab hung from or supported on a frame, about one or more axes in a horizontal plane. Such axes may,
10 but need not, be defined for purposes of control as orthogonal axes in such a horizontal plane and which may be parallel to the hoistway walls. In such a case, a plurality of actuators may be employed at both the top and bottom of the car wherein those at the top control
15 horizontal accelerations in the roof while those at the bottom control horizontal accelerations in the floor. By independently controlling horizontal accelerations in the top and bottom, rotations are automatically taken care of. If the four-actuator approach described previously
20 is implemented for a non-pendulum car (in conjunction with control of horizontal translations and vertical rotations) it need not but may use only eight actuators (four at the top and four at the bottom) using a novel rail shape for active control. Similarly, if such a
25 concept is implemented for a pendulum or frame-supported cab (in conjunction with control of horizontal translations and vertical rotations) it may, but need not, utilize only eight actuators using four on the top of the cab and four on the bottom.

30 In accordance still further with an aspect of the present invention, the actuators may be of the electromagnetic type.

 In further accord with an aspect of the present invention, the actuators may be electromechanical, e.g.,
35 solenoid actuated wheels.

 In further accord with an aspect of the present invention, four electromagnetic actuators are utilised,

23 June 2004

each operating along an axis which, for a non-pendulum or non-frame-supported car embodiment, is disposed for imparting forces at an angle of forty-five degrees to a hoistway wall, e.g., opposite hoistway-railed walls and, for the hung cab embodiment, is disposed for imparting forces along axes at an angle of forty-five degrees to the planes of the hung or supported cab walls.

The present invention teaches, among other things, that, instead of position, accelerometers are most advantageously used in a closed loop for actively controlling an elevator car or cab. It further teaches that, for a car guided by rails mounted on hoistway walls, Ando's twelve electromagnets for controlling horizontal translations of an elevator car can be replaced by a lesser number of actuators. According to a preferred embodiment of an aspect of the present invention, four actuators are sufficient for controlling such translational forces in the horizontal plane. Moreover, as a further teaching, the same four actuators may be used to control rotational forces about vertical. For a non-pendulum cab embodiment, although conventional-style rails may be used in an Ando-like configuration, a new rail configuration may be advantageously applied in an active system based on acceleration feedback, and four or more actuators may be well-disposed for controlling translational forces in the horizontal plane. Moreover, as a further teaching, the same actuators may be used to control rotational forces about vertical. Furthermore, the same teachings may be extended for application to a cab hung or supported in a car frame. In such a case, four or more well-disposed actuators are similarly sufficient for controlling translational forces in the horizontal plane. And also similarly, as a further teaching, the same actuators may be used to control rotational forces about vertical.

These approaches have the added advantage of greatly simplifying the design. Moreover, by using

23 June 2004

accelerometers, there is then no need to use Ando's cable which may be subject to out-of-straightness forces due to many factors such as building sway, expansion and contraction due to temperature changes, vibrations due to
5 air currents in the hoistway and other causes. Such a construct can be replaced, according to a preferred embodiment of the present invention by accelerometers used to provide signals which can also be indicative of position in a closed loop control system.

10 Although we teach that a position control system based on an accelerometer output is a superior approach, we also recognize that drift is associated with accelerometers which we teach may be corrected, according to one aspect of the present invention, based on a slow
15 regulating loop to control the average car or cab position with respect to a fixed referent.

Thus, in further accord with an aspect of the present invention, a preferred embodiment comprises a relatively fast, simple, analog control loop responsive
20 to accelerometers with one or more, relatively slower, but more accurate, digital control loops responsive to position or acceleration sensors or to both.

Another aspect of the present invention originated from the need to improve the combined strength to weight
25 ratio of the guide rails, without lessening their control characteristics. This aspect of the present invention achieves this goal by using a "Y" shaped section rail in place of the standard "T" shaped guide rail.

Such a rail design achieves the same amount of
30 control over the car being guided with also an enhanced strength to weight ratio.

The guide rail of this aspect of the present invention may likewise interface with three wheels attached to the elevator car, in which the three wheels
35 ride on comparable surfaces to that of the "T" shape, namely on two, opposed sides of the base, but with the mounting surface being through the upper part of the "Y"

23 June 2004

through the legs of the "Y", which form a "V", instead of the flat, orthogonally disposed "top" of the "T".

The guide rail of this aspect of the present invention may also be used to act as a rail for active control. Such may be embodied in two or three actively controlled wheels or other actuators such as electromagnets using the "T's" upright portion or the top part of the "Y" as ferromagnetic masses.

The Y-shape of the invention has better section properties than a corresponding T-shape and yet weighs considerably less. This saving in weight, while retaining the section properties, is achieved by spreading the material in the two legs of the "Y". The T-section has more material, below the blade, concentrated near the center line and thus contributes less to the moment of inertia of the section about the center line.

In the Y-shape plural-bladed rail of this aspect of the present invention, the material below the blade is spread in the two legs of the "Y" and further away from the center line. They contribute more to the moment of inertia of the section about the center line. Consequently, a Y-shape having the same section properties is lighter than the corresponding T-shape.

Appropriately configured "Y" shaped guide rails designed in accordance with the principles of this aspect of the present invention can be developed to replace each of the T-shapes presently being used, with a savings in weight of, for example, ten to twenty percent (10% to 20%).

The Y-shape rails of this aspect of the invention present an opportunity to guide elevator cars successfully and at reduced cost of material and shipment.

It thus is a general and basic object of this aspect of the present invention to provide a more economically produced or manufactured guide rail without having to sacrifice the guidance or control characteristics of the

23 June 2004

guide rail and preferably to do so without having to significantly redesign the other elements of the car guidance control subsystem, including particularly the three wheel interfacing of the elevator car to each guide rail.

As previously suggested, the passive restraints employed by Shigeta et al and Luinstra et al are not as effective as the present invention in that they do not actively counteract the undesirable translational forces to which the cab is subjected and thus do not provide as smooth a ride for the passenger as that provided by the present invention. Furthermore, they do not actively counteract the undesirable rotational forces to which the cab is subjected and thus similarly fail to provide as smooth a ride for the passenger as that provided by the present invention. And certainly they do not consider even passive restraints and certainly not active countermeasures of any kind with respect to rotational axes other than vertical, as taught herein.

These and other objects, features and advantages of the present invention will become more apparent in light of the following detailed description, given by way of example only, as illustrated in the accompanying drawings, in which:

Fig. 1 is a block diagram of an active control system for an elevator car or cab, according to the present invention;

Fig. 2 is an illustration of an elevator car or cab, with a coordinate system shown;

Fig. 3 shows the coordinate system of Fig. 2 in more detail;

Figs. 4 - 7 show various plural-bladed, active rail configurations, according to the present invention;

Fig. 8 shows a prior art active rail configuration;

Figs. 9 - 13 show various plural-bladed, active rail configurations, according to the present invention;

Fig. 14A is a top view of a pendulum car shown in

23 June 2004

Fig. 14B from the side;

Fig. 14B is a side view of the pendulum car of Fig. 14A with an active suspension shown, according to the present invention;

5 Fig. 14C is a sectional, plan view illustration looking up at the bottom of an elevator cab comprising a five degree of freedom platform hung in or supported from a frame which is itself suspended from a rope or mounted on a piston, showing a novel actuator arrangement (which
10 may be similar at the top of the cab) using only four electromagnets between the underside of the suspended or supported cab and the floor of the frame, according to the present invention;

Fig. 14D is another, similar illustration (as in
15 Fig. 14C) of a group of electromagnetic actuators situated between the underside of the suspended or supported cab and the floor of the car frame, except using six electromagnets;

Fig. 15 is an illustration of the bottom (top may be
20 similar) of an elevator car platform in plan view having an active control using "V" or triangular shaped rails, according to the present invention;

Fig. 16 is an illustration of a signal processor which may be used as the means 20 shown in Fig. 1 for
25 determining the magnitude of the response required to counteract disturbances;

Fig. 17 is an illustration of a series of steps which may be carried out by the processor of Figure 16 or its equivalent in determining the magnitude of the
30 response required to counteract disturbances;

Fig. 18 shows a mathematical abstract of a preferred control scheme for carrying out the active control of Fig. 1 having an inner loop with acceleration feedback and slower outer loops with position and acceleration
35 feedback;

Fig. 19 shows concrete means for carrying out the abstracted control of Fig. 18 for the control of Fig. 14C

23 June 2004

in which a fast, analog control is used in the inner loop and a relatively slow but more accurate, digital control is used in the outer loop;

Fig. 20 shows the analog control of Fig. 19 in more detail;

Fig. 21 is an illustration of a power controller;

Fig. 22 illustrates a firing board for gating SCRs in the power controller of Fig. 21;

Fig. 23 illustrates the concept of nonlinearity and offset in exaggerated form;

Fig. 24 shows the theory of operation of Fig. 18 in a reduced block diagram form;

Fig. 25 shows an even more reduced model valid at all but the lowest frequencies;

Fig. 26 shows a graph of current vs. air gap;

Fig. 27 shows a graph of power vs. air gap;

Fig. 28 shows a graph of time constant vs. air gap;

Fig. 29 shows a pair of coils for use with the core of Fig. 30;

Fig. 30 shows a laminated core for use with the coils of Fig. 29;

Fig. 31 is an illustration of a single-axis lateral vibration stabilization system, such as may be used in the actuator arrangement of Fig. 14D;

Fig. 32 illustrates the force summation technique employed in the system of Fig. 31;

Fig. 33 illustrates a negative rectifier and inverter such as employed in the system of Fig. 31;

Fig. 34 illustrates a positive rectifier-inverter such as employed in the system of Fig. 31;

Fig. 35 illustrates an FC-controlled clamp circuit such as employed in the system of Fig. 31;

Fig. 36A is another systems level block diagram of a specific implementation of an active suspension system for a particular pendulum cab (shown in U.S. Patent No. 4,899,852), according to the present invention;

Fig. 36B is a qualitative presentation of design

23 June 2004

requirements on the overall loop gain for a particular pendulum cab (e.g., as shown in U.S. Patent No. 4,899,852), according to the present invention;

5 Figs. 37A and 37B are plots of the open-loop gain and phase angle of the product ($L(s)$) of $C(s)$ and $G(s)$ in Fig. 36A;

Figs. 38A and 38B are plots of the feedback compensator gain and phase angle for that particular pendulum cab design, according to the present invention;

10 Figs. 39 - 41 summarize the results of a simulation study of an active suspension system using the compensator of Figs. 36A and 36B, 37A and 37B, and 38A and 38B, according to the present invention;

15 Fig. 42 is an illustration of a digital control which may be used in implementing the control of Fig. 36A;

Fig. 43 is an illustration of a series of steps which may be carried out by the processor of Fig. 42;

20 Fig. 44 shows the results of a test to evaluate the effectiveness of the active system of Fig. 36A for a pendulum cab in mitigating direct car forces which shows a ratio of the measured car acceleration to the magnitude of a sinusoidal input force over a sweep of frequencies;

25 Fig. 45 shows a comparison of the predicted time response (via simulation) and the achieved response for direct pendulum cab force mitigation;

Fig. 46 illustrates the response of the pendulum cab system to a rail irregularity as simulated on a test bed with a rotating imbalance;

30 Fig. 47 is a detailed schematic of a circuit for controlling one of the electromagnets of Fig. 14D in response to a force command signal 106 from a signal processor, such as is illustrated in Fig. 42;

35 Fig. 48 shows preferred means for carrying out the preferred control scheme of Fig. 15;

Fig. 49 is an illustration of a three wheel active guide, according to the present invention;

23 June 2004

Fig. 50 shows a solenoid actuated wheel for use in an active system such as that of Fig. 49;

Fig. 51 illustrates steps which may be carried out in using actuators to bring a suspended or supported platform to rest at a sill, according to the present invention;

Fig. 52 is an end, sectional view of the standard, established "T" shaped section guide rail, showing its interfacing with the standard three wheels, of the prior art;

Fig. 53 is an end, sectional view of the "Y" shaped section guide rail, which serves as the exemplary, preferred embodiment of the invention, showing its interfacing with the standard three wheels of the prior art; while

Fig. 54 is an end, sectional view of the "Y" shaped section guide rail of Fig. 52 with two electromagnetic actuators; and

Fig. 55A and 55B include a detailed comparative chart comprising Tables 1 and 2 comparing the characteristics of the "T" shaped guide rail of the prior art, as shown in Fig. 55A, to the "Y" shape guide rail of the invention as shown in Fig. 55B, including at the top thereof illustrated definitions of the elemental parts and dimensions of the two shapes being compared, along with two related tables below the illustration and below that a listing of definitions used in the tables.

Fig. 56 is a perspective view of a guide roller cluster, according to the present invention;

Fig. 57 is a side elevational view of the guide roller cluster of Fig. 56 showing details of the secondary suspension's side-to-side roller adjustment mechanism;

Fig. 58 is an exploded, schematic view of the front-to-back roller adjustment crank to which the spring of Fig. 59 is connected;

Fig. 59 is a plan view of the flat spiral spring

23 June 2004

used in the front-to-back guide for damping and adjusting the front and back rollers in the cluster;

Fig. 60 is a front elevational view of the front and back guide rollers of the cluster;

5 Fig. 61 is a partial plan view of a guide and one of the rollers of the guide rail cluster of the guide of Fig. 56 showing the positioning of the electromagnets of a relatively small-force actuator;

Fig. 62 shows a gap sensor;

10 Fig. 63 shows a flux sensor which may be used in the acceleration loop of Fig. 69;

Fig. 64 shows a side view of an electromagnet core;

Fig. 65 shows a top view of the core of Fig. 64 with coils in phantom;

15 Fig. 66 is a simplified block diagram of a steering circuit for controlling two active guides situated on opposite sides of an elevator car for side-to-side control but which may be used for front-to-back control of guides on opposite sides of a rail blade;

20 Fig. 67 is a plot of a biasing technique for controlling a pair of opposite electromagnets wherein, for example, the force command for the righthand active guide of Fig. 66 is biased in a positive direction and the force command for the lefthand guide is biased in a
25 negative direction to provide a composite response that avoids abrupt switching between the pair;

Fig. 68 is a more detailed illustration of the discrete signal processor of Fig. 66;

Fig. 69 is a control scheme for a pair of active
30 guides such as are shown in Fig. 66 including control of both the small actuators and the large actuators and including a steering arrangement for the large actuators;

Fig. 70 is an illustration of some of the parameters illustrated in the control scheme of Fig. 69;

35 Fig. 71 is an illustration of the response of a single position transducer associated with, for example, each one of the position transducers such as illustrated

23 June 2004

in Fig. 62; and

Fig. 72 is an illustration of a composite of two such transducer responses such as might appear on line 698 of Fig. 69.

5 In Fig. 1, a passenger platform 10 for an elevator car or cab is suspended or supported by means 12. As used herein, "cab" refers to a passenger platform suspended or movably supported within an outer frame (not shown in Fig. 1). "Car" refers to a passenger platform
10 that is not movably supported within a frame or, alternatively, to a frame for a suspended or supported cab platform (sometimes referred to as a "car frame"). Several examples of the use of each term are: (i) a car suspended by a cable laid over a rotating sheave, (ii) a
15 ("pendulum") cab suspended by a cable, rod or rods within a car frame, (iii) a car supported on a movable platform mounted on a hydraulically operated piston, (iv) a cab supported on a movable platform in a supported or suspended car frame, etc. In all cases, the elevator car
20 or car frame is moved up and down in an elevator hoistway (not shown in Fig. 1) guided by means such as vertical rails (not shown) attached to the hoistway walls.

 According to the present invention, one or more disturbances 14 (such as an air current in the hoistway
25 acting on the car or car frame, a bumpy ride disturbance transmitted to the car or cab as a result of an out-of-straightness condition in a section of rail, etc.) may be sensed by a sensor 16 disposed in or on the car or cab platform 10. The sensor 16 typically senses an effect of
30 the disturbance 14 for providing a signal having a magnitude indicative of the magnitude of the effect on a line 18. Means 20 is responsive to the signal provided on line 18 for determining the magnitude of the response required to counteract the sensed effect of the
35 disturbance and for providing a signal on a line 22 for commanding an actuator 24 to actuate the platform 10 as indicated by an actuation signal on a line 26. The

23 June 2004

actuator 24 may be disposed, without limitation, between the car or car frame and the hoistway or it may be disposed between the car frame and the cab inside the frame for imparting forces therebetween in response to
5 the control signal on line 22.

A plurality of sensors similar to sensor 16 may be disposed to be responsive to one or more selected parameters indicative of translational and rotational movements of the car or cab which cause it to deviate
10 from staying perfectly centered on an imaginary vertical line through the center of the hoistway. Such sensors may be responsive to any one or any number of selected parameters such as the position of the car or cab with respect to the hoistway, the translational accelerations
15 experienced by the car or cab, etc. According to a preferred embodiment of the present invention, acceleration is sensed. Such sensors may provide one or more sensed signals to the means 20 or another similar means in order to complete a closed loop for purposes of
20 automatic feedback control, according to the present invention.

As suggested above, one way to view a preferred embodiment of the invention is to think of the control system as causing the elevator car's vertical centerline
25 (or elevator frame-suspended or frame-supported cab's vertical centerline) to remain coincident with an imaginary, stationary reference line up the center of the hoistway, without the suspended car or cab's centerline departing from coincidence with the hoistway reference
30 centerline or without the car or cab, having its centerline coincident with the stationary centerline, from rotating about the stationary centerline.

Fig. 2 illustrates car or cab mounted accelerometers 16a, 16b, 16c which together serve as an example of a
35 sensor arrangement that may be used to sense horizontal accelerations manifesting small horizontal translations causing deviations of the car or cab's centerline from

23 June 2004

the hoistway's centerline and, without necessarily
limiting the foregoing, by further sensing accelerations
manifesting small rotations of the car or cab about the
hoistway centerline. An additional set of similar
5 sensors 16d, 16e, 16f may, but need not, be located near
the top of the car or cab. Selective use of one or more
groups of actuators, e.g., actuator groups 24a, 24b, 24c,
24d permits the exertion of forces to maintain the
desired coincidence of the car or cab and hoistway
10 centerlines and, if desired, with no rotation about
vertical or even about one or more axes in the horizontal
plane. A preferred embodiment of the present invention
utilizes two groups of actuators 24a, 24b, e.g., each
group comprising a pair of actuators. Thus, although two
15 groups of actuators are shown near both the top and the
bottom of the car or cab, it should be understood that
such are shown to indicate actuators acting from any
position or in any grouping, i.e., other groupings at
other positions are certainly encompassed by the present
20 invention. As mentioned, the preferred embodiment only
uses actuators at the bottom. The fact that the
actuators are shown detached from the platform (implying
electromagnetic actuators utilizing a contactless (air
gap) form) in no way excludes actuators mechanically
25 attached to the platform.

An arbitrary three dimensional coordinate system
illustration 44 in Fig. 2 has its x-z plane in the paper
and should be thought of as having its origin in the
center of gravity of the car or cab 10 and having its
30 minus y-axis pointing up perpendicular to the paper
toward the reader. The coordinate system 44 of Fig. 2 is
illustrated in more detail in Fig. 3. There, it will be
observed that in addition to rotations about the vertical
z-axis, there may be rotations about the x and y-axes
35 which may also be controlled, according to the present
invention, if desired. According to the present
invention, translations in the horizontal plane may be

23 June 2004

controlled using the apparatus shown. Such may also, but
need not be, used for controlling rotations. Thus, the
present invention may be used to control rotations in the
horizontal plane and may be extended to two or even to a
5 plurality of axes including an additional horizontal axis
and a vertical axis.

It will be further observed that the sensors, in
this case accelerometers, cannot be positioned at the
center of gravity as would be desired. A floor or roof
10 of a passenger compartment is illustrated here without
limitation as an acceptable compromise. The selected
positioning of the illustrated sensors is of course
arbitrary. It should not be inferred from the symmetry
of such positioning with respect to the illustrated
15 coordinate system, or to each other, that the selected
relationship is required to practice the claimed
invention. In other words, for example, sensors could be
aligned for sensing accelerations along axes parallel to
or coincident with the axes of actuation, i.e., forty-
20 five degrees with respect to the hoistway walls. In any
case, it might be advantageous, in some cases, to utilize
a coordinate system having axes similarly aligned with
the force actuation directions of the actuators. It
should be understood also that the orientation of the
25 actuators at forty-five degree angles with respect to the
hoistway walls is not absolutely essential. Indeed, the
relationships of the actuators to the car or cab are not
critical. It is preferred, however, to have
orthogonality of actuators to achieve universal force
30 vector capability and to have a distance between lines of
opposite force to enable torque development. Thus, one
could arrange the actuators in each corner to act along
the diagonals instead of perpendicularly thereto.
Although such an arrangement is not presently preferred
35 as it would eliminate the capability to counter vertical
rotations, it would still fall within the scope of the
claims hereof.

23 June 2004

It will be observed still further from the locations of the illustrated acceleration sensors near the floor that translational accelerations along the x-axis can be sensed by accelerometer 16a while those along the y-axis
5 can be sensed by accelerometers 16b, 16c. A miscomparison of the outputs of the two y-sensitive accelerometers will indicate a rotation about the z-axis. A clockwise or counterclockwise rotation will be indicated depending upon which y-accelerometer 16b or 16c
10 provides the larger magnitude sensed signal. The magnitude of the difference is indicative of the magnitude of the angle of rotation from a reference position. A similar situation exists for sensors 16d, 16e, 16f in the roof.

15 Although guide rails are not illustrated, such would typically be situated oppositely on two of the four hoistway walls. Such may, for a car example, serve as ferromagnetic masses for use, for example, by the actuators 24a, 24b, 24c, 24d should the actuators be of
20 the electromagnetic type. In that case, the actuators 24a, 24b can be attached near the bottom and 24c, 24d near the top of the platform 10 for producing magnetic flux for contactless interaction across air gaps with the rails. Or, electromechanical, i.e., contact-type active
25 actuators, to be disclosed below, can be employed. Conventional, passive-type wheel guides can be used instead of active actuators 24c, 24d at opposite sides at the top of the car to lend additional stability without adding the need for additional active control systems as
30 required by Ando, for example, but for his more limited purposes.

In a suspended (pendulum) cab example, electromagnetic, contactless-type actuators 24a, 24b can be attached to the underside of the cab with suitable
35 ferromagnetic reaction plates erected on the floor of the car frame for providing a path for magnetic flux provided by the actuators. In such a case, there would be no need

23 June 2004

for additional passive guides at the top of the cab.

In a supported car or cab example using a horizontally sliding platform for support, for example as shown in U.S. Patent 4,660,682 to Luinstra et al, but
5 mounted on a hydraulic piston or within a suspended car frame (as shown by Luinstra et al), electromagnetic, contactless-type actuators 24a, 24b can be attached to the underside of the sliding platform with suitable ferromagnetic reaction plates erected under the sliding
10 platform on a nonsliding horizontal platform mounted on the top of the piston or, for a supported cab, on the floor of the car frame, for providing a path for magnetic flux provided by the actuators.

It should be understood from the foregoing that a
15 preferred embodiment of present invention may be utilized for increasing ride comfort in an elevator car or cab. The preferred embodiment of the present invention will be described first for a cab and then for a car. It will become apparent that the same approach is used for both
20 the car and cab, differing in detail only to the extent necessary to account for the fact that the actuators for a car act against a rail on a hoistway wall, as shown in Fig. 15, while the actuators for a cab act on a frame as shown in Figs. 14B, 14C, and 14D.

25 Fig. 14A is a top view and Fig. 14B is a side view of a pendulum car 46. It includes an active suspension system comprising an actuator 45 shown in Fig. 14B, driven by a control (not shown) to process sensed data relative to the motion of a platform 10b. Sensors 50,
30 52, 54, which may be accelerometers, measure the platform motion. The platform 10b is suspended by rods 56, 58 from a frame 60 which is suspended by a cable 62 for moving the car 46 up and down in an elevator hoistway having walls 64, 66 with rails 68, 70 mounted thereon. A
35 plurality of wheels 72, 74, 76, 78 are mounted by means of springs 80, 82, 84, 86 to the frame 60. A passive pendulum car of this type (without the actuator 45) is

23 June 2004

shown in detail in U.S. Patent 4,899,852.

In moving up and down the hoistway, the wheels are subjected to bumpiness in the rails, e.g., caused by a rail butt joint misalignment 88 or waviness 90. Such butt joint irregularities induce relatively high frequency car vibrations, while waviness usually produces lower frequency vibrations. In addition to vibrations imparted to the platform 10b through the frame 60 by rail irregularities, the platform 10b is subjected to what we call direct forces 92, which may comprise a large number of different influences, including wind forces, motion of people within the car standing on the platform, and numerous other similar "direct" forces.

A coordinate system is shown in both Figs. 14A and 14B (similar to Fig. 2) and shows an X-Y plane in the floor of the platform 10b with the Z-axis in the vertical direction. The present invention mitigates both direct forces and rail irregularity forces imparted to the platform 10b through the frame 60. It does this by counteracting lateral forces in both the X and Y directions. Rotations about the Z-axis are mitigated also by virtue of lateral control along the X and Y axes as further disclosed below.

In Fig. 14C, a floor 200 of a passenger platform similar to the cab 10b of Figs. 14A and 14B and a bottom 202 of a frame similar to the frame 60 of Figs. 14A and 14B are superimposed and are presented in a plan view which shows the two substantially in registration at rest. For descriptive purposes and not by way of limitation, if one assumes a rectangular or, for even greater simplicity, a square layout for the cab floor 200 and frame bottom 202, one can visualize a pair of reaction planes perpendicular to the cab floor and frame bottom which intersect one another along a vertical cab centerline which perpendicularly intersects the center of the square. The reaction planes may or may not intersect the floor and bottom along the bottom's (and floor's)

23 June 2004

diagonals.

As mentioned, one way to view the preferred embodiment of the invention is to think of the control system as causing the elevator cab's centerline to remain
5 coincident with an imaginary reference line up the center of the hoistway without the suspended or supported cab rotating about the coincident cab and hoistway centerlines.

It may do this by the use of cab-mounted
10 accelerometers 204, 206, 208 which together are used to sense accelerations manifesting small translational deviations of the cab's centerline from the hoistway's centerline and by further sensing accelerations manifesting small rotations of the cab about the hoistway
15 centerline and by the selective use of actuators 210, 212, 214, 216 exerting forces perpendicular to the reaction planes to maintain the centerlines' desired coincidence with no vertical rotation of the cab about the hoistway's centerline. These actuators correspond to
20 the actuator 45 shown in Fig. 14B. A three dimensional coordinate system illustration 218 in Fig. 14C has its x-y plane in the paper and should be thought of as having its origin in the center of the squares 200, 202 and having its z-axis pointing up perpendicular to the paper
25 toward the reader, similar to the coordinate system of Fig. 14B. It will be observed from the locations of the accelerometers that translational accelerations along the y-axis can be sensed by accelerometer 206 while those along the x-axis can be sensed by either accelerometer
30 204 or 208. A miscomparison of the outputs of the two x-sensitive accelerometers will indicate a rotation about the z-axis. A clockwise or counterclockwise rotation will be indicated depending upon which x-accelerometer 204 or 208 provides the larger magnitude sensed signal.
35 I.e., the magnitude and sign of the miscomparison is indicative of the magnitude and direction of the angle of rotation. In the contemplated embodiment, however, i.e.,

23 June 2004

a closed loop control, the sensed movements are imperceptible to the passenger.

Ferromagnetic reaction plates 218, 220, 222, 224 of the same size can be erected symmetrically about the center of the frame's floor near each corner along the diagonals so as to lie in the reaction planes. Four electromagnet cores 226, 228, 230, 232 with coils may be attached to the bottom surface of a suspended or supported platform so that each faces one of the reaction plates. Attractive forces generated by the control system by means of the four electromagnet core-coils are exerted in such a way as to separate or bring closer the core-coils from their associated reaction plates.

The positioning of the core-coils with respect to the reaction planes can of course vary. As shown, for example in Fig. 14C, electromagnet core-coils situated along the same diagonal at opposite corners, i.e., the pair 226, 232 or the pair 228, 230 are arranged to exert attractive forces on opposite sides of the reaction plane so that a pair of electromagnets associated with one of the reaction planes act in concert to counteract clockwise rotational forces while the other pair counteracts counterclockwise rotational forces. Electromagnetic actuators acting along axes intersecting the same cab wall, e.g., 230, 232 or 226, 228 may be situated in between that wall and their respective reaction plates so they may co-act to offset translational forces.

However, it should be understood that the electromagnets in Fig. 14C could all be situated on opposite sides of the reaction plates than the sides shown with the only change being that all control actions would be reversed. Or, the core-coil pairs for co-acting against a particular direction of rotational disturbing forces can be associated with adjacent corners of the cab such that they are arranged, with respect to the diagonals, on the same side of each reaction plate so

23 June 2004

that the diagonally associated pairs are no longer co-acting. In that case, the equations to be disclosed below would of course have to be rewritten but the same principles as disclosed herein would apply.

5 It should also be understood that, alternatively, the reaction plates could be mounted on the underside of the cab with the electromagnet core-coils mounted on the floor of the frame.

10 It should also be understood that an "X" or diagonal concept with "reaction planes" has been introduced as a teaching tool, is merely a conceptual aid for describing a preferred cab embodiment and need not necessarily be embodied or even conceptually applicable in all applications of the invention.

15 Even if conceptually applicable in whole or in part to other embodiments, though it certainly need not be, as evidenced by the embodiment of Fig. 14D to be described below, it should be understood that the orientation of the "X" need not be from corner to corner as described
20 but could lie in any convenient orientation. Similarly, the actuators and reaction plates need not be located between the bottom of the cab and the floor of the frame. Nor need they all necessarily be at the same level, although such an arrangement could cause unneeded
25 complexity. Needless to say, the invention is not restricted to the use of four actuators, as three, four, five or more could be used. Four has been selected as a convenient number that fits well with the symmetry of a typical elevator car and hoistway. An "X" orientation
30 was first disclosed in commonly owned U.S. Patent 4,899,852 to Salmon et al in connection with a passive stabilization system.

For the car embodiment to be disclosed in more detail below, Figs. 4-7 and Figs. 9-13 show various
35 embodiments of a novel, plural-bladed rail configuration, in each case according to the present invention for use with active control systems, which plural-bladed rails

23 June 2004

are all distinguished from the prior art single-bladed rail, shown in Fig. 8, used in at least one prior art active system. (See U.S. Patent 4,754,849 to Ando).

In Figs. 4-7 and Figs. 9-13, more than one "blade" is used in each case to interface with two or more corresponding actuators. In Fig. 8, in contrast, a single blade 40 is used by all three actuators 42, 44, 46. It should be understood that for all of the plural-bladed rails shown below, the associated actuators may be disposed differently than in the exact manner illustrated.

In Fig. 4, a rectangular shape rail 48 has three blades 50, 52, 54 for serving as ferromagnetic paths or masses for three separate electromagnetic actuators 56, 58, 60 respectively. As an example of how an associated actuator could be disposed differently than illustrated, the actuator 58 could be positioned between the blade 52 and the hoistway wall instead, to save space and make the arrangement more compact.

In Fig. 5, a two-bladed rail 62, is shown having a V-shape comprising a blade 64 and a blade 66. A triangle-shaped configuration was previously disclosed for a passive system by Charles R. Otis in U.S. Patent 134,698. However, according to the present invention, plural blades may be used in an active system, e.g., the blade 64 serves as a ferromagnetic mass for electromagnetic actuator 68 while blade 66 serves a similar function for actuator 70. It should be understood that the rail 62 may have footings 72, 74 for easily attaching the rail to a hoistway-way wall 76. Or, the rail 62 may be formed in a full triangular cross-section with or without footings (not shown). Similarly, referring back to Fig. 4, the three-bladed embodiment may comprise a four-blade box-shaped rail without footings. As another example of how an associated actuator could be disposed differently than illustrated, the actuator 70 could be positioned opposite actuator 68, on the other

23 June 2004

side of blade 64 and blade 66 could be used as an engagement projection for a safety brake (not shown).

In Fig. 6, an I-beam 78 approach is used. A blade 80 is used by a pair of opposed electromagnetic actuators 82, 84 while a second blade 86 is used by a third actuator 88. A third blade 90 is not used as a ferromagnetic mass or path by any actuator but may be used to attach the other two blades to a hoistway wall 92.

10 Fig. 7 illustrates a variation of the two-bladed V-shaped rail 62 of Fig. 5. Rail 94 comprises a pair of blades 96, 98 for interfacing with respective actuators 100, 102. The rail also includes a projecting blade 104 which may be used as a convenient handle, upon which to
15 engage a safety brake (not shown).

Fig. 9 shows an inverted V-shaped rail 106 having a blade 108 for interacting with an electromagnetic coil 110 and a blade 112 for a coil 114. Blades 116, 118 provide structural strength.

20 Fig. 10 shows a C-shaped rail 120 having a blade 122 and a blade 124 for providing a ferromagnetic path for coils 126, 128, respectively. A coil 130 uses a blade 132 as its ferromagnetic mass. Blade 132 may also be used to attach rail 120 to a hoistway wall 134.

25 Fig. 11 illustrates a rail 136 mounted on a hoistway wall using a facing pedestal 140. The rail 136 comprises a curved section 142 which, in effect, comprises two "blades", one on either side of a projecting blade 144 for safety brake purposes. One side of the curved
30 section is used for interacting with a coil 146 while the other is used for interacting with a coil 148.

Fig. 12 is an illustration of a rail 150 attached to hoistway wall 152 by means of a footing 154. The active part of the rail 150 comprises a circular rail 156 which
35 in effect comprises two half-circles on either side of a projection 158. Coils 160, 162 used the respective halves of the circle 156 as ferromagnetic masses. Thus,

23 June 2004

rail 150 is, in effect, a two-bladed rail.

Fig. 13 is an illustration of a rail 164 mounted on a hoistway wall 166 by means of footings 168, 170. A curved section 172 is, in effect, split into two sections on either side of a projection 174. Each section is utilized by an actuator, i.e., actuator 176, 178 respectively. The rail 164 is similar in concept to rail 136 Fig. 11 except it has an "omega" shape rather than a "D" shape.

10 The rail 94 in Fig. 7 is the preferred embodiment for enabling the utilization of only eight electromagnets as shown below in connection with stabilization in the horizontal plane and about three axes of rotation.

For a suspended (pendulum) cab there is little or no need for stabilization of the top of the cab with respect to the frame from which it is suspended because of the lack of any appreciable rotations about any horizontal axes. However, for a supported cab, for example, supported in a tiltable manner on a point mounted on a translatable platform within the frame, rotations about horizontal axes may be appreciable. In such a case it may be desired to employ a control system similar or identical to that which has previously been described above in connection with Fig. 14C for the roof of the cab and acting completely independently of the control system operating for stabilizing the floor. For the problem of stabilizing tilt, at first glance it might be thought necessary to actually measure the tilt of the cab to directly counteract rotations about any horizontal axis or axes. Although such is certainly within the scope of the present invention, according to the teachings of the present invention, for cabs as well as cars, by using two independent control systems to stabilize horizontal translations in the roof and floor; surprisingly, any rotations about any horizontal axes are automatically taken care of. Although applicable to both cabs (and particularly supported cabs) and cars, the description

23 June 2004

below will describe the case for a car. One skilled in the art will have no difficulty in using the following teachings to make and use a cab with horizontal rotation stabilization.

5 Fig. 14D is a top view of the pendulum car of Fig. 14B looking down from the bottom surface of the platform 10b of an actuator arrangement in the space between the car frame's floor and the underside of the suspended cab. In this case, we have shown three actuators 240, 242, 244
10 in lieu of the single actuator 45 shown in Fig. 14B. The actuators shown in Fig. 14D are of the electromagnetic type to be described in detail below. The orientation of the platform 10b is the same as is shown in Fig. 14A, and the same coordinate system applies. Thus, the actuator
15 242 produces forces along the X-axis while the actuators 240, 244 produce forces along axes parallel to the Y-axis. Each of the actuators 240, 242, 244 has a separate control loop which is independent of the others at least in the sense of not depending on sensors in any other
20 axis. It will, of course, be understood that the various axes of control are mechanically coupled.

Several active suspension inventions are disclosed herein which describe embodiments of the present invention which include separate, single-axis controls
25 such as disclosed herein in connection with Fig. 14D, and several of which embodiments describe combined, multi-axis control channels, such as shown in Figs. 14C and 15. It should be understood that the separate, single-axis controls disclosed herein are advantageous for simplicity
30 of design and for the advantage of being able to electronically decouple the various control axes. It will be noted, however, that the separate, single-axis approach is somewhat more expensive than the combined, multi-axis approach because of the added number of
35 electromagnets required. On the other hand, there are only three channels of electronics required in the separate channels while the combined, multi-axis approach

23 June 2004

requires a minimum of four channels of electronics.

It was previously indicated that it should be understood that a preferred embodiment of the present invention may be utilized for increasing ride comfort in an elevator car or cab. The preferred embodiment of the present invention was in part described first for a cab and will now be described for a car. Again, it will be apparent that the same approach is used for both the car and cab, differing in detail only to the extent necessary to account for the fact that the actuators for a car act against a rail on a hoistway wall while the actuators for a cab act on a frame as shown in Fig. 14C.

Referring now to Fig. 15, the bottom of a suspended or supported car 250 is presented in a plan view which shows the car at rest. Again, in a manner similar to the above presentation for a cab, for descriptive purposes and not by way of limitation, if one assumes a rectangular or, for even greater simplicity, a square layout for the passenger platform or car floor, one can visualize a pair of reaction planes perpendicular to the car 250 floor which intersect one another along a vertical car centerline which perpendicularly intersects the center of the square. The reaction planes may or may not intersect the floor along the floor's diagonals.

Again, as mentioned previously, one way to view the preferred embodiment of the invention is to think of the control system as causing the elevator car's centerline to remain coincident with an imaginary reference line up the center of the hoistway without the suspended or supported car rotating about the coincident car and hoistway centerlines.

It does this by the use of car-mounted accelerometers 252, 254, 256 (analogous to sensors 16b, 16a, 16c, respectively, of Fig. 2) which together are used to sense accelerations manifesting small translational deviations of the car's centerline from the hoistway's centerline and by further sensing

23 June 2004

accelerations manifesting small rotations of the car about the hoistway centerline and by the selective use of actuators 258, 260, 262, 264 exerting forces perpendicular to the reaction planes to maintain the centerlines' desired coincidence with no rotation. A three dimensional coordinate system illustration 266 in Fig. 15 has its x-y plane in the paper and should be thought of as having its origin in the center of the square 250 and having its z-axis pointing up perpendicular to the paper toward the reader. It will be observed from the locations of the accelerometers that translational accelerations along the y-axis can be sensed by accelerometer 254 while those along the x-axis can be sensed by either accelerometer 252 or 256. A miscomparison of the outputs of the two x-sensitive accelerometers will indicate a rotation about the z-axis. A clockwise or counterclockwise rotation will be indicated depending upon which x-accelerometer 252 or 256 provides the larger magnitude sensed signal. I.e., the magnitude and sign of the miscomparison is indicative of the magnitude and direction of the angle of rotation.

V-shaped rails 267, 268, similar to the rail pictured in Figs. 5 and 7, or similar, such as that of C. R. Otis, affixed to opposite hoistway walls 267a, 268a provide ferromagnetic reaction plates 268, 270, 272, 274. Four electromagnet cores 280, 282, 284, 286 with associated coils may be attached to the sides, near the bottom, of a suspended or supported platform so that each faces one of the reaction plates. Attractive forces generated by the control system by means of the four electromagnet core-coils are exerted in such a way as to separate or bring closer the core-coils from their associated reaction plates. The positioning of the core-coils with respect to the reaction planes can of course vary, as with the cab example, except in this case most especially according to the selected rail shape.

Turning now to Fig. 16, the means 20 of Fig. 1 is

23 June 2004

illustrated in a digital signal processor embodiment which may comprise an Input/Output (I/O) device 280 which may include an Analog-to-Digital (A/D) converter (not shown) responsive to an analog signal provided by sensor 5 16, which may be accelerometers 204, 206, 208 as shown in Fig. 14C or accelerometers 252, 254, 256 shown in Fig. 15, or any sensed parameter indicative of the effect(s) of the disturbance(s) 14C. The I/O device 280 may further comprise a Digital-to-Analog (D/A) converter (not 10 shown) for providing force command signals on line 22 to an analog actuator 24 which may instead comprise the actuators 210, 212, 214, 216 of Fig. 14C, the actuators 258, 260, 262, 264 of Fig. 15, or any other suitable actuators. Also within the control 20 of Fig. 16 is a 15 control, data and address bus 282 interconnecting a Central Processing Unit (CPU) 284, a Random Access Memory (RAM) 286 and a Read Only Memory (ROM) 288. The CPU executes a step-by-step program resident in the ROM, stores input signals having magnitudes indicative of the 20 value of the sensed parameter as manifested on the line 18 in the RAM, as well as signals having magnitudes representing the results of intermediate calculations and output signals having magnitudes indicative of the value of the parameter to be controlled as manifested in the 25 output signal on line 22.

Returning to the arrangement of the cab and car platforms of Figs. 14C and 15 and at the same time referring to Fig. 17, a simplified step-by-step program will be explained for execution by the CPU of Fig. 16 in 30 effecting the closed loop control function previously explained in connection with the means 20 of Fig. 1 and the embodiment thereof shown in Fig. 16. After entering at a step 300, an input step 302 is executed in which the magnitude(s) of the signal(s) on line 18 is(are) acquired 35 by the I/O unit 280. For the purposes of Figs. 14C and 15, these shall be referred to as signals A_{x1} , A_{x2} and A_y provided, respectively, by accelerometers 204, 208, 206

23 June 2004

of Fig. 14C (or accelerometers 252, 256, 254 of Fig. 15 (with suitable transformation of coordinates)) and stored in the RAM 286 of Fig. 16. One or the other of the two x-axis accelerometers 204, 208 (or 252, 256) can be used
5 in a step 304 to compute the magnitude of a positive or negative A_x signal, or both can be used as a check against one another, used to provide an average, or used in some such similar redundancy technique. (Of course, it should be realized that the steps 302, 304 can be combined into
10 a single sensing step if a rotation sensor is provided along with two translational [x and y] sensors). From a comparison of the two signals provided by accelerometers 204, 208 (or, 252, 256) a computation of A_θ may be made in step 304. The magnitude of the signal A_θ will depend
15 on the degree to which the magnitude of the signals from accelerometers 204, 208 (or, 252, 256) differ. The sign of their summation determines the rotational direction. The values of A_x , A_y and A_θ are stored temporarily in RAM 286.

20 A step 306 is next executed in which a computation is made of the forces needed to counteract the effect(s) of the disturbance(s) as manifested in one or more sensed parameter(s) (accelerations preferred). Such may be made based on the known mass of the suspended or supported cab
25 or car and the formula $F=ma$ where "F" represents the required counterforce, "m" the mass of the suspended or supported cab or car and "a" the value of the sensed acceleration. Thus, F_x , F_y and F_θ are computed from the signals A_x , A_y and A_θ that were stored in RAM 286 in step
30 304. These computed values are provided in the form of force command signals on line 22 as indicated in a step 308. It should be understood that the orientation of the actuators as shown in Figs. 14C and 15 are such that a command signal calling for a positive x-direction
35 counterforce will have to be exerted by electromagnets 210 and 214 (or, 258, 262) acting in concert, each providing half the required counterforce by each

23 June 2004

providing a force equal to the commanded x-direction force multiplied by $\cos(45^\circ)$. Similar divisions of counterforces are made for the y-direction and for rotations as well. A set of formulae that will cover all

5 the possibilities follows {in the following equations, the subscripts 1, 2, 3, 4 correspond, respectively, to electromagnetic actuators 210, 212, 214, 216 of Fig. 14C (or, actuators 258, 260, 262, 264 of Fig. 15)}:

$$\begin{array}{ll}
 F_{x+}: & F_1 = (KCS)(F_{x+}) \\
 10 & F_3 = (KCS)(F_{x+}) \\
 F_{y+}: & F_1 = (KCS)(F_{y+}) \\
 & F_2 = (KCS)(F_{y+}) \\
 F_{\theta+}: & F_2 = (KCS)(F_{\theta+}) \\
 & F_3 = (KCS)(F_{\theta+}) \\
 F_{x-}: & F_2 = (KCS)(F_{x-}) \\
 & F_4 = (KCS)(F_{x-}) \\
 F_{y-}: & F_3 = (KCS)(F_{y-}) \\
 & F_4 = (KCS)(F_{y-}) \\
 F_{\theta-}: & F_1 = (KCS)(F_{\theta-}) \\
 & F_4 = (KCS)(F_{\theta-})
 \end{array}$$

15 where F = force, and
 $KCS = \cos(45^\circ) = \sin(45^\circ) = 0.707$.

After making the necessary computations and providing the required counterforce command signals the program may then be exited in a step 310. However, it is

20 preferable to add additional steps in order to superimpose a system for insuring against imperfectly levelled accelerometers and also against a changing offset in the accelerometers. For purposes of

embodiments of the present invention, accelerometers have

25 two major errors: (i) offset drift and (ii) pickup of unwanted gravity components due to not being perfectly level; also present, but not as significant, are (iii) linearity errors. A nonlevel accelerometer will sense accelerations due to gravity in proportion to the sine of

30 the angle it makes with true vertical. Correction for nonlinearity is not usually important in embodiments of this invention but may be corrected for, if desired (see Fig. 23 below). Assuming the nonlinearity retains its basic relationship with true linearity as adjusted for

35 changes in offset, such nonlinearity may be corrected at each stage of sensed acceleration by consulting a lookup table which is used to supply a corrective factor. If

23 June 2004

offset were constant over time it could be corrected for straightforwardly with a constant correction factor.

But, since offset can change over time due to temperature, aging, etc., corrections should be made in a

5 dynamic manner. Offset and changing offset, as well as accelerations due to gravity, can be corrected by providing a relatively slower acting feedback control system for controlling the position of the car or cab with respect to the hoistway centerline. This may be
10 done by recognizing that the average lateral acceleration must be zero (or the car or cab would travelling off into space). The slow acting loop offsets the average accelerometer output signal. Averaging may be accomplished, e.g., using an analog low-pass filter or a
15 digital filter.

Thus, if we think of a single axis of control such as the x-axis shown in Fig. 2, the theory of operation of such a system for controlling the cab or car with both acceleration and position sensors is shown in Fig. 18.

20 The system in elementary form comprises the car or cab mass as illustrated by a block 320. The car or cab mass is acted upon by a force on a line 322 which causes an acceleration as illustrated by a line 324. A disturbing force is shown schematically as a signal on a line 326
25 summed in a "summer" 328 (an abstract way of representing that the disturbing force is physically opposed by the counteracting force) with a counterforce signal on a line 330 provided in proportion (K_a) to the acceleration (A) shown on the line 324 as sensed by an accelerometer 332
30 which provides a sensed acceleration signal on a line 334 to a summer 336. The scale factor (K_a) of the accelerometer is (volt/m²/s). (As previously indicated, the acceleration on line 324 is produced by the disturbing force on line 326 interacting with the mass of
35 the suspended or supported car or cab according to the relation F/M as suggested in block 332, where F is the disturbing force and M is the mass of the car or cab.

23 June 2004

The summer 328 represents the summation of the disturbing force on line 326 and the counterforce on line 330 to provide a net force on a line 322 acting on the mass 320.) The summer 336 may provide a signal on a line 338 to a force generator 340 which may have a transfer characteristic of 1.0 Newton/volt. The summer 336 serves to collect an inner acceleration loop signal on line 334 with the outer acceleration and position loop signals to be described below prior to introduction on the line 338 into the force generator 340. The inner acceleration loop comprising elements 320, 332, 340 and the associated summers forms the primary control loop used for "mass augmentation" as defined herein.

The description of Fig. 18 so far covers the theory of the control system previously described in connection with Figs. 1-17. Secondary control loops may also be added as illustrated in the abstract in Fig. 18.

Shown are two secondary control loops which may be used for nulling offsets in the accelerometer 332 caused, e.g., by misalignment with gravity and due to manufacturing imperfections. The first of these secondary loops corrects on the basis of position offsets. A position transducer that gives car position is represented abstractly by an integrator block 342 and an integrator block 344. The integrator 342 provides a velocity signal on a line 346 to the integrator 344 which in turn provides a position signal on a line 348. The cab position signal on line 348 is compared in a summer 350 with a reference signal on a line 352. The signal on the line 352 would ordinarily be a fixed DC level scaled to represent, e.g., the x-position (in the cab coordinate system 218 of Fig. 14C or in the car coordinate system 266 of Fig. 15) of a selected referent such as the hoistway centerline (which will be substantially coincident with true vertical, i.e., a line along which the earth's gravity will act). This entire process is carried out in practice by use of a position sensor that

23 June 2004

gives the relative position between the cab and car frame. The summer 350 provides a signal on a line 354 which represents the relative position of the cab with respect to the frame and may be characterized as the
5 relative position signal or the position error signal. It is provided on a line 356 to a low-pass filter 358 after being summed in a summer 360 with a signal on a line 362. The low-pass filter 358 provides a filtered signal on a line 364 which causes the force on the line
10 330 to be applied on the line 322 to the car or cab 320 until the position error signal is driven to zero or close to zero.

A second secondary control loop may be introduced if a position signal is not conveniently available or to
5 enhance the stability of the position correction control loop. The position error signal on line 354 may thus be modified in the summer 360 by being summed with the signal on line 362 which is provided by a gain block 366 which is in turn responsive to the signal on line 338
10 which is representative of the acceleration sensed in the primary loop.

An extraneous signal on line 338 will appear directly on line 322 if $G_1=0$ and $G_2=0$. Assuming no indicated position error on line 354 and nonzero gains G_1
15 and G_2 , a disturbance manifested by an acceleration signal on line 334 will appear on line 322 reduced by a dynamic factor

$$\frac{S\tau + 1}{S\tau + (1 + G_1 \cdot G_2)}$$

15 This factor approaches unity at higher frequencies, indicating no effectiveness. At lower frequencies, however, this factor approaches $[1/(1 + G_1 \cdot G_2)]$. Typically, $G_1 \cdot G_2$ could be chosen equal to nine (9) to reduce accelerometer offsets by a factor of ten (10).

20 The position feedback loop offers the advantage of very low error. Without the accelerometer feedback loop 366, 360, 358, 336 and/or practical control elements

23 June 2004

being present this loop may not be as stable. Assuming gain $G_2=0$, the only way for the position loop to be stable is for the car or cab mass to be acted upon by damping, friction and an inherent spring rate due to pendulousity, acting singly or in concert. One or more of these elements will be present in a practical system. Use of an accelerometer loop by making G_2 nonzero can enhance the operation of the position loop.

The control represented in abstracted form in Fig. 18 may be carried out in numerous different ways but a preferred approach is shown in Fig. 19.

There, a fast-acting analog loop for quickly counteracting disturbing forces is combined with a slower acting but more accurate digital loop for compensating for gravity components and drifts in the accelerometers. A plurality of such fast-acting analog loops may be embodied in analog controls 370, 372, 374, 376 as shown, one for each of the respective actuators 210 or 258, 212 or 260, 214 or 262, 216 or 264, of Figs. 14C or 15, respectively. With proper interfacing (not shown), a single digital controller 380 can handle the signals to be described to and from all four analog controls. Each analog control responds to a force command signal on lines 382, 384, 386, 388 from the digital controller 380. The force command signals will have different magnitudes depending on the translational and rotational forces to be counteracted. The digital controller 380 is in turn responsive to acceleration signals on lines 390, 392, 394 from the accelerometers 204 or 252, 206 or 254, 208 or 256, respectively (the accelerometers being from either Fig. 14C or 15), and to position signals on lines 396, 398, 400, 402 indicative of the size of the air gaps between the coil-cores 226 or 280, 228 or 282, 230 or 284, 232 or 286 and their respective plates 218 or 270, 220 or 272, 222 or 274, 224 or 276.

In response to the force command signals on lines 382, 384, 386, 388, the analog controls 370, 372, 374,

23 June 2004

376 provide actuation signals on lines 404, 406, 408, 410 to the coils of the coil-cores 226 or 280, 228 or 282, 230 or 284, 232 or 286 for causing more or less attractive forces between the respective core-coils 226 or 289, 228 or 282, 230 or 284, 232 or 286 and their associated reaction plates. The return current through the coils is monitored by current monitoring devices 412 or 420, 414 or 422, 416 or 424, 418 or 426 which provide current signals on lines 428, 430, 432, 434 to the respective analog controls 370, 372, 374, 376. The current sensors may be, e.g., Bell IHA-150 with multiple looping of the "through" lead.

A plurality of sensors 440 or 448, 442 or 450, 444 or 452, 446 or 452, which may be Hall cells (e.g., of the type Bell GH-600), are respectively associated with each core 226 or 280, 228 or 282, 230 or 284, 232 or 286, for the purpose of providing an indication of the flux density or magnetic induction (volt-sec/m²) in the gap, i.e., between the faces of the cores and the associated plates or, otherwise stated, the flux density in the air gaps therebetween. The sensors 440 or 448, 442 or 450, 444 or 452, 446 or 452 provide sensed signals on lines 460, 462, 464, 466, respectively, to the analog controls 370, 372, 374, 376.

Referring now to Fig. 20, the analog control 370 among the plurality of analog controls 370, 372, 374, 376 of Fig. 20, is shown for one embodiment in detail. The other analog controls 372, 374, 376 may be the same or similar. The force command signal on line 382 from the digital controller 380 of Fig. 19 is provided to a summer 470 where it is summed with a signal on a line 472 from a multiplier 474 configured as a squaring circuit (to linearize control) having a gain selected dimensionally to be equivalent to magnetization (amp/meter) and properly scaled to convert a signal on a line 476 indicative of flux density to one indicative of force. The flux density signal on line 476 is provided by a Hall

23 June 2004

cell amplifier 478 which is used to boost the level of the signal on a line 480 from the Hall cell 440 or 448.

The summer 470 provides a force error signal on a line 484 to a proportional-integral (P-I) amplifier 486 which provides a P-I amplified signal on a line 488 to a firing angle compensator 490. Compensator 490 provides a firing angle signal on a line 492 which controls the firing angle of a plurality of SCRs in a controller 494 after being filtered by a filter 496 which in turn provides a filtered firing angle signal on a line 498 to the controller 494 which is more fully described as a single phase, two-quadrant, full-wave, SCR power converter. This type of converter is preferred over one-quadrant and half-wave converters. The least preferred combination would be a one-quadrant, half-wave. There would be a slight cost savings in using these non-preferred approaches but the dynamic performance would be significantly degraded. An inexpensive, one-quadrant system is possible using a DC rectifier and a transistor PWM chopper. The highest performance approach would be a full-wave, two-quadrant, three phase converter but this is not the preferred approach because of cost considerations. The two-quadrant, full wave converter 494 of Fig. 21 may be made up, for example, of a pair of Powerex CD4A1240 dual SCRs and a circuit configuration as shown in part Fig. 21 (not shown are RC snubbers across the SCRs) and a commercial firing board 253 such as a Phasetronics PTR1209 which is shown in Fig. 22. Gate signals on a plurality of lines 253a for the SCRs are provided by the firing board 253. The power controller 252 is powered with 120 VAC on a line 254 as is the firing board and provides the proper level of current on line 180 in response to the filtered firing angle signal on line 250.

The signal on the line 428 from the current sensor 412 is provided to an analog multiplier/divider 504 (such as an Analog Devices AD534) which is also responsive to

23 June 2004

the flux density signal on line 476 for dividing the magnitude of the current signal on line 428 by the magnitude of the flux density signal on line 476 and multiplying the result by a proportionality factor in order to provide the signal on line 396 (back to the digital controller 380 of Fig. 19) indicative of the magnitude of a gap (g_1) between the face of the core of the core-coil 226 and the plate 218.

As mentioned previously, the digital controller 380 is responsive to the gap signals on the lines 396, 398, 400, 402, as well as the acceleration signals on lines 390, 392, 394, for carrying out, in conjunction with analog controls of the type shown in Fig. 20, the control functions of Fig. 18. Instead of generating force signals on the lines 382, 384, 386, 388 in exactly the same manner as previously disclosed in connection with Figs. 16 and 17, such signals, though generated in a similar manner, are modified by summation with corrective force signals calculated to correct for position imbalances detected by the position sensor 440 or 448 and similar sensors 442 or 450, 444 or 452, 446 or 452 associated respectively with the actuators 212 or 260, 214 or 262, 216 or 264 as shown in Figs. 14C or 15. (Note: These are the Hall sensors used to find flux density. The signals from the position sensors such as sensor 440 or 448 and from current sensor C1, when processed by the divider circuit 504 give the GAP1 signal on line 396. Similar processing in the other channels yields the GAP2, GAP3 and GAP4 signals on lines 398, 400, 402.) Such corrective force signals may be generated, for example, by first resolving the sensed position signals into components along the axes of the Cartesian coordinate system 218 or 266 of Fig. 14C or 15 as in the equations which follow,

$$\begin{aligned} P_{x+} &= (P_1 + P_3)/(2KCS), & P_{x-} &= (P_2 + P_4)/(2KCS), \\ P_{y+} &= (P_1 + P_2)/(2KCS), & P_{y-} &= (P_3 + P_4)/(2KCS), \\ P_{\theta+} &= (P_2 + P_3)/2, & P_{\theta-} &= (P_1 + P_4)/2, \end{aligned}$$

23 June 2004

and then, based on the above, computing or selecting P_x , P_y , and P_θ (which together specify the absolute position of the car or cab), from P_{x-} and P_{x+} , P_{y-} and P_{y+} , and $P_{\theta+}$ and $P_{\theta-}$. P_x , for example, may be computed as follows:

$$P_x = (P_{x+} - P_{x-})/2.$$

Or, one can select P_{x+} or P_{x-} , depending on which quantity is smaller. (Note: For large gaps, i.e., for large P_{x+} or P_{x-} , the value is likely to be inaccurate and may be discarded). The resultant components are used to determine position-control force components F_{px} , F_{py} , $F_{p\theta}$ as illustrated in Fig. 18 on a single-axis basis ("P" stands for position feedback). P_x , for example on line 348, is compared to a reference on line 352 to generate an x-position error signal on line 354. This in turn is passed through a low-pass such as filter 358. This provides an F_{px} signal. For purposes of resolving the required x-counterforce, if a positive force is required, $F_{p1}=F_{p3}=(0.5)(F_{px})/(\cos 45^\circ)$. For a negative force, $F_{p2}=F_{p4}=(0.5)(F_{px})/(\cos 45^\circ)$. This same procedure may be followed for F_{py} and $F_{p\theta}$ using, of course, the appropriate equations. Thus, the force components F_{px} , F_{py} and $F_{p\theta}$ may be resolved into corrective signals F_{p1} , F_{p2} , F_{p3} , F_{p4} , according to the following complete set of equations,

$$\begin{array}{ll} F_{px+}: F_1 = (KCS)(F_{px+}) & F_{px-}: F_2 = (KCS)(F_{px-}) \\ F_3 = (KCS)(F_{px+}) & F_4 = (KCS)(F_{px-}) \\ F_{py+}: F_1 = (KCS)(F_{py+}) & F_{py-}: F_3 = (KCS)(F_{py-}) \\ F_2 = (KCS)(F_{py+}) & F_4 = (KCS)(F_{py-}) \\ F_{p\theta+}: F_2 = (KCS)(F_{p\theta+}) & F_{p\theta-}: F_1 = (KCS)(F_{p\theta-}) \\ F_3 = (KCS)(F_{p\theta+}) & F_4 = (KCS)(F_{p\theta-}) \end{array}$$

where F = force, and
 $KCS = \cos(45^\circ) = \sin(45^\circ) = 0.707$,

which are then summed with the acceleration feedback signals F_1 , F_2 , F_3 , F_4 (such as the signal on line 364 or line 382) generated in the manner previously described in connection with Figs. 1-20.

23 June 2004

It should be realized that a valid position reading will only be available from the flux sensors of the type described unless its associated force actuator is being driven. This means that any processing algorithm must be dependent upon whether or not there are magnet coil actuation currents present.

It should be realized that the gap signals on lines 396, 398, 400, 402 could be provided by a simple position sensor only.

An additional teaching of our invention is that the electromagnets may be used to control the position of the car or cab at stops, e.g., to bring the suspended or supported car or cab to rest with respect to the frame while on- and off-loading passengers. Of course, the signal processor of Fig. 16, the digital controller 380 of Fig. 19 or an additional signal processor may handle additional control functions such as the starting and stopping of cars and the dispatching of cars. In the case of stopping at a floor, the processor 20 of Fig. 16 may receive a sensed signal on line 18 or an algorithmically determined but similar signal indicating the car is vertically at rest and will then provide a signal on line 22 to control the position of the suspended or supported car or cab. For, example, if the cab platform 200 of Fig. 14C is oriented in the hoistway such that the left hand vertical edge of the cab represents the cab's sill in alignment with a hoistway door sill 700, then the signal processor 20 of Fig. 16 may be programmed to provide force command signals to actuators 210, 214 in order to provide the attractive forces needed to force the suspended cab up against, e.g., stops 702, 704a mounted in the car frame 202 so as to push the cab sill into position at rest with respect to, and in close alignment with the hoistway entrance sill 700 after the signal processor 20 causes the frame 202 to come to rest. Or, the stops may be part of the actuators themselves, for example, mounted on the top

23 June 2004

faces of the legs 304, 306 of the core shown in Fig. 30 such that in applying a selected current level for the coils, an attractive force is generated that is sufficiently strong to bring the stops up against the reaction plates. For a double-doored platform, as a further example, if the platform 200 of Fig. 14C is oriented in the hoistway such that the left hand vertical edge of the cab represents the cab's sill in alignment with a hoistway door sill 700, and the right hand vertical edge is at the same time in alignment with a sill 514 then the signal processor 20 of Fig. 16 may be programmed to provide force command signals to actuators 212, 216 in order to provide the attractive forces needed to force the suspended cab up against, e.g., stops 513, 513a mounted in the car frame 202 so as to push the cab sill into position at rest with respect to, and in close alignment with the hoistway entrance sill 514 after the frame 202 comes to rest.

The method used to accomplish the same is shown in Fig. 51 to be described later in connection with Fig. 15.

We have, in the foregoing description of a best mode embodiment of a three-axis active control for a suspended cab, paid considerable attention to the details of that particular embodiment and taught how to carry it out. But it will be recalled that we have previously indicated that there are any number of additional different approaches for carrying out the subject matter of our invention which is active control of a suspended cab. The fundamental principle of active control can be carried out in a plurality of coordinated single axis controls as previously described. Recall that Fig. 18 illustrated the theory of operation of single-axis stabilization of horizontal motion of a cab suspended in an elevator frame. In connection therewith, it has been suggested that an accelerometer may be used in a feedback loop to, in effect, increase the cab mass by

23 June 2004

electromechanical means. Slow position and accelerometer regulating loops may be used to compensate for accelerometer offsets, etc. Fig. 24 shows a reduced block diagram of the same concept and Fig. 25 shows an even further reduced model valid at all but the lowest frequencies.

The Fig. 25 diagram may be expressed in units scaled to as follows:

Acceleration of cab = $[FD/G][1/(M+K_a)]$,

where FD is the disturbing force,

M is the mass of the suspended cab,

K_a is the counter-mass "added" by the actuator, and

FD/G is the mass equivalent of the disturbing force using the acceleration due to gravity (G) at the earth's surface.

If, in the foregoing equation, we let K_a=0, i.e., we assume the absence of active control, and let M=1000kg and FD/G=25kg, then we obtain an acceleration due to the disturbing force (FD) of 25/1000=25mG. If we now wish to introduce active control, we can assume K_a=9000kg and we now obtain a tenfold reduction in acceleration due to the disturbance, i.e., 25/(1000+9000)=2.5mG. We can thus conclude that if we proceed along these lines we will at least have an order of magnitude improvement in ride comfort.

Now, assuming a K_a of 9000kg is desired, we can assign an acceleration scale factor (ASF) of 100 Volt/G and a force generator scale factor (FGSF) of K_a/ASF which is equal to 9000kg/100Volt/G=90kg (force)/Volt or 882 Newton/Volt.

An electromagnetic actuator such as described previously may be constructed in a U-shape as shown in Figs. 29 and 30. In Fig. 29 double coils 300, 302 are shown which fit over legs 304, 306, respectively, as shown in Fig. 30. The coils 300, 302 constitute a

23 June 2004

continuous winding and are shown in isometric section in Fig. 30. Coil 300 and coil 302 may each, for example be wound with 936 turns of #11 AWG magnet wire at a 0.500 packing factor. The U-shaped core may, for example, be of interleaved construction, 29 GA M6 laminations made of 3.81cm strip stock, vacuum impregnated. The dimensions shown in Fig. 30 may be, for example; A=10.16cm, B=3.81cm, C=7.62cm and D=7.62cm. In that case, the resistance would be 6.7 ohms and the inductance 213mH. Such weighs 22.2kg and is capable of exerting 578 Newtons.

If we use such an electromagnetic actuator in a control system such as described previously we can expect an average delay in responding to a command of, say, 4.2 msec. The time delay to develop a full force, say, of 578 Newton at a maximum gap of 20 mm can be estimated at 15 msec as follows (based on the relation $v=Ldi/dt$):

$$\Delta t = L\Delta i/\Delta v = (0.3)(8.6)/(170) = 15 \text{ msec.}$$

The time to develop full force (578 Newton) at minimum gap (5 mm) would be:

$$\Delta t = L\Delta i/\Delta v = (1.2)(2.15)/(170) = 15 \text{ msec.}$$

as well.

The time to develop half force would of course be half the time. An accuracy in the gap signal of 10% of full scale can be tolerated. We can present the relation between the gap and several other factors in graphical form as shown in Figs. 26, 27 and 28. The maximum power is 500 Watts at a maximum allowed 20 mm gap. The average power can be expected to be approximately 125 Watts.

As for short term thermal considerations, the mass of the copper in such an electromagnet is 14.86 kg, having a specific heat of 0.092 cal/g-°C (=385J/kg°C). The change in temperature for a sixty second application of energy at a rate of 500 Watts will thus be:

$$\begin{aligned}\Delta T &= \text{Watt-sec}/(385)(14.86) \\ &= (500)(60)/(385)(14.86)\end{aligned}$$

23 June 2004

$$\Delta T = 5.24^{\circ}\text{C}.$$

Thus, there is little temperature rise even for maximum power input for one minute.

Fig. 31 shows a single-axis lateral vibration stabilization system for use in a system such as shown in Fig. 14D. The concept is the same as shown in Figs. 18, 24, and 25. The implementation to be described will be analog but it will be understood that it can be carried out digitally as well. In this case, a plate 352 is attached, without limitation, to the suspended cab while a pair of electromagnetic actuators 354, 356 are attached to the elevator car frame. The accelerometer 358 senses accelerations of the suspended cab and provides a sensed signal on a line 360 to an amplifier 362 which in turn provides an amplified sensed acceleration signal on a line 364 to a summing junction 366 where it is "summed" with a disturbing force signal on a line 368 and a position loop corrective or "error" signal on a line 370.

A resultant summed signal on a line 372 is provided to a pair of rectifiers 374, 376 which are shown respectively in Figs. 33 and 34. The rectifier 374 provides a signal on a line 378 to a signal inverter 380, which is also shown in Fig. 34, and which provides a signal on a line 382 which may be characterized as a negative control signal. Similarly, the rectifier 376 provides a signal on a line 384 which may be characterized as a positive control signal. Both the signals on lines 382 and 384 are summed in respective summing junctions 388, 390 with a bias signal on a line 392. These provide biased control signals on lines 394, 396 to electromagnetic actuator controllers 398, 400, respectively. The controllers 398, 400 are or may be similar to those shown in Fig. 20.

The effect of the bias signal on line 392 is illustrated in Fig. 32 which shows the composite resultant force (in dashed lines) of the two forces on either side of the reaction plate 352 (in solid lines)

23 June 2004

vs. the control signal (FC) for the system of Fig. 31.

This technique is used to prevent discontinuities in control about the zero position point. Without bias, turn-off of one magnet and turn-on of the other could occur at the same time. The illustrated technique, using bias, results in reduced control gain at or near zero force. The advantage is that only one magnet goes from on to off or vice versa at any given time. Bias helps assure that "dither" of the cab will not occur during periods requiring little or no correction.

The signals on lines 394 and 396 may be thought of as force command signals similar to the force command signal on line 382 in Fig. 20. Similarly, the controls 398, 400 provide actuator output signals on lines 402, 404 to actuators 356, 354, respectively, in a manner similar to the output signal on line 500 in Fig. 20.

In similar fashion each control 398, 400 provides position output signals 406, 408 corresponding to the gap signal on line 396 in Fig. 20.

For purposes of the position loop, both position signals on line 406, 408 and the corresponding, but opposite sided, rectification signal on lines 384, 378 are provided to a pair of FC-controlled clamp circuits 410, 412 for the purpose of selection of the valid position signal (both P_+ and P_- provide position signals; however, only the position signal corresponding to the driven force generator is valid).

The outputs of the clamp circuits are provided to a summing junction 414 for the purpose of obtaining the valid position signal. Also provided to the summing junction 414 is an attenuated acceleration signal on a line 415 from an attenuator 415a responsive to the amplified acceleration signal on line 364.

Both of the FC-controlled clamps 410, 412 and the summing junction 414 are shown in more detail in Fig. 35. The output of the summing junction is a composite

23 June 2004

position and acceleration signal on a line 416 which is provided to a low pass filter 418 which has a time constant in the range of 1 to 10 seconds. The low pass filter 418 in turn provides the corrective signal on the line 370 to summing junction 366, previously described.

Three single-axis controls such as just described can be used for the actuators of Fig. 14D in lieu of the combined three-axis schemes described previously in connection with Figs. 14C and 15. However, the three-axis scheme has many advantages. Among these are stabilization of all sensitive axes using a minimum number of electromagnets. Furthermore, the gap motion will be $\cos 45^\circ = 0.707$ of the motion in the x or y direction. Thus, a plus or minus 15 mm gap variation for a single-axis or multiple-single-axis system reduces to a plus or minus 10.5 mm variation in a three-axis scheme. In Figs. 14C and 15, only four electromagnets are used and, also, only four power-electronic controllers are needed. Since magnets are used two-at-a-time in Figs. 14C and 15, magnet size can be reduced. Thus, use of magnets half the strength of those needed for the single-axis approach suffices for a commercially viable system.

Fig. 36A is another block diagram of a specific implementation of an active suspension system, according to the present invention. For one axis (e.g., side-to-side along the X-axis passing through the car's vertical centerline), and for the other axes (e.g., front-to-back along two axes parallel to the Z-axis and lying, e.g., equidistantly from and on opposite sides of the vertical centerline), there is a separate feedback loop, but only a single axis is shown in Fig. 36A. An acceleration reference signal may be input on a line 100 and may be set to zero. The difference between the reference signal on the line 100 and a measured car acceleration signal on a line 102 forms an error signal on a line 104, which is in turn fed into a feedback compensator 106 labelled $C(s)$.

23 June 2004

The summing junction 109 is shown responsive to the compensator output and to disturbances of the indirect type, such as rail disturbances, as provided by the system dynamics 109a and of the direct type of disturbance, such as wind forces, as provided by system dynamics 109b.

C(s) may be characterized as follows:

DC Washout Pendulum Compensation Control

$$\frac{F_{cmd}}{Accel} = \frac{s}{s + \omega_1} \cdot \frac{s^2 + 2\zeta_p \omega_p s + \omega_p^2}{GOL \cdot s^2} \cdot \frac{s^2}{Gain(s + \frac{1}{4}\omega_1)(s + \omega_o)^2(s + 4\omega_2)}$$

ω_1 = Low Control band frequency [rad/s]
 ω_2 = High control band frequency [rad/s]
 ω_o = $\sqrt{(\omega_1 \cdot \omega_2)}$
 Gain = Control gain selected so that loop gain @ $\omega_1 \omega_2 = 1$
 GOL = Open loop system gain [mg] N
 ω_p = Pendulum resonant frequency [rad/s]
 ζ_p = Pendulum damping ratio

The first term covers DC washout, the second is for pendulum compensation, and the third term is for control.

The feedback compensator in each axis processes the car acceleration error signal for that axis to generate actuator commands. In this case, a force command signal is provided on a line 110. These compensators can be viewed as dynamic filters whose properties (gain and phase vs. frequency) are designed to meet elevator system requirements. The design of C(s) can be recast into design requirements on the overall loop gain, labelled L(s), which is the product of C(s) and the plant dynamics as illustrated in a block 108, labelled G(s).

Conceptually, the force command signal on the line 110 is provided to plant dynamics 108. As shown in Fig. 36B, in regions where car acceleration is to be minimized, the

23 June 2004

loop gain is made to be greater than one, i.e., in a region about a frequency ω_0 . At high frequencies, above ω_2 , the loop gain is "rolled off" to meet stability robustness requirements. At low frequencies, below ω_1 , the loop gain is "washed-out" to reduce the effects of sensor noise and drift.

Based on the model of the pendulum car of U.S. Patent 4,899,852, we performed an analysis of the performance of an active suspension concept. Figs. 37A and 38B are actually a plot of the designed open loop transfer function for an active system, $L(s)$, that resulted from that analysis. A plot of the feedback compensator gain and phase angle are shown, respectively, in Figs. 38A and 38B for this particular design.

Figs. 39 through 41 summarize the results of a simulation study of the performance of the resulting active suspension system. The upper lefthand plots in each of these figures (labelled (a)) is the particular disturbing input (direct car force or rail profile). The remaining plots on each of these figures show the car acceleration response for three configurations: (1) pendulum car (upper-right, labelled (b)), (2) conventional car (lower-left, labelled (c)), and (3) active suspension using the control design of Figs. 36A, 36B, 37A, 37B, 38A, and 38B (lower-right, labelled (d)). It can be seen that this system reduces the levels of cab platform acceleration relative to conventional systems and even those of the pendulum car without active control.

Fig. 39 is the predicted response to butt joint misalignment.

Fig. 40 is the predicted response to rail waviness.

Fig. 41 is the predicted response to car force disturbance.

Tests have been conducted utilizing a half scale model of the elevator system shown in Figs. 14A and 14B. The effectiveness of the concept was performed using a

rotating imbalance mounted on the frame to simulate rail-induced disturbances and by simulating a direct disturbance force by means of an actuator between the frame and cab.

5 The feedback compensator 106 of Fig. 36A was implemented using a digital computer 100 as shown in Fig. 42. Sensor 102 data is provided on a line 103 into a 12-bit A/D converter (not shown) to be processed after passing through an Input/Output Port 104. A digital form
10 of the feedback compensator 106 was utilized to produce a command signal on a line 106 to an actuator capable of exerting forces on a car 110.

15 The signal processor 100 comprises a central processing unit 104a, a read-only memory 104b, a random access memory 104c, all communicating by means of data, address, and control bus 104d.

20 Fig. 43 is an illustration of a series of steps which may be carried out by the signal processor 100 of Fig. 42. For example, after entering in a step 112, acceleration is sensed in a step 114 by means of an accelerometer, such as sensor 102. The processor then computes the magnitude of a counteractive force by implementing the dynamic compensation 106. A step 118 is
25 next executed in which the signal processor 100 provides the counteraction signal on line 106 which may be a counterforce signal, such as the signal on line 106 and as computed in step 116. An exit is then made in a step 120.

30 Fig. 44 shows the results of a test to evaluate the effectiveness of the active system in mitigating direct car forces. The plot shows the ratio of the measured car acceleration to the magnitude of the sinusoidal input force over a sweep of frequencies. The top curve is the response of the pendulum car system without active
35 suspension control. The bottom curve response of the active suspension system verifies the expected 80%-90% reduction. Fig. 45 shows a comparison of the predicted

23 June 2004

time response (via simulation in Figs. 45B and D) and the achieved (experimental) time response (Figs. 45A and C) for direct car force mitigation.

5 This reduction in the system sensitivity to direct car forces was achieved without compromising the performance of the system in the presence of rail-induced disturbances. Fig. 46 illustrates the response of the system to a rail irregularity as simulated on a test bed with a rotating imbalance. Fig. 46A shows the
10 unaugmented pendulum car response to a 3 Hz input frequency. Fig. 46B is the response of the active suspension system. It can be seen that the magnitude of the car acceleration has been decreased. Thus, the active suspension system improves the ride quality using
15 car acceleration as the metric of performance in the presence of both rail-induced disturbances and direct car forces.

In any event, the actuator command signal on line 106 as shown in Fig. 42 may be a force command signal, as
20 previously explained, and as shown in more detail in Fig. 47, as being applied to a particular actuator which may include, for example, the core-coils and ferromagnetic plates of Figs. 29 and 30.

In Fig. 47, the force command signal on line 106
25 from the signal processor 100 of Fig. 42 is provided to a PWM amplifier which may be made by Copley Controls Corp. of 375 Elliot Street, Newton, Massachusetts, U.S.A., and called a "Class B PWM Servo Amplifier Model 218A" as described in published specification sheet entitled
30 "Model 215A, 218 Servo Amplifier". The PWM Amplifier 150 is responsive also to a force feedback signal on a line 152. The PWM amplifier serves as an electronic double pole-double throw switch to apply a selected voltage to lines 154, 156 with a polarity reversal at a selected duty
35 cycle. A pair of steering diodes 158, 160 steer the output current on either line 154 or 156 into the proper coil of the corresponding magnet 130, 132. It will be

23 June 2004

understood that either the ferromagnetic mass 134 or the electromagnets will be erected on the base of the frame 26 while the other element is erected on the bottom surface of the platform 14. In a preferred embodiment, the electromagnets 130, 132 are erected on the bottom of the frame 26 while the ferromagnetic mass 134 is fixedly attached in a hanging down fashion to the bottom of the platform 10b. This is the case for the other actuators 240, 244 of Fig. 14D as well.

In order to construct an effective feedback loop, Hall cells 170, 172 may be placed in the magnetic circuit path so as to sense magnetic flux in the gap between the ferromagnetic plate 134 and the respective cores of core-coils 130, 132. The Hall cells 170, 172 provide sensed flux signals on lines 174, 176, respectively, to a device 182, which may be a multiplying IC such as an AD 534, which squares the magnitudes of the flux signals on lines 174, 176 and provides a difference signal indicative of the difference therebetween as the force feedback on line 152.

Again, the control represented in abstracted form in Figs. 36A and 36B may be carried out in numerous different ways, including a wholly digital approach similar to that of Fig. 42, but a preferred approach is shown in Fig. 48. The embodiment of Fig. 48 includes two such independent control systems, each for controlling actuators on opposite sides of the car, identical or similar to that illustrated in Fig. 15, one system for the floor or near the bottom of the car, and the other system for the ceiling or near the top of the car.

Of course, the fundamental principal of active control can be carried out in a plurality of coordinated single axis controls as previously suggested. Thus, the control represented in abstracted single-axis form in Fig. 36A may be carried out in numerous different ways but a preferred approach is to extend the same principles as disclosed in the three-axis control of Fig. 15 to

23 June 2004

achieve the five-axis control shown in Fig. 48. Although shown for a car, the same principles shown in Fig. 48 may be extended to a pendulum or supported cab, as will be apparent to one skilled in the art.

5 In Fig. 48, fast-acting analog loops for quickly counteracting disturbing forces are combined with slower acting but more accurate digital loops for compensating for gravity components and drifts in the accelerometers. A plurality of such fast-acting analog loops may be embodied in analog controls 500, 502, 504, 506, for 10 independently controlling the top of the car, and analog controls 508, 510, 512, 514 for independently controlling the floor of the car as shown, one for each of eight actuators 516, 518, 520, 522, and 524, 526, 528, 530, 15 respectively. With proper interfacing (not shown), a single digital controller 532 can handle the signals to be described to and from all eight analog controls. Each analog control responds to a force command signal on lines 534, 536, 538, 540, and 542, 544, 546, 548 from the 20 digital controller 532. The force command signals will have different magnitudes depending on the translational and rotational forces to be counteracted. The digital controller 532 is in turn responsive to acceleration signals on lines 552, 558, 559, and 550, 554, 556 from 25 the accelerometers 562, 568, 569, and 560, 564, 566, respectively, and to position signals on lines 570, 572, 574, 576, and 578, 580, 582, 584 indicative of the size of the air gaps between the cores of actuators 516, 518, 520, 522, and 524, 526, 528, 530 and their respective 30 facing ferromagnetic blades.

 In response to the force command signals on lines 534, 536, 538, 540, and 542, 544, 546, 548, the respective analog controls 500, 502, 504, 506, and 508, 510, 512, 514 provide actuation signals on lines 586, 35 588, 590, 592, and 594, 596, 598, 600 to the coils of the actuators 516, 518, 520, 522, and 524, 526, 528, 530 for causing more or less attractive forces between the

23 June 2004

respective actuator cores and their associated ferromagnetic blades. The return current through the coils is monitored by current monitoring devices 602, 604, 606, 608, and 610, 612, 614, 616 which provide
5 current signals on lines 618, 620, 622, 624, and 626, 628, 630, 632 to the respective analog controls 500, 502, 504, 506, and 508, 510, 512, 514. The current sensors may be, e.g., Bell IHA-150.

10 A plurality of sensors 634, 636, 638, 640, and 642, 644, 646, 648 which may be Hall cells (e.g., of the type Bell GH-600), are respectively associated with each actuator core for the purpose of providing an indication of the flux density or magnetic induction (volt-sec/m²) in the gap, i.e., between the faces of the cores and the
15 associated blades or, otherwise stated, the flux density in the air gaps therebetween. The sensors 634, 636, 638, 640, and 642, 644, 646, 648 provide sensed signals on lines 650, 652, 654, 656, and 658, 660, 662, 664, respectively, to the analog controls 500, 502, 504, 506,
20 and 508, 510, 512, 514.

The analog control 500 among the plurality of analog controls of Fig. 48, is similar or identical to that shown in greater detail in Fig. 20. The other analog controls may be the same or similar.

25 As mentioned previously, the digital controller 532 is responsive to the gap signals on the lines 570, 572, 574, 576 and 578, 580, 582, 284, as well as the acceleration signals on lines 552, 558, 559, and 550, 554, 556, for carrying out, in conjunction with an analog
30 control, such as shown in Fig. 20, the single axis control functions of Fig. 36A in five axes, i.e., translations along two horizontal axes in both the floor and roof, rotations about the same two axes in both the floor and roof, and rotations of both floor and roof
35 about a vertical axis.

To be more precise, for the best mode embodiment of this aspect of the invention, we are describing control

23 June 2004

actions with respect to nine axes, i.e., two translational axes and two rotational axes in both floor and ceiling and one rotational axis about vertical common to both floor and ceiling. However, if the horizontal axes in the floor and ceiling are approximated for descriptive purposes by a single set of horizontal axes in a plane midway between the top and bottom of the car or cab, then we can speak of "five axes" of control. In this way, for a purpose of descriptive simplification, but not by way of limitation, regardless of the actual stiffness or lack thereof in the structural connection between the floor and ceiling, we may view the car or cab as a solid or stiff cube having a three axis Cartesian coordinate system with its origin in the center and subject to translations along, and rotations about, the horizontal axes and rotations about the vertical axis.

The force command signals in both the floor and at the top of the car or cab may be generated, for example, by first resolving the sensed position (gap) signals into components along the axes of the Cartesian coordinate system 30 of Fig. 3 (which would be located with its origin in the plane of the floor or ceiling depending on which independent control system is being treated) as in the equations which follow,

$$\begin{aligned} P_{x+} &= (P_1 + P_3)/(2KCS), & P_{x-} &= (P_2 + P_4)/(2KCS), \\ P_{y+} &= (P_1 + P_2)/(2KCS), & P_{y-} &= (P_3 + P_4)/(2KCS), \\ P_{\theta+} &= (P_2 + P_3)/2, & P_{\theta-} &= (P_1 + P_4)/2, \end{aligned}$$

and then, based on the above, computing or selecting P_x , P_y , and P_θ (which together specify the absolute position of the car or cab), from P_{x-} and P_{x+} , P_{y-} and P_{y+} , and $P_{\theta+}$ and $P_{\theta-}$. P_x , for example, may be computed as follows:

$$P_x = (P_{x+} - P_{x-})/2.$$

Or, one can select P_{x+} or P_{x-} , depending on which quantity is smaller. (Note: For large gaps, i.e., for large P_{x+} or P_{x-} , the value is likely to be inaccurate and

23 June 2004

may be discarded). The resultant components are used to determine position-control force components F_{px} , F_{py} , $F_{p\theta}$ as illustrated in Fig. 48 on a single-axis basis ("P" stands for position feedback). P_x , for example on line 348, is compared to a reference on line 352 to generate an x-position error signal on line 354. This in turn is passed through a low-pass such as filter 358. This provides an F_{px} signal. For purposes of resolving the required x-counterforce, if a positive force is required, $F_{p1}=F_{p3}=(0.5)(F_{px})/(\cos 45^\circ)$. For a negative force, $F_{p2}=F_{p4}=(0.5)(F_{px})/(\cos 45^\circ)$. This same procedure may be followed for F_{py} and $F_{p\theta}$ using, of course, the appropriate equations. Thus, the force components F_{px} , F_{py} and $F_{p\theta}$ may be resolved into corrective signals F_{p1} , F_{p2} , F_{p3} , F_{p4} , according to the following complete set of equations,

$$\begin{array}{ll} F_{px+}: F_1 = (KCS)(F_{px+}) & F_{px-}: F_2 = (KCS)(F_{px-}) \\ & F_4 = (KCS)(F_{px-}) \\ & F_3 = (KCS)(F_{px+}) \\ F_{py+}: F_1 = (KCS)(F_{py+}) & F_{py-}: F_3 = (KCS)(F_{py-}) \\ & F_4 = (KCS)(F_{py-}) \\ & F_2 = (KCS)(F_{py+}) \\ F_{p\theta+}: F_2 = (KCS)(F_{p\theta+}) & F_{p\theta-}: F_1 = (KCS)(F_{p\theta-}) \\ & F_4 = (KCS)(F_{p\theta-}) \\ & F_3 = (KCS)(F_{p\theta+}) \end{array}$$

where F = force, and

$$KCS = \cos(45^\circ) = \sin(45^\circ) = 0.707,$$

which are then summed with the acceleration signals F_1 , F_2 , F_3 , F_4 (such as the signal on line 364 or line 382 of Fig. 20) generated in the manner previously described.

It should be realized that a valid position reading will only be available from the flux sensors of the type described if its associated force actuator is being driven. This means that any processing algorithm must be dependent upon whether or not there are magnet coil actuation currents present.

An additional teaching of our invention is that the electromagnets may be used to control the position of the car or cab at stops, e.g., to bring the suspended or supported car or cab to rest with respect to the frame

23 June 2004

while on- and off-loading passengers. Of course, the signal processor of Fig. 16, the digital controllers 380, 532 of Figs. 19 and 48 or an additional signal processor may handle additional control functions such as the
5 starting and stopping of cars and the dispatching of cars. In the case of stopping at a floor, it may receive a sensed signal on line 18 or an algorithmically determined but similar signal indicating the car is at rest and will then provide a signal on line 22 to control
10 the position of the suspended or supported car or cab. To repeat the previous example, if the cab platform 200 of Fig. 14C is oriented in the hoistway such that the left hand vertical edge of the cab represents the cab's sill in alignment with a hoistway door sill 700, then the
15 signal processor 20 of Fig. 16 may be programmed to provide force command signals to actuators 210, 214 in order to provide the attractive forces needed to force the suspended cab up against, e.g., stops 702, 704 mounted in the car frame 202 so as to push the cab sill
20 into position at rest with respect to, and in close alignment with the hoistway entrance sill after the frame 202 comes to rest.

The method used to accomplish the same is shown in Fig. 51 where a stop signal is provided in a step 720
25 from means 722 (which may be incorporated in the processor 532 in an additional role of controlling a car or group of cars) for indicating the car frame has come to rest, providing a stop or stop command signal and, in response thereto, an actuator 724 (which may be actuators
30 210 and 214 acting in concert) provides an actuating signal as shown in a step 726 for causing a suspended cab 728 (which may be cab 200) to come to rest with respect to the car frame (which may be frame 202) such that the cab sill is adjacent to the hall sill and motionless with
35 respect thereto.

A similar set of stops 730, 732 can be provided at each landing for the car of Fig. 15 to be pushed against

23 June 2004

and a similar procedure as that of Fig. 51 can be followed.

It should be understood that although a preferred embodiment of the invention utilizes electromagnetic, noncontact type actuators and, in particular, in connection with a suspended or supported car uses electromagnetic actuators such as are shown in Fig. 15 in conjunction with hoistway rails, it is also possible to employ contact-type, active actuators. For example, Fig. 49 shows a standard rail 750 attached to a hoistway wall 752 having three contact-type actuators having wheels 754, 756, 758 in contact therewith for guiding an elevator car. Fig. 50 shows one of the actuators 760 in detail having wheel 754 associated therewith actuated with a solenoid 762 having a coil 764 similar to a coil which would be used in an electromagnetic actuator of the previously disclosed, contact-less type. The other wheels 756, 758, would have similar solenoids associated therewith.

Referring back to Fig. 49, it is, of course, standard practice to provide one or more guide rails for each elevator car in an elevator system to guide and stabilize the car as it moves up and down between floors. In such guide rails, wheels mounted by means of springs on the car typically ride on the rail for guidance and motion control of the car.

Since an elevator car needs to be guided to remain along the specified path of travel, the guide rails have to withstand all the forces that may result from, for example, normal elevator operation and emergency stops. In general, the guide rail can be of any shape capable of constraining the elevator in its path. The problem then becomes finding the most economical shape.

It is now standard for such rails to have an inverted "T" shaped section, with the elevator car having three wheels riding on different parts of the guide rail typically in the arrangement as shown in Fig. 49. As can

23 June 2004

be seen in that figure, two of the wheels are directly opposed, while the third rides on the bottom foot of the "T" between the other two.

However, one problem with this standard inverted "T" rail is that it weighs a relatively significant amount in comparison to its strength and therefore does not have as great a ratio of strength to weight as may be desired.

The present invention is designed to provide an improved guide rail design, which can achieve at least the same amount of strength with relatively less weight or to at least to achieve a higher strength to weight ratio than that of the standard inverted "T" section rail, while still achieving a comparable (if not equal or greater) amount of guidance and stabilization control as achieved by the standard, established design. Moreover, the improved design is particularly suited to the use suggested in Figs. 5 and 7.

Although others, including a relative of the very "father" of the elevator, have suggested other configurations for the guide rails, for example, one with a "V" shaped section with two wheels riding on the exterior, diverging sides of the "V" (note e.g. U.S. Patent No. 134,698 issued Jan. 7, 1873 to Charles R. Otis), each of these, it is believed, fail to achieve the desired combination of control with as good a strength to weight ratio as achieved in the present invention.

Another configuration known is a round tubular shape, similar to a pipe, but this design has generally been limited to cases where emergency stopping by safety brakes is not necessary. Other shapes considered for guide rails have included, for further example, a "hat" shape somewhat like an inverted, flat bottomed, inverted "U" with end tabs, a "bell" shape, and a rectangular tubular shape.

For further background or general information on an overall elevator car guide system and its mountings and interrelationships with other parts of the elevator

23 June 2004

system, using the standard, established "T" shaped section, see, for example, U.S. Patent 4,793,441 issued Dec. 27, 1988 to Cilderman et al entitled "Elevator Car System with Three Guide Rails." See also, for further
5 example, U.S. Patent 3,669,222 issued June 13, 1972 entitled "Guiding and Dampening Device" of Takamura et al, and U.S. Patent 4,754,849 issued July 5, 1988 entitled "Control System for Elevator Cage Guide Magnets" of Ando.

10 As can be seen in Figs. 53 and 54, the preferred embodiment of the longitudinally extended guide rail 1 of this aspect of the present invention includes a base or blade section 2 with two, preferably integrally formed, diverging blades or legs 3 with the legs terminating in
15 end tab portions 4. The end tab portions are used for mounting and fastening the guide rail 1 to the building structure. The two diverging legs form between them a void 3A.

As can be seen in Fig. 53, three guide wheels 5A, 5B
20 and 5C interface with the base or blade section 2, in similar fashion and configuration as they did with the "T" shape guide rail, as illustrated in Fig. 52. The two opposed wheels 5A and 5B bear against the opposed sides of the blade section 2, while the intermediate wheel 5C
25 bears against the distal tip of the blade section.

The comparative characteristics of the "T" shape and the "Y" shape are compared in detail in the chart of Fig. 55, using an exemplary sixty-six and 72/100 Newton (66.72 NT) "T" rail for comparative purposes. Tables 1 and 2 of
30 Fig. 55 give the corresponding dimensions and properties of the two shapes, showing that the corresponding Y-shape can replace the present, prior art "T" rail with savings in weight of about eighteen (18%) percent.

Thus, as can be further seen from Table 2, the Y-
35 shape of the invention is slightly better in section properties than the corresponding T-shape and yet weighs eighteen (18%) percent less. The overall dimensions of

23 June 2004

both shapes are almost the same (Table 1), namely, twelve and seven-tenths centimeters by eight and 89/100 centimeters (12.7 cm x 8.89 cm) for the T-shape and thirteen and 02/100 centimeters by nine and 53/100 centimeters (3.02 cm x 9.53 cm) for the Y-shape.

It is noted that all present equipment such as roller guides, sliding guides, safeties, etc., used at present with the T-shape rail, can also be used with the Y-shape of the invention without any change. It is also noted that the legs or blades 3 of Fig. 53 can be used to support wheels or electromagnetic flux as shown in Fig. 54.

The Y-shape rails of the invention can be rolled in-steel mills in pieces of desired length, for example, four and 88/100 meters (4.88 m) each. Machining of the blades can be done easily in milling or planing machines, in similar fashion to that done for the "T" rail. Cutting of mating slots at the end and drilling of holes in the "Y" shaped guide rail would typically be included and are made as easy as in the "T" shaped rail.

Figs. 56 and 57 are still other illustrations of an embodiment of means for carrying out the present invention, in the form of an "active" roller guide, showing details of a roller cluster 1000. Although one of the rollers (side-to-side) is elevated with respect to the other two, it will be appreciated that the roller cluster 1000 is a relatively conventional arrangement of rollers on a rail 1001. However, we are only aware of such clusters being used passively and we know of no such prior art roller cluster used with actuators.

The cluster 1000 includes a side-to-side guide roller 1002 and front-to-back guide rollers 1004 and 1006. The roller cluster 1000 is mounted on a base plate 1008 which is fixed to an elevator cab frame crosshead (not shown). The guide rail 1001 will be a conventional, generally T-shaped structure having basal flanges 1010 for securement to the hoistway walls 1012, and a blade

23 June 2004

1014 which projects into the hoistway toward the rollers 1002, 1004 and 1006. The blade 1014 has a distal face 1016 which is engaged by the side-to-side roller 1002, and side faces 1018 which are engaged by the front-to-back rollers 1004 and 1006. The guide rail blade 1014 extends through a slot 1020 in the roller cluster base plate 1008 so that the rollers 1002, 1004 and 1006 can engage the blade 1014.

As shown most clearly in Fig. 57, the side-to-side roller 1002 is journaled on a link 1022 which is pivotally mounted on a pedestal 1024 via a pivot pin 1026. The pedestal 1024 is secured to the base plate 1008. The link 1022 includes a cup 1028 which receives one end of a coil spring 1030. The other end of the spring 1030 is engaged by a spring guide 1032 which is connected to the end of a telescoping ball screw adjustment device 1034 by a bolt 1036. The adjuster 1034 can be extended or retracted to vary the force exerted on the link 1022, and thus on the roller 1002, by the spring 1030. The ball screw device 1034 is mounted on a clevis 1038 bolted to a platform 1040 which in turn is secured to the base plate 1008 by brackets 1042 and 1044. The use of the platform 1040 and brackets 1042 and 1044 allows the assembly to be retrofitted on a conventional roller guide assembly directly on the existing base plate 1008. The ball screw device 1034 is powered by an electric motor 1046. A ball screw actuator suitable for use in connection with this invention can be obtained from Motion Systems Corporation, of Box 11, Shrewsbury, New Jersey 07702. The actuator motor 1046 can be an AC or a DC motor, both of which are available from Motion Systems Corporation. The Motion systems Model 85151/85152 actuator has been found to be particularly suitable for use in this invention. These devices have the AC or DC motor 1046 attached to a gear reducer 1048 for motor speed reduction to drive the ball drive actuator which is an epicyclic ball screw 1034, only the

23 June 2004

cover of which is shown. Or, a brushless DC motor may be provided. Although shown only schematically, a position sensor 1049 such as a potentiometer or optical sensor may be attached to the car frame by attachment to the reducer 1048 to a lip on the rear of the spring holder 1032 in order to measure the linear extension of the screw. Of course, other position sensors may be used as well.

The guide roller 1002 is journaled on an axle 1050 which is mounted in an adjustable receptor 1052 in the upper end of the link 1022. A pivot stop 1054 is mounted on a threaded rod 1056 which extends through a passage 1058 in the upper end 1060 of the pedestal 1024. The rod 1056 is screwed into a bore 1062 in the link 1022. The stop 1054 is operable by selective engagement with the pedestal 1024 to limit the extent of movement of the link 1022 in the counter-clockwise direction about the pin 1026, and therefore limit the extent of movement of the roller 1002 in a direction away from the rail, which direction is indicated by an arrow D. The pedestal 1024 is formed with a well 1064 containing a magnetic button 1066 which contains a rare earth compound. Samarium cobalt is a rare earth compound which may be used in the magnetic button 1066. A steel tube 1068 which contains a Hall effect detector (not shown) proximate its end 1070 is mounted in a passage which extends through the link 1022. The magnetic button 1066 and the Hall effect detector form a proximity sensor which is operably connected to a switch controlling power to the electric motor 1046. The proximity sensor detects the spacing between the magnetic button 1066 and the steel tube 1068, which distance mirrors the distance between the pivot stop 1054 and the pedestal 1024. Thus as the tube 1068 and its Hall effect detector moves away from the magnet 1066, the pivot stop 1054 moves toward the pedestal 1024. The detector produces a signal proportional to the size of the gap between the detector and the magnetic button 1066, which signal is used to control the electric motor

23 June 2004

1046 whereby the ball screw 1034 jack is caused to move the link 1022 and roller 1002 toward or away from the rail, as the case may be. Depending on the type of control system employed, the stop 1054 may be prevented from contacting or at least prevented from establishing prolonged contact with the pedestal 1024. This ensures that roller 1002 will continue to be damped by the spring 1030 and will not be grounded to the base plate 1008 by the stop 1054 and pedestal 1024. Side-to-side canting of the car by asymmetrical passenger loading or other direct car forces is also corrected. As mentioned, the electric motors 1046 can be reversible motors whereby adjustments on each side of the cab can be coordinated in both directions, both toward and away from the rails.

Referring now to Figs. 56, 57 and 58, the mounting of the front and back rollers 1004, 1006 on the base plate 1008 will be clarified. Each roller 1004, 1006 is mounted on a link 1070 connected to a pivot pin 1072 which carries a crank arm 1074 on the end thereof remote from the roller 1004, 1006. Axles 1076 of the rollers 1004, 1006 are mounted in adjustable recesses 1078 in the links 1070. The pivot pin 1072 is mounted in split bushings 1080 which are seated in grooves 1082 formed in a base block 1084 and a cover plate 1086 which are bolted together on the base plate 1008. A flat spiral spring 1088 (see Fig. 59) is mounted in a space 1089 (see Fig. 56) and has its outer end 1090 connected to a rotatable collar (not shown) which is rotated by a gear train (not shown) mounted in a gear box 1094, which gear train is rotated in either direction by a reversible electric motor 1096. The spiral spring 1088 is the suspension spring for the roller 1006, and provides the spring bias force which urges the roller 1006 against the rail blade 1018. The spiral spring 1088, when rotated by the electric motor 1096 also provides the recovery impetus to the roller 1006 through crank arm 1074 and pivot pin 1072 to offset cab tilt in the front-to-back directions caused

23 June 2004

by front-to-back direct car forces such as asymmetrical passenger loading of the car.

A rotary position sensor (not shown) such as an RVDT, a rotary potentiometer or the like, may be provided for fulfilling the function of the sensor 127a of Fig. 9. Such sensor may be attached at one end to the crank arm 1074 and on the other to the base 1008.

Each roller 1004 and 1006 can be independently controlled, as shown below in Fig. 69, by respective electric motors and spiral springs if desired, or they can be mechanically interconnected and controlled by only one motor/spring set, as shown in Figs. 56 and 60.

Details of an operable interconnection for the rollers 1004 and 1006 are shown in Fig. 60. It will be noted in Figs. 58 and 60 that the links 1070 have a downwardly extending clevis 1098 with bolt holes 1100 formed therein. The link clevis 1098 extends downwardly through a gap 1102 in the mounting plate 1008. A collar 1104 is connected to the clevis 1098 by a bolt 1106. A connecting rod 1108 is telescoped through the collar 1104, and secured thereto by a pair of nuts 1109 screwed onto threaded end parts of the rod 1108. A coil spring 1110 is mounted on the rod 1108 to bias the collar 1104, and thus the link 1070 in a counter-clockwise direction about the pivot pin 1072, as seen in Fig. 60. It will be understood that the opposite roller 1004 has an identical link and collar assembly connected to the other end of the rod 1108 and biased by the spring in the clockwise direction. It will be appreciated that movement of the link 1070 in clockwise direction caused by the electric motor 1096 will also result in movement of the opposite link in a counter-clockwise direction due to the connecting rod 1108. At the same time, the spring 1110 will allow both links to pivot in opposite directions if necessary due to discontinuities on the rail blade 1018. A flexible and soft ride thus results even with the two roller links tied together by a connecting rod.

23 June 2004

As shown in Fig. 60, a stop and position sensor assembly similar to that previously described is mounted on the link 1070. A block 1112 is bolted to the base plate 1008 below an arm 1114 formed on the link 1070. A cup 1116 is fixed to the block 1112 and contains a magnetic button 1116 formed from a rare earth element such as samarium cobalt. A steel tube 1118 is mounted in a passage 1120 in the link arm 1114, the tube 1118 carrying a Hall effect detector in its lower end so as to complete the proximity sensor which monitors the position of the link 1070. A pivot stop 1122 is mounted on the end of the link arm 1114 opposite the block 1112 so as to limit the extent of possible pivotal movement of the link 1070 and roller 1006 away from the rail blade 1014. The distance between the pivot stop 1122 and block 1112 is proportional to the distance between the Hall effect detector and the magnetic button 1116. The Hall effect detector is used as a feedback signal operable to activate the electric motor 1096, for example, whenever the stop 1122 comes within a preset distance from the block 1112, whereupon the motor 812 will pivot the link 786 via the spiral spring 804 to move the stop 836 away from the block 824 or, as another example, in a proportional, proportional-integral, or proportional-integral-derivative type feedback loop so that the position signal is compared to a reference and the difference therebetween is more or less continually zeroed by the loop. The position sensor 1049 of Fig. 57 may also be used to keep track of the position of the actuator with respect to the base 1008 as described below in connection with Fig. 69. In any event, this movement will push the roller 1006 against the rail blade 1014 and will, through the connecting rod 1108, pull the roller 1004 in the direction indicated by the arrow E, in Fig. 60. The concurrent shifting of the rollers 1004 and 1006 will tend to rectify any cant or tilting of the elevator cab in the front-to-back direction caused, for example,

23 June 2004

by asymmetrical passenger loading.

Referring now to Figs. 56, 57 and 61, an electromagnet with coils 1130, 1132 is mounted on a U-shaped core 1134 which is in turn mounted on the bracket 1044. The bracket 1044 is itself mounted on the base plate 1008. As previously described, the shaft 1034 of the ball drive exerts forces along the axis of the ball screw against the pivoted link 1022. The link 1022 pivots at the point 1026 and extends down below the pivot point to the electromagnet coils 1130, 1132 and has a face 1138 separated from the core faces of the electromagnet core 1134 for receiving electromagnetic flux across a gap therebetween.

Fig. 62 is an illustration of the cup 1064, which should be of ferromagnetic material, with the rare earth magnet 1066 mounted therein. The depression in the cup may be 15 mm deep and have an inside diameter of 25 mm and an outside diameter of 30 mm, as shown, for example. The sleeve 1068 may have a length of 45 mm with an inside diameter of 12 mm and an outside diameter of 16 mm, for example. A hall cell 1140 is shown positioned near the opening of the tube 1068 so as to be in position to sense the flux from magnet 1066. The composition of the tube is ferromagnetic, according to the teachings of the present invention, in order to enhance the ability of the hall cell to sense the flux from the magnet and also to provide shielding from flux generated by the electromagnets mounted elsewhere on the roller guide.

Specification for Position Transducers

1. Magnetic transducer may be used.
2. Operating Range: 10 mm
3. Repeatability: 0.1 mm
4. Temperature Range: 0-55C
5. Temperature Coef.: <.02%/C
6. Magnetic Field 100 Gauss at a distance of 30 mm
- Sensitivity: should not affect transducer output by more than 0.5%.

23 June 2004

- 7. Power Voltage: 9-15 VDC
- 8. Leads: Use separate signal and power grounds. Use twisted shielded pairs.

5 Fig. 63 shows such a hall cell 1140a mounted on a face of the reaction plate 1138 with a projection 1134a of the electromagnet core 1134 onto the plate 1138 associated with coil 1130 (shown also in a projection 1130a) shown in Figs. 56, 57 and 61. The sensor can also
10 be mounted on the face of the core itself but could get overheated in that position.

Specification for Hall Sensor Assembly

- 1. Application is on or opposite face of electromagnet.
- 2. Operating Range: .05 to 1.0 Tesla
- 15 3. Accuracy: 5% tolerable, 2% desired
- 4. Scale Factor: 10 V/Tesla
- 5. Temperature Range: 0-55C
- 6. Temperature Coef.: <.02%/C
- 7. Thickness: Must not exceed 2.0 mm
- 20 8. Power Voltage: ± 12 to 15 VDC
- 9. Leads: Use separate signal and power grounds. Use twisted shielded pairs.

Turning again now to the front-to-back roller 1006,
25 a pair of electromagnets 1144, 1146 is shown in Fig. 57. A block 1148 portion of link 1070, shown in Fig. 58 in perspective and in Fig. 60 in section, has an extension 1150 shown in Figs. 57 and 60 (not shown in Fig. 58) having a face 1152 opposite a pair of core faces
30 associated with a core 1156 upon which coils 1144, 1146 are mounted, only one face 1154 of which is shown in Fig. 60.

Fig. 64 is a side view of a ferromagnetic core such as is used for mounting the coils 1130, 1132 of Fig. 56
35 or the coils 1144, 1146 of Fig. 57. The dimensions shown are in millimeters. Fig. 65 shows a top view of the same core with the depth dimensions shown along with a pair of

23 June 2004

coils shown in dashed lines. The core of Figs. 64 and 65 may be made of grain-oriented (M6) 29 gauge steel, mounted on an angle iron by means of a weld, for example. The coils 1130, 1132, for example, will be required in pairs, each having, for example, 1050 turns of wire having a diameter of 1.15 mm. The coil connection should be series with the possibility made for parallel reconnection. The wire insulation can be heavy (double) build GP200 or equivalent rated at 200C. The impregnation can be vacuum-rated at 180C or higher. The coil working voltage may be on the order of around 250 volts and the coil itself may be high potential to ground tested at 2.5 kilovolts or similar, as required. The coil leads for hookup may be stranded wire, having a diameter of 1.29 mm, and about 50 centimeters in length. The weight is approximately 2.0 kilograms, consisting of 0.8 kg of iron and 1.2 kg of copper. At an air gap of 2-10 mm with a flux density of about 0.6 Tesla, a force of about two hundred Newtons can be achieved. Such a design is adequate for the active roller guide disclosed above. It has a force capability reserve of more than twice needed.

Fig. 66 illustrates a pair of active roller guides 1140, 1142 mounted on the bottom of an elevator car 1144 for side-to-side control. Fig. 66 also illustrates a control for a corresponding pair of electromagnets 1146, 1148. Acceleration feedback is utilized in the described control circuit for the electromagnets, although other means of control may be used. Acceleration control will be described in detail in conjunction with position control of the high-force actuators in connection with Fig. 69. An accelerometer 1150 measures the side-to-side acceleration at the bottom of the platform, and it may be positioned inbetween the two active roller guides 1140, 1142. The direction of sensitivity of the accelerometer is shown by an arrow labelled S-S and would be perpendicular to the hoistway walls. A sensed signal on

23 June 2004

a line 1152 is provided to a signal processor 1154 which, in response thereto, provides a force command signal on a line 1156 to a second signal processor 1158 which may be made up of discrete components in order to provide faster response. The force command signal on line 1156 is summed with a force feedback signal on a line 1158 in a summer 1160 which provides a force error signal on a line 1162 to a steering circuit comprising a pair of diodes 1164, 1166. A positive force error signal will result in conduction through diode 1164 while a negative force error signal will result in conduction through diode 1166. In order to prevent abrupt turn-on and turn-off, action of the two electromagnets 1146, 1148 near the crossover between positive force response and negative force response as shown in Fig. 67, a bias voltage is provided to bias the left and right signals provided to the PWM controls. This is done by means of a pair of summers 1168, 1170 from a potentiometer 1172 which is biased with an appropriate voltage to provide the force summation technique illustrated in Fig. 67. This allows a smooth transition between the two electromagnets. A pair of pulse width modulated controls 1174, 1176 are responsive to summed signals from the summers 1168, 1170 and provide signals on lines 1178, 1180 having variable duty cycles according to the magnitudes of signals on line 1182, 1184 from the summers 1168, 1170, respectively.

The force feedback on line 1158 is provided from a summer 1186 responsive to a first force signal on a line 1188 and a second force signal on a line 1190. A squaring circuit 1192 is responsive to a sensed flux signal on a line 1194 from a Hall cell 1196 and provides the first force signal on line 1188 by squaring and scaling the flux signal on line 1194. Similarly, a squaring circuit 1198 is responsive to a sensed flux signal on a line 1200 from a Hall cell 1202. The pair of Hall cells 1196, 1202 are mounted on or opposite one of

23 June 2004

the core faces of their respective electromagnets in order to be in a position to sense the flux between the electromagnet and the respective arms 1204, 1206 of the roller guides 1140, 1142.

5 The signal processor 1154 of Fig. 66 will be programmed to carry out the compensation described in detail in connection with Figs. 18 and 24.

10 The signal processor 1158 of Fig. 66 is shown in more detail in Fig. 68. There, an integrated circuit 1230, which may be an Analog Device AD534, is responsive to the force command signal on line 1156, the first flux signal on line 1194, and the second flux signal on line 1200 and provides the force error signal on line 1162 as shown in Fig. 66. A PI controller 1252 amplifies the
15 force error signal and provides an amplified signal on a line 1254 to a 100 volt per volt (gain of 100) circuit to the precision rectifier or diode steering circuits 1164, 1166, similar to that shown in simplified form in Fig. 66. An inverter 1258 inverts the output of steering
20 circuit 1164 so that signals on lines 1260, 1262 applied to summers 1168, 1170 are of corresponding polarities. The summed signals on lines 1182, 1184 are provided to PWM controllers which may be a Signetics NE/SE 5560 type
25 controllers. These provide variable duty cycle signals on the lines 1178, 1180, which are in turn provided to high voltage gate driver circuits 1260, 1262 which in turn provide gating signals for bridge circuits 1264, 1266 which provide current to the electromagnets 1146, 1148.

30 Amplifiers 1268, 1270 monitor the current in the bridge and provide a shutdown signal to the PWM controls 1174, 1176 in the presence of an overcurrent.

35 Also, a reference signal can be provided by a potentiometer 1272 to a comparator 1274 which compares the output of current sensor 1270 to the reference signal and provides an output signal on a line 1276 to an OR gate 1278 which provides the signal on line 1276 as a

23 June 2004

signal on a line 1280 to the high voltage gate driver
1262 in the case where the signal from the current sense
1270 exceeds the reference from reference potentiometer
1272. Also, a thermistor or thermocouple can be used on
5 the heat sink of the circuit shown in order to be
compared to an over-temperature reference signal on a
line 1284 in a comparator 1286. The comparator 1286 will
provide an output signal on a line 1288 to the OR gate
1278 in cases where the temperature of the heat sink
10 exceeds the over-temperature reference. In that case,
the signal on the line 1280 is provided to the high
voltage gate driver to shut down the H-bridge. Although
most of the above-described protective circuitry of a
current and over-temperature is not shown for the H-
15 bridge for magnet number 1 (1146), it should be realized
that the same can be equally provided for that bridge,
but is not shown for purposes of simplifying the drawing.

Turning now to Fig. 69, a system-level diagram is
presented to show a control scheme for a pair of opposed
20 guides such as the side-to-side active roller guides
1140, 1142 of Fig. 66. The diagram includes both
acceleration feedback as described, for example, in
detail above for the pair of small actuators 1146, 1148
and position feedback for a pair of high-force actuators
25 such as the screw actuators 1300, 1302. It should be
understood that the scheme of Fig. 69 is also applicable
to independently controlled opposed (on opposite sides of
the same rail blade), front-to-back suspensions, i.e.,
for those not mechanically linked as in Fig. 60. The
30 elevator car mass 1304 is shown in Fig. 69 being acted on
by a net force signal on line 1306 from a summer 1308
which is responsive to a disturbing force on a line 1310
and a plurality of forces represented on lines 1312,
1314, 1316, 1318, 1320, and 1322, all for summation in
35 the summer 1308. The disturbing force on line 1310 may
represent a plurality of disturbing forces, all
represented on one line 1310. These disturbing forces

23 June 2004

may include direct car forces or rail-induced forces. The distinction between the two types of forces is that direct car forces tend to be higher force, but slower acting, such as wind, or even static, such as load imbalances, while rail-induced forces are low force disturbances at higher frequencies. The forces represented on lines 1312-1322 represent forces which counteract the disturbing forces represented on line 1310. In any event, the net force on line 1306 causes the elevator mass 1304 to accelerate as manifested by an acceleration as shown on a line 1324. The elevator system integrates the acceleration as indicated by an integrator 1326 which is manifested by the car moving at a certain velocity as indicated by a line 1328 which is in turn integrated by the elevator system as indicated by an integrator 1330 into a position change for the elevator car mass as indicated by a line 1332.

Both of the electromagnets 1346, 1348 and driver, as represented by the signal processor 1358 of Fig. 66, are together represented in fig. 69 as a block 1334 responsive to a signal on a line 1336 from a summer 1338 which is in turn responsive to the force command signal on line 1156 from the digital signal processor 1154 of Fig. 66, represented in Fig. 69 as a "filters & compensation" block similarly numbered as 1154. This block carries out the compensation and filtering described in detail in connection with Figs. 4 and 5. A position control speed-up signal on line 1340 may be provided from the gap error signal on line 1398. Suffice it to say that the speed-up signal may be used to permit the fast control to assist the slow control. Such assistance is also inherently provided by direct sensing by the accelerometer. The accelerometer 1150 of Fig. 66 is shown in Fig. 68 being responsive to the elevator car acceleration, as represented on line 1324 but as also corrupted by a vertical component of acceleration, as shown on a line 1350, being summed with the actual

23 June 2004

acceleration in a summer 1352. Thus, the side-to-side acceleration shown in Fig. 66 on the line labelled S-S may be corrupted by a small vertical component so that the signal on line 1152 is not a completely pure side-to-side acceleration. Similarly, the accelerometer is subject to drift, as shown on a signal line 1354 which may be represented as being summed with the output of the accelerometer 1150 in a summer 1356 to model a spurious acceleration signal. Finally, a sensed acceleration signal is provided on a line 1358 to the processor 1154. That finishes the description of the acceleration loop.

It will be appreciated that the two electromagnets 1146, 1148 of Fig. 66 do not present a problem of "opposition" or "fighting" each other because of the fact that control is steered between the two. For the case of two opposed, large size actuators, e.g., the two ball-screw actuators 1300, 1302, we have a similar problem in operating them independently since they may end up "fighting" each other. Now we shall present a concept for controlling the two high-force actuators 1300, 1302 of Fig. 66 by steering actuation to one or the other of the actuators.

The novel technique of developing a centering command signal and the steering of that signal to control two opposed actuators, as shown in Fig. 69, will be explained in conjunction with Fig. 70. Reference points are marked by zeros. A pair of elevator hoistway walls 1360, 1362 has a corresponding pair of rails 1364, 1366 attached thereto. Upon the surface of each rail a primary suspension, such as a roller 1368, 1370 rolls on a surface of the corresponding rail at a distance respectively labelled XRAIL2 and XRAIL1. A spring constant K2, shown in Fig. 69 as a block 1371a, acts between rollers 1368 and actuator 1300 while spring constant K1, shown in Fig. 69 as a block 1371b, acts between roller 1370 and actuator 1302. The position of the actuator 1300 with respect to the car 1304 is

23 June 2004

indicated by a distance X2 while the distance between the car 1304 and the centered position 1371 is indicated by a distance POS with positive to the right and negative to the left of center. The distance between the elevator car 1304 and the surface of the rail 1364 is indicated by a distance GAP2, and thus the distance between the actuator 1300 and the surface of the rail is GAP2 - X2. GAP20 represents the distance between the hoistway wall 1360 and the car 1304 when the car is centered. Similar quantities are shown on the other side of the car.

Referring now back to Fig. 69, a position sensor similar to the sensor 1066, 1070 of Fig. 57 is shown as a block 1376 for measuring the distance GAP1 in Fig. 70. Similarly, a position sensor 1378 measures the quantity GAP2 of Fig. 70. It should be understood that although a pair of sensors 1376, 1378 are shown in Figs. 66 and 69, such function of measuring the gaps (GAP1 and GAP2) may be carried out by a single sensor albeit without the self centering quality of the signal obtained by taking the difference between two GAP signals. It will be realized by examination of Fig. 69 that the measured quantities are related to the quantities shown in Fig. 70 by the following equations:

$$\text{GAP1} = -\text{POS} - \text{XRAIL1} + \text{GAP10}, \text{ and}$$

$$\text{GAP2} = \text{POS} - \text{XRAIL2} + \text{GAP20}.$$

It will be noted that Fig. 69 is similar to Fig. 18 in many respects, except there are two position sensors 1376, 1378 responsive to the position (POS) of the cab, as indicated on the line 1332 and also the additional inner loops having position sensors for retracting the large actuators back to the home or zero position whenever not being actively used as an actuator. In Fig. 70, two gap position lines (GAP10 and GAP20) represent the distances between the car and the hoistway walls when the car is centered. These are further represented as

23 June 2004

"signals" being injected into "summers" 1384, 1386 in producing the physical gaps indicated as GAP1 and GAP2 lines 1388, 1390. These are useful for understanding the system.

5 Output signals from position sensors 1376, 1378 are provided on respective signal lines 1392, 1394 to a summer 1396 which takes the difference between the magnitudes of the two signals and provides a difference (centering control) signal on a line 1398 to a lag filter
10 1400 which provides a filtered centering control signal on a line 1402 to a junction 1404 which provides the filtered difference signal to each of a pair of precision rectifiers 1406, 1408 which together with the junction 1404 comprise a steering control 1409 for steering the
15 filtered centering signal on the line 1402 to one or the other at a time, i.e., not both at the same time. A pair of geared motor controls 1410, 1412 is shown, one of which will respond to the steered centering command signal by moving at a relatively slow velocity as
20 indicated on a line 1412 or 1414 as integrated by the system as indicated by integration blocks 1416 or 1418 to an actuator position (X1 or X2) as indicated on a line 1420 or 1422 for actuating a spring rate 1371d or 1371c for providing the force indicated by line 1316 or 1314.
25 It should be realized that in this control system diagram, the spring rates 1371b and 1371d are associated with the same spring which is actuated by actuator 1410. Similarly, spring rates 1371a and 1371c are associated with the same spring, in this case actuated by actuator
30 1412. A pair of position feedback blocks 1420, 1422 are responsive to the actuator positions indicated by lines 1420, 1422 and include position sensors for providing feedback position signals on lines 1428, 1430 indicative of the position of the actuator with respect to the car.
35 These position signals may be subjected to signal conditioning which may comprise providing a low gain feedback path. A pair of summers 1432, 1434 are

23 June 2004

responsive to the feedback signals on the lines 1428,
1430 and the centering command signal on line 1402 as
steered by the steering control for providing difference
signals on lines 1436, 1438 indicative of the difference
therebetween. It should be understood that one signal of
a pair of output signals on lines 1440, 1442 from the
precision rectifiers 1406, 1408 will comprise the steered
centering command signal on line 1402 and the other will
be zero. By zero we mean a command having a magnitude
equal to that required to cause the actuator to return to
its zero position which will be that position required to
maintain at least the desired preload on the primary
suspension.

Referring now to Fig. 71, the response of a position
transducer, such as is shown in Fig. 62, is shown. This
is an experimentally determined response. Although the
response for a particular transducer is shown, it will be
realized that any other suitable type of position sensor
may be used, including linear position sensors. The
summation of the two signals on the lines 1392, 1394 is
shown in Fig. 70 over the whole range of displacement of
the elevator car (scaled to the particular sensing
arrangement we have shown). The positioning of the links
on the active guides according to the embodiment shown is
such that no more than ten millimeters of displacement is
to be expected. Thus, it will be seen that the two
position sensors for the corresponding two roller guides
can be combined in a seamless response, such as shown in
Fig. 72, for presentation to the lag filter 1400 of Fig.
68.

Although this invention has been shown and described
with respect to at least one detailed, exemplary embodi-
ment thereof, it should be understood by those skilled in
the art that various changes in form, detail, methodology
and/or approach may be made without departing from the
scope of this invention.

23 June 2004

CLAIMS

1. An elevator car including apparatus for stabilizing the elevator car in a hoistway, the apparatus comprising:
- an accelerometer, responsive to a horizontal acceleration of the car for providing a sensed signal having a magnitude indicative thereof:
- position sensing means, responsive to the degree of centering of the car for providing a sensed signal having a magnitude indicative of a horizontal position of the car; and
- control means, responsive to the sensed acceleration signal for controlling actuator means for horizontally actuating the car against the acceleration wherein
- when supplying the acceleration signal to the actuator means, the control means is also responsive to the signal from the position sensing means, thereby to compensate for the components of the acceleration signal not representative of the actual horizontal acceleration acting on the elevator car and to compensate for forces acting on the car tending to decentre it.
2. The car of claim 1, wherein
- the control means is responsive to the sensed centering signal for integrating or lag filtering the sensed centering signal, for providing an integrated or lag filtered signal having a magnitude indicative thereof; and wherein
- the control means is responsive to the acceleration signal and to the integrated or lag filtered signal for controlling the actuator means, such that the actuator means exerts counterforces against the car in a direction opposite that of the sensed horizontal acceleration for effectively adding mass to the car in proportion to the magnitude of the sensed horizontal

acceleration signal and for centering the car in proportion to the magnitude of the integrated or lag filtered signal.

- 5 3. The car of claim 1, wherein the central means includes

 comparator means, responsive to the centering
 signal and to a comparison signal having a selected
 magnitude, for comparing said magnitude of the sensed
10 signal with the selected magnitude of the comparison
 signal for providing a difference signal having a
 magnitude indicative of the difference therebetween; and

 wherein the actuator means is responsive to the
 difference signal for actuating the car.

15

4. The car of claim 1, 2 or 3 wherein the actuator
 means comprises a pair of opposed actuators.

5. The car of claim 4, wherein only one actuator of
20 the pair of actuators is effective at a time except in a
 central crossover region.

6. The car of claim 4 or 5, wherein the sensed
 centering signal is steered between one or the other of
25 the opposed actuators.

7. The car of claim 6, wherein the steered signal is
 steered between one or the other of the opposed
 actuators.

30

8. The car of any preceding claim, wherein the sensing
 means comprises:

 means for sensing acceleration along a car lower
 horizontal axis for providing a car bottom acceleration
35 signal having a magnitude indicative thereof;

 means for sensing acceleration along a car upper
 horizontal axis parallel to the car lower horizontal

23 June 2004

axis, for providing a car top acceleration signal having a magnitude indicative thereof; and wherein the actuator comprises:

5 means responsive to the car bottom acceleration signal for exerting a counterforce against the car bottom in a direction opposite that of the sensed car bottom acceleration; and

10 means responsive to the car top acceleration signal for exerting a counterforce against the car top in a direction opposite that of the sensed car top acceleration.