



(51) International Patent Classification:
E21B 33/03 (2006.01)

(21) International Application Number:
PCT/US2010/024339

(22) International Filing Date:
16 February 2010 (16.02.2010)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
61/164,362 27 March 2009 (27.03.2009) US

(71) Applicant (for all designated States except US):
CAMERON INTERNATIONAL CORPORATION
[US/US]; 1333 W Loop South, Suite 1700, Houston,
Texas 77027 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **NGUYEN, Dennis P.** [US/US]; 3305 Aspenbrook Court, Pearland, Texas 77581 (US). **GUIDRY, Kirk P.** [US/US]; 13603 Branson Lane Ct., Cypress, Texas 77429 (US).


(74) Agent: **SWANSON, Tait R.**; 7915 FM 1960 West, Suite 330, Houston, TX 77070 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: FULL BORE COMPRESSION SEALING METHOD



(57) Abstract: An annular seal, in certain embodiments, includes a top seal section, a bottom seal section, and a core seal section including non-orthogonal top and bottom faces relative to a radial axis of the core seal section disposed between the top seal section and the bottom seal section. The core seal section is configured to expand radially when an axial load is applied to the top and bottom faces of the core seal section such that the top and bottom faces are deformed into an orthogonal alignment relative to the radial axis of the core seal section.

**Declarations under Rule 4.17:**

- *as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))*
- *as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii))*

Published:

- *without international search report and to be republished upon receipt of that report (Rule 48.2(g))*