

SCANNING FOR WIRELESS LOCAL AREA NETWORKS

[0001] The invention generally relates to wireless local area networks (WLAN). In particular, embodiments of the invention relate to power saving for one or more client devices in a wireless network.

5 [0002] Some wireless networks are based on a cellular architecture where the system is subdivided into wireless network cells. One type of wireless network cell, known as a basic service set (BSS), contains client devices controlled by a wireless network access point (AP), and another type of wireless network cell, known as an independent basic service set (IBSS), contains client devices which are not controlled by an access point.

10 [0003] In a BSS, client devices may communicate with the access point over a common wireless communication channel using a time sharing scheme. In an IBSS, client devices may communicate directly with other client devices over a common wireless communication channel using a time sharing scheme. A service set identifier (SSID) is a label or name that distinguishes one wireless network from another. Client devices use the
15 SSID to establish and maintain connectivity. Wireless access points of different BSSs may be connected via a distribution system (DS) that is usually a wired network. The entire interconnected WLAN network, including the different WLAN cells, their respective WLAN access points and the distribution system is known as an extended service set (ESS). A client device may be able to switch between BSS mode and IBSS mode.

20 [0004] A client device may, or may not, be battery-powered. For example, a client device, such as a wireless-enabled laptop, a wireless-enabled cellphone, a wireless-enabled personal digital assistant (PDA), and the like, may sometimes be battery-powered, and at other times may receive power from an external source, such as a power outlet. Other client devices, such as a desktop computer, may receive power from an external source,
25 such as a power outlet, and may not have the option to be battery-powered.

[0005] EP1398912 discloses that, in response to a search process performed by a mobile terminal, individual access points "APs" transmit AP data required for roaming directly to the mobile terminal. The mobile terminal performs a passive scanning search or an active scanning search for the peripheral APs at short time intervals, and obtains and
30 stores the latest AP data in an AP data table. However, when the passive scanner fails to

obtain the AP through passive scanning, the active scanner performs the active scanning. Consequently, the passive scanning process is completed before the decision to initiate active scanning is made.

[0006] It may be beneficial to enhance the battery lifetime of battery-powered client
5 devices.

SUMMARY

[0007] In accordance with one aspect of the present invention, there is provided a method in a wireless device, the method comprising: initiating active scanning for a particular wireless network name during passive scanning for a wireless local area network
10 that matches a profile stored in a wireless local area network controller, said profile comprising said particular wireless network name, wherein active scanning for said particular wireless network name comprises transmitting one or more probe requests.

[0008] In accordance with another aspect of the present invention, there is provided a wireless device comprising: a memory arranged to store profiles of one or more wireless
15 local area networks; a wireless local area network controller arranged to support passive scanning for wireless networks matching a profile and arranged to support active scanning for wireless networks having a wireless network name; and a processor, wherein said memory is arranged to store executable code means which, when executed by said processor, initiates active scanning by said controller for a particular wireless network
20 name during passive scanning by said controller for a wireless network that matches a profile including said particular wireless network name, wherein active scanning for said particular wireless network name comprises transmitting one or more probe requests.

BRIEF DESCRIPTION OF THE DRAWINGS

[0009] Embodiments of the invention are illustrated by way of example and not limitation in the figures of the accompanying drawings, in which like reference numerals indicate corresponding, analogous or similar elements, and in which:

5 [0010] Figure 1 is an illustration of an exemplary communications system, according to some embodiments of the invention;

[0011] Figure 2 is a block diagram of an exemplary client device, according to some embodiments of the invention; and

[0012] Figure 3 is a flowchart of an exemplary method to be performed by a client
10 device, according to some embodiments of the invention.

[0013] It will be appreciated that for simplicity and clarity of illustration, elements shown in the figures have not necessarily been drawn to scale. For example, the dimensions of some of the elements may be exaggerated relative to other elements for clarity.

15

DETAILS

[0014] In the following detailed description, numerous specific details are set forth in order to provide a thorough understanding of embodiments of the invention. However it will be understood by those of ordinary skill in the art that the embodiments of the
20 invention may be practiced without these specific details. In other instances, well-known methods, procedures, components and circuits have not been described in detail so as not to obscure the embodiments of the invention.

[0015] Figure 1 is an illustration of an exemplary communications system 100 according to embodiments of the invention. System 100 includes a wireless access point
25 (AP) 102 and a network gateway 104 coupled to AP 102 via wired connections 106. Network gateway 104 and wired connections 106 may be part of a “distribution system” for AP 102. Non-limiting examples for network gateway 104 are cable modems, Asymmetric Digital Subscriber Line (ADSL) modems, Asynchronous Transfer Mode (ATM) network gateways, dial-up modems, satellite modems, Integrated Services Digital

Network (ISDN) gateways, T-carrier 1 (T1) modems, and the like. It is obvious that any other configuration of a distribution system for AP 102 is possible.

[0016] AP 102 has at least one antenna 108 and is configurable to support at least one wireless network name, for example, at least one service set identifier (SSID). A non-
5 exhaustive list of examples for antenna 108 includes a dipole antenna, a monopole antenna, a multilayer ceramic antenna, a planar inverted-F antenna, a loop antenna, a shot antenna, a dual antenna, an omnidirectional antenna and any other suitable antenna. AP 102 may include a router.

[0017] Exemplary communications system 100 includes a wireless client device 110.
10 A non-exhaustive list of examples for client device 110 includes a wireless-enabled laptop, a wireless-enabled cellphone, a wireless-enabled personal digital assistant (PDA), a wireless-enabled video camera, a wireless-enabled gaming console, a wireless Internet-Protocol (IP) phone and any other suitable wireless client device. Client device 110 is able to execute a process to associate itself with AP 102 in a wireless network. For example,
15 client device 110 may become associated with AP 102 over a wireless network 112.

[0018] Figure 2 is a block diagram of an exemplary client device 110, according to some embodiments of the invention. Wireless client device 110 includes at least one antenna 201 coupled to a radio 202, which in turn is coupled to a WLAN controller 204. WLAN controller 204 may be coupled to a memory 206 storing firmware 208 to be
20 executed by WLAN controller 204. Wireless client device 110 includes a processor 210 and a memory 212 coupled to processor 210. Memory 212 may store executable code 214 to be executed by processor 210.

[0019] Processor 210 may be coupled to WLAN controller 204 and may be able to control, at least in part, the operation of WLAN controller 204. Client device 110 includes
25 a battery 216 to provide power to radio 202, WLAN controller 204, processor 210 and memories 206 and 212. Wireless client device 110 may include other components that, for clarity, are not shown.

[0020] A non-exhaustive list of examples for processor 210 includes a central processing unit (CPU), a digital signal processor (DSP), a reduced instruction set computer
30 (RISC), a complex instruction set computer (CISC) and the like. Memories 206 and 212

may be fixed in or removable from client device 110. A non-exhaustive list of examples for memories 206 and 212 includes any combination of the following:

- a) semiconductor devices such as registers, latches, read only memory (ROM), mask ROM, electrically erasable programmable read only memory devices (EEPROM), flash memory devices, non-volatile random access memory devices (NVRAM), synchronous dynamic random access memory (SDRAM) devices, RAMBUS dynamic random access memory (RDRAM) devices, double data rate (DDR) memory devices, static random access memory (SRAM), universal serial bus (USB) removable memory, and the like;
- b) optical devices, such as compact disk read only memory (CD ROM), and the like; and
- c) magnetic devices, such as a hard disk, a floppy disk, a magnetic tape, and the like.

[0021] A non-exhaustive list of examples for antenna 201 includes a dipole antenna, a monopole antenna, a multilayer ceramic antenna, a planar inverted-F antenna, a loop antenna, a shot antenna, a dual antenna, an omnidirectional antenna and any other suitable antenna.

[0022] Radio 202, WLAN controller 204, processor 210 and memories 206 and 212 are functional blocks and may be implemented in any physical way in client device 110. For example, radio 202, WLAN controller 204, processor 210 and memories 206 and 212 may each be implemented in a separate integrated circuit, and optionally in additional discrete components. Alternatively, some of the functional blocks may be grouped in one integrated circuit. Furthermore, the functional blocks may be parts of application specific integrated circuits (ASIC), field programmable gate arrays (FPGA) or application specific standard products (ASSP).

[0023] In the example of FIG. 1, AP 102 and client device 110 are both “802.11-enabled”, which means that wireless communications therebetween are in accordance with one or more of the following standards defined by the Institute of Electrical and Electronic Engineers (IEEE) for Wireless LAN MAC and Physical layer (PHY) specifications. However, it will be obvious to those of ordinary skill in the art how to modify the

following for other existing WLAN standards or future related standards, including 802.11n.

Standard	Published	Maximum Speed	Frequency
802.11	1997	2 Mbps	2.4 GHz
802.11a	1999	54 Mbps	5.0 GHz
802.11b	1999	11 Mbps	2.4 GHz
802.11g	2003	54 Mbps	2.4 GHz

The 1999 edition of the 802.11 standard (as reaffirmed June 12, 2003) distinguishes between infrastructure WLANs (BSS) and ad-hoc WLANs (IBSS).

- 10 [0024] In order to join a BSS managed by AP 102, i.e. to become connected to AP 102 over wireless network 112, client device 110 has to initiate and perform a “connectivity sequence” with AP 102. In client device 110, WLAN controller 204 may perform the connectivity sequence, optionally jointly with processor 210. The connectivity sequence may include three consecutive processes – a “probing” process, an “authentication”
15 process and an “association” process.

- [0025] The probing process begins by having the client device transmit one or more “probe request” frames over one or more communication channels defined by the communication standard. Standard 802.11B, for example, defines 11 different communication channels. The probe request frame contains information about client
20 device 110, such as which data rates are supported by client device 110 and to which SSID client device 110 requests to connect. Client device 110 may send probe requests blindly, without being aware whether an access point with the same SSID exists in its vicinity, and without knowing what data rate is acceptable for that access point. For that reason, client device 110 may send probe requests at the lowest data rate defined by the respective
25 standard, e.g. 1 Mbps (Megabits per second).

- [0026] If AP 102 receives a probe request frame on one of the communication channels, it may reply to the probe request frame by transmitting a “probe response” frame on that channel. A probe response frame includes information such as the SSID for which

AP 102 is configured, a timestamp, data rates supported by AP 102, "beacon interval" information and physical layer information.

[0027] If client device 110 receives a probe response frame transmitted by AP 102, it may examine whether the SSID of AP 102 matches the SSID sent by client device 110 in the probe request, may examine other information included in the probe response frame and may examine the strength of the signal carrying the frame. Client device 110 may decide whether to continue the process for connecting with AP 102.

[0028] After completing the probing process, client device 110 may have to identify itself and to get permission to connect with AP 102. This process can have different forms, depending on a security mechanism deployed in the particular network. In one simple example for this process, client device 110 may send an "authentication request" frame to AP 102 and in response may receive an "authentication response" frame from AP 102. If the authentication response frame grants client device 110 permission to connect with AP 102, client device 110 may initiate the association process.

[0029] Client device 110 may initiate an association process by transmitting an "association" frame. In response, AP 102 may transmit an "association response" frame that indicates the success or failure of the association. If the association succeeded, the association response frame may include an association identification (AID) for client device 110.

[0030] The total time to complete a full connectivity sequence, from the first probe request to reception of the association response, may vary and may be as long as several seconds, for example, 3 seconds. The probing process itself may take, for example, 1 second. The timing in which the different response frames arrive at client device 110 during the connectivity sequence is unknown, and therefore, during the entire connectivity sequence, radio 202 may have to be able to receive signals and cannot be in a "sleep" state to conserve power.

[0031] It may be desired to decrease the amount of power consumed by client device 110 while performing a connectivity sequence in order to conserve the power stored in battery 216.

[0032] The 802.11 standard explains that access points transmit beacon frames at substantially regular time periods to announce the existence of and to synchronize wireless networks. The format of beacon frames and their contents is explained in detail in the 802.11 standard. The beacon interval is included in each beacon frame. The number of
5 time units between target beacon transmission times is referred to as a “beacon interval”.

[0033] Beacon frames may, or may not include the SSID of the wireless network they belong to. For example, beacon frames transmitted by AP 102 over wireless network 112 may contain the SSID associated with wireless network 112. In addition, each beacon frame also includes a timestamp which is the value of a clock internal to the access point at
10 the actual transmission time of the beacon. A client device receiving the beacon frame will update its internal clock according to the timestamp in the received beacon frame. Moreover, beacon frames may include other information.

[0034] Client device 110 may look for a wireless network, for example, wireless network 112, using techniques known as “active scanning” and “passive scanning”. In
15 preparation, processor 210 may program a profile of the wireless network that is sought, including the network’s SSID, to WLAN controller 204. Upon being operatively coupled to radio 202, WLAN controller 204 may automatically initiate passive scanning for the sought network. In passive scanning, WLAN controller 204 listens for beacon frames, one communication channel at a time. If a beacon frame including the SSID of the sought
20 wireless network is received, WLAN controller 204 may initiate an authentication process and, if the authentication process is successful, may initiate an association process with the access point that sent the beacon frame. If a beacon frame not including any SSID is received, WLAN controller 204 may initiate a connectivity sequence by sending a probe request on the communication channel of the received beacon frame. If the profile in the
25 probe response matches the profile stored in WLAN controller 204, WLAN controller 204 may initiate an authentication process and, if the authentication process is successful, may initiate an association process with the access point that sent the probe response. If the profile in the probe response matches the SSID of the profile stored in WLAN controller 204, but does not match other characteristics of that profile, or if the profile in the probe
30 response does not match the SSID of the profile stored in WLAN controller 204, then WLAN controller 204 may proceed to passively scan on the next communication channel.

Client device 110 may wait a predefined period of time, for example, 3 seconds, for WLAN controller 204 to report having successfully associated with the sought wireless network. If no such report is received during this predefined period of time (timed using a timer 218 in processor 210), client device 110 may take additional action, such as, for
5 example, programming into WLAN controller 204 the profile of an additional wireless network to search for, or putting radio 202 into a sleep state.

[0035] If client device 110 were to use only passive scanning when looking for a wireless network and the sought network was unavailable, then client device 110 would be required to wait the full predefined period of time before taking additional action.

10 [0036] Figure 3 is a flowchart of an exemplary method to be implemented by client device 110, according to some embodiments of the invention. Executable code 214, when executed by processor 110, may cause client device 110 to implement the method of Figure 3.

[0037] At 302, client device 110 may store a profile that includes a particular wireless
15 network name in WLAN controller 204.

[0038] At 304, client device 110 may initiate active scanning for the particular wireless network name during passive scanning for a wireless network that matches the profile stored in WLAN controller 204 at 302. Active scanning for the particular wireless network name may include transmitting one or more probe requests, each of the probe
20 requests transmitted on a different communication channel.

[0039] In active scanning, WLAN controller 204 does not wait for the receipt of a beacon frame in order to transmit the probe request. Moreover, WLAN controller 204 reports back to processor 210 as soon as WLAN controller 204 has succeeded in discovering an access point with the particular wireless network name in the probe requests
25 of the active scanning. Similarly, WLAN controller 204 reports back to processor 210 as soon as WLAN controller 204 has failed to discover any access points with the particular wireless network name in the probe requests of the active scanning. Consequently, if no access point with the particular wireless network name has been discovered due to the active scanning, client device 110 will be notified of such sooner than if it had relied only
30 on passive scanning.

[0040] If processor 210 receives a response that indicates a failure to discover any access points with the particular wireless network name (checked at 306), processor 210 may abort the passive scanning at 308.

[0041] Memory 212 may store profiles of more than one wireless network to be sought. For example, a user of client device 110 may store in memory 212 profiles of the wireless networks at the user's home, the user's workplace and other wireless networks that the user may wish to connect to.

[0042] If there are no additional wireless networks to be sought (checked at 309), then client device 110 may put radio 202 into a sleep state at 310. After sleeping for some time, client device 110 may put radio 202 into an active state and resume the method of Figure 3. The sleeping duration may be increased with each unsuccessful attempt to find the wireless network, until it reaches an upper limit.

[0043] If there are additional wireless networks to be sought (checked at 309), then client device may resume the method at 302 to store a different profile with a different wireless network name in WLAN controller 204. This may cause WLAN controller 204 to perform passive scanning for wireless networks that match the different profile.

[0044] If, however, processor 210 receives a response that indicates discovery of one or more access points with the particular wireless network name (checked at 306), then the passive scanning, if successful (checked at 312), ought to result in association of client device 110 and the wireless network at 314. If passive scanning is not successful (checked at 312) despite the discovery of one or more access points with the particular wireless network name via active scanning, this is an indication that the profile stored in WLAN controller 204 at 302 is misconfigured (316).

[0045] In the event of a misconfigured profile, client device 110 may post an error to the user indicating an invalid configuration in the profile, and/or may automatically omit that profile from further scans until the user has edited the parameters of the profile (perhaps changing the authentication setting or the encryption setting).

[0046] While certain features of the invention have been illustrated and described herein, many modifications, substitutions, changes, and equivalents will now occur to those of ordinary skill in the art within the scope of the appended claims.

Claims:

1. A method in a wireless device (110), the method comprising:
 - initiating active scanning (304) for a particular wireless network name during
passive scanning for a wireless network (112) that matches a profile stored in a
5 wireless local area network controller (204) , said profile comprising said particular
wireless network name,
 - wherein active scanning for said particular wireless network name comprises
transmitting one or more probe requests.
2. The method of claim 1, further comprising:
 - 10 aborting said passive scanning (308) upon receipt of a response that indicates a
failure to discover any access points with said particular wireless network name.
3. The method of claim 2, further comprising:
 - storing a different profile with a different wireless network name in said wireless
local area network controller (204); and
15 during passive scanning for a wireless network matching said different profile,
initiating active scanning for said different wireless network name (309).
4. The method of claim 2, further comprising:
 - putting a radio (202) of said device (110) into a sleep state (310).
5. The method of claim 1, further comprising:
 - 20 following receipt of a response that indicates discovery of one or more access
points (102) with said particular wireless network name, identifying that said profile is
misconfigured (316) if said passive scanning fails to result in an association.

6. A wireless device (110) comprising:
- a memory (212) arranged to store profiles of one or more wireless local area networks (112);
 - a wireless local area network controller (204) arranged to support passive scanning for wireless networks matching a profile and arranged to support active scanning for wireless networks having a wireless network name; and
 - a processor (210),
- wherein said memory (212) is arranged to store executable code means (214) which, when executed by said processor (210), initiates active scanning by said controller (204) for a particular wireless network name during passive scanning by said controller (204) for a wireless network that matches a profile comprising said particular wireless network name,
- wherein active scanning for said particular wireless network name comprises transmitting one or more probe requests.
7. The wireless device (110) of claim 6, wherein said code means (214), when executed by said processor (210), causes said controller (204) to abort said passive scanning upon receipt of a response that indicates a failure to discover any access points (102) with said particular wireless network name.
8. The wireless device (110) of claim 7, wherein said code means (214), when executed by said processor (210), stores a different profile with a different wireless network name in said wireless local area network controller (204); and initiates active scanning for said different wireless network name during passive scanning for a wireless local area network matching said different profile.
9. A machine readable medium comprising program code means (214) executable by a processor (210) of the device (110) of any one of claims 6 to 8 for implementing the method of any one of claims 1 to 5.
10. A communication system (100) comprising an access point (102) and at least one wireless device (110) according to any one of claims 6 to 8.