

## Information Transmission Method, Network Device and Terminal Device

### Technical Field

Embodiments of the present invention relate to the communication field, and more particularly, to a method for transmitting information, a network device, and a terminal device.

### Background

At present, a Long Term Evolution Advanced (LTE-A) communication system supports Carrier Aggregation (CA) function and supports cross-carrier scheduling between Component Carriers (CCs), that is, scheduling data channels of other carriers through a control channel of a carrier.

In the Fifth generation mobile communication technology (5G) CA system, a cross-carrier scheduling technology which is similar to that in the LTE-A is introduced. However, when 5G CA system adopts the cross-carrier scheduling technology which is similar to that in the LTE-A, there will be some problems. Specifically, the bandwidth of 5G system is much larger than that of the LTE-A, and a control channel responsible for data scheduling is much more complex than that in the LTE-A system, which may include a two-layer structure of a common control channel and a UE-specific control channel. If a complete common control channel and a UE-specific control channel are sent in each carrier, the overhead of control channels may be very large, and adopting cross-carrier scheduling will excessively increase the burden of a control channel of the main carrier. Based on this, it is urgent to put forward a method to solve this problem.

### Summary

Embodiments of the present invention provide a method for transmitting information, a network device, and a terminal device, which can save overhead of a common control channel.

In a first aspect, a method for transmitting information is provided, which includes: sending, by a network device, first configuration information to a terminal device through a first

control channel on a first carrier, wherein the first configuration information is used for indicating a configuration on a second carrier, and the first carrier and the second carrier are different.

5 In an embodiment of the present invention, a network device may indicate configuration information of resources of other carriers (such as a second carrier) through a channel on a first carrier (such as a first control channel), and send relevant configuration information (such as first configuration information) to a terminal device. Thus the network device does not need to transmit a common control channel on each carrier, so as to save the overhead of the common control channel. Correspondingly, the terminal device may receive the first configuration  
10 information sent by the network device through the first control channel of a carrier to obtain the configuration information of multiple carriers, so as to avoid a detection for a common control channel on the multiple carriers, reduce the complexity of the terminal device and save the power of the terminal device.

15 In an embodiment of the present invention, the first carrier and the second carrier are different carriers, such as a low-frequency carrier and a high-frequency carrier. For example, with the method for transmitting information according to the embodiment of the present invention, a problem of insufficient coverage of the common control channel on the high-frequency carrier can be solved by sending configuration information of the high-frequency carrier through the common control channel on the low-frequency carrier.  
20 Therefore, with the technical solution of the embodiment of the present invention, the coverage capability of the common control channel of the high-frequency carrier can further be equivalently improved.

In an embodiment of the present invention, the first configuration information may indicate various configuration information of resources of the second carrier, such as slot  
25 structure information, reserved resources, and resource pool information. It should be understood that the first configuration information may include various configuration information of the resources of the second carrier, and this is not restricted in the present invention.

In some possible implementation modes, the first control channel may be a common

control channel and the second control channel may be a UE-specific control channel. That is, the network device may indicate relevant configuration of the UE-specific control channel on the second carrier through the common control channel on the first carrier.

5 In some possible implementation modes, the first configuration information may include at least one of serial number information of a time domain scheduling unit in which the second control channel is located, information of a resource used by the second control channel, and information of a numerology used by the second control channel.

In some possible implementation modes, the first control channel and the second control channel may adopt different carriers.

10 Optionally, the numerology adopted by the second control channel may be indicated in the information of a resource used by the second control channel, or it may be indicated by a network device through other implicit forms.

In some possible implementation modes, the first configuration information is resource configuration information of resources on the second carrier.

15 Optionally, the first configuration information may include: at least one of structural information of a time domain scheduling unit within the resources of the second carrier, reserved resource information of the resources of the second carrier, and resource pool information within the resources of the second carrier.

20 Optionally, the first configuration information may include structural information of a time domain scheduling unit within time-frequency resources of the second carrier, where the structure of the time domain scheduling unit within the resources of the second carrier may include information of an uplink resource part, a downlink resource part, or a length of a protection period GAP, etc.

25 It should be understood that the information included in the first configuration information may be sent through the same configuration information or may be sent in different configuration information, and this is not restricted in the present invention.

In some possible implementation modes, the first control channel may further carry indication information used for indicating a serial number of a time domain scheduling unit

corresponding to the first configuration information.

In a second aspect, a method for transmitting information is provided, which includes: sending, by a network device, first configuration information to a terminal device through system information on a first carrier, wherein the first configuration information is used for  
5 indicating a configuration on a second carrier, and the first carrier and the second carrier are different.

In an embodiment of the present invention, the network device may send the first configuration information to the terminal device through the system information on the first carrier, wherein the first configuration information is used for indicating the configuration on  
10 the second carrier, and the first carrier is different from the second carrier. In this way, the network device does not need to send all of the system information on each carrier, which saves the overhead of the system information. Correspondingly, the terminal device can receive the first configuration information sent by the network device through the system information on  
15 the first carrier, so as to obtain configurations of multiple carriers according to the first configuration information, so as to avoid a detection for the system information of the multiple carriers, reduce the complexity of the terminal device, and save the power of the terminal device.

In an embodiment of the present invention, system information may be understood as system broadcast information.

20 In some possible implementation modes, the first configuration information is configuration information of the control channel on the second carrier.

In some possible implementation modes, the first configuration information includes at least one of serial number information of a time domain scheduling unit in which the control channel is located, information of a resource used by the control channel, and information of a  
25 carrier used by the control channel.

In some possible implementation modes, the time domain scheduling unit includes a time slot, a mini-slot, or a sub-frame.

In some possible implementation modes, the first configuration information is resource allocation information of resources on the second carrier.

In some possible implementation modes, the first configuration information may include at least one of structure information of a time domain scheduling unit within resources of the second carrier, reserved resource information of resources of the second carrier, and resource pool information of resources of the second carrier.

5 In some possible implementation modes, the system information carries indication information used for indicating a serial number of a time domain scheduling unit corresponding to the first configuration information.

10 In a third aspect, a method for transmitting information is provided, which includes: receiving, by a terminal device, first configuration information sent by a network device through a first control channel on a first carrier, wherein the first configuration information is used for indicating a configuration on a second carrier, and the first carrier and the second carrier are different.

15 In an embodiment of the present invention, the terminal device receives the first configuration information sent by the network device through the first control channel on the first carrier, wherein the first configuration information is used for indicating the configuration on the second carrier, and the first carrier and the second carrier are different, therefore the overhead of common control channel can be saved, and electric energy of the terminal device can be saved. In other words, the terminal device can receive the first configuration information sent by the network device through the first control channel of a carrier to obtain configuration  
20 information of multiple carriers, so as to avoid a detection for a common control channel on the multiple carriers, reduce the complexity of the terminal device, and save the power of the terminal device.

25 In an embodiment of the present invention, the first carrier and the second carrier are different carriers, such as a low-frequency carrier and a high-frequency carrier. For example, with the method for transmitting information according to the embodiment of the present invention, a problem of insufficient coverage of the common control channel on high-frequency carrier can be solved by sending configuration information of the high-frequency carrier through the common control channel on the low-frequency carrier. Therefore, with the technical solution of the embodiment of the present invention, the coverage capability of the common

control channel of the high-frequency carrier can further be equivalently improved.

In some possible implementation modes, the first configuration information is configuration information of a second control channel on the second carrier.

5 In some possible implementation modes, the first control channel is a common control channel and the second control channel is a UE-specific control channel of the terminal device.

In some possible implementation modes, the first configuration information includes at least one of serial number information of a time domain scheduling unit in which the second control channel is located, information of a resource used by the second control channel, and information of a numerology used by the second control channel.

10 In some possible implementation modes, the first configuration information is resource configuration information of resources of the second carrier.

In some possible implementation modes, the first configuration information may include at least one of structure information of a minimum time domain scheduling unit within resources of the second carrier, reserved resource information of resources of the second carrier,  
15 and resource pool information of resources of the second carrier.

In some possible implementation modes, the first control channel carries indication information used for indicating a number of a time domain scheduling unit corresponding to the first configuration information.

20 In some possible implementation modes, the time domain scheduling unit includes a time slot, mini-slot, or a sub-frame.

In some possible implementation modes, the first control channel and the second control channel adopt different carriers.

25 In some possible implementation modes, the numerology used by the second control channel includes at least one of following parameters: a subcarrier interval, a width of minimum frequency domain scheduling unit, a length of orthogonal frequency division multiplexing (OFDM) symbol, a length of minimum time domain scheduling unit, and a length of Cyclic Prefix (CP).

In a fourth aspect, a method for transmitting information is provided, which includes:

receiving, by a terminal device, first configuration information sent by a network device through system information on a first carrier, wherein the first configuration information is used for indicating a configuration on a second carrier, and the first carrier and the second carrier are different.

5           In an embodiment of the present invention, the terminal device receives the first configuration information sent by the network device through the system information on the first carrier, wherein the first configuration information is used for indicating the configuration on the second carrier, and the first carrier and the second carrier are different, thus the overhead of common control channel can be saved, and the power of the terminal device can be saved. In  
10 other words, the terminal device can receive the first configuration information sent by the network device through the system information on the first carrier to obtain configurations of multiple carriers according to the first configuration information, so as to avoid a detection for the system information of the multiple carriers, reduce the complexity of the terminal device, and save the power of the terminal device.

15           In some possible implementation modes, the first control channel is a common control channel and the second control channel is a UE-specific control channel of the terminal device.

          In some possible implementation modes, the first configuration information includes at least one of serial number information of a time domain scheduling unit in which the second control channel is located, information of a resource used by the second control channel, and  
20 information of a numerology used by the second control channel.

          In some possible implementation modes, the time domain scheduling unit includes a time slot, mini-slot or a sub-frame.

          In some possible implementation modes, the first configuration information is resource allocation information of resources of the second carrier.

25           In some possible implementation modes, the first configuration information may include at least one of structure information of a time domain scheduling unit within resources of the second carrier, reserved resource information of resources of the second carrier, and resource pool information of resources of the second carrier.

          In some possible implementation modes, the system information carries indication

information used for indicating a number of a time domain scheduling unit corresponding to the first configuration information.

In some possible implementation modes, the time domain scheduling unit includes a time slot, mini-slot, or a sub-frame.

5        In some possible implementation modes, the numerology used by the control channel includes at least one of following parameters: a subcarrier interval, a width of frequency domain scheduling unit, a length of orthogonal frequency division multiplexing (OFDM) symbol, a length of minimum domain scheduling unit, and a length of cyclic prefix (CP).

10       In a fifth aspect, a network device is provided for performing the method in the first aspect or any possible implementation mode of the first aspect described above. Specifically, the apparatus includes units for performing the method in the first aspect or any possible implementation mode of the first aspect described above.

15       In a sixth aspect, a network device is provided for performing the method in the second aspect or any possible implementation mode of the second aspect described above. Specifically, the apparatus includes units for performing the method in the second aspect or any possible implementation mode of the second aspect described above.

20       In a seventh aspect, a terminal device is provided for performing the method in the third aspect or any possible implementation mode of the third aspect described above. Specifically, the apparatus includes units for performing the method in the third aspect or any possible implementation mode of the third aspect described above.

In an eighth aspect, a terminal device is provided for performing the method in the fourth aspect or any possible implementation mode of the fourth aspect described above. Specifically, the apparatus includes units for performing the method in the fourth aspect or any possible implementation mode of the fourth aspect described above.

25       In a ninth aspect, a network device is provided. The network device includes a processor, a memory, and a communication interface. The processor is connected with the memory and the communication interface. The memory is used for storing instructions, the processor is used for executing the instructions, and the communication interface is used for communicating with other network elements under the control of the processor. When the processor executes

instructions stored in the memory, the execution causes the processor to perform the method in the first aspect or any possible implementation mode of the first aspect.

In a tenth aspect, a network device is provided. The network device includes a processor, a memory, and a communication interface. The processor is connected with the memory and the communication interface. The memory is used for storing instructions, the processor is used for executing the instructions, and the communication interface is used for communicating with other network elements under the control of the processor. When the processor executes instructions stored in the memory, the execution causes the processor to perform the method in the second aspect or any possible implementation mode of the second aspect.

In an eleventh aspect, a terminal device is provided. The terminal device includes a processor, a memory, and a communication interface. The processor is connected with the memory and the communication interface. The memory is used for storing instructions, the processor is used for executing the instructions, and the communication interface is used for communicating with other network elements under the control of the processor. When the processor executes the instructions stored in the memory, the execution causes the processor to perform the method in the third aspect or any possible implementation mode of the third aspect.

In a twelfth aspect, a terminal device is provided. The terminal device includes a processor, a memory, and a communication interface. The processor is connected with the memory and the communication interface. The memory is used for storing instructions, the processor is used for executing the instructions, and the communication interface is used for communicating with other network elements under the control of the processor. When the processor executes the instructions stored in the memory, the execution causes the processor to perform the method in the fourth aspect or any possible implementation mode of the fourth aspect.

In a thirteenth aspect, a computer-readable storage medium is provided, which stores a program that causes a network device to perform any method for transmitting information in the above-described first aspect and various implementation modes of the first aspect.

In a fourteenth aspect, a computer-readable storage medium is provided, which stores a program that causes a network device to perform any method for transmitting information in the

above-described second aspect and various implementation modes of the second aspect.

In a fifteenth aspect, a computer-readable storage medium is provided, which stores a program that causes a terminal device to perform any method for transmitting information in the above-described third aspect and various implementation modes of the third aspect.

5 In a sixteenth aspect, a computer-readable storage medium is provided, which stores a program that causes a terminal device to perform any method for transmitting information in the above-described fourth aspect and various implementation modes of the fourth aspect.

## Brief Description of Drawings

10 FIG. 1 is a schematic diagram of a scene.

FIG. 2 is a schematic flowchart of a method for transmitting information according to an embodiment of the present invention.

FIG. 3A is a schematic diagram of an example according to an embodiment of the present invention.

15 FIG. 3B is a schematic diagram of another example according to an embodiment of the present invention.

FIG. 4A is a schematic diagram of an example according to an embodiment of the present invention.

20 FIG. 4B is a schematic diagram of another example according to an embodiment of the present invention.

FIG. 5 is a schematic flowchart of a method for transmitting information according to another embodiment of the present invention.

FIG. 6A is a schematic diagram of an example according to another embodiment of the present invention.

25 FIG. 6B is a schematic diagram of another example according to another embodiment of the present invention.

FIG. 7 is a schematic flowchart of a method for transmitting information according to an

embodiment of the present invention.

FIG. 8 is a schematic flowchart of a method for transmitting information according to another embodiment of the present invention.

FIG. 9 is a schematic block diagram of a network device according to an embodiment of  
5 the present invention.

FIG. 10 is a schematic block diagram of a network device according to another embodiment of the present invention.

FIG. 11 is a schematic block diagram of a terminal device according to an embodiment of the present invention.

10 FIG. 12 is a schematic block diagram of a terminal device according to another embodiment of the present invention.

FIG. 13 is a structural block diagram of a network device provided according to an embodiment of the present invention.

15 FIG. 14 is a structural block diagram of a network device provided according to an embodiment of the present invention.

FIG. 15 is a structural block diagram of a terminal device provided according to another embodiment of the present invention.

FIG. 16 is a structural block diagram of a terminal device provided according to yet another embodiment of the present invention.

20

## Detailed Description

Technical solutions in embodiments of the present invention are described below with reference to drawings in the embodiments of the present invention.

25 It should be understood that the technical solutions of the embodiments of the present invention may be applied to various communication systems, for example, current communication systems such as a Global System of Mobile Communication (GSM), a Code Division Multiple Access (CDMA) system, a Wideband Code Division Multiple Access

(WCDMA) system, General Packet Radio Service (GPRS), a Long Term Evolution (LTE) system, an LTE Frequency Division Duplexing (FDD) system, an LTE time Division Duplex (TDD) system, and a Universal Mobile Communication system (UMTS), and especially to a future 5G system or a 5G New Radio (NR) prototype system.

5        It should also be understood that in the embodiments of the present invention, a network-side device may also be referred to as a network device or a base station, etc., and the base station may be a Base Transceiver Station (BTS) in GSM or CDMA, a base station (NodeB) in WCDMA, an evolution base station (eNB or NodeB) in LTE, or a base station device in a future 5G network, etc., and this is not restricted in the present invention.

10        It should also be understood that in the embodiments of the present invention, a terminal device may communicate with one or more Core Networks via a Radio Access Network (RAN), and the terminal device may be referred to as an access terminal, User Equipment (UE), a subscriber unit, a subscriber station, a mobile station, a mobile platform, a remote station, a remote terminal, a mobile device, a user terminal, a terminal, a wireless communication device,  
15        a user agent or a user apparatus. The terminal device may be a cellular phone, a cordless phone, a Session Initiation Protocol (SIP) phone, a Wireless Local Loop (WLL) station, a Personal Digital Assistant (PDA), a handheld device or a computing device with a wireless communication function, or other processing device connected to a wireless modem, an on-board device, a wearable device, a terminal device in a future 5G network, etc.

20        FIG. 1 is a schematic diagram of a scene. It should be understood that the scene in FIG. 1 is introduced as an example for sake of understanding, which does not constitute a limitation on the present invention. In FIG. 1, a terminal device 11, a terminal device 12, a terminal device 13 and a base station 21 are shown.

25        As shown in FIG. 1, the terminal device 11 may communicate with the base station 21, the terminal device 12 may communicate with the base station 21, and the terminal device 13 may communicate with the base station 21. Alternatively, the terminal device 12 may communicate with the terminal device 11. Alternatively, as another case, the terminal device 13 communicates with the base station 12. Here, for the communication between the terminal device and the base station or the communication between the terminal device and the terminal

device, a UE-specific control channel of the terminal device may be indicated through a Common control channel.

However, in the prior art, if the 5G CA system adopts a cross-carrier scheduling technology which is similar to that in the LTE-A, there will be some problems: the control channel responsible for data scheduling in the 5G system may be far more complex than that in LTE-A system, accordingly, the overhead of the common control channel may be larger, and a channel burden of another carrier will be increased when transmitting with the other carrier, which may result in some waste of channel resources. In addition, as the common control channel needs to broadcast to all users, it is much difficult to improve coverage capability of the common control channel by using beamforming technology, which results in a problem of insufficient coverage of the common control channel on high-frequency carriers. In addition, correspondingly, the terminal device further needs to search for the common control channel at multiple positions, thus the complexity of the terminal device is increased and the power consumption of the terminal device is relatively large.

Therefore, the network device or terminal device in the embodiment of the present invention tries to indicate control information of other multiple carriers (such as a UE-specific control channel) through a common control channel of a carrier, so as to save the overhead of the common control channel. Furthermore, the problem of insufficient coverage of common control channel on high-frequency carriers can be improved.

FIG. 2 shows a schematic flowchart of a method 200 for transmitting information according to an embodiment of the present invention. The method 200 may be performed by a network device, for example, the network device may be the base station 21 in FIG. 1. As shown in FIG. 2, the method 200 includes the act S210.

In S210, a network device sends first configuration information to a terminal device through a first control channel on a first carrier, wherein the first configuration information is used for indicating a configuration on a second carrier, and the first carrier and the second carrier are different.

Specifically, the network device may indicate configuration information of resources of other carriers (such as the second carrier) through a channel (such as the first control channel)

on the first carrier, and send relevant configuration information (such as the first configuration information) to the terminal device. In this way, the network device does not need to transmit a common control channel on each carrier, and the overhead of the common control channel is saved. Correspondingly, the terminal device may receive the first configuration information  
5 sent by the network device through the first control channel of a carrier to obtain configuration information of multiple carriers, so as to avoid a detection of the common control channel on the multiple carriers, reduce the complexity of the terminal device and save the power of the terminal device.

Here, the first carrier and the second carrier are different carriers, such as a low-frequency  
10 carrier and a high-frequency carrier. For example, with the method for transmitting information according to the embodiment of the present invention, the problem of insufficient coverage of a common control channel on the high-frequency carriers can be solved by sending the configuration information of the high-frequency carriers through the common control channel on the low-frequency carrier. Therefore, with the technical solution of the embodiment of the  
15 present invention, the coverage capability of the common control channels on the high-frequency carriers can be further equivalently improved.

In an embodiment of the present invention, the first configuration information may indicate various configuration information of resources of the second carrier, such as slot structure information, reserved resources, and resource pool information. It should be  
20 understood that the first configuration information may include various configuration information of the resources of the second carrier, which are not restricted in the present invention.

Optionally, as an embodiment, the first configuration information may be configuration information of a second control channel of resources of the second carrier. In other words, the  
25 first configuration information may indicate a related configuration of the second control channel of time-frequency resources of the second carrier.

Optionally, the first control channel may be a common control channel and the second channel may be a UE-specific control channel. That is, the network device may indicate the relevant configuration of the UE-specific control channel on the second carrier through the

common control channel on the first carrier.

Optionally, the first configuration information may include at least one of serial number information of a time domain scheduling unit in which the second control channel is located, information of a resource used by the second control channel, and information of a numerology  
5 used by the second control channel.

Optionally, in an embodiment of the present invention, the time domain scheduling unit may be specifically a time slot, a mini-slot, or a sub-frame.

In an embodiment of the present invention, the first control channel and the second control channel may adopt different carriers. That is, the carrier adopted by the common control  
10 channel and the carrier adopted by the UE-specific control channel of the terminal may be different.

Optionally, the numerology adopted by the second control channel may be indicated in the information of a resource used by the second control channel, or it may also be indicated by the network device through other implicit forms.

15 Therefore, in the method for transmitting information according to the embodiment of the present invention, the network device sends first configuration information to the terminal device through the first control channel on the first carrier, wherein the first configuration information is used for indicating the configuration on the second carrier, and the first carrier and the second carrier are different, and the overhead of the common control channel can be  
20 saved.

Optionally, as an embodiment, the first configuration information may be configuration information of resources on the second carrier.

Optionally, the first configuration information may include: at least one of structural information of a time domain scheduling unit within resources of the second carrier, reserved  
25 resource information of resources of the second carrier, and resource pool information of resources of the second carrier.

For example, the first configuration information may include structural information of a time domain scheduling unit within time-frequency resources of the second carrier, wherein, the

structure of the time domain scheduling unit within the resources of the second carrier may include information such as an uplink resource part, a downlink resource part, or a length of a protection period GAP.

Alternatively, for another example, the first configuration information may include reserved resource information of the time-frequency resources of the second carrier.

Alternatively, for another example, the first configuration information may include resource pool information within the time-frequency resources of the second carrier.

It should be understood that the above only shows some examples of the first configuration information, and there may be more forms of combination in specific implementations, or the first configuration information may further include other reasonable configuration information, and this is not restricted in the present invention.

The above describes related examples of the first configuration information. Optionally, the first control channel may further carry indication information used for indicating a serial number of a time domain scheduling unit corresponding to the first configuration information.

That is, when the network device sends the configuration information through the first control channel, that the configuration information is to be sent to which time domain scheduling unit (such as to which sub-frame, time slot or mini-slot) may further be specified. In specific implementation, the network device may indicate the time domain scheduling unit corresponding to the configuration information to the terminal device by carrying the serial number of the time domain scheduling unit in the first configuration information. Alternatively, if several mini-slots are connected in series to form a time slot, a serial number of each mini-slot in the time slot may also be indicated, and this is not restricted in the present invention.

It should be understood that in an embodiment of the present invention, the first configuration information is only taken as an example for explanation, and multiple pieces of configuration information may be introduced in practice, and this is not restricted in the present invention.

It should also be understood that the information included in the first configuration information may be sent through the same configuration information or may be sent in different

configuration information, and this is not restricted in the present invention.

It should also be understood that in embodiments of the present invention, the introduction of the serial numbers “first” and “second”... is only used for distinguishing different objects, for example, to distinguish different “channels” or to distinguish different “carriers”, which does not constitute limitation on the present invention.

A method for transmitting information according to an embodiment of the present invention will be described below with reference to an example in FIG. 3A. As shown in FIG. 3A,  represents a common control channel on carrier 1, and  represents a UE-specific control channel on carrier 2. Here, the common control channel on carrier 1 may be understood as the first control channel described above. The network device may indicate the UE-specific control channel on other carrier (such as carrier 2) through the common control channel on carrier 1. Of course, the network device may also indicate the UE-specific control channel on carrier 1 through the common control channel on carrier 1. Each of multiple pieces of indication information shown in FIG. 3A may be understood as the first configuration information described above. Optionally, the network device may further indicate other configuration information (not shown) on carrier 1 and carrier 2 in FIG. 3A, which are not restricted in the present invention.

Therefore, with the method for transmitting information according to the embodiment of the present invention, it is not needed to transmit a common control channel on each carrier, thus the overhead of the common control channel may be obviously saved. Correspondingly, the terminal device may receive the first configuration information sent by the network device through the first control channel of a carrier to obtain configuration information of multiple carriers, so as to avoid a detection of a common control channel on the multiple carriers, reduce the complexity of the terminal device, and save the power of the terminal device.

In the following, a method for transmitting information according to an embodiment of the present invention will be described with reference to an example in FIG. 3B, some similar concepts in FIG. 3B and FIG. 3A will not be described in detail for sake of conciseness. As shown in FIG. 3B,  represents a common control channel on carrier 1, and  represents UE-specific control channels corresponding to multiple time-frequency units on carrier 2. The

network device may indicate the UE-specific control channels of multiple time-frequency scheduling units (such as time-frequency scheduling unit 1, time-frequency scheduling unit 2, time-frequency scheduling unit 3, and time-frequency scheduling unit 4) on carrier 2 through the common control channel on carrier 1. Optionally, multiple pieces indication information in  
5 FIG. 3B may be understood as the first configuration information previously mentioned.

In the following, a method for transmitting information according to an embodiment of the present invention will be described with reference to an example in FIG. 4A. As shown in FIG. 4A, ■ represents a common control channel on carrier 1. In FIG. 4A, other various configuration information on carrier 2, which is not limited to a UE-specific control channel,  
10 may be indicated by the network device through the common control channel on carrier 1. Optionally, the indication information in FIG. 4A may be understood as the first configuration information previously mentioned.

In the following, a method for transmitting information according to an embodiment of the present invention will be described with reference to an example in FIG. 4B. As shown in FIG. 4B, ■ represents a common control channel on carrier 1. In FIG. 4B, other various configuration information in each time-frequency scheduling unit (such as time-frequency scheduling unit 1, time-frequency scheduling unit 2, time-frequency scheduling unit 3, and time-frequency scheduling unit 4) on carrier 2, which is not limited to a UE-specific control channel, may be indicated by the network device through the common control channel on  
15 carrier 1. Optionally, various indication information in FIG. 4B may be understood as the first configuration information previously mentioned.

It should be understood that the examples in FIG. 3A, FIG. 3B, FIG. 4A and FIG. 4B are introduced herein only for the convenience of understanding the technical solutions of embodiments of the present invention by those skilled in the art, which does not constitute  
25 limitation on the present invention.

In the following, a method for transmitting information according to another embodiment of the present invention will be described with reference to FIG. 5. FIG. 5 shows an illustrative flow chart of a method 500 for transmitting information according to another embodiment of the present invention. The method 500 may be performed by a network device, for example, the

network device may be the base station 21 in FIG. 1. As shown in FIG. 5, the method 500 includes the act S510.

5 In S510, a network device sends first configuration information to a terminal device through system information on a first carrier, wherein the first configuration information is used for indicating a configuration on the second carrier, and the first carrier and the second carrier are different.

In an embodiment of the present invention, the system information may be understood as system broadcast information.

10 The difference from the previous embodiments is that, in this embodiment, the first control channel and the second control channel are not distinguished, but the related configuration information is sent to the terminal device through the system information. Alternatively, it may also be understood that the “system information” in the embodiment of the present invention may correspond to the “first control channel” in the preceding method 200, and the “control channel” in the embodiment of the present invention may correspond to the  
15 “second control channel” in the preceding method 200.

Specifically, the network device may send the first configuration information to the terminal device through the system information on the first carrier, wherein the first configuration information is used for indicating the configuration on the second carrier, and the first carrier is different from the second carrier. In this way, the network device does not need to  
20 send all of system information on each carrier, which saves the overhead of the system information. Correspondingly, the terminal device may receive the first configuration information sent by the network device through the system information on the first carrier, so as to obtain configurations of multiple carriers according to the first configuration information, thus avoiding the detection of the system information of the multiple carriers, reducing the  
25 complexity of the terminal device, and saving the power of the terminal device.

Optionally, as an embodiment, the first configuration information is configuration information of a control channel on the second carrier.

Optionally, as an embodiment, the first configuration information includes at least one of serial number information of a time domain scheduling unit in which the control channel is

located, information of a resource used by the control channel, and information of a numerology used by the control channel.

Optionally, as an embodiment, the time domain scheduling unit includes a time slot, mini-slot, or a sub-frame.

5        Optionally, as an embodiment, the first configuration information may be resource allocation information of resources on the second carrier.

Optionally, as an embodiment, the first configuration information may include at least one of structure information of a time domain scheduling unit within resources of the second carrier, reserved resource information of resources of the second carrier, and resource pool information  
10 of resources of the second carrier.

Optionally, as an embodiment, the system information carries indication information used for indicating a serial number of a time domain scheduling unit corresponding to the first configuration information.

Here, concepts or terms appeared in this embodiment are similar to those in the previous  
15 embodiment, and will not be repeated for sake of conciseness.

Therefore, with the method for transmitting information according to the embodiment of the present invention, the network device sends the first configuration information to the terminal device through system information on the first carrier, wherein the first configuration information is used for indicating the configuration on a second carrier, and the first carrier is  
20 different from the second carrier, the network device does not need to send all of system information on each carrier, thus saving the overhead of the system information.

Now, a method for transmitting information according to an embodiment of the present invention will be described with reference to an example in FIG. 6A. As shown in FIG. 6A,  represents system broadcast information (located within the resources of carrier 1) and  represents a control channel corresponding to each carrier (such as carrier 1 and carrier 2). Here,  
25 the network device may transmit control channels of other carriers (such as carrier 1 and carrier 2) to the terminal device through system broadcast information. Optionally, the network device may further send other configuration information (such as the first configuration information) to the terminal device through the system broadcast information, and this is not restricted in the

present invention. Similarly, the indication information in FIG. 6A may also be understood as the first configuration information or other configuration information.

In the following, a method for transmitting information according to an embodiment of the present invention will be described with reference to an example in FIG. 6B. As shown in  
 5 FIG. 6B, ■ represents system broadcast information (located in the resources using subcarrier interval f1), and □ represents a control channel corresponding to a time domain scheduling unit (such as time domain scheduling unit 1, time domain scheduling unit 2, time domain scheduling unit 3, time domain scheduling unit 4, or time domain scheduling unit 5) in each carrier (such as carrier 1 or carrier 2). Here, the network device may transmit control channels  
 10 of time domain scheduling units of other carriers to the terminal device through the system broadcast information. Optionally, the network device may send other configuration information (such as the first configuration information) to the terminal device through system broadcast information, and this is not restricted in the present invention. Similarly, multiple  
 15 pieces of indication information in FIG. 6B may also be understood as the first configuration information or other configuration information.

In this example, the network device sends first configuration information (i.e., indication information) to the terminal device through system broadcast information on the first carrier, wherein the first configuration information is used for indicating the configuration within the resources of the second carrier, and the first carrier is different from the second carrier, and the  
 20 overhead of common control channel can be saved.

The methods according to embodiments of the present invention have been described above from a network device side. Next, a method according to an embodiment of the present invention will be described from a terminal device side. For the sake of conciseness, the concepts or terms same as or similar to those on the network device side will not be repeated.

25 FIG. 7 shows a schematic flowchart of a method 700 for transmitting information according to an embodiment of the present invention. The method 700 may be performed by a terminal device, for example, the terminal device may be the terminal device 11, or the terminal device 12, or the terminal device 13 in FIG. 1. The method 700 may correspond to the preceding method 200. As shown in FIG. 7, the method 700 includes the act S710.

In S710, a terminal device receives first configuration information sent by a network device through a first control channel on a first carrier, wherein the first configuration information is used for indicating a configuration on a second carrier, and the first carrier and the second carrier are different.

5        In an embodiment of the present invention, the terminal device receives the first configuration information sent by the network device through the first control channel on the first carrier, wherein the first configuration information is used for indicating the configuration on the second carrier, the first carrier is different from the second carrier. The terminal device can receive the first configuration information sent by the network device through the first  
10 control channel of a carrier to obtain configuration information of multiple carriers, so as to avoid a detection of a common control channels on the multiple carriers, reduce the complexity of the terminal device, and save the power of the terminal device.

Optionally, as an embodiment, the first configuration information is configuration information of a second control channel on the second carrier.

15        Optionally, as an embodiment, the first control channel is a common control channel and the second control channel is a UE-specific control channel of the terminal device.

Optionally, as an embodiment, the first configuration information includes at least one of serial number information of a time domain scheduling unit in which the second control channel is located, information of a resource used by the second control channel, and  
20 information of a numerology used by the second control channel.

Optionally, as an embodiment, the first configuration information is resource configuration information of resources of the second carrier.

Optionally, as an embodiment, the first configuration information includes at least one of structure information of a minimum time domain scheduling unit within resources of the second  
25 carrier, reserved resource information of resources of the second carrier, and resource pool information of resources of the second carrier.

Optionally, as an embodiment, the first control channel carries indication information used for indicating a serial number of a time domain scheduling unit corresponding to the first configuration information.

Optionally, as an embodiment, the time domain scheduling unit includes a time slot, a mini-slot, or a sub-frame.

Optionally, as an embodiment, the numerology used by the second control channel includes at least one of the following parameters:

- 5 a subcarrier interval, a width of minimum frequency domain scheduling unit, a length of orthogonal frequency division multiplexing (OFDM) symbol, a length of minimum time domain scheduling unit, and a length of Cyclic Prefix (CP).

Therefore, the terminal device receives the first configuration information sent by the network device through the first control channel on the first carrier, wherein the first  
10 configuration information is used for indicating the configuration on the second carrier, and the first carrier and the second carrier are different, so that the overhead of common control channel can be saved, the complexity of the terminal device can be reduced, and the power of the terminal device can be saved.

FIG. 8 shows a schematic flowchart of a method 800 for transmitting information  
15 according to an embodiment of the present invention. The method 800 may be performed by a terminal device, for example, the terminal device may be the terminal device 11, or the terminal device 12, or the terminal device 13 in FIG. 1. The method 800 may correspond to the preceding method 500. As shown in FIG. 8, the method 800 includes the act S810.

In S810, a terminal device receives first configuration information sent by a network  
20 device through system information on a first carrier, wherein the first configuration information is used for indicating a configuration on a second carrier, and the first carrier and the second carrier are different.

In an embodiment of the present invention, the terminal device may receive the first configuration information sent by the network device through the system information on the  
25 first carrier, so as to obtain configurations of multiple carriers according to the first configuration information, thus avoiding the detection of system information of the multiple carriers, reducing the complexity of the terminal device, and saving the power of the terminal device.

Optionally, as an embodiment, the first configuration information is configuration

information of a control channel on the second carrier.

Optionally, as an embodiment, the first configuration information includes at least one of serial number information of a time domain scheduling unit in which the control channel is located, information of a resource used by the control channel, and information of a  
5 numerology used by the control channel.

Optionally, as an embodiment, the time domain scheduling unit includes a time slot, a mini-slot, or a sub-frame.

Optionally, as an embodiment, the first configuration information is resource allocation information of resources of the second carrier.

10      Optionally, as an embodiment, the first configuration information may include at least one of structure information of a time domain scheduling unit within resources of the second carrier, reserved resource information of resources of the second carrier, and resource pool information of resources of the second carrier.

15      Optionally, as an embodiment, the system information carries indication information used for indicating a serial number of a time domain scheduling unit corresponding to the first configuration information.

Optionally, as an embodiment, the time domain scheduling unit includes a time slot, a mini-slot, or a sub-frame.

20      Optionally, the numerology used by the control channel includes at least one of the following parameters:

a subcarrier interval, a width of frequency domain scheduling unit, a length of orthogonal frequency division multiplexing (OFDM) symbol, a length of minimum domain scheduling unit, and a length of cyclic prefix (CP).

25      Therefore, the terminal device may receive the first configuration information sent by the network device through the system information on the first carrier, so as to obtain the configurations of multiple carriers according to the first configuration information, thus avoiding a detection of system information of the multiple carriers, reducing the complexity of the terminal device, and saving the power of the terminal device.

Now, a network device according to an embodiment of the present invention will be described. FIG. 9 shows a network device 900 according to an embodiment of the present invention. As shown in FIG. 9, the network device 900 includes a sending module 910.

5 The sending module 910 is used for sending first configuration information to a terminal device through a first control channel on a first carrier, wherein the first configuration information is used for indicating a configuration on a second carrier, and the first carrier and the second carrier are different.

Optionally, as an embodiment, the first configuration information is configuration information of a second control channel on the second carrier.

10 Optionally, as an embodiment, the first control channel is a common control channel, and the second control channel is a UE-specific control channel of the terminal device.

Optionally, as an embodiment, the first configuration information includes at least one of serial number information of a time domain scheduling unit in which the second control channel is located, information of a resource used by the second control channel, and  
15 information of a numerology used by the second control channel.

Optionally, as an embodiment, the first configuration information is resource configuration information of resources of the second carrier.

Optionally, the first configuration information may include at least one of structure information of a time domain scheduling unit within resources of the second carrier, reserved  
20 resource information of resources of the second carrier, and resource pool information of resources of the second carrier.

Optionally, as an embodiment, the first control channel carries indication information used for indicating a serial number of a time domain scheduling unit corresponding to the first configuration information.

25 Optionally, as an embodiment, the time domain scheduling unit includes a time slot, a mini-slot, or a sub-frame.

The network device 900 according to the embodiment of the present invention may perform the method 200 for transmitting information according to the embodiment of the

present invention, and the above and other operations and/or functions of various units in the network device 900 are respectively for implementing the corresponding flows of the various methods mentioned above, which will not be described here in detail for sake of conciseness.

The network device 900 according to the embodiment of the present invention sends first  
5 configuration information to a terminal device through a first control channel on a first carrier, wherein the first configuration information is used for indicating a configuration on a second carrier, and the first carrier and the second carrier are different. The network device 900 does not need to transmit a common control channel on each carrier, thus saving the overhead of common control channel.

10 FIG. 10 shows a network device 1000 according to another embodiment of the present invention. As shown in FIG. 10, the network device 1000 includes a sending module 1010.

The sending module 1010 is used for sending first configuration information to a terminal  
device through system information on a first carrier, wherein the first configuration information is used for indicating a configuration on a second carrier, and the first carrier and the second  
15 carrier are different.

Optionally, as an embodiment, the first configuration information is configuration information of a control channel on the second carrier.

Optionally, as an embodiment, the first configuration information includes at least one of  
serial number information of a time domain scheduling unit in which the control channel is  
20 located, information of a resource used by the control channel, and information of a numerology used by the control channel.

Optionally, as an embodiment, the first configuration information is resource allocation information of resources of the second carrier.

Optionally, as an embodiment, the first configuration information may include at least one  
25 of structure information of a time domain scheduling unit within resources of the second carrier, reserved resource information of resources of the second carrier, and resource pool information of resources of the second carrier.

Optionally, as an embodiment, the system information carries indication information used

for indicating a serial number of a time domain scheduling unit corresponding to the first configuration information.

Optionally, as an embodiment, the time domain scheduling unit includes a time slot, mini-slot, or a sub-frame.

5       The network device 1000 according to the embodiment of the present invention may perform the method 500 for transmitting information according to the embodiment of the present invention, and the above and other operations and/or functions of various units in the network device 1000 are respectively for implementing the corresponding flows of the various methods mentioned above, which will not be described here in detail for sake of conciseness.

10       Therefore, the network device 1000 according to the embodiment of the present invention sends the first configuration information to a terminal device through system information on a first carrier, wherein the first configuration information is used for indicating the configuration on a second carrier, and the first carrier and the second carrier are different. The network device does not need to send all of system information on each carrier, thus saving the overhead of the  
15       system information.

Now, a terminal device according to an embodiment of the present invention will be described. FIG. 11 shows a terminal device 1100 according to an embodiment of the present invention. For sake of conciseness, some similar terms, definitions or concepts will not be repeated. As illustrated in FIG. 11, the terminal device 1100 includes a receiving module 1110.

20       The receiving module 1110 is used for receiving first configuration information sent by a network device through a first control channel on a first carrier, wherein the first configuration information is used for indicating a configuration on a second carrier, and the first carrier and the second carrier are different.

25       The receiving module 1110 is further used for: receiving the first configuration information sent by the network device through the first control channel on the first carrier, wherein the first configuration information is resource configuration information of resources of the second carrier.

The terminal device 1100 according to the embodiment of the present invention may perform the method 700 for transmitting information according to the embodiment of the

present invention, and the above and other operations and/or functions of various units in the terminal device 1100 are respectively for implementing the corresponding flows of the various methods mentioned above, which will not be described here in detail for sake of conciseness.

Therefore, the terminal device 1100 according to the embodiment of the present invention receives first configuration information sent by a network device through a first control channel on a first carrier, wherein the first configuration information is used for indicating the configuration on the second carrier, and the first carrier is different from the second carrier, and the overhead of common control channel can be saved and the power of the terminal device can be saved.

FIG. 12 shows a terminal device 1200 according to an embodiment of the present invention. For sake of conciseness, some similar terms, definitions or concepts will not be repeated. As illustrated in FIG. 12, the terminal device 1200 includes a receiving module 1210.

The receiving module 1210 is used for receiving first configuration information sent by a network device through system information on a first carrier, wherein the first configuration information is used for indicating a configuration on a second carrier, and the first carrier and the second carrier are different.

The terminal device 1200 according to the embodiment of the present invention may perform the method 800 for transmitting information according to the embodiment of the present invention, and the above and other operations and/or functions of various units in the terminal device 1200 are respectively for implementing the corresponding flows of the various methods mentioned above, which will not be described here in detail for sake of conciseness.

Therefore, the terminal device 1200 according to the embodiment of the present invention receives the first configuration information sent by a network device through the system information on the first carrier, wherein the first configuration information is used for indicating the configuration on the second carrier, and the first carrier and the second carrier are different. The terminal device may receive the first configuration information sent by the network device through the system information on the first carrier, so as to obtain configurations of multiple carriers according to the first configuration information, thus avoiding a detection of the system information of the multiple carriers, reducing the complexity of the terminal device, and saving

the power of the terminal device.

FIG. 13 shows a structure of a network device provided according to an embodiment of the present invention, which includes at least one processor 1302 (e.g., CPU), at least one network interface 1303 or another communication interface, and a memory 1304. Optionally, the network device may also include a receiver 1305 and a transmitter 1306. The processor 1302 is used for executing an executable module, such as a computer program, stored in the memory 1304. The memory 1304 may include high-speed Random Access Memory (RAM) or non-volatile memory, such as at least one disk memory. Communication connection with at least one of other network elements is realized through at least one network interface 1303 (which may be wired or wireless). Receiver 1305 and transmitter 1306 are used for transmitting various signals or information.

In some embodiments, the memory 1304 stores a program 13041 that may be executed by the processor 1302 for implementing a method of a network device side of an embodiment of the present invention described above.

In an embodiment of the present invention, the transmitter 1306 sends first configuration information to a terminal device through a first control channel on a first carrier, wherein the first configuration information is used for indicating a configuration on a second carrier, and the first carrier and the second carrier are different.

FIG. 14 shows a structure of a network device provided according to another embodiment of the present invention, which includes at least one processor 1402 (e.g., CPU), at least one network interface 1403 or another communication interface, and a memory 1404. Optionally, the network device may also include a receiver 1405 and a transmitter 1406. The processor 1402 is used for executing an executable module, such as a computer program, stored in the memory 1404. The memory 1404 may include high-speed Random Access Memory (RAM) or non-volatile memory, such as at least one disk memory. Communication connection with at least one of other network elements is realized through at least one network interface 1403 (which may be wired or wireless). Receiver 1405 and transmitter 1406 are used for transmitting various signals or information.

In some embodiments, the memory 1404 stores a program 14041, which may be executed

by the processor 1402 for implementing a method of a network device side of an embodiment of the present invention described above.

In an embodiment of the present invention, the transmitter 1406 sends first configuration information to a terminal device through system information on a first carrier, wherein the first  
5 configuration information is used for indicating a configuration on a second carrier, and the first carrier and the second carrier are different.

FIG. 15 shows a structure of a terminal device provided according to another embodiment of the present invention, which includes at least one processor 1502 (e.g., CPU), at least one network interface 1503 or another communication interface, and a memory 1504. Optionally,  
10 the terminal device may also include a receiver 1505 and a transmitter 1506. The processor 1502 is used for executing an executable module, such as a computer program, stored in the memory 1504. The memory 1504 may include high-speed Random Access Memory (RAM) or non-volatile memory, such as at least one disk memory. Communication connection with at least one of other network elements is realized through at least one network interface 1503  
15 (which may be wired or wireless). Receiver 1505 and transmitter 1506 are used for transmitting various signals or information.

In some embodiments, the memory 1504 stores a program 15041 that can be executed by the processor 1502 for implementing a method of a terminal device side of an embodiment of the present invention described above.

20 In an embodiment of the present invention, the receiver 1505 receives first configuration information sent by a network device through a first control channel on a first carrier, wherein the first configuration information is used for indicating a configuration on a second carrier, and the first carrier and the second carrier are different.

FIG. 16 shows a structure of a terminal device provided according to an embodiment of  
25 the present invention, which includes at least one processor 1602 (e.g., CPU), at least one network interface 1603 or another communication interface, and a memory 1604. Optionally, the terminal device may also include a receiver 1605 and a transmitter 1606. The processor 1602 is used for executing executable modules, such as computer programs, stored in the memory 1604. The memory 1604 may include high-speed Random Access Memory (RAM) or

non-volatile memory, such as at least one disk memory. Communication connection with at least one of other network elements is realized through at least one network interface 1603 (which may be wired or wireless). Receiver 1605 and transmitter 1606 are used for transmitting various signals or information.

5        In some embodiments, the memory 1604 stores a program 16041 that can be executed by the processor 1602 for implementing a method of the terminal device side of an embodiment of the present invention described above.

10        In an embodiment of the present invention, the receiver 1605 receives first configuration information sent by a network device through system information on a first carrier, wherein the first configuration information is used for indicating a configuration on a second carrier, and the first carrier and the second carrier are different.

15        It should be understood that in various embodiments of the present invention, values of sequence numbers in the above-mentioned processes do not imply an order of execution, and an order of execution of each process should be determined by its function and internal logic, and should not constitute any limitation on an implementation process of the embodiment of the present invention.

20        Those of ordinary skill in the art will recognize that the exemplary elements and algorithm acts described in connection with the embodiments disclosed herein can be implemented in electronic hardware, or a combination of computer software and electronic hardware. Whether these functions are performed in hardware or software depends on the specific application and design constraints of the technical solution. Skilled in the art may use different methods to implement the described functions for each particular application, but such implementation should not be considered to be beyond the scope of embodiments of the present invention.

25        Those skilled in the art can clearly understand that for convenience and conciseness of description, corresponding processes in the aforementioned method embodiments may be referred to for the specific working processes of the system, device, and unit described above, which are not repeated here.

      In several embodiments provided according to the present invention, it should be

understood that the disclosed system, apparatus and method may be implemented in other ways. For example, the apparatus embodiments described above are only illustrative, for example, the division of the units is only a logical function division, and there may be other division manners in actual implementation. For example, multiple units or components may be combined or  
5 integrated into another system, or some features may be ignored or not executed. On the other hand, the mutual coupling or direct coupling or communication connection shown or discussed may be indirect coupling or communication connection through some interface, apparatus or unit, and may be electrical, mechanical or in other forms.

The unit described as a separate component may or may not be physically separated, and  
10 the component shown as a unit may or may not be a physical unit, i.e., it may be located in one place or may be distributed over multiple network units. Some or all of the units may be selected according to practical needs to achieve a purpose of embodiments.

In addition, various functional units in various embodiments of the present invention may be integrated in one processing unit, or various units may be physically present separately, or  
15 two or more units may be integrated in one unit.

The functions may be stored in a computer readable storage medium if implemented in a form of software functional units and sold or used as a separate product. Based on this understanding, the technical solution of embodiments of the present invention, in essence, or the part contributing to the related art, or the part of the technical solution, may be embodied in  
20 the form of a software product stored in a storage medium, including several instructions for causing a computer device (which may be a personal computer, a server, or a network device, etc.) to perform all or part of the acts of the methods described in various embodiments of the present invention. The aforementioned storage media include various media capable of storing program codes such as U disk, mobile hard disk, read-only memory (ROM), random access  
25 memory (RAM), magnetic disk or optical disk.

The foregoing are merely specific implementation modes of embodiments of the present invention, but the protection scope of embodiments of the present invention is not limited thereto. Any person skilled in the art can easily conceive changes or substitutions within the technical scope disclosed by embodiments of the present invention, which should be included

within the protection scope of embodiments of the present invention. Therefore, the protection scope of embodiments of the present invention should be subject to the protection scope of the claims.

## Claims

1. A method for transmitting information, comprising:

5 sending, by a network device, first configuration information to a terminal device through a first control channel on a first carrier, wherein the first configuration information is used for indicating a configuration on a second carrier, and the first carrier and the second carrier are different.

2. The method of claim 1, wherein the first configuration information is configuration information of a second control channel on the second carrier.

10 3. The method of claim 2, wherein the first control channel is a common control channel and the second control channel is a UE-specific control channel of the terminal device.

4. The method of claim 2 or 3, wherein the first configuration information comprises at least one of serial number information of a time domain scheduling unit in which the second control channel is located, information of a resource used by the second control channel, and information of a numerology used by the second control channel.

15 5. The method of any one of claims 1 to 4, wherein the first configuration information comprises at least one of structural information of a time domain scheduling unit within resources of the second carrier, reserved resource information of resources of the second carrier, and resource pool information of resources of the second carrier.

20 6. The method of any one of claims 1 to 5, wherein the first control channel carries indication information used for indicating a serial number of a time domain scheduling unit corresponding to the first configuration information.

7. The method of any one of claims 4 to 6, wherein the time domain scheduling unit comprises a time slot, a mini-slot, or a sub-frame.

8. A method for transmitting information, comprising:

25 sending, by a network device, first configuration information to a terminal device through system information on a first carrier, wherein the first configuration information is used for indicating a configuration on a second carrier, and the first carrier and the second carrier are different.

9. The method of claim 8, wherein the first configuration information is configuration information of a control channel on the second carrier.

10. The method of claim 8 or claim 9, wherein the first configuration information comprises at least one of serial number information of a time domain scheduling unit in which  
5 the control channel is located, information of a resource used by the control channel, and information of a numerology used by the control channel.

11. The method of any one of claims 8 to 10, wherein the first configuration information comprises at least one of structural information of a time domain scheduling unit within  
resources of the second carrier, reserved resource information of resources of the second carrier,  
10 and resource pool information of resources of the second carrier.

12. The method of any one of claims 8 to 11, wherein the system information carries indication information used for indicating a serial number of a time domain scheduling unit corresponding to the first configuration information.

13. The method of any one of claims 10 to 12, wherein the time domain scheduling unit  
15 comprises a time slot, a mini-slot, or a sub-frame.

14. A method for transmitting information, comprising:

receiving, by a terminal device, first configuration information sent by a network device through a first control channel on a first carrier, wherein the first configuration information is used for indicating a configuration on a second carrier, and the first carrier and the second  
20 carrier are different.

15. The method of claim 14, wherein the first configuration information is configuration information of a second control channel on the second carrier.

16. The method of claim 15, wherein the first control channel is a common control channel and the second control channel is a UE-specific control channel of the terminal device.

25 17. The method of claim 15 or claim 16, wherein the first configuration information comprises at least one of serial number information of a time domain scheduling unit in which the second control channel is located, information of a resource used by the second control channel, and information of a numerology used by the second control channel.

18. The method of any one of claims 14 to 17, wherein the first configuration information comprises at least one of structural information of a time domain scheduling unit within resources of the second carrier, reserved resource information of resources of the second carrier, and resource pool information of resources of the second carrier.

5        19. The method of any one of claims 14 to 18, wherein the first control channel carries indication information used for indicating a serial number of a time domain scheduling unit corresponding to the first configuration information.

20. The method of any one of claims 17 to 19, wherein the time domain scheduling unit comprises a time slot, a mini-slot, or a sub-frame.

10       21. A method for transmitting information, comprising:  
receiving, by a terminal device, first configuration information sent by a network device through system information on a first carrier, wherein the first configuration information is used for indicating configuration on a second carrier, and the first carrier and the second carrier are different.

15       22. The method of claim 21, wherein the first configuration information is configuration information of a control channel on the second carrier.

20       23. The method of claim 21 or claim 22, wherein the first configuration information comprises at least one of serial number information of a time domain scheduling unit in which the control channel is located, information of a resource used by the control channel, and information of a numerology used by the control channel.

24. The method of any one of claims 21 to 23, wherein the first configuration information comprises at least one of structural information of a time domain scheduling unit within resources of the second carrier, reserved resource information of resources of the second carrier, and resource pool information of resources of the second carrier.

25       25. The method of any one of claims 21 to 24, wherein the system information carries indication information used for indicating a serial number of a time domain scheduling unit corresponding to the first configuration information.

26. The method of any one of claims 23 to 25, wherein the time domain scheduling unit

comprises a time slot, a mini-slot, or a sub-frame.

27. A network device, comprising:

5 a sending module, used for sending first configuration information to a terminal device through a first control channel on a first carrier, wherein the first configuration information is used for indicating a configuration on a second carrier, and the first carrier and the second carrier are different.

28. The network device of claim 27, wherein the first configuration information is configuration information of a second control channel on the second carrier.

10 29. The network device of claim 28, wherein the first control channel is a common control channel and the second control channel is a UE-specific control channel of the terminal device.

30. The network device of claim 28 or claim 29, wherein the first configuration information comprises at least one of serial number information of a time domain scheduling unit in which the second control channel is located, information of a resource used by the second control channel, and information of a numerology used by the second control channel.

15 31. The network device of any one of claims 27 to 30, wherein the first configuration information comprises at least one of structural information of a time domain scheduling unit within resources of the second carrier, reserved resource information of resources of the second carrier, and resource pool information of resources of the second carrier.

20 32. The network device of any one of claims 27 to 31, wherein the first control channel carries indication information used for indicating a serial number of a time domain scheduling unit corresponding to the first configuration information.

33. The network device of any one of claims 30 to 32, wherein the time domain scheduling unit comprises a time slot, a mini-slot, or a sub-frame.

34. A network device, comprising:

25 a sending module, used for sending first configuration information to a terminal device through system information on a first carrier, wherein the first configuration information is used for indicating a configuration on a second carrier, and the first carrier and the second carrier are different.

35. The network device of claim 34, wherein the first configuration information is configuration information of a control channel on the second carrier.

36. The network device of claim 34 or 35, wherein the first configuration information comprises at least one of serial number information of a time domain scheduling unit in which  
5 the control channel is located, information of a resource used by the control channel, and information of a numerology used by the control channel.

37. The network device of any one of claims 34 to 36, wherein the first configuration information comprises at least one of structural information of a time domain scheduling unit within resources of the second carrier, reserved resource information of resources of the second  
10 carrier, and resource pool information of resources of the second carrier.

38. The network device of any one of claims 34 to 37, wherein the system information carries indication information used for indicating a serial number of a time domain scheduling unit corresponding to the first configuration information.

39. The network device of any one of claims 36 to 38, wherein the time domain  
15 scheduling unit comprises a time slot, a mini-slot, or a sub-frame.

40. A terminal device, comprising:

a receiving module, used for receiving first configuration information sent by a network device through a first control channel on a first carrier, wherein the first configuration information is used for indicating a configuration on a second carrier, and the first carrier and  
20 the second carrier are different.

41. The terminal device of claim 40, wherein the first configuration information is configuration information of a second control channel on the second carrier.

42. The terminal device of claim 41, wherein the first control channel is a common control channel, and the second control channel is a UE-specific control channel of the terminal device.

25 43. The terminal device of claim 40 or claim 41, wherein the first configuration information comprises at least one of serial number information of a time domain scheduling unit in which the second control channel is located, information of a resource used by the second control channel, and information of a numerology used by the second control channel.

44. The terminal device of any one of claims 40 to 43, wherein the first configuration information comprises at least one of structural information of a time domain scheduling unit within resources of the second carrier, reserved resource information of resources of the second carrier, and resource pool information of resources of the second carrier.

5        45. The terminal device of any one of claims 40 to 44, wherein the first control channel carries indication information used for indicating a serial number of a time domain scheduling unit corresponding to the first configuration information.

46. The terminal device of any one of claims 43 to 45, wherein the time domain scheduling unit comprises a time slot, a mini-slot, or a sub-frame.

10       47. A terminal device, comprising:

a receiving module, used for receiving first configuration information sent by a network device through system information on a first carrier, wherein the first configuration information is used for indicating a configuration on a second carrier, and the first carrier and the second carrier are different.

15       48. The terminal device of claim 47, wherein the first configuration information is configuration information of a control channel on the second carrier.

49. The terminal device of claim 47 or claim 48, wherein the first configuration information comprises at least one of serial number information of a time domain scheduling unit in which the control channel is located, information of a resource used by the control  
20 channel, and information of a numerology used by the control channel.

50. The terminal device of any one of claim 47 to 49, wherein the first configuration information comprises at least one of structural information of a time domain scheduling unit within resources of the second carrier, reserved resource information of resources of the second carrier, and resource pool information of resources of the second carrier.

25       51. The terminal device of any one of claims 47 to 50, wherein the system information carries indication information used for indicating a serial number of a time domain scheduling unit corresponding to the first configuration information.

52. The terminal device of any one of claims 49 to 51, wherein the time domain

scheduling unit comprises a time slot, a mini-slot, or a sub-frame.