

Description

BACKGROUND OF THE INVENTION

Field of the Invention

This invention relates to a rotary type injection orientation blow molding machine which can perform operations from injection molding of a preform formed of a synthetic resin to orientation blow molding of a hollow molded article.

Description of the Prior Art

The molding machines of this kind include one type in which a rotary disk on the machine bed is held by a base plate secured by a tie bar, and an injection mold is moved with respect to a hold mold on the lower side of the rotary disk to effect clamping, and include another type in which a mold is fixed, and a base plate is moved together with a rotary disk to effect clamping.

In the molding machine of the base plate-fixed type, since the injection mold is vertically moved, the injection apparatus cannot always be placed in nozzle touch with the mold, and it is necessary to move the injection apparatus backward after every completion of injection. Therefore, it takes time for the injection molding, which comprises a bottle-neck in improving the molding cycle. Furthermore, both the injection core and mold need be clamped, as a consequence of which a larger clamping device is required.

On the other hand, in the molding machine of the base plate movable type, since the injection mold is fixed, the aforementioned problem can be overcome. However, it is necessary to move the clamping plate provided with the injection core up and down so as not to be delayed in the movement of the base plate, and the moving stroke thereof is larger than in the case of the fixed type. Therefore, it takes time for open- and closing the mold, which comprises a bottle-neck in shortening the molding cycle.

A molding machine of this type is disclosed in EP-A-0 162 422. It has four kinds of different plates arranged above a base, namely a top plate, a movable plate, a clamping plate, and a transfer plate.

Accordingly, the known machine is very heavy. In addition, the downwardly moving device is only the clamping device and it has to move the heavy clamping plate including an expanding device and the heavy movable plate with the transfer plate at the same time. Furthermore since the position for pushing the movable plate and the clamping plate is only one which is spaced off the center point of the plates, the force from the clamping device is

unbalancedly transferred to these plates. The clamping force, however, has to be transferred to the clamping plate and the plate holding the molds as equally as possible so as to maintain high production accuracy, thus the speed for clamping is have to be decreased over the whole stroke of the clamping device and the productivity is reduced.

WO-A-88 06 513 discloses a clamping cylinder for injection molding machines using a booster ram in co-axial arrangement.

OBJECT OF THE INVENTION

This invention has been contemplated in view of the above. An object of the invention to provide, in a molding machine of the type in which the base plate side is moved, a new rotary type injection orientation blow molding machine capable of vertically moving the clamping plate at a high speed.

SUMMARY OF THE INVENTION

According to the present invention, there is provided a rotary type injection orientation blow molding machine as defined in claims 1 and 2

BRIEF DESCRIPTION OF THE DRAWINGS

The drawings show embodiments of a rotary type injection blow molding machine according to this invention.

FIG. 1 is a plan view of the molding machine, a part of which is cut away;

FIG. 2 is a side view when the mold is opened;

FIG. 3 is a longitudinal sectional side view of an injection molding portion and an orientation blow molding portion during molding;

FIG. 4 is a longitudinal sectional front view of the injection molding portion;

FIG. 5 is a longitudinal sectional side view of an injection molding portion and an orientation blow molding portion when the mold is opened;

FIG. 6 is a longitudinal sectional side view of an injection molding portion and an orientation blow molding portion during molding according to another embodiment; and

FIG. 7 is a partly longitudinal sectional side view of an upper portion of a molding machine according to still another embodiment.

In the drawings, reference numeral 1 designates a machine bed, 2 a horizontal base plate above the machine bed, 3 a transfer plate rotatably embraced in the underside of the base plate 2, and 4 a seat plate on the machine bed.

Tie bars 5 stand vertically upright at four portions of the seat plate 4, and peripheral edges of the base plate are slidably inserted into the tie bars

5. Insert holes are bored in three portions of the transfer plate 3, and hold molds 6 also serving as a mold forming a mouth portion of a preform are radially closeably mounted on the lower surface of the transfer plate at the portions of the insert holes.

A drive device 7 for intermittently rotating the transfer plate 3 every 120° leftwise is provided in the central portion at the upper portion of the base plate. Stop positions of the hold molds 6 of the transfer plate 2 are set to be an injection molding portion, an orientation blow molding portion and a releasing portion, respectively. Core insert portions 8 are bored, and a clamping device 9, an orientation blow device 10 and a releasing device 11 are disposed in order on said portions.

A fixed plate 12 of the clamping device 9 is formed integral with a frame 13 for connecting upper ends of the tie bars 5 to each other, the fixed plate 12 being mounted over the upper ends of a pair of tie bars 5 on the both sides of the injection molding portion. A clamping cylinder 14 is downwardly integrally formed at the upper portion of the fixed plate 12, and a charge cylinder 15 for pressurized oil and a bypass 16 vertically communicated within the clamping cylinder are provided on both sides thereof.

The inner diameter of the upper chamber of the clamping cylinder is larger than the inner diameter of the lower chamber, the lower chamber being communicated with the charge cylinder 15, and a booster ram 18 having a piston inserted into a cylindrical clamping ram 17 is positioned in the central portion therein. A piston 19 of the clamping ram 17 has the outer diameter water-tightly fitted into the lower chamber, and the clamping ram 17 is moved downward due to the pressurized oil within the cylinder according to a difference in pressure receiving area between the upper surface and lower surface of the piston.

The bypass 16 is interiorly provided with a valve 20 which defines upper and lower supply and discharge ports connected to a hydraulic circuit (not shown) if necessary and which opens and closes the bypass (see FIG. 3).

The cylindrical clamping ram 17 and a pair of piston rods 21 of the charge cylinder 15 on the both sides are connected to a clamping plate 22 vertically movably inserted over both the tie bars 5, and an injection core 23 is mounted on the underside of the clamping plate 22.

Reference numeral 24 designates a base-plate vertically moving cylinder. The cylinders 24 are provided on a seat plate externally of the tie bar 5 of the injection molding portion and on a seat plate between the orientation blow molding portion and the releasing portion, and their piston rods 25 are connected to the edge side of the base plate 2.

Reference numeral 26 designates an injection mold, which is secured to a pedestal 29 vertically movably provided by a limit pin 27 and a spring member 28 on the seat plate 4. A lock 31 always placed in nozzle touch with an injection device 30 is secured to the seat plate interiorly of the pedestal 29.

An air or hydraulically operated core insert cylinder 32 and an orientation cylinder 33 are provided on the base plate 2 of the orientation blow molding portion 10, and a blow core 36 interiorly provided with an orientation rod 35 is mounted under a bed plate 34 having a piston rod 32a connected thereto.

A blow mold 37 is provided on the seat plate. The blow mold 37 is radially closeably provided together with a clamping cylinder 41 on a support bed 40 connected to a ram 39 of an air or hydraulically operated elevating device 38 installed underside of the seat plate.

An air or hydraulically operated releasing cylinder 42 is provided on the base plate of the releasing portion 11. Wedge members 45 entered from the base plate and an opening 44 (see FIG. 1) of the transfer plate to force open the hold mold 6 are mounted on both ends of a bed plate 43 connected to a piston rod of the cylinder 42.

Reference numeral 46 designates a preform and 47 denotes a molded article.

In an embodiment shown in FIG. 7, the base-plate vertically moving cylinder 24 is mounted on a beam member 48 integrally mounted over the frame 3 and a central portion on the fixed plate side of the clamping device 9, the piston rod 25 is connected to a cover member 49 of the drive device in the central portion of the base plate, and the base plate 2 is moved up and down in the central portion.

In the molding machine having the construction as described above, when the piston rod 25 of the base-plate vertically moving cylinder 24 is contracted, the base plate 2 together with the transfer plate 3 moves down, and in the injection molding portion 9, the hold mold 6 is fitted into an upper opening of the cavity of the injection mold 26. In the orientation molding portion 10, the hold mold 6 is positioned at the central portion of the blow mold 37.

When during the downward movement of the base plate 2, pressure oil is supplied from a supply port in the bypass 16 on the side to the clamping cylinder 14, the clamping ram is moved downward due to a difference in pressure received by the piston 19 to downwardly move the injection core 23 together with the clamping plate 22. Since the piston rod 21 of the charge cylinder 15 is pulled downward due to the downward movement of the clamping plate 22, pressure oil within the charge

cylinder is delivered from the lower chamber to the clamping cylinder 14. Such a delivery is continued till the piston 19 is fitted into the lower chamber, and the pressure oil within the chamber is fed toward the upper chamber because of presence of a clearance around the piston 19. Therefore, even if pressure oil is present in the lower chamber, it will not act as a resistance, and the clamping ram 17 is moved down at a high speed.

When the piston 19 is fitted into the lower chamber, oil-pressure resistance is produced therein so that the descending speed of the clamping ram 17 slows down. When at that time, the bypass 16 is closed to let pressure oil in the lower chamber escape from a discharge port at the lower portion of the bypass to the hydraulic circuit, the mode is switched to clamping.

During the course of clamping, in the orientation blow molding portion 10, closing and clamping of the blow mold 37 are carried out. Then, this step is shifted to injection molding of the preform 46 and orientation blow molding of the molded article 47.

Upon completion of the molding, the blow mold 37 is opened, and a supply of pressure oil into the clamping cylinder is stopped, and when the bypass 16 is opened to supply pressure oil to the booster ram 18, the clamping ram 17 is moved upward together with the clamping plate 22 by the pressure oil fed under pressure into the clamping ram. At the same time, the piston rod 21 is also forced upward through the clamping plate 22, and therefore, pressure oil within the clamping cylinder is pumped up into the charge cylinder 15 via the bypass 16. Therefore, pressure oil in the upper chamber comprises no resistance so that the clamping ram 17 is moved upward at a high speed.

When the piston 25 of the base-plate vertically moving cylinder 24 is extended in synchronism with the upward movement of the clamping ram 17, the base plate 2 is moved upward together with the transfer plate 3 having the preform 46 held by the hold mold 6, and the injection core 13 is removed during such upward movement.

The difference in level of the injection mold 36 and the blow mold 37 can be adjusted by vertically changing the position of the blow mold 37.

In molding of a short preform 46, a moving stroke of the clamping ram 17 is restricted, and therefore, the injection core 23 is mounted by applying a block 50 having a predetermined thickness to compensate for the stroke to the clamping plate 22.

This invention has a configuration as mentioned above, and even in the case where the base plate is moved upward together with the transfer plate, mold opening can be done at a high speed. Moreover, since the injection device may be al-

ways placed in nozzle touch with the injection mold, there is a feature that the molding cycle time is materially shortened.

5 Claims

1. A rotary injection orientation blow molding machine comprising;
 - a machine bed (1),
 - a seat plate (4) mounted on the machine bed (1),
 - a horizontal base plate (2) vertically movably supported above said machine bed (1),
 - tie bars (5) standing upright on said seat plate (4), said base plate (2) having portions of a peripheral edge thereof which are slidably inserted by said tie bars (5), said base plate (2) having an underside portion spaced above said machine bed (1) and an upperside portion,
 - a transfer plate (3) rotatably mounted on said underside portion of said base plate (2), said transfer plate (3) having a lower surface and having hold molds (6) at three locations of said lower surface thereof,
 - a drive device (7) located in a central portion of said upperside portion of said base plate (2) to intermittently rotate said transfer plate (3) by a predetermined angle to bring each said hold mold (6) to one of said three location of said transfer plate (3),
 - a vertical clamping device (9) and an injection mold (26) with a stop position of said hold molds (6) serving as an injection molding portion; a blow mold (37) and orientation blow molding device (10) with a stop position of said hold molds (6) serving as an orientation blow molding portion; a releasing device (11) with a stop position of said hold molds (6) serving as a releasing portion; said injection molding portion, orientation blow molding portion and releasing portion being respectively provided at predetermined locations above said machine bed (1),
 - a frame (13) for connecting upper ends of said tie bars (5) with each other, and
 - a plurality of cylinders (24) for vertically moving said base plate (2) up and down, said cylinders (24) being provided between said seat plate (4) and the peripheral edge of the base plate (2), wherein said clamping device (9) comprises
 - a clamping cylinder (14) including an upper and lower chamber wherein the inner diameter of said upper chamber is larger than the inner diameter of said lower chamber and both said chambers are communicated by a bypass (16) provided with a closing valve,



cylinder is delivered from the lower chamber to the clamping cylinder 14. Such a delivery is continued till the piston 19 is fitted into the lower chamber, and the pressure oil within the chamber is fed toward the upper chamber because of presence of a clearance around the piston 19. Therefore, even if pressure oil is present in the lower chamber, it will not act as a resistance, and the clamping ram 17 is moved down at a high speed.

When the piston 19 is fitted into the lower chamber, oil-pressure resistance is produced therein so that the descending speed of the clamping ram 17 slows down. When at that time, the bypass 16 is closed to let pressure oil in the lower chamber escape from a discharge port at the lower portion of the bypass to the hydraulic circuit, the mode is switched to clamping.

During the course of clamping, in the orientation blow molding portion 10, closing and clamping of the blow mold 37 are carried out. Then, this step is shifted to injection molding of the preform 46 and orientation blow molding of the molded article 47.

Upon completion of the molding, the blow mold 37 is opened, and a supply of pressure oil into the clamping cylinder is stopped, and when the bypass 16 is opened to supply pressure oil to the booster ram 18, the clamping ram 17 is moved upward together with the clamping plate 22 by the pressure oil fed under pressure into the clamping ram. At the same time, the piston rod 21 is also forced upward through the clamping plate 22, and therefore, pressure oil within the clamping cylinder is pumped up into the charge cylinder 15 via the bypass 16. Therefore, pressure oil in the upper chamber comprises no resistance so that the clamping ram 17 is moved upward at a high speed.

When the piston 25 of the base-plate vertically moving cylinder 24 is extended in synchronism with the upward movement of the clamping ram 17, the base plate 2 is moved upward together with the transfer plate 3 having the preform 46 held by the hold mold 6, and the injection core 13 is removed during such upward movement.

The difference in level of the injection mold 36 and the blow mold 37 can be adjusted by vertically changing the position of the blow mold 37.

In molding of a short preform 46, a moving stroke of the clamping ram 17 is restricted, and therefore, the injection core 23 is mounted by applying a block 50 having a predetermined thickness to compensate for the stroke to the clamping plate 22.

This invention has a configuration as mentioned above, and even in the case where the base plate is moved upward together with the transfer plate, mold opening can be done at a high speed. Moreover, since the injection device may be al-

ways placed in nozzle touch with the injection mold, there is a feature that the molding cycle time is materially shortened.

Claims

1. A rotary injection orientation blow molding machine comprising;
 - a machine bed (1),
 - a seat plate (4) mounted on the machine bed (1),
 - a horizontal base plate (2) vertically movably supported above said machine bed (1),
 - tie bars (5) standing upright on said seat plate (4), said base plate (2) having portions of a peripheral edge thereof which are slidably inserted by said tie bars (5), said base plate (2) having an underside portion spaced above said machine bed (1) and an upperside portion,
 - a transfer plate (3) rotatably mounted on said underside portion of said base plate (2), said transfer plate (3) having a lower surface and having hold molds (6) at three locations of said lower surface thereof,
 - a drive device (7) located in a central portion of said upperside portion of said base plate (2) to intermittently rotate said transfer plate (3) by a predetermined angle to bring each said hold mold (6) to one of said three location of said transfer plate (3),
 - a vertical clamping device (9) and an injection mold (26) with a stop position of said hold molds (6) serving as an injection molding portion; a blow mold (37) and orientation blow molding device (10) with a stop position of said hold molds (6) serving as an orientation blow molding portion; a releasing device (11) with a stop position of said hold molds (6) serving as a releasing portion; said injection molding portion, orientation blow molding portion and releasing portion being respectively provided at predetermined locations above said machine bed (1),
 - a frame (13) for connecting upper ends of said tie bars (5) with each other, and
 - a plurality of cylinders (24) for vertically moving said base plate (2) up and down, said cylinders (24) being provided between said seat plate (4) and the peripheral edge of the base plate (2), wherein said clamping device (9) comprises
 - a clamping cylinder (14) including an upper and lower chamber wherein the inner diameter of said upper chamber is larger than the inner diameter of said lower chamber and both said chambers are communicated by a bypass (16) provided with a closing valve,



a fixed plate (12) having said clamping cylinder (14) acting downwardly said fixed plate (12) being integrally molded to said frame (13) and said clamping cylinder (14), said fixed plate (12) being secured to said tie bars (5) on both sides of said injection molding portion,

a cylindrical clamping ram (17) extended through a central portion of said clamping cylinder (14), said cylindrical clamping ram (17) comprising a piston (19) having an outer diameter matched to the diameter of said lower chamber and further comprising a booster ram (18) inserted therein,

at least one parallel charge cylinder (15) being arranged on the side of said clamping cylinder (14), said parallel charge cylinder (15) being communicated with said lower chamber of said clamping cylinder (14), said parallel charge cylinder (15) comprising a piston rod (21), and

a clamping plate (22) to which said piston rod (21) of said charge cylinder (15) is connected together with said clamping ram (17).

2. A rotary injection orientation blow molding machine comprising;

a machine bed (1),

a seat plate (4) mounted on the machine bed (1),

a horizontal base plate (2) vertically movably supported above said machine bed (1),

tie bars (5) standing upright on said seat plate (4), said base plate (2) having portions of a peripheral edge thereof which are slidably inserted by said tie bars (5), said base plate (2) having an underside portion spaced above said machine bed (1) and an upperside portion,

a transfer plate (3) rotatably mounted on said underside portion of said base plate (2), said transfer plate (3) having a lower surface and having hold molds (6) at three locations of said lower surface thereof,

a drive device (7) located in a central portion of said upperside portion of said base plate (2) to intermittently rotate said transfer plate (3) by a predetermined angle to bring each said hold mold (6) to one of said three location of said transfer plate (3),

a vertical clamping device (9) and an injection mold (26) with a stop position of said hold molds (6) serving as an injection molding portion; a blow mold (37) and orientation blow molding device (10) with a stop position of said hold molds (6) serving as an orientation blow molding portion; a releasing device (11) with a stop position of said hold molds (6) serving as

a releasing portion; said injection molding portion, orientation blow molding portion and releasing portion being respectively provided at predetermined locations above said machine bed (1),

a frame (13) for connecting upper ends of said tie bars (5) with each other, and

at least one cylinder (24) for vertically moving said base plate (2) up and down, said cylinder (24) being provided over a beam member (48) and said drive device side in the central portion of said base plate (2), said beam member (48) being integrally mounted over said frame (13) and a fixed plate (12) of said clamping device (9),

wherein said clamping device (9) comprises

a clamping cylinder (14) including an upper and lower chamber wherein the inner diameter of said upper chamber is larger than the inner diameter of said lower chamber and both said chambers are communicated by a bypass (16) provided with a closing valve,

the fixed plate (12) having said clamping cylinder (14) acting downwardly, said fixed plate (12) being integrally molded to said frame (13) and said clamping cylinder (14), said fixed plate (12) being secured to said tie bars (5) on both sides of said injection molding portion,

a cylindrical clamping ram (17) extended through a central portion of said clamping cylinder (14), said cylindrical clamping ram (17) comprising a piston (19) having an outer diameter matched to the diameter of said lower chamber and further comprising a booster ram (18) inserted therein,

at least one parallel charge cylinder (15) being arranged on the side of said clamping cylinder (14), said parallel charge cylinder (15) being communicated with said lower chamber of said clamping cylinder (14), said parallel charge cylinder (15) comprising a piston rod (21), and

a clamping plate (22) to which said piston rod (21) of said charge cylinder (15) is connected together with said clamping ram (17).

Patentansprüche

1. Umlaufende Spritzgieß- und Streckblasmaschine mit:

einem Maschinenbett (1),

einer auf dem Maschinenbett (1) montierten Auflageplatte (4),

einer oberhalb des Maschinenbetts (1) vertikalbewegbar gelagerten, horizontalen Grundplatte (2),

auf der Auflageplatte (4) aufrechtstehenden



Zugankern (5), wobei die Grundplatte (2) Umfangsrandteile besitzt, die von den Zugankern (5) gleitend durchsetzt sind, und die oberhalb des Maschinenbetts (1) im Abstand von ihm angeordneten Grundplatte (2) eine im Abstand oberhalb des Maschinenbetts (1) angeordnete Unterseite und eine Oberseite besitzt,

einer auf der Unterseite der Grundplatte (2) drehbar gelagerten Übergabepatte (3), die eine Unterseite und an drei Stellen ihrer Unterseite Halteformen (6) besitzt,

einer in einem mittleren Bereich der Oberseite der Grundplatte (2) angeordneten Antriebseinrichtung (7) zum intermittierenden Drehen der Übergabepatte (3) jeweils um einen vorherbestimmten Winkel derart, daß jede der Halteformen (6) an eine der drei Stellen der Übergabepatte (3) bewegt wird,

einer vertikal bewegbaren Schließeinrichtung (9) und einer Spritzgußform (26), wobei die Halteformen (6) in je einer Stillstandsstellung als Spritzgießteil, als Blasform (37) und als Streckblaseinrichtung (10) dienen und die Halteformen (6) in einer Stillstandsstellung als Streckblaseinrichtung dienen, ferner mit einer Entformeinrichtung (11), wobei die Halteformen (6) in einer Stillstandsstellung einen Teil der Entformeinrichtung bilden, der Spritzgießteil, der Streckblastteil und der Entformteil an je einer vorherbestimmten Stelle oberhalb des Maschinenbetts (1) angeordnet sind,

einem die oberen Enden der Zuganker (5) miteinander verbindenden Rahmen (13) und

einer Mehrzahl von Zylindern (24), die zum Vertikalaufwärts- und -abwärtsbewegen der Grundplatte (2) dienen und zwischen der Auflagerplatte (4) und dem Umfangsrand der Grundplatte (2) vorgesehen sind, wobei die Schließeinrichtung (9)

einen Schließzylinder (14) aufweist, der eine obere und eine untere Kammer enthält, wobei der Innendurchmesser der oberen Kammer größer ist als der Innendurchmesser der unteren Kammer und die beiden Kammern miteinander durch eine Umgehungsleitung (16) in Verbindung stehen, die mit einem Absperrventil versehen ist,

ferner eine mit dem abwärtswirkenden Schließzylinder (14) versehene, ortsfeste Platte (12), die mit dem Rahmen (13) und dem Schließzylinder (14) einstückig ist auf beiden Seiten des Spritzgießteils an den Zugankern (5) befestigt ist,

einen einen zentralen Teil des Schließzylinders (14) durchsetzenden zylindrischen Schließstempel (17) der einen Kolben (19) besitzt, dessen Außendurchmesser dem Durchmesser der unteren Kammer angepaßt ist, wo-

bei der Schließstempel ferner einen darin eingesetzten Zusatzstempel (18) besitzt,

mindestens einen auf der Seite des Schließzylinders (14) angeordneten, parallelen Füllzylinder (15), der mit der unteren Kammer des Schließzylinders (14) in Strömungsverbindung steht und mit einer Kolbenstange (21) versehen ist, und

eine Schließplatte (22), mit der sowohl die Kolbenstange (21) des Füllzylinders (15) als auch der Schließstempel (17) verbunden ist.

2. Umlaufende Spritzgieß- und Streckblasmaschine mit:

einem Maschinenbett (1),

einer auf dem Maschinenbett (1) montierten Auflagerplatte (4),

einer oberhalb des Maschinenbetts (1) vertikalbewegbar gelagerten, horizontalen Grundplatte (2),

auf der Auflagerplatte (4) aufrechtstehenden Zugankern (5), wobei die Grundplatte (2) Umfangsrandteile besitzt, die von den Zugankern (5) gleitend durchsetzt sind, und die oberhalb des Maschinenbetts (1) im Abstand von ihm angeordneten Grundplatte (2) eine im Abstand oberhalb des Maschinenbetts (1) angeordnete Unterseite und eine Oberseite besitzt,

einer auf der Unterseite der Grundplatte (2) drehbar gelagerten Übergabepatte (3), die eine Unterseite und an drei Stellen ihrer Unterseite Halteformen (6) besitzt,

einer in einem mittleren Bereich der Oberseite der Grundplatte (2) angeordneten Antriebseinrichtung (7) zum intermittierenden Drehen der Übergabepatte (3) jeweils um einen vorherbestimmten Winkel derart, daß jede der Halteformen (6) an eine der drei Stellen der Übergabepatte (3) bewegt wird,

einer vertikal bewegbaren Schließeinrichtung (9) und einer Spritzgußform (26), wobei die Halteformen (6) in je einer Stillstandsstellung als Spritzgießteil, als Blasform (37) und als Streckblaseinrichtung (10) dienen und die Halteformen (6) in einer Stillstandsstellung als Streckblaseinrichtung dienen, ferner mit einer Entformeinrichtung (11), wobei die Halteformen (6) in einer Stillstandsstellung einen Teil der Entformeinrichtung bilden, der Spritzgießteil, der Streckblastteil und der Entformteil an je einer vorherbestimmten Stelle oberhalb des Maschinenbetts (1) angeordnet sind,

einem die oberen Enden der Zuganker (5) miteinander verbindenden Rahmen (13) und

mindestens einem Zylinder (24), der zum Vertikalaufwärts- und -abwärtsbewegen der Grundplatte (2) dient und über einem Träger (48) und der Antriebseinrichtung im mittleren



Teil der Grundplatte (2) vorgesehen ist, wobei der Träger (48) mit dem Rahmen (13) und einer ortsfesten Platte (12) der Schließeinrichtung (9) einstückig und über ihnen angeordnet ist,

wobei die Schließeinrichtung (9)

einen Schließzylinder (14) aufweist, der eine obere und eine untere Kammer enthält, wobei der Innendurchmesser der oberen Kammer größer ist als der Innendurchmesser der unteren Kammer und die beiden Kammern miteinander durch eine Umgehungsleitung (16) in Verbindung stehen, die mit einem Absperrventil versehen ist,

ferner eine mit dem abwärtswirkenden Schließzylinder (14) versehene, ortsfeste Platte (12), die mit dem Rahmen (13) und dem Schließzylinder (14) einstückig ist auf beiden Seiten des Spritzgießteils an den Zugankern (5) befestigt ist,

einen einen zentralen Teil der Schließzylinders (14) durchsetzenden zylindrischen Schließstempel (17) der einen Kolben (19) besitzt, dessen Außendurchmesser dem Durchmesser der unteren Kammer angepaßt ist, wobei der Schließstempel ferner einen darin eingesetzten Zusatzstempel (18) besitzt,

mindestens einen auf der Seite des Schließzylinders (14) angeordneten, parallelen Füllzylinder (15), der mit der unteren Kammer des Schließzylinders (14) in Strömungsverbindung steht und mit einer Kolbenstange (21) versehen ist, und

eine Schließplatte (22), mit der sowohl die Kolbenstange (21) des Füllzylinders (15) als auch der Schließstempel (17) verbunden ist.

Revendications

1. Une presse d'injection et de soufflage directionnel à carrousel comprenant

- un banc (1),
- une plaque d'assise (4) montée sur le banc (1),
- une plaque d'appui (2) horizontale, mobile verticalement au-dessus dudit banc (1),
- des traverses (5) s'élevant à la verticale de ladite plaque d'assise (4) et coulissant à travers le bord constituant la périphérie de ladite plaque d'assise (4), ladite plaque d'appui (2) comportant une partie inférieure disposée au-dessus dudit banc (1) et une partie supérieure,
- une plaque de transfert (3) montée à rotation sur ladite partie inférieure de ladite plaque d'appui (2), ladite plaque de transfert (3) comportant, sur sa face inférieure,

rieure, des éléments de moule (6) en trois positions,

- un dispositif d'entraînement (7) situé en position centrale sur ladite partie supérieure de ladite plaque d'appui (2) entraînant en rotation, de façon intermittente, ladite plaque de transfert (3) d'un angle pré-déterminé pour amener chacun desdits éléments de moule (6) à une desdites trois positions sur ladite plaque de transfert (3),
- un dispositif de serrage vertical (9) et un moule d'injection (26) à une position d'arrêt desdits éléments de moule (6) tenant lieu de site de moulage par injection ; un moule de soufflage (37) et un dispositif de moulage par soufflage directionnel (10) à une position d'arrêt desdits éléments de moule (6) tenant lieu de site de moulage par soufflage directionnel, un dispositif de dégagement (11) à une position d'arrêt desdits éléments de moule (6) tenant lieu de site de dégagement ; lesdits sites de moulage par injection, de moulage par soufflage directionnel et de dégagement étant respectivement prévus à des positions déterminées au-dessus dudit banc (1),
- un châssis (13) reliant les extrémités supérieures desdites traverses (5) entre elles et,
- une pluralité de vérins (24) pour le déplacement vertical de ladite plaque d'appui (2) vers le haut et vers le bas, lesdits vérins (24) étant prévus entre ladite plaque d'assise (4) et le bord constituant la périphérie de la plaque d'appui (2), caractérisée en ce que ledit dispositif de serrage (9) comprend :
- un vérin (14) de serrage comportant une chambre supérieure et une chambre inférieure, le diamètre intérieur de ladite chambre supérieure étant supérieur au diamètre intérieur de ladite chambre inférieure et les deux chambres communiquant l'une avec l'autre par l'intermédiaire d'une dérivation (16) munie d'une vanne de fermeture,
- une plaque fixe (12) portant ledit vérin de serrage (14) se déployant vers le bas, ladite plaque fixe (12) étant moulée en une pièce avec ledit châssis (13) et ledit vérin de serrage (14), ladite plaque fixe (12) étant fixée aux traverses (5) sur les deux côtés dudit site de moulage par injection,
- un organe de serrage (17) cylindrique s'étendant à travers la partie centrale du-



- dit vérin de serrage (14), ledit organe de serrage (17) comprenant un piston (19) dont le diamètre extérieur correspond au diamètre de ladite chambre inférieure et comportant également un organe de relevage (18) inséré dans ledit vérin de serrage (14),
- au moins un vérin (15) de charge disposé parallèlement et sur le côté du vérin de serrage (14), ledit vérin de charge (15) communiquant avec ladite chambre inférieure dudit vérin de serrage (14), ledit vérin de charge (15) comprenant une tige de piston (21) et,
 - une plaque de serrage (22) à laquelle sont reliées ladite tige de piston (21) dudit cylindre de charge (15) et ledit organe de serrage (17).
2. Une presse d'injection et de soufflage directionnel à carrousel comprenant :
- un banc (1),
 - une plaque d'assise (4) montée sur le banc (1),
 - une plaque d'appui (2) horizontale mobile verticalement au-dessus dudit banc (1),
 - des traverses (5) s'élevant à la verticale de ladite plaque d'assise (4) et coulissant à travers le bord constituant la périphérie de ladite plaque d'assise (4), ladite plaque d'appui (2) comportant une partie inférieure disposée au-dessus dudit banc (1) et une partie supérieure,
 - une plaque de transfert (3) montée à rotation sur ladite partie inférieure de ladite plaque d'appui (2), ladite plaque de transfert (3) comportant, sur sa face inférieure, des éléments de moule (6) en trois positions,
 - un dispositif d'entraînement (7) disposé en position centrale sur ladite partie supérieure de ladite plaque d'appui (2) entraînant en rotation, de façon intermittente, ladite plaque de transfert (3) d'un angle pré-déterminé pour amener chacun desdits éléments de moule (6) à une desdites trois positions de ladite plaque de transfert (3),
 - un dispositif de serrage vertical (9) et un moule d'injection (26) à une position d'arrêt desdits éléments de moule (6) tenant lieu de site de moulage par injection ; un moule de soufflage (37) et un dispositif de moulage par soufflage directionnel (10) à une position d'arrêt desdits éléments de moule (6) tenant lieu de site de moulage par soufflage directionnel ; un dispositif de dégagement (11) à une

position d'arrêt desdits éléments de moule (6) tenant lieu de site de dégagement ; lesdits sites de moulage par injection, de moulage par soufflage directionnel et de dégagement étant respectivement prévus en des positions déterminées au-dessus dudit banc (1),

- un châssis (13) reliant les extrémités supérieures desdites traverses (5) entre elles et,
- au moins un vérin (24) pour le déplacement vertical de ladite plaque d'appui (2) vers le haut et vers le bas, ledit vérin (24) étant prévu au-dessus d'une poutre (48) et dudit dispositif d'entraînement (7), en position centrale sur la plaque d'appui (2), ladite poutre (48) étant monté sur ledit châssis (13) et sur une plaque fixe (12) dudit dispositif de serrage (9),

caractérisée en ce que le dispositif de serrage (9) comprend :

- un vérin de serrage (14) comprenant une chambre supérieure et une chambre inférieure, le diamètre intérieur de ladite chambre supérieure étant supérieur au diamètre intérieur de ladite chambre inférieure et les deux chambres communiquant par une dérivation (16) munie d'une vanne de fermeture,
- la plaque fixe (12) portant ledit vérin de serrage (14) se déployant vers le bas, ladite plaque fixe (12) formant une seule pièce avec ledit châssis (13) et ledit vérin de serrage (14), ladite plaque fixe (12) étant fixée auxdites traverses (5) sur les deux côtés dudit site de moulage par injection,
- un organe de serrage (17) cylindrique s'étendant à travers une partie centrale dudit vérin de serrage (14), ledit organe de serrage (17) cylindrique comprenant un piston (19) dont le diamètre extérieur correspond au diamètre de ladite chambre inférieure et comportant également un organe de relevage (18) inséré dans ledit vérin de serrage (14),
- au moins un vérin de charge (15) disposé parallèlement et sur le côté du vérin de serrage (14), ledit vérin de charge (15) communiquant avec ladite chambre inférieure dudit vérin de serrage (14), ledit vérin de charge (15) comprenant une tige de piston (21), et,
- une plaque de serrage (22) à laquelle sont reliées ladite tige de piston (21) dudit vérin de charge (15) et ledit organe de serrage (17).