



17 FEB 2006

Improved Hand-held Laser Device

TECHNICAL FIELD

5 This invention relates generally to devices that employ lasers. More particularly, this invention relates to an improved hand-held laser light generator device.

BACKGROUND ART

10 Low energy laser therapy (LLLT) is used in the treatment of a broad range of conditions. LLLT improves wound healing, reduces edema, and relieves pain of various etiologies, including successful application post-operatively to liposuction to reduce inflammation and pain. LLLT is also used during liposuction procedures to facilitate removal of fat by causing intracellular fat to be released into the interstice. It is also used in the treatment and repair of injured muscles and tendons.

15 LLLT utilizes low level laser energy, that is, the treatment has a dose rate that causes no immediate detectable temperature rise of the treated tissue and no macroscopically visible changes in tissue structure. Consequently, the treated and surrounding tissue is not heated and is not damaged. There are a number of variables in laser therapy including the wavelength of the laser beam, the area impinged by the laser beam, laser energy, pulse width, treatment duration and tissue characteristics.
20 The success of each therapy depends on the relationship and combination of these variables. For example, liposuction may be facilitated with one regimen utilizing a given wavelength and treatment duration, whereas pain may be treated with a regimen utilizing a different wavelength and treatment duration, and inflammation a third
25 regimen. Specific devices are known in the art for each type of therapy.

Often it is desirable to treat a patient for multiple types of problems during a single treatment. Because specific therapies require different regimens, treating multiple problems currently requires multiple laser devices. It is desirable to provide a device that enables multiple types of treatments with a single device. It is also desirable
30 to be able to provide multiple treatments simultaneously with a single device.

Therefore, an object of this invention is to provide a laser device that enables multiple types of treatments. It is another object to provide a single device that provides these treatments simultaneously. It is another object of this invention to provide an apparatus that can simultaneously emit multiple beams of laser light. It is another



object of this invention to provide an apparatus that can simultaneously emit laser light in multiple different pulse widths. It is a further object of this invention to provide an apparatus that can simultaneously emit laser light in multiple beam shapes and spot sizes. It is a particular object of this invention to provide a hand-held laser device to
5 provide low level laser treatments which can be used to simultaneously facilitate liposuction, treat post-operative inflammation, and post-operative pain.

DISCLOSURE OF THE INVENTION

This invention is an improved hand-held laser device that can simultaneously
10 provide multiple types of low level laser treatments. The device enables laser light of different pulse widths, different beam shapes and spot sizes to be applied externally to a patient's body. The device includes multiple laser sources. In the preferred embodiment, two semiconductor diode laser sources simultaneously provide two separate laser beams, one laser beam producing a line of continuous red laser light
15 and the other producing a spot of pulsed laser light.

In one embodiment, the improved laser device comprises a wand from which the laser beams emit. The wand is capable of being retained in a hand of a user and freely moved relative to the surface of the skin of a patient. The improvement of the laser device is characterized by a plurality of laser energy sources for generating a plurality
20 of laser beams wherein the plurality of laser energy sources are housed in the wand. The laser device is also characterized by an optical arrangement attached to the wand for receiving the laser beams and for transforming each of the laser beams into a desired spot shape.

In another embodiment, the improved laser device comprises a wand from which
25 the laser beams emit. The wand comprises an interior cavity and is capable of being retained in a hand of a user and freely moved relative to the surface of the skin of a patient. The improvement of the laser device is characterized by a first semiconductor diode laser energy source for generating a first laser beam and a second semiconductor diode laser energy source for generating a second laser beam. The first
30 and second laser energy sources are housed in the wand and at least one of the laser beams has a wavelength in the red range of the visible spectrum. The laser device is further characterized by an optical arrangement mounted in the interior cavity of the wand that receives the laser beams and transforms each of the laser beams into a desired spot shape. The first laser beam's spot shape is substantially linear and the

second laser beam's spot shape is substantially circular. Finally, the laser device is characterized by a control circuit that controls the pulse width of each laser beam wherein the first laser beam is a continuous emission and the second laser beam has a second pulse width that is greater than zero.

5 In yet another embodiment, the improved laser device comprises a wand from which the laser beams emit. The wand is capable of being retained in a hand of a user and freely moved relative to the surface of the skin of a patient. The improvement of the laser device is characterized by a plurality of laser energy sources for generating a plurality of laser beams. At least two of the laser beams have the same color and the
10 plurality of laser energy sources are housed in the wand. The laser device is also characterized by an optical arrangement attached to the wand that receives the laser beams and transforms each of the laser beams into a desired spot shape.

In another embodiment of the present invention, the improved laser device comprises wand from which the laser beams emit. The wand is capable of being
15 retained in a hand of a user and freely moved relative to the surface of the skin of a patient. The improvement of the laser device is characterized by a plurality of laser energy sources for generating a plurality of laser beams wherein the plurality of laser energy sources are housed in the wand. The improvement is also characterized by an optical arrangement attached to the wand that receives the laser beams and transforms
20 each of the laser beams into a desired spot shape. Additionally, the laser device is characterized by a control circuit that independently controls the parameters of laser energy generated from each laser energy source.

In still yet another embodiment of the present invention, an improved laser device comprises a wand from which the laser beams emit. The wand is capable of
25 being retained in a hand of a user and freely moved relative to the surface of the skin of a patient. The improvement of the laser device is characterized by a plurality of laser energy sources for generating a plurality of laser beams, wherein the plurality of laser energy sources are housed in the wand. The laser device is also characterized by an optical arrangement attached to the wand that receives the laser beams and transforms
30 each of the laser beams into a desired spot shape, wherein at least two of the spot shapes are different from each other.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is an electrical schematic illustration of a preferred embodiment of the present invention.

FIG. 2 is a schematic view of the optical arrangement of the linear spot shape of the preferred embodiment.

FIG. 3 is a schematic view of the optical arrangement of the circular spot shape of the preferred embodiment.

FIG. 4 is a schematic illustration of application of low-level laser radiation to a human using the preferred embodiment of the present invention.

BEST MODE FOR CARRYING OUT THE INVENTION

Referring to the drawings, there is illustrated a hand-held laser device designated generally as 10. The device includes a plurality of laser energy sources, a power source, an optical arrangement, a wand, and a control circuit.

Fig. 1 shows the preferred embodiment in which a first laser energy source 11 and a second energy source 12 are connected to a power source 13. The power source preferably provides direct current, such as that provided by a battery, but may instead provide alternating current such as that provided by conventional building current that is

then converted to direct current. Separate control means 15, 16 are connected to the laser energy sources 11, 12 respectively and act as on/off switches to control the period of time the laser light is generated. These laser energy sources can be energized independently or simultaneously which, throughout this specification, refers to acts
5 occurring at generally at the same time.

Laser energy sources are known in the art for use in low-level laser therapy. They include Helium-Neon lasers having a 632 nm wavelength and semiconductor diode lasers with a broad range of wavelengths between 600-800 nm. The laser energy sources in the preferred embodiment are two semiconductor laser diodes that produce
10 light in the red range of the visible spectrum, having a wavelength of about 635 nm. Other suitable wavelengths are used for other particular applications. While many LLLT regimen include visible laser light, it is advantageous to utilize at least one laser beam in the visible/UV energy spectrum so that the operator can see the laser light as it impinges the patient's body and the area treated can be easily defined. Solid state and
15 tunable semiconductor laser diodes may also be employed to achieve the desired wavelength.

Different therapy regimens require diodes of different wattages. The preferred laser diodes use less than one watt of power each to simultaneously facilitate liposuction, treat post-operative inflammation, and post-operative pain. Diodes of
20 various other wattages may also be employed to achieve the desired laser energy for the given regimen. Further, patients may be human or other animal, and different therapy regimens are utilized depending on the species of patient.

Control means 21, 22 are connected to the laser energy sources 11, 12, respectively, to form a control circuit that controls the duration of each pulse of laser
25 light emitted, referred to herein as the pulse width. When there are no pulses, a continuous beam of laser light is generated. Pulse widths from 0 to 100,000 Hz may be employed to achieve the desired effect on the patient's tissue. The goal for LLLT regimen is to deliver laser energy to the target tissue utilizing a pulse width short enough to sufficiently energize the targeted tissue and avoid thermal damage to
30 adjacent tissue.

Each laser beam 41, 42 exits the laser and is shone through optical arrangements 31, 32, respectively, that produce beam spots 51, 52 respectively of certain shapes. The beam spot is the cross-sectional shape and size of the emitted beam as it exits the optical arrangement. For example, a laser beam of circular cross-

section creates a circular beam spot as the laser light impinges the patient's skin. If the laser light emitted is in the visible range, a circular spot can be seen on the patient's skin. In the preferred embodiment, the first laser beam is passed through an optical arrangement that generates a beam of substantially linear cross-section, resulting in a
5 line of laser light seen on the patient's skin. The second laser passes through an optical arrangement that generates a beam of circular cross-section, resulting in a circular spot shape as seen on the patient's skin.

As shown in Fig. 2 the first optical arrangement 31 of the preferred device includes a collimating lens 34 and a line generating prism 36. The collimating lens 34
10 and the line generating prism 36 are disposed in serial relation to the laser energy source 11. The collimating lens 34 and the line generating prism 36 receive and transform the generated beam of laser light into the line of laser light L. As an alternative, a suitable electrical or mechanical arrangement could be substituted for the optical arrangement 31.

As shown in Fig. 3 the second optical arrangement 32 of the preferred device includes a collimating lens 34. As with the first optical arrangement, the collimating lens 34
15 is disposed in serial relation to the laser energy source 12. The collimating lens 34 receives and transforms the generated beam of laser light into a circular beam spot of laser light C. As an alternative, a suitable electrical or mechanical arrangement could
20 be substituted for the optical arrangement 32 to achieve a desired spot shape.

The device may utilize as many lasers and optical arrangements as necessary to obtain the desired emissions and spot shapes. For example, the device may employ two laser diodes each with a collimating lens, such that two substantially circular spot shapes are achieved. Or, for example, the device may employ two laser diodes each
25 with an optical arrangement such that two substantially linear spot shapes are achieved. Or, in another example, more than two lasers may be used and optical arrangements aligned such that two or more of the laser beams have substantially similar spot shapes and are co-incident where they impinge the patient's skin.

In order to direct the laser light to the desired area on a patient, the laser light is
30 emitted from a lightweight, hand-held pointer referred to herein as a wand 61. See Fig. 4. The wand 61 is preferably an elongated hollow tube defining an interior cavity which is shaped to be easily retained in a user's hand. In the preferred embodiment the laser energy sources 11, 12 are mounted in the wand's interior cavity, although the laser energy sources could be remotely located and the laser light conducted by fiber optics

energy sources could be remotely located and the laser light conducted by fiber optics to the wand. The wand may take on any shape that enables the laser light to be directed as needed such as tubular, T-shaped, substantially spherical, or rectangular (like a television remote control device).

5 While there has been illustrated and described what is at present considered to be a preferred embodiment of the present invention, it will be understood by those skilled in the art that various changes and modifications may be made, and equivalents may be substituted for elements thereof without departing from the true scope of the invention. Therefore, it is intended that this invention not be limited to the particular
10 embodiment disclosed as the best mode contemplated for carrying out the invention, but that the invention will include all embodiments falling within the scope of the appended claims.

We claim:

1. An improved laser device comprising a wand from which the laser beams emit, the wand being capable of being retained in a hand of a user and freely moved relative to the surface of the skin of a patient, the improvement characterized by:
 - 5 a) a plurality of laser energy sources for generating a plurality of laser beams, the plurality of laser energy sources housed in the wand; and
 - b) an optical arrangement attached to the wand for receiving the laser beams and for transforming each of the laser beams into a desired spot shape.
- 10 2. A device according to claim 1 wherein at least two of the laser beams are emitted simultaneously.
3. A device according to claim 1 further characterized by a controller for independently controlling the generation of laser energy by each of the plurality of laser energy sources.
- 15 4. A device according to claim 1 wherein each of the laser energy sources is less than one watt.
5. A device according to claim 1 wherein at least one of the laser energy sources is a semiconductor diode.
6. A device according to claim 5 wherein the laser energy source generates a laser beam having a wavelength in the visible range.
- 20 7. A device according to claim 1 wherein at least one of the spot shapes is substantially linear.
8. A device according to claim 1 further characterized by a first laser beam having a first spot shape and a second laser beam having a second spot shape wherein the first spot shape is substantially linear and the second spot shape is circular.
- 25 9. A device according to claim 1 further characterized by a control circuit for controlling the pulse width of each laser beam.
10. A device according to claim 9 wherein the pulse width of at least one of the laser beams is such that the laser light emitted is substantially continuous.
- 30 11. A device according to claim 9 further characterized by a first laser beam having a first pulse width and a second laser beam having a second pulse width wherein the first pulse width is such that the laser light emitted is substantially continuous and the second pulse width is not zero.

12. A device according to claim 11 wherein the pulse width of the second pulse width is less than 100,000 Hz.
13. An improved laser device comprising a wand from which the laser beams emit, the wand having an interior cavity and being capable of being retained in a hand of a user and freely moved relative to the surface of the skin of a patient, the improvement characterized by:
 - a) a first semiconductor diode laser energy source generating a first laser beam and a second semiconductor diode laser energy source generating a second laser beam, the first and second laser energy sources housed in the wand, wherein at least one of the laser beams has a wavelength in the red range of the visible spectrum;
 - b) an optical arrangement mounted in the interior cavity of the wand for receiving the laser beams and for transforming each of the laser beams into a desired spot shape wherein the first laser beam's spot shape is substantially linear and the second laser beam's spot shape is substantially circular;
 - c) a control circuit for controlling the pulse width of each laser beam wherein the first laser beam is a continuous emission and the second laser beam has a second pulse width that is greater than zero.
14. An improved laser device comprising a wand from which the laser beams emit, the wand being capable of being retained in a hand of a user and freely moved relative to the surface of the skin of a patient, the improvement characterized by:
 - a) a plurality of laser energy sources for generating a plurality of laser beams, wherein at least two of the laser beams have the same colour, the plurality of laser energy sources housed in the wand; and
 - b) an optical arrangement attached to the wand for receiving the laser beams and for transforming each of the laser beams into a desired spot shape.
15. A device according to claim 14 wherein at least two of the laser beams have the same wavelength.
16. An improved laser device comprising a wand from which the laser beams emit, the wand being capable of being retained in a hand of a user and freely moved relative to the surface of the skin of a patient, the improvement characterized by:

- a) a plurality of laser energy sources for generating a plurality of laser beams, the plurality of laser energy sources housed in the wand;
 - b) an optical arrangement attached to the wand for receiving the laser beams and for transforming each of the laser beams into a desired spot shape;
 - c) a control circuit for independently controlling the parameters of laser energy generated from each laser energy source.
17. An improved laser device comprising a wand from which the laser beams emit, the wand being capable of being retained in a hand of a user and freely moved relative to the surface of the skin of a patient, the improvement characterized by:
- a) a plurality of laser energy sources for generating a plurality of laser beams, the plurality of laser energy sources housed in the wand; and
 - b) an optical arrangement attached to the wand for receiving the laser beams and for transforming each of the laser beams into a desired spot shape, wherein at least two of the spot shapes are different from each other.