

## ELECTROMAGNETIC SHUTTER FOR IMAGING SENSORS

## FIELD OF THE INVENTION

- 5 [0001] The present invention relates to imaging. More particularly it relates to an electromagnetic shutter for imaging sensors.

## BACKGROUND OF THE INVENTION

- 10 [0002] In optical systems, and in particular in imaging systems, such as thermal cameras, it is needed to provide a shutter that can be placed in front of the imaging sensor and block its view when desired. In an Infra-Red (IR) camera a shutter is provided for occasional calibration of the imaging sensor, or for preventing undesired irradiation from reaching the imaging sensor.
- 15 [0003] Calibration is necessary in thermal sensors in order to ensure accurate measurements and to obtain correct images. Calibration is especially important in IR cameras, which have a thermal sensor that is not cooled to supercool temperatures.
- [0004] Every once in a while a uniform surface of a black body is placed in front of the sensor and the sensor matrix is calibrated to measure a surface of uniform temperature.
- 20 [0005] There are known IR cameras, which include such an optical shutter. Typically the shutter comprises a black painted plate, which is displaced between two positions in front of the sensor – a blocking position in front of the sensor view and a retracted position, where the shutter is removed from the sensor's field of view.
- [0006] A known shutter mechanism includes a shutter plate turning about a motor axis
- 25 to and out of the blocking position. Another shutter mechanism includes a shutter plate coupled to a motor with linear transmission so as to facilitate linear motion of the shutter between the two positions.
- [0007] In some cases it is desired to have a shutter mechanism that is silent in order to prevent exposing the existence and location of the imaging system.

[0008] It is an object of the present invention to provide a shutter mechanism for imaging systems, which electromechanically activated.

[0009] Another object of the present invention is to provide a shutter mechanism for imaging systems, which is silent.

[0010] Yet another object of the present invention is to provide a shutter mechanism for imaging systems, which is reliable, holding the shutter plate in either of its positions firmly and stably.

[0011] Other advantages and objects of the present invention will become apparent after reading the present specification and reviewing the accompanying figures.

## SUMMARY OF THE INVENTION

[0012] One aspect of the present invention provides a shutter mechanism for an optical system, the shutter mechanism comprising: a linear track having a first end and a second end; a first magnetic assembly located adjacent the first end of the track and a second magnetic assembly located adjacent the second end of the track, the two magnetic assemblies arranged in opposite polarities; a shutter plate coupled to a coil mounted on and movable across the track, whereby when a direct electric current is passed through the coil in one direction the shutter is forced to move to the first end of the track, whereas when a direct electric current is passed through the coil in an opposite direction the shutter is forced to move to the second end of the track.

[0012a] An alternate aspect of the present provides a method for providing accurate and synchronized optical shutter the method comprising: providing a shutter mechanism for an optical system, the shutter mechanism comprising: a linear track having a first end and a second end; a first magnetic assembly located adjacent the first end of the track and a second magnetic assembly located adjacent the second end of the track, the two magnetic assemblies arranged in opposite polarities; a shutter plate coupled to a coil mounted on and movable across the track; passing a direct electric current through the coil in one direction thus forcing the shutter to move to the first end of the track; and passing a direct electric current through the coil in an opposite direction thus forcing the shutter to move to the second end of the track.

## BRIEF DESCRIPTION OF THE DRAWINGS

[0013] In order to better understand the present invention, and appreciate its practical applications, the following Figures are provided and referenced hereafter. It should be noted that the Figures are given as examples only and in no way limit the scope of the invention. Like components are denoted by like reference numerals.

[0014] Fig. 1 illustrates an electromagnetic shutter mechanism assembly for an optical system, in accordance with a preferred embodiment of the present invention.

[0015] Fig. 2 illustrates an exploded view of the electromagnetic shutter mechanism shown in Fig. 1.

[0016] Fig. 3 illustrates one layer of a multi-layer electromagnetic coil chip, suitable for incorporation in an electromagnetic shutter mechanism according to a preferred embodiment of the present invention.

[0017] Fig. 4 illustrates an IR camera with an electromagnetic shutter mechanism, in accordance with a preferred embodiment of the present invention.

5

#### DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

[0018] The present invention introduces a shutter mechanism that has a low profile (small dimensions), which is electromagnetically actuated, and is silent (or at least does not produces a noticeable noise when operated) and highly reliable. The shutter travels  
10 linearly along a straight track.

[0019] In principle a shutter mechanism according to the present invention comprises a shutter plate, which is coupled to an electromagnetic coil chip that can travel linearly between to positions across a confined track. On either ends of the track a magnet assembly is placed, in opposing magnetic polarities. When an electric (direct) current is  
15 passed through the coil the induced magnetic field of the coil aligns with one magnetic assembly and opposes the magnetic polarity of the other magnetic assembly, so that the chip is either attracted by one magnetic assembly and repelled by the other or repelled by the first magnetic assembly and attracted by the other, forcing the chip and hence forcing the shutter to move from one end of the track to the other in a predetermined  
20 manner, governed by the direction of the induced electromagnetic field of the coil, which is controlled.

[0020] Reference is made to Fig. 1, illustrating an electromagnetic shutter mechanism assembly, indicated by numeral 10, for an optical system, in accordance with a preferred embodiment of the present invention. The shutter mechanism assembly comprises a  
25 shutter 24, which is a plate whose color is black for absorbing light and acting as a black body. The shutter plate 24 is coupled to bar 25 (which may form an integral part, or assembled together), which can ride across rod 28 forming a track (a substantially parallel rod 28 is provided opposite this rod). The track is placed between two opposite cover plates 12 and is confined between two opposing end walls 18. A pair of opposite  
30 facing magnets is provided on either side of the track (shown are only the top magnets

of each pair, designated 20A and 20B, the opposing magnets 22A and 22B shown in Fig. 2), the two magnets of each pair aligned with respect to their magnetic polarity (both same direction), the magnet pairs arranged in opposing magnetic polarities. An electromagnetic coil (see also Fig. 3), formed on a chip 26 is provided, coupled to bar 25 of the shutter 24 (in the embodiment shown in this Figure the bar is provided with a groove into which the edge of chip 26 matchingly fits). Washer 30 is provided on either sides of each track rod 28, preferably made from an elastic material serving as a damper to absorb some of the kinetic energy of the shutter when it bumps into it, so as to reduce or totally eliminate impact noise. Alternatively (or in addition) an elastic bumper can be placed on either ends of the track attached internally on end walls 18. The washers also serve to distinctly mark the end of the track and their predetermined dimensions facilitate accurate positioning of the shutter on either end.

[0021] Extension of end wall 18 with bore 9 is provided for fastening the shutter mechanism assembly in a desired position by screws or pins.

[0022] Fig. 2 illustrates an exploded view of the electromagnetic shutter mechanism shown in Fig. 1. Cover plates 12 are provided with bores 17 through which pins (or screws) 13 are inserted passing into bores 15 of end walls 18, thus rigidly forming a housing for the track. Bar 25 is provided with bore 32 across into which rod 28 is inserted and on which bar 25 may ride, and the ends of each rod 28 are inserted in bores 31 of end walls 18. While bar 25 rides across one of the rods 28, chip 26, which is coupled to bar 25, sits and rides over both rods.

[0023] A ferroelectric element 40 is provided on chip 26, so that when the chip resides between either of the magnet pairs it is held firmly due to the magnetic forces, which act on the ferromagnetic element. This facilitates holding the shutter on either sides of the track firmly and stably, while maintaining the electromagnetic coil idle (no current is passed through the coil).

[0024] When current is passed through the coil it is repelled by one magnet assembly and repelled by the other, forcing the shutter to move to the one end of the track whereas when the current through the coil is reversed the shutter is forced to move to the opposite end of the track.

[0025] Fig. 3 illustrates one layer of a multi-layer electromagnetic coil chip 26, suitable for incorporation in an electromagnetic shutter mechanism according to a preferred embodiment of the present invention. A multi-layer coil is formed in order to gain a electromagnetic field that is sufficient to influence the chip to move across the track.

5 Each layer comprises a spiral conductive element 34 embedded in that layer and insulated from spiral conductive elements of adjacent layers. Contacts 27 and 29 facilitate inter-layer electrical connection between the spiral elements 34. Electrical wires 16 (see Fig. 1 and Fig. 2) are used to supply electrical current to the coil. In one alternative embodiment of a multi-layer electromagnetic coil chip, according to a  
10 preferred embodiment of the present invention, all of the coils (of all layers) are designed to induce an electromagnetic field in the same direction, and the shutter is driven from one end of the track to the opposite end by switching the electric polarity of the coil assembly. In an alternative embodiment some of a second coil assembly is provided on the chip, whose induced electric field is opposite to the first one, in which  
15 case in order to change the induced electromagnetic field of the chip the coil assemblies are operated alternately.

[0026] A proposed operation scheme comprises generating electric pulse of predetermined duration in a predetermined direction (by a controller 42, see Fig. 1) so as to force the shutter to move in a desired direction and move to a chosen end of the  
20 track, and then a substantially shorter pulse of reversed electrical polarity to induce counter forces and reduce the kinetic energy of the shutter and chip and cause an inhibited impact on the end wall 18, thus eliminating, or greatly reducing impact noises. Same sequence, but with reversed polarity is applied when it is desired to move the shutter to the other end of the track.

25 [0027] Fig. 4 illustrates an IR camera 60 with an electromagnetic shutter mechanism 10, in accordance with a preferred embodiment of the present invention. The shutter 24 is placed in front of the imaging sensor and in a first position covers the field of view of the sensor and in a second position is retracted so that it does not obstruct the field of view of the sensor. Magnet element 62 is optionally provided, aimed at cooperate with a  
30 hall-effect sensor, which is capable of identifying the presence of the magnetic element

in position, and if it moves (due to shakes or jolts) electric current is passed through the coil to force the shutter back in place.

[0028] The shutter mechanism of the present invention is made to maintain a low-profile and takes up very small space, relatively to other shutter assemblies. It is a very accurate and reliable mechanism.

[0029] It should be clear that the description of the embodiments and attached Figures set forth in this specification serves only for a better understanding of the invention, without limiting its scope.

[0030] It should also be clear that a person skilled in the art, after reading the present specification could make adjustments or amendments to the attached Figures and above described embodiments that would still be covered by the present invention.

## CLAIMS

1. A shutter mechanism for an optical system, the shutter mechanism comprising:  
a linear track having a first end and a second end;  
a first magnetic assembly located adjacent the first end of the track and a second  
5 magnetic assembly located adjacent the second end of the track, the two  
magnetic assemblies arranged in opposite polarities;  
a shutter plate coupled to a coil mounted on and movable across the track,  
whereby when a direct electric current is passed through the coil in one direction the  
shutter is forced to move to the first end of the track, whereas when a direct  
10 electric current is passed through the coil in an opposite direction the shutter is  
forced to move to the second end of the track.

2. The shutter mechanism as claimed in claim 1, wherein the shutter plate  
comprises a black-colored plate.

3. The shutter mechanism as claimed in claim 1, wherein the shutter plate is  
coupled to a bar, which is adapted to ride across a rod forming the track.

4. The shutter mechanism as claimed in claim 1, wherein the track is provided in a  
20 housing.

5. The shutter mechanism as claimed in claim 1, wherein the housing comprises  
two substantially opposite cover plates, the track confined by two substantially  
opposing end walls.

6. The shutter mechanism as claimed in claim 1, wherein the magnetic assemblies  
comprise, each, a pair of substantially opposite magnets whose magnetic polarity is  
aligned substantially in the same direction.

7. The shutter mechanism as claimed in claim 1, wherein the coil comprises a coil formed on a chip.

8. The shutter mechanism as claimed in claim 1, wherein a damper is provided on either sides of the track.

9. The shutter mechanism as claimed in claim 8, wherein the damper comprises a washer.

10. The shutter mechanism as claimed in claim 1, wherein a ferromagnetic element is coupled to the coil.

11. The shutter mechanism as claimed in claim 1, wherein the coil comprises a multi-layered coil.

12. The shutter mechanism as claimed in claim 11, wherein all coil layers are designed to induce an electromagnetic field in substantially same direction.

13. The shutter mechanism as claimed in claim 11, wherein the coil is provided with a first coil assembly and a second coil assembly, the electromagnetic field induced by the first coil assembly being substantially opposite to the electromagnetic field induced by the second coil assembly.

14. The shutter mechanism as claimed in claim 1, further provided with a controller for controlling timing, duration and direction of the electric current through the coil.

15. The shutter mechanism as claimed in claim 1, incorporated with and placed in front of an imaging sensor.

16. A method for providing accurate and synchronized optical shutter the method comprising:

providing a shutter mechanism for an optical system, the shutter mechanism comprising:

- 5 a linear track having a first end and a second end;
- a first magnetic assembly located adjacent the first end of the track and a second magnetic assembly located adjacent the second end of the track, the two magnetic assemblies arranged in opposite polarities;
- a shutter plate coupled to a coil mounted on and movable across the track;
- 10 passing a direct electric current through the coil in one direction thus forcing the shutter to move to the first end of the track; and
- passing a direct electric current through the coil in an opposite direction thus forcing the shutter to move to the second end of the track.

15 17. The method as claimed in claim 16, further comprising passing the electric current in the form of an electric pulse of predetermined duration in a predetermined direction.

18. The method as claimed in claim 17, wherein the electric current comprises a  
20 pulse of reversed electric polarity and shorter than earlier pulses.