

**Video Encoder, Video Decoder, Methods for Encoding and Decoding and Video  
Data Stream for realizing advanced Video Coding Concepts**

Description

5

The present invention relates to video encoding and video decoding and, in particular, to a video encoder, to a video decoder, to methods for encoding and decoding and to a video data stream for realizing advanced video coding concepts.

- 10 H.265/HEVC (HEVC = High Efficiency Video Coding) is a video codec which already provides tools for elevating or even enabling parallel processing at an encoder and/or at a decoder. For example, HEVC supports a sub-division of pictures into an array of tiles which are encoded independently from each other. Another concept supported by HEVC pertains to WPP, according to which CTU-rows or CTU-lines of the pictures may be processed in  
15 parallel from left to right, e.g. in stripes, provided that some minimum CTU offset is obeyed in the processing of consecutive CTU lines (CTU = coding tree unit). It would be favorable, however, to have a video codec at hand which supports parallel processing capabilities of video encoders and/or video decoders even more efficiently.

- 20 In the following, an introduction to VCL partitioning according to the state-of-the-art is described (VCL = video coding layer).

- Typically, in video coding, a coding process of picture samples requires smaller partitions, where samples are divided into some rectangular areas for joint processing such as  
25 prediction or transform coding. Therefore, a picture is partitioned into blocks of a particular size that is constant during encoding of the video sequence. In H.264/AVC standard fixed-size blocks of 16x16 samples, so called macroblocks, are used (AVC = Advanced Video Coding).

- 30 In the state-of-the-art HEVC standard (see [1]), there are Coded Tree Blocks (CTB) or Coding Tree Units (CTU) of a maximum size of 64 x 64 samples. In the further description of HEVC, for such a kind of blocks, the more common term CTU is used.

- CTUs are processed in raster scan order, starting with the top-left CTU, processing CTUs  
35 in the picture line-wise, down to the bottom-right CTU.

The coded CTU data is organized into a kind of container called slice. Originally, in former video coding standards, slice means a segment comprising one or more consecutive CTUs of a picture. Slices are employed for a segmentation of coded data. From another point of view, the complete picture can also be defined as one big segment and hence, historically, the term slice is still applied. Besides the coded picture samples, slices also comprise additional information related to the coding process of the slice itself which is placed into a so-called slice header.

According to the state-of-the-art, a VCL (video coding layer) also comprises techniques for fragmentation and spatial partitioning. Such partitioning may, e.g., be applied in video coding for various reasons, among which are processing load-balancing in parallelization, CTU size matching in network transmission, error-mitigation etc.

Other examples relate to RoI (RoI = Region of Interest) encodings, where there is for example a region in the middle of the picture that viewers can select e.g. with a zoom in operation (decoding only the RoI), or gradual decoder refresh (GDR) in which intra data (that is typically put into one frame of a video sequence) is temporally distributed over several successive frames, e.g. as a column of intra blocks that swipes over the picture plane and resets the temporal prediction chain locally in the same fashion as an intra picture does it for the whole picture plane. For the latter, two regions exist in each picture, one that is recently reset and one that is potentially affected by errors and error propagation.

Reference Picture Resampling (RPR) is a technique used in video coding to adapt the quality/rate of the video not only by using a coarser quantization parameter but by adapting the resolution of potentially each transmitted picture. Thus, references used for inter prediction might have a different size than the picture that is currently being predicted for encoding. Basically, RPR requires a resampling process in the prediction loop, e.g., upsampling and downsampling filters to be defined.

Depending on flavor, RPR can result in a change of coded picture size at any picture, or be limited to happen at only some particular picture, e.g. only at particular positions bounded for instance to segment boundaries adaptive HTTP streaming.

The object of the present invention is to provide improved concepts for video encoding and video decoding.

The object of the present invention is solved by the subject-matter of the independent claims.

There is disclosed an apparatus for receiving an input video data stream is provided. The input video data stream has a video encoded thereinto. The apparatus is configured to generate an output video data stream from the input video data stream. Moreover, the apparatus is to determine whether a picture of the video preceding a dependent random access picture shall be output or not.

Moreover, a video data stream is provided. The video data stream has a video encoded thereinto. The video data stream comprises an indication that indicates whether a picture of the video preceding a dependent random access picture shall be output or not.

Furthermore, a video encoder is provided. The video encoder is configured to encode a video into a video data stream. Moreover, the video encoder is configured to generate the video data stream such that the video data stream comprises an indication that indicates whether a picture of the video preceding a dependent random access picture shall be output or not.

Moreover, a video decoder for receiving a video data stream having a video stored therein is provided. The video decoder is configured to decode the video from the video data stream. The video decoder is configured to decode the video depending on an indication indicating whether a picture of the video preceding a dependent random access picture shall be output or not.

Furthermore, a method for receiving an input video data stream is provided. The input video data stream has a video encoded thereinto. The method comprises generating an output video data stream from the input video data stream. Moreover, the method comprises determining whether a picture of the video preceding a dependent random access picture shall be output or not.

Moreover, a method for encoding a video into a video data stream is provided. The method comprises generating the video data stream such that the video data stream comprises an indication that indicates whether a picture of the video preceding a dependent random access picture shall be output or not.

Furthermore, a method for receiving a video data stream having a video stored therein is provided. The method comprises decoding the video from the video data stream. Decoding the video is conducted depending on an indication indicating whether a picture of the video preceding a dependent random access picture shall be output or not.

5

Moreover, computer programs for implementing one of the above-described methods when being executed on a computer or signal processor are provided.

10 In accordance with an aspect of the invention, an apparatus for receiving one or more input video data streams is provided. Each of the one or more input video data streams has an input video encoded thereinto. The apparatus is configured to generate an output video data stream from the one or more input video data streams, the output video data stream encoding an output video, wherein the apparatus is configured to generate the output video data stream such that the output video is the input video being encoded within one of the  
15 one or more input video data streams, or such that the output video depends on the input video of at least one of the one or more input video data streams. Moreover, if a concatenation flag is set to a first value, the apparatus is configured to determine that coded picture buffer delay offset information is to be used for determining an access unit removal time of a current picture of a plurality of pictures of the output video from a coded picture  
20 buffer. If the concatenation flag is set to a second value, the apparatus is configured to determine that the coded picture buffer delay offset information is not to be used to determine the access unit removal time.

Furthermore, a video data stream is provided. The video data stream has a video encoded  
25 thereinto. The video data stream comprises coded picture buffer delay offset information.

In accordance with another aspect of the invention, a non-transitory digital storage medium storing a video data stream is provided. The video data stream has a video encoded thereinto. The video data stream comprises coded picture buffer delay offset information  
30 and a concatenation flag. A determination of whether or not to use the coded picture buffer delay offset information is used for determining a removal time of a picture from a coded picture buffer depends at least on the concatenation flag. If the concatenation flag is set to a first value then the concatenation flag indicates that the coded picture buffer delay offset information needs to be used to determine one or more removal times. If the concatenation  
35 flag is set to a second value being different from the first value then the concatenation flag indicates that the indicated offset is not used to determine the one or more removal times.

In accordance with another aspect of the invention, a video encoder is provided. The video encoder is configured to encode a video into a video data stream. The video encoder is configured to generate the video data stream such that the video data stream comprises coded picture buffer delay offset information. The video encoder is configured to determine whether or not to use the coded picture buffer delay offset information for determining a removal time of a picture from a coded picture buffer. if a concatenation flag is set to a first value, the coded picture buffer delay offset information is determined to be used for determining the removal time. If the concatenation flag is set to a second value, the coded picture buffer delay offset information is determined not to be used to determine the removal time.

In accordance with an aspect of the invention, a video decoder for receiving a video data stream a video stored therein is provided. The video decoder is configured to decode the video from the video data stream. Moreover, the video decoder is configured to decode the video depending on an access unit removal time of a current picture of a plurality of pictures of the video from a coded picture buffer. The video decoder is configured to decode the video depending at least on a concatenation flag indicating whether or not to use coded picture buffer delay offset information for determining the access unit removal time of the current picture from the coded picture buffer. If the concatenation flag is set to a first value then the video decoder is configured to use the coded picture buffer delay offset information to determine one or more removal times. If the concatenation flag is set to a second value being different from the first value then the video decoder is configured to not use the coded picture buffer delay offset information to determine the one or more removal times.

Moreover, a method for receiving one or more input video data streams is provided. Each of the one or more input video data streams has an input video encoded thereinto. The method comprises generating an output video data stream from the one or more input video

data streams, the output video data stream encoding an output video, wherein generating the output video data stream is conducted such that the output video is the input video being encoded within one of the one or more input video data streams, or such that the output video depends on the input video of at least one of the one or more input video data streams.

5 Moreover, the method comprises determining an access unit removal time of a current picture of a plurality of pictures of the output video from a coded picture buffer. Furthermore, the method comprises determining whether or not to use coded picture buffer delay offset information for determining the access unit removal time of the current picture from the coded picture buffer.

10

Furthermore, a method for encoding a video into a video data stream according to an embodiment is provided. The method comprises generating the video data stream such that the video data stream comprises coded picture buffer delay offset information.

15 Moreover, a method for receiving a video data stream a video stored therein is provided. The method comprises decoding the video from the video data stream. Decoding the video is conducted depending on an access unit removal time of a current picture of a plurality of pictures of the video from a coded picture buffer. Moreover, decoding the video is conducted depending on an indication indicating whether or not to use coded picture buffer delay offset  
20 information for determining the access unit removal time of the current picture from the coded picture buffer.

Furthermore, computer programs for implementing one of the above-described methods when being executed on a computer or signal processor are provided.

25

There is disclosed a video data stream is provided. The video data stream has a video encoded thereinto. Moreover, the video data stream comprises an initial coded picture buffer removal delay. Furthermore, the video data stream comprises an initial coded picture buffer removal offset. Moreover, the video data stream comprises information that indicates  
30 whether or not a sum of the initial coded picture buffer removal delay and the initial coded picture buffer removal offset is defined to be constant across two or more buffering periods.

Furthermore, a video encoder is provided. The video encoder is configured to encode a video into a video data stream. Moreover, the video encoder is configured to generate the  
35 video data stream such that the video data stream comprises an initial coded picture buffer

removal delay. Furthermore, the video encoder is configured to generate the video data stream such that the video data stream comprises an initial coded picture buffer removal offset. Moreover, the video encoder is configured to generate the video data stream such that the video data stream comprises information that indicates whether or not a sum of the initial coded picture buffer removal delay and the initial coded picture buffer removal offset is defined to be constant across two or more buffering periods.

Moreover, an apparatus for receiving two input video data streams, being a first input video data stream and a second input video data stream, is provided. Each of the two input video data streams has an input video encoded thereinto. The apparatus is configured to generate an output video data stream from the two input video data streams, the output video data stream encoding an output video, wherein the apparatus is configured to generate an output video data stream by concatenating the first input video data stream and the second input video data stream. Moreover, the apparatus is configured to generate the output video data stream such that the output video data stream comprises an initial coded picture buffer removal delay. Furthermore, the apparatus is configured to generate the output video data stream such that the output video data stream comprises an initial coded picture buffer removal offset. Moreover, the apparatus is configured to generate the output video data stream such that the output video data stream comprises information that indicates whether or not a sum of the initial coded picture buffer removal delay and the initial coded picture buffer removal offset is defined to be constant across two or more buffering periods.

Furthermore, a video decoder for receiving a video data stream a video stored therein is provided. The video decoder is configured to decode the video from the video data stream. Moreover, the video data stream comprises an initial coded picture buffer removal delay. Furthermore, the video data stream comprises an initial coded picture buffer removal offset. Moreover, the video data stream comprises information that indicates whether or not a sum of the initial coded picture buffer removal delay and the initial coded picture buffer removal offset is defined to be constant across two or more buffering periods. Furthermore, the video decoder is configured to decode the video depending on the information that indicates whether or not the sum of the initial coded picture buffer removal delay and the initial coded picture buffer removal offset is defined to be constant across the two or more buffering periods.

Moreover, a method for encoding a video into a video data stream is provided. The method comprises generating the video data stream such that the video data stream comprises an

initial coded picture buffer removal delay. Furthermore, the method comprises generating the video data stream such that the video data stream comprises an initial coded picture buffer removal offset. Moreover, the method comprises generating the video data stream such that the video data stream comprises information that indicates whether or not a sum of the initial coded picture buffer removal delay and the initial coded picture buffer removal offset is defined to be constant across two or more buffering periods.

Furthermore, a method for receiving two input video data streams, being a first input video data stream and a second input video data stream, is provided. Each of the two input video data streams has an input video encoded therein. The method comprises generating an output video data stream from the two input video data streams, the output video data stream encoding an output video, wherein the apparatus is configured to generate an output video data stream by concatenating the first input video data stream and the second input video data stream. Moreover, the method comprises generating the output video data stream such that the output video data stream comprises an initial coded picture buffer removal delay. Furthermore, the method comprises generating the output video data stream such that the output video data stream comprises an initial coded picture buffer removal offset. Moreover, the method comprises generating the output video data stream such that the output video data stream comprises information that indicates whether or not a sum of the initial coded picture buffer removal delay and the initial coded picture buffer removal offset is defined to be constant across two or more buffering periods.

Moreover, a method for receiving a video data stream a video stored therein is provided. The method comprises decoding the video from the video data stream. The video data stream comprises an initial coded picture buffer removal delay. Moreover, the video data stream comprises an initial coded picture buffer removal offset. Furthermore, the video data stream comprises information that indicates whether or not a sum of the initial coded picture buffer removal delay and the initial coded picture buffer removal offset is defined to be constant across two or more buffering periods. The method comprises decoding the video depending on the information that indicates whether or not the sum of the initial coded picture buffer removal delay and the initial coded picture buffer removal offset is defined to be constant across the two or more buffering periods.

Furthermore, computer programs for implementing one of the above-described methods when being executed on a computer or signal processor are provided.

There is disclosed a video data stream is provided. The video data stream has a video encoded thereinto. Moreover, the video data stream comprises an indication indicating whether or not a non-scalable nested picture timing supplemental enhancement information message of a network abstraction layer unit of an access unit of the plurality of access units of a coded video sequence of a one or more coded video sequences of the video data stream is defined to apply to all output layer sets of a plurality of output layer sets of said access unit. If the indication has a first value, then the non-scalable nested picture timing supplemental enhancement information message of said network abstraction layer unit of said access unit is defined to apply to all output layer sets of the plurality of output layer sets of said access unit. If the indication has a value being different from the first value, then the indication does not define whether or not the non-scalable nested picture timing supplemental enhancement information message of said network abstraction layer unit of said access unit applies to all output layer sets of the plurality of output layer sets of said access unit.

Moreover, a video encoder is provided. The video encoder is configured to encode a video into a video data stream. Moreover, the video encoder is configured to generate the video data stream such that the video data stream comprises an indication indicating whether or not a non-scalable nested picture timing supplemental enhancement information message of a network abstraction layer unit of an access unit of the plurality of access units of a coded video sequence of a one or more coded video sequences of the video data stream is defined to apply to all output layer sets of a plurality of output layer sets of said access unit. If the indication has a first value, then the non-scalable nested picture timing supplemental enhancement information message of said network abstraction layer unit of said access unit is defined to apply to all output layer sets of the plurality of output layer sets of said access unit. If the indication has a value being different from the first value, then the indication does not define whether or not the non-scalable nested picture timing supplemental enhancement information message of said network abstraction layer unit of said access unit applies to all output layer sets of the plurality of output layer sets of said access unit.

Furthermore, an apparatus for receiving an input video data stream is provided., The input video data stream has a video encoded thereinto. The apparatus is configured to generate an processed video data stream from the input video data stream. Moreover, the apparatus is configured to generate the processed video data stream such that the processed video data stream comprises an indication indicating whether or not a non-scalable nested picture

timing supplemental enhancement information message of a network abstraction layer unit of an access unit of the plurality of access units of a coded video sequence of a one or more coded video sequences of the processed video data stream is defined to apply to all output layer sets of a plurality of output layer sets of said access unit. If the indication has a first value, then the non-scalable nested picture timing supplemental enhancement information message of said network abstraction layer unit of said access unit is defined to apply to all output layer sets of the plurality of output layer sets of said access unit. If the indication has a value being different from the first value, then the indication does not define whether or not the non-scalable nested picture timing supplemental enhancement information message of said network abstraction layer unit of said access unit applies to all output layer sets of the plurality of output layer sets of said access unit.

Moreover, a video decoder for receiving a video data stream having a video stored therein is provided. The video decoder is configured to decode the video from the video data stream. The video data stream comprises an indication indicating whether or not a non-scalable nested picture timing supplemental enhancement information message of a network abstraction layer unit of an access unit of the plurality of access units of a coded video sequence of a one or more coded video sequences of the video data stream is defined to apply to all output layer sets of a plurality of output layer sets of said access unit. If the indication has a first value, then the non-scalable nested picture timing supplemental enhancement information message of said network abstraction layer unit of said access unit is defined to apply to all output layer sets of the plurality of output layer sets of said access unit. If the indication has a value being different from the first value, then the indication does not define whether or not the non-scalable nested picture timing supplemental enhancement information message of said network abstraction layer unit of said access unit applies to all output layer sets of the plurality of output layer sets of said access unit.

Furthermore, a method for encoding a video into a video data stream is provided. The method comprises generating the video data stream such that the video data stream comprises an indication indicating whether or not a non-scalable nested picture timing supplemental enhancement information message of a network abstraction layer unit of an access unit of the plurality of access units of a coded video sequence of a one or more coded video sequences of the video data stream is defined to apply to all output layer sets of a plurality of output layer sets of said access unit. If the indication has a first value, then the non-scalable nested picture timing supplemental enhancement information message of

said network abstraction layer unit of said access unit is defined to apply to all output layer sets of the plurality of output layer sets of said access unit. If the indication has a value being different from the first value, then the indication does not define whether or not the non-scalable nested picture timing supplemental enhancement information message of said network abstraction layer unit of said access unit applies to all output layer sets of the plurality of output layer sets of said access unit.

Moreover, a method for receiving an input video data stream is provided. The input video data stream has a video encoded thereinto. The method comprises generating an processed video data stream from the input video data stream. Moreover, the method comprises generating the processed video data stream such that the processed video data stream comprises an indication indicating whether or not a non-scalable nested picture timing supplemental enhancement information message of a network abstraction layer unit of an access unit of the plurality of access units of a coded video sequence of a one or more coded video sequences of the processed video data stream is defined to apply to all output layer sets of a plurality of output layer sets of said access unit. If the indication has a first value, then the non-scalable nested picture timing supplemental enhancement information message of said network abstraction layer unit of said access unit is defined to apply to all output layer sets of the plurality of output layer sets of said access unit. If the indication has a value being different from the first value, then the indication does not define whether or not the non-scalable nested picture timing supplemental enhancement information message of said network abstraction layer unit of said access unit applies to all output layer sets of the plurality of output layer sets of said access unit.

Furthermore, a method for receiving a video data stream having a video stored therein is provided. The method comprises decoding the video from the video data stream. The video data stream comprises an indication indicating whether or not a non-scalable nested picture timing supplemental enhancement information message of a network abstraction layer unit of an access unit of the plurality of access units of a coded video sequence of a one or more coded video sequences of the video data stream is defined to apply to all output layer sets of a plurality of output layer sets of said access unit. If the indication has a first value, then the non-scalable nested picture timing supplemental enhancement information message of said network abstraction layer unit of said access unit is defined to apply to all output layer sets of the plurality of output layer sets of said access unit. If the indication has a value being different from the first value, then the indication does not define whether or not the non-scalable nested picture timing supplemental enhancement information message of said

network abstraction layer unit of said access unit applies to all output layer sets of the plurality of output layer sets of said access unit.

Moreover, computer programs for implementing one of the above-described methods when  
5 being executed on a computer or signal processor are provided.

There is disclosed a video data stream is provided. The video data stream has a video encoded thereinto. Moreover, the video data stream comprises one or more scalable nested supplemental enhancement information messages. The one or more scalable nested  
10 supplemental enhancement information messages comprise a plurality of syntax elements. Each syntax element of one or more syntax elements of the plurality of syntax elements is defined to have a same size in every one of the scalable nested supplemental enhancement information messages of the video data stream or of a portion of the video data stream.

Moreover, a video encoder is provided. The video encoder is configured to encode a video into a video data stream. Moreover, the video encoder is configured to generate the video data stream such that the video data stream comprises one or more scalable nested supplemental enhancement information messages. Furthermore, the video encoder is configured to generate the video data stream such that the one or more scalable nested  
20 supplemental enhancement information messages comprise a plurality of syntax elements. Moreover, the video encoder is configured to generate the video data stream such that each syntax element of one or more syntax elements of the plurality of syntax elements is defined to have a same size in every one of the scalable nested supplemental enhancement information messages of the video data stream or of a portion of the video data stream.

Furthermore, an apparatus for receiving an input video data stream is provided. The input video data stream has a video encoded thereinto. The apparatus is configured to generate an output video data stream from the input video data stream. The video data stream comprises one or more scalable nested supplemental enhancement information messages.  
30 The one or more scalable nested supplemental enhancement information messages comprise a plurality of syntax elements. Each syntax element of one or more syntax elements of the plurality of syntax elements is defined to have a same size in every one of the scalable nested supplemental enhancement information messages of the video data stream or of a portion of the video data stream. The apparatus is configured to process the  
35 one or more scalable nested supplemental enhancement information messages.

Moreover, a video decoder for receiving a video data stream having a video stored therein is provided. The video decoder is configured to decode the video from the video data stream. The video data stream comprises one or more scalable nested supplemental enhancement information messages. The one or more scalable nested supplemental enhancement information messages comprise a plurality of syntax elements. Each syntax element of one or more syntax elements of the plurality of syntax elements is defined to have a same size in every one of the scalable nested supplemental enhancement information messages of the video data stream or of a portion of the video data stream. The video decoder is configured to decode the video depending on the one or more syntax elements of the plurality of syntax elements.

Furthermore, a method for encoding a video into a video data stream is provided. The method comprises generating the video data stream such that the video data stream comprises one or more scalable nested supplemental enhancement information messages. Moreover, the method comprises generating the video data stream such that the one or more scalable nested supplemental enhancement information messages comprise a plurality of syntax elements. Furthermore, the method comprises generating the video data stream such that each syntax element of one or more syntax elements of the plurality of syntax elements is defined to have a same size in every one of the scalable nested supplemental enhancement information messages of the video data stream or of a portion of the video data stream.

Moreover, a method for receiving an input video data stream is provided. The input video data stream has a video encoded thereinto. The method comprises generating an output video data stream from the input video data stream. The video data stream comprises one or more scalable nested supplemental enhancement information messages. The one or more scalable nested supplemental enhancement information messages comprise a plurality of syntax elements. Each syntax element of one or more syntax elements of the plurality of syntax elements is defined to have a same size in every one of the scalable nested supplemental enhancement information messages of the video data stream or of a portion of the video data stream. The method comprises processing the one or more scalable nested supplemental enhancement information messages.

Furthermore, a method for receiving a video data stream having a video stored therein is provided. The method comprises decoding the video from the video data stream. The video

data stream comprises one or more scalable nested supplemental enhancement information messages. The one or more scalable nested supplemental enhancement information messages comprise a plurality of syntax elements. Each syntax element of one or more syntax elements of the plurality of syntax elements is defined to have a same size  
5 in every one of the scalable nested supplemental enhancement information messages of the video data stream or of a portion of the video data stream. Decoding the video is conducted depending on the one or more syntax elements of the plurality of syntax elements.

10 Moreover, computer programs for implementing one of the above-described methods when being executed on a computer or signal processor are provided.

Preferred embodiments are provided in the dependent claims.

15 In the following, embodiments of the present invention are described in detail with reference to the figures, in which:

Fig. 1 illustrates a video encoder for encoding a video into a video data stream according to an embodiment.  
20

Fig. 2 illustrates an apparatus for receiving an input video data stream according to an embodiment.

Fig. 3 illustrates a video decoder for receiving a video data stream having a video stored therein according to an embodiment.

Fig. 4 illustrates an original bitstream (depicted at the top of Fig. 4), and a bitstream after dropping pictures (depicted at the bottom of Fig. 4) according to an embodiment.  
25

Fig. 5 illustrates a splicing of two bitstreams after pictures have been dropped from the one of the two bitstreams according to an embodiment.

Fig. 6 illustrates a splicing of two bitstreams according to another embodiment.

Fig. 7 illustrates two sets of HRD SEIs, scalable nested SEIs and non-scalable

nested SEIs, in a two-layer bitstream according to an embodiment.

Fig. 8 illustrates a video encoder.

Fig. 9 illustrates a video decoder.

5

Fig. 10 illustrates the relationship between the reconstructed signal, e.g., the reconstructed picture, on the one hand, and the combination of the prediction residual signal as signaled in the data stream, and the prediction signal, on the other hand.

10

The following description of the figures starts with a presentation of a description of an encoder and a decoder of a block-based predictive codec for coding pictures of a video in order to form an example for a coding framework into which embodiments of the present invention may be built in. The respective encoder and decoder are described with respect to Fig. 8 to Fig. 10. Thereinafter the description of embodiments of the concept of the present invention is presented along with a description as to how such concepts could be built into the encoder and decoder of Fig. 8 and Fig. 9, respectively, although the embodiments described with Fig. 1 to Fig. 3 and following, may also be used to form encoders and decoders not operating according to the coding framework underlying the encoder and decoder of Fig. 8 and Fig. 9.

Fig. 8 shows a video encoder, an apparatus for predictively coding a picture 12 into a data stream 14 exemplarily using transform-based residual coding. The apparatus, or encoder, is indicated using reference sign 10. Fig. 9 shows a corresponding video decoder 20, e.g., an apparatus 20 configured to predictively decode the picture 12' from the data stream 14 also using transform-based residual decoding, wherein the apostrophe has been used to indicate that the picture 12' as reconstructed by the decoder 20 deviates from picture 12 originally encoded by apparatus 10 in terms of coding loss introduced by a quantization of the prediction residual signal. Fig. 8 and Fig. 9 exemplarily use transform based prediction residual coding, although embodiments of the present application are not restricted to this kind of prediction residual coding. This is true for other details described with respect to Fig. 8 and Fig. 9, too, as will be outlined hereinafter.

The encoder 10 is configured to subject the prediction residual signal to spatial-to-spectral transformation and to encode the prediction residual signal, thus obtained, into the data stream 14. Likewise, the decoder 20 is configured to decode the prediction residual signal from the data stream 14 and subject the prediction residual signal thus obtained to spectral-to-spatial transformation.

Internally, the encoder 10 may comprise a prediction residual signal former 22 which generates a prediction residual 24 so as to measure a deviation of a prediction signal 26 from the original signal, e.g., from the picture 12. The prediction residual signal former 22 may, for instance, be a subtractor which subtracts the prediction signal from the original signal, e.g., from the picture 12. The encoder 10 then further comprises a transformer 28 which subjects the prediction residual signal 24 to a spatial-to-spectral transformation to obtain a spectral-domain prediction residual signal 24' which is then subject to quantization by a quantizer 32, also comprised by the encoder 10. The thus quantized prediction residual signal 24'' is coded into bitstream 14. To this end, encoder 10 may optionally comprise an entropy coder 34 which entropy codes the prediction residual signal as transformed and quantized into data stream 14. The prediction signal 26 is generated by a prediction stage 36 of encoder 10 on the basis of the prediction residual signal 24'' encoded into, and decodable from, data stream 14. To this end, the prediction stage 36 may internally, as is shown in Fig. 8, comprise a dequantizer 38 which dequantizes prediction residual signal 24'' so as to gain spectral-domain prediction residual signal 24''', which corresponds to signal 24' except for quantization loss, followed by an inverse transformer 40 which subjects the latter prediction residual signal 24''' to an inverse transformation, e.g., a spectral-to-spatial transformation, to obtain prediction residual signal 24''', which corresponds to the original prediction residual signal 24 except for quantization loss. A combiner 42 of the prediction stage 36 then recombines, such as by addition, the prediction signal 26 and the prediction residual signal 24''' so as to obtain a reconstructed signal 46, e.g., a reconstruction of the original signal 12. Reconstructed signal 46 may correspond to signal 12'. A prediction module 44 of prediction stage 36 then generates the prediction signal 26 on the basis of signal 46 by using, for instance, spatial prediction, e.g., intra-picture prediction, and/or temporal prediction, e.g., inter-picture prediction.

Likewise, decoder 20, as shown in Fig. 9, may be internally composed of components corresponding to, and interconnected in a manner corresponding to, prediction stage 36. In particular, entropy decoder 50 of decoder 20 may entropy decode the quantized spectral-domain prediction residual signal 24'' from the data stream, whereupon dequantizer 52,

inverse transformer 54, combiner 56 and prediction module 58, interconnected and cooperating in the manner described above with respect to the modules of prediction stage 36, recover the reconstructed signal on the basis of prediction residual signal 24" so that, as shown in Fig. 9, the output of combiner 56 results in the reconstructed signal, namely picture 12'.

Although not specifically described above, it is readily clear that the encoder 10 may set some coding parameters including, for instance, prediction modes, motion parameters and the like, according to some optimization scheme such as, for instance, in a manner optimizing some rate and distortion related criterion, e.g., coding cost. For example, encoder 10 and decoder 20 and the corresponding modules 44, 58, respectively, may support different prediction modes such as intra-coding modes and inter-coding modes. The granularity at which encoder and decoder switch between these prediction mode types may correspond to a subdivision of picture 12 and 12', respectively, into coding segments or coding blocks. In units of these coding segments, for instance, the picture may be subdivided into blocks being intra-coded and blocks being inter-coded. Intra-coded blocks are predicted on the basis of a spatial, already coded/decoded neighborhood of the respective block as is outlined in more detail below. Several intra-coding modes may exist and be selected for a respective intra-coded segment including directional or angular intra-coding modes according to which the respective segment is filled by extrapolating the sample values of the neighborhood along a certain direction which is specific for the respective directional intra-coding mode, into the respective intra-coded segment. The intra-coding modes may, for instance, also comprise one or more further modes such as a DC coding mode, according to which the prediction for the respective intra-coded block assigns a DC value to all samples within the respective intra-coded segment, and/or a planar intra-coding mode according to which the prediction of the respective block is approximated or determined to be a spatial distribution of sample values described by a two-dimensional linear function over the sample positions of the respective intra-coded block with driving tilt and offset of the plane defined by the two-dimensional linear function on the basis of the neighboring samples. Compared thereto, inter-coded blocks may be predicted, for instance, temporally. For inter-coded blocks, motion vectors may be signaled within the data stream, the motion vectors indicating the spatial displacement of the portion of a previously coded picture of the video to which picture 12 belongs, at which the previously coded/decoded picture is sampled in order to obtain the prediction signal for the respective inter-coded block. This means, in addition to the residual signal coding comprised by data stream 14, such as the entropy-coded transform coefficient levels representing the quantized spectral-

domain prediction residual signal 24'', data stream 14 may have encoded thereinto coding mode parameters for assigning the coding modes to the various blocks, prediction parameters for some of the blocks, such as motion parameters for inter-coded segments, and optional further parameters such as parameters for controlling and signaling the subdivision of picture 12 and 12', respectively, into the segments. The decoder 20 uses these parameters to subdivide the picture in the same manner as the encoder did, to assign the same prediction modes to the segments, and to perform the same prediction to result in the same prediction signal.

Fig. 10 illustrates the relationship between the reconstructed signal, e.g., the reconstructed picture 12', on the one hand, and the combination of the prediction residual signal 24'''' as signaled in the data stream 14, and the prediction signal 26, on the other hand. As already denoted above, the combination may be an addition. The prediction signal 26 is illustrated in Fig. 10 as a subdivision of the picture area into intra-coded blocks which are illustratively indicated using hatching, and inter-coded blocks which are illustratively indicated not-hatched. The subdivision may be any subdivision, such as a regular subdivision of the picture area into rows and columns of square blocks or non-square blocks, or a multi-tree subdivision of picture 12 from a tree root block into a plurality of leaf blocks of varying size, such as a quadtree subdivision or the like, wherein a mixture thereof is illustrated in Fig. 10 in which the picture area is first subdivided into rows and columns of tree root blocks which are then further subdivided in accordance with a recursive multi-tree subdividing into one or more leaf blocks.

Again, data stream 14 may have an intra-coding mode coded thereinto for intra-coded blocks 80, which assigns one of several supported intra-coding modes to the respective intra-coded block 80. For inter-coded blocks 82, the data stream 14 may have one or more motion parameters coded thereinto. Generally speaking, inter-coded blocks 82 are not restricted to being temporally coded. Alternatively, inter-coded blocks 82 may be any block predicted from previously coded portions beyond the current picture 12 itself, such as previously coded pictures of a video to which picture 12 belongs, or picture of another view or an hierarchically lower layer in the case of encoder and decoder being scalable encoders and decoders, respectively.

The prediction residual signal 24'''' in Fig. 10 is also illustrated as a subdivision of the picture area into blocks 84. These blocks might be called transform blocks in order to distinguish same from the coding blocks 80 and 82. In effect, Fig. 10 illustrates that encoder 10 and

decoder 20 may use two different subdivisions of picture 12 and picture 12', respectively, into blocks, namely one subdividing into coding blocks 80 and 82, respectively, and another subdivision into transform blocks 84. Both subdivisions might be the same, e.g., each coding block 80 and 82, may concurrently form a transform block 84, but Fig. 10 illustrates the case where, for instance, a subdivision into transform blocks 84 forms an extension of the subdivision into coding blocks 80, 82 so that any border between two blocks of blocks 80 and 82 overlays a border between two blocks 84, or alternatively speaking each block 80, 82 either coincides with one of the transform blocks 84 or coincides with a cluster of transform blocks 84. However, the subdivisions may also be determined or selected independent from each other so that transform blocks 84 could alternatively cross block borders between blocks 80, 82. As far as the subdivision into transform blocks 84 is concerned, similar statements are thus true as those brought forward with respect to the subdivision into blocks 80, 82, e.g., the blocks 84 may be the result of a regular subdivision of picture area into blocks (with or without arrangement into rows and columns), the result of a recursive multi-tree subdividing of the picture area, or a combination thereof or any other sort of blockation. Just as an aside, it is noted that blocks 80, 82 and 84 are not restricted to being of quadratic, rectangular or any other shape.

Fig. 10 further illustrates that the combination of the prediction signal 26 and the prediction residual signal 24''' directly results in the reconstructed signal 12'. However, it should be noted that more than one prediction signal 26 may be combined with the prediction residual signal 24''' to result into picture 12' in accordance with alternative embodiments.

In Fig. 10, the transform blocks 84 shall have the following significance. Transformer 28 and inverse transformer 54 perform their transformations in units of these transform blocks 84. For instance, many codecs use some sort of DST or DCT for all transform blocks 84. Some codecs allow for skipping the transformation so that, for some of the transform blocks 84, the prediction residual signal is coded in the spatial domain directly. However, in accordance with embodiments described below, encoder 10 and decoder 20 are configured in such a manner that they support several transforms. For example, the transforms supported by encoder 10 and decoder 20 could comprise:

- DCT-II (or DCT-III), where DCT stands for Discrete Cosine Transform
- DST-IV, where DST stands for Discrete Sine Transform
- DCT-IV
- DST-VII

- Identity Transformation (IT)

Naturally, while transformer 28 would support all of the forward transform versions of these transforms, the decoder 20 or inverse transformer 54 would support the corresponding  
5 backward or inverse versions thereof:

- Inverse DCT-II (or inverse DCT-III)
- Inverse DST-IV
- Inverse DCT-IV
- 10 ○ Inverse DST-VII
- Identity Transformation (IT)

The subsequent description provides more details on which transforms could be supported by encoder 10 and decoder 20. In any case, it should be noted that the set of supported  
15 transforms may comprise merely one transform such as one spectral-to-spatial or spatial-to-spectral transform.

As already outlined above, Fig. 8 to Fig. 10 have been presented as an example where the inventive concept described further below may be implemented in order to form specific  
20 examples for encoders and decoders according to the present application. Insofar, the encoder and decoder of Fig. 8 and Fig. 9, respectively, may represent possible implementations of the encoders and decoders described herein below. Fig. 8 and Fig. 9 are, however, only examples. An encoder according to embodiments of the present application may, however, perform block-based encoding of a picture 12 using the concept  
25 outlined in more detail below and being different from the encoder of Fig. 8 such as, for instance, in that same is no video encoder, but a still picture encoder, in that same does not support inter-prediction, or in that the sub-division into blocks 80 is performed in a manner different than exemplified in Fig. 10. Likewise, decoders according to embodiments of the present application may perform block-based decoding of picture 12' from data stream 14  
30 using the coding concept further outlined below, but may differ, for instance, from the decoder 20 of Fig. 9 in that same is no video decoder, but a still picture decoder, in that same does not support intra-prediction, or in that same sub-divides picture 12' into blocks in a manner different than described with respect to Fig. 10 and/or in that same does not derive the prediction residual from the data stream 14 in transform domain, but in spatial  
35 domain, for instance.

Fig. 1 illustrates a video encoder 100 for encoding a video into a video data stream according to an embodiment. The video encoder 100 is configured to generate the video data stream such that the video data stream comprises an indication that indicates whether a picture of the video preceding a dependent random access picture shall be output or not.

5

Fig. 2 illustrates an apparatus 200 for receiving an input video data stream according to an embodiment. The input video data stream has a video encoded thereinto. The apparatus 200 is configured to generate an output video data stream from the input video data stream.

10 Fig. 3 illustrates a video decoder 300 for receiving a video data stream having a video stored therein according to an embodiment. The video decoder 300 is configured to decode the video from the video data stream. The video decoder 300 is configured to decode the video depending on an indication indicating whether a picture of the video preceding a dependent random access picture shall be output or not.

15

Moreover, a system according to an embodiment is provided. The system comprises the apparatus of Fig. 2 and the video decoder of Fig. 3. The video decoder 300 of Fig. 3 is configured to receive the output video data stream of the apparatus of Fig. 2. The video decoder 300 of Fig. 3 is configured to decode the video from the output video data stream  
20 of the apparatus 200 of Fig. 2.

In an embodiment, the system may, e.g., further comprise a video encoder 100 of Fig. 1. The apparatus 200 of Fig. 2 may, e.g., be configured to receive the video data stream from the video encoder 100 of Fig. 1 as the input video data stream.

25

The (optional) intermediate device 210 of the apparatus 200 may, e.g., be configured to receive the video data stream from the video encoder 100 as an input video data stream and to generate an output video data stream from the input video data stream. For example, the intermediate device may, e.g., be configured to modify (header/meta data) information  
30 of the input video data stream and/or may, e.g., be configured to delete pictures from the input video data stream and/or may be configured to mix/splice the input video data stream with an additional second bitstream having a second video encoded thereinto.

The (optional) video decoder 221 may, e.g., be configured to decode the video from the  
35 output video data stream.

The (optional) Hypothetical Reference Decoder 222 may, e.g., be configured to determine timing information for the video depending on the output video data stream, or may, e.g., be configured to determine buffer information for a buffer into which the video or a portion of the video is to be stored.

5

The system comprises the video encoder 101 of Fig. 1 and the video decoder 151 of Fig. 2.

10 The video encoder 101 is configured to generate the encoded video signal. The video decoder 151 is configured to decode the encoded video signal to reconstruct the picture of the video.

A first aspect of the invention is claimed in claims 1 to 38.

15 A second aspect of the invention is claimed in claims 39 to 78.

A third aspect of the invention is claimed in claims 79 to 108.

20 A fourth aspect of the invention is claimed in claims 109 to 134.

A fifth aspect of the invention is claimed in claims 135 to 188.

In the following, the first aspect of the invention is now described in detail.

25 In accordance with the first aspect of the invention, an apparatus 200 for receiving an input video data stream is provided. The input video data stream has a video encoded thereinto. The apparatus 200 is configured to generate an output video data stream from the input video data stream. Moreover, the apparatus 200 is to determine whether a picture of the video preceding a dependent random access picture shall be output or not.

30

According to an embodiment, the apparatus 200 may, e.g., be configured to determine a first variable (e.g., a NoOutputBeforeDrpFlag) indicating whether the picture of the video that precedes the dependent random access picture shall be output or not.

35 In an embodiment, the apparatus 200 may, e.g., be configured to generate the output video data stream such that the output video data stream may, e.g., comprise an indication that

may, e.g., indicate whether the picture of the video preceding the dependent random access picture shall be output or not.

5 According to an embodiment, the apparatus 200 may, e.g., be configured to generate the output video data stream such that the output video data stream may, e.g., comprise supplemental enhancement information comprising the indication that may, e.g., indicate whether the picture of the video preceding the dependent random access picture shall be output or not.

10 In an embodiment, the picture of the video that precedes the dependent random access picture may, e.g., be an independent random access picture. The apparatus 200 may, e.g., be configured to generate the output video data stream such that the output video data stream may, e.g., comprise a flag (e.g., a `ph_pic_output_flag`) having a predefined value (e.g., 0) in a picture header of the independent random access picture, such that the  
15 predefined value (e.g., 0) of the flag (e.g., a `ph_pic_output_flag`) may, e.g., indicate for the independent random access picture directly precedes said dependent random access picture within the video data stream, and that said independent random access picture shall not be output.

20 According to an embodiment, the flag may, e.g., be a first flag, wherein the apparatus 200 may, e.g., be configured to generate the output video data stream such that the output video data stream may, e.g., comprise a further flag in a picture parameter set of the video data stream, wherein the further flag may, e.g., indicate whether or not the first flag (e.g., a `ph_pic_output_flag`) exists in the picture header of the independent random access picture.

25 In an embodiment, the apparatus 200 may, e.g., be configured to generate the output video data stream such that the output video data stream may, e.g., comprise as the indication that may, e.g., indicate whether the picture of the video preceding the dependent random access picture shall be output or not a supplemental enhancement information flag within a  
30 supplemental enhancement information of the output video data stream, or a picture parameter set flag within a picture parameter set of the output video data stream, or a sequence parameter set flag within a sequence parameter set of the output video data stream, or an external means flag, wherein a value of the external means flag may, e.g., be set by an external unit being external to the apparatus 200.

35

According to an embodiment, the apparatus 200 may, e.g., be configured to determine a value of a second variable (e.g., a PictureOutputFlag) for the picture of the video that precedes the dependent random access picture depending on the first variable (e.g., a NoOutputBeforeDrapFlag), wherein the second variable (e.g., a PictureOutputFlag) may, e.g., indicate for said picture whether said picture shall be output or not, and wherein the apparatus 200 may, e.g., be configured to output or to not output said picture depending on the second variable (e.g., a PictureOutputFlag).

In an embodiment, the picture of the video that precedes the dependent random access picture may, e.g., be an independent random access picture. The first variable (e.g., a NoOutputBeforeDrapFlag) may, e.g., indicate that the independent random access picture shall not be output.

According to an embodiment, the picture of the video that precedes the dependent random access picture may, e.g., be an independent random access picture. The apparatus 200 may, e.g., be configured to set the first variable (e.g., a NoOutputBeforeDrapFlag) such that the first variable (e.g., a NoOutputBeforeDrapFlag) may, e.g., indicate that the independent random access picture shall be output.

In an embodiment, the apparatus 200 may, e.g., be configured to signal to a video decoder 300, whether a picture of the video preceding a dependent random access picture shall be output or not.

Moreover, a video data stream is provided. The video data stream has a video encoded thereinto. The video data stream comprises an indication that indicates whether a picture of the video preceding a dependent random access picture shall be output or not.

According to an embodiment, the video data stream may, e.g., comprise supplemental enhancement information comprising the indication that may, e.g., indicate whether the picture of the video preceding the dependent random access picture shall be output or not.

In an embodiment, the picture of the video that precedes the dependent random access picture may, e.g., be an independent random access picture. The video data stream may, e.g., comprise a flag (e.g., a ph\_pic\_output\_flag) having a predefined value (e.g., 0) in a picture header of the independent random access picture, such that the predefined value (e.g., 0) of the flag (e.g., a ph\_pic\_output\_flag) may, e.g., indicate for the independent

random access picture directly precedes said dependent random access picture within the video data stream, and that said independent random access picture shall not be output.

5 According to an embodiment, the flag may, e.g., be a first flag, wherein the video data stream may, e.g., comprise a further flag in a picture parameter set of the video data stream, wherein the further flag may, e.g., indicate whether or not the first flag (e.g., a ph\_pic\_output\_flag) exists in the picture header of the independent random access picture.

10 In an embodiment, the video data stream may, e.g., comprise as the indication that may, e.g., indicate whether the picture of the video preceding the dependent random access picture shall be output or not a supplemental enhancement information flag within a supplemental enhancement information of the output video data stream, or a picture parameter set flag within a picture parameter set of the output video data stream, or a sequence parameter set flag within a sequence parameter set of the output video data stream, or an external means flag, wherein a value of the external means flag may, e.g., be set by an external unit being external to an apparatus 200.

20 Furthermore, a video encoder 100 is provided. The video encoder 100 may, e.g., be configured to encode a video into a video data stream. Moreover, the video encoder 100 may, e.g., be configured to generate the video data stream such that the video data stream comprises an indication that indicates whether a picture of the video preceding a dependent random access picture shall be output or not.

25 According to an embodiment, the video encoder 100 may, e.g., be configured to generate the video data stream such that the video data stream may, e.g., comprise supplemental enhancement information comprising the indication that may, e.g., indicate whether the picture of the video preceding the dependent random access picture shall be output or not.

30 In an embodiment, the picture of the video that precedes the dependent random access picture may, e.g., be an independent random access picture. The video encoder 100 may, e.g., be configured to generate the video data stream such that the video data stream may, e.g., comprise a flag (e.g., a ph\_pic\_output\_flag) having a predefined value (e.g., 0) in a picture header of the independent random access picture, such that the predefined value (e.g., 0) of the flag (e.g., a ph\_pic\_output\_flag) may, e.g., indicate for the independent random access picture directly precedes said dependent random access picture within the video data stream, and that said independent random access picture shall not be output.

According to an embodiment, the flag may, e.g., be a first flag, wherein the video encoder 100 may, e.g., be configured to generate the video data stream such that the video data stream may, e.g., comprise a further flag in a picture parameter set of the video data stream, wherein the further flag may, e.g., indicate whether or not the first flag (e.g., a ph\_pic\_output\_flag) exists in the picture header of the independent random access picture.

In an embodiment, the video encoder 100 may, e.g., be configured to generate the video data stream such that the video data stream may, e.g., comprise as the indication that may, e.g., indicate whether the picture of the video preceding the dependent random access picture shall be output or not a supplemental enhancement information flag within a supplemental enhancement information of the output video data stream, or a picture parameter set flag within a picture parameter set of the output video data stream, or a sequence parameter set flag within a sequence parameter set of the output video data stream, or an external means flag, wherein a value of the external means flag may, e.g., be set by an external unit being external to an apparatus 200.

Moreover, a video decoder 300 for receiving a video data stream having a video stored therein is provided. The video decoder 300 is configured to decode the video from the video data stream. The video decoder 300 is configured to decode the video depending on an indication indicating whether a picture of the video preceding a dependent random access picture shall be output or not.

According to an embodiment, the video decoder 300 may, e.g., be configured to decode the video depending on a first variable (e.g., a NoOutputBeforeDrapFlag) indicating whether the picture of the video that precedes the dependent random access picture shall be output or not.

In an embodiment, the video data stream may, e.g., comprise the indication that may, e.g., indicate whether the picture of the video preceding the dependent random access picture shall be output or not. The video decoder 300 may, e.g., be configured to decode the video depending on the indication within the video data stream.

According to an embodiment, the video data stream may, e.g., comprise supplemental enhancement information comprising the indication that may, e.g., indicate whether the picture of the video preceding the dependent random access picture shall be output or not.

The video decoder 300 may, e.g., be configured to decode the video depending on the supplemental enhancement information.

5 In an embodiment, the picture of the video that precedes the dependent random access picture may, e.g., be an independent random access picture. The video data stream may, e.g., comprise a flag (e.g., a `ph_pic_output_flag`) having a predefined value (e.g., 0) in a picture header of the independent random access picture, such that the predefined value (e.g., 0) of the flag (e.g., a `ph_pic_output_flag`) may, e.g., indicate for the independent random access picture directly precedes said dependent random access picture within the video data stream, and that said independent random access picture shall not be output.  
10 The video decoder 300 may, e.g., be configured to decode the video depending on the flag.

According to an embodiment, the flag may, e.g., be a first flag, wherein the video data stream may, e.g., comprise a further flag in a picture parameter set of the video data stream, wherein the further flag may, e.g., indicate whether or not the first flag (e.g., a `ph_pic_output_flag`) exists in the picture header of the independent random access picture.  
15 The video decoder 300 may, e.g., be configured to decode the video depending on the further flag.

20 In an embodiment, the video data stream may, e.g., comprise as the indication that may, e.g., indicate whether the picture of the video preceding the dependent random access picture shall be output or not a supplemental enhancement information flag within a supplemental enhancement information of the output video data stream, or a picture parameter set flag within a picture parameter set of the output video data stream, or a sequence parameter set flag within a sequence parameter set of the output video data stream, or an external means flag, wherein a value of the external means flag may, e.g., be set by an external unit being external to an apparatus 200. The video decoder 300 may, e.g., be configured to decode the video depending on the indication within the video data stream.  
25

30 According to an embodiment, the video decoder 300 may, e.g., be configured to reconstruct the video from the video data stream. The video decoder 300 may, e.g., be configured to output or to not output the picture of the video that precedes the dependent random access picture depending on the first variable (e.g., a `NoOutputBeforeDrpFlag`).  
35

In an embodiment, the video decoder 300 may, e.g., be configured to determine a value of a second variable (e.g., a PictureOutputFlag) for the picture of the video that precedes the dependent random access picture depending on the first variable (e.g., a NoOutputBeforeDrapFlag), wherein the second variable (e.g., a PictureOutputFlag) may, e.g., indicate for said picture whether said picture shall be output or not, and wherein the apparatus 200 may, e.g., be configured to output or to not output said picture depending on the second variable (e.g., a PictureOutputFlag).

According to an embodiment, the picture of the video that precedes the dependent random access picture may, e.g., be an independent random access picture. The video decoder 300 may, e.g., be configured to decode the video depending on the first variable (e.g., a NoOutputBeforeDrapFlag) which may, e.g., indicate that the independent random access picture shall not be output.

In an embodiment, the picture of the video that precedes the dependent random access picture may, e.g., be an independent random access picture. The video decoder 300 may, e.g., be configured to decode the video depending on the first variable (e.g., a NoOutputBeforeDrapFlag) which may, e.g., indicate that the independent random access picture shall be output.

Furthermore, a system is provided. The system comprises an apparatus 200 as described above and a video decoder 300 as described above. The video decoder 300 is configured to receive the output video data stream of the apparatus 200. Moreover, the video decoder 300 is configured to decode the video from the output video data stream of the apparatus 200.

According to an embodiment, the system may, e.g., further comprise a video encoder 100. The apparatus 200 may, e.g., be configured to receive the video data stream from the video encoder 100 as the input video data stream.

In particular, the first aspect of the invention relates to CVS start at DRAP and to omit IDR output in decoding and conformance testing.

When a bitstream comprises pictures marked as DRAP (i.e. only using the previous IRAP as reference for the DRAP and from there on in the bitstream) it is possible to utilize these DRAP pictures for random access functionality at lower rate overhead. However, when

using some target DRAP for random accessing a stream, it is undesirable to display any initial picture before the target DRAP (i.e. the associated IRAP of target DRAP) at the decoder output as the temporal distance between these pictures would lead to a shaky/jittery video playback when played back at the rate of the original video until the video is played back in a smooth way from the target DRAP on.

Therefore, it is desirable to omit the output of the pictures preceding the DRAP picture. This aspect of the invention presents means to control the decoder accordingly.

10 In one embodiment, an external means to set the PicOutputFlag variable of an IRAP picture is made available for implementations to use as follows:

- If some external means not specified in this Specification is available to set the variable NoOutputBeforeDrapFlag for the picture to a value,  
15 NoOutputBeforeDrapFlag for the picture is set equal to the value provided by the external means.

[...]

- The variable PictureOutputFlag of the current picture is derived as follows:
  - If sps\_video\_parameter\_set\_id is greater than 0 and the current layer is not an output layer (i.e., nuh\_layer\_id is not equal to  
20 OutputLayerIdInOls[ TargetOlsIdx ][ i ] for any value of i in the range of 0 to NumOutputLayersInOls[ TargetOlsIdx ] – 1, inclusive), or one of the following conditions is true, PictureOutputFlag is set equal to 0:
    - The current picture is a RASL picture and NoOutputBeforeRecoveryFlag of  
25 the associated IRAP picture is equal to 1.
    - The current picture is a GDR picture with NoOutputBeforeRecoveryFlag equal to 1 or is a recovering picture of a GDR picture with NoOutputBeforeRecoveryFlag equal to 1.
    - The current picture is a IRAP picture with NoOutputBeforeDrapFlag equal  
30 to 1.
  - Otherwise, PictureOutputFlag is set equal to ph\_pic\_output\_flag.

In another embodiment, the NoOutputBeforeDrapFlag is set by external means only for the first IRAP picture in a CVS, and set to 0 otherwise.

- If some external means not specified in this Specification is available to set the variable NoOutputBeforeDrapFlag for the picture to a value,  
NoOutputBeforeDrapFlag for the first picture in the CVS is set equal to the value provided by the external means. Otherwise, NoOutputBeforeDrapFlag is set to 0.
- 10 The above mentioned flag NoOutputBeforeDrapFlag could also be associated with the usage of alternative HRD timings conveyed in the bitstream for the case of removal of pictures between the IRAP picture and the DRAP picture, e.g. a the flag UseAltCpbParamsFlag in the VVC specification.
- 15 In an alternative embodiment, it is a constraint that IRAP pictures that directly precede DRAP pictures without non-DRAP pictures in between shall have a value of 0 in the output flag ph\_pic\_output\_flag in the picture header. In this case, whenever an extractor or player uses a DRAP for random accessing, i.e. it removes intermediate pictures between IRAP and DRAP from the bitstream, it is also required to verify or adjust that the respective output
- 20 flag is set to 0 and output of the IRAP is omitted.

For this operation to be simple the original bitstream needs to be prepared correspondingly. More concretely, pps\_output\_flag\_present\_flag, which determines the presence of the flag ph\_pic\_output\_flag in the picture header shall be equal to 1 so that

25 the picture header can be easily change and it is not required to change also parameter sets. That is:

It is a requirement of bitstream conformance that the value of pps\_output\_flag\_present\_flag shall be equal to 1 if the PPS is referred to by a picture within a CVSS AU that has

30 associated DRAP AUs.

In addition to the options listed above, in another embodiment, it is indicated in a parameter set PPS or an SPS whether the first AU in the bitstream, i.e. a CRA or IDR that constitutes a CLVS start, is to be output or not after decoding. Thus, the system integration is simpler,

as only a parameter set needs to be adjusted instead of requiring comparatively low-level syntax such as a PHs also to be changed, e.g. when parsing a file in file format ISOBMFF.

An example is shown in the following:

5

|                                     |                        |
|-------------------------------------|------------------------|
| seq_parameter_set_rbsp( ) {         | <b>Descript<br/>or</b> |
| [...]                               |                        |
| if( sps_conformance_window_flag ) { |                        |
| sps_conf_win_left_offset            | ue(v)                  |
| sps_conf_win_right_offset           | ue(v)                  |
| sps_conf_win_top_offset             | ue(v)                  |
| sps_conf_win_bottom_offset          | ue(v)                  |
| }                                   |                        |
| sps_pic_in_cvss_au_no_output_flag   | u(1)                   |
| sps_log2_ctu_size_minus5            | u(2)                   |
| [...]                               |                        |
| }                                   |                        |

**sps\_pic\_in\_cvss\_au\_no\_output\_flag** equal to 1 specifies that a picture in a CVSS AU referring to the SPS is not output. **sps\_pic\_in\_cvss\_au\_no\_output\_flag** equal to 0 specifies that a picture in a CVSS AU referring to the SPS may or may not be output.

- 10 It is a requirement of bitstream conformance that the value of **sps\_pic\_in\_cvss\_au\_no\_output\_flag** shall be the same for any SPS referred to by any output layer in an OLS.

In 8.1.2

- The variable **PictureOutputFlag** of the current picture is derived as follows:
  - 15 – If **sps\_video\_parameter\_set\_id** is greater than 0 and the current layer is not an output layer (i.e., **nuh\_layer\_id** is not equal to **OutputLayerIdInOls[ TargetOlsIdx ][ i ]** for any value of *i* in the range of 0 to **NumOutputLayersInOls[ TargetOlsIdx ] – 1**, inclusive), or one of the following conditions is true, **PictureOutputFlag** is set equal to 0:
    - 20 – The current picture is a RASL picture and **NoOutputBeforeRecoveryFlag** of the associated IRAP picture is equal to 1.
    - The current picture is a GDR picture with **NoOutputBeforeRecoveryFlag** equal to 1 or is a recovering picture of a GDR picture with **NoOutputBeforeRecoveryFlag** equal to 1.
    - 25 – Otherwise, if the current AU is a CVSS AU and **sps\_pic\_in\_cvss\_au\_no\_output\_flag** equal to 1 **PictureOutputFlag** is set equal to 0.

- Otherwise, PictureOutputFlag is set equal to ph\_pic\_output\_flag.

NOTE – In an implementation, the decoder could output a picture not belonging to an output layer. For example, when there is only one output layer while in an AU the picture of the output layer is not available, e.g., due to a loss or layer down-switching, the decoder could set PictureOutputFlag set equal to 1 for the picture that has the highest value of nuh\_layer\_id among all pictures of the AU available to the decoder and having ph\_pic\_output\_flag equal to 1, and set PictureOutputFlag equal to 0 for all other pictures of the AU available to the decoder.

In another embodiment, for example, a requirement may, e.g., be defined as follows:

It is a requirement of bitstream conformance that the value of ph\_pic\_output\_flag shall be equal to 0 if the a picture belongs to a IRAP AU and the IRAP AU is directly preceding a DRAP AU.

In the following, the second aspect of the invention is now described in detail.

In accordance with the second aspect of the invention, an apparatus 200 for receiving one or more input video data streams is provided. Each of the one or more input video data streams has an input video encoded thereinto. The apparatus 200 is configured to generate an output video data stream from the one or more input video data streams, the output video data stream encoding an output video, wherein the apparatus is configured to generate the output video data stream such that the output video is the input video being encoded within one of the one or more input video data streams, or such that the output video depends on the input video of at least one of the one or more input video data streams. Moreover, the apparatus 200 is configured to determine an access unit removal time of a current picture of a plurality of pictures of the output video from a coded picture buffer. The apparatus 200 is configured to determine whether or not to use coded picture buffer delay offset information for determining the access unit removal time of the current picture from the coded picture buffer.

According to an embodiment, the apparatus 200 may, e.g., be configured to drop a group of one or more pictures of the input video of a first video data stream of the one or more input video data streams to generate the output video data stream. The apparatus 200 may, e.g., be configured to determine an access unit removal time for at least one of the plurality

of pictures of the output video from the coded picture buffer depending on the coded picture buffer delay offset information.

5 In an embodiment, the first video received by the apparatus 200 may, e.g., be a preprocessed video which results from an original video from which a group of one or more pictures has been dropped to generate the preprocessed video. The apparatus 200 may, e.g., be configured to determine an access unit removal time for at least one of the plurality of pictures of the output video from the coded picture buffer depending on the coded picture buffer delay offset information.

10

According to an embodiment, the buffer delay offset information depends on a number of pictures of the input video that have been dropped.

15 In an embodiment, the one or more input video data streams are two or more input video data streams. The apparatus 200 may, e.g., be configured to splice the processed video and the input video of a second video data stream of the two or more input video data streams to obtain the output video, and may, e.g., be configured to encode the output video into the output video data stream.

20 According to an embodiment, the apparatus 200 may, e.g., be configured to determine whether or not to use coded picture buffer delay offset information for determining the access unit removal time of the current picture depending on a location of the current picture within the output video. Or, the apparatus 200 may, e.g., be configured to determine whether or not to set a coded picture buffer delay offset value of the coded picture buffer delay offset information to 0 for determining the access unit removal time of the current picture depending on the location of the current picture within the output video.

25 In an embodiment, the apparatus 200 may, e.g., be configured to determine whether or not to use coded picture buffer delay offset information for determining the access unit removal time of the current picture depending on a position of a previous non-discardable picture which precedes the current picture within the output video.

30 According to an embodiment, the apparatus 200 may, e.g., be configured to determine whether or not to use coded picture buffer delay offset information for determining the access unit removal time of the current picture depending on whether or not the previous

35

non-discardable picture which precedes the current picture within the output video may, e.g., be a first picture in a previous buffering period.

5 In an embodiment, the apparatus 200 may, e.g., be configured to determine whether or not to use coded picture buffer delay offset information for determining the access unit removal time of the current picture depending on a concatenation flag, the current picture being a first picture of the input video of the second video data stream.

10 According to an embodiment, the apparatus 200 may, e.g., be configured to determine the access unit removal time of the current picture depending on a removal time of a preceding picture.

15 In an embodiment, the apparatus 200 may, e.g., be configured to determine the access unit removal time of the current picture depending on initial coded picture buffer removal delay information.

20 According to an embodiment, the apparatus 200 may, e.g., be configured to update the initial coded picture buffer removal delay information depending on a clock tick to obtain temporary coded picture buffer removal delay information to determine the access unit removal time of the current picture.

25 According to an embodiment, if the concatenation flag is set to a first value, then the apparatus 200 is configured to use the coded picture buffer delay offset information to determine one or more removal times. If the concatenation flag is set to a second value being different from the first value then the apparatus 200 is configured to not use the coded picture buffer delay offset information to determine the one or more removal times.

30 In an embodiment, the apparatus 200 may, e.g., be configured to signal to a video decoder 300, whether or not to use coded picture buffer delay offset information for determining the access unit removal time of the current picture from the coded picture buffer.

According to an embodiment, the current picture may, e.g., be located at a splicing point of the output video, where two input videos have been spliced.

35 Furthermore, a video data stream is provided. The video data stream has a video encoded thereinto. The video data stream comprises coded picture buffer delay offset information.

According to an embodiment, the video data stream may, e.g., comprise a concatenation flag.

- 5 In an embodiment, the video data stream may, e.g., comprise initial coded picture buffer removal delay information.

According to an embodiment, if the concatenation flag is set to a first value (e.g., 0) then the concatenation flag indicates that the coded picture buffer delay offset information needs  
10 to be used to determine one or more (picture or access unit) removal times, e.g., when it is known that some pictures (e.g., RASL pictures) have been dropped. If the concatenation flag is set to a second value being different from the first value (e.g., 1) then the concatenation flag indicates that the indicated offset is not used to determine the one or more (picture or access unit) removal times, e.g., irrespective of an offset signaling and,  
15 e.g., irrespective of whether RASL pictures have been dropped. If pictures are not dropped, then, e.g., the offset is not to be used.

Moreover, a video encoder 100, is provided. The video encoder 100 is configured to encode a video into a video data stream. The video encoder 100 is configured to generate the video  
20 data stream such that the video data stream comprises coded picture buffer delay offset information.

According to an embodiment, the video encoder 100 may, e.g., be configured to generate the video data stream such that the video data stream may, e.g., comprise a concatenation  
25 flag.

In an embodiment, the video encoder 100 may, e.g., be configured to generate the video data stream such that the video data stream may, e.g., comprise coded picture buffer delay offset information.

30 Furthermore, a video decoder 300 for receiving a video data stream a video stored therein is provided. The video decoder 300 is configured to decode the video from the video data stream. Moreover, the video decoder 300 is configured to decode the video depending on an access unit removal time of a current picture of a plurality of pictures of the video from a coded picture buffer. The video decoder 300 is configured to decode the video depending  
35 on an indication indicating whether or not to use coded picture buffer delay offset

information for determining the access unit removal time of the current picture from the coded picture buffer.

5 According to an embodiment, the access unit removal time for at least one of the plurality of pictures of the video from the coded picture buffer depends on the coded picture buffer delay offset information.

10 In an embodiment, the video decoder 300 is configured to decode the video depending on whether or not to use coded picture buffer delay offset information for determining the access unit removal time of the current picture depending on a location of the current picture within the video.

15 According to an embodiment, the video decoder 300 may, e.g., be configured to decode the video depending on whether or not a coded picture buffer delay offset value of the coded picture buffer delay offset information may, e.g., be set to 0.

20 In an embodiment, the video decoder 300 may, e.g., be configured to determine whether or not to use coded picture buffer delay offset information for determining the access unit removal time of the current picture depending on a position of a previous non-discardable picture which precedes the current picture within the video.

25 According to an embodiment, the video decoder 300 may, e.g., be configured to determine whether or not to use coded picture buffer delay offset information for determining the access unit removal time of the current picture depending on whether or not the previous non-discardable picture which precedes the current picture within the video may, e.g., be a first picture in a previous buffering period.

30 In an embodiment, the video decoder 300 may, e.g., be configured to determine whether or not to use coded picture buffer delay offset information for determining the access unit removal time of the current picture depending on a concatenation flag, the current picture being a first picture of the input video of the second video data stream.

35 According to an embodiment, the video decoder 300 may, e.g., be configured to determine the access unit removal time of the current picture depending on a removal time of a preceding picture.

In an embodiment, the video decoder 300 may, e.g., be configured to determine the access unit removal time of the current picture depending on initial coded picture buffer removal delay information.

5 According to an embodiment, the video decoder 300 may, e.g., be configured to update the initial coded picture buffer removal delay information depending on a clock tick to obtain temporary coded picture buffer removal delay information to determine the access unit removal time of the current picture.

10 According to an embodiment, if the concatenation flag is set to a first value, then the video decoder 300 is configured to use the coded picture buffer delay offset information to determine one or more removal times. If the concatenation flag is set to a second value being different from the first value then the video decoder 300 is configured to not use the coded picture buffer delay offset information to determine the one or more removal times.

15 Furthermore, a system is provided. The system comprises an apparatus 200 as described above and a video decoder 300 as described above. The video decoder 300 is configured to receive the output video data stream of the apparatus 200. Moreover, the video decoder 300 is configured to decode the video from the output video data stream of the apparatus  
20 200.

According to an embodiment, the system may, e.g., further comprise a video encoder 100. The apparatus 200 may, e.g., be configured to receive the video data stream from the video encoder 100 as the input video data stream.

25 In particular, the second aspect of the invention relates to that `prevNonDiscardable` in case of alternative timing may (when it is not a BP start) already include the alternative offset (`CpbDelayOffset`), so for the AU with `concatenation_flag == 1`, `CpbDelayOffset` should be temporally set to zero.

30 When splicing of two bitstreams happens the derivation of the removal time of an AU from the CPB is done differently than for non-spliced bitstreams. At the splicing point a Buffering Period SEI message (BP SEI message; SEI = supplemental enhancement information) comprises a `concatenationFlag` being equal to 1. Then the decoder needs to check among  
35 2 values and take the bigger one of both:

- previous Non Discardable Pic (`prevNonDiscardablePic`) removal time plus a delta signalled in the BP SEI message (`auCpbRemovalDelayDeltaMinus1 + 1`), or
- preceding Pic removal time plus `InitCpbRemovalDelay`

5 However, when the previous Pic with a BP SEI message was an AU for which alternative timings have been used (i.e. a second timing information used when the RASL picture or pictures up to a DRAP have been dropped) for derivation of the removal times, an offset is used (`CpbDelayOffset`) to compute each removal time that computed as a delta to the previous pic with a buffering period, i.e. `AuNominalRemovalTime[`  
 10 `firstPicInPrevBuffPeriod ]` plus `AuCpbRemovalDelayVal – CpbDelayOffset`, as illustrated in Fig. 4.

Fig. 4 illustrates an original bitstream (top of Fig. 4), and a bitstream after dropping pictures (bottom of Fig. 4): An offset is incorporated into a calculation of the removal delay after  
 15 dropping AUs (lines 1, 2 and 3 in the original bitstream).

The offset is added since the removal time is computed using a delta to the removal time of the picture referred to as `firstPicInPrevBuffPeriod`, after which some AUs have been dropped and therefore a `CpbDelayOffset` is necessary to account (compensate) for the AU  
 20 dropping.

Fig. 5 illustrates the splicing of two bitstreams (at a different position), a first bitstream (in Fig. 5 middle left) and a second bitstream (in Fig. 5, middle, right), after pictures were dropped from the original first bitstream (in Fig. 5, middle, left).

The example for using the preceding Pic removal time as anchor instead of the previous non-discardable picture is similar and would not require the “-3” correction factor (`CpbDelayOffset`) neither.

25

However, in the splicing case as illustrated in Fig. 5, note that it is not necessarily the case that the two derivations use the removal time of the AU associated with a BP SEI message (`firstPicInPrevBuffPeriod`). As discussed, for the splicing case a delta added to either the `prevNonDiscardablePic` or just the preceding Pic. This means that when the  
 30 `prevNonDiscardablePic` is not the `firstPicInPrevBuffPeriod`, the `CpbDelayOffset` cannot be used to derive the removal time from the CPB of the current AU, as the removal time of

prevNonDiscardablePic already accounts for AU dropping and no AUs are dropped between prevNonDiscardablePic and the AU for which the removal time is computed. Now imagine that the preceding Pic removal time is used instead, as for the case that the current AU (i.e. the splicing point with a new BP SEI message) has an InitialCpbRemovalDelay that

5 forces the removal time of the current AU to come after its desired removal time, which would have achieved an equidistant removal time (when the prevNonDiscardablePic is used instead). In such a case, the removal time of the current AU cannot be smaller than the time computed by using the preceding Pic removal time plus InitCpbRemovalDelay as this could lead to buffer underruns (AUs not in the buffer before they need to be removed). Therefore,

10 as part of the invention, for this case the CpbDelayOffset is not used for the computation or considered to be equal to 0.

Summarizing the embodiment herein is to use a CpbDelayOffset for the computation of AU removal times when RASL AUs are dropped from a bitstream or AUs in between an IRAP and DRAP AUs are dropped depending on a check. The check to determine whether

15 CpbDelayOffset is not used or considered to be equal to 0 being one of the following:

- prevNonDiscardablePic is not the firstPicInPrevBuffPeriod
  - preceding Pic removal time plus InitCpbRemovalDelay is used for the computation of
- 20 the removal of the current AU

The implementation in the specification could be as follows:

– When AU n is the first AU of a BP that does not initialize the HRD, the following

25 applies:

The nominal removal time of the AU n from the CPB is specified by:

```

if( !concatenationFlag ) {
    baseTime = AuNominalRemovalTime[ firstPicInPrevBuffPeriod ]
    tmpCpbRemovalDelay = AuCpbRemovalDelayVal
    tmpCpbDelayOffset = CpbDelayOffset
30 } else {
    baseTime1 = AuNominalRemovalTime[ prevNonDiscardablePic ]
    tmpCpbRemovalDelay1 = ( auCpbRemovalDelayDeltaMinus1 + 1 )

```

```

baseTime2 = AuNominalRemovalTime[ n - 1 ]
tmpCpbRemovalDelay2 =
    Ceil( ( InitCpbRemovalDelay[ Htid ][ ScIdx ] ÷ 90000 +
5      AuFinalArrivalTime[ n - 1 ] - AuNominalRemovalTime[ n - 1 ] ) ÷ ClockTick )
    if( baseTime1 + ClockTick * tmpCpbRemovalDelay1 <
        baseTime2 + ClockTick * tmpCpbRemovalDelay2 ) {
        baseTime = baseTime2
        tmpCpbRemovalDelay = tmpCpbRemovalDelay2
10      tmpCpbDelayOffset = 0
    } else {
        baseTime = baseTime1
        tmpCpbRemovalDelay = tmpCpbRemovalDelay1
        tmpCpbDelayOffset = ((prevNonDiscardablePic=
15      =firstPicInPrevBuffPeriod)?CpbDelayOffset:0)
    }
}
AuNominalRemovalTime[ n ] =
    baseTime + ( ClockTick * tmpCpbRemovalDelay - tmpCpbDelayOffset
20      )

```

Alternatively, in another embodiment illustrated in Fig. 6, the CpbDelayOffset for the computation of AU removal times when RASL AUs are dropped from a bitstream or AUs in between an IRAP and DRAP AUs are dropped depending on a different check that comprises checking the concatenationFlag.

25

In that case the delta in the bitstream when concatenationFlag is set to 1 needs to match the proper value as if the CpbDelayOffset was accounted for (as evident when comparing Fig. 5 and 6), as for that figure CpbDelayOffset is not applied or considered to be 0.

30 The implementation in the specification could be as follows:

– When AU n is the first AU of a BP that does not initialize the HRD, the following applies:

The nominal removal time of the AU n from the CPB is specified by:

```

if( !concatenationFlag ) {
5   baseTime = AuNominalRemovalTime[ firstPicInPrevBuffPeriod ]
   tmpCpbRemovalDelay = AuCpbRemovalDelayVal
   tmpCpbDelayOffset = CpbDelayOffset
} else {
   baseTime1 = AuNominalRemovalTime[ prevNonDiscardablePic ]
10  tmpCpbRemovalDelay1 = ( auCpbRemovalDelayDeltaMinus1 + 1 )
   baseTime2 = AuNominalRemovalTime[ n - 1 ]
   tmpCpbRemovalDelay2 =
(C.10)      Ceil( ( InitCpbRemovalDelay[ Htid ][ ScIdx ] ÷ 90000 +
15      AuFinalArrivalTime[ n - 1 ] - AuNominalRemovalTime[ n - 1 ] ) ÷ ClockTick )
   if( baseTime1 + ClockTick * tmpCpbRemovalDelay1 <
       baseTime2 + ClockTick * tmpCpbRemovalDelay2 ) {
       baseTime = baseTime2
       tmpCpbRemovalDelay = tmpCpbRemovalDelay2
20  } else {
       baseTime = baseTime1
       tmpCpbRemovalDelay = tmpCpbRemovalDelay1
   }
   tmpCpbDelayOffset = 0
25  }
   AuNominalRemovalTime[ n ] =
   baseTime + ( ClockTick * tmpCpbRemovalDelay - tmpCpbDelayOffset

```

In the following, the third aspect of the invention is now described in detail.

30

In accordance with the third aspect of the invention, a video data stream is provided. The video data stream has a video encoded thereinto. Moreover, the video data stream comprises an initial coded picture buffer removal delay. Furthermore, the video data stream

comprises an initial coded picture buffer removal offset. Moreover, the video data stream comprises information that indicates whether or not a sum of the initial coded picture buffer removal delay and the initial coded picture buffer removal offset is defined to be constant across two or more buffering periods.

5

According to an embodiment, the initial coded picture buffer removal delay may, e.g., indicate a time that needs to pass for a first access unit of a picture of the video data stream that initializes a video decoder 300 before sending the first access unit to the video decoder 300.

10

In an embodiment, the video data stream may, e.g., comprise a single indication that may, e.g., indicate whether or not the sum of the initial coded picture buffer removal delay and the initial coded picture buffer removal offset may, e.g., be defined to be constant across the two or more buffering periods.

15

According to an embodiment, the video data stream may, e.g., comprise a concatenation flag as the single indication, that may, e.g., indicate whether or not the sum of the initial coded picture buffer removal delay and the initial coded picture buffer removal offset may, e.g., be defined to be constant across the two or more buffering periods. If the concatenation flag is equal to a first value, the sum of the initial coded picture buffer removal delay and the initial coded picture buffer removal offset is constant across the two or more buffering periods. If the concatenation flag is different from the first value, the concatenation flag does not define whether or not the sum of the initial coded picture buffer removal delay and the initial coded picture buffer removal offset is constant across the two or more buffering periods.

25

In an embodiment, if the single indication does not indicate that the sum of the initial coded picture buffer removal delay and the initial coded picture buffer removal offset is defined to be constant across the two or more buffering periods, the video data stream may, e.g., comprise continuously updated information on the initial coded picture buffer removal delay information and continuously updated information on the initial coded picture buffer removal offset information.

30

According to an embodiment, if the video data stream comprises the information that indicates that the sum of the initial coded picture buffer removal delay and the initial coded picture buffer removal offset is defined to be constant across the two or more buffering

35

periods, the sum of the initial coded picture buffer removal delay and the initial coded picture buffer removal offset may, e.g., be defined to be constant starting from a current position within the video data stream.

- 5 Furthermore, a video encoder 100 is provided. The video encoder 100 is configured to encode a video into a video data stream. Moreover, the video encoder 100 is configured to generate the video data stream such that the video data stream comprises an initial coded picture buffer removal delay. Furthermore, the video encoder 100 is configured to generate the video data stream such that the video data stream comprises an initial coded picture
- 10 buffer removal offset. Moreover, the video encoder 100 is configured to generate the video data stream such that the video data stream comprises information that indicates whether or not a sum of the initial coded picture buffer removal delay and the initial coded picture buffer removal offset is defined to be constant across two or more buffering periods.
- 15 According to an embodiment, the initial coded picture buffer removal delay may, e.g., indicate a time that needs to pass for a first access unit of a picture of the video data stream that initializes a video decoder 300 before sending the first access unit to the video decoder 300.
- 20 In an embodiment, the video encoder 100 may, e.g., be configured to generate the video data stream such that the video data stream may, e.g., comprise a single indication that may, e.g., indicate whether or not the sum of the initial coded picture buffer removal delay and the initial coded picture buffer removal offset may, e.g., be defined to be constant across the two or more buffering periods.
- 25 According to an embodiment, the video encoder 100 may, e.g., be configured to generate the video data stream such that the video data stream may, e.g., comprise a concatenation flag as the single indication, that may, e.g., indicate whether or not the sum of the initial coded picture buffer removal delay and the initial coded picture buffer removal offset may,
- 30 e.g., be defined to be constant across the two or more buffering periods. If the concatenation flag is equal to a first value, the sum of the initial coded picture buffer removal delay and the initial coded picture buffer removal offset is constant across the two or more buffering periods. If the concatenation flag is different from the first value, the concatenation flag does not define whether or not the sum of the initial coded picture buffer removal delay and the
- 35 initial coded picture buffer removal offset is constant across the two or more buffering periods.

In an embodiment, if the single indication does not indicate that the sum of the initial coded picture buffer removal delay and the initial coded picture buffer removal offset is defined to be constant across the two or more buffering periods, the video encoder 100 may, e.g., be configured to generate the video data stream such that the video data stream may, e.g., comprise continuously updated information on the initial coded picture buffer removal delay information and continuously updated information on the initial coded picture buffer removal offset information.

According to an embodiment, if the video data stream comprises the information that may, e.g., indicate that the sum of the initial coded picture buffer removal delay and the initial coded picture buffer removal offset is defined to be constant across the two or more buffering periods, the sum of the initial coded picture buffer removal delay and the initial coded picture buffer removal offset is defined to be constant starting from a current position within the video data stream.

Moreover, an apparatus 200 for receiving two input video data streams, being a first input video data stream and a second input video data stream, is provided. Each of the two input video data streams has an input video encoded thereinto. The apparatus 200 is configured to generate an output video data stream from the two input video data streams, the output video data stream encoding an output video, wherein the apparatus is configured to generate an output video data stream by concatenating the first input video data stream and the second input video data stream. Moreover, the apparatus 200 is configured to generate the output video data stream such that the output video data stream comprises an initial coded picture buffer removal delay. Furthermore, the apparatus 200 is configured to generate the output video data stream such that the output video data stream comprises an initial coded picture buffer removal offset. Moreover, the apparatus 200 is configured to generate the output video data stream such that the output video data stream comprises information that indicates whether or not a sum of the initial coded picture buffer removal delay and the initial coded picture buffer removal offset is defined to be constant across two or more buffering periods.

According to an embodiment, the initial coded picture buffer removal delay may, e.g., indicate a time that needs to pass for a first access unit of a picture of the output video data stream that initializes a video decoder 300 before sending the first access unit to the video decoder 300.

In an embodiment, the apparatus 200 may, e.g., be configured to generate the output video data stream such that the output video data stream may, e.g., comprise a single indication that may, e.g., indicate whether or not the sum of the initial coded picture buffer removal  
5 delay and the initial coded picture buffer removal offset may, e.g., be defined to be constant across the two or more buffering periods.

According to an embodiment, the apparatus 200 may, e.g., be configured to generate the output video data stream such that the output video data stream may, e.g., comprise a  
10 concatenation flag as the single indication, that may, e.g., indicate whether or not the sum of the initial coded picture buffer removal delay and the initial coded picture buffer removal offset may, e.g., be defined to be constant across the two or more buffering periods. If the concatenation flag is equal to a first value, the sum of the initial coded picture buffer removal delay and the initial coded picture buffer removal offset is constant across the two or more  
15 buffering periods. If the concatenation flag is different from the first value, the concatenation flag does not define whether or not the sum of the initial coded picture buffer removal delay and the initial coded picture buffer removal offset is constant across the two or more buffering periods.

20 In an embodiment, if the single indication does not indicate that the sum of the initial coded picture buffer removal delay and the initial coded picture buffer removal offset is defined to be constant across the two or more buffering periods, the apparatus 200 is configured to generate the output video data stream such that the output video data stream comprises continuously updated information on the initial coded picture buffer removal delay  
25 information and continuously updated information on the initial coded picture buffer removal offset information.

According to an embodiment, if the video data stream comprises the information that indicates that the sum of the initial coded picture buffer removal delay and the initial coded  
30 picture buffer removal offset is defined to be constant across the two or more buffering periods, the sum of the initial coded picture buffer removal delay and the initial coded picture buffer removal offset is defined to be constant starting from a current position within the video data stream.

35 Furthermore, a video decoder 300 for receiving a video data stream a video stored therein is provided. The video decoder 300 is configured to decode the video from the video data

stream. Moreover, the video data stream comprises an initial coded picture buffer removal delay. Furthermore, the video data stream comprises an initial coded picture buffer removal offset. Moreover, the video data stream comprises information that indicates whether or not a sum of the initial coded picture buffer removal delay and the initial coded picture buffer removal offset is defined to be constant across two or more buffering periods. Furthermore, the video decoder 300 is configured to decode the video depending on the information that indicates whether or not the sum of the initial coded picture buffer removal delay and the initial coded picture buffer removal offset is defined to be constant across the two or more buffering periods.

According to an embodiment, the initial coded picture buffer removal delay may, e.g., indicate a time that needs to pass for a first access unit of a picture of the output video data stream that initializes the video decoder 300 before sending the first access unit to the video decoder 300.

In an embodiment, the video data stream may, e.g., comprise a single indication that may, e.g., indicate whether or not the sum of the initial coded picture buffer removal delay and the initial coded picture buffer removal offset may, e.g., be defined to be constant across the two or more buffering periods. The video decoder 300 may, e.g., be configured to decode the video depending on the single indication.

According to an embodiment, the video data stream may, e.g., comprise a concatenation flag as the single indication, that may, e.g., indicate whether or not the sum of the initial coded picture buffer removal delay and the initial coded picture buffer removal offset may, e.g., be defined to be constant across the two or more buffering periods. If the concatenation flag is equal to a first value, the sum of the initial coded picture buffer removal delay and the initial coded picture buffer removal offset is constant across the two or more buffering periods. If the concatenation flag is different from the first value, the concatenation flag does not define whether or not the sum of the initial coded picture buffer removal delay and the initial coded picture buffer removal offset is constant across the two or more buffering periods. The video decoder 300 is configured to decode the video depending on the concatenation flag.

In an embodiment, if the single indication does not indicate that the sum of the initial coded picture buffer removal delay and the initial coded picture buffer removal offset is defined to be constant across the two or more buffering periods, the video data stream comprises

continuously updated information on the initial coded picture buffer removal delay information and continuously updated information on the initial coded picture buffer removal offset information. The video decoder 300 is configured to decode the video depending on the continuously updated information on the initial coded picture buffer removal delay  
5 information and on the continuously updated information on the initial coded picture buffer removal offset information.

According to an embodiment, if the video data stream comprises the information that indicates that the sum of the initial coded picture buffer removal delay and the initial coded  
10 picture buffer removal offset is defined to be constant across the two or more buffering periods, the sum of the initial coded picture buffer removal delay and the initial coded picture buffer removal offset is defined to be constant starting from a current position within the video data stream.

Moreover, a system is provided. The system comprises an apparatus 200 as described above and a video decoder 300 as described above. The video decoder 300 is configured to receive the output video data stream of the apparatus 200. Moreover, the video decoder 300 is configured to decode the video from the output video data stream of the apparatus  
15 200.

According to an embodiment, the system may, e.g., further comprise a video encoder 100. The apparatus 200 according to one of claims 221 to 226 may, e.g., be configured to receive the video data stream from the video encoder 100 according to one of claims 211 to 216 as the input video data stream.  
20

In particular, the third aspect of the invention relates to splicing, to an Initial Cpb Removal Delay and to an Initial Cpb Removal Offset  
25

Currently the specification indicates that the sum of Initial Cpb Removal Delay and Initial  
30 Cpb Removal Offset are constant within a CVS. The same constraint is expressed for the alternative timings. The Initial Cpb Removal Delay indicates the time that needs to pass for the first AU in the bitstream that initializes the decoder before sending the first AU for decoding. The Initial Cpb Removal Offset is a property of the bitstream that means that the AUs earliest arrival time in the decoder is not necessarily equidistant with respect to the  
35 time 0 at which the first AU arrive the decoder. It helps determining when the first bit of an AU can earliest reach the decoder.

The current constraint in the VVC draft specification indicates that the sum of these two values needs to be constant within a CVS:

5        Over the entire CVS, for each value pair of  $i$  and  $j$ , the sum of  $\text{nal\_initial\_cpb\_removal\_delay}[i][j]$  and  $\text{nal\_initial\_cpb\_removal\_offset}[i][j]$  shall be constant, and the sum of  $\text{nal\_initial\_alt\_cpb\_removal\_delay}[i][j]$  and  $\text{nal\_initial\_alt\_cpb\_removal\_offset}[i][j]$  shall be constant.

10      The problem appears when editing or splicing bitstreams to form a new joint bitstream. It is desirable also to be able to indicate whether this property is fulfilled across the CVS boundary for the bitstream as having a different value of the sum could lead to buffer underruns or overflows.

15      Therefore, in an embodiment an indication is carried in the bitstream that from a certain point in the bitstream on (e.g. splicing point), the value constraint regarding the constant sum of `InitCpbRemovalDelay` and `InitCpbRemovalDelayOffset` (and the alternative counterparts) is reset and the sums before and after the point in the bitstream may be different. Unless this indication is present in the bitstream the sum stays constant.

20

For instance:

When `concatenationFlag` is equal to 0, it is a constraint of bitstream conformance that the sum of `InitCpbRemovalDelay` and `InitCpbRemovalDelayOffset` is constant across buffering  
25      periods.

Otherwise, sum of `InitCpbRemovalDelay` and `InitCpbRemovalDelayOffset` does not have to be constant across buffering periods. The values of `InitCpbRemovalDelay` and `InitCpbRemovalDelayOffset` are updated to account for the arrival times.

30

In an embodiment, if several bitstreams are spliced, at each splicing point a concatenation flag may, e.g., define whether the sum stays constant or not.

In the following, the fourth aspect of the invention is now described in detail.

35

In accordance with the fourth aspect of the invention, a video data stream is provided. The video data stream has a video encoded thereinto. Moreover, the video data stream comprises an indication (e.g., a `general_same_pic_timing_in_all_ols_flag`) indicating whether or not a non-scalable nested picture timing supplemental enhancement information message of a network abstraction layer unit of an access unit of the plurality of access units of a coded video sequence of a one or more coded video sequences of the video data stream is defined to apply to all output layer sets of a plurality of output layer sets of said access unit. If the indication (e.g., a `general_same_pic_timing_in_all_ols_flag`) has a first value, then the non-scalable nested picture timing supplemental enhancement information message of said network abstraction layer unit of said access unit is defined to apply to all output layer sets of the plurality of output layer sets of said access unit. If the indication (e.g., a `general_same_pic_timing_in_all_ols_flag`) has a value being different from the first value, then the indication does not define whether or not the non-scalable nested picture timing supplemental enhancement information message of said network abstraction layer unit of said access unit applies to all output layer sets of the plurality of output layer sets of said access unit.

According to an embodiment, for example, if the indication (e.g., a `general_same_pic_timing_in_all_ols_flag`) has the first value, then said network abstraction layer unit does not comprise any other supplemental enhancement information message that is different from a picture timing supplemental enhancement information message.

In an embodiment, e.g., if the indication (e.g., a `general_same_pic_timing_in_all_ols_flag`) has the first value, then said network abstraction layer unit does not comprise any other supplemental enhancement information message.

According to an embodiment, for example, if the indication (e.g., a `general_same_pic_timing_in_all_ols_flag`) has the first value, then for each network abstraction layer unit, which comprises a non-scalable nested picture timing supplemental enhancement information message, of each access unit of the plurality of access units of a coded video sequence of the one or more coded video sequences, said network abstraction layer unit does not comprise any other supplemental enhancement information message that is different from a picture timing supplemental enhancement information message, or does not comprise any other supplemental enhancement information message.

In an embodiment, if the indication (e.g., a `general_same_pic_timing_in_all_ols_flag`) has the first value, then for each network abstraction layer unit, which comprises a non-scalable nested picture timing supplemental enhancement information message, of each access unit of the plurality of access units of each of the one or more coded video sequences of the video data stream, said network abstraction layer unit does not comprise any other supplemental enhancement information message that is different from a picture timing supplemental enhancement information message, or does not comprise any other supplemental enhancement information message.

Moreover, a video encoder 100 may, e.g., be provided. The video encoder 100 is configured to encode a video into a video data stream. Moreover, the video encoder 100 is configured to generate the video data stream such that the video data stream comprises an indication (e.g., a `general_same_pic_timing_in_all_ols_flag`) indicating whether or not a non-scalable nested picture timing supplemental enhancement information message of a network abstraction layer unit of an access unit of the plurality of access units of a coded video sequence of a one or more coded video sequences of the video data stream is defined to apply to all output layer sets of a plurality of output layer sets of said access unit. If the indication (e.g., a `general_same_pic_timing_in_all_ols_flag`) has a first value, then the non-scalable nested picture timing supplemental enhancement information message of said network abstraction layer unit of said access unit is defined to apply to all output layer sets of the plurality of output layer sets of said access unit. If the indication (e.g., a `general_same_pic_timing_in_all_ols_flag`) has a value being different from the first value, then the indication does not define whether or not the non-scalable nested picture timing supplemental enhancement information message of said network abstraction layer unit of said access unit applies to all output layer sets of the plurality of output layer sets of said access unit.

According to an embodiment, for example, if the indication (e.g., a `general_same_pic_timing_in_all_ols_flag`) has the first value, then the video encoder 100 is configured to generate the video data stream such that said network abstraction layer unit does not comprise any other supplemental enhancement information message that is different from a picture timing supplemental enhancement information message.

In an embodiment, e.g., if the indication (e.g., a `general_same_pic_timing_in_all_ols_flag`) has the first value, then the video encoder 100 is configured to generate the video data

stream such that said network abstraction layer unit does not comprise any other supplemental enhancement information message.

According to an embodiment, for example, if the indication (e.g., a  
5 `general_same_pic_timing_in_all_ols_flag`) has the first value, then the video encoder 100 may, e.g., be configured to generate the video data stream such that for each network abstraction layer unit, which comprises a non-scalable nested picture timing supplemental enhancement information message, of each access unit of the plurality of access units of a coded video sequence of the one or more coded video sequences, said network abstraction  
10 layer unit does not comprise any other supplemental enhancement information message that is different from a picture timing supplemental enhancement information message, or does not comprise any other supplemental enhancement information message.

In an embodiment, e.g., if the indication (e.g., a `general_same_pic_timing_in_all_ols_flag`)  
15 has the first value, then the video encoder 100 may, e.g., be configured to generate the video data stream such that for each network abstraction layer unit, which comprises a non-scalable nested picture timing supplemental enhancement information message, of each access unit of the plurality of access units of each of the one or more coded video sequences of the video data stream, said network abstraction layer unit does not comprise  
20 any other supplemental enhancement information message that is different from a picture timing supplemental enhancement information message, or does not comprise any other supplemental enhancement information message.

Furthermore, an apparatus 200 for receiving an input video data stream is provided. The  
25 input video data stream has a video encoded therein. The apparatus 200 is configured to generate an processed video data stream from the input video data stream. Moreover, the apparatus 200 is configured to generate the processed video data stream such that the processed video data stream comprises an indication (e.g., a  
30 `general_same_pic_timing_in_all_ols_flag`) indicating whether or not a non-scalable nested picture timing supplemental enhancement information message of a network abstraction layer unit of an access unit of the plurality of access units of a coded video sequence of a one or more coded video sequences of the processed video data stream is defined to apply to all output layer sets of a plurality of output layer sets of said access unit. If the indication  
(e.g., a `general_same_pic_timing_in_all_ols_flag`) has a first value, then the non-scalable  
35 nested picture timing supplemental enhancement information message of said network abstraction layer unit of said access unit is defined to apply to all output layer sets of the

plurality of output layer sets of said access unit. If the indication (e.g., a `general_same_pic_timing_in_all_ols_flag`) has a value being different from the first value, then the indication does not define whether or not the non-scalable nested picture timing supplemental enhancement information message of said network abstraction layer unit of  
5 said access unit applies to all output layer sets of the plurality of output layer sets of said access unit.

According to an embodiment, for example, if the indication (e.g., a `general_same_pic_timing_in_all_ols_flag`) has the first value, then the apparatus 200 is  
10 configured to generate the processed video data stream such that said network abstraction layer unit does not comprise any other supplemental enhancement information message that is different from a picture timing supplemental enhancement information message.

In an embodiment, e.g., if the indication (e.g., a `general_same_pic_timing_in_all_ols_flag`)  
15 has the first value, then the apparatus 200 is configured to generate the processed video data stream such that said network abstraction layer unit does not comprise any other supplemental enhancement information message.

According to an embodiment, for example, if the indication (e.g., a `general_same_pic_timing_in_all_ols_flag`) has the first value, then the apparatus 200 may,  
20 e.g., be configured to generate the processed video data stream such that for each network abstraction layer unit, which comprises a non-scalable nested picture timing supplemental enhancement information message, of each access unit of the plurality of access units of a coded video sequence of the one or more coded video sequences, said network abstraction  
25 layer unit does not comprise any other supplemental enhancement information message that is different from a picture timing supplemental enhancement information message, or does not comprise any other supplemental enhancement information message.

In an embodiment, e.g., if the indication (e.g., a `general_same_pic_timing_in_all_ols_flag`)  
30 has the first value, then the apparatus 200 may, e.g., be configured to generate the processed video data stream such that for each network abstraction layer unit, which comprises a non-scalable nested picture timing supplemental enhancement information message, of each access unit of the plurality of access units of each of the one or more coded video sequences of the processed video data stream, said network abstraction layer  
35 unit does not comprise any other supplemental enhancement information message that is

different from a picture timing supplemental enhancement information message, or does not comprise any other supplemental enhancement information message.

Moreover, a video decoder 300 for receiving a video data stream having a video stored  
5 therein is provided. The video decoder 300 is configured to decode the video from the video data stream. The video data stream comprises an indication (e.g., a `general_same_pic_timing_in_all_ols_flag`) indicating whether or not a non-scalable nested picture timing supplemental enhancement information message of a network abstraction layer unit of an access unit of the plurality of access units of a coded video sequence of a  
10 one or more coded video sequences of the video data stream is defined to apply to all output layer sets of a plurality of output layer sets of said access unit. If the indication (e.g., a `general_same_pic_timing_in_all_ols_flag`) has a first value, then the non-scalable nested picture timing supplemental enhancement information message of said network abstraction layer unit of said access unit is defined to apply to all output layer sets of the plurality of  
15 output layer sets of said access unit. If the indication (e.g., a `general_same_pic_timing_in_all_ols_flag`) has a value being different from the first value, then the indication does not define whether or not the non-scalable nested picture timing supplemental enhancement information message of said network abstraction layer unit of said access unit applies to all output layer sets of the plurality of output layer sets of said  
20 access unit. The video decoder 300 is configured to decode the video depending on said indication.

According to an embodiment, for example, if the indication (e.g., a `general_same_pic_timing_in_all_ols_flag`) has the first value, then said network abstraction  
25 layer unit does not comprise any other supplemental enhancement information message that is different from a picture timing supplemental enhancement information message.

In an embodiment, e.g., if the indication (e.g., a `general_same_pic_timing_in_all_ols_flag`) has the first value, then said network abstraction layer unit does not comprise any other  
30 supplemental enhancement information message. The video decoder 300 is configured to decode the video depending on said indication.

According to an embodiment, for example, if the indication (e.g., a `general_same_pic_timing_in_all_ols_flag`) has the first value, then for each network  
35 abstraction layer unit, which comprises a non-scalable nested picture timing supplemental

enhancement information message, of each access unit of the plurality of access units of a coded video sequence of the one or more coded video sequences, said network abstraction layer unit does not comprise any other supplemental enhancement information message that is different from a picture timing supplemental enhancement information message, or  
5 does not comprise any other supplemental enhancement information message.

In an embodiment, e.g., if the indication (e.g., a `general_same_pic_timing_in_all_ols_flag`) has the first value, then for each network abstraction layer unit, which comprises a non-scalable nested picture timing supplemental enhancement information message, of each  
10 access unit of the plurality of access units of each of the one or more coded video sequences of the video data stream, said network abstraction layer unit does not comprise any other supplemental enhancement information message that is different from a picture timing supplemental enhancement information message, or does not comprise any other supplemental enhancement information message.

15 Furthermore, a system is provided. The system comprises an apparatus 200 as described above and a video decoder 300 as described above. The video decoder 300 is configured to receive the processed video data stream of the apparatus 200. Moreover, the video decoder 300 is configured to decode the video from the output video data stream of the  
20 apparatus 200.

According to an embodiment, the system may, e.g., further comprise a video encoder 100. The apparatus 200 may, e.g., be configured to receive the video data stream from the video encoder 100 as the input video data stream.

25 In particular, the fourth aspect of the invention relates to constraining PT SEI to not be paired with other HRD SEIs when `general_same_pic_timing_in_all_ols_flag` equal to 1

The VVC draft specification comprises a flag called  
30 `general_same_pic_timing_in_all_ols_flag` in the general HRD parameter structure which the following semantics:

general\_same\_pic\_timing\_in\_all\_ols\_flag equal to 1 specifies that the non-scalable-nested PT SEI message in each AU applies to the AU for any OLS in the bitstream  
35 and no scalable-nested PT SEI messages are present.

general\_same\_pic\_timing\_in\_all\_ols\_flag equal to 0 specifies that the non-scalable-nested PT SEI message in each AU may or may not apply to the AU for any OLS in the bitstream and scalable-nested PT SEI messages may be present.

5 In general, when an OLS sub-bitstream is extracted from an original bitstream (comprises OLS data plus non-OLS data), corresponding HRD-related timing/buffer information for the target OLS in the form of Buffering Period, Picture Timing and Decoding Unit Information SEI messages which are encapsulated in so called scalable-nesting SEI messages are decapsulated. This decapsulated SEI messages are subsequently used to replace the non-  
10 scalable nested HRD SEI information in the original bitstream. However, in many scenarios, the content of some messages, e.g. the Picture Timing SEI message, may remain the same when a layer is dropped, i.e. from one OLS to a sub-set thereof. Therefore, general\_same\_pic\_timing\_in\_all\_ols\_flag provides a shortcut so that only BP and DUI SEI messages are to be replaced, but the PT SEI in the original bitstream may stay in effect,  
15 i.e. it is simply not removed during extraction when general\_same\_pic\_timing\_in\_all\_ols\_flag is equal to 1. Therefore, no replacement PT SEI message needs to be encapsulated in the scalable-nesting SEI message carrying the replacement BP and DUI SEI messages and no bitrate overhead is introduced for this information.

20 However, in the state-of-the-art, the PT SEI message is allowed to be carried within one SEI NAL unit (NAL unit = network abstraction layer unit) jointly with other HRD SEI messages, i.e. BP, PT and SEI messages may all be encapsulated within the same Prefix SEI NAL unit. Hence, an extractor would have to do a deeper inspection of such an SEI  
25 NAL unit to understand the comprised messages and when only one of the comprised messages (PT) is to be kept during the extraction procedure, it would be required to practically re-write the show SEI NAL units (i.e. remove non-PT SEI messages). In order to avoid this cumbersome low-level processing and allow an extractor to operate on the non-parameter-set portion of a bitstream entirely on the NAL unit level, it is part of the invention  
30 that a bitstream constraint disallows such bitstream construction. In one embodiment, the constraint is phrased as follows:

35 general\_same\_pic\_timing\_in\_all\_ols\_flag equal to 1 specifies that the non-scalable-nested PT SEI message in each AU applies to the AU for any OLS in the bitstream and no scalable-nested PT SEI messages are present.

general\_same\_pic\_timing\_in\_all\_ols\_flag equal to 0 specifies that the non-scalable-nested PT SEI message in each AU may or may not apply to the AU for any OLS in the bitstream and scalable-nested PT SEI messages may be present. When  
5 general\_same\_pic\_timing\_in\_all\_ols\_flag equal to 1, it is a constraint of bitstream conformance that all general SEI messages in the bitstream containing an SEI message with payload\_type equal to 1 (Picture Timing ) shall not contain SEI messages with payload\_type unequal to 1.

In the following, the fifth aspect of the invention is now described in detail.

10

In accordance with the fifth aspect of the invention, a video data stream is provided. The video data stream has a video encoded thereinto. Moreover, the video data stream comprises one or more scalable nested supplemental enhancement information messages. The one or more scalable nested supplemental enhancement information messages  
15 comprise a plurality of syntax elements. Each syntax element of one or more syntax elements of the plurality of syntax elements is defined to have a same size in every one of the scalable nested supplemental enhancement information messages of the video data stream or of a portion of the video data stream.

20

According to an embodiment, the video data stream may, e.g., comprise one or more non-scalable nested supplemental enhancement information messages. The one or more scalable nested supplemental enhancement information messages and the one or more non-scalable nested supplemental enhancement information message comprise the plurality of syntax elements. Each syntax element of the one or more syntax elements of  
25 the plurality of syntax elements is defined to have the same size in every one of the scalable nested supplemental enhancement information messages of the video data stream or of the portion of the video data stream and in every one of the non-scalable nested supplemental enhancement information messages of the video data stream or of the portion of the video data stream.

30

In an embodiment, the video data stream may, e.g., comprise a plurality of access units, wherein each access unit of the plurality of access units may, e.g., be assigned to one of a plurality of pictures of the video. The portion of the video data stream may, e.g., be an access unit of the plurality of access units of the video data stream. Each syntax element  
35 of the one or more syntax elements of the plurality of syntax elements may, e.g., be defined

to have the same size in every one of the scalable nested supplemental enhancement information messages of the access unit.

5 According to an embodiment, the video data stream may, e.g., comprise one or more non-  
scalable nested supplemental enhancement information messages. The one or more  
scalable nested supplemental enhancement information messages and the one or more  
non-scalable nested supplemental enhancement information message comprise the  
plurality of syntax elements. Each syntax element of the one or more syntax elements of  
10 the plurality of syntax elements may, e.g., be defined to have the same size in every one of  
the scalable nested supplemental enhancement information messages of the access unit  
and in every one of the non-scalable nested supplemental enhancement information  
messages of the access unit.

15 In an embodiment, the portion of the video data stream may, e.g., be a coded video  
sequence of the video data stream. Each syntax element of the one or more syntax  
elements of the plurality of syntax elements may, e.g., be defined to have the same size in  
every one of the scalable nested supplemental enhancement information messages of the  
coded video sequence.

20 According to an embodiment, the video data stream may, e.g., comprise one or more non-  
scalable nested supplemental enhancement information messages. The one or more  
scalable nested supplemental enhancement information messages and the one or more  
non-scalable nested supplemental enhancement information message comprise the  
plurality of syntax elements. Each syntax element of the one or more syntax elements of  
25 the plurality of syntax elements may, e.g., be defined to have the same size in every one of  
the scalable nested supplemental enhancement information messages of the coded video  
sequence and in every one of the non-scalable nested supplemental enhancement  
information messages of the coded video sequence.

30 In an embodiment, each syntax element of the one or more syntax elements of the plurality  
of syntax elements may, e.g., be defined to have the same size in every one of the scalable  
nested supplemental enhancement information messages of the video data stream.

35 According to an embodiment, each syntax element of the one or more syntax elements of  
the plurality of syntax elements may, e.g., be defined to have the same size in every one of  
the scalable nested supplemental enhancement information messages of the video data

stream and in every one of the non-scalable nested supplemental enhancement information messages of the video data stream.

5 In an embodiment, the video data stream or the portion of the video data stream may, e.g., comprise at least one buffering period supplemental enhancement information message, wherein said buffering period supplemental enhancement information message defines the size for each syntax element of the one or more syntax elements of the plurality of syntax elements.

10 According to an embodiment, said buffering period supplemental enhancement information message comprises, for defining the size for each syntax element of the one or more syntax elements of the plurality of syntax elements, at least one of

15 a bp\_cpb\_initial\_removal\_delay\_length\_minus1 element,

a bp\_cpb\_removal\_delay\_length\_minus1 element,

a bp\_dpb\_output\_delay\_length\_minus1 element,

20 a bp\_du\_cpb\_removal\_delay\_increment\_length\_minus1 element,

a bp\_dpb\_output\_delay\_du\_length\_minus1 element.

25 In an embodiment, for each access unit of a plurality of access units of the video data stream, which comprises a scalable-nested buffering period supplemental enhancement information message, said access unit may, e.g., also comprise a non-scalable-nested buffering period supplemental enhancement information message.

30 According to an embodiment, for each single-layer access unit of a plurality of single-layer access units of the video data stream, which comprises a scalable-nested buffering period supplemental enhancement information message, said single-layer access unit may, e.g., also comprise a non-scalable-nested buffering period supplemental enhancement information message.

35 Moreover, a video encoder 100 is provided. The video encoder 100 is configured to encode a video into a video data stream. Moreover, the video encoder 100 is configured to generate

the video data stream such that the video data stream comprises one or more scalable nested supplemental enhancement information messages. Furthermore, the video encoder 100 is configured to generate the video data stream such that the one or more scalable nested supplemental enhancement information messages comprise a plurality of syntax elements. Moreover, the video encoder 100 is configured to generate the video data stream such that each syntax element of one or more syntax elements of the plurality of syntax elements is defined to have a same size in every one of the scalable nested supplemental enhancement information messages of the video data stream or of a portion of the video data stream.

According to an embodiment, the video encoder 100 may, e.g., be configured to generate the video data stream such that the video data stream may, e.g., comprise one or more non-scalable nested supplemental enhancement information messages. The video encoder 100 may, e.g., be configured to generate the video data stream such that the one or more scalable nested supplemental enhancement information messages and the one or more non-scalable nested supplemental enhancement information message comprise the plurality of syntax elements. The video encoder 100 may, e.g., be configured to generate the video data stream such that each syntax element of the one or more syntax elements of the plurality of syntax elements may, e.g., be defined to have the same size in every one of the scalable nested supplemental enhancement information messages of the video data stream or of the portion of the video data stream and in every one of the non-scalable nested supplemental enhancement information messages of the video data stream or of the portion of the video data stream.

In an embodiment, the video encoder 100 may, e.g., be configured to generate the video data stream such that the video data stream may, e.g., comprise a plurality of access units, wherein each access unit of the plurality of access units may, e.g., be assigned to one of a plurality of pictures of the video. The portion of the video data stream may, e.g., be an access unit of the plurality of access units of the video data stream. The video encoder 100 may, e.g., be configured to generate the video data stream such that each syntax element of the one or more syntax elements of the plurality of syntax elements may, e.g., be defined to have the same size in every one of the scalable nested supplemental enhancement information messages of the access unit.

According to an embodiment, the video encoder 100 may, e.g., be configured to generate the video data stream such that the video data stream may, e.g., comprise one or more

non-scalable nested supplemental enhancement information messages. The video encoder 100 may, e.g., be configured to generate the video data stream such that the one or more scalable nested supplemental enhancement information messages and the one or more non-scalable nested supplemental enhancement information message comprise the plurality of syntax elements. The video encoder 100 may, e.g., be configured to generate the video data stream such that each syntax element of the one or more syntax elements of the plurality of syntax elements may, e.g., be defined to have the same size in every one of the scalable nested supplemental enhancement information messages of the access unit and in every one of the non-scalable nested supplemental enhancement information messages of the access unit.

In an embodiment, the portion of the video data stream may, e.g., be a coded video sequence of the video data stream. The video encoder 100 may, e.g., be configured to generate the video data stream such that each syntax element of the one or more syntax elements of the plurality of syntax elements may, e.g., be defined to have the same size in every one of the scalable nested supplemental enhancement information messages of the coded video sequence.

According to an embodiment, the video encoder 100 may, e.g., be configured to generate the video data stream such that the video data stream may, e.g., comprise one or more non-scalable nested supplemental enhancement information messages. The video encoder 100 may, e.g., be configured to generate the video data stream such that the one or more scalable nested supplemental enhancement information messages and the one or more non-scalable nested supplemental enhancement information message comprise the plurality of syntax elements. The video encoder 100 may, e.g., be configured to generate the video data stream such that each syntax element of the one or more syntax elements of the plurality of syntax elements may, e.g., be defined to have the same size in every one of the scalable nested supplemental enhancement information messages of the coded video sequence and in every one of the non-scalable nested supplemental enhancement information messages of the coded video sequence.

In an embodiment, the video encoder 100 may, e.g., be configured to generate the video data stream such that each syntax element of the one or more syntax elements of the plurality of syntax elements may, e.g., be defined to have the same size in every one of the scalable nested supplemental enhancement information messages of the video data stream.

According to an embodiment, the video encoder 100 may, e.g., be configured to generate the video data stream such that each syntax element of the one or more syntax elements of the plurality of syntax elements may, e.g., be defined to have the same size in every one  
5 of the scalable nested supplemental enhancement information messages of the video data stream and in every one of the non-scalable nested supplemental enhancement information messages of the video data stream.

In an embodiment, the video encoder 100 may, e.g., be configured to generate the video  
10 data stream such that the video data stream or the portion of the video data stream may, e.g., comprise at least one buffering period supplemental enhancement information message, wherein said buffering period supplemental enhancement information message defines the size for each syntax element of the one or more syntax elements of the plurality of syntax elements.

15 According to an embodiment, the video encoder 100 may, e.g., be configured to generate the video data stream such that said buffering period supplemental enhancement information message comprises, for defining the size for each syntax element of the one or more syntax elements of the plurality of syntax elements, at least one of

- 20
- a bp\_cpb\_initial\_removal\_delay\_length\_minus1 element,
  - a bp\_cpb\_removal\_delay\_length\_minus1 element,
  - 25 a bp\_dpb\_output\_delay\_length\_minus1 element,
  - a bp\_du\_cpb\_removal\_delay\_increment\_length\_minus1 element,
  - a bp\_dpb\_output\_delay\_du\_length\_minus1 element.

30 In an embodiment, the video encoder 100 may, e.g., be configured to generate the video data stream such that for each access unit of a plurality of access units of the video data stream, which comprises a scalable-nested buffering period supplemental enhancement information message, said access unit may, e.g., also comprise a non-scalable-nested  
35 buffering period supplemental enhancement information message.

According to an embodiment, the video encoder 100 may, e.g., be configured to generate the video data stream such that for each single-layer access unit of a plurality of single-layer access units of the video data stream, which comprises a scalable-nested buffering period supplemental enhancement information message, said single-layer access unit may, e.g., also comprise a non-scalable-nested buffering period supplemental enhancement information message.

Furthermore, an apparatus 200 for receiving an input video data stream is provided. The input video data stream has a video encoded therein. The apparatus 200 is configured to generate an output video data stream from the input video data stream. The video data stream comprises one or more scalable nested supplemental enhancement information messages. The one or more scalable nested supplemental enhancement information messages comprise a plurality of syntax elements. Each syntax element of one or more syntax elements of the plurality of syntax elements is defined to have a same size in every one of the scalable nested supplemental enhancement information messages of the video data stream or of a portion of the video data stream. The apparatus 200 is configured to process the one or more scalable nested supplemental enhancement information messages.

According to an embodiment, the video data stream may, e.g., comprise one or more non-scalable nested supplemental enhancement information messages. The one or more scalable nested supplemental enhancement information messages and the one or more non-scalable nested supplemental enhancement information message comprise the plurality of syntax elements. Each syntax element of the one or more syntax elements of the plurality of syntax elements is defined to have the same size in every one of the scalable nested supplemental enhancement information messages of the video data stream or of the portion of the video data stream and in every one of the non-scalable nested supplemental enhancement information messages of the video data stream or of the portion of the video data stream. The apparatus 200 is configured to process the one or more scalable nested supplemental enhancement information messages and the one or more non-scalable nested supplemental enhancement information messages.

In an embodiment, the video data stream may, e.g., comprise a plurality of access units, wherein each access unit of the plurality of access units may, e.g., be assigned to one of a plurality of pictures of the video. The portion of the video data stream may, e.g., be an access unit of the plurality of access units of the video data stream. Each syntax element

of the one or more syntax elements of the plurality of syntax elements may, e.g., be defined to have the same size in every one of the scalable nested supplemental enhancement information messages of the access unit.

- 5 According to an embodiment, the video data stream may, e.g., comprise one or more non-scalable nested supplemental enhancement information messages. The one or more scalable nested supplemental enhancement information messages and the one or more non-scalable nested supplemental enhancement information message comprise the plurality of syntax elements. Each syntax element of the one or more syntax elements of  
10 the plurality of syntax elements may, e.g., be defined to have the same size in every one of the scalable nested supplemental enhancement information messages of the access unit and in every one of the non-scalable nested supplemental enhancement information messages of the access unit. The apparatus 200 may, e.g., be configured to process the one or more scalable nested supplemental enhancement information messages and the  
15 one or more non-scalable nested supplemental enhancement information messages.

- In an embodiment, the portion of the video data stream may, e.g., be a coded video sequence of the video data stream. Each syntax element of the one or more syntax elements of the plurality of syntax elements may, e.g., be defined to have the same size in  
20 every one of the scalable nested supplemental enhancement information messages of the coded video sequence.

- According to an embodiment, the video data stream may, e.g., comprise one or more non-scalable nested supplemental enhancement information messages. The one or more  
25 scalable nested supplemental enhancement information messages and the one or more non-scalable nested supplemental enhancement information message comprise the plurality of syntax elements. Each syntax element of the one or more syntax elements of the plurality of syntax elements may, e.g., be defined to have the same size in every one of the scalable nested supplemental enhancement information messages of the coded video  
30 sequence and in every one of the non-scalable nested supplemental enhancement information messages of the coded video sequence. The apparatus 200 may, e.g., be configured to process the one or more scalable nested supplemental enhancement information messages and the one or more non-scalable nested supplemental enhancement information messages.

In an embodiment, each syntax element of the one or more syntax elements of the plurality of syntax elements may, e.g., be defined to have the same size in every one of the scalable nested supplemental enhancement information messages of the video data stream.

- 5 According to an embodiment, each syntax element of the one or more syntax elements of the plurality of syntax elements may, e.g., be defined to have the same size in every one of the scalable nested supplemental enhancement information messages of the video data stream and in every one of the non-scalable nested supplemental enhancement information messages of the video data stream. The apparatus 200 may, e.g., be configured  
10 to process the one or more scalable nested supplemental enhancement information messages and the one or more non-scalable nested supplemental enhancement information messages.

- In an embodiment, the video data stream or the portion of the video data stream may, e.g.,  
15 comprise at least one buffering period supplemental enhancement information message, wherein said buffering period supplemental enhancement information message defines the size of the one or more of the plurality of syntax elements. The apparatus 200 may, e.g., be configured to process the at least one buffering period supplemental enhancement information message.

- 20 According to an embodiment, said buffering period supplemental enhancement information message comprises, for defining the size of the one or more of the plurality of syntax elements, at least one of

- 25 a bp\_cpb\_initial\_removal\_delay\_length\_minus1 element,  
  
a bp\_cpb\_removal\_delay\_length\_minus1 element,  
  
a bp\_dpb\_output\_delay\_length\_minus1 element,  
30 a bp\_du\_cpb\_removal\_delay\_increment\_length\_minus1 element,  
  
a bp\_dpb\_output\_delay\_du\_length\_minus1 element.

- 35 In an embodiment, for each access unit of a plurality of access units of the video data stream, which comprises a scalable-nested buffering period supplemental enhancement

information message, said access unit may, e.g., also comprise a non-scalable-nested buffering period supplemental enhancement information message. The apparatus 200 may, e.g., be configured to process the scalable nested supplemental enhancement information messages and the non-scalable nested supplemental enhancement information messages.

5

According to an embodiment, for each single-layer access unit of a plurality of single-layer access units of the video data stream, which comprises a scalable-nested buffering period supplemental enhancement information message, said single-layer access unit may, e.g., also comprise a non-scalable-nested buffering period supplemental enhancement information message. The apparatus 200 may, e.g., be configured to process the scalable nested supplemental enhancement information messages and the non-scalable nested supplemental enhancement information messages.

10

Moreover, a video decoder 300 for receiving a video data stream having a video stored therein is provided. The video decoder 300 is configured to decode the video from the video data stream. The video data stream comprises one or more scalable nested supplemental enhancement information messages. The one or more scalable nested supplemental enhancement information messages comprise a plurality of syntax elements. Each syntax element of one or more syntax elements of the plurality of syntax elements is defined to have a same size in every one of the scalable nested supplemental enhancement information messages of the video data stream or of a portion of the video data stream. The video decoder 300 is configured to decode the video depending on the one or more syntax elements of the plurality of syntax elements.

15

20

According to an embodiment, the video data stream may, e.g., comprise one or more non-scalable nested supplemental enhancement information messages. The one or more scalable nested supplemental enhancement information messages and the one or more non-scalable nested supplemental enhancement information message comprise the plurality of syntax elements. Each syntax element of the one or more syntax elements of the plurality of syntax elements may, e.g., be defined to have the same size in every one of the scalable nested supplemental enhancement information messages of the video data stream or of the portion of the video data stream and in every one of the non-scalable nested supplemental enhancement information messages of the video data stream or of the portion of the video data stream.

30

35

In an embodiment, the video data stream may, e.g., comprise a plurality of access units, wherein each access unit of the plurality of access units may, e.g., be assigned to one of a plurality of pictures of the video. The portion of the video data stream may, e.g., be an access unit of the plurality of access units of the video data stream. Each syntax element  
5 of the one or more syntax elements of the plurality of syntax elements may, e.g., be defined to have the same size in every one of the scalable nested supplemental enhancement information messages of the access unit.

According to an embodiment, the video data stream may, e.g., comprise one or more non-  
10 scalable nested supplemental enhancement information messages. The one or more scalable nested supplemental enhancement information messages and the one or more non-scalable nested supplemental enhancement information message comprise the plurality of syntax elements. Each syntax element of the one or more syntax elements of the plurality of syntax elements may, e.g., be defined to have the same size in every one of  
15 the scalable nested supplemental enhancement information messages of the access unit and in every one of the non-scalable nested supplemental enhancement information messages of the access unit.

In an embodiment, the portion of the video data stream may, e.g., be a coded video  
20 sequence of the video data stream. Each syntax element of the one or more syntax elements of the plurality of syntax elements may, e.g., be defined to have the same size in every one of the scalable nested supplemental enhancement information messages of the coded video sequence.

According to an embodiment, the video data stream may, e.g., comprise one or more non-  
25 scalable nested supplemental enhancement information messages. The one or more scalable nested supplemental enhancement information messages and the one or more non-scalable nested supplemental enhancement information message comprise the plurality of syntax elements. Each syntax element of the one or more syntax elements of  
30 the plurality of syntax elements may, e.g., be defined to have the same size in every one of the scalable nested supplemental enhancement information messages of the coded video sequence and in every one of the non-scalable nested supplemental enhancement information messages of the coded video sequence.

In an embodiment, each syntax element of the one or more syntax elements of the plurality of syntax elements may, e.g., be defined to have the same size in every one of the scalable nested supplemental enhancement information messages of the video data stream.

- 5 According to an embodiment, each syntax element of the one or more syntax elements of the plurality of syntax elements may, e.g., be defined to have the same size in every one of the scalable nested supplemental enhancement information messages of the video data stream and in every one of the non-scalable nested supplemental enhancement information messages of the video data stream.

10

In an embodiment, the video data stream or the portion of the video data stream may, e.g., comprise at least one buffering period supplemental enhancement information message, wherein said buffering period supplemental enhancement information message defines the size for each syntax element of the one or more syntax elements of the plurality of syntax

15

elements.

According to an embodiment, said buffering period supplemental enhancement information message comprises, for defining the size for each syntax element of the one or more syntax elements of the plurality of syntax elements, at least one of

20

a bp\_cpb\_initial\_removal\_delay\_length\_minus1 element,

a bp\_cpb\_removal\_delay\_length\_minus1 element,

- 25 a bp\_dpb\_output\_delay\_length\_minus1 element,

a bp\_du\_cpb\_removal\_delay\_increment\_length\_minus1 element,

a bp\_dpb\_output\_delay\_du\_length\_minus1 element.

30

In an embodiment, for each access unit of a plurality of access units of the video data stream, which comprises a scalable-nested buffering period supplemental enhancement information message, said access unit may, e.g., also comprise a non-scalable-nested buffering period supplemental enhancement information message.

35

According to an embodiment, for each single-layer access unit of a plurality of single-layer access units of the video data stream, which comprises a scalable-nested buffering period supplemental enhancement information message, said single-layer access unit may, e.g., also comprise a non-scalable-nested buffering period supplemental enhancement  
5 information message.

Furthermore, a system is provided. The system comprises an apparatus 200 as described above and a video decoder 300 as described above. The video decoder 300 is configured to receive the output video data stream of the apparatus 200. Moreover, the video decoder  
10 300 configured to decode the video from the output video data stream of the apparatus 200.

According to an embodiment, the system may, e.g., further comprise a video encoder 100. The apparatus 200 may, e.g., be configured to receive the video data stream from the video encoder 100 as the input video data stream.  
15

In particular, the fifth aspect of the invention relates to constraining all BP SEIs messages in a bitstream to indicate the same length of certain variable-length coded syntax elements and not be scalable-nested without a non-scalable nested variant in the same AU

20 The buffering period SEI message, the picture timing SEI message and the decoding unit information SEI message are used to provide precise timing information for the NAL units within a bitstream to control their transition through the buffers of a decoder in conformance tests. Some syntax elements in the PT and DUI SEI message are coded with variable length and the length of these syntax elements is conveyed in the BP SEI message. This parsing  
25 dependency is a design trade-off. For the cost of not allowing PT and DUI SEI message parsing without parsing the associated BP SEI message first, the benefit of saving sending of those length syntax elements at each PT or DUI SEI message is achieved. As the BP SEI message (once per multiple frames) is send much less often than PT (once per each frame) or DUI SEI messages (multiple times per frame), a bit-saving is achieved through  
30 this common design trade-off similar as to how picture header structures can reduce the bit-cost of slice headers when many slices are used.

More specifically, the BP SEI message in the current VVC draft specification includes the syntax elements that are the root of parsing dependencies:  
35

- **bp\_cpb\_initial\_removal\_delay\_length\_minus1** that specifies the coded length of alternative timing initial CPB removal delays of AUs in the PT SEI message and,
- **bp\_cpb\_removal\_delay\_length\_minus1** that specifies the coded length of CPB removal delays and removal delay offsets of AUs in the PT SEI message and,
- 5   • **bp\_dpb\_output\_delay\_length\_minus1** that specifies the coded length of DPB output delays of AUs in the PT SEI message and,
- **bp\_du\_cpb\_removal\_delay\_increment\_length\_minus1** that specifies the coded length of the individual and common CPB removal delays of DUs in the PT SEI message and the CPB removal delays of DUs in the DUI SEI message and,
- 10   • **bp\_dpb\_output\_delay\_du\_length\_minus1** that specifies the coded length DPB output delays of AUs in the PT SEI message and in the DU SEI message.

However, a problem arises when a bitstream comprises multiple OLSs. While the BP/PT/DUI SEI messages that apply to the OLS that represents the bitstream are carried in a verbatim fashion in the bitstream are keeping track of the parsing dependency is trivial, other pairs of BP/PT/DUI SEI messages that correspond to the OLSs representing (sub-)bitstreams are to be carried in an encapsulated form in so-called scalable nesting SEI messages. Still, the parsing dependencies apply and given that the number of OLS might be very high, it is a considerable burden for a decoder or parser to keep track of the correct encapsulated BP SEI message for the sake of the parsing dependency when processing the encapsulated PT and DUI SEI messages. Especially, since those messages can also be encapsulated in different scalable nesting SEI messages.

Therefore, as part of the invention, in one embodiment, a bitstream constraint is established that the coded value of the respective syntax elements describing the lengths must be the same in all scalable-nested and non-scalable nested BP SEI messages in an AU. Therefore, a decoder or parser only needs to store the respective length values when parsing the first non-scalable BP SEI message in the AU and can resolve the parsing dependencies of all PT and DUI SEI message in the buffering periods that start at the respective AU, whether encapsulated in scalable-nesting SEI messages or not. The following is an example of the respective specification text:

It is a requirement of bitstream conformance that all scalable-nested and non-scalable nested buffering period SEI messages in an AU have the same respective value of

the syntax elements bp\_cpb\_initial\_removal\_delay\_length\_minus1,  
 bp\_cpb\_removal\_delay\_length\_minus1, bp\_dpb\_output\_delay\_length\_minus1,  
 bp\_du\_cpb\_removal\_delay\_increment\_length\_minus1,  
 bp\_dpb\_output\_delay\_du\_length\_minus1.

5

In another embodiment, the constraint is expressed only for scalable-nested BP SEI messages that are in the buffering period that the current non-scalable-nested BP SEI message determine as follows:

10

It is a requirement of bitstream conformance that all scalable nested buffering period SEI messages in a buffering period have the same respective value of the syntax elements bp\_cpb\_initial\_removal\_delay\_length\_minus1,  
 bp\_cpb\_removal\_delay\_length\_minus1, bp\_dpb\_output\_delay\_length\_minus1,  
 bp\_du\_cpb\_removal\_delay\_increment\_length\_minus1,

15

bp\_dpb\_output\_delay\_du\_length\_minus1 then the non-scalable nested buffering period SEI messages of the buffering period.

Here, the BPs of the bitstream define the scope of the constraints for the scalable-nested BPs from one scalable nested BP to the next scalable nested BP.

20

In another embodiment, the constraint is expressed for all AUs of the bitstream, e.g. as follows:

25

It is a requirement of bitstream conformance that all scalable-nested and non-scalable nested buffering period SEI messages in the bitstream have the same respective value of the syntax elements bp\_cpb\_initial\_removal\_delay\_length\_minus1,  
 bp\_cpb\_removal\_delay\_length\_minus1, bp\_dpb\_output\_delay\_length\_minus1,  
 bp\_du\_cpb\_removal\_delay\_increment\_length\_minus1,  
 bp\_dpb\_output\_delay\_du\_length\_minus1.

30

In another embodiment, the constraint is expressed only for the AUs in a CVS, so a smart encoder may still be able to facilitate the difference in duration of BPs in the bitstream for the coding of the relevant delay and offset syntax elements. Specification text would be as follows:

It is a requirement of bitstream conformance that all scalable-nested and non-scalable nested buffering period SEI messages in a CVS have the same respective value of the syntax elements `bp_cpb_initial_removal_delay_length_minus1`,  
5 `bp_cpb_removal_delay_length_minus1`, `bp_dpb_output_delay_length_minus1`,  
`bp_du_cpb_removal_delay_increment_length_minus1`,  
`bp_dpb_output_delay_du_length_minus1`.

Here, the constraint scope is the CVS.

10

More specifically, the buffering period or BP SEI message defines a so-called buffering period in which timings of individual pictures use the picture at the start of a buffering period as an anchor. The beginning of a buffering period is instrumental, for instance, to test conformance of random-access functionality in a bitstream.

15

Fig. 7 illustrates two sets of HRD SEIs, scalable nested SEIs and non-scalable nested SEIs, in a two-layer bitstream according to an embodiment.

In a multi-layer scenario as shown in Fig. 7, for instance, the scalable-nested HRD SEIs provide a different buffering period setup (through the BP at POC 0 and POC 3) than the non-scalable nested SEIs (only POC 0) to be used when only layer L0 is extracted and played from POC3 onwards.

20

However, this also comes at the increased complexity cost of tracking the parsing dependencies between the PT and the individual BP messages as explained above which is undesirable. Therefore, as part of the invention, in one embodiment, it is prohibited to have scalable-nested BP SEI message in AUs without a non-scalable nested BP SEI message as follows:

25

It is a requirement of bitstream conformance that no scalable-nested BP SEI message shall be in an AU that does not contain a non-scalable-nested BP SEI message.

30

As the above usage scenario is limited to multi-layer bitstreams, in another embodiment, the related constraint is limited to single-layer bitstreams as follows:

It is a requirement of bitstream conformance that no scalable-nested BP SEI message shall be in a single-layer AU that does not contain a non-scalable-nested BP SEI message.

- 5 Although some aspects have been described in the context of an apparatus, it is clear that these aspects also represent a description of the corresponding method, where a block or device corresponds to a method step or a feature of a method step. Analogously, aspects described in the context of a method step also represent a description of a corresponding block or item or feature of a corresponding apparatus. Some or all of the method steps may  
10 be executed by (or using) a hardware apparatus, like for example, a microprocessor, a programmable computer or an electronic circuit. In some embodiments, one or more of the most important method steps may be executed by such an apparatus.

- Depending on certain implementation requirements, embodiments of the invention can be  
15 implemented in hardware or in software or at least partially in hardware or at least partially in software. The implementation can be performed using a digital storage medium, for example a floppy disk, a DVD, a Blu-Ray, a CD, a ROM, a PROM, an EPROM, an EEPROM or a FLASH memory, having electronically readable control signals stored thereon, which cooperate (or are capable of cooperating) with a programmable computer system such that  
20 the respective method is performed. Therefore, the digital storage medium may be computer readable.

- Some embodiments according to the invention comprise a data carrier having electronically readable control signals, which are capable of cooperating with a programmable computer  
25 system, such that one of the methods described herein is performed.

- Generally, embodiments of the present invention can be implemented as a computer program product with a program code, the program code being operative for performing one of the methods when the computer program product runs on a computer. The program  
30 code may for example be stored on a machine readable carrier.

Other embodiments comprise the computer program for performing one of the methods described herein, stored on a machine readable carrier.

In other words, an embodiment of the inventive method is, therefore, a computer program having a program code for performing one of the methods described herein, when the computer program runs on a computer.

- 5 A further embodiment of the inventive methods is, therefore, a data carrier (or a digital storage medium, or a computer-readable medium) comprising, recorded thereon, the computer program for performing one of the methods described herein. The data carrier, the digital storage medium or the recorded medium are typically tangible and/or non-transitory.

10

A further embodiment of the inventive method is, therefore, a data stream or a sequence of signals representing the computer program for performing one of the methods described herein. The data stream or the sequence of signals may for example be configured to be transferred via a data communication connection, for example via the Internet.

15

A further embodiment comprises a processing means, for example a computer, or a programmable logic device, configured to or adapted to perform one of the methods described herein.

- 20 A further embodiment comprises a computer having installed thereon the computer program for performing one of the methods described herein.

- A further embodiment according to the invention comprises an apparatus or a system configured to transfer (for example, electronically or optically) a computer program for performing one of the methods described herein to a receiver. The receiver may, for example, be a computer, a mobile device, a memory device or the like. The apparatus or system may, for example, comprise a file server for transferring the computer program to the receiver.

- 25 30 In some embodiments, a programmable logic device (for example a field programmable gate array) may be used to perform some or all of the functionalities of the methods described herein. In some embodiments, a field programmable gate array may cooperate with a microprocessor in order to perform one of the methods described herein. Generally, the methods are preferably performed by any hardware apparatus.

35

The apparatus described herein may be implemented using a hardware apparatus, or using a computer, or using a combination of a hardware apparatus and a computer.

5 The methods described herein may be performed using a hardware apparatus, or using a computer, or using a combination of a hardware apparatus and a computer.

10 The above described embodiments are merely illustrative for the principles of the present invention. It is understood that modifications and variations of the arrangements and the details described herein will be apparent to others skilled in the art. It is the intent, therefore, to be limited only by the scope of the impending patent claims and not by the specific details presented by way of description and explanation of the embodiments herein.

References

- [1] ISO/IEC, ITU-T. High efficiency video coding. ITU-T Recommendation H.265 | ISO/IEC 23008 10 (HEVC), edition 1, 2013; edition 2, 2014.

Claims

1. An apparatus for receiving one or more input video data streams, wherein each of the one or more input video data streams has an input video encoded thereinto,  
5 wherein the apparatus is configured to generate an output video data stream from the one or more input video data streams, the output video data stream encoding an output video, wherein the apparatus is configured to generate the output video data stream such that the output video is the input video being encoded within one of the  
10 one or more input video data streams, or such that the output video depends on the input video of at least one of the one or more input video data streams,  
  
wherein, if a concatenation flag is set to a first value, the apparatus is configured to determine that coded picture buffer delay offset information is to be used for  
15 determining an access unit removal time of a current picture of a plurality of pictures of the output video from a coded picture buffer, and  
  
if the concatenation flag is set to a second value, the apparatus is configured to determine that the coded picture buffer delay offset information is not to be used to  
20 determine the access unit removal time.
2. The apparatus according to claim 1,  
  
25 wherein the apparatus is configured to drop a group of one or more pictures of the input video of a first video data stream of the one or more input video data streams to generate the output video data stream,  
  
wherein the apparatus is configured to determine an access unit removal time for at least one of the plurality of pictures of the output video from the coded picture buffer  
30 depending on the coded picture buffer delay offset information.
3. The apparatus according to claim 1,  
  
35 wherein a first video received by the apparatus is a preprocessed video which results from an original video from which a group of one or more pictures has been dropped to generate the preprocessed video,

wherein the apparatus is configured to determine an access unit removal time for at least one of the plurality of pictures of the output video from the coded picture buffer depending on the coded picture buffer delay offset information.

5

4. The apparatus according to claim 2, wherein the buffer delay offset information depends on a number of pictures of the input video that have been dropped.

5. The apparatus according to claim 2,

10

wherein the one or more input video data streams are two or more input video data streams, and

15

wherein the apparatus is configured to splice the processed video and the input video of a second video data stream of the two or more input video data streams to obtain the output video, and is configured to encode the output video into the output video data stream.

6. The apparatus according to claim 5,

20

wherein the apparatus is configured to determine whether or not to use coded picture buffer delay offset information for determining the access unit removal time of the current picture, depending on a location of the current picture within the output video, or

25

wherein the apparatus is configured to determine whether or not to set a coded picture buffer delay offset value of the coded picture buffer delay offset information to 0 for determining the access unit removal time of the current picture depending on the location of the current picture within the output video.

30

7. The apparatus according to claim 1, wherein the apparatus is configured to determine the access unit removal time of the current picture depending on a removal time of a preceding picture.

8. The apparatus according to claim 1, wherein the apparatus is configured to determine the access unit removal time of the current picture depending on initial coded picture buffer removal delay information.
- 5 9. The apparatus according to claim 8, wherein the apparatus is configured to update the initial coded picture buffer removal delay information depending on a clock tick to obtain temporary coded picture buffer removal delay information to determine the access unit removal time of the current picture.
- 10 10. The apparatus according to claim 1, wherein the apparatus is configured to signal to a video decoder, whether or not to use coded picture buffer delay offset information for determining the access unit removal time of the current picture from the coded picture buffer.
- 15 11. The apparatus according to claim 10, wherein the current picture is located at a splicing point of the output video, where two input videos have been spliced.
12. A non-transitory digital storage medium storing a video data stream,
- 20 wherein the video data stream has a video encoded thereinto,
- wherein the video data stream comprises coded picture buffer delay offset information and a concatenation flag,
- 25 wherein a determination of whether or not to use the coded picture buffer delay offset information is used for determining a removal time of a picture from a coded picture buffer depends at least on the concatenation flag,
- 30 wherein if the concatenation flag is set to a first value then the concatenation flag indicates that the coded picture buffer delay offset information needs to be used to determine one or more removal times, and
- 35 wherein if the concatenation flag is set to a second value being different from the first value then the concatenation flag indicates that the indicated offset is not used to determine the one or more removal times.

13. The non-transitory digital storage medium storing a video data stream according to claim 12, wherein the video data stream comprises initial coded picture buffer removal delay information.
- 5 14. A video encoder,
- wherein the video encoder is configured to encode a video into a video data stream, wherein the video encoder is configured to generate the video data stream such that the video data stream comprises coded picture buffer delay offset information,
- 10 wherein the video encoder is configured to determine whether or not to use the coded picture buffer delay offset information for determining a removal time of a picture from a coded picture buffer,
- 15 wherein, if a concatenation flag is set to a first value, the coded picture buffer delay offset information is determined to be used for determining the removal time, and
- if the concatenation flag is set to a second value, the coded picture buffer delay offset information is determined not to be used to determine the removal time.
- 20 15. The video encoder according to claim 14, wherein the video encoder is configured to generate the video data stream such that the video data stream comprises initial coded picture buffer delay offset information.
- 25 16. A video decoder for receiving a video data stream a video stored therein,
- wherein the video decoder is configured to decode the video from the video data stream,
- 30 wherein the video decoder is configured to decode the video depending on an access unit removal time of a current picture of a plurality of pictures of the video from a coded picture buffer,
- wherein the video decoder is configured to decode the video depending at least on
- 35 a concatenation flag indicating whether or not to use coded picture buffer delay offset

information for determining the access unit removal time of the current picture from the coded picture buffer,

5 wherein if the concatenation flag is set to a first value then the video decoder is configured to use the coded picture buffer delay offset information to determine one or more removal times, and

10 wherein if the concatenation flag is set to a second value being different from the first value then the video decoder is configured to not use the coded picture buffer delay offset information to determine the one or more removal times.

15 17. The video decoder according to claim 16, wherein the access unit removal time for at least one of the plurality of pictures of the video from the coded picture buffer depends on the coded picture buffer delay offset information.

18. The video decoder according to claim 16, wherein the video decoder is configured to decode the video depending on whether or not a coded picture buffer delay offset value of the coded picture buffer delay offset information is set to 0.

20 19. The video decoder according to claim 16,

wherein the video decoder is configured to determine the access unit removal time of the current picture depending on a removal time of a preceding picture.

25 20. The video decoder according to claim 16, wherein the video decoder is configured to determine the access unit removal time of the current picture depending on initial coded picture buffer removal delay information.

30 21. The video decoder according to claim 20, wherein the video decoder is configured to update the initial coded picture buffer removal delay information depending on a clock tick to obtain temporary coded picture buffer removal delay information to determine the access unit removal time of the current picture.