

Redundant serial bus and method for its operation

5

Description

The invention relates to a redundant serial bus and to a method for its operation.

10

The general problem is to connect serial bus systems which are known per se but have no system-integrated redundancy means, that is to say correctly standardized and thus interoperable bus systems, to one another by means of bus lines of redundant design.

15

Furthermore, there is a problem in selecting one of the bus lines of redundant design for communication in that it is no longer possible to identify complex faults at the purely physical level by, for example, transmission level identification. The evaluation must be carried out at a higher level of protocol processing. First of all, at least a portion of the serial transmission must be identified as being correct before the selected line can be selected for receiving the message. The monitored portion of the message must be at least sufficiently long that reflections, which may have a specific delay time on the bus, are reliably identified.

25
30

Normally, bus systems use special bus controllers for the lower layers of the transmission protocol. If these controllers do not provide appropriate redundancy, the necessary locations for the implementation of appropriate redundancy are no longer accessible to a user of this controller.

35

It is known from the publication
"Automatisierungstechnik" [Automation Engineering]

R. Oldenbourg Verlag Vienna 1992, Volume I, page 406
for the data traffic to be switched from the active bus
to a passive bus in a redundant system when a
changeover criterion occurs, in which case the
5 respective active bus represents a selection, which can
be predetermined, of identical and equal-priority buses
in the redundant bus system. Failures of the active bus
and cyclic interrogations of the difference between the
transfer requests on the active and passive buses are
10 intended to be used as the changeover criterion.

A method for operation of an asynchronous and redundant
serial bus, comprising $n > 1$ parallel independent lines,
is known from DE 195 13 318, in which at least two
15 multiplexers are provided which can be synchronized to
one another and are suitable for bidirectional
transmission of data information between a serial bus
interface and one of the parallel lines. In this case,
the invention provides that a preferred line of the
20 redundant serial bus is defined as the primary bus and
the $n-1$ remaining lines are defined as standby buses,
that, when data traffic takes place without any
disturbance, data information is interchanged between
the stations connected via the multiplexers, via the
25 primary bus as the active bus, and control information
is interchanged between the multiplexers via at least
one bus which can be predetermined, that, if the
transmission quality on the active bus falls below a
limit which can be predetermined, a standby bus which
30 can be predetermined is defined as the active bus, a
fault message is passed to a higher-level entity and
the deactivated bus is analysed, and that, if the
transmission quality of the primary bus rises beyond a
limit which can be predetermined, the primary bus is
35 defined as the active bus once again.

In this case, the complexity for synchronization of all
the bus subscribers to the active bus is regarded as
being disadvantageous both in terms of material and

with respect to the protocol functions required for this purpose. Since the synchronization means are bus subscribers themselves, / the number of available subscriber addresses for stations that can be connected
5 is, furthermore, reduced.

An Ethernet bus system which can be segmented and has $n > 1$ bus lines is known from DE 195 13 316 for redundant networking of single-port stations with one control
10 output and one communications port, in which bidirectional multiplexers are provided, having one multiplexed port and n line ports, and a control input. At least one monitoring device having n line ports is connected to the n bus lines of an Ethernet segment.
15 Each single-port station is assigned a multiplexer, in which case the communications port of the single-port station is connected to the multiplexed port of the multiplexer, and the control output of the single-port station is connected to the control input of the
20 multiplexer. The n line ports of each multiplexer are connected to the n bus lines of an Ethernet segment.

Disadvantageously, each single-port station has to be equipped with a control output for controlling the
25 multiplexer. Particularly when retrofitting redundant bus lines in existing systems, no such control output is available.

Furthermore, an Ethernet bus system, which can be
30 segmented, is known from DE 195 13 315 for redundant networking of single-port stations, in which two lines are arranged in parallel, at least in segment elements, and addressable bidirectional multiplexers are provided as active network subscribers for connection of the
35 single-port stations to the two lines, which multiplexers can be controlled by means of at least one monitoring unit, which can be addressed as an active network subscriber.

This Sheet Has Been Replaced



PART OF THIS SHEET HAS BEEN
REPLACED

~~THIS SHEET HAS BEEN
REPLACED~~

A disadvantage in this case is the large number of network addresses required, which limits the number of possible single-port stations in the same network.

5 The invention is based on the object of specifying means which allow serial bus systems which are known per se and have no system-integrated redundancy means to be connected to one another by means of bus lines of redundant design. In this case, the existing bus system
10 is intended to remain as uninfluenced as possible, and to be capable of compatible use. Mixed operation with non-redundant subscribers is intended to be possible, and the redundancy means are intended to identify and process even relatively complex faults, such as
15 incorrect bus terminations and the like, correctly.

According to the invention, this object is achieved by the means of Patent Claim 1 and the steps in Patent Claim 10. Advantageous refinements of the invention are
20 described in the dependent Claims 2 to 9 and 11.

The invention now comprises, for each of the receiving lines, additionally handling a portion of the protocol in the upstream device in order to satisfy the
25 necessary decision criteria. After the evaluation, a line which has been identified as being fault-free is then selected. The selected line is then converted back to the original signal, in such a way that it can be read to the normal communications controller or the
30 appliance.

The invention is in this case based on the knowledge that faults in the transmission path can normally be identified in the preamble or, in the case of UART
35 protocols, during the transmission of the first byte. /

/ According to the invention, an upstream device is provided to which, on the one hand, bus lines of redundant design and, on the other hand, subscribers or

goto
Pg. 5.



appliances without system-integrated redundancy means
are connected, in which case one of the bus lines is in
each case connected to the connected subscriber or
appliance, completely dispensing with system-integrated
5 redundancy means.

In such redundant bus systems, transmissions are always
made on all the lines, while any fault-free line is
selected for reception. This means that different
10 receivers connected to the same bus lines can identify
different bus lines as being fault-free.

The available bus controllers can still be used, in an
advantageous manner. Furthermore, existing appliances
15 with bus controllers but without system-integrated
redundancy means can easily be networked redundantly,
without changing the system architecture. / There is no
need for any additional subscriber addresses for
synchronization means.

20 The concept of upstream redundancy applies to all types
of serial communication, and is implemented in the
physical layer. One receiving line from n ($n \geq m+1$)
receiving lines is selected for redundancy, depending
25 on the validity of a data stream. The selection applies
for the duration of a transmission block (frame).
Transmission takes place on all the transmitting lines.
Receiving and transmitting lines may be combined to
form a bidirectional bus line.

30 The invention will be explained in more detail in the
following text with reference to an exemplary
embodiment with two parallel bus lines. In the drawings
required for this purpose:

35 Figure 1 shows an outline illustration of a redundant
bus system

This Sheet Has Been Replaced



PART OF THIS SHEET HAS BEEN
REPLACED

Figure 2 shows a block diagram of a redundancy means which can be connected upstream

Figure 3 shows an outline illustration of a redundant bus system with monitoring

Figure 4 shows a block diagram of a redundancy means which can be connected upstream, with monitoring

10

The outline of a redundant bus system according to the invention is shown in Figure 1. Groups 21 to 25 of bus subscribers 2 are connected to a redundant serial bus 1, which comprises two bus lines 11 and 12, with each of the bus subscribers 2 having a single, redundancy-free bus communications interface 200.

The bus subscribers 2 in the first and second groups 21 and 22 are each connected via a subscriber-specific redundancy means 3, which can be connected upstream, to both bus lines 11 and 12 of the redundant serial bus 1. The bus subscribers 2 in the fourth group 24 are connected via a redundancy-free serial bus 4 and a common redundancy means 3, which can be connected upstream, to both bus lines 11 and 12 of the redundant serial bus 1. The bus subscribers 2 in the third group 23 are connected exclusively to the bus line 11 of the redundant serial bus 1. The connection to one of the bus lines 11 and 12 is in this case advantageously optional, and the connections can be mixed. There is no need for any preferred position in this case.

The redundancy of the serial bus 1 can be scaled in a particularly advantageous manner to satisfy the requirements for availability of the individual bus subscribers 2. Furthermore, mixed operation of subscribers 2, connected in a redundant and non-redundant fashion, on the same redundant serial bus 1 is possible.

The fifth group 25 comprises so-called repeaters, which are each intended for connecting one bus line 11 and 12 in a first segment to in each case one bus line in a
5 second segment of the same bus system.

Figure 2 shows the outline structure of a redundancy means 3 which can be connected upstream. The redundancy means 3 which can be connected upstream is equipped
10 with a receiver 31 and a transmitter 32. The receiver 31 comprises in each case one input stage 311, one evaluation stage 312 and one output stage 313 at least for each bus line 11 and 12. The input stage 311 is equipped with means for synchronization, filtering and
15 serial/parallel conversion. Furthermore, means may also be provided for evaluation of the data stream (parity, framing ...), and the states may be passed on to the evaluation stage 312. It is expedient for the input stage 311 to have an amplifier 314 connected upstream
20 of it, which has means for matching the input stage 311 to the physical transmission medium of the bus line 11 and 12 of the redundant serial bus 1.

The evaluation stage 312 comprises means for evaluation
25 of the data stream, for time evaluation, for assessing the state of the receiving lines and for line selection.

The output stage 313 has means for parallel/serial
30 conversion, for muting in the case of faulty received data and driver stages (RS485, RS232, optical conductor, ...) for matching to the redundancy-free bus communications interface 200 of the bus subscribers 2. Alternatively, it is possible for the serial data
35 stream, delayed for the reception identification time, to be passed on directly from the input stage 311 to the output stage 313. There is then no need for the parallel/serial conversion.

In the input stage 311, the received signal is passed via a filter to a synchronization stage. In the synchronization stage, the receiver 31 is synchronized to the data stream. The transmission rate can be
5 configured or identified automatically. The incoming data stream is evaluated for automatic rate identification. The data stream may be passed on to the evaluation stage 312 in serial or parallel form.

10 In the evaluation stage 312, the receiving line 11 or 12 is selected on the basis of criteria which are determined from the serial or parallel data stream, the time response and the state of the receiving line 11 and 12. The criteria from the data stream include the
15 frame error, parity error, preambles, synchronization sequences, etc. Further criteria are derived from the time response, from pause times during the data transfer or from the data transfer duration. A time-dependent changeover strategy may also provide
20 criteria. One selection criterion which may characterize the state of the receiving line 11 and 12 is also the signal level, which indicates an overload or underload.

25 In the output stage 313, bit retiming is carried out for the data stream which has been identified as being valid and has been selected, and this is output via a driver stage. The time delay which occurs in the redundancy means 3 which can be connected upstream is
30 not critical since it is in the same order of magnitude as the cable propagation times (reflection propagation time). If no valid data stream is identified, then the output stage 313 supplies the rest state as the output signal.

35

At the transmitting end, the redundancy means 3 which can be connected upstream has a transmitter 32 with in each case one driver 321 for each bus line 11 and 12 of the redundant serial bus 1. The data stream to be

transmitted is output via the drivers 321 to all the bus lines 11 and 12.

Using the same reference symbols for the same means,
5 Figure 3 shows the outline of a redundant bus system in which selected bus subscribers 2 are equipped with diagnosis means. In this case, the selected bus subscribers 2 in the first subscriber group 21 are equipped with an additional diagnosis interface 201 and
10 are connected by means of additional control lines 5 to the associated redundancy means 3 which can be connected upstream.

In this context, Figure 4 shows a block diagram of a
15 redundancy means 3 which can be connected upstream, with additional control lines 5 for monitoring and diagnosis. The evaluation stage 312 in the receiver 31 has an output for outputting status information, and inputs for selection of a dedicated bus line 11 or 12
20 as the receiving line, which is connected via in each case one of the additional control lines 5 to the additional diagnosis interface 201 of the selected bus subscriber 2 in the first subscriber group 21.

25 Furthermore, the receiver 31 has means for testing and for diagnosis, which allow the receiver 31 to be set to different operating modes. In addition to selecting a bus line 11 or 12 as the receiving line, which is called the normal mode, reception on a permanently set
30 bus line 11 or 12 is also envisaged, as a function of the validity of a data stream, in which case the evaluation stage 312 may be switched on and off.

For test and diagnosis purposes, the receiver 31 can be
35 configured such that reception takes place exclusively on a specific bus line 11 or 12. In this case, it is possible for the selected bus line 11 or 12 to make a direct connection between the input and the output of the receiver 31. For this purpose, the evaluation stage

312 of the receiver 31 is initialized appropriately by the selected bus subscriber 2, via the control lines 5.

At the transmitting end, the invention provides, for
5 test and diagnosis purposes, for the data stream to be output in a specifically configurable manner on exclusively one or more bus lines 11 and 12. For this purpose, the drivers 321 in the transmitter 32 are equipped with gate circuits, by means of which the
10 output of the respective driver 321 is muted. Each gate circuit has a control input, which is connected via one of the control lines 5 to the diagnosis interface 201 of the selected subscriber 2.

15 During diagnosis, a selected subscriber may deliberately transmit and receive data via one and the same selected bus line 11 or 12. This method identifies a defective bus line 11 and 12, and signals this to a higher-level device.



Patent Claims

1. Redundant serial bus having $n > 1$ parallel bus lines
for redundant networking of bus subscribers each
5 having a single bus communications interface,
characterized
- in that a redundancy means (3), which can be
connected upstream, having n interfaces for
connection to n parallel bus lines (11, 12) and
10 one interface for connection to the single bus
communications interface (200) of at least one
bus subscriber (2) are provided,
 - in that the redundancy means (3) which can be
connected upstream has, at the receiving end,
15 an input stage (311) at least for each bus line
(11, 12), and has an evaluation stage (312) and
an output stage (313) for all the bus lines
(11, 12),
 - in that the evaluation stage (312) has means
20 for evaluating the validity of a data stream
and for selection of one of the bus lines
(11, 12) as the receiving line, and
 - in that the redundancy means (3) which can be
connected upstream has, at the transmitting
25 end, a driver (321) for each bus line (11, 12). ,
2. Redundant serial bus according to Claim 1,
characterized
in that the input stage (311) has means for
30 synchronization and filtering.
3. Redundant serial bus according to one of Claims 1
and 2,
characterized
35 in that the input stage (311) has means for
serial/parallel conversion.
4. Redundant serial bus according to Claim 3,
characterized



PART OF THIS SHEET HAS BEEN
REPLACED

in that the output stage (313) has means for parallel/serial conversion.

5. Redundant serial bus according to Claim 1,
5 characterized
in that the evaluation stage (312) has means for evaluation of the data stream, for time evaluation, for assessment of the state of the receiving lines and for line selection.
- 10 6. Redundant serial bus according to one of Claims 1 to 5,
characterized
in that the redundancy means (3) which can be
15 connected upstream can be permanently set to one bus line (11, 12) on the receiving side.
7. Redundant serial bus according to one of Claims 1 to 5,
20 characterized
in that the redundancy means (3) which can be connected upstream can be permanently set to one bus line (11, 12) on the transmitting side.
- 25 8. Redundant serial bus according to Claim 7,
characterized
in that each driver (321) comprises a gate circuit for muting the driver output.
- 30 9. Redundant serial bus according to one of Claims 1 to 8,
characterized
- 35 - in that at least one selected bus subscriber (2) is equipped with a diagnosis interface (201) for connection of control lines (5),
- in that the evaluation stage (312) of the redundancy means (3) which can be connected upstream is equipped with connections for connection of control lines (5), and



- in that the gate circuits of the drivers (321) have control inputs which are connected by means of control lines (5) to the diagnosis interface (201).

5

10. Method for operating a redundant serial bus according to Claim 1, characterized

- in that, during operation, identical message packets are sent in parallel and at the same time to all the bus lines (11, 12),
- in that the identical message packets on all the bus lines (11, 12) are received in parallel by the redundancy means (3) which can be connected upstream,
- in that the data streams of the received message packets are checked for their validity, and
- in that, depending on the validity of the data streams, one of the bus lines (11, 12) is selected, whose data stream is passed on to the connected bus subscriber (2).

11. Method according to Claim 10, characterized

25

in that data packets are sent and received on one and the same bus line (11, 12) in order to diagnose the redundant serial bus (1) with the same selected bus subscriber (2).

