(2005025978)

27 APR 2005

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau

(43) International Publication Date
21 May 2004 (21.05.2004)

PCT

(10) International Publication Number
WO 2004/041455 A3

(51) International Patent Classification[7]: E21B 33/035

(21) International Application Number:
PCT/US2003/034866

(22) International Filing Date: 31 October 2003 (31.10.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/423,283 1 November 2002 (01.11.2002) US

(71) Applicant: FMC TECHNOLOGIES, INC. [US/US]; 200 East Randolph Drive, Chicago, IL 60601 (US).

(72) Inventor: BARTLETT, Christopher, D.; 8506 Shadow Valley Lane, Spring, TX 77388 (US).

(74) Agent: QUERY, Henry, C., Jr.; 504 S. Pierce Avenue, Wheaton, IL 60187 (US).

(81) Designated States *(national)*: AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States *(regional)*: ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

— *as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for all designations*

[Continued on next page]

(54) Title: VACUUM ASSISTED SEAL ENGAGEMENT FOR ROV DEPLOYED EQUIPMENT



(57) Abstract: A method for attaching a first component (10) which comprises a depending portion (12) to a second component (82) which comprises a bore (84) that is sized and configured to receive the depending portion, wherein the first and second components are exposed to a fluid which is at an ambient pressure, comprises the steps of inserting the depending portion at least partially into the bore and then creating a bore pressure within the bore which is less than the ambient pressure. In this manner a pressure difference between the ambient pressure and the bore pressure will force the depending portion into the bore to thereby attach the first component to the second component. The first component is a tree cap and the second component is a subsea christmas tree.

WO 2004/041455 A3

162162

ACTION

— *as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii)) for all designations*

Published:

— *with international search report*

— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

(88) Date of publication of the international search report:
22 July 2004

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.