



(43) International Publication Date
20 March 2014 (20.03.2014)

(10) International Publication Number
WO 2014/041435 A2

- (51) International Patent Classification: Not classified
- (21) International Application Number: PCT/IB2013/002819
- (22) International Filing Date: 23 July 2013 (23.07.2013)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 61/677,855 31 July 2012 (31.07.2012) US
- (71) Applicant: **CETAMAX VENTURES LTD.** [CN/CN]; Suite 1201, Tower 2, The Gateway 25, Canton Road, Tsimshatsui, Kowloon, Hong Kong (CN).
- (72) Inventors; and
- (71) Applicants : **LOTT, Roger, Kai** [CA/CA]; 10819-18 Avenue, Edmonton, AB T6J 6P2 (CA). **YUSOF, Kamalul, Arifin** [MY/MY]; No. 1, Lott 282, Jalan Senyum Matahari, Country Heights, Kajang Selangot, 43000 (MY).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM,

AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

- without international search report and to be republished upon receipt of that report (Rule 48.2(g))

(54) Title: METHODS AND SYSTEMS FOR COMBINED OXIDATIVE AND HYDROTREATMENT OF HYDROCARBON FUEL

(57) Abstract: A method for combined reductive and oxidative treatment of liquid hydrocarbon feedstock to form upgraded liquid fuel having increased cetane number and reduced sulfur content. The yield of upgraded liquid fuel having a given cetane number is higher than processes than only increase cetane number by oxidative treatment. The feedstock can be initially hydrotreated to reduce sulfur content followed by oxidative treatment to increase cetane number. A first portion of a hydrotreated intermediate stream can be oxidative ly treated to yield high cetane number blending stock, which is combined with a second portion of the hydrotreated intermediate stream to yield upgraded liquid fuel having increased cetane number and reduced sulfur content. Combining hydrotreatment with oxidative treatment facilitated by high energy cavitation maximizes yield and fuel quality.



WO 2014/041435 A2