

Multi-purpose sports apparatus particularly for improving footballers' technical skills

The utility model relates to a multi-purpose sports apparatus, comprising a foundation body comprising a playing surface, the playing surface of the foundation body looking from the interior of the foundation body has a convex top surface, a support structure separating the playing surface from the base and an obstacle placed on the foundation body.

State of the art

Present utility model belongs to the field of sport, more precisely to the field of equipment or devices for training/exercising, namely to table games for physical exercising based on the outdoor games, according to the International patent classification (IPC) A63B67/04.

Many technical devices have been developed for training sportspeople. Among the devices which have been described are aids for polishing technical skills for ball games, including ball control and kicking techniques for football.

Among these skills-improvement devices are those described in the patent of registration number HU 222643 and the utility model of registration number HU U2188. These essentially consist of a vertically-configured target body similar to football goalposts carrying several targets which the player has to hit with the ball. A hit indicator unit evaluates the striking of the targets and displays the results to the player. This arrangement is useful for improving kicking skills, but has the disadvantages of not requiring intensive movement and of requiring substantial free space for the player if the shots are to be made while in motion.

The specification of the patent of registration number HU 222429 is for a device which may be used in a game similar to football. The apparatus comprises an enclosure and a depression in the central part of the casing to receive the ball. The specification of the utility model of registration number HU U1917 describes skills game to be played with a ball which must be rolled into holes placed in an area surrounded by posts similar to the board game "Rex". This arrangement is suitable for a small game as a practice, and also requires substantial free space. A further disadvantage is that these games do not require the player to engage in intensive movement with frequent changes of place, and so do not improve stamina.

In DE 200301215 U1 a table for ball games, e.g. table tennis is disclosed, having a central flat region between two regions sloping downwards. This ensures that low trajectory balls can still be reached and returned, thus extending the scope of the game. The two sloping regions are identical and elliptical, oval or part circular. The whole table is mounted on ground supports. A net is fitted across the centre of the table. The table can be made of any suitable materials. It is not possible to amend the geometry of the table as well as the playing height.

US 5,398,926 A shows a table top to be used in games of table tennis and the like. The table top is convex in one or more directions serving to accelerate the game. However, there is no possibility to adjust the playing height or modify the convexity of the table.

The GB 25767 relates to an attachment to a table for deflecting the ball in games, such as ping-pong, wherein one or more wedge or similar shaped blocks can be fastened on a flat table in desired positions. The dimensions and shapes of the blocks cause local effects on the ball and cannot influence the shape of a full table surface on either side.

FR 2 606 653 describes a table sport played by two or four players, as singles or doubles, with a ping-pong ball and racquets of semi-circular shape, inside which one slips one's hand, as well as to a table of the same size as that of ping-pong but articulated in its centre in order to make two panels thereof which are tilted towards the players. There is no net in the centre of the table and the panels are entirely flat in their whole extent.

Technical problem

The technical problem which is to be solved by the present utility model is related to how to constructionally build a sports apparatus that would enable eliminating the deficiencies of known football skills improvement devices and to implement a sports apparatus which may be used in a small area, requires the person using it to move with frequent changes of place and position, and demands excellent ball control and kicking technique, by the use of a suitable playing surface. Where these skills are deficient, it should substantially improve them in the course of play.

Summary of the utility model

It has been realized that said purpose may be fulfilled if the top surface of a table-tennis-table-like structure is formed with an adjustable curvature deviating from the usual range and a playing area of unusual dimensions, and the carrier base is placed at the appropriate height from the ground, then a ball impinging on the playing surface will in every case bounce outwards from the space occupied by the sports apparatus and so the person using it, by appropriate movement, can in every case reach the ball with his foot or head without the sports apparatus causing any inhibiting or disturbing obstruction.

The greatest benefit deriving from the special design of the sports apparatus of the utility model is that on a small area, possibly even indoors, and involving considerable bodily movement, the persons using it may perform activities involving ball handling and targeted return kicks. These activities will gradually develop their stamina, speed, ball sensitivity and ball control. Furthermore, it develops concentration, rapid situation appraisal and decision-making.

Also among the advantages is that the sports apparatus of the model, in addition to its utility as a device for improving skills, provides an enjoyable game for people who like football tennis, with the difference that this apparatus permits a similar game to be played on a much smaller area.

Also among the advantages is that the sports apparatus of the model may be made and assembled using simple tools and known manufacturing technology, so that its production cost may be kept low. Also beneficial is that the sports apparatus does not demand special maintenance. A further advantage deriving from the foregoing is that with modest expenditure it is possible to acquire a long-lasting aid for training and playing.

The sports apparatus of the model has the further advantage that it can be erected and dismantled easily and without special expertise, and thus it may easily be transferred from one site to another, and so the location of skills improvement may easily be changed.

It is important to note that the sports apparatus of the model may be made in such a way that the trajectory and speed of the ball bouncing from the playing area can be changed, so that the same sports apparatus may be used by both adults and children. This involves only the adjustment to the desired extent of the height of the playing area and, where necessary, the curvature of the top surface of the playing area.

Short description of the drawings

The accompanying drawing, which is included to provide a further understanding of the utility model and is incorporated in and constitute a part of this application, illustrates an embodiment of the utility model and together with the description serves to explain the principle of the utility model. In the drawing:

Fig. 1 shows a preferred embodiment of the sports apparatus of the utility model, partly in

cross-section.

Detailed description of the utility model

Figure 1 shows a preferred embodiment of a sports apparatus 1. The sports apparatus 1 has a support structure 30 placed on a base 2 by its lower part 32 and has a foundation body 10 held by the support structure 30. The foundation body 10 also has an upper member 10a and a lower member 10b. The upper member 10a contains the playing area 11, whose external upper side 12 opposite the base 2 has a convex top surface 15. Although the top surface 15 shown in Fig. 1 is formed as a part of a cylindrical shell, in other embodiments of the sport apparatus the convex top surface 15 can comprise a spatial curvature consisting of several curved sections as well.

On the convex top surface 15 is arranged an obstacle 20, which is a plate-like body made of an appropriately rigid, in this embodiment transparent material and whose task is to divide the playing area 11 into two halves and prevent the ball – not shown in Fig. 1 – from simply rolling over the convex top surface 15 of the foundation body 10. In order to permit the height of the obstacle 20 to be adjusted, a spacing adjuster component 22 is assigned to the obstacle 20. The spacing adjuster component 22 rests on the convex top surface 15 of the upper member 10a of the foundation body 10 so that it also supports the obstacle 20. The upper edge 21 of the obstacle 20 can be raised or lowered relative to the convex top surface 15 by means of the spacing adjuster component 22. Said spacing adjuster component 22 can be formed e.g. as a slotted rod – not shown in the drawing – projecting from the convex top surface 15 and holding the obstacle 20.

The upper member 10a is made from plywood treated by a suitable timber industry process enabling bowing the plywood into a curve within certain limits. By contrast with the material of the upper member 10a, the lower member 10b of the foundation body 10 is made of rigid material and this lower member 10b essentially connects the upper member 10a of the foundation body 10 with the support structure 30.

The radius of curvature of the convex top surface 15 of the upper member 10a can be adjusted in a range between 3 m and 20 m. The radius of curvature of the convex top surface 15 may be changed in said range using a curvature adjustment mechanism 40 that comprises connection pieces 41 fastened to the upper member 10a and a tensioning mechanism 42. The connection pieces 41 are arranged near each shorter edge 14 of the upper member 10a and fastened to the inner side 13 of the upper member 10a and run parallel to each shorter edge 14 of the upper member 10a. The tensioning mechanism 42 is arranged between said connection pieces 41 and consists in this case of several threaded rods placed side by side and linked to the lower member 10b of the foundation body 10.

A length H of foundation body 10 can be chosen in a range between 2,7 m and 3,3 m. A width SZ of foundation body 10 can be chosen in a range between 1,3 m and 1,8 m. A distance T between the lowest point of the convex top surface 15, which in this embodiment is that part of the convex top surface 15 at the shorter edge 14, and base 2 can be chosen in a range between 0,45 m and 0,75 m.

The distance T can be adjusted using a height adjustment unit 31 of the support structure 30. The height adjustment unit 31 comprises connecting bodies 31a and 31b and an actuator component 31c arranged between the connecting bodies 31a and 31b. One of the connecting bodies 31a of height adjustment unit 31 rests on the lower part 32 of the support structure 30, while the other connector body 31b of support structure 30 is connected to the lower member 10b of foundation body 10. In the embodiment shown the actuator component 31c is a hydraulic cylinder which can be actuated manually to continuously alter the distance T

between the foundation body 10 and the base 2. According to a preferred embodiment it is advantageous to make the distance T adjustable so that the convex top surface 15 of the playing area 11 can be lowered to enable smaller persons, such as children, to play the game.

The support structure 30 and the lower part 32 have overall horizontal dimensions that the area covered by the lower part 32 contacting the base 2 is less than the area bounded by the perpendicular projection of the foundation body 10 on the base 2 supporting the sports apparatus 1 and therefore they do not disturb the users even if the ball, impinging with low energy on the convex top surface 15 of the upper body 10a of the foundation body 10, only bounces to a short distance from the convex top surface 15 to the area outside the foundation body 10.

To use the sports apparatus 1 of the utility model, the desired distance T between the foundation body 10 and the base 2 is set using the height adjusting unit 31 of the support structure 30. For this, by pumping the actuator component 31c, the foundation body 10 and thus the convex top surface 15 of the upper member 10a may be raised from the lowest distance T of 45 cm from the base 2 up to a maximum of 75 cm from the base 2.

Then the radius of curvature of the convex top surface 15 may be adjusted. This involves rotating the tensioning mechanism 42 of the curvature adjustment mechanism 40 so that the shorter edges 14 of upper member 10a of the foundation body 10 become closer or further away from each other. When the shorter edges 14 move closer to each other, the radius of curvature of the convex top surface 15 decreases. When the shorter edges 14 move away from each other, the radius of curvature of the convex top surface 15 increases. A longer radius of curvature reduces the bounce of the ball from the convex top surface 15, and a shorter radius of curvature causes the ball to bounce further from the foundation body 10.

After making the adjustments, the persons using the sports apparatus 1 arrange themselves opposite the shorter edges 14 of the foundation body 10 and one person - in accordance with the rules of the game - kicks the ball so that it bounces on the playing area 11 of the foundation body 10 on the part which is separated by the obstacle 20 from the player who kicked the ball. The ball bouncing upwards and outwards from the convex top surface 15 of the foundation body 10 is returned by the other person using his or her foot or head in such a way that the ball flies over the obstacle 20 and bounces on the other side of the convex top surface 15 of the foundation body 10. The rally continues until one player misreturns the ball, which bounces on playing area 11 on the part between the player and the obstacle 20 or does not impinge on the convex top surface 15 of the foundation body 10 at all. The sports apparatus of the utility model is of use in all cases where it is desired, by means of an enjoyable game involving intensive movement and on a small area, to develop ball control and ball direction, increase strength and improve concentration, rapid appraisal skills and decision-making ability.

CLAIMS

1. Multi-purpose sports apparatus comprising a foundation body (10) comprising a playing surface (11) and the playing surface (11) of the foundation body (10) looking from the interior of the foundation body (10) has a convex top surface (15), the foundation body (10) has a support structure (30) separating the playing surface (11) from the base (2),

characterized in that

- the support structure (30) has an additional height adjustment unit (31) which has one connecting body (31a) fastened to the support structure (30) and another connecting body (31b) attached to the foundation body (10) containing the playing area (11), and an actuator component (31c) interposed between one connecting body (31a) and the other connecting body (31b), and
- the foundation body (10) has an upper member (10a) fitted with the convex top surface (15) containing the playing area (11) and a lower member (10b) located under the upper member, where the upper member (10a) is made of flexible material and the lower member (10b) of rigid material, and furthermore has a curvature adjustment mechanism (40) to alter the curvature of the upper member (10a), said curvature adjustment mechanism (40) is interposed between the upper member (10a) and the support structure (30).

2. Sports apparatus of claim 1, *characterized in* that the radius of curvature of the convex top surface (15) is between 3 m and 20 m.

3. Sports apparatus of claims 1, *characterized in* that the convex top surface (15) is formed as a part of a cylindrical shell.

4. Sports apparatus of claims 1 or 2, *characterized in* that the convex top surface (15) has a spatial curvature consisting of several curved sections.

5. Sports apparatus according to claim 1, *characterized in* that the support structure (30) comprises a lower part (32), the area covered by said lower part (32) contacting the base (2) is less than the area bounded by the perpendicular projection of the foundation body (10) on the base (2) supporting the sports apparatus (1).