

## **VIEWFINDER WITH MOBILE RED DOT AND ILLUMINATOR**

### **Field of the invention**

5   **[0001]** The present invention relates to a targeting system for firearms for munitions having a parabolic trajectory.

### **Prior art**

10   **[0002]** It is known from document EP 1 818 645 to superpose on a target a red dot that is movable to a target in order to improve the targeting of a parabolic shot. By parabolic shot, what is meant here is a ballistic shot for which the difference between the  
15   direct angle of sight and the angle of elevation of the weapon correcting for the effect of gravity is large, in particular, in excess of 5 to 10°. Document EP 2 221 571 proposes a similar solution in which a two-prism beamsplitter plays the role of reflective surface for  
20   steering the image of the red dot to the desired position. In these two documents, elevation is set by rotating a movable mirror.

**[0003]** It is sometimes necessary, besides superposition of a movable red dot, to designate or  
25   illuminate the target. These two documents have nothing to say on this subject.

### **Aims of the invention**

**[0004]** A first aspect of the invention aims to provide  
30   a targeting system combining illumination and movable red dot into a single synchronous device.

**[0005]** A second aspect of the invention aims to provide a targeting system allowing the user to correct for azimuthal drift of a munition due to the Magnus  
35   effect.

### **Summary of the invention**

**[0006]** The present invention relates to a movable red dot sight comprising a first fixed light source and a

first reflective plate, the light source generating a first collimated light beam that is projected onto the reflective plate in order to materialize a red dot or reticle that is visible to the shooter in reflection from the reflective plate and the first beam being projected onto the reflective plate by way of a rotatable mirror the angle of inclination of which with respect to the first light beam is adjustable.

**[0007]** By parabolic shot, what is meant in the present description is a shot for which the difference between the angle of elevation of the target and the angle of elevation for the shot is larger than  $10^\circ$ .

**[0008]** According to preferred embodiments of the invention, the movable red dot sight of the invention includes at least one, or a suitable combination, of the following features:

- the sight comprises an illuminator/designator in which said sight comprises a second fixed light source that generates a second collimated light beam that is initially parallel to the first light beam and that is steered by said rotatable mirror toward a second reflective plate placed at an angle of  $90^\circ$  to the first reflective plate in order to illuminate/designate a target;
- the first and/or second reflective plate is a semi-transparent plate beamsplitter;
- the sight comprises a device for adjusting the angle of inclination of the rotatable mirror with respect to the light beams, allowing the angle of the mirror to be adjusted depending on the distance of the target and/or the type of munition;
- the adjusting device is equipped with a graduation representing the distance of the target;
- the adjusting device is equipped with a plurality of graduations specific to different types of munition;
- the adjusting device comprises a motor or mechanical actuator for adjusting the angle of the rotatable

mirror and a ballistic computer that controls said motor/actuator and that allows the required mirror angle to be calculated and instigated depending on the distance of the target and on the type of munition used;

- the ballistic computer is equipped with a rangefinder that automatically communicates thereto the distance of the target when the shooter triggers the measurement;
- the first and/or second light source comprises a collimator with a convergent lens and a light source placed at the focal point of the lens of the collimator;
- the diameter of the generated light beam is small, preferably about 15 mm or smaller;
- the light source of the beam of the red dot is point-like, preferably with a diameter of about one tenth of a millimeter or of about one millimeter;
- the light source of the red dot is formed by an LED placed behind a mask that is located at the focal point of the lens of the collimator and that is drilled with a hole in the location of the optical axis of the generated light beam;
- the lateral position of the reticle is automatically moved laterally by a device controlled by the ballistic computer depending on the type of munition used and the distance of the target, so as to correct for the deviation in the trajectory of the munition due to the Magnus effect;
- the sight comprises a ballistic computer equipped with an inclinometer that measures the cant of the weapon, the computer determining the cant of the weapon that corrects for the Magnus effect, indications in the sight indicating when this inclination is achieved.

### 35 **Brief description of the figures**

[0009] Figure 1 shows the general parameters of a parabolic shot.

[0010] Figures 2 and 3 show a side view of a targeting system according to the invention.

[0011] Figure 4 shows a top view of a targeting system according to the invention.

5 [0012] Figure 5 shows an example of a display of a targeting system according to the invention.

**Reference numbers used in the figures**

- |    |         |                                                                           |
|----|---------|---------------------------------------------------------------------------|
|    | 1.      | User                                                                      |
| 10 | 2.      | Target                                                                    |
|    | 3.      | Shooting distance                                                         |
|    | 4.      | Axis of sight                                                             |
|    | 5.      | Weapon                                                                    |
|    | 6.      | Trajectory                                                                |
| 15 | 7.      | Sighting scope                                                            |
|    | 10.     | Illuminating light beam                                                   |
|    | 11.     | Light beam of the red dot                                                 |
|    | 12.     | Reticle or red dot                                                        |
|    | 13.     | Bore axis                                                                 |
| 20 | 20.     | Indicator of actual inclination                                           |
|    | 21.     | Visual inclination objective indicators                                   |
|    | 30.     | Red dot (reticle) light source                                            |
|    | 31.     | Collimating device (lens)                                                 |
|    | 32.     | Movable mirror                                                            |
| 25 | 33.     | Axis of rotation of the movable mirror                                    |
|    | 34.     | Semi-reflective plate for steering the red<br>dot                         |
|    | 35.     | (Semi-)reflective plate for steering the<br>designating/illuminating beam |
| 30 | 36.     | Designating/illuminating light source                                     |
|    | 51, 52. | Beamsplitter cubes                                                        |
|    | 53, 54. | Reflective surfaces of the beamsplitter<br>cubes                          |

35 **Detailed description of the invention**

[0013] The idea behind the invention consists in using one and the same movable part to define, on the one hand, the position of a movable red dot, and on the

other hand, the angle between an illuminating/designating beam and the bore axis of the weapon.

5     **[0014]** This system comprises two separate sources 30, 36 that illuminate the same reflective movable plane 32 (mirror). These two separate sources are collimated and/or focused by optical means 31, 37 and the obtained beams are parallel to each other. These two sources are vertically fixed.

10    **[0015]** The light source 30 that serves for the movable red dot is steered by the movable mirror 32 toward a first semi-reflective surface 34, 53 that steers it toward the eye of the user 1. The semi-reflective surface then allows the movable red dot to be  
15    superposed on the target. The angle at which this red dot is seen is adjusted via the position of the movable mirror 32.

**[0016]** The light source 30 that serves for the movable red dot is a point-like source of low brightness. It  
20    may for example form part of a screen of good resolution, so as to allow other information to be displayed.

**[0017]** The light source 36 that serves for the illumination is steered by the same movable mirror 32  
25    toward a second reflective surface 35, 54 that is perpendicular to the first, which steers it toward the target 2. The angle at which the illuminating beam is then emitted is parallel to the beam of the movable red dot, but, oriented at 180°. This second reflective  
30    surface may optionally be semi-reflective. Specifically, it may be sufficiently offset laterally in order not to obstruct the field of view of the user. Nevertheless, in order not to obstruct the field of view of the user, this surface is, preferably, semi-  
35    reflective.

**[0018]** The steering angle of the movable mirror may for example be modified by a piezoelectric,

electromagnetic or electrical actuator, or any other suitable means.

**[0019]** The illuminating source is sufficiently bright to illuminate a distant target. It may furthermore have  
5 a wavelength outside of the visible, for example in the case of use of a night-vision device (IR).

**[0020]** So as to obtain beams of plane waves (collimated or parallel beam) the light sources are, for example, placed in the focal plane of an optical  
10 system 31, 37. In the case of certain types of laser pointers, the laser beam is already collimated and no additional optics are required.

**[0021]** Such as described in document EP 2 221 571, which is incorporated herein by reference, the fixed  
15 mirrors, or one thereof, may advantageously be replaced by prisms. In this case, specifically, refraction induces a decrease in the movement of the light beams over the reflective surfaces 53, 54, this allowing the length thereof, and therefore the bulk of the system,  
20 to be decreased. These prisms are preferably integrated into two beamsplitter cubes 51, 52 allowing the image of the target to be superposed on the reticle.

**[0022]** Lastly, when the Magnus effect is to be taken into consideration, the luminous red dot and the  
25 designating beam may advantageously be moved to correct the azimuthal direction by moving the corresponding light sources laterally in their respective focal planes. This movement may either be obtained by an actuator or by lateral movement of the reticle over a  
30 screen.

**[0023]** Another way of taking into account the Magnus effect is to take advantage of the azimuthal error introduced by a non-zero cant. Advantageously, the sighting scope of the invention then comprises an  
35 inclinometer that measures the cant of the weapon and an optical display projected from the focal plane of the lens 31 of the red dot. In this case, the light source of the red dot advantageously comprises a screen

of good resolution, allowing both inclination (cant) information and the red dot to be displayed.

**[0024]** Preferably, depending on the distance of the target, a cant correcting for the Magnus effect is determined, the optical display indicating to the user when this cant is achieved. For example, the reticle may flash when the cant is achieved.

**[0025]** Figure 5 shows a display comprising cant indications. In this figure, visual indicators 21 define the ideal angle, and a straight-line segment 20 indicates the actual inclination of the weapon. Figure 5(a) shows the situation in which a cant of zero is sought, for example in the case where the azimuthal correction is obtained by moving the reticle. Figure 5(b) shows the situation in which the visual indicators have been inclined to inform the shooter that he must incline the weapon to correct for the Magnus effect. In figure 5(c), the inclination has been corrected and the weapon is in firing position (i.e. the inclination indicator 20 is aligned with the visual indicators 21). This aspect of the invention may be used in combination with the simultaneous use of an illuminator, or independently thereof.

**CLAIMS**

1. A movable red dot sight and illuminator comprising  
a first fixed light source (30) and a first reflective  
5 plate (34, 53), the light source generating a first  
collimated light beam that is projected onto the  
reflective plate (34, 53) in order to materialize a  
reticle or red dot that is visible to the shooter in  
reflection from the reflective plate (34, 53) and the  
10 first beam being projected onto the reflective plate  
(34, 53) by way of a rotatable mirror (32) the angle of  
inclination of which with respect to the first light  
beam is adjustable, characterized in that said sight  
furthermore comprises a second fixed light source (36)  
15 that generates a second collimated light beam that is  
initially parallel to the first light beam and that is  
steered by said rotatable mirror toward a second  
reflective plate (35, 54) placed at an angle of 90° to  
the first reflective plate in order to  
20 illuminate/designate a target.

2. The sight as claimed in claim 1, characterized in  
that the first and/or second reflective plate (34, 35,  
53, 54) is a semi-transparent plate beamsplitter.

25 3. The sight as claimed in either of claims 1 and 2,  
characterized in that it comprises a device for  
adjusting the angle of inclination of the rotatable  
mirror (32) with respect to the light beams, allowing  
30 the angle of the mirror to be adjusted depending on the  
distance of the target and/or the type of munition.

4. The sight as claimed in claim 3, characterized in  
that the adjusting device is equipped with a graduation  
35 representing the distance of the target.

5. The sight as claimed in claim 4, characterized in that the adjusting device is equipped with a plurality of graduations specific to different types of munition.

5 6. The sight as claimed in one of claims 3 to 5, characterized in that the adjusting device comprises a motor or mechanical actuator for adjusting the angle of the rotatable mirror (32) and a ballistic computer that controls said motor/actuator and that allows the  
10 required mirror angle to be calculated and instigated depending on the distance of the target (3) and on the type of munition used.

7. The sight as claimed in claim 6, characterized in  
15 that the ballistic computer is equipped with a rangefinder that automatically communicates thereto the distance of the target when the shooter triggers the measurement.

20 8. The sight as claimed in any one of the preceding claims, characterized in that the first and/or second light source (30, 36) comprises a collimator (31, 37) with a convergent lens and a light source placed at the focal point of the lens of the collimator.

25 9. The sight as claimed in one of the preceding claims, characterized in that the light source of the beam of the red dot or reticle is point-like, preferably with a diameter of about one tenth of a  
30 millimeter or of about one millimeter.

10. The sight as claimed in claim 9, characterized in that the light source of the red dot is formed by an LED placed behind a mask that is located at the focal  
35 point of the lens of the collimator and that is drilled with a hole in the location of the optical axis of the generated light beam.

11. The sight as claimed in any one of the preceding claims, characterized in that the lateral position of the reticle is automatically moved laterally by a device controlled by the ballistic computer depending  
5 on the type of munition used and the distance of the target, so as to correct for the deviation in the trajectory of the munition due to the Magnus effect.

12. The sight as claimed in any one of claims 1 to 10,  
10 characterized in that the sight comprises a ballistic computer equipped with an inclinometer that measures the cant of the weapon, the computer determining the cant of the weapon that corrects for the Magnus effect, indications (20, 21) in the sight indicating when this  
15 inclination is achieved.