**Claims**

1. A container for containing a product, comprising a container body having an aperture and a seal assembly, the seal assembly comprising a seal and a seal support member,

wherein the container is configured to have an intermediate configuration prior to containing the product in which the container aperture is temporarily closed by the seal assembly to prevent contamination of the interior space of the container during transportation of the container prior to filling of the container with the product, the seal assembly being removable from the container to open the temporarily closed container aperture for filling the product,

wherein the container is configured to have a filled configuration containing the product in which the container aperture is sealed by the seal alone, without the seal support member present, and

wherein the seal support member and seal are attached by means of a bond in the intermediate configuration, the bond being breakable to allow separation of the seal support member and seal to adopt the filled configuration.

2. The container of claim 1, wherein a shoulder is provided on the container body around the periphery of the aperture, the seal contacting the shoulder in both configurations.

3. The container of claim 1 or 2, wherein the seal is held in place by the seal support member in the intermediate configuration.

4. The container of any preceding claim, wherein the seal support member is configured to be movable into an interference fit with the container body to hold the seal in place in the intermediate configuration.

5. The container of claim 4, wherein the seal support member is provided with projections which, when the seal support member is rotated, engage with corresponding surfaces provided on the container body to provide the interference fit.

6. The container of claim 5, wherein the surfaces project inwardly from the internal periphery of the aperture.

7. The container of claims 2 and 6, wherein the surfaces are provided adjacent to the shoulder.

8. The container of any preceding claim, wherein the seal support member is a disc.

9. The container of any preceding claim, wherein the seal and the seal support member are coterminous.

10. The container of any preceding claim, wherein the seal and the seal support member are coextensive.

11. The container of any preceding claim, wherein the seal is coextensive with the aperture or has a larger area than the area of the aperture.

12. The container of any preceding claim, wherein the container aperture is substantially circular and wherein the seal is a disc.

13. The container of any preceding claim, wherein the bond is breakable by heating.

14. The container of any preceding claim, wherein the container aperture is sealed in the filled configuration by heating the seal.

15. A container for containing a product, comprising a container body having an aperture and a seal assembly, the seal assembly comprising a seal and a seal support member,

wherein the container is configured to have an intermediate configuration prior to containing the product in which the container aperture is closed by the seal assembly, the

seal assembly being removable from the container to open the container aperture for filling the product,

wherein the container is configured to have a filled configuration containing the product in which the container aperture is sealed by the seal alone, without the seal support member present, and

wherein the seal support member and seal are attached by means of a bond in the intermediate configuration, the bond being breakable by heating to allow separation of the seal support member and seal to adopt the filled configuration,

wherein the container aperture is sealed in the filled configuration by heating the seal, and

wherein the heating of the seal simultaneously heats the bond holding the seal support member and seal together to permit separation.

16. The container of any preceding claim, wherein the seal is an induction seal and the container aperture is sealed in the filled configuration by applying electromagnetic energy to heat the seal.

17. The container of any preceding claim, wherein the container further includes a cap.

18. A method of adding a product to a container as claimed in any preceding claim, comprising the steps of:

providing the container in the intermediate configuration, in which the container aperture is temporarily closed by the seal assembly thereby preventing contamination of the interior space of the container during transportation of the container prior to filling of the container with the product;

removing the seal assembly to open the temporarily closed container;

adding the product to the interior of the container;

replacing the seal assembly; and

separating the seal support member from the seal and applying energy to create a seal between the seal and the container so that the container adopts the filled configuration sealed by the seal alone without the seal support member present,

wherein the seal support member and seal are attached by means of a bond in the intermediate configuration, the bond being breakable to allow separation of the seal support member and seal to adopt the filled configuration.

19. The method of claim 18, wherein the bond is breakable by heating.

20. The method of any of claims 18 or 19, wherein the step of applying energy comprises heating the seal.

21. A method of adding a product to a container as claimed in claim 15, comprising the steps of:

providing the container in the intermediate configuration, in which the container aperture is closed by the seal assembly;

removing the seal assembly to open the container;

adding the product to the interior of the container;

replacing the seal assembly; and

separating the seal support member from the seal and applying energy to heat the seal to create a seal between the seal and the container so that the container adopts the filled configuration sealed by the seal alone without the seal support member present,

wherein the seal support member and seal are attached by means of a bond in the intermediate configuration, the bond being breakable by heating to allow separation of the seal support member and seal to adopt the filled configuration, and

wherein the step of heating the seal simultaneously heats the bond holding the seal support member and seal together to permit separation.

22. The method of any of claims 18 to 21, wherein the seal is an induction seal and the step of applying energy comprises applying electromagnetic energy to heat the seal.