

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
17 February 2005 (17.02.2005)

PCT

(10) International Publication Number
WO 2005/014459 A2

(51) International Patent Classification⁷: **B66B**
(21) International Application Number:
PCT/JP2004/010443
(22) International Filing Date: 15 July 2004 (15.07.2004)
(25) Filing Language: English
(26) Publication Language: English
(30) Priority Data:
2003-290863 8 August 2003 (08.08.2003) JP

(71) Applicant (for all designated States except US):
TOSHIBA ELEVATOR KABUSHIKI KAISHA
[JP/JP]; 5-27, Kitashinagawa 6-chome, Shinagawa-ku,
Tokyo, 1410001 (JP).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **FUJITA, Yoshiaki**
[JP/JP].

(74) Agents: **SUZUYE, Takehiko** et al.; c/o SUZUYE &
SUZUYE, 7-2, Kasumigaseki 3-chome, Chiyoda-ku,
Tokyo, 1000013 (JP).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG,
KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG,
MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH,
PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN,
TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,
SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished
upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: GUIDING DEVICES OF ELEVATOR



(57) Abstract: A device, which is provided at a car, for guiding the car along guide rails, the device comprises, a non-contact type of actuator (11) configured to generate a magnetic force which keeps the actuator away from surfaces of a rail by predetermined distances, a unit (12) configured to detect a distance between the rail and the car, a unit (22) configured to determine an amount of displacement of the rail which is caused by a load which generates at time of guiding, based on a value of the magnetic force and the distance, a unit (25) configured to acquire position information regarding the car, a unit (24) configured to calculate an amount of a warp occurring at time of setting the rail, which corresponds to the information, and a unit (21) configured to control the magnetic force based on a total value of the determined amount of the displacement and the amount of the warp.

WO 2005/014459 A2