

CLAIMS

1. A computer-implemented method of base calling a target cluster, the method including:
for the target cluster,
 reading current channel-specific intensities registered for a current sequencing cycle of a sequencing run from a base-specific intensity distribution to which the target cluster is base called at the current sequencing cycle,
 reading current channel-specific distribution intensities from a centroid of the base-specific intensity distribution,
 determining a set of current intensity correction parameters for the current sequencing cycle based on the current channel-specific intensities and the current channel-specific distribution intensities,
 determining a set of current accumulated intensity correction parameters for the current sequencing cycle by accumulating the set of current intensity correction parameters and a set of preceding accumulated intensity correction parameters for a preceding sequencing cycle of the sequencing run,
 determining a current amplification coefficient and current channel-specific offset coefficients for the current sequencing cycle based on the set of current accumulated intensity correction parameters, and
 using the current amplification coefficient and the current channel-specific offset coefficients to correct next channel-specific intensities registered for a next sequencing cycle of the sequencing run and generate corrected next channel-specific intensities for the next sequencing cycle; and
base calling the target cluster at the next sequencing cycle based on the corrected next channel-specific intensities.
2. The computer-implemented method of claim 1, wherein the set of current intensity correction parameters includes the current channel-specific distribution intensities, current channel-specific intensity errors, current distribution centroid-to-origin distance, and current distribution intensity-to-intensity error similarity measure.
3. The computer-implemented method of any of claims 1-2, wherein the current channel-specific intensity errors are channel-wise differences between the current channel-specific intensities and the current channel-specific distribution intensities.

4. The computer-implemented method of any of claims 1-3, wherein the current distribution centroid-to-origin distance is Euclidean distance between the centroid and an origin of a multi-dimensional space that contains the base-specific intensity distribution.
5. The computer-implemented method of any of claims 1-4, wherein the multi-dimensional space is at least one of a cartesian space, a polar space, a cylindrical space, and a spherical space.
6. The computer-implemented method of any of claims 1-5, wherein the current distribution intensity-to-intensity error similarity measure is a summation of channel-wise dot products between the current channel-specific distribution intensities and the current channel-specific intensity errors.
7. The computer-implemented method of any of claims 1-6, wherein the set of current accumulated intensity correction parameters are intensity correction parameter-wise sums of current intensity correction parameters in the set of current intensity correction parameters and preceding accumulated intensity correction parameters in the set of preceding accumulated intensity correction parameters.
8. The computer-implemented method of any of claims 1-7, wherein the set of current accumulated intensity correction parameters are intensity correction parameter-wise averages of the current intensity correction parameters and the preceding accumulated intensity correction parameters.
9. The computer-implemented method of any of claims 1-8, wherein the set of preceding accumulated intensity correction parameters and the set of current accumulated intensity correction parameters are stored in a quantized fixed bit width format.
10. The computer-implemented method of claim 1-9, wherein the current channel-specific offset coefficients are configured to be same.
11. The computer-implemented method of any of claims 1-10, wherein current accumulated intensity correction parameters in the set of current accumulated intensity correction parameters include a first common current accumulated intensity correction parameter for the current channel-specific distribution intensities, and a second common current accumulated intensity correction parameter for the current channel-specific intensity errors.
12. The computer-implemented method of any of claims 1-11, wherein the current channel-specific offset coefficients are channel-wise subtracted from the next channel-specific intensities

to generate next channel-specific shifted intensities, and the next channel-specific shifted intensities are divided by the current amplification coefficient to generate the corrected next channel-specific intensities.

13. The computer-implemented method of any of claims 1-12, further including using a weighting function to combine an initial amplification coefficient with the current amplification coefficient, and initial channel-specific offset coefficients with the current channel-specific offset coefficients to generate a weighted current amplification coefficient and weighted current channel-specific offset coefficients for the current sequencing cycle.

14. The computer-implemented method of any of claims 1-13, wherein the weighting function applies a minimum weight ($w_{\min}$) to initial amplification coefficient and the initial channel-specific offset coefficients, and a maximum weight ($w_{\max}$) to the current amplification coefficient and the current channel-specific offset coefficients, wherein $w_{\min} = (1 - w_{\max})$.

15. The computer-implemented method of any of claims 1-14, wherein the maximum weight ($w_{\max}$) is defined as $(c-p)/c$, where c is an index for the current sequencing cycle and p is a number between 2 to 7.

16. The computer-implemented method of any of claims 1-15, further including using the weighted current amplification coefficient and the weighted current channel-specific offset coefficients to correct the next channel-specific intensities and generate the corrected next channel-specific intensities.

17. The computer-implemented method of any of claims 1-16, further including:
using a maximum likelihood solution to generate, for the current sequencing cycle, respective current maximum likelihood weights for the current amplification coefficient and the current channel-specific offset coefficients;

respectively applying the current maximum likelihood weights to the current amplification coefficient and the current channel-specific offset coefficients to generate a maximum likelihood weighted current amplification coefficient and maximum likelihood weighted current channel-specific offset coefficients for the current sequencing cycle; and

using the maximum likelihood weighted current amplification coefficient and the maximum likelihood weighted current channel-specific offset coefficients to correct the next channel-specific intensities and generate the corrected next channel-specific intensities.

18. The computer-implemented method of any of claims 1-17, further including:
applying a decay factor to the current intensity correction parameters to generate decayed

current intensity correction parameters for the current sequencing cycle; and

determining the current accumulated intensity correction parameters by intensity correction parameter-wise accumulating the decayed current intensity correction parameters and the preceding accumulated intensity correction parameters.

19. The computer-implemented method of any of claims 1-18, wherein the decay factor is kept fixed for a certain number of sequencing cycles of the sequencing run, and exponentially decayed thereafter based on a decay logic.

20. The computer-implemented method of any of claims 1-19, wherein the decay logic is $1 - 1/\tau$, where τ is a predefined number.

21. The computer-implemented method of any of claims 1-20, further including iterating the reading, the determining, the determining, the determining, the using, and the base calling for the target cluster at successive sequencing cycles of the sequencing run.

22. The computer-implemented method of any of claims 1-21, further including executing the reading, the determining, the determining, the determining, the using, and the base calling in parallel for multiple clusters.

23. The computer-implemented method of any of claims 1-22, wherein closed-form expressions for the set of current intensity correction parameters, the set of current accumulated intensity correction parameters, the current amplification coefficient, and the current channel-specific offset coefficients are determined using a least-squares solution.

24. The computer-implemented method of any of claims 1-23, wherein the current channel-specific intensities respectively correspond to intensity channels.

25. The computer-implemented method of any of claims 1-24, wherein the current channel-specific offset coefficients are the channel-wise differences between the current channel-specific intensities and the current channel-specific distribution intensities.

26. A computer-implemented method of base calling a target cluster, the method including:
for the target cluster,
 accessing current intensity data and historic intensity data,
 wherein the current intensity data is for a current sequencing cycle of a sequencing run, and
 wherein the historic intensity data is for one or more preceding sequencing cycles of

the sequencing run,
determining a scale correction coefficient and channel-specific shift correction coefficients based on the current intensity data and the historic intensity data,
using the scale correction coefficient and the channel-specific shift correction coefficients to correct next intensity data and generate corrected next intensity data,
wherein the next intensity data is for a next sequencing cycle of the sequencing run;
and
base calling the target cluster at the next sequencing cycle based on the corrected next intensity data.

27. A computer-implemented method of base calling a target cluster, the method including:
for the target cluster,
accessing current intensity data and historic intensity data,
wherein the current intensity data is for a current sequencing cycle of a sequencing run, and
wherein the historic intensity data is for one or more preceding sequencing cycles of the sequencing run,
using the current intensity data and the historic intensity data to correct next intensity data and generate corrected next intensity data,
wherein the next intensity data is for a next sequencing cycle of the sequencing run;
and
base calling the target cluster at the next sequencing cycle based on the corrected next intensity data.

28. A system including one or more processors coupled to memory, the memory loaded with computer instructions to base call a target cluster, when executed on the processors implement the instructions of claims 1.

29. A system including one or more processors coupled to memory, the memory loaded with computer instructions to base call a target cluster, when executed on the processors implement the instructions of claim 26.

30. A system including one or more processors coupled to memory, the memory loaded with computer instructions to base call a target cluster, when executed on the processors implement the instructions of claim 27.