

LOCATION-BASED GROUP GENERATION METHOD, APPARATUS AND SYSTEM

FIELD OF THE TECHNOLOGY

[0001] The present invention relates to the field of mobile communication and, in particular, to a location-based group generation method, apparatus and system.

BACKGROUND OF THE INVENTION

[0002] With development of the Internet technology, more and more applications can be implemented on a mobile terminal, which improves the user experience in using the mobile terminal. Such numerous applications include a positioning application, which is used to determine a location of a mobile terminal. The positioning application may adopt a Global Positioning System (GPS, Global Positioning System) to locate the mobile terminal. Specifically, a GPS module is set in a mobile terminal to determine the current location of the mobile terminal based on a mobile network. After the location of the mobile terminal has been determined, building information in the area where the mobile terminal resides may be obtained. The building information in each area may be pre-stored in a server of the mobile network, or the building information in a certain area is pre-downloaded to the mobile terminal. After determining the location of the mobile terminal by using the GPS module, the mobile terminal can obtain building information in the area around the location from the server, or obtain the building information in the corresponding area from local. Herein, buildings include restaurants, cinemas, and so on.

[0003] With the development of the positioning application in the Internet technologies, not only the building information in the area around the location point of a first mobile terminal can be obtained, but also other mobile terminals in the area around the location point of the first mobile terminal can be located. The detailed solution is as follows:

[0004] first, an identifier of a mobile terminal to be located is registered on a server of the mobile network, where the identifier may be an email box address, a username or a mobile network number of the mobile terminal;

[0005] then, the mobile terminal to be located creates a link to the server of the mobile network, that is, the user who uses the mobile terminal to be located logs in to a network-side server of the mobile network; and

[0006] then, the mobile terminal to be located uses a GPS module to determine its own location periodically, and reports the determined location and corresponding mobile terminal identifier to the server of the mobile network for storing; and

[0007] finally, after one of the mobile terminals to be located determines its own location by using the GPS module, when this mobile terminal sends a request for acquiring information of other mobile terminals in the area around the location point of this mobile terminal to the server of the mobile network, according to the stored location information of other mobile terminals to be located, the server of the mobile network determines other mobile terminals to be located in the area around the location point of the mobile terminal that sends the request, and sends identifiers of the determined other mobile terminals to the mobile terminal that sends the request.

[0008] In this way, the mobile terminal that sends the request knows other mobile terminals to be located in the area around the location point of this mobile terminal, and,

through the server of the mobile network, exchanges messages with other mobile terminals to be located in the area, for example, performs WeChat transmission, and so on.

[0009] However, although the foregoing solution can locate other mobile terminals in the area around the location point of the first mobile terminal, the messages are exchanged between the first mobile terminal and other mobile terminals in the area around the location point of the first mobile terminal in a point-to-point mode. When notifying information, the first mobile terminal notifies each of the other terminals in the area around the location point of the first mobile terminal in the point-to-point mode, respectively, which is rather complicated and leads to unfavorable experience of the user who uses the first mobile terminal.

SUMMARY OF THE INVENTION

[0010] Therefore, embodiments of the present invention provide a location-based group generation method to create a group that includes a first mobile terminal and other mobile terminals in a location area of the first mobile terminal.

[0011] Embodiments of the present invention further provide a location-based group generation apparatus to create a group that includes a first mobile terminal and other mobile terminals in a location area of the first mobile terminal.

[0012] Embodiments of the present invention further provide a location-based group generation system to create a group that includes a first mobile terminal and other mobile terminals in a location area of the first mobile terminal.

[0013] A location-based group generation method includes:

[0014] storing mobile terminal location information corresponding to mobile terminal identifiers;

[0015] receiving a group generation request that carries a location area from a first mobile terminal;

[0016] determining, according to the stored mobile terminal location information, other mobile terminal identifiers in the location area carried in the group generation request besides a first mobile terminal identifier; and

[0017] setting the determined other mobile terminal identifiers and the first mobile terminal identifier into a group corresponding to a group identifier.

[0018] A location-based group generation system includes mobile terminals and a server, where the mobile terminals include a first mobile terminal and other mobile terminals, where:

[0019] the first mobile terminal is configured to send a group generation request that carries a location area to the server; and

[0020] the server is configured to: store mobile terminal location information corresponding to mobile terminal identifiers, receive the group generation request that carries the location area from the first mobile terminal, determine, according to the stored mobile terminal location information, other mobile terminal identifiers in the location area carried in the group generation request besides a first mobile terminal identifier, and set the determined other mobile terminal identifiers and the first mobile terminal identifier into a group corresponding to a group identifier.

[0021] A location-based group generation apparatus includes a setting module, a storage module, and a transceiver module, where:

[0022] the storage module is configured to store mobile terminal location information corresponding to mobile terminal identifiers;

[0023] the transceiver module is configured to receive a group generation request that carries a location area from a first mobile terminal and send the request to the setting module; and

[0024] the setting module is configured to: determine, according to the mobile terminal location information stored in the storage module, other mobile terminal identifiers in the location area carried in the group generation request besides a first mobile terminal identifier, and set the determined other mobile terminal identifiers and the first mobile terminal identifier into a group corresponding to a group identifier.

[0025] As revealed in the above technical solution, when a server in a mobile network in the present invention receives a group generation request that carries a location area from a first mobile terminal, the server creates a group that includes the first mobile terminal and other mobile terminals in the location area. In this way, the present invention can create a group that includes the first mobile terminal and other mobile terminals in the location area of the first mobile terminal, and forward information in the group. Therefore, when a user who uses the first mobile terminal sends information, the user is free from the trouble of sending the information to the terminals one by one like the prior art, and thus the use is simple and convenient, and the user experience is favorable.

BRIEF DESCRIPTION OF THE DRAWINGS

[0026] FIG. 1 is a flowchart of a location-based group generation method according to an embodiment of the present invention;

[0027] FIG. 2 is a schematic structural diagram of a location-based group generation system according to an embodiment of the present invention; and

[0028] FIG. 3 is a schematic structural diagram of a location-based group generation apparatus according to an embodiment of the present invention.

DETAILED DESCRIPTION OF THE EMBODIMENTS

[0029] To make advantages of the technical solutions of the present invention more comprehensible, the following describes the present invention in detail with reference to accompanying drawings and embodiments of the present invention.

[0030] As revealed in the background description, when a user who uses a first mobile terminal sends a message, the user has to send the message to other mobile terminals in the location area of the first mobile terminal one by one, which is rather complicated and leads to unfavorable user experience. Therefore, the method, the system, and the apparatus provided in the present invention create a group on a server when the server of the mobile network receives a group generation request that carries a location area from the first mobile terminal, where the group includes the first mobile terminal and other mobile terminals in the location area.

[0031] Further, when a group message that carries a group identifier and group information is received from a mobile terminal in the group, the server determines other mobile terminal identifiers in the group corresponding to the group identifier and sends the group information carried in the group message to other mobile terminals in the group.

[0032] In this way, the present invention can create a group that includes the first mobile terminal and other mobile terminals in the location area of the first mobile terminal, and forward information in the group.

[0033] In embodiments of the present invention, the "first mobile terminal" is so termed in order to discriminate it from other mobile terminals, but not to impose a special restriction

on it. Any mobile terminal may send a group generation request, that is, any terminal may serve as the first mobile terminal.

[0034] In embodiments of the present invention, a location point of a location area is a location point of the first mobile terminal or a geographic location specified by the first mobile terminal, where the location area is a circular or rectangular area centered on the location point or the geographic location specified by the mobile terminal and extended to a set distance.

[0035] FIG. 1 is a flowchart of a location-based group generation method according to an embodiment of the present invention. The method includes:

[0036] Step 100: A server stores mobile terminal location information corresponding to mobile terminal identifiers.

[0037] This step is performed by the server beforehand.

[0038] Step 101: The server receives a group generation request that carries a location area from a first mobile terminal.

[0039] In this step, the first mobile terminal and other mobile terminals are all mobile terminals registered on the server. That is, as instructed by the server, after connecting to the server, the first mobile terminal and other mobile terminals report their own mobile terminal location information detected by themselves to the server periodically or at irregular intervals, and the server stores the mobile terminal location information corresponding to the mobile terminals.

[0040] Step 102: According to the stored mobile terminal location information, the server determines other mobile terminal identifiers in the location area carried in the group generation request besides a first mobile terminal identifier.

[0041] In this step, because the first mobile terminal and other mobile terminals report their own mobile terminal location information to the server, the group includes the first mobile terminal and other mobile terminals in the location area.

[0042] Step 103: The server sets the determined other mobile terminal identifiers and the first mobile terminal identifier into a group, and sets an identifier for the group.

[0043] In this step, the first mobile terminal in the group may be identified as a group master.

[0044] In this way, the group is created.

[0045] After the group is created on the server, the server may send the group identifier to mobile terminals in the group.

[0046] Further, in FIG. 1, subsequent steps may include:

[0047] Step 104: The server receives a group message that carries the group identifier and group information from the mobile terminal.

[0048] Step 105: The server determines the group according to the group identifier, and sends the group information carried in the group message to mobile terminals in the corresponding group except the mobile terminal that sends the group message.

[0049] The first mobile terminal may download a map of the area around the location of the first mobile terminal from the server, and display the map on a user interface of the first mobile terminal. When the first mobile terminal sends a group generation request that carries a location area, the first mobile terminal receives the group generation request, which carries the location area and is input by the user through the user interface. For example, the user may use a touchscreen input mode or a character input mode to specify an area by drawing a rectangle or a circle on the map, so as to search for other mobile terminals in the area, where the search area is a specified area or an area around a location point of the first mobile

terminal, and is a circular or rectangular area centered on the location point of the first mobile or a geographic location specified by the first mobile terminal and extended to a set distance. The location point in the area may be a geographic location point of the first mobile terminal of the user (that is, the location point of the first mobile terminal), or a geographic location point specified by the user on the first mobile terminal by using a map or by other means.

[0050] In an embodiment of the present invention, after the server creates a group for the first mobile terminal, the first mobile terminal can perform group activities by sending a group message that carries the group identifier and group information. For example, when initiating a group activity, the first mobile terminal sends group information including a place, time, and content of the activity, and so on, so as to invite users of other mobile terminals in the group to join the activity; or when initiating a group session, the first mobile terminal sends group information including session content, so as to perform session interaction in the group. Other mobile terminals in the group may also perform a group activity by sending a group message.

[0051] In an embodiment of the present invention, the method further includes:

[0052] The server receives a group message that carries a group identifier and group information from a mobile terminal other than the first mobile terminal that sends the group generation request; and the server determines a group corresponding to the group identifier, and sends the group information carried in the group message to mobile terminals in the group corresponding to the group identifier except the mobile terminal that sends the group message.

[0053] Here, any other mobile terminal may also be linked onto the server to obtain the group identifier of the group that includes the mobile terminal from the server, so as to send a group message in the group.

[0054] In an embodiment of the present invention, the method further includes:

[0055] The server deletes a stored group corresponding to a group identifier carried in a group deletion message after receiving the group deletion message that carries the group identifier from the first mobile terminal.

[0056] Before the deletion, the server needs to determine whether the received group deletion message is a group deletion message sent by the first mobile terminal; and, if so, performs the deletion, or, if the group deletion message is sent by another mobile terminal in the group, the deletion is not performed.

[0057] FIG. 2 is a schematic structural diagram of a location-based group generation system according to an embodiment of the present invention. The system includes mobile terminals and a server 23, where the mobile terminals include a first mobile terminal (this mobile terminal) 21 and other mobile terminals 22, where:

[0058] The first mobile terminal 21 is configured to send a group generation request that carries a location area to the server 23; and

[0059] The server 23 is configured to: store mobile terminal location information corresponding to mobile terminal identifiers, receive the group generation request that carries the location area from the first mobile terminal 21, determine, according to the stored mobile terminal location information, other mobile terminal identifiers in the location area carried in the group generation request besides a first mobile terminal identifier, and set the determined other mobile terminal identifiers and the first mobile terminal identifier into a group corresponding to a group identifier.

[0060] In the system, the server 23 is further configured to send the group identifier to mobile terminals in the group.

[0061] In the system, mobile terminals in the group are further configured to send and receive a group message that carries the group identifier and group information.

[0062] The server 23 is further configured to receive the group message that carries the group identifier and the group information from the mobile terminal in the group, determine the group corresponding to the group identifier, and send the group information carried in the group message to other mobile terminals 22 in the corresponding group.

[0063] In the system, the first mobile terminal 21 is further configured to send a group deletion message that carries a group identifier to the server 23; and

[0064] The server 23 is further configured to receive the group deletion message that carries the group identifier from the first mobile terminal 21 and delete the group corresponding to the group identifier.

[0065] In the system, the mobile terminal location information stored in the server 23 is reported by the first mobile terminal 21 and other mobile terminals 22 as instructed by the server after the first mobile terminal 21 and other mobile terminals 22 perform a self-detection respectively.

[0066] FIG. 3 is a schematic structural diagram of a location-based group generation apparatus according to an embodiment of the present invention. The apparatus is a server, including a setting module 31, a storage module 32, and a transceiver module 33, where:

[0067] the storage module 32 is configured to store mobile terminal location information corresponding to mobile terminal identifiers;

[0068] the transceiver module 33 is configured to receive a group generation request that carries a location area from a first mobile terminal and send the request to the setting module 31; and

[0069] the setting module 31 is configured to: determine, according to the mobile terminal location information stored in the storage module 32, other mobile terminal identifiers in the location area carried in the group generation request besides a first mobile terminal identifier, and set the determined other mobile terminal identifiers and the identifier of the first mobile terminal into a group corresponding to a group identifier.

[0070] In the apparatus, the transceiver module 33 is further configured to send the group identifier to mobile terminals in the group.

[0071] In the apparatus, the transceiver module 33 is further configured to receive a group message that carries the group identifier and the group information from the mobile terminal in the group, determine a group corresponding to the group identifier in the setting module 31, and send the group information carried in the group message to the mobile terminals in the determined corresponding group corresponding to the group identifier except the mobile terminal that sends the group message.

[0072] The apparatus further includes a deleting module (not illustrated in the figure), which is configured to delete a group corresponding to a group identifier after the receiving module receives a group deletion message that carries the group identifier from the first mobile terminal.

[0073] In the apparatus, the mobile terminal location information stored by storage module 32 is reported by the first mobile terminal and other mobile terminals through the transceiver module as instructed by the server after the first mobile terminal and other mobile terminals perform a self detection respectively.

[0074] With the method, system and apparatus provided in embodiments of the present invention, the user that uses the first mobile terminal can generate a group specific to a pertinent geographical area based on a location area. The user of the first mobile terminal in

the group and the users of other mobile terminals can discuss issues that they are all interested in, or join an activity that they are all interested in, thereby improving the means of group collaboration, increasing flexibility of group collaboration, making it easier and more flexible to generate a group, and enhancing user experience and substantive communication.

[0075] The methods disclosed in embodiments of the present invention may be embodied in the form of a computer software product. The computer software product is stored in a storage medium, such as a floppy disk, a hard disk, or an optical disk of the computer, and contains several instructions used to instruct a computer device (for example, a personal computer, a server, or a network device) to perform the method disclosed in each embodiment of the present invention, or a universal hardware device is configured as a device of the present invention to implement the solution disclosed in each embodiment of the present invention. The universal hardware device may be a memory, such as a ROM-RAM, used for storing instructions, or may be a processor, such as a CPU, coupled with the memory and configured to execute the instructions stored in the memory.

[0076] The foregoing descriptions are merely preferred embodiments of the present invention, but are not intended to limit the protection scope of the present invention. Any modifications, equivalent substitutions, and improvements made within the spirit and principles of the present invention shall fall within the protection scope of the present invention.

CLAIMS

1. A location-based group generation method, comprising:
 - storing mobile terminal location information corresponding to mobile terminal identifiers;
 - receiving a group generation request that carries a location area from a first mobile terminal;
 - determining, according to the stored mobile terminal location information, other mobile terminal identifiers in the location area carried in the group generation request besides a first mobile terminal identifier; and
 - setting the determined other mobile terminal identifiers and the first mobile terminal identifier into a group corresponding to a group identifier.
2. The method according to claim 1, wherein:
 - the mobile terminal location information is reported by mobile terminals after a self-detection.
3. The method according to claim 1, wherein:
 - a location point in the location area is one of a location point of the first mobile terminal and a geographic location specified by the first mobile terminal.
4. The method according to claim 3, wherein:
 - the location area is one of a circular and a rectangular area centered on one of the location point and the geographic location specified by the first mobile terminal and extended to a specific distance.
5. The method according to claim 1, further comprising:

receiving a group message that carries a group identifier and group information from a mobile terminal in the group, determining a group corresponding to the group identifier, and sending the group information carried in the group message to mobile terminals in the group corresponding to the group identifier except the mobile terminal that sends the group message.

6. The method according to claim 1, further comprising:

receiving a group deletion message that carries the group identifier from the first mobile terminal, and deleting the group corresponding to the group identifier.

7. The method according to claim 1, further comprising:

sending the group identifier to mobile terminals in the group.

8. A location-based group generation system, comprising mobile terminals and a server, wherein the mobile terminals comprise a first mobile terminal and other mobile terminals, wherein:

the first mobile terminal is configured to send a group generation request that carries a location area to the server; and

the server is configured to: store mobile terminal location information corresponding to mobile terminal identifiers, receive the group generation request that carries the location area from the first mobile terminal, determine, according to the stored mobile terminal location information, other mobile terminal identifiers in the location area carried in the group generation request besides a first mobile terminal identifier, and set the determined other mobile terminal identifiers and the first mobile terminal identifier into a group corresponding to a group identifier.

9. The system according to claim 8, wherein:

the server is further configured to send the group identifier to mobile terminals in the group.

10. The system according to claim 9, wherein:

mobile terminals in the group are further configured to send and receive a group message that carries the group identifier and group information; and

the server is further configured to receive the group message that carries the group identifier and the group information from the mobile terminal in the group, determine a group corresponding to the group identifier, and send the group information carried in the group message to the mobile terminals in the group corresponding to the group identifier except the mobile terminal that sends the group message.

11. The system according to claim 8, wherein:

the first mobile terminal is further configured to send a group deletion message that carries the group identifier to the server; and

the server is further configured to receive the group deletion message that carries the group identifier from the first mobile terminal, and delete the group corresponding to the group identifier.

12. A location-based group generation apparatus, comprising a setting module, a storage module, and a transceiver module, wherein:

the storage module is configured to store mobile terminal location information corresponding to mobile terminal identifiers;

the transceiver module is configured to receive a group generation request that carries a location area from a first mobile terminal and send the request to the setting module; and

the setting module is configured to: determine, according to the mobile terminal location information stored in the storage module, other mobile terminal identifiers in the location area

carried in the group generation request besides a first mobile terminal identifier, and set the determined other mobile terminal identifiers and the first mobile terminal identifier into a group corresponding to a group identifier.

13. The apparatus according to claim 12, wherein:

the transceiver module is further configured to send the group identifier to mobile terminals in the group.

14. The apparatus according to claim 12, wherein:

the transceiver module is further configured to receive a group message that carries the group identifier and the group information from a mobile terminal in the group, determine a group corresponding to the group identifier in the setting module, and send the group information carried in the group message to mobile terminals in the determined group corresponding to the group identifier except the mobile terminal that sends the group message.

15. The apparatus according to claim 12, further comprising:

a deleting module, configured to delete the group corresponding to the group identifier after the receiving module receives a group deletion message that carries the group identifier from the first mobile terminal.