# CLAIMS

1. A method for operating a service object, applied to a first terminal, and comprising:

receiving a data acquisition apparatus enabling request sent by a second terminal;

obtaining first person's behavior data;

generating a first service object control instruction corresponding to the first person's behavior data according to a preset correspondence between multiple first person's behavior data and multiple first service object control instructions; and

sending the first service object control instruction to the second terminal, so that the second terminal displays a service object based on the first service object control instruction,

wherein obtaining the first person's behavior data comprises:

obtaining the first person's behavior data when a user confirmation operation based on the data acquisition apparatus enabling request is detected,

wherein generating the first service object control instruction corresponding to the first person's behavior data comprises:

determining whether the first person's behavior data matches trigger data for a preset service object starting instruction;

generating the first service object control instruction when the first person's behavior data matches the trigger data for the preset service object starting instruction; and

displaying, on the first terminal, prompt information for a result indicating that the first person's behavior data does not match the trigger data for the preset service object starting instruction when the first person's behavior data does not match the trigger data for the preset service object starting instruction.

2. The method according to claim 1, wherein the step of obtaining the first person's behavior data further comprises:

obtaining the first person's behavior data by a data acquisition apparatus, the

data acquisition apparatus comprising: a data acquisition apparatus of the first terminal, or a data acquisition apparatus of a smart device associated with the first terminal.

3. The method according to claim 2, wherein the data acquisition apparatus comprises at least one of: a video image acquisition apparatus, an infrared data acquisition apparatus, or an ultrasonic data acquisition apparatus; the video image acquisition apparatus comprises a camera of the first terminal.

4. The method according to any one of claims 1 to 3, wherein the first person's behavior data comprises at least one of: body movement data, gesture movement data, facial movement data, or facial expression data.

5. The method according to any one of claims 1 to 4, wherein the service object comprises a game.

6. A method for operating a service object, applied to a second terminal, comprising:

sending a data acquisition apparatus enabling request to a first terminal, the data acquisition apparatus enabling request being used for enabling a data acquisition apparatus corresponding to the first terminal, so that the first terminal obtains the first person's behavior data when a user confirmation operation based on the data acquisition apparatus enabling request is detected;

receiving a first service object control instruction sent by the first terminal;

generating a second service object control instruction corresponding to second person's behavior data according to a preset correspondence between multiple second person's behavior data and multiple second service object control instructions, the second person's behavior data being obtained by the second terminal; and

displaying a service object based on the first service object control instruction and the second service object control instruction,

wherein generating the second service object control instruction corresponding to the second person's behavior data comprises:

determining whether the second person’s behavior data matches a preset control behavior for the service object;

generating the second service object control instruction when the second person’s behavior data matches the preset control behavior for the service object; and

displaying, on the second terminal, prompt information for a result indicating that the second person’s behavior data does not match the preset control behavior for the service object when the second person’s behavior data does not match the preset control behavior for the service object.

7. The method according to claim 6, wherein the step of displaying the service object based on the first service object control instruction and the second service object control instruction comprises:

obtaining a first operation result corresponding to the first service object control instruction, and a second operation result corresponding to the second service object control instruction; and

displaying the first operation result and the second operation result.

8. The method according to claim 6 or 7, further comprising:

displaying first behavior data and second behavior data, the first behavior data being behavior data corresponding to the first operation result, and the second behavior data being behavior data corresponding to the second operation result.

9. The method according to any one of claims 6 to 8, further comprising:

displaying the service object and a current video image in a split-screen manner; or

displaying the service object and the current video image in a picture-in-picture manner, the display size of the current video image being less than that of the service object.

10. The method according to any one of claims 6 to 9, further comprising:

obtaining the second person’s behavior data by a data acquisition apparatus,

the data acquisition apparatus comprising: a data acquisition apparatus of the second terminal, or a data acquisition apparatus of a smart device associated with the second terminal.

11. The method according to claim 10, wherein the data acquisition apparatus comprises at least one of: a video image acquisition apparatus, an infrared data acquisition apparatus, or an ultrasonic data acquisition apparatus; the video image acquisition apparatus comprises a camera of the second terminal.

12. The method according to any one of claims 6 to 11, wherein the second person's behavior data comprises at least one of: body movement data, gesture movement data, facial movement data, or facial expression data.

13. The method according to any one of claims 6 to 12, wherein the service object comprises a game.

14. An apparatus for operating a service object, applied to a first terminal, and comprising:

a first receiving module, configured to receive a data acquisition apparatus enabling request sent by a second terminal;

a first obtaining module, configured to obtain first person's behavior data;

a first generating module, configured to generate a first service object control instruction corresponding to the first person's behavior data according to a preset correspondence between multiple first person's behavior data and multiple first service object control instructions; and

a first sending module, configured to send the first service object control instruction to the second terminal, so that the second terminal displays a service object based on the first service object control instruction,

wherein the first obtaining module comprises:

a second obtaining sub-module, configured to obtain the first person's behavior data when a user confirmation operation based on the data acquisition

apparatus enabling request is detected,

wherein the first generating module comprises:

a first data determining sub-module, configured to determine whether the first person's behavior data matches trigger data for a preset service object starting instruction; and

a first instruction generating sub-module, configured to generate the first service object control instruction when the first person's behavior data matches the trigger data for the preset service object starting instruction; and display, on the first terminal, prompt information for a result indicating that the first person's behavior data does not match the trigger data for the preset service object starting instruction when the first person's behavior data does not match the trigger data for the preset service object starting instruction.

15. The apparatus according to claim 14, wherein the first obtaining module comprises:

a first obtaining sub-module, configured to obtain the first person's behavior data by a data acquisition apparatus, the data acquisition apparatus comprising: a data acquisition apparatus of the first terminal, or a data acquisition apparatus of a smart device associated with the first terminal.

16. The apparatus according to claim 15, wherein the data acquisition apparatus comprises at least one of: a video image acquisition apparatus, an infrared data acquisition apparatus, or an ultrasonic data acquisition apparatus; the video image acquisition apparatus comprises a camera of the first terminal.

17. The apparatus according to any one of claims 14 to 16, wherein the first person's behavior data comprises at least one of: body movement data, gesture movement data, facial movement data, or facial expression data.

18. The apparatus according to any one of claims 14 to 17, wherein the service object comprises a game.

19. An apparatus for operating a service object, applied to a second terminal, and comprising:

a second sending module, configured to send a data acquisition apparatus enabling request to a first terminal, the data acquisition apparatus enabling request being used for enabling a data acquisition apparatus corresponding to the first terminal, so that the first terminal obtains the first person's behavior data when a user confirmation operation based on the data acquisition apparatus enabling request is detected;

a second receiving module, configured to receive a first service object control instruction sent by the first terminal;

a second generating module, configured to generate a second service object control instruction corresponding to second person's behavior data according to a preset correspondence between multiple second person's behavior data and multiple second service object control instructions, the second person's behavior data being obtained by the second terminal; and

a service object displaying module, configured to display a service object based on the first service object control instruction and the second service object control instruction,

wherein the second generating module comprises:

a second data determining sub-module, configured to determine whether the second person's behavior data matches a preset control behavior for the service object; and

a second instruction generating sub-module, configured to generate the second service object control instruction when the second person's behavior data matches the preset control behavior for the service object; and display, on the second terminal, prompt information for a result indicating that the second person's behavior data does not match the preset control behavior for the service object when the second person's behavior data does not match the preset control behavior for the service object.

20. The apparatus according to claim 19, wherein the service object displaying module comprises:

an operation result obtaining sub-module, configured to obtain a first operation result corresponding to the first service object control instruction, and a second operation result corresponding to the second service object control instruction; and

an operation result displaying sub-module, configured to display the first operation result and the second operation result.

21. The apparatus according to claim 19 or 20, further comprising:

a behavior data displaying module, configured to display first behavior data and second behavior data, the first behavior data being behavior data corresponding to the first operation result, and the second behavior data being behavior data corresponding to the second operation result.

22. The apparatus according to any one of claims 19 to 21, further comprising:

a service object and video image displaying module, configured to display the service object and a current video image in a split-screen manner; or to display the service object and the current video image in a picture-in-picture manner, the display size of the current video image being less than that of the service object.

23. The apparatus according to any one of claims 19 to 22, further comprising:

a second obtaining module, configured to obtain the second person’s behavior data by a data acquisition apparatus, the data acquisition apparatus comprising: a data acquisition apparatus of the second terminal, or a data acquisition apparatus of a smart device associated with the second terminal.

24. The apparatus according to claim 23, wherein the data acquisition apparatus comprises at least one of: a video image acquisition apparatus, an infrared data acquisition apparatus, or an ultrasonic data acquisition apparatus; the video image acquisition apparatus comprises a camera of the second terminal.

25. The apparatus according to any one of claims 19 to 24, wherein the second person’s behavior data comprises any one or any combination of: body movement data, gesture movement data, facial movement data, and facial expression data.

26. The apparatus according to any one of claims 19 to 25, wherein the service object comprises a game.

27. An electronic device, comprising a processor and a memory, wherein

the memory is configured to store at least one executable instruction, and the executable instruction enables the processor to perform corresponding operations of the method for operating a service object according to any one of claims 1 to 13.

28. An electronic device, comprising:

a processor and the apparatus for operating a service object according to any one of claims 14 to 26, wherein

when the processor runs the apparatus for operating a service object, units in the apparatus for operating a service object according to any one of claims 14 to 26 are run.

29. A computer program, comprising a computer-readable code, wherein when the computer-readable code is running in a device, a processor in the device executes instructions for implementing the steps of the method for operating a service object according to any one of claims 1 to 13.

30. A computer-readable storage medium, configured to store computer-readable instructions, wherein when the instructions are executed, the operations in the steps of the method for operating a service object according to any one of claims 1 to 13 are implemented.