



(43) International Publication Date
25 April 2013 (25.04.2013)

(10) International Publication Number
WO 2013/057250 A1

- (51) **International Patent Classification:**
B65D 17/00 (2006.01) *B21D 51/44* (2006.01)
B21D 22/06 (2006.01)
- (21) **International Application Number:**
PCT/EP2012/070756
- (22) **International Filing Date:**
19 October 2012 (19.10.2012)
- (25) **Filing Language:** English
- (26) **Publication Language:** English
- (30) **Priority Data:**
1118284.7 21 October 2011 (21.10.2011) GB
- (71) **Applicant: CROWN PACKAGING TECHNOLOGY, INC.** [US/US]; 11535 South Central Avenue, Alsip, Illinois 60803-2599 (US).
- (72) **Inventor; and**
- (71) **Applicant (for US only): DUNWOODY, Paul Robert** [GB/GB]; 3, Witan Way, Wantage Oxfordshire OX12 9EU (GB).
- (74) **Agents: RUSSELL, JOHN ALISTAIR et al.;** Hoffmann . Eitle, Arabellastrasse 4, 81925 Munich (DE).
- (81) **Designated States** (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM,

AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

- (84) **Designated States** (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report (Art. 21(3))
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))

(54) **Title:** CAN END




FIG. 4

(57) **Abstract:** There is disclosed herein a can end (10) for a can for pressurized contents, the can end being configured to be joined by a peripheral annular joining portion (24,26) to one axial end of a can body of the can and having an outer side arranged to face outwardly from the can and an inner side arranged to face inwardly into the can, the can end comprising: a central panel (18); a panel wall (20) annularly surrounding the central panel and extending axially inwardly and radially outwardly from the central panel; an annular chuck wall structure (12, 14, 50) extending radially- and axially-inwardly from the joining portion; and an annular bead (16) which is connected between a radially outer edge (38) of the panel wall and a radially inner edge (50e) of the chuck wall structure and which is concave with respect to the outer side of the can end and extends at least partially radially outwardly with respect to the radially inner edge of the chuck wall structure, wherein wall portions adjacent inner and outer ends of the concave annular bead (16) form a bead mouth (m) that is open towards the outer side of the can end.



WO 2013/057250 A1