

Description

The present invention relates to additives suitable for use as extreme pressure (EP)/anti-wear (AW) additives and/or antioxidants in lubricating oil compositions and/or AW/lubricity agents and/or antioxidants in middle distillate fuels compositions and to lubricating oil compositions and middle distillate fuels compositions containing such.

The use of zinc dialkyl dithiophosphates (ZDTPs) as additives in lubricating oils for the purpose of improving the wear and corrosion characteristics of the oil has long been known from, for example GB Patents Nos. 957,017; 1,358,478 and 1,565,961.

Despite the fact that ZDTPs have been very effective and very successful in a number of engine lubricating oils, it is presently considered desirable to reduce the phosphorus content of the finished lubricating oil by the provision of alternative and/or supplementary additives for the purpose of reducing environmental pollution.

The use of sulphurised materials as EP/AW additives in lubricating oil compositions is also well-known from, for example, US Patent Nos. 3953347. USP 3953347 discloses sulphurised compositions prepared by reacting, at about 100 to 250°C, sulphur with a mixture comprising (A) 100 parts by weight of at least one fatty acid ester, (B) about 0 to 50 parts by weight of at least one fatty acid, and (C) about 25 to 400 parts by weight of at least one aliphatic olefin containing about 8 to 36 carbon atoms.

US 3915873 relates to a lubricating composition comprising a major amount of oil and an antiwear amount of a cosulphurised C_7 - C_{40} alkyl phenol and fatty acid ester of a C_{10} - C_{30} fatty acid and a C_1 - C_{30} alkanol or alkenol.

According to the present invention there is provided an additive suitable for use as an extreme pressure/anti-wear additive in lubricating oil comprising the product obtainable by reacting at elevated temperature a mixture comprising (i) sulphur, (ii) at least one C_{10} to C_{100} unsaturated carboxylic acid, or amide or acid salt thereof and (iii) at least one hydrocarbyl-substituted phenol, the amount of (iii) in the mixture being 15 to 65% by weight based on the combined weight of (i) (ii) and (iii).

The present invention also provides an additive suitable for use as an extreme pressure/anti-wear additive in lubricating oil comprising the product obtainable by reacting at elevated temperature a mixture comprising (i) sulphur, (ii) at least one C_{10} to C_{100} unsaturated carboxylic acid and (iii) at least one hydrocarbyl-substituted phenol, the amount of (i) in the mixture being from 1 to 25% by weight based on the combined weight of (ii) and (iii), the amount of (ii) in the mixture being 20 to 85% by weight based on the combined weight of (i), (ii) and (iii), and the amount of (iii) in the mixture being 15 to 65% by weight based on the combined weight of (i), (ii) and (iii).

Sulphur (component (i)) is preferably in the form of elemental sulphur, although other sources can be used for example sulphur monohalides or sulphur dihalides.

The unsaturated carboxylic acid (component (ii)) is preferably a C_{14} to C_{22} unsaturated carboxylic acid. It may be a straight-chain or branched-chain acid and may be mono-, di- or poly-unsaturated. The acid may be mono-, di- or poly-basic. Examples of suitable acids include oleic acid, linoleic acid, linolenic acid, and the like. Mixtures of acids, for example rape top fatty acid and tall oil fatty acid, may also be employed.

Alternatively, or in addition, acid derivatives, for example amides, or acid salts eg of calcium or sodium may be used.

The hydrocarbyl-substituted phenol (component (iii)) may suitably be an alkyl phenol. The alkyl substituent (or substituents) of the alkyl phenol may suitably be C_8 to C_{100} , preferably C_8 to C_{24} , alkyl groups which may be straight-chain or branched-chain. The alkyl phenol may be a monoalkyl phenol or a polyalkyl phenol; where the alkyl phenol is a polyalkyl phenol it is preferably a dialkyl phenol; a particularly suitable dialkyl phenol is dinonyl phenol. The alkyl group (or groups) may be ortho, meta or para in relation to the hydroxyl function of the phenol.

In addition to the components (i) to (iii) the mixture may also contain at least one olefin and/or at least one mercaptan and/or a lubricating oil as a diluent.

The olefin may be either a mono-, di- or polyolefin, which may contain from 6 to 100 carbon atoms. Both internal and terminal olefins may be employed. Suitable olefins include C_{18} -alpha olefins, propylene tetramer, isobutene oligomers and polyisobutenes.

Both aliphatic and aromatic mercaptans may be employed. Examples of suitable mercaptans include 1-dodecanethiol, 2-mercaptobenzothiazole and 2,5-dimercapto-1,3,4-thiadiazole.

The olefin and/or mercaptan and/or lubricating oil as a diluent may suitably be present in an amount sufficient to provide from 0 to 65% by weight in the final product.

Sulphurisation promoters may also be employed if desired. Suitable promoters include organic or inorganic bases, aliphatic alcohols, glycols and glycol ethers. Examples of suitable promoters include diphenylamine, di-butylamine, calcium hydroxide, sodium hydroxide, butanol, ethylene glycol, 1,2-propane diol and methyldiglycol, preferably diphenylamine.

The elevated temperature at which the mixture is reacted may suitably be in the range from 100 to 250, preferably from 130 to 200°C. Reaction may suitably be carried out at atmospheric pressure, optionally with agitation and/or nitrogen sparging. Alternatively, elevated pressure may be employed.

Finally, it is preferred to filter the product.

In another aspect the present invention provides a lubricating oil composition comprising a major proportion of an lubricating oil base stock and a minor proportion of the additive as hereinbefore described.

The amount of the additive present in the lubricating oil composition will vary depending on the nature of the lubricating oil base stock and its field of application, for example automotive, marine or industrial, but will generally be in the range from 0.01 to 10%, more generally from 0.1 to 5% w/w.

The lubricating oil base stock may be any oil of lubricating viscosity, which may be a mineral oil or a synthetic lubricating oil. Suitable mineral oils include both solvent extracted or solvent refined oils obtained in accordance with conventional methods of treating lubricating oils. The base oil may be derived from paraffinic, naphthenic, asphaltic or mixed base crudes. Alternatively, the base oil may be a synthetic oil, or a mixture thereof with mineral oil.

In addition, the lubricating oil composition may contain conventional additives, for example dispersants, detergents, VI improvers, anti-oxidants, pour-point depressants, or the like.

The additives of the present invention have good EP/AW and antioxidant properties, as will be demonstrated hereinafter, and maintain good compatibility with other lubricating oil additives and base oils. Moreover, they are essentially non-corrosive to copper and engine bearings.

Lubricating oil additives are generally manufactured and marketed in the form of a concentrate for subsequent blending into finished lubricating oils.

In another embodiment of the invention there is provided a lubricating oil additive concentrate for use in the production of finished lubricating oils which comprises a lubricating oil base stock and an additive as hereinbefore described in a concentration of from 2 to 20 % w/w based on the weight of the additive concentrate.

The lubricating oil base stock may be any of the aforescribed lubricating oils, but is preferably a solvent neutral oil. As an alternative to incorporating conventional additives directly in the finished lubricating oil composition some or all of them may be incorporated with the additive in the additive concentrate.

The invention will now be further illustrated by reference to the following Examples and Comparison Tests; the latter, although not illustrative of the invention, are included only for purposes of comparison.

(A) PREPARATION OF ADDITIVES

Example 1

(a) Reaction Mixture:

C ₁₂ - alkyl phenol	= 92.0 g
Rape top fatty acid	= 232.0 g
C ₁₈ - alpha olefin	= 84.1 g
Diphenylamine	= 2.5 g
Sulphur	= 51.7 g

(b) Method

(i) The reaction mixture (a) was heated to 180-190°C and held at this temperature for 20 hours with a nitrogen sparge.

(ii) The mixture was stripped at 150°C/10 mm Hg/60 minutes.

(iii) The reaction product was filtered.

(c) Product Weight

Crude product = 405 g

(d) Product Composition

Sulphur	= 8.81% w/w
Alkyl phenol	= 22.7% w/w

Example 2

(a) Reaction Mixture

C ₁₂ -alkyl phenol	= 84.0 g
Rape top fatty acid	= 92.8 g
C ₁₈ -alpha olefin	= 0 g
Diphenylamine	= 2 g

Sulphur = 20.6 g

(b) Method

The procedure of Example 1(b) was repeated.

(c) Product Weight

Crude product = 177 g

(d) Product Composition

Sulphur = 7.49% w/w

Alkyl phenol = 47.5% w/w

Comparison Test 1

(a) Reaction Mixture

C₁₂-Alkyl phenol = 0 g

Rape top fatty acid = 1000.0 g

C₁₈-alpha olefin = 0 g

Diphenylamine = 0 g

Sulphur = 113.3 g

(b) Method

The procedure of Example 1(b) was repeated except that in step (ii) the mixture was stripped at 200°C instead of 150°C.

(c) Product Weight

Crude product = 972 g

(d) Product Composition

Sulphur = 9.40% w/w

Alkyl phenol = 0% w/w

Comparison Test 2

(a) Reaction Mixture

C₁₂-Alkyl phenol = 7.8 g

Rape top fatty acid = 81.2 g

C₁₈-alpha olefin = 0 g

Diphenylamine = 0.9 g

Sulphur = 10.1 g

(b) Method

The procedure of Example 1(b) was repeated.

(c) Product Weight

Crude product = 89 g

(d) Product Composition

Sulphur = 9.10% w/w

Alkyl phenol = 8.8% w/w

Comparison Test 3

(a) Reaction Mixture

C₁₂-Alkyl phenol = 42.7 g

Rape top fatty acid = 280.9 g

C₁₈-alpha olefin = 84.1 g

Diphenylamine = 2.5 g

Sulphur = 51.7 g

(b) Method

The procedure of Example 1(b) was repeated.

(c) Product Weight

Crude product = 414 g

(d) Product Composition

Sulphur = 8.95 g

Alkyl phenol = 10.3% w/w

Comparison Test 4(a) Reaction Mixture

C ₁₂ -Alkyl phenol	= 344.2 g
Rape top fatty acid	= 0 g
C ₁₈ -alpha olefin	= 0 g
Diphenylamine	= 0 g
Sulphur	= 68.8 g
Ethylene glycol	= 76.5 g
Lime	= 8.4 g

(b) Method

- (i) The reaction mixture (a) was stirred at 165°C for 1 hour.
- (ii) The mixture was stripped at 200°C/10 mm Hg/90 minutes.
- (iii) The product was filtered.

(c) Product Weight

Crude product	= 380 g (prior to filtration)
Lights	= 90 g

(d) Product Composition

Sulphur	= 9.5% w/w
Alkyl phenol	= 90.6% w/w

Comparison Tests 1 to 4 are not examples in accordance with the present invention because the alkyl phenol content in the mixture was not in the range from 15 to 65% w/w based on the combined weight of sulphur, carboxylic acid and phenol in the mixture as hereinbefore defined. The Tests are included only for the purpose of comparison.

(B) Testing of Additive CompositionsShell-Seta Four-Ball Test

The products of Examples 1 and 2 and Comparison Tests 1 to 3 were diluted with SN150 base oil. In addition, commercially available ZDTP was also diluted with 150SN base oil. The diluted additive compositions were tested for EP/AW properties in the Shell-Seta Four-Ball Test. This test involved pressing a rotating steel ball against a triangle of three stationary balls lubricated with the composition under test. The Initial Seizure Load (ISL), the Weld Load (WL) and the Scar Size after 1 hour at 40 kg load (AW) were determined. The results of the Test are given in Table 1.

Rotary Bomb Oxidation Test

The products of Examples 1 and 2 and Comparison Tests 1 to 4 and a ZDTP (identical to that used above) all diluted with SN150 base oil as in the Shell-Seta Four Ball Test were tested for antioxidant activity in the Rotary Bomb Oxidation Test. The time taken to achieve a 25 psi oxygen pressure drop (T) was determined. the results are given in Table 2.

Copper Strip Test

The products of Examples 1 and 2 and Comparison Tests 1 to 4 and a ZDTP (as used in the previous tests) all diluted with SN150 base oil as in the Shell-Seta Four Ball Test were tested for their corrosivity to copper in the Copper Strip Test. The copper strip ratings were determined at 150°C after 3 hours in conventional manner according to the following:-

- 1A - 1B slight tarnish
- 2A - 2F moderate tarnish
- 3A - 3B dark tarnish
- 4A - 4C corrosion

The results of the Test are given in Table 2.

TABLE 1

REFERENCE	CONCN wt % in SN150	ISL kg	WL kg	AW mm
Example 1	0.3	105	150	0.85
Example 2	0.3	110	150	0.68
Comp. Test 1	0.3	73	150	0.32
Comp. Test 2	0.3	75	160	0.34
Comp. Test 3	0.3	100	140	0.65
ZDTP	1.0	85	140	ND
SN150	-	40	117	1.75

The results presented in Table 1 demonstrate that the additive compositions according to the invention are superior EP/AW agents to the Comparison Test additive compositions and the ZDTP.

TABLE 2

REFERENCE	CONCN % in SN150	RBOT T mins	COPPER STRIP RATING
Example 1	0.3	92.5	1B
Example 2	0.3	84.0	1B
Comp. Test 1	0.3	35.5	1B
Comp. Test 2	0.3	33.5	1B
Comp. Test 3	0.3	35.5	1B
Comp. Test 4	0.3	33.5	3B (1.0%)
ZDTP	0.3	80.0	ND
SN150	-	25.5	1B

The results presented in Table 2 demonstrate that the additives according to the invention have significantly improved antioxidant properties as compared with the Comparison Test additives and are roughly equal in antioxidant performance to the ZDTP. The additive according to the invention are no more corrosive to copper than the additives of the Comparison Tests.

Claims

1. An additive suitable for use as an extreme pressure/anti-wear additive in lubricating oil comprising the product obtainable by reacting at elevated temperature a mixture comprising (i) sulphur, (ii) at least one C₁₀ to C₁₀₀ unsaturated carboxylic acid, or amide or acid salt thereof and (iii) at least one hydrocarbyl-substituted phenol, the amount of (iii) in the mixture being 15 to 65% w/w based on the combined weight of (i) (ii) and (iii).
2. An additive as claimed in claim 1 wherein the amount of (i) in the mixture is 1 to 25% w/w based on the combined weight of (ii) and (iii) in the mixture and the amount of (ii) in the mixture is 20 to 85% w/w based on the combined weight of (i) (ii) and (iii).
3. An additive as claimed in either claim 1 or claim 2 wherein (i) is elemental sulphur.
4. An additive as claimed in any one of claims 1 to 3 wherein (ii) is a C₁₄ - C₂₂ unsaturated carboxylic acid, or amide or acid salt thereof.
5. An additive as claimed in any one of claims 1 to 4 wherein (iii) is a mono or dialkyl phenol.
6. An additive as claimed in any one of claims 1 to 5 wherein said mixture further comprises a C₆ - C₁₀₀ olefin.
7. An additive as claimed in claim 6 wherein said olefin is a C₁₈ alpha olefin.
8. An additive as claimed in any one of claims 1 to 7 wherein said mixture further comprises a mercaptan.
9. An additive as claimed in any one of claims 1 to 8 wherein said mixture further comprises a lubricating oil.
10. An additive concentrate comprising a lubricating oil and an additive as claimed in any one of claims 1 to 9 said additive being present in an amount 2 to 20% w/w based on the weight of the concentrate.
11. A lubricating oil composition comprising a lubricating oil and an additive as claimed in any one of claims 1 to 9 said additive being present in an amount 0.01 to 10% w/w based on the weight of the composition.

Patentansprüche

1. Additiv, geeignet für eine Verwendung als Hochdruck-/verschleißhinderndes Additiv in Schmieröl, enthaltend das Produkt, das man durch Umsetzen bei erhöhter Temperatur einer Mischung erhält, enthaltend (i) Schwefel, (ii) zumindest eine C₁₀- bis C₁₀₀-ungesättigte Carbonsäure, oder eines Amids oder eines Säuresalzes derselben und (iii) zumindest ein Hydrocarbyl-substituiertes Phenol, wobei die Menge an (iii) in der Mischung 15 bis 65 % Gew./Gew., bezogen auf das kombinierte Gewicht von (i), (ii) und (iii), beträgt.
2. Additiv nach Anspruch 1, dadurch gekennzeichnet, daß die Menge an (i) in der Mischung von 1 bis 25 % Gew./Gew., bezogen auf das kombinierte Gewicht von (ii) und (iii) in der Mischung, und die Menge an (ii) in der Mischung 20 bis 85 % Gew./Gew., bezogen auf das kombinierte Gewicht von (i), (ii) und (iii), beträgt.
3. Additiv nach einem der Ansprüche 1 oder 2, dadurch gekennzeichnet, daß (i) elementarer Schwefel ist.
4. Additiv nach einem der Ansprüche 1 bis 3, dadurch gekennzeichnet, daß (ii) eine C₁₄- bis C₂₂-ungesättigte Carbonsäure, oder ein Amid oder Säuresalz derselben, ist.
5. Additiv nach einem der Ansprüche 1 bis 4, dadurch gekennzeichnet, daß (iii) ein Mono- oder Dialkylphenol ist.
6. Additiv nach einem der Ansprüche 1 bis 5, dadurch gekennzeichnet, daß die Mischung ferner ein C₆- bis C₁₀₀-Olefin enthält.
7. Additiv nach Anspruch 6, dadurch gekennzeichnet, daß das Olefin ein C₁₈- α -Olefin ist.



8. Additiv nach einem der Ansprüche 1 bis 7, dadurch gekennzeichnet, daß die Mischung ferner ein Mercaptan enthält.
9. Additiv nach einem der Ansprüche 1 bis 8, dadurch gekennzeichnet, daß die Mischung ferner ein Schmieröl enthält.
10. Additiv-Konzentrat, enthaltend ein Schmieröl und ein Additiv gemäß einem der Ansprüche 1 bis 9, dadurch gekennzeichnet, daß das Additiv in einer Menge von 2 bis 20 % Gew./Gew., bezogen auf das Gewicht des Konzentrats, zugegen ist.
11. Schmierölszusammensetzung, enthaltend ein Schmieröl und ein Additiv nach einem der Ansprüche 1 bis 9, dadurch gekennzeichnet, daß das Additiv in einer Menge von 0,01 bis 10 % Gew./Gew., bezogen auf das Gewicht der Zusammensetzung, zugegen ist.

Revendications

1. Additif utilisable comme additif d'extrême pression/anti-usure dans une huile lubrifiante, comprenant le produit obtenu en faisant réagir à une température élevée un mélange comprenant (i) du soufre, (ii) au moins un acide carboxylique insaturé en C_{10} à C_{100} , ou un amide ou un sel acide de celui-ci et (iii) au moins un phénol hydrocarbonyl substitué, la proportion de (iii) dans le mélange étant de 15 à 65% en poids par rapport au poids combiné de (i), (ii) et (iii).
2. Additif selon la revendication 1, dans lequel la proportion de (i) dans le mélange est de 1 à 25% en poids par rapport au poids combiné de (ii) et (iii) dans le mélange et la proportion de (ii) dans le mélange est de 20 à 85% en poids par rapport au poids combiné de (i), (ii) et (iii).
3. Additif selon la revendication 1 ou 2, dans lequel (i) est le soufre élémentaire.
4. Additif selon l'une quelconque des revendications 1 à 3, dans lequel (ii) est un acide carboxylique insaturé en C_{14} à C_{22} , ou bien un amide ou un sel acide de celui-ci.
5. Additif selon l'une quelconque des revendications 1 à 4, dans lequel (iii) est un mono ou un dialkylphénol.
6. Additif selon l'une quelconque des revendications 1 à 5, dans lequel ledit mélange comprend, de plus, une oléfine en C_8 à C_{100} .
7. Additif selon la revendication 6, dans lequel ladite oléfine est une alpha-oléfine en C_{18} .
8. Additif selon l'une quelconque des revendications 1 à 7, dans lequel ledit mélange comprend, de plus, un mercaptan.
9. Additif selon l'une quelconque des revendications 1 à 8, dans lequel ledit mélange comprend, de plus, une huile lubrifiante.
10. Concentré d'additif comprenant une huile lubrifiante et un additif selon l'une quelconque des revendications 1 à 9, ledit additif étant présent en une proportion de 2 à 20 % en poids par rapport au poids du concentré.
11. Composition d'huile lubrifiante comprenant une huile lubrifiante et un additif selon l'une quelconque des revendications 1 à 9, ledit additif étant présent en une proportion de 0,01 à 10% en poids par rapport au poids de la composition.

