



PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : A62C 31/05, 37/14		A1	(11) International Publication Number: WO 96/08291
			(43) International Publication Date: 21 March 1996 (21.03.96)
(21) International Application Number: PCT/FI95/00495		(81) Designated States: AM, AT, AU, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TT, UA, UG, US, UZ, VN, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG), ARIPO patent (KE, MW, SD, SZ, UG).	
(22) International Filing Date: 12 September 1995 (12.09.95)			
(30) Priority Data: 944264 14 September 1994 (14.09.94) FI			
(71)(72) Applicant and Inventor: SUNDHOLM, Göran [FI/FI]; Ilmari Kiannon kuja 3, FIN-04310 Tuusula (FI).			
(74) Agent: OY KOLSTER AB; Iso Roobertinkatu 23, P.O. Box 148, FIN-00121 Helsinki (FI).		Published With international search report.	

(54) Title: SPRINKLER

(57) Abstract

The present invention relates to a sprinkler which in stand-by mode comprises a heat-sensitive releasing device (20) in close contact with a spindle (15). In order to provide a new sprinkler which ensures even and straight load on the releasing device (20) and which also guarantees even spreading of extinguishing liquid in the form of liquid fog, the sprinkler is characterized in that the spindle (15) is mounted in a channel (12) with a liquid inlet (10) and outlet (13) to preferably obliquely positioned nozzles (14), and bears slidably or almost slidably against the wall of the channel (12) on both sides of the liquid inlet (10) for balancing the liquid pressure at the liquid inlet when the sprinkler is in stand-by mode, and that a nozzle (27) centrally directed in relation to the obliquely positioned nozzles is provided at the end of the spindle (15) which faces the releasing device (20).

