

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
29 April 2004 (29.04.2004)


PCT

(10) International Publication Number
WO 2004/035983 A2

- (51) International Patent Classification⁷: **E21B**
- (21) International Application Number:
PCT/US2003/032797
- (22) International Filing Date: 16 October 2003 (16.10.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
60/419,399 18 October 2002 (18.10.2002) US
Not furnished 16 October 2003 (16.10.2003) US
- (71) Applicant: **DRIL-QUIP, INC.** [US/US]; 13550 Hempstead Highway, Houston, TX 77040 (US).
- (72) Inventors: **WADE, Morris, B.**; 1006 Suwanee, Houston, TX 77090 (US). **WILLIAMS, Gregory, D.**; 11715 Moorcreek, Houston, TX 77070 (US). **MILBERGER, Lionel, J.**; 8911 Rocky Lane, Houston, TX 77040 (US).
- (74) Agent: **HELMREICH, Loren, G.**; Browning Bushman, P.C., 5718 Westheimer, Suite 1800, Houston, TX 77057 (US).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: OPEN WATER RUNNING TOOL AND LOCKDOWN SLEEVE ASSEMBLY



(57) Abstract: A running tool 10, a lockdown sleeve 27, and a seal ring 24 are provided for axially fixing upward movement of a tubular hanger with respect to a subsea wellhead. The running tool 10 includes a tool latching and unlatching mechanism 51 for axially connecting the running tool to the subsea wellhead housing, a tool force applicator 64 for exerting a downward setting force, and a sleeve latching mechanism 73 for securing the lockdown sleeve to the subsea wellhead housing 20. The seal 24 is provided between the lockdown sleeve and one of the tubular hanger and the wellhead housing. The method of the invention includes running the tool and sleeve in open water to the subsea wellhead housing, locking the tool to the housing, setting the seal, locking the sleeve to the housing, then retrieving the tool in open water.



Published:

— without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.