



(51) International Patent Classification:

F24H 1/10 (2006.01) *G01K 7/16* (2006.01)
F24H 9/14 (2006.01) *G01K 13/02* (2006.01)
F24H 9/20 (2006.01) *F24H 9/00* (2006.01)

(21) International Application Number:

PCT/US2011/050967

(22) International Filing Date:

9 September 2011 (09.09.2011)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

12/879,233 10 September 2010 (10.09.2010) US
 12/889,581 24 September 2010 (24.09.2010) US

(71) Applicant (for all designated States except US): **ISI TECHNOLOGY, LLC** [US/US]; 1655 Middle Street, Sullivan's Island, SC 29482 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **BOWERS, John, H.** [US/US]; P.O. Box 401, c/o Teknokon, L.L.C., Clarksburg, NJ 08510 (US). **LYON, Gregory, S.** [US/US]; c/o LTB Engineering, 907 Stuart Avenue, Mamaroneck, NY 10543 (US).

(74) Agents: **MILLET, Marcus J.** et al.; Lerner, David, Littenberg, Krumholz & Mentlik, LLP, 600 South Avenue West, Westfield, NJ 07090 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

[Continued on next page]

(54) Title: LIQUID HEATER WITH TEMPERATURE CONTROL



(57) Abstract: A liquid heater such as a direct electrical resistance liquid heater having multiple flow channels (48, 52) is provided with a temperature-sensing element in the form of a wire (76) extending across numerous channels, preferably all of the channels, near the downstream ends of the channels. The resistance of the wire represents the average temperature of the liquid passing through all of the channels, and hence the temperature of the mixed liquid exiting from the heater. A bubble suppressing structure (54) is provided in the vicinity of the wire.



(88) Date of publication of the international search report:
14 March 2013