

CLAIMS

1. A beautification roller which brings a rotor into contact with a skin surface and rotates the rotor and applies a current in the frequency of 0.5 MHz to 3.0 MHz and the current of 10 W to 35 W to perform beautification, comprising:
 - a substantially rod-like main body part which includes rotatable support parts rotatably supporting rotating shafts of at least two rotors and disposed near an end portion and formed so that a longitudinal outer periphery can be gripped;
 - two rotating shafts of the rotors protruding from the longitudinal direction of the main body in different directions with a predetermined opening angle;
 - at least two rotors which have electrode parts freely rotating about the rotating shafts, respectively, and applying a high-frequency current to at least a portion brought into contact with the skin surface; and
 - a generating means electrically connected to the electrode parts to generate a the current; said high frequency generating means provided in the main body for energizing the electrode unit to generate a high-frequency current, and comprising a conduction part that supplies the high-frequency current from the main unit to the rotating shaft in the shaft support unit; the electrode is portion formed in a ring shape on the outer periphery along the rotation direction of the rotating body;
 - wherein a fold-shaped uneven surface is formed on a surface of the rotating body in parallel with a direction of a rotation shaft.

2. The beautification roller as claimed in claim 1, wherein the roller is disposed of ring like first ring parts are disposed on outer peripheries of an equatorial portion of the roller bodies, and the frequency current can be applied from the first ring parts.
3. The beautification roller as claimed in claim 1, wherein the roller is disposed of ring like second ring parts are disposed on an outer peripheries of an equatorial portion of the roller bodies, and the frequency current can be applied from the second ring parts.
4. The beautification roller as claimed in any one of claims 1 to 3, wherein in the beautification roller, rotation sensor or vibration sensor, which detect rotation of the rotor is disposed as rotation detecting means, and turning on/off of the frequency current is controlled depending on detection results.