(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau

(43) International Publication Date
21 August 2008 (21.08.2008)

PCT

(10) International Publication Number
WO 2008/098901 A3

(51) International Patent Classification:
G06F 9/46 (2006.01)

(21) International Application Number:
PCT/EP2008/051616

(22) International Filing Date:
11 February 2008 (11.02.2008)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
11/705,652 13 February 2007 (13.02.2007) US

(71) Applicant *(for all designated States except US)*: **AMADEUS S.A.S.** [—/FR]; 485 Route du Pin Montard, Les Bouillides BP 69, F-06092 Sophia Antipolis Cedex (FR).

(72) Inventors; and

(75) Inventors/Applicants *(for US only)*: **DANIEL, Jérome** [FR/FR]; Lotissement Rivage Azur, Villa 1, Avenue Honoré Lions, F-06130 Grasse (FR). **THIERRY, Paul** [FR/FR]; 58, Corniche Fleuri, Batiment A, F-06200 Nice (FR).

(74) Agent: **MURGITROYD & COMPANY**; Scotland House, 165 - 169 Scotland House, Glasgow Central Scotland G5 8PL (GB).

(81) Designated States *(unless otherwise indicated, for every kind of national protection available)*: AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States *(unless otherwise indicated, for every kind of regional protection available)*: ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

[Continued on next page]

(54) Title: INTERFACE MODULE




Fig. 1

(57) Abstract: An interface module between a communication module and a number of instances of business logic modules of a software engine comprises first and second functional elements. The first functional element receives incoming data from the communications module and selects which of the instances of business logic modules to forward the incoming data. The selection of an instance of the business logic module is based upon a ruie set held within a data structure at the first functional element. The incoming data passes to the selected logic module instance via the second functional element. The second functional element determines a mode of operation of the selected logic module instance. The mode of operation corresponds to either a single shot or a multiple shot mode of operation. If a multiple shot mode of operation is selected incoming data passes to the selected logic module instance sequentially. Alternatively, if a single shot mode of operation is selected a summary data record corresponding summary of incoming data received at the first function element passes to the selected logic module instance.

WO 2008/098901 A3

European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MT, NL, NO, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— *with international search report*

— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

(88) Date of publication of the international search report:
16 October 2008