(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau

(43) International Publication Date
19 April 2001 (19.04.2001)

PCT

(10) International Publication Number
WO 01/26520 A2

(51) International Patent Classification[7]: A47J 31/44

(21) International Application Number: PCT/EP00/09511

(22) International Filing Date:
28 September 2000 (28.09.2000)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
99120443.9 14 October 1999 (14.10.1999) EP

(71) Applicant *(for all designated States except US)*: SOCIETE DES PRODUITS NESTLE S.A. [CH/CH]; P.O. Box 353, CH-1800 Vevey (CH).

(72) Inventors; and

(75) Inventors/Applicants *(for US only)*: YOAKIM, Alfred [FR/CH]; Ch. de la Routiaz 2, CH-1806 St-Légier (CH). STIEGER, Mischa [CH/CH]; Hagenbuchstrasse 30c, CH-9000 St-Gallen (CH).

(74) Agent: THOMAS, Alain; Avenue Nestlé, 55, CH-1800 Vevey (CH).

(81) Designated States *(national)*: AE, AU, BR, CA, CN, CZ, HU, ID, IL, JP, MA, MX, NO, PL, SG, SI, SK, TR, UA, US.

(84) Designated States *(regional)*: ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:
— *Without international search report and to be republished upon receipt of that report.*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: COFFEE MACHINE WITH INTEGRATED STEAM DELIVERY DEVICE



(57) Abstract: Coffee machine of the "espresso" type comprising a water tank, a pump, a heater unit and circuits for feeding hot water and steam to a percolation nozzle (2). The machine further comprises an integrated steam delivery device (3) which comprises a steam inlet (12) connected to the steam feed circuit and a steam outlet (10). The steam delivery circuit possesses a cylindrical body (14) equipped with an aperture connected to the steam inlet (12) and a cylindrical piece (13) which can move within the body (14) to open or close the steam circuit depending on its position in the body (14). A control member actuated by means of a control finger (17) enables the steam outlet (10) to be brought into contact with the aperture (9) in the closure (4) of a receptacle (5).

WO 01/26520 A2