

Description

The present invention relates to wave soldering of printed wiring boards. More specifically, the present invention relates to wave soldering of surface mounted devices or components on printed wiring boards as well as standard components on single sided, double sided and/or multi-layer boards.

New technologies in the electronic component industry have introduced surface mounted devices such as resistors, capacitors, integrated circuits and the like, in the form of chip components. These components are mounted usually with an adhesive to the bottom side of a printed wiring board. These conditions present new problems for existing soldering processes.

The present methods of wave soldering surface mounted devices on printed wiring boards include systems having two solder waves. The first solder wave typically has a narrow turbulent parabolic shape. The narrow wave contacts a small area on the wiring board allowing gases to escape. The gases are generated by flux volatiles and the like, which can inhibit solder wetting. The narrow wave also provides a vertical pressure to force solder into the small spaces and openings between the components to ensure that all circuit pads, components, terminations, contacts, and the like, are wetted with solder.

The second solder wave is typically a solder wave as used in commercially available machines for soldering printed wiring boards with leaded components and the like. The second wave completes the process and provides optimum exit conditions for the printed wiring boards leaving the solder wave to minimize or eliminate excess solder deposits and eliminate bridges between contacts.

The dual solder wave process has proven to be effective for soldering surface mounted devices onto printed wiring boards, but the process suffers from certain disadvantages. One problem is excessive dross (oxide) production. Dual wave systems typically produce up to twice as much dross as single wave systems. Another problem is the lack of fine control of a turbulent parabolic solder wave. Best soldering results have been obtained by immersing the printed wiring board as deeply as possible in this wave. However, the turbulence of the wave makes this task difficult and may result in solder flooding onto the top side of the printed wiring boards. A still further problem with the dual solder wave process can occur when particles of dross, particles of carbonized oil or other particles in the solder stream block or partially block the narrow nozzle of the first solder wave. Such a blockage can affect the turbulent flow.

It has previously been proposed to apply ultrasonic energy to a molten solder wave or stream in a wave soldering process with a view to facilitating cleaning operations and eliminating fluxing of components to be soldered. Such processes are described in US-A-3,266,136, 3,430,332 and 3,536,243.

It is one aim of the present invention to provide a process and apparatus for wave soldering elements, such as printed wiring boards with surface mounted devices, which overcome the above-mentioned problems of the current two-wave systems. It is a further aim of the invention to provide a controllable vibration or oscillation to a solder wave as opposed to random turbulence. The term "vibration" and "oscillation" used throughout the specification and claims refer to frequencies below about 20 kHz.

The present invention consists in a process for wave soldering a prefluxed element such as wave soldering surface mounted devices to a prefluxed printed wiring board, comprising the steps of moving the element along a predetermined path, forming a solder wave having a predetermined configuration beneath the path, so that at least a portion of the element passes through the solder wave, and producing an oscillation in the solder wave during the passage of the element there-through, characterised in that the oscillation has a frequency in the range from 20 to 400 Hz.

The invention also consists in apparatus for wave soldering a prefluxed element such as surface mounted devices to a prefluxed printed wiring board, comprising means for moving the element along a predetermined path so that at least a portion of the element passes through a solder wave of predetermined configuration formed beneath the path, and oscillating means for producing oscillations in the solder wave during the passage of the element therethrough, characterised in that the oscillating means comprises at least one vibrating vane disposed in the solder wave, and a vibrator for oscillating the vibrating vane at a frequency in the range from 20 to 400 Hz.

The oscillation or vibration provided in the solder wave aids in filling small holes in a board, crevices, corners adjacent to solder masks and all other areas where solder wetting is difficult to achieve with conventional machines. An additional benefit is overcoming problems that occur with thick dry film solder mask. A relatively high frequency oscillation in the solder wave displaces or dislodges gas bubbles that form beneath the boards, allowing the solder to reach all areas in the matrix of components on the printed wiring boards, overcoming the repelling effect of any non-metallized elements such as component bodies, solder masks and the like.

The vibrating or oscillating concept of the present invention can be applied to existing types of solder wave machines for wave soldering, either as a permanent installation or a temporary installation for soldering certain difficult to solder elements.

Preferably, the frequency of the oscillation and/or the amplitude of the oscillation are controlled and at least one vibrating zone is formed in the solder wave. In one embodiment the oscillation occurs in a direction substantially parallel to the path of the element and, in another embodiment, the oscillation occurs in a direction substantially

perpendicular to the path of the element.

The vibrating vane may be in the form of a flat strip and extends in the solder wave substantially perpendicular to the path of the wiring board, and the vibrator oscillates the flat strip in a direction substantially parallel to the path of the wiring board. In another embodiment, a plurality of vibrating vanes are joined by a connector rod, and the vibrator oscillates the vanes in a direction substantially perpendicular to the path of the wiring board.

Means is preferably provided to enable adjustment of the frequency and/or amplitude of vibration over the frequency range of 20 to 400 cycles per second, and an amplitude range up to at least about 1.5 mm (0.060 ins.). Furthermore, the position of the vane in the solder wave is preferably adjustable. Means is also provided in one embodiment for optionally feeding a surface additive, such as oil, to the solder wave.

In other embodiments, the solder wave is formed from a discharge nozzle facing upwards positioned above a solder reservoir with a pump means for forming the solder wave from the nozzle. A vibrating vane is, in one embodiment, positioned in the solder wave and at least two zones of vibration are formed.

In another embodiment, at least one adjustable passive vane is located in the solder wave downstream from the discharge nozzle at the element exit side. The position of the passive vane provides a further zone of vibration to aid in separation of the element, such as a wiring board or the like, from the solder wave.

At least one liquid surface additive feeding tube may be positioned downstream of the passive vane and means is provided to supply liquid surface additive through the feeding tube to the surface of the solder wave.

In the accompanying drawings which illustrate embodiments of the invention:

Fig. 1 shows a cross section of a solder wave applied to the underside of a wiring board illustrating one embodiment of a vibrating vane;

Fig. 2 shows a cross section of a solder wave illustrating another embodiment of a vibrating vane;

Fig. 3 shows a plan view of the vibrating vane shown in Fig. 2;

Fig. 4 shows a cross section of a solder wave illustrating yet another embodiment of a vibrating vane;

Fig. 5 shows a cross section of a solder wave illustrating a still further embodiment of a vibrating vane with a liquid surface additive feeding tube;

Fig. 6 shows a side isometric view of the vibrating vane shown in Fig. 5.

Referring now to the drawings, Fig. 1 and 2 illustrate cross sections through a typical solder wave nozzle 10 such as that shown in Canadian Patent 1,002,391 to Elliott et al. The nozzle 10 is connected to a solder supply conduit 11 by means of a flange 12. Solder enters the nozzle 10 and forms the desired shape of solder wave. The

solder flows back into a solder pot 13.

Above the solder pot 13 is a wiring board path 14 along which wiring boards 15 are conveyed. The drawings illustrate a straight inclined path 14, however, the present invention may be applied to solder wave machines with horizontal or curved paths. Furthermore, the elements to be soldered may follow dip type paths in the solder wave such as a reciprocal dip, curved dip or other path. Such a dipping step may be used for tinning one or more surfaces. The printed wiring boards 15 have surface mounted devices 16 with pads and contacts 17 to be coated with solder and form soldered connections. The entry side of the nozzle 10 has a guide 20 to provide a downward sloping path for a portion of the solder. The exit solder wave flows to a weir plate 21.

Fig. 1 shows a vibrating vane 30 in the form of a flat strip positioned in the nozzle 10 extending along the length of the nozzle. The vane 30 has a top edge shown to be substantially the same height as the top edge of the nozzle 10. Alternatively, the top edge of the vane 30 may be below the top edge of the nozzle or higher than the top edge of the nozzle provided it is not so high as to interfere with passage of the assembly being soldered.

A connecting rod 31 which in some nozzles may be two or more rods, pass through an aperture 32 in the exit side of the nozzle 10 to support the vane 30. The rods 31 connect to a vibrator 33 positioned away from the solder nozzle 10 above the solder pot 13. The exact position of the vibrator 33 as well as the rods 31 to the vane or vanes 30 may be varied. The vibrator may be located above or below the solder wave and is supported to ensure that vibration is transmitted to the vane 30. The frequency and/or amplitude of vibration is controllable by the vibrator 33. It is preferred to vibrate the solder wave a sufficient amount so that gas bubbles that form beneath the wiring board 15 are displaced or dislodged, allowing solder to reach component terminations and other hard to reach areas to be soldered. Large gas bubbles may be broken into smaller ones and all the bubbles are continuously shifted allowing the solder to reach all areas. The vibration is also sufficient to cause the molten solder to be forced up on either side of the surface mounted devices overcoming the repelling effect of the non-metallized component bodies. The solder then wets the metallic areas to be soldered, such as component terminations, pads etcetera or forms solder joints as required. The vibrating frequency together with the amplitude of vibration is adjustable to suit different types of wiring boards.

Figs 2 and 3 illustrate another embodiment wherein a series of short individual vanes 40 are positioned perpendicular to the length of the nozzle 10 and have a connecting rod 41 connecting all the vanes 40 together. Wherein one rod 41 is shown, it would be apparent that two or more rods may be used if necessary. The rod 41 is supported at apertures 42 in the end plates 43 of the nozzle 10 and is connected to a vibrator 44

such that vibration occurs in a different plane to that shown in Fig. 1. Fig. 1 illustrates that vibrations or oscillations occur substantially parallel with the travel of the wiring board path 14, and Figs. 2 and 3 show that vibrations or oscillations occur substantially perpendicular to the travel of the wiring board path 14. The position of the vanes 40 in the nozzle 10 may be raised or lowered and the number of vanes 40 may depend on the particular type of wave soldering machine and the particular type of printed wiring boards being soldered. The size, shape, quantity and angle of vanes can be varied as required. The vibrations or oscillations may be applied at any angle between the two directions shown in Figs. 1 and 2.

In the embodiment shown in Fig. 4 the vibrating vane 30 is connected to the vibrator 33 by one or more connecting rods 31. As shown in this figure, the top edge of the vibrating vane 30 protrudes slightly above the top edge of the nozzle 10. The top edge of the vane 30 must not interfere with the surface mounted devices on the wiring board 15. The position of the vibrating vane 30 is adjustable for optimizing the vibrating characteristics and soldering results. The wiring board path in Fig. 4 has a slope of 60 upwards in the direction of travel. The slope angle of the path may vary from about 0 to 10° dependent upon the type of solder machine. Furthermore, curved paths or dip type paths may be provided through the solder wave.

In the embodiment shown in Figs. 4 and 5, two solder wave vibrating zones 50 and 51 are shown, one on each side of the vibrating vane 30 under the wiring board 15. These zones 50 and 51 allow the solder to reach all the areas requiring solder wetting. A further zone or zones of vibration 52 is formed by using a passive vane 53 on the exit side of the nozzle 10 before the weir plate 21. The passive vane 53 may be located at the most suitable position avoiding the components on the printed wiring board 15, and the further vibration zone 52 preferably occurs between the nozzle and the weir. In one embodiment the further vibration zone occurs at the point or close to the point of separation of the board 15 from the solder wave. This further vibration applied to the board and solder wave in the further zone 52 reduces the possibilities of bridges occurring between contacts or pads. The passive vane 53 also has a damping effect on the solder located between the weir 21 and the passive vane 53. The U-shaped passive vane 53 shown in the drawing may be located at different positions in the exit trough 54 to vary the position of the further zone 52.

Figs. 5 and 6 show a modification to the apparatus shown in Fig. 4 wherein a feeding tube 55 for a surface additive such as oil, is positioned adjacent to the weir 21 which allows an oil reservoir 56 to be formed between the tube 55 and the surface of the solder. A thin coating of oil or other surface additive is created on the surface of the solder wave that reduces surface tension and at the same time reduces dross formation on the wave surface.

Whereas several embodiments of vanes have

been shown herein, it will be understood that the vanes need not necessarily be located in the nozzle itself, but may be positioned in the solder stream between the nozzle exit and the weir 21. The vanes may be positioned on the input side of the solder wave indicated as zone 50 in Figs. 4 and 5. There are no random parameters in the vibratory wave because the frequency of oscillation and amplitude of oscillation are precisely controlled. The shape or form of the vanes may be varied in order to apply vibration at a suitable location in the solder wave. The suitable location being one which displaces or dislodges gas bubbles from underneath the wiring board, and allows solder to reach all areas to be soldered. In one embodiment the vibrator can produce a frequency in the range of 20 to 400 cycles per second and can also vary the amplitude of vibration up to at least about 1.5 mm (0.060 inches). By utilizing the vibrating device with a streamline solder wave, it has been found that the quality of soldering on wiring boards is at least as good as the two solder wave type of solder machine.

Claims

1. Process for wave soldering a prefluxed element (15) such as wave soldering surface mounted devices to a prefluxed printed wiring board, comprising the steps of moving the element along a predetermined path (14), forming a solder wave having a predetermined configuration beneath the path, so that at least a portion of the element passes through the solder wave, and producing an oscillation in the solder wave during the passage of the element (15) therethrough, characterised in that the oscillation has a frequency in the range from 20 to 400 Hz.

2. A process according to claim 1, characterised in that the frequency of the oscillation is controllable.

3. A process according to claim 1 or 2, characterised in that the amplitude of the oscillation is controllable.

4. A process according to claim 1, 2 or 3, characterised in that a plurality of oscillating zones (50, 51, 52) are formed in the solder wave.

5. A process according to any preceding claim, characterised in that the oscillation occurs in a direction substantially parallel to the path of the element.

6. A process according to any preceding claim 1 to 4, characterised in that the oscillation occurs in a direction substantially perpendicular to the path of the element.

7. A process according to any preceding claim, characterised by application of a surface additive (56) to the surface of the solder wave.

8. Apparatus for wave soldering a prefluxed element (15) such as surface mounted devices to a prefluxed printed wiring board, in which comprising means for moving the element along a predetermined path (14) so that at least a portion of the element passes through a solder wave of predetermined configuration formed beneath the

such that vibration occurs in a different plane to that shown in Fig. 1. Fig. 1 illustrates that vibrations or oscillations occur substantially parallel with the travel of the wiring board path 14, and Figs. 2 and 3 show that vibrations or oscillations occur substantially perpendicular to the travel of the wiring board path 14. The position of the vanes 40 in the nozzle 10 may be raised or lowered and the number of vanes 40 may depend on the particular type of wave soldering machine and the particular type of printed wiring boards being soldered. The size, shape, quantity and angle of vanes can be varied as required. The vibrations or oscillations may be applied at any angle between the two directions shown in Figs. 1 and 2.

In the embodiment shown in Fig. 4 the vibrating vane 30 is connected to the vibrator 33 by one or more connecting rods 31. As shown in this figure, the top edge of the vibrating vane 30 protrudes slightly above the top edge of the nozzle 10. The top edge of the vane 30 must not interfere with the surface mounted devices on the wiring board 15. The position of the vibrating vane 30 is adjustable for optimizing the vibrating characteristics and soldering results. The wiring board path in Fig. 4 has a slope of 60 upwards in the direction of travel. The slope angle of the path may vary from about 0 to 10° dependent upon the type of solder machine. Furthermore, curved paths or dip type paths may be provided through the solder wave.

In the embodiment shown in Figs. 4 and 5, two solder wave vibrating zones 50 and 51 are shown, one on each side of the vibrating vane 30 under the wiring board 15. These zones 50 and 51 allow the solder to reach all the areas requiring solder wetting. A further zone or zones of vibration 52 is formed by using a passive vane 53 on the exit side of the nozzle 10 before the weir plate 21. The passive vane 53 may be located at the most suitable position avoiding the components on the printed wiring board 15, and the further vibration zone 52 preferably occurs between the nozzle and the weir. In one embodiment the further vibration zone occurs at the point or close to the point of separation of the board 15 from the solder wave. This further vibration applied to the board and solder wave in the further zone 52 reduces the possibilities of bridges occurring between contacts or pads. The passive vane 53 also has a damping effect on the solder located between the weir 21 and the passive vane 53. The U-shaped passive vane 53 shown in the drawing may be located at different positions in the exit trough 54 to vary the position of the further zone 52.

Figs. 5 and 6 show a modification to the apparatus shown in Fig. 4 wherein a feeding tube 55 for a surface additive such as oil, is positioned adjacent to the weir 21 which allows an oil reservoir 56 to be formed between the tube 55 and the surface of the solder. A thin coating of oil or other surface additive is created on the surface of the solder wave that reduces surface tension and at the same time reduces dross formation on the wave surface.

Whereas several embodiments of vanes have

been shown herein, it will be understood that the vanes need not necessarily be located in the nozzle itself, but may be positioned in the solder stream between the nozzle exit and the weir 21. The vanes may be positioned on the input side of the solder wave indicated as zone 50 in Figs. 4 and 5. There are no random parameters in the vibratory wave because the frequency of oscillation and amplitude of oscillation are precisely controlled. The shape or form of the vanes may be varied in order to apply vibration at a suitable location in the solder wave. The suitable location being one which displaces or dislodges gas bubbles from underneath the wiring board, and allows solder to reach all areas to be soldered. In one embodiment the vibrator can produce a frequency in the range of 20 to 400 cycles per second and can also vary the amplitude of vibration up to at least about 1.5 mm (0.060 inches). By utilizing the vibrating device with a streamline solder wave, it has been found that the quality of soldering on wiring boards is at least as good as the two solder wave type of solder machine.

Claims

1. Process for wave soldering a prefluxed element (15) such as wave soldering surface mounted devices to a prefluxed printed wiring board, comprising the steps of moving the element along a predetermined path (14), forming a solder wave having a predetermined configuration beneath the path, so that at least a portion of the element passes through the solder wave, and producing an oscillation in the solder wave during the passage of the element (15) therethrough, characterised in that the oscillation has a frequency in the range from 20 to 400 Hz.

2. A process according to claim 1, characterised in that the frequency of the oscillation is controllable.

3. A process according to claim 1 or 2, characterised in that the amplitude of the oscillation is controllable.

4. A process according to claim 1, 2 or 3, characterised in that a plurality of oscillating zones (50, 51, 52) are formed in the solder wave.

5. A process according to any preceding claim, characterised in that the oscillation occurs in a direction substantially parallel to the path of the element.

6. A process according to any preceding claim 1 to 4, characterised in that the oscillation occurs in a direction substantially perpendicular to the path of the element.

7. A process according to any preceding claim, characterised by application of a surface additive (56) to the surface of the solder wave.

8. Apparatus for wave soldering a prefluxed element (15) such as surface mounted devices to a prefluxed printed wiring board, in which comprising means for moving the element along a predetermined path (14) so that at least a portion of the element passes through a solder wave of predetermined configuration formed beneath the



path, and oscillating means (30, 40) for producing oscillations in the solder wave during the passage of the element (15) therethrough, characterised in that the oscillating means comprises at least one vibrating vane (30, 40) disposed in the solder wave, and a vibrator (33, 44) for oscillating the vibrating vane (5) at a frequency in the range from 20 to 400 Hz.

9. Apparatus according to claim 8, characterised by at least one connector rod (31, 41) connecting the vane(s) (30, 40) to the vibrator (33, 44) which is located away from the solder wave.

10. Apparatus according to claim 8 or 9, characterised in that the or each vibrating vane (30) is in the form of a flat strip which extends in the solder wave substantially perpendicular to the path (14) of the element (15), and the vibrator (33) is arranged to oscillate the flat strip in a direction substantially parallel to the path (14) of the element.

11. Apparatus according to claim 9, characterised in that a plurality of the vibrating vanes (40) are interconnected by a connector rod (41), and the vibrator (44) is arranged to oscillate the vanes in a direction substantially perpendicular to the path (14) of the element.

12. Apparatus according to claim 8, 9, 10 or 11, characterised in that the vibrator (33, 44) includes controllable means for the frequency of the oscillation produced by the vibrator.

13. Apparatus according to any preceding claim 8 to 12, characterised in that the vibrator (33, 44) includes controllable means for the amplitude of the oscillation produced by the vibrator.

14. Apparatus according to claim 13, characterised in that the amplitude is controllable up to at least 1.5 mm (0.060 ins).

15. Apparatus according to any preceding claim 8 to 14, characterised in that the position of the or at least one vibrating vane (30, 40) in the solder wave is adjustable.

16. Apparatus according to any preceding claim 8 to 15, characterised by means (55) for feeding a surface additive (56) to the solder wave.

17. Apparatus according to any preceding claim 8 to 16, characterised by a reservoir (13) adapted to contain molten solder, a discharge nozzle (10) facing upwards positioned above the reservoir, and pump means for forming the solder wave of a predetermined configuration from the nozzle.

18. Apparatus according to claim 17, characterised in that at least two zones (50, 51) of oscillation are formed in the solder wave, one zone on each side of the vane (30).

19. Apparatus according to claim 18, characterised in that at least one passive element (53) is located in the solder wave downstream from the discharge nozzle (10) at the wiring board exit side, the position of the passive element providing a further zone (52) of oscillation to aid in separation of the wiring board from the solder wave.

20. Apparatus according to claim 19, characterised by at least one liquid surface additive feeding tube (55) positioned downstream of the passive element (53), and means for supplying

liquid surface additive through the feeding tube to the surface of the solder wave.

21. Apparatus according to claim 17, 18, 19 or 20, for applying solder to exposed metallic surfaces and protruding metallic surfaces on one face of a circuit board (15) or the like characterised by

a reservoir (13) adapted to contain solder at a predetermined level;

a discharge nozzle (10) facing upwards positioned above the solder level in the reservoir (13) and having a circuit board entry side and a circuit board exit side;

pump means for forming the solder wave of predetermined configuration from the nozzle (10) for contacting the lower face of the circuit board (15) and being higher than any protruding metallic surfaces;

an upwardly sloping circuit board path (14) above the reservoir (13) passing over the nozzle (10), and

means for moving a circuit board (15) up the path at a predetermined speed from the entry side to the exit side of the nozzle (10);

the nozzle (10) being adapted to permit a greater volumetric portion of the solder wave to flow downwards at the entry side, the entry side of the nozzle having a contoured downwards sloping guide (20) adapted to return the solder to the reservoir (13) in a smooth flow;

the exit side of the nozzle having a substantially rectangular tray attached thereto with an adjustable weir (21) at the edge of the tray parallel to the exit side of the nozzle (10), and the shape of the tray together with the weir (21) being adapted to reduce feedback of flow disturbances on the solder wave, and guide the remaining volumetric portion of the solder wave in a smooth horizontal or downward sloping stream in substantially the same direction at approximately the same speed as the circuit board (15) moving up the path (14).

22. Apparatus according to claim 21, characterised in that a solder receiving section is provided at the circuit board entry side between the nozzle (10) and the solder level of the reservoir (13), the section having an adjustable guide means for varying the cross sectional area of the section between the adjustable guide means and the contoured downward sloping guide (20).

23. Apparatus according to claim 21 or 22, characterised in that the discharge nozzle (10) has a vertical wall on the circuit board entry side and an inward sloping wall at the exit side.

24. Apparatus according to claim 21, 22 or 23, characterised in that the adjustable weir (21) at the edge of the tray parallel to the exit side of the nozzle (10) has an inward slope towards the nozzle of a maximum of 15° to the vertical.

25. Apparatus according to claim 21, 22, 23 or 24, characterised by a deflector plate mounted beneath the adjustable weir (21) adapted to guide solder to the reservoir (13).

26. Apparatus according to any preceding claim 21 to 25, characterised by at least one drain hole in the rectangular tray adjacent the nozzle (10).



Patentansprüche

1. Verfahren zum Schwallöten eines mit Flußmittel überzogenen Bauteiles (15) wie beispielsweise von an der Oberfläche angeordneten Vorrichtungen an eine mit Flußmittel überzogene gedruckte Leiterplatte, wobei das Bauteil längs eines vorbestimmten Weges bewegt wird, wobei eine Lotwelle gebildet wird, die unterhalb des Weges eine bestimmte Konfiguration aufweist, so daß wenigstens ein Teil des Bauteiles durch die Lotwelle geführt wird, und wobei in der Lotwelle während des Durchganges des Bauteiles durch die Welle ein Schwingen erzeugt wird, dadurch gekennzeichnet, daß die Schwingung eine Frequenz im Bereich von 20 bis 400 Hz aufweist.

2. Verfahren nach Anspruch 1, dadurch gekennzeichnet, daß die Frequenz der Schwingung steuerbar ist.

3. Verfahren nach Anspruch 1 oder 2, dadurch gekennzeichnet, daß die Amplitude der Schwingung steuerbar ist.

4. Verfahren nach Anspruch 1, 2 oder 3, dadurch gekennzeichnet, daß eine Vielzahl von Schwingzonen (50, 51, 52) in der Lotwelle ausgebildet wird.

5. Verfahren nach einem der vorherigen Ansprüche, dadurch gekennzeichnet, daß das Schwingen in einer Richtung auftritt, die zum Weg des Bauteiles im wesentlichen parallel ist.

6. Verfahren nach einem der Ansprüche 1 bis 4, dadurch gekennzeichnet, daß das Schwingen in einer Richtung auftritt, die im wesentlichen senkrecht zum Weg des Bauteiles verläuft.

7. Verfahren nach einem der vorherigen Ansprüche, dadurch gekennzeichnet, daß auf die Oberfläche der Lotwelle ein Oberflächenadditiv aufgebracht wird.

8. Vorrichtung zum Schwallöten eines mit Flußmittel überzogenen Bauteiles (15) wie beispielsweise von an der Oberfläche angeordneten Vorrichtungen an eine mit Flußmittel versehene gedruckte Leiterplatte, wobei eine Einrichtung zum Bewegen des Bauteiles längs eines bestimmten Weges (14) vorgesehen ist, so daß wenigstens ein Teil des Bauteiles durch eine Lotwelle bestimmter Konfiguration führbar ist, welche unterhalb des Weges ausgebildet ist, mit einer Schwingeinrichtung (30, 40), um in der Lotwelle während des Durchganges des Bauteiles (15) durch die Welle Schwingungen zu erzeugen, dadurch gekennzeichnet, daß die Schwingeinrichtung wenigstens einen Vibrierflügel (30, 40), welcher in der Lotwelle angeordnet ist, und einen Vibrator (33, 44) umfaßt, welcher den Schwingflügel in Schwingungen mit einer Frequenz im Bereich von 20 bis 400 Hz versetzt.

9. Vorrichtung nach Anspruch 8, dadurch gekennzeichnet, daß wenigstens eine Verbindungsstange (31, 41) vorgesehen ist, welche die Flügel (30, 40) mit dem Vibrator (33, 44) verbindet, welcher im Abstand von der Lotwelle angeordnet ist.

10. Vorrichtung nach Anspruch 8 oder 9,

dadurch gekennzeichnet, daß der oder jeder Schwingflügel (30) die Form eines flachen Streifens aufweist, der sich in der Lotwelle im wesentlichen rechtwinklig zum Weg (14) des Bauteiles (15) erstreckt, und daß der Vibrator (33) angeordnet ist, um den flachen Streifen in einer Richtung in Schwingungen zu versetzen, welche im wesentlichen parallel zum Weg (14) des Bauteiles verläuft.

11. Vorrichtung nach Anspruch 9, dadurch gekennzeichnet, daß eine Vielzahl Schwingflügel (40) mittels einer Verbindungsstange (41) miteinander verbunden ist, und da der Vibrator (44) so angeordnet ist, daß er die Flügel in einer Richtung in Schwingungen versetzt, die im wesentlichen rechtwinklig zum Weg (14) des Bauteiles verläuft.

12. Vorrichtung nach Anspruch 8, 9, 10 oder 11, dadurch gekennzeichnet, daß der Vibrator (33, 44) eine steuerbare Einrichtung für die Frequenz der von dem Vibrator erzeugten Schwingung einschließt.

13. Vorrichtung nach einem der Ansprüche 8 bis 12, dadurch gekennzeichnet, daß der Vibrator (33, 44) eine steuerbare Einrichtung für die Amplitude der von dem Vibrator erzeugten Schwingung aufweist.

14. Vorrichtung nach Anspruch 13, dadurch gekennzeichnet, daß die Amplitude bis zu wenigstens 1, 5 mit steuerbar ist.

15. Vorrichtung nach einem der Ansprüche 8 bis 14, dadurch gekennzeichnet, daß die Lage des oder wenigstens eines Schwingflügels (30, 40) in der Lotwelle einstellbar ist.

16. Vorrichtung nach einem der Ansprüche 8 bis 15, dadurch gekennzeichnet, daß eine Einrichtung (55) zum Zugeben eines Oberflächenadditivs (56) zu der Lotwelle vorgesehen ist.

17. Vorrichtung nach einem der Ansprüche 8 bis 16, dadurch gekennzeichnet, daß ein Behälter (13) vorgesehen ist, welcher geschmolzenes Lot enthalten kann, das eine Abgabedüse (10) aufwärts weist und oberhalb des Behälters angeordnet ist, und daß eine Pumpeinrichtung vorgesehen ist, welche die Lotwelle einer bestimmten Konfiguration aus der Düse bildet.

18. Vorrichtung nach Anspruch 17, dadurch gekennzeichnet, daß wenigstens zwei Schwingzonen (50, 51) in der Lotwelle ausgebildet sind, wobei eine Zone auf jeder Seite des Flügels (30) angeordnet ist.

19. Vorrichtung nach Anspruch 18, dadurch gekennzeichnet, daß wenigstens ein passives Element (53) in der Lotwelle stromab der Abgabedüse (10) an der Leiterplatten-Austrittsseite angeordnet ist, und daß die Lage des passiven Elementes eine weitere Schwingzone (52) schafft, um das Trennen der Leiterplatte von der Lotwelle zu unterstützen.

20. Vorrichtung nach Anspruch 19, dadurch gekennzeichnet, daß wenigstens ein Zufuhrrohr (55) für ein flüssiges Oberflächenadditiv stromab des passiven Elementes (53) vorgesehen ist, und daß eine Einrichtung zum Zuführen des flüssigen Oberflächenadditivs durch das Rohr zu der Oberfläche der Lotwelle angeordnet ist.



21. Vorrichtung nach Anspruch 17, 18, 19 oder 20 zum Auftragen eines Lotes auf freigelegte metallische Oberflächen und vorspringende metallische Oberflächen an einer Fläche einer Leiterplatte (15) oder dergleichen, dadurch gekennzeichnet,

daß ein Behälter (13) zur Aufnahme eines Lotes mit bestimmten Niveau vorgesehen ist,

daß eine Abgabledüse (10) aufwärtsweisend oberhalb des Lotniveaus in dem Behälter (13) vorgesehen ist, und eine Leiterplatten-Eintrittsseite und eine Leiterplatten-Austrittsseite aufweist,

daß eine Pumpeinrichtung zum Ausbilden der Lotwelle bestimmter Konfiguration aus der Düse (10) vorgesehen ist, um die untere Fläche der Leiterplatte (15) zu berühren und welche höher als die vorspringenden metallischen Oberflächen ist,

daß ein aufwärts geneigter Leiterplattenweg (14) oberhalb des Behälters (13) vorgesehen ist, der sich über der Düse (10) erstreckt,

daß eine Einrichtung zum Bewegen der Leiterplatte (15) längs des Weges (14) mit einer bestimmten Geschwindigkeit von der Eintrittsseite zur Austrittsseite der Düse (10) vorgesehen ist,

daß die Düse (10) so ausgebildet ist, daß sie einen größeren Volumenanteil der Lotwelle an der Eintrittsseite abwärts strömen läßt, wobei die Eintrittsseite der Düse eine konturierte, abwärts geneigte Führung (20) aufweist, welche das Lot zu dem Behälter (13) in glatter Strömung zurückführt,

daß die Austrittsseite der Düse eine im wesentlichen rechteckige Mulde aufweist, die daran befestigt ist, wobei ein einstellbares Wehr (21) an Rand der Mulde parallel zur Austrittsseite der Düse (10) vorgesehen ist, und

daß die Form der Mulde zusammen mit dem Wehr (21) Rückwirkungen von Strömungsstörungen auf die Lotwelle reduziert, wobei der verbleibende Volumenanteil der Lotwelle in einem glatten horizontalen oder abwärtsgeneigten Strom in im wesentlichen gleicher Richtung bei annähernd gleicher Geschwindigkeit geführt ist, mit welcher sich die Leiterplatte (15) auf dem Weg (14) aufwärts bewegt.

22. Vorrichtung nach Anspruch 21, dadurch gekennzeichnet, daß ein Lot-Aufnahmeabschnitt an der Leiterplatten-Eintrittsseite zwischen der Düse (10) und dem Lotniveau des Behälters (13) vorgesehen ist, und daß der Abschnitt eine einstellbare Führungseinrichtung aufweist, um den Querschnittsbereich des Abschnittes zwischen der einstellbaren Führungseinrichtung und der konturierten, abwärtsgeneigten Führung (20) zu variieren.

23. Vorrichtung nach Anspruch 21 oder 22, dadurch gekennzeichnet, daß die Abgabledüse (10) an der Leiterplatten-Eintrittsseite eine vertikale Wand und an der Austrittsseite eine einwärts geneigte Wand aufweist.

24. Vorrichtung nach Anspruch 21, 22 oder 23, dadurch gekennzeichnet, daß das einstellbare Wehr (21) an dem zur Austrittsseite der Düse (10)

parallelen Rand des Trog eine Einwärtsneigung zur Düse von maximal 15° zur Vertikalen aufweist.

25. Vorrichtung nach einem der Ansprüche 21 bis 24, dadurch gekennzeichnet, daß unterhalb des einstellbaren Wehrs (21) eine Ablenkplatte vorgesehen ist, welche das Lot zu dem Behälter (13) führt.

26. Vorrichtung nach einem der Ansprüche 21 bis 25, dadurch gekennzeichnet, daß wenigstens ein Ablaufloch in dem rechteckigen Trog neben der Düse (10) vorgesehen ist.

Revendications

1. Procédé de soudage à la vague d'un élément (15) préalablement enduit d'un flux, tel que le soudage à la vague de dispositifs montés en surface sur une carte de circuit imprimé préalablement enduite d'un flux, comprenant les étapes suivantes: le déplacement de l'élément suivant un trajet prédéterminé (14), la formation d'une vague de soudure ayant une configuration prédéterminée au-dessous du trajet afin qu'une partie au moins de l'élément passe dans la vague de soudure, et la création d'une oscillation dans la vague de soudure pendant le passage de l'élément (15) dans la vague, caractérisé en ce que l'oscillation a une fréquence comprise entre 20 et 400 Hz.

2. Procédé selon la revendication 1, caractérisé en ce que la fréquence d'oscillation est réglable.

3. Procédé selon la revendication 1 ou 2, caractérisé en ce que l'amplitude d'oscillation est réglable.

4. Procédé selon la revendication 1, 2 ou 3, caractérisé en ce que plusieurs zones oscillantes (50, 51, 52) sont formées dans la vague de soudure.

5. Procédé selon l'une quelconque des revendications précédentes, caractérisé en ce que l'oscillation est produite en direction sensiblement parallèle au trajet de l'élément.

6. Procédé selon l'une quelconque des revendications 1 à 4, caractérisé en ce que l'oscillation est produite en direction sensiblement perpendiculaire au trajet de l'élément.

7. Procédé selon l'une quelconque des revendications précédentes, caractérisé par l'application d'un adjuvant superficiel (56) à la surface de la vague de soudure.

8. Appareil de soudage à la vague d'un élément (15) préalablement enduit de flux, par exemple de dispositifs montés en surface sur une carte de circuit imprimé préalablement enduite de flux, comprenant des moyens de déplacement de l'élément suivant un trajet prédéterminé (14) afin qu'une partie au moins de l'élément passe dans une vague de soudure de configuration prédéterminée formée sous ledit trajet, et des moyens d'oscillation (30, 40) destinés à créer des oscillations dans la vague de soudure lors du passage de l'élément (15) dans cette vague, caractérisé en ce que les moyens d'oscillation comportent au moins une palette vibrante (30, 40) placée dans la vague de soudure, et un vibreur (33, 44) destiné



à faire osciller la palette vibrante (5) à une fréquence comprise entre 20 et 400 Hz.

9. Appareil selon la revendication 8, caractérisé par au moins une tige (31, 41) de raccordement de la palette ou des palettes (30, 40) au vibreur (33, 44), que est placé à distance de la vague de soudure.

10. Appareil selon la revendication 8 ou 9, caractérisé en ce que la palette ou chaque palette vibrante (30) est sous forme d'une bande plate qui est disposée dans la vague de soudure en direction sensiblement perpendiculaire au trajet (14) de l'élément (15), et le vibreur (33) est disposé afin qu'il fasse osciller la bande plate en direction sensiblement parallèle au trajet (14) de l'élément.

11. Appareil selon la revendication 9, caractérisé en ce que plusieurs palettes vibrantes (40) sont raccordées par une tige (41), et le vibreur (44) est agencé pour faire osciller les palettes en direction sensiblement perpendiculaire au trajet (14) de l'élément.

12. Appareil selon la revendication 8, 9, 10 ou 11, caractérisé en ce que le vibreur (33, 44) comporte un dispositif de réglage de la fréquence d'oscillation produite par le vibreur.

13. Appareil selon l'une quelconque des revendications 8 à 12, caractérisé en ce que le vibreur (33, 44) comprend un dispositif de réglage de l'amplitude d'oscillation produite par le vibreur.

14. Appareil selon la revendication 13, caractérisé en ce que l'amplitude est réglable jusqu'à une valeur au moins égale à 1, 5 mm (0, 060 pouce).

15. Appareil selon l'une quelconque des revendications 8 à 14, caractérisé en ce que la position de la palette ou d'au moins une palette vibrante (30, 40) dans la vague de soudure est réglable.

16. Appareil selon l'une quelconque des revendications précédentes 8 à 15, caractérisé par un dispositif (55) destiné à amener un adjuvant (56) à la surface de la vague de soudure.

17. Appareil selon l'une quelconque des revendications 8 à 16, caractérisé par un réservoir (13) destiné à contenir de la soudure fondue, une buse d'évacuation (10) tournée vers le haut et placée au-dessus du réservoir, et une pompe destinée à former la vague de soudure de configuration prédéterminée à l'aide de la buse.

18. Appareil selon la revendication 17, caractérisé en ce que deux zones au moins (50, 51) d'oscillation sont formées dans la vague de soudure, les zones étant placées de part et d'autre de la palette (30).

19. Appareil selon la revendication 18, caractérisé en ce qu'au moins un élément passif (53) est disposé dans la vague de soudure en aval de la buse d'évacuation (10) du côté de sortie des cartes de circuit, la position de l'élément passif provoquant la formation d'une zone supplémentaire (52) d'oscillation qui facilite la séparation de la carte de circuit de la vague de soudure.

20. Appareil selon la revendication 19, caractérisé par au moins un tube (55) destiné à amener

un adjuvant liquide de surface, ce tube étant placé en aval de l'élément passif (53), et un dispositif destiné à transmettre un adjuvant liquide superficiel à la surface de la vague de soudure par l'intermédiaire de ce tube.

21. Appareil selon la revendication 17, 18, 19 ou 20, destiné à appliquer de la soudure à des surfaces métalliques exposées et à des surfaces métalliques en saillie sur une face d'une carte de circuit (15) ou analogue, caractérisé par

un réservoir (13) destiné à contenir de la soudure à un niveau prédéterminé,

une buse d'évacuation (10) tournée vers le haut et placée au-dessus du niveau de soudure dans le réservoir (13) et ayant un côté d'entrée et un côté de sortie de cartes de circuit,

une pompe destinée à former la vague de soudure de configuration prédéterminée à l'aide de la buse (10) afin que la vague soit au contact de la face inférieure de la carte de circuit (15) et au-dessus de toutes les surfaces métalliques en saillie,

un trajet (14) de cartes de circuit, ce trajet étant incliné vers le haut au-dessus du réservoir (13) et passant au-dessus de la buse (10), et

des moyens pour déplacer vers le haut une carte de circuit (15) le long du trajet à une vitesse prédéterminée du côté d'entrée au côté de sortie de la buse (10),

la buse (10) étant adaptée pour permettre l'écoulement d'une plus grande partie volumique de la vague de soudure vers le bas, du côté d'entrée, le côté d'entrée de la buse ayant un guide profilé (20) incliné vers le bas et adapté pour renvoyer la soudure vers le réservoir (13) en formant un courant régulier,

le côté de sortie de la buse ayant un plateau sensiblement rectangulaire qui lui est fixé et qui comporte un déversoir réglable (21) placé au bord du plateau et parallèlement au côté de sortie de la buse (10), la configuration du plateau, en coopération avec le déversoir (21), étant adaptée pour réduire la répercussion en retour des perturbations d'écoulement sur la vague de soudure et pour guider la partie volumique restante de la vague de soudure afin qu'elle forme un courant régulier horizontal ou incliné vers le bas pratiquement dans le même sens et approximativement à la même vitesse que la carte de circuit (15) qui se déplace en remontant le long du trajet (14).

22. Appareil selon la revendication 21, caractérisé en ce qu'une partie de réception de soudure est placée du côté d'entrée de carte de circuit entre la buse (10) et le niveau de soudure dans le réservoir (13), cette partie de réception ayant un dispositif réglable de guidage destiné à faire varier la section de cette partie entre le dispositif réglable de guidage et le guide profilé incliné vers le bas (20).

23. Appareil selon la revendication 21 ou 22, caractérisé en ce que la buse d'évacuation (10) a une paroi verticale du côté d'entrée de carte et une paroi inclinée vers l'intérieur du côté de sortie.



24. Appareil selon la revendication 21, 22 ou 23, caractérisé en ce que le déversoir réglable (21) placé au bord du plateau parallèlement au côté de sortie de la buse (10) est incliné vers l'intérieur vers la buse et forme un angle maximal de 15° avec la verticale.

25. Appareil selon la revendication 21, 22, 23 ou

24, caractérisé par une plaque déflectrice montée sous le déversoir réglable (21) et adaptée pour guider la soudure vers le réservoir (13).

26. Appareil selon l'une quelconque des revendications 21 à 25, caractérisé par au moins un trou d'évacuation placé dans le plateau rectangulaire à proximité de la buse (10).

10

15

20

25

30

35

40

45

50

55

60

65

9

