

DESCRIPTION

INGREDIENT CONTROL DEVICE, INGREDIENT CONTROL METHOD,
TRANSPORTATION METHOD, COOKING METHOD, AND PROGRAM
Field

5 [0001] The present invention relates to ingredient
control devices, ingredient control methods, transportation
methods, cooking methods, and programs, and particularly
relates to an ingredient control device, an ingredient
control method, a transportation method, a cooking method,
10 and a program that can put an object in a good condition.

Background

[0002] There is known a fryer by means of which food is
cooked in a space where electromagnetic waves in a
predetermined frequency range generate, so that the eating
15 quality of the cooked food can be made very high (see
Patent Literature 1: JP-A-2016-129672). The entire
contents of Patent Literature 1 are incorporated herein by
reference. According to Patent Literature 1, it is
described that when food is cooked in a space where
20 electromagnetic waves in the predetermined frequency range
generate, good effects, including prevention of food oil
oxidation and degradation and improvement of the eating
quality of cooked food, can be obtained.

Citation List

25 Patent Literature

[0003] Literature 1: JP-A-2016-129672

Summary

Technical Problem

[0004] However, at the time when the fryer and the
30 cooking method both according to Patent Literature 1 were
invented, even the inventor did not quite understand
reasons why the above good effects were obtained, and
therefore the above technique could not be applied to all

kinds of food and had difficulty being applied to things other than food.

[0005] The present invention is made to solve the problem above and an object of the present invention is to provide an ingredient control device, an ingredient control method, a transportation method, a cooking method, and a program that can put an object in a good condition.

Solution to Problem

[0006] To attain the above objective, an ingredient control device (100, 0100, 0400, 10, 4001, 4010) according to a first aspect of the present invention includes a pair of vibration generating portions (102, 0101, 0102, 0401, 0402, 3, 4) configured to generate vibrations, in which vibration is generated between the vibration generating portions to control an ingredient in an object disposed between the vibration generating portions.

[0007] In the ingredient control device (100, 0100, 0400, 10, 4001, 4010), the vibration generating portions (102, 0101, 0102, 0401, 0402, 3, 4) may be electrodes configured to generate electromagnetic waves, and a water activity of the object may be controlled by generating electromagnetic waves between the electrodes.

[0008] In the ingredient control device (100, 0100, 0400, 10, 4001, 4010), electromagnetic waves may be generated between the electrodes to increase interfacial polarization between a water phase and another phase of the object and thus decrease an interfacial tension between the water phase and the other phase and bind water in the object into a pearl-chain structure.

[0009] The ingredient control device (0100, 0400) may further include a first circuit portion (0105, 0405) configured to apply alternating current of a first frequency to a first vibration generating portion (0101,

0401) of the pair of vibration generating portions, and a second circuit portion (0106, 0406) configured to apply alternating current of a second frequency to a second vibration generating portion (0102, 0402) of the pair of vibration generating portions.

[0010] The ingredient control device (0400) may further include a frequency controller (0413, 0414) configured to control the first frequency and the second frequency to different frequencies.

10 [0011] In the ingredient control device (0400), the first frequency and the second frequency may be at least 10 kilohertz to at most 150 kilohertz.

[0012] The ingredient control device (0400) may further include a phase controller (0415, 0416) configured to control a phase of the alternating current.

[0013] The ingredient control device (0100, 0400) may further include a frying tank (1541), and a heating portion (1542) configured to heat the frying tank, in which the vibration generating portions (1501, 1502) may generate electromagnetic waves, and the pair of vibration generating portions may be disposed to form an electromagnetic field in the frying tank.

[0014] The ingredient control device (0100, 0400) may further include a food soaking tank (1643) capable of storing edible liquid for soaking food (1661) to allow the edible liquid (1662) to soak into the food and/or to extract an ingredient from the food into the edible liquid, in which the vibration generating portions (1601, 1602) may generate electromagnetic waves, and the pair of vibration generating portions (1601, 1602) may be disposed to form an electromagnetic field in the food soaking tank.

[0015] The ingredient control device (0100, 0400) may further include a high-temperature food cooking portion

(1744) configured to heat food (1761a, 1761b, 1761c) as the object at high temperature, in which the vibration generating portions (1701, 1702) may generate electromagnetic waves, and the pair of vibration generating portions may be disposed to form an electromagnetic field in the high-temperature food cooking portion.

[0016] The ingredient control device (0100, 0400) may further include a room-temperature food cooking portion (1845) in which food (1861) as the object is placed at room temperature, in which the vibration generating portions (1801, 1802) may generate electromagnetic waves, and the pair of vibration generating portions may be disposed to form an electromagnetic field in the room-temperature food cooking portion.

[0017] The ingredient control device (0100, 0400) may further include a refrigerated food cooking portion (1946) configured to refrigerate food (1961) as the object, in which the vibration generating portions (1901, 1902) may generate electromagnetic waves, and the pair of vibration generating portions may be disposed to form an electromagnetic field in the refrigerated food cooking portion.

[0018] The ingredient control device (0100, 0400) may further include a low-temperature refrigerated food cooking portion (2048) configured to store food (2061) as the object by low-temperature refrigeration, in which the vibration generating portions (2001, 2002) may generate electromagnetic waves, and the pair of vibration generating portions may be disposed to form an electromagnetic field in the low-temperature refrigerated food cooking portion.

[0019] The ingredient control device (0100, 0400) may further include a food defrost cooking portion (2149) for defrosting food as the object frozen, in which the

vibration generating portions (2101, 2102) may generate electromagnetic waves, and the pair of vibration generating portions may be disposed to form an electromagnetic field in the food defrost cooking portion.

5 [0020] The ingredient control device (0100, 0400) may further include a vapor supply portion (2250) configured to supply water vapor and/or water spray.

[0021] The ingredient control device (0100, 0400) may further include a frozen food storing portion (2351)
10 configured to store food as the object by freezing, in which the vibration generating portions (2301, 2302) may generate electromagnetic waves, and the pair of vibration generating portions may be disposed to form an electromagnetic field in the frozen food storing portion.

15 [0022] The ingredient control device (10, 4001, 4010) may further include a power source (10) configured to generate alternating current, in which a first vibration generating portion (3) of the pair of vibration generating portions may be coupled to one electrode of the power
20 source, and a second vibration generating portion (4) of the pair of vibration generating portions may be coupled to another electrode of the power source.

[0023] In the ingredient control device (10, 4001, 4010), the vibration generating portions (3, 4) may be sheet-like
25 members.

[0024] The ingredient control device (10) may further include a temperature controller (6) configured to control ambient temperature.

[0025] The ingredient control device (10) may further
30 include a container (11) in which the object is disposed, in which the vibration generating portions (3, 4) may be electrodes configured to generate electromagnetic waves, the container may have a part serving as one electrode of a

pair of the electrodes and another part serving as another electrode of the pair of the electrodes, and an insulating member (7) may be installed between a pair of the electrodes to separate a pair of the electrodes from each other.

[0026] To attain the above objective, an ingredient control method using an ingredient control device (100, 0100, 0400, 10, 4001, 4010) including a pair of vibration generating portions (102, 0101, 0102, 0401, 0402, 3, 4) configured to generate vibrations according to a second aspect of the present invention includes generating vibrations between the vibration generating portions to control an ingredient in an object disposed between the vibration generating portions.

[0027] In the ingredient control method, the vibration generating portions (102, 0101, 0102, 0401, 0402, 3, 4) may be electrodes configured to generate electromagnetic waves, and a water activity of the object may be controlled by generating electromagnetic waves between the electrodes.

[0028] In the ingredient control method, electromagnetic waves may be generated between the electrodes to increase interfacial polarization between a water phase and another phase of the object to decrease an interfacial tension between the water phase and the other phase and bind water in the object into a pearl-chain structure.

[0029] In the ingredient control method, a DC electric field may be applied as an offset electric field to an AC electric field to increase interfacial polarization between a water phase and another phase of the object to decrease an interfacial tension between the water phase and the other phase and bind water in the object into a pearl-chain structure.

[0030] In the ingredient control method, the DC electric

field of approximately +100 V may be applied as an offset electric field on the water phase side relative to the other phase in the AC electric field to increase interfacial polarization between the water phase and the other phase of the object and thus decrease the interfacial tension between the water phase and the other phase and bind water in the object into a pearl-chain structure.

[0031] In the ingredient control method, the electromagnetic waves may be low-frequency waves.

[0032] In the ingredient control method, the electromagnetic waves may have a frequency of approximately 10 kHz to approximately 500 kHz.

[0033] In the ingredient control method, the water in the object may be divided into bound water and free water, and the free water in the object may be bound in a pearl-chain structure.

[0034] In the ingredient control method, the vibration generating portions may generate electromagnetic waves, one (0101, 0401) of the pair of vibration generating portions may apply an electromagnetic field of a first frequency to the object, and the other (0102, 0402) of the pair of vibration generating portions may apply an electromagnetic field of a second frequency different from the first frequency to the object.

[0035] To attain the above objective, a transportation method using an ingredient control device (10) including a pair of vibration generating portions (3, 4) configured to generate vibrations according to a third aspect of the present invention includes installing an object between the vibration generating portions, and transporting the object while generating vibrations between the vibration generating portions to control an ingredient in the object.

[0036] To attain the above objective, a transportation

method using an ingredient control device (10) including a pair of vibration generating portions (3, 4) configured to generate vibrations according to a fourth aspect of the present invention includes installing an object between the vibration generating portions, generating vibrations between the vibration generating portions to control an ingredient in the object, removing the object from the ingredient control device after elapse of a predetermined period of time, and thereafter transporting the object.

10 [0037] To attain the above objective, a cooking method using an ingredient control device (4001, 4010) including a pair of vibration generating portions (3, 4) configured to generate vibrations and an oil reservoir (4006, 4011) in which the vibration generating portions are installed
15 according to a fifth aspect of the present invention includes storing oil in the oil reservoir, frying an ingredient in oil in the oil reservoir in which the vibration generating portions generate vibrations, and thereafter washing the ingredient with water.

20 [0038] In the cooking method, after the ingredient is washed with water, the ingredient may be baked.

[0039] In the cooking method, after the ingredient is washed with water, the ingredient may be boiled.

[0040] In the cooking method, after the ingredient is
25 washed with water, the ingredient may be steamed.

[0041] In the cooking method, the vibration generating portions (3, 4) may generate electromagnetic waves.

[0042] In the cooking method, the vibration generating portions (3, 4) may be electrodes configured to generate
30 electromagnetic waves, the oil reservoir may have a part serving as one electrode of a pair of the electrodes and another part serving as the other electrode of the pair of the electrodes, and an insulating member (12) may be

installed between a pair of the electrodes to separate a pair of the electrodes from each other.

[0043] To attain the above objective, a program for a computer of an ingredient control device (0100, 0400) including a pair of vibration generating portions configured to generate electromagnetic waves according to a sixth aspect of the present invention causes the computer to perform applying an electromagnetic field of a first frequency by one (0101, 0401) of the pair of vibration generating portions to an object installed between the pair of vibration generating portions, and applying an electromagnetic field of a second frequency different from the first frequency by the other (0102, 0402) of the pair of vibration generating portions to the object installed between the pair of vibration generating portions.

Advantageous Effects of Invention

[0044] The ingredient control device, the ingredient control method, the transportation method, the cooking method, and the program according to the present invention can put an object in a good condition.

Brief Description of Drawings

[0045] These and other aspects, features and advantages of which embodiments of the invention are capable of will be apparent and elucidated from the following description of embodiments of the present invention, reference being made to the accompanying drawings, in which

FIG. 1 is a side view schematically showing a fryer according to an embodiment.

FIG. 2 shows an example of a processing flow in a water control method using the fryer according to the above embodiment.

FIG. 3A is a graph showing measurement results of

interfacial tension when an electric field was applied to additive-free fresh food oil with phosphate-buffered saline as a water phase and FIG. 3B is a graph showing measurement results of interfacial tension when an electric field was applied to additive-free fresh food oil with saline as a water phase.

FIG. 4A is a graph showing measurement results of interfacial tension when an electric field was applied to oleic acid-added food oil with phosphate-buffered saline as a water phase and FIG. 4B is a graph showing measurement results of interfacial tension when an electric field was applied to sodium oleate-added food oil with phosphate-buffered saline as a water phase.

FIG. 5 is a graph showing measurement results of interfacial tension when only a DC electric field was applied to sodium oleate-added food oil with phosphate-buffered saline as a water phase.

FIG. 6 is a graph showing measurement results of interfacial tension when only an AC electric field was applied to sodium oleate-added food oil with phosphate-buffered saline as a water phase.

FIG. 7 is a graph showing measurement results of interfacial tension when a DC electric field of +100 V was applied, in an AC electric field, to sodium oleate-added food oil with phosphate-buffered saline as a water phase.

FIG. 8 is a graph showing measurement results of interfacial tension when a DC electric field of -100 V was applied, in an AC electric field, to sodium oleate-added food oil with phosphate-buffered saline as a water phase.

FIG. 9 is a graph showing measurement results of interfacial tension when an electric field was applied to sodium oleate-added food oil with saline as a water phase.

FIG. 10 is a graph showing measurement results of

interfacial tension when only an AC electric field was applied to sodium oleate-added food oil with saline as a water phase.

FIG. 11 is a graph showing measurement results of
5 interfacial tension when a DC electric field of +100 V was applied, in an AC electric field, to sodium oleate-added food oil with saline as a water phase.

FIG. 12 is a graph showing measurement results of
interfacial tension when a DC electric field of -100 V was
10 applied, in an AC electric field, to sodium oleate-added food oil with saline as a water phase.

FIG. 13 is a graph showing measurement results of
interfacial tension when an electric field was applied to
additive-free used food oil with phosphate-buffered saline
15 as a water phase.

FIG. 14 is a graph showing measurement results of
interfacial tension when an electric field was applied to
additive-free used food oil with saline as a water phase.

FIG. 15 is a table showing observation results of W/O
20 emulsions.

FIG. 16 is a schematic view showing the formation of
pearl chains.

FIG. 17A is a table showing observation results of
water microdroplets of phosphate-buffered saline to which
25 various AC electric fields were applied in additive-free
fresh food oil and FIG. 17B is a table showing observation
results of water microdroplets of saline under the same
conditions.

FIG. 18A is a table showing observation results of
30 water microdroplets of phosphate-buffered saline to which
various AC electric fields were applied in sodium oleate-
added food oil and FIG. 18B is a table showing observation

results of water microdroplets of saline under the same conditions.

FIG. 19 is a diagram showing an example of the functional blocks of a food composition control device in a
5 second embodiment.

FIG. 20 is a circuit diagram showing an example of a pair of antenna function portions.

FIG. 21 is a circuit diagram showing an example of one antenna function portion.

10 FIG. 22 is a diagram showing an example of the functional blocks of the food composition control device in the second embodiment.

FIG. 23 is a circuit diagram showing an example of the food composition control device in the second embodiment
15 and a diagram showing an example of waveforms of electromagnetic fields.

FIG. 24 is a circuit diagram showing an example of the food composition control device in the second embodiment
and a diagram showing an example of waveforms of
20 electromagnetic fields.

FIG. 25 is a circuit diagram showing an example of the food composition control device in the second embodiment
and a diagram showing an example of waveforms of
electromagnetic fields.

25 FIG. 26 is a circuit diagram showing an example of the food composition control device in the second embodiment
and a diagram showing an example of waveforms of
electromagnetic fields.

FIG. 27 is a circuit diagram showing an example of the
30 food composition control device in the second embodiment
and a diagram showing an example of waveforms of
electromagnetic fields.

FIG. 28A is a schematic diagram showing an example of

the arrangement of antennas of a pair of antenna function portions.

FIG. 28B is an image diagram showing an example of the timing of stopping and outputting alternating current
5 output in the food composition control device in the second embodiment.

FIG. 29A is a schematic diagram showing an example of the arrangement of antennas of a pair of antenna function portions.

10 FIG. 29B is a schematic diagram showing an example of the arrangement of antennas of a pair of antenna function portions.

FIG. 29C is a schematic diagram showing an example of the arrangement of antennas of a pair of antenna function
15 portions.

FIG. 30 is a diagram showing a long-chain fatty acid salt.

FIG. 31 is a schematic diagram showing an example of the configuration of the food composition control device in
20 the second embodiment.

FIG. 32 is a flowchart showing an example of the process flow in the food composition control device in the second embodiment.

FIG. 33A is a conceptual diagram showing an overview
25 of a food composition control device in a third embodiment.

FIG. 33B shows the result of an evaluation test in the third embodiment.

FIG. 33C shows the result of an evaluation test in the third embodiment.

30 FIG. 34A is a conceptual diagram showing an overview of a food composition control device in a fourth embodiment.

FIG. 34B shows the result of an evaluation test in the fourth embodiment.

FIG. 34C shows the result of an evaluation test in the fourth embodiment.

FIG. 34D shows the result of an evaluation test in the fourth embodiment.

5 FIG. 34E shows the result of an evaluation test in the fourth embodiment.

FIG. 34F shows the result of an evaluation test in the fourth embodiment.

10 FIG. 35A is a conceptual diagram showing an overview of a food composition control device in a fifth embodiment.

FIG. 35B shows the result of an evaluation test in the fifth embodiment.

FIG. 35C shows the result of an evaluation test in the fifth embodiment.

15 FIG. 35D shows the result of an evaluation test in the fifth embodiment.

FIG. 36A is a conceptual diagram showing an overview of a food composition control device in a sixth embodiment.

20 FIG. 36B shows the result of an evaluation test in the sixth embodiment.

FIG. 36C shows the result of an evaluation test in the sixth embodiment.

25 FIG. 37A is a conceptual diagram showing an overview of a food composition control device in a seventh embodiment.

FIG. 37B shows the result of an evaluation test in the seventh embodiment.

FIG. 37C shows the result of an evaluation test in the seventh embodiment.

30 FIG. 38A is a conceptual diagram showing an overview of a food composition control device in an eighth embodiment.

FIG. 38B shows the result of an evaluation test in the

eighth embodiment.

FIG. 39A is a conceptual diagram showing an overview of a food composition control device in a ninth embodiment.

FIG. 39B shows the result of an evaluation test in the
5 ninth embodiment.

FIG. 40A is a conceptual diagram showing an overview of a food composition control device in a tenth embodiment.

FIG. 40B shows the result of an evaluation test in the tenth embodiment.

10 FIG. 41A is a conceptual diagram showing an overview of a food composition control device in an eleventh embodiment.

FIG. 41B shows the result of an evaluation test in the eleventh embodiment.

15 FIG. 42 is a diagram showing a molecular arrangement adjusting unit and a molecular arrangement adjusting device according to a twelfth embodiment.

FIG. 43 is a diagram showing the arrangement of water molecules of an object in a normal state and the
20 arrangement of water molecules of an object in an electric field produced between a first electrode and a second electrode.

FIG. 44 is a diagram showing an example including a temperature controller in the molecular arrangement
25 adjusting unit in the twelfth embodiment.

FIG. 45 is a diagram showing the molecular arrangement adjusting device in another embodiment.

FIG. 46 is a diagram showing a fryer in a thirteenth embodiment.

30 FIG. 47 is a diagram showing an ingredient cooking method in the thirteenth embodiment.

FIG. 48 is a diagram showing a fryer in another embodiment.

Description of Embodiments

[0046] Hereinafter, the present invention will be described with reference to the drawings. The present invention is not at all limited by the descriptions of the specification and drawings and various modifications and variations thereof can be appropriately made without changing the gist of the invention.

[0047] Embodiments of the present invention will be described below. It should be noted that the present invention is not limited by those embodiments and can be carried out in various modes without departing from the spirit of the invention. The correspondence between the embodiments and claims is as follows. The first embodiment mainly relates to claims 1 and 2 and claims 20 to 26, the second embodiment mainly relates to claims 1 to 6, claim 27, and claim 36, the third embodiment mainly relates to claim 5 and claim 7, the fourth embodiment mainly relates to claim 5 and claim 8, the fifth embodiment mainly relates to claim 5 and claim 9, the sixth embodiment mainly relates to claim 5 and claim 10, the seventh embodiment mainly relates to claim 5 and claim 11, the eighth embodiment mainly relates to claim 5 and claim 12, the ninth embodiment mainly relates to claim 5 and claim 13, the tenth embodiment mainly relates to claim 5 and claim 14, the eleventh embodiment mainly relates to claim 12 and claim 15, the twelfth embodiment mainly relates to claims 16 to 19 and claim 29 and claim 30, and the thirteenth embodiment mainly relates to claims 31 to 35.

<<First Embodiment>>

[0048] A fryer according to this embodiment is formed of, for example, an electric field-applicable fryer by means of which food can be cooked in a space where electromagnetic waves in a predetermined frequency range

generate, and controls water contained in the food.

[0049] FIG. 1 is a side view schematically showing a fryer 100 according to an embodiment. The fryer 100 essentially includes an oil reservoir 101, a pair of
5 opposed plate antennas 102, a drive portion 103, and a heating portion 104.

[0050] The oil reservoir 101 is provided for the purpose of storing food oil therein and cooking food therein. In other words, food is fried by putting the food into the
10 heated food oil in the oil reservoir 101. The oil reservoir 101 is where food is to be put in and the internal surface of the oil reservoir 101 thus comes into contact with hot oil. Therefore, the oil reservoir 101 is preferably made of a material harmless to humans and less
15 degradable even after a long period of use at high temperatures, for example, stainless steel. The volume and shape of the oil reservoir 101 are arbitrarily selected depending on where the fryer 100 is to be placed, how much food is to be cooked at once by the fryer 100, and/or other
20 requirements.

[0051] The pair of opposed plate antennas 102 are placed oppositely and upright in the oil reservoir 101. While electromagnetic waves in a predetermined frequency range are generated between the opposed plate antennas 102, food
25 is cooked in the space where the electromagnetic waves generate. The surfaces of the opposed plate antennas 102 are preferably coated with an insulating material. Through the use of this structure, for example, it can be prevented that an AC voltage supplied to the opposed plate antennas
30 102 is transmitted to the oil reservoir 101 to shock the user of the fryer 100 and cause failures or the like of devices around the fryer 100.

[0052] For example, the opposed plate antennas 102 may

each have an approximately L-shaped cross-section, may be each composed of a base portion 111 approximately parallel to the bottom surface of the oil reservoir 101 and a vertical portion 112 approximately perpendicular to the bottom surface of the oil reservoir 101, and may be placed upright with the ends of the base portions 111 facing each other. As seen from the above description of

"approximately L-shaped", instead of the configuration where the base portion 111 and the vertical portion 112 are joined at a right angle to form the plate antenna 102 in an L-shape, for example, the plate antenna 102 may be configured so that the cross section of the joint between the base portion 111 and the vertical portion 112 has a round, R-shape.

[0053] Furthermore, the base portion 111 and/or the vertical portion 112 of the plate antenna 102 may have multiple holes. The shape of the holes is arbitrary, for example, circular, triangle, rectangle, pentagonal or hexagonal. The size and arrangement of the holes are also arbitrary.

[0054] The drive portion 103 is provided for the purpose of driving the opposed plate antennas 102 to generate electromagnetic waves (radio waves) having a frequency of approximately 10 kHz to approximately 500 kHz between the opposed plate antennas 102. The electromagnetic waves formed between the opposed plate antennas 102 are preferably low-frequency waves having a frequency of 30 kHz to 300 kHz and more preferably 50 kHz to 100 kHz. To form electromagnetic waves in a predetermined frequency range between the opposed plate antennas 102, for example, it is conceivable to connect to the opposed plate antennas 102 an oscillator for generating electromagnetic waves of a predetermined frequency. In this case, the drive portion

103 may be electrically connected through terminals 113 to the opposed plate antennas 102.

[0055] The heating portion 104 is provided for the purpose of heating food oil stored in the oil reservoir 101 to 120°C to 200°C to cook food. Various methods can be used as the heating method and examples include: a heating method in which a heating coil is housed in a metal pipe and an electric current is passed through the heating coil to generate heat; and a heating method of combusting a gas to generate heat. Although in this embodiment the heating portion 104 is provided outside of the oil reservoir 101, the heating portion 104 may be provided in the oil reservoir 101 or integrally formed with the oil reservoir 101.

[0056] FIG. 2 shows an example of a processing flow in a water control method (ingredient control method) using the fryer according to this embodiment. In the cooking method shown in FIG. 2, first, the heating portion 104 of the fryer 100 heats food oil in the oil reservoir 101 to a temperature range of 120°C to 200°C (step S1). Next, the drive portion 103 of the fryer 100 drives the opposed plate antennas 102 to generate electromagnetic waves having a frequency of 50 kHz to 100 kHz in the food oil being heated by the heating portion 104 (step S2). Then, when food to be cooked is put in the food oil, the fryer 100 cooks the food while controlling water contained in the food in the space where electromagnetic waves in the predetermined frequency range generate (step S3). When the cooking is finished, the food is picked up from the food oil.

Example 1

[0057] Generally, when food is cooked, water contained in the food turns into water vapor in food oil, so that bumping occurs. In the water control method according to

this embodiment, the interfacial tension at the oil-water interface can be decreased by generating electromagnetic waves in the predetermined frequency range. Thus, the water contained in the food is likely to be desorbed from the food and dispersed in the form of water droplets in the food oil. Therefore, even if the water turns into vapor and gasifies in the heated food oil, only minor bumping occurs. By controlling water contained in food in this manner to reduce bumping, good effects, including prevention of oil penetration into the food, can be obtained. Coupled with this, the cooked food has very good eating quality.

[0058] To verify the reduction of bumping by the water control method according to this embodiment, an AC electric field in a frequency range of 50 kHz to 100 kHz and/or a DC electric field was applied to measure the interfacial tension at the oil-water interface at room temperature (20°C to 25°C) (Example 1). In this case, the interfacial tension is defined as work (energy) necessary to extend the oil-water interface by 1 m² and measured by the sessile drop method. In the sessile drop method, the magnitude of the interfacial tension corresponds to the volume (weight) of a water droplet falling from a capillary tube.

[0059] In this example, harvest oil was used as the food oil. Furthermore, because the pH of food (such as fish, meat, and vegetables) to be cooked is within a range of 5 to 7, phosphate-buffered saline with a pH of 7.2 to 7.4 and saline with a pH of 5.4 to 5.6 were used as model aqueous solutions for water contained in food.

30 Measurement of Interfacial Tension in Fresh Food Oil

[0060] First, measurement was made of the interfacial tension when an AC electric field of 200 Vpp at 50 kHz was applied to additive-free fresh food oil with phosphate-

buffered saline of pH 7.2 to 7.4 as a water phase, and the interfacial tension when a DC electric field of ± 100 V was further applied as an offset electric field on the water phase side relative to the oil phase in the above AC electric field.

[0061] FIG. 3A is a graph showing measurement results of interfacial tension when an electric field was applied to additive-free fresh food oil with phosphate-buffered saline as a water phase. The abscissa axis of the graph in FIG. 3A represents the DC electric field [V] applied as an offset electric field, while the ordinate axis represents the rate of change of the interfacial tension due to the application of the electric field.

[0062] As shown in FIG. 3A, in the case where phosphate-buffered saline was used as a water phase and fresh food oil was free from additive, there was substantially no change in interfacial tension found due to the application of the electric field.

[0063] Next, because a thermolysate or hydrolysate of the food oil may have been produced, 10^{-3} M (= mol/l) oleic acid or an oleic compound, such as 10^{-3} M sodium oleate, which are model substances of the thermolysate or hydrolysate, was added to the fresh food oil and measurement was made of the interfacial tension when an AC electric field of 200 Vpp at 50 kHz was applied to the additive-contained food oil with the water phase and the interfacial tension when a DC electric field of ± 100 V was further applied as an offset electric field in the above AC electric field.

[0064] FIG. 4A is a graph showing measurement results of interfacial tension when an electric field was applied to oleic acid-added food oil with phosphate-buffered saline as a water phase and FIG. 4B is a graph showing measurement

results of interfacial tension when an electric field was applied to sodium oleate-added food oil with phosphate-buffered saline as a water phase. Like the graph shown in FIG. 3A, the abscissa axes of the graphs in FIGS. 4A and 4B represent the DC electric field [V] applied as an offset electric field, while the ordinate axes represent the rate of change of the interfacial tension due to the application of the electric field.

[0065] As shown in FIG. 4A, even in the case where 10^{-3} M oleic acid was added to fresh food oil, there was substantially no change in interfacial tension found due to the application of the electric field. On the other hand, as shown in FIG. 4B, in the case where 10^{-3} M sodium oleate was added to fresh food oil, there was substantially no change found in interfacial tension when only an AC electric field was applied, but a decrease in interfacial tension was confirmed when a DC electric field of ± 100 V was further applied as an offset electric field in the AC electric field.

[0066] As shown in FIG. 3A, in the case where phosphate-buffered saline was used as a water phase and 10^{-3} M sodium oleate was added to fresh food oil, measurement was made of interfacial tensions when various electric fields were applied.

[0067] FIG. 5 is a graph showing measurement results of interfacial tension when only a DC electric field was applied to sodium oleate-added food oil with phosphate-buffered saline as a water phase. Like the graphs shown in FIGS. 3B, 4A, and 4B, the abscissa axis of the graph in FIG. 5 represents the DC electric field [V] applied as an offset electric field, while the ordinate axis represents the rate of change of the interfacial tension due to the application of the electric field.

[0068] FIG. 6 is a graph showing measurement results of interfacial tension when only an AC electric field was applied to sodium oleate-added food oil with phosphate-buffered saline as a water phase. FIG. 7 is a graph
5 showing measurement results of interfacial tension when a DC electric field of +100 V was applied, in an AC electric field, to sodium oleate-added food oil with phosphate-buffered saline as a water phase. FIG. 8 is a graph
10 showing measurement results of interfacial tension when a DC electric field of -100 V was applied, in an AC electric field, to sodium oleate-added food oil with phosphate-buffered saline as a water phase. The abscissa axes of the graphs shown in FIGS. 6 to 8 represent the frequency [Hz] of the AC electric field, while the ordinate axes
15 represent the rate of change of the interfacial tension due to the application of the electric field.

[0069] As shown in FIG. 5, also when only a DC electric field of ± 100 V was applied as an offset electric field without the application of an AC electric field, a decrease
20 in interfacial tension was confirmed, like when a DC electric field of ± 100 V was further applied as an offset electric field in the AC electric field. On the other hand, as shown in FIG. 6, when only an AC electric field was applied and no DC electric field was applied as an
25 offset electric field, there was substantially no change in interfacial tension found even when the frequency of the AC electric field was varied.

[0070] However, as shown in FIG. 7, when a DC electric field of +100 V was applied as an offset electric field in
30 the AC electric field of 200 Vpp at 50 Hz to 100 kHz, a decrease of about 20% in interfacial tension was confirmed regardless of the frequency of the AC electric field. Furthermore, as shown in FIG. 8, when a DC electric field

of -100 V was applied as an offset electric field in the AC electric field of 200 Vpp at 50 Hz to 100 kHz, a decrease of a little over 10% in interfacial tension was confirmed regardless of the frequency of the AC electric field.

5 [0071] Next, measurement was made of the interfacial tension when an AC electric field of 200 Vpp at 50 kHz was applied to additive-free fresh food oil with saline of pH5.4 to 5.6 as a water phase, and the interfacial tension when a DC electric field of ± 100 V was further applied as an
10 offset electric field in the above AC electric field.

[0072] FIG. 3B is a graph showing measurement results of interfacial tension when an electric field was applied to additive-free fresh food oil with saline as a water phase. Like the graphs shown in FIGS. 3A, 4A, 4B, and 5, the
15 abscissa axis of the graph in FIG. 3B represents the DC electric field [V] applied as an offset electric field, while the ordinate axis represents the rate of change of the interfacial tension due to the application of the electric field.

20 [0073] As shown in FIG. 3B, also in the case where saline was used as a water phase, like the case where phosphate-buffered saline was used as a water phase, there was substantially no change in interfacial tension found due to the application of the electric field when fresh
25 food oil was free from additive.

[0074] Next, measurement was made of the interfacial tension when an AC electric field of 200 Vpp at 50 kHz was applied to saline as a water phase and 10^{-3} M sodium oleate-added fresh food oil, and the interfacial tension
30 when a DC electric field of ± 100 V was further applied as an offset electric field in the above AC electric field.

[0075] FIG. 9 is a graph showing measurement results of interfacial tension when an electric field was applied to

sodium oleate-added food oil with saline as a water phase. Like the graphs shown in FIGS. 3A, 4A, 4B, 5, and 3B, the abscissa axis of the graph in FIG. 9 represents the DC electric field [V] applied as an offset electric field, while the ordinate axis represents the rate of change of the interfacial tension due to the application of the electric field.

[0076] As shown in FIG. 4B, in the case where phosphate-buffered saline was used as a water phase, even if 10^{-3} M sodium oleate was added to fresh food oil, there was substantially no change in interfacial tension found when only an AC electric field was applied. On the other hand, as shown in FIG. 9, in the case where saline was used as a water phase, it was confirmed that the interfacial tension was decreased a little over 10% by the addition of 10^{-3} M sodium oleate to fresh food oil even when only an AC electric field was applied.

[0077] When a DC electric field of +100 V was further applied as an offset electric field in the AC electric field, a decrease of over 60% in interfacial tension was confirmed. Furthermore, when a DC electric field of -100 V was further applied as an offset electric field in the AC electric field, a decrease of about 15% in interfacial tension was confirmed.

[0078] Next, in the case where saline was used as a water phase and 10^{-3} M sodium oleate was added to fresh food oil, measurement was made of interfacial tensions when AC electric fields at various frequencies were applied.

[0079] FIG. 10 is a graph showing measurement results of interfacial tension when only an AC electric field was applied to sodium oleate-added food oil with saline as a water phase. FIG. 11 is a graph showing measurement results of interfacial tension when a DC electric field of

+100 V was applied, in an AC electric field, to sodium oleate-added food oil with saline as a water phase. FIG. 12 is a graph showing measurement results of interfacial tension when a DC electric field of -100 V was applied, in an AC electric field, to sodium oleate-added food oil with saline as a water phase. Like the graphs shown in FIGS. 6 to 8, the abscissa axes of the graphs in FIGS. 10 to 12 represent the frequency [Hz] of the AC electric field, while the ordinate axes represent the rate of change of the interfacial tension due to the application of the electric field.

[0080] As shown in FIG. 10, when only an AC electric field of 200 Vpp at 50 Hz to 100 kHz and 200 Vpp was applied and no DC electric field was applied as an offset electric field, the rate of decrease in interfacial tension tends to increase with decreasing frequency of the AC electric field although variations in interfacial tension value were found.

[0081] On the other hand, as shown in FIG. 11, when a DC electric field of +100 V was further applied as an offset electric field in the AC electric field, decreases of over 60% in interfacial tension were confirmed and the interfacial tension reached a minimum in the vicinity of 1 kHz. Furthermore, as shown in FIG. 12, when a DC electric field of -100 V was further applied as an offset electric field in the AC electric field, decreases of about 15% in interfacial tension were confirmed although variations in the rate of decrease in interfacial tension value were found, and the decrease in interfacial tension tends to be suppressed in the vicinity of 1 kHz.

[0082] The above measurement results of the interfacial tensions at the oil-water interfaces will be summarized as follows:

A as shown in FIG. 4A, even in the case where 10^{-3} M oleic acid was added to fresh food oil, there was substantially no change in interfacial tension found due to the application of the electric field;

5 B on the other hand, as shown in FIGS. 4B, 5 to 8, and 9 to 12, in the case where 10^{-3} M sodium oleate was added to fresh food oil, a decrease in interfacial tension was confirmed when an electric field was applied, and the rate of decrease in interfacial tension significantly depended
10 on the pH of the water phase;

C as shown in FIGS. 4B and 5 to 8, in the case where phosphate-buffered saline of pH 7.2 to 7.4 was used as a water phase, there was no decrease in interfacial tension found when only an AC electric field was applied, while a
15 decrease in interfacial tension was confirmed when a DC electric field was applied;

D on the other hand, as shown in FIGS. 9 to 12, in the case where saline of pH 5.4 to 5.6 was used as a water phase, a decrease in interfacial tension was confirmed even when
20 only an AC electric field was applied and the rate of decrease in interfacial tension tends to increase with decreasing frequency of the AC electric field; and

E furthermore, as shown in FIG. 11, in the case where saline of pH 5.4 to 5.6 was used as a water phase, a
25 decrease of over 60% in interfacial tension was confirmed when a DC electric field of +100 V was applied as an offset electric field in an AC electric field, while, as shown in FIG. 12, the decrease in interfacial tension was only about 15% when a DC electric field of -100 V was applied as an
30 offset electric field in the AC electric field.

[0083] It can be seen from the above measurement results that the lower the pH of water contained in food, the

higher the rate of decrease in interfacial tension at the oil-water interface and the more bumping can be reduced.

Measurement of Interfacial Tension in Used Food Oil

[0084] Next, in the case where no additive was added to food oil used by the fryer 100, measurement was made of the interfacial tension when an AC electric field of 200 Vpp at 50 kHz was applied and the interfacial tension when a DC electric field of ± 100 V was further applied as an offset electric field on the water phase side relative to the oil phase in the above AC electric field.

[0085] FIG. 13 is a graph showing measurement results of interfacial tension when an electric field was applied to additive-free used food oil with phosphate-buffered saline as a water phase. FIG. 14 is a graph showing measurement results of interfacial tension when an electric field was applied to additive-free used food oil with saline as a water phase. Like the graphs shown in FIGS. 3A, 3B, 4A, 4B, 5, and 9, the abscissa axes of the graphs in FIGS. 13 and 14 represent the DC electric field [V] applied as an offset electric field, while the ordinate axes represent the rate of change of the interfacial tension due to the application of the electric field.

[0086] As shown in FIGS. 3A and 3B, in the case where no additive was added to fresh food oil, there was substantially no change in interfacial tension found due to the application of the electric field. On the other hand, as shown in FIGS. 13 and 14, in the case where no additive was added to used food oil, it was confirmed that the interfacial tension was decreased slightly about 5% by the application of the electric field. Regarding the effect of the pH of the water phase, a similar tendency to the case where 10^{-3} M sodium oleate was added to fresh food oil was

exhibited although the rate of decrease in interfacial tension was different from that in the above case.

Example 2

[0087] In Example 1 above, it was confirmed that the
5 presence of sodium oleate (salt of higher fatty acid),
which may be produced by thermolysis or hydrolysis of food
oil, caused a decrease in interfacial tension when an
electric field was applied. A decrease in interfacial
tension is due to an increase of interfacial polarization
10 caused by the application of an electric field.

[0088] Oil-side oleate ions and water-side sodium ions
adsorbed at the oil-water interface act to extend the
interface owing to electrostatic repulsive energy acting
between adjacent ions of the same kind. When the
15 concentrations of oleate ions and sodium ions at the oil-
water interface are increased by the application of an
electric field, the distance between adjacent ions
decreases, so that electrostatic repulsive energy, i.e., an
action to extend the interface, increases. As a result,
20 the interfacial tension, which is defined as work necessary
to extend the oil-water interface by 1 m^2 , decreases.

[0089] When water contained in food turns into water
vapor in food oil, the size of water desorbing from the
food to turn into tiny water droplets (hereinafter,
25 referred to as "water microdroplets") in the food oil is
smaller than the size (capillary tube diameter to 5 mm) of
water droplets falling from a capillary tube in the sessile
drop method. When such water microdroplets in food oil
develop sufficient interfacial polarization to decrease
30 their interfacial tension, pearl chains of the water
microdroplets are formed by the dipole-dipole attraction.
On the other hand, when the interfacial polarization is
weak, no pearl chains of the water microdroplets are formed.

[0090] To evaluate the interfacial polarization state of water microdroplets in food oil (a water-in-oil (W/O) emulsion) based on the above viewpoints, microscopic observation was made on water microdroplets of each of (1) a phosphate-buffered saline of pH 7.2 to 7.4 conditioned by additive-free fresh food oil, (2) a saline of pH 5.4 to 5.6 conditioned by additive-free fresh food oil, (3) a phosphate-buffered saline of pH 7.2 to 7.4 conditioned by 10^{-3} M sodium oleate-added food oil, and (4) a saline of pH 5.4 to 5.6 conditioned by 10^{-3} M sodium oleate-added food oil, by applying electric fields of various voltages from 200 to 2000 Vpp/cm at 50 kHz to the water microdroplets (Example 2).

[0091] FIG. 15 is a table showing observation results of W/O emulsions. As shown in FIG. 15, in the 10^{-3} M sodium oleate-added food oil, the formation of such pearl chains as formed in FIG. 16 was confirmed, independent of the pH of the phosphate-buffered saline or saline contained in water microdroplets, about two minutes after the application of an AC electric field of 200 to 2000 Vpp/cm at 50 kHz. The size of formed pearl chains was approximately 200 μm and the diameter of each pearl was about 10 to about 100 μm . Once pearl chains were formed, they were held in that state for a week. On the other hand, in the additive-free fresh food oil, the formation of pearl chains was not confirmed about two minutes after the application of the AC electric field, but it was confirmed 40 minutes or more after the application of the AC electric field. This suggests that the 10^{-3} M sodium oleate-added food oil generated greater interfacial polarization at the water-oil interface than the additive-free fresh food oil. This results agree with the measurement results in Example 1 above.

[0092] Next, microscopic observation was made on water microdroplets of each of the above salines (1) to (4) two minutes after the application of various AC electric fields with various voltages of 200 to 2000 Vpp/cm at various frequencies of 50 Hz to 100 kHz to the water microdroplets.

[0093] FIG. 17A is a table showing observation results of water microdroplets of phosphate-buffered saline to which various AC electric fields were applied in additive-free fresh food oil and FIG. 17B is a table showing

observation results of water microdroplets of saline under the same conditions. FIG. 18A is a table showing observation results of water microdroplets of phosphate-buffered saline to which various AC electric fields were applied in 10^{-3} M sodium oleate-added food oil and FIG. 18B is a table showing observation results of water microdroplets of saline under the same conditions.

[0094] As shown in FIGS. 17A and 17B, in the fresh food oil, there was no formation of pearl chains of water microdroplets found at any of the frequencies. On the other hand, as shown in FIGS. 18A and 18B, in the 10^{-3} M sodium oleate-added food oil, the formation of pearl chains of water microdroplets was confirmed within a range of 500 to 2000 Vpp/cm at any of the frequencies. However, at low frequencies in the above frequency range, the formation of pearl chains could not be confirmed because of disturbance of fluid motion attributed to electroosmotic flow.

[0095] It can be seen from the above observation results that even water microdroplets with a diameter of 100 μ m or less dispersed into food oil develop interfacial polarization at the water-oil interface by the application of an electric field and the interfacial polarization at the water-oil interface is increased by the addition of 10^{-3} M sodium oleate to the food oil to decrease the

interfacial tension.

[0096] Food contains a large amount of polar ingredients, besides fatty acid salts, such as sodium oleate. Food also contains a large amount of polar organic polymers. For
5 example, water contained in large amounts in food is one of polar molecules. In food of plant or animal origin, water is contained in an amount of about 70% and the cell membrane of the food is formed of a lipid bilayer membrane. Specifically, fruits and vegetables contain water
10 constituting 80% or more of their weight and fishes and meats contain water constituting 70 to 80% of their weight. If 5% water in a vegetable or 3% water in fish or meat is lost, its freshness and quality cannot be maintained.

[0097] Although water, which is one of polar molecules,
15 is contained in large amounts in food, it is broadly divided into "bound water" and "free water" according to its state of being. "Bound water" is water bound by hydrogen bonding to and hydrated with protein and carbohydrate in food and is stable because its molecular
20 motion is constrained by the hydration. "Free water" is water that is freely movable and can therefore freeze at 0°C, vaporize near 100°C or dissolve substances. As food contains a larger amount of free water, the food can be said to be fresher, or juicier. However, its molecule has
25 a polarity and is therefore easily bindable to other molecules. Microorganisms, such as putrefying bacteria, cannot be bound to bound water already bound to food ingredients and, therefore, bound water cannot be used for their growth. On the other hand, microorganisms can be
30 bound to free water and, therefore, free water can be used for their growth. Free water bound to microorganisms causes rot.

[0098] In the water control method according to this

embodiment, droplets of free water are turned into a stable state of a pearl-chain structure, like bound water, so that surplus water can be prevented from leaking from food into food oil, thus maintaining the juiciness of the food.

5 [0099] Furthermore, an enormous amount of energy (vaporization heat) is necessary when water breaks hydrogen bonding to change from a liquid to a gas. In the water control method according to this embodiment, water contained in food is held in a liquid phase by the
10 formation of pearl chains and not vaporized in food oil. Thus, good effects can be obtained, including prevention of oil splash due to water in the food, decreased oil temperature during cooking, decreased food cooking time, and its attendant reduction of food oil oxidation.

15 [0100] As described previously, the fryer 100, which is the ingredient control device according to this embodiment, includes a pair of opposed plate antennas 102 which are the electrodes forming the vibration generating portion capable of generating vibrations. The fryer 100 controls water
20 which is an ingredient of food as the object placed between the pair of opposed plate antennas 102, to be more specific, the water activity of the food, by generating electromagnetic waves (radio waves) at a frequency of approximately 10 kHz to approximately 500 kHz between the
25 pair of opposed plate antennas 102.

[0101] In the water control method using the fryer 100 according to this embodiment, the fryer 100 applies a DC electric field of +100 V as an offset electric field on the water phase side relative to the oil phase, which is the
30 other phase, in an AC electric field to irradiate food with electromagnetic waves at a frequency of 50 kHz. Thus, the interfacial polarization between the water phase and the oil phase can be increased to decrease the interfacial

tension between the water phase and the oil phase by approximately 60% and bind water in a pearl-chain structure. Water contained in food is divided into bound water and free water. Free water in water contained in food becomes
5 bound in a pearl-chain structure, so that the water activity representing the proportion of free water in food can be decreased.

[0102] When the interfacial tension between the water phase and the oil phase is decreased by approximately 60%
10 in the above manner, water contained in the food is likely to be desorbed from the food and dispersed in the form of water droplets in the food oil. Therefore, even if the water in the food turns into vapor and gasifies in the food oil being heated, only minor bumping occurs. By
15 controlling water contained in food in this manner to reduce bumping, good effects, including prevention of oil penetration into the food, can be obtained. Coupled with this, the cooked food has very good eating quality.

[0103] Furthermore, since droplets of free water are
20 bound together in a pearl-chain structure and thus turned into a stable state, surplus water can be prevented from leaking from food into food oil, thus maintaining the juiciness of the food. Moreover, in the water control method according to this embodiment, water contained in
25 food is held in a liquid phase by the formation of pearl chains and not vaporized in food oil. Thus, good effects can be obtained, including prevention of oil splash due to water in the food, decreased oil temperature during cooking, decreased food cooking time, and its attendant reduction of
30 food oil oxidation.

[0104] As thus far described, the fryer 100 and the water control method both according to this embodiment can improve food containing water to a better state.

[0105] The present invention is not limited to the above embodiment and various modifications and applications can be made therein. A description will be given below of modifications of the above embodiment which are applicable to the present invention.

[0106] Although the description of the above embodiment was given by taking water as an example of the ingredient, the present invention is not limited to this and the ingredient may be anything controllable by vibrations, such as other kinds of liquids.

[0107] Although the description of the above embodiment was given by taking a fryer as an example of the ingredient control device, the present invention is not limited to this and the ingredient control device may be anything that can control an ingredient of an object, such as food.

Examples of the ingredient control device include a freezer, a container, and a warehouse which can control the water activity of food. Specifically, by controlling the water activity of food using the ingredient control device according to the present invention, the taste, flavor, and nutrition of the food can be improved.

[0108] When water contained in meats, fishes, vegetables, and fruits serving as foods is bound in a pearl-chain structure using the ingredient control device according to the present invention, even normal freezers can keep the qualities of the meats, fishes, and so on for a long period of time (several times as long as usual) without rotting them. In fact, when a crimson sea-bream was irradiated with an electric field for an hour by the ingredient control device and then preserved in a freezer for two days, the freshness of the fish could be maintained two days longer than when a crimson sea-bream was irradiated with an electric field for only 15 minutes and then preserved in

the freezer for two days and when a crimson sea-bream was preserved in the freezer for two days without being irradiated with an electric field.

[0109] Although the description of the above embodiment
5 was given by taking food as an example of the object, the present invention is not limited to this and the object may be anything an ingredient of which can be controlled by vibrations, such as electromagnetic waves. Examples of the object include beverages, plants other than foods, such as
10 plants for use in drugs, human bodies, animals, gunpowder, drugs, such as vaccines, and water itself.

[0110] Specifically, by controlling the water activities of beverages, plants, human bodies, animals, gunpowder or drugs, such as vaccines, using the ingredient control
15 device according to the present invention, not only foods but also beverages, plants, human bodies, animals, gunpowder, drugs, and so on can become difficult to degrade or rot.

[0111] Furthermore, crops cultivated using water
20 decreased in interfacial tension by the ingredient control device according to the present invention can germinate and grow very fast and uniformly, suppress the growth of algae and weeds, and provide very good eating qualities.

[0112] When using the ingredient control device
25 according to the present invention free water in a living organism is changed from a state where it has already been bound to active oxygen, viruses, microorganisms including bacteria, or the like to a pearl-chain structure of water droplets, the free water is released from hydrogen bonds
30 with active oxygen, viruses, microorganisms including bacteria, or the like and thus can exert a significant therapeutic effect. Although conventional drug research and development is carried out on the assumption of a state

of free water where it has already been bound to active oxygen, viruses, microorganisms including bacteria, or the like, the present invention can undermine this assumption itself and thus improve the therapeutic effect.

5 Furthermore, when the ingredient control device according to the present invention is contained in a cellular phone, a smartphone, a tablet computer, a personal computer, a chair, a bed or a pillow, free water bound to microorganisms including bacteria, active oxygen, viruses
10 or the like is separated therefrom and droplets of the free water are bound together in a pearl-chain structure. Thus, the activity of microorganisms including bacteria, active oxygen, viruses or the like can be terminated, stopped or deactivated.

15 [0113] When in mixing cement with water the water to be mixed into the cement is turned into a pearl-chain structure using the ingredient control device according to the present invention, the strength of the resultant concrete can be increased. When water used in a refining
20 process for iron or resin is turned into a pearl-chain structure using the ingredient control device according to the present invention, the strength of iron or resin can be increased, so that defects can be reduced. When in a production process of semiconductor device-related products,
25 such as wafers for LSI (large-scale integration) devices and liquid crystal displays, cleaning water for substrates is turned into a pearl-chain structure using the ingredient control device according to the present invention, the cleaning effect can be increased. With the use of the
30 water control method according to the present invention, the production technique for dilutional preparation of an etching liquid can be improved and the resolution of fine patterns to be printed in an exposure process can be

increased. When water contained in ink or paint is turned into a pearl-chain structure using the ingredient control device according to the present invention, nozzle clogging can be reduced.

5 [0114] With the use of the ingredient control device according to the present invention, the effect of cleaning test devices for precise quantitative analysis can be increased and problems with the preparation of reagents and standards, blanks, solvents for two-phase extraction, and
10 so on can be solved. Furthermore, the ingredient control device according to the present invention can be used for cell culture in the biotechnology field, such as genetic engineering, particularly for DNA (deoxyribonucleic acid) amplification. The ingredient control device according to
15 the present invention can also be applied to water for drug injection during the production of injectables (exclusive of water for dilution or as a solvent during inoculation) and sealed purified water.

[0115] The ingredient control device according to the
20 present invention can be applied to condensate demineralization of ultrahigh-pressure boilers in thermal power plants where supercritical water is totally evaporated and traditional boilers. Furthermore, although primary cooling water coming into contact as a coolant with
25 the core of a light-water reactor of a nuclear power plant brings secondary radioactivity due to radio activation of impurities, particularly, nuclide having a large reaction cross-section, such as boron and cadmium, the ingredient control device according to the present invention can be
30 used to prevent the secondary radioactivity. Moreover, also in solar power generation and hydrogen power generation, the efficiency of electric power generation can be increased by using the ingredient control device

according to the present invention to eliminate impurities in solvents and thus make highly pure water.

[0116] The ingredient control device according to the present invention can also be applied to media for
5 specialized particle detectors in particle physics.

Furthermore, when, also in molecular structures of gasoline and heavy oil, free water is turned into a pearl-chain structure using the ingredient control device according to the present invention, the fuel combustion efficiency can
10 be increased.

<<Second Embodiment>>

[0117] In the fryer 100 according to the first embodiment, when food is cooked in a space where electromagnetic waves in a predetermined frequency range
15 are generated, good effects, including prevention of food oil oxidation and degradation and improvement of the eating quality of cooked food, can be obtained. However, the fryer 100 according to the first embodiment has limitation in adaptation to cooking methods other than frying and in
20 application to improvement of the eating quality of food during storage and keeping freshness.

[0118] The inventor of the present invention has conducted further studies and found that improvement of the eating quality and keeping freshness for a long time can be
25 achieved by forming an electromagnetic field suitable for each individual food by controlling the frequency and/or the phase of electromagnetic waves that are vibrations applied to a pair of antenna function portions which are vibration generating portions generating vibrations.

30 [0119] A food composition control device according to the second embodiment is adapted to a variety of cooking methods including frying and can improve the eating quality of food during storage and keep freshness for a long time

by applying electromagnetic waves of a predetermined frequency to a pair of antenna function portions to form an electromagnetic field with a plurality of electromagnetic waves, and bringing food in contact with the electromagnetic field.

<Functional Configuration>

[0120] FIG. 19 is a diagram showing an example of the functional blocks of the food composition control device in the present embodiment. The functional blocks of the present device described below can be implemented as a combination of hardware and software. Specifically, when a computer is used, the hardware configuration includes a central processing unit (CPU), a main memory, a bus, or a secondary storage device (a storage medium such as hard disk, nonvolatile memory, compact disc (CD), and digital versatile disc (DVD), and a reading drive for those media), an input device for input of information, a printer, a display device, and other external peripheral devices. Examples of the hardware include a fryer or a heating portion that constitutes a fry reservoir and a heater, a food soaking tank, a hot plate, an oven, or a grill that may constitute a high-temperature food cooking portion, a refrigerator that may constitute a refrigerated food cooking portion or a low-temperature refrigerated food cooking portion, a microwave oven that may constitute a food defrost cooking portion, a steamer or a steam convection oven that may cooperate with each cooking portion and constitute a vapor supply portion, and a freezer that may constitute a frozen food storing portion, as well as a driver program for controlling such hardware, other application programs, and user interface applications. Other examples include an interface for external peripheral devices, a communication interface, a driver program for

controlling such hardware, an application program, and a user interface application. Data input from an input device or other interfaces and held on a memory or a hard disk is processed or accumulated, and an instruction for
5 controlling the hardware and the software is generated, through the operation processing by the CPU in accordance with a program loaded on the main memory. Alternatively, the functional blocks of the present device may be implemented by dedicated hardware.

10 [0121] The present invention can be embodied not only as a device but also as a method. Part of the invention may be configured as software. A software product used to cause a computer to execute such software and a recording medium having the product fixed thereon also fall in the
15 technical scope of the present invention, as a matter of course (this is applicable throughout the present description).

[0122] As shown in FIG. 19, the "food composition control device" (0100) in the present embodiment includes a
20 pair of antenna function portions (0101, 0102), a first circuit portion (0105), a first controller (0107), a second circuit portion (0106), and a second controller (0108). Alternating current of a first frequency (0103) is applied from the first circuit portion to one antenna function
25 portion of a pair of antenna function portions, and alternating current of a second frequency (0104) is applied from the second circuit portion to the other antenna function portion. The configuration of the food composition control device in the present embodiment is
30 described below.

(Antenna Function Portion)

[0123] "A pair of antenna function portions" (0101, 0102) can be disposed to face the placed food. A pair of

antenna function portions refers to an antenna function portion configured with two antenna function portions

[0124] FIG. 20 is a circuit diagram showing an example

of a pair of antenna function portions. A pair of antenna

5 function portions in the food composition control device in the present embodiment is configured with two antenna

function portions, and each antenna function portion may

include a plurality of antennas. The antenna function

portion at least includes an antenna (0209) and a feeding

10 point (0210) and receives alternating current output by the circuit portion at the feeding point. The antenna has the

function of emitting electromagnetic waves. The antenna in

one antenna function portion (hatched in FIG. 20) of a pair of antenna function portions emits electromagnetic waves

15 (0211) of a first frequency applied from the first circuit portion to generate an electromagnetic field. The other

antenna function portion (shaded in FIG. 20) emits

electromagnetic waves (0212) of a second frequency applied from the second circuit portion to generate an

20 electromagnetic field. A pair of antenna function portions has the function of forming a predetermined electromagnetic field through interaction of an electromagnetic field

generated by one antenna function portion and an

electromagnetic field generated by the other antenna

25 function portion. Food is placed in the electromagnetic

field formed by a pair of antenna function portions whereby the food composition is controlled. The electromagnetic

field formed by the antenna function portions is disposed

so as to act on the entire food as a target to control the

30 food composition. Specifically, it is preferable that the entire food is disposed in a region in which an

electromagnetic field is formed.

[0125] FIG. 21 is a circuit diagram showing an example

of one antenna function portion. One antenna function portion may be formed with one antenna as shown in FIG. 21A or may have three antennas as shown in FIG. 21B. As shown in FIG. 20, one antenna function portion may be formed with
5 two antennas. Although not shown in the figures, it may be formed with four or more antennas, as a matter of course.

[0126] The shape of the antenna is not limited and may be a rod shape, a flat plate shape, an approximate L-shape, or a semispherical shape, for example. The material of the
10 antenna is not limited, but preferably the surface of the antenna is coated with an insulating material. Two or more antennas included in one antenna function portion may be formed of different materials. For example, it is preferable that one of two antennas included in one antenna
15 function portion is formed of stainless steel and the other is formed of aluminum. For example, it is preferable that one of two antennas included in one antenna function portion is formed of stainless steel and the other is formed of copper.

20 (Circuit Portion)

[0127] A description is given with reference to FIG. 19 again. The "first circuit portion" (0105) is configured to apply alternating current of a first frequency (0103) to one antenna function portion of a pair of antenna function
25 portions. The "second circuit portion" (0106) is configured to apply alternating current of a second frequency (0104) to the other antenna function portion. It is preferable that the first frequency and the second frequency are basically different frequencies. However,
30 the first frequency and the second frequency may be the same. The first frequency and the second frequency may be 10 kilohertz or higher and 150 kilohertz or lower.

(Controller)

[0128] The "first controller" (0107) is configured to control alternating current output from the first circuit portion, and the "second controller" (0108) is configured to control alternating current output from the second circuit portion.

[0129] FIG. 22 is a diagram showing an example of the functional blocks of the food composition control device in the present embodiment. The first controller and the second controller may include a first frequency controller (4013) and a second frequency controller (0414), respectively, which control the frequency of the output alternating current. It is preferable that the first frequency and the second frequency are controlled to different frequencies by the first controller and the second controller, respectively. However, the first frequency and the second frequency may be the same. The first controller and the second controller may include a first phase controller (0415) and a second phase controller (0416), respectively, which control the phase of output alternating current. The first controller and the second controller may further include a first timing controller (0417) and a second timing controller (0418), respectively, which control the timing of stopping and outputting alternating current output.

(Control of Frequency)

<Example of Electromagnetic Fields Formed with Electromagnetic Waves of Different Frequencies (50 kHz and 47 kHz)>

[0130] FIG. 23 is a circuit diagram showing an example of the food composition control device in the present embodiment and shows an example of waveforms of electromagnetic fields. The food composition control device shown in the circuit diagram in FIG. 23A has a pair

of antenna function portions. One antenna function portion of a pair of antenna function portions has an antenna A and receives alternating current of 50 kHz as a first frequency from the first circuit portion. The other antenna function
5 portion of a pair of antenna function portions has an antenna B and receives alternating current of 47 kHz as a second frequency from the second circuit portion. In FIG. 23B, the waveform (P wave) of electromagnetic wave (0511) of the first frequency emitted from the antenna A is shown
10 by a solid line, and the waveform (Q wave) of electromagnetic wave (0512) of the second frequency emitted from the antenna B is shown by a dotted line. The electromagnetic field formed by a pair of antenna function portions is the waveform (P wave + Q wave) in FIG. 23C
15 obtained by adding the solid line and the broken line in FIG. 23B.

[0131] In the fryer 100 according to the first embodiment, an electromagnetic field is formed of electromagnetic waves of a single frequency, and the
20 waveform of electromagnetic waves is a simple waveform as shown by a solid line in FIG. 23B, for example, when the frequency applied to the antenna is 50 kHz. On the other hand, in the food composition control device in the present embodiment, the waveform can be formed in a complicated
25 shape with repeating amplification and attenuation, as shown in FIG. 23C.

<Example of Electromagnetic Fields Formed with Electromagnetic Waves of Different Frequencies (50 kHz and 30 kHz)>

30 [0132] FIG. 24 is a circuit diagram showing an example of the food composition control device in the second embodiment and a diagram showing an example of waveforms of electromagnetic fields for explaining another example of

the waveforms of electromagnetic field when a first frequency and a second frequency that are different are output. The food composition control device shown in the circuit diagram in FIG. 24A has a pair of antenna function
5 portions. One antenna function portion of a pair of antenna function portions has an antenna A and receives alternating current of 50 kHz as a first frequency from the first circuit portion. The other antenna function portion of a pair of antenna function portions has an antenna B and
10 receives alternating current of 30 kHz as a second frequency from the second circuit portion. In FIG. 24B, the waveform (P wave) of electromagnetic wave (0611) of the first frequency emitted from the antenna A is shown by a solid line, and the waveform (Q wave) of electromagnetic
15 wave (0612) of the second frequency emitted from the antenna B is shown by a dotted line. Then, the electromagnetic field formed by a pair of antenna function portions is the waveform (P wave + Q wave) in FIG. 24C obtained by adding the solid line and the broken line in
20 FIG. 24B. In FIG. 24C, compared with FIG. 23C, the waveform has regularity but the waveform is very characteristic.

[0133] As shown in FIG. 23 and FIG. 24, in the food composition control device in the present embodiment, the
25 first frequency and the second frequency that are basically different are applied, whereby a wide variety of complicated waveforms can be formed. The circuit diagrams shown in FIG. 23 and FIG. 24 have the simplest configuration as an example of a pair of antenna function
30 portions, and the number, direction, and shape of antennas may be changed and combined so that an even more complicated waveform can be formed into an electromagnetic field.

(Control of Phases)

<Description of Phase>

[0134] For example, the voltage of alternating current of an electromagnetic wave applied to the antenna function portion at a given time is expressed by Equation (1), where V_0 is the maximum value of intensity of wave, ω is angular frequency, and $\omega t + \alpha$ is the phase. The relation between angular frequency and frequency (f) is expressed by Equation 2.

10 (Equation 1)

$$V(t) = V_0 \cdot \sin(\omega t + \alpha)$$

(Equation 2)

$$\omega = 2\pi \cdot f$$

<Example of Electromagnetic Fields Formed with

15 Electromagnetic Waves of Different Phases: Same frequency of 50 kHz>

[0135] FIG. 25 is a circuit diagram showing an example of the food composition control device in the second embodiment and a diagram showing an example of waveforms of electromagnetic fields for explaining change in waveform of the electromagnetic field when different phases are applied to the first frequency and the second frequency. First of all, a case where the electromagnetic waves applied to a pair of antenna function portions have the same phase and frequency is described. In the food composition control device shown in the circuit diagram in FIG. 25A, the first frequency (0711) applied to the antenna function portion having an antenna A and the second frequency (0712) applied to the antenna function portion having an antenna B are 50 kHz, and the phase is $\alpha = 0$ for each. The waveform obtained by adding the waveform (P wave) of the electromagnetic wave of the first frequency emitted from the antenna A and the waveform (Q wave) of the

electromagnetic wave of the second frequency emitted from the antenna B is shown in FIG. 25B.

[0136] Next, a case where the electromagnetic waves applied to a pair of antenna function portions have the same frequency and different phases is described. In the food composition control device shown in the circuit diagram in FIG. 25C, the first frequency (0711) applied to the antenna function portion having an antenna A' is 50 kHz, and the phase is $\alpha = 0$. The second frequency (0712) applied to the antenna function portion having an antenna B' is 50 kHz, and the phase is $\alpha = \pi/2$. The waveform obtained by adding the waveform (P wave) of the electromagnetic wave of the first frequency emitted from the antenna A' and the waveform (Q wave) of the electromagnetic wave of the second frequency emitted from the antenna B' is shown in FIG. 25D. Basically, the waveform is a sine wave and a fundamental waveform. When the waveforms in FIG. 25B and FIG. 25D are compared, the frequencies are the same but the maximum value and the minimum value of wave intensity are different. In this way, in the food composition control device in the present embodiment, for example, when the first frequency and the second frequency are the same, the phase is controlled whereby the maximum value and the minimum value of wave intensity can be controlled with the frequency kept constant. Controlling the maximum value and the minimum value of the waveform with the frequency kept constant is possible even by changing the voltage. However, in the food composition control device in the present embodiment, the phase of the first frequency and the second frequency are controlled without controlling the voltage.

<Example of Electromagnetic Fields Formed with
Electromagnetic Waves of Different Phases: Different

Frequencies (50 kHz and 47 kHz)>

[0137] FIG. 26 is a circuit diagram showing an example of the food composition control device in the second embodiment and a diagram showing an example of waveforms of electromagnetic fields for explaining change in waveform of the electromagnetic field when different frequencies and phases are applied to the first frequency and the second frequency. First, a case where the frequencies of electromagnetic waves applied to a pair of antenna function portions are different is described. In the food composition control device shown in the circuit diagram in FIG. 26A, the first frequency (0811) applied to the antenna function portion having an antenna A is 50 kHz, the second frequency (0812) applied to the antenna function portion having an antenna B is 47 kHz, and the phase is $\alpha = 0$ for each. The waveform obtained by adding the waveform (P wave) of the electromagnetic wave of the first frequency emitted from the antenna A and the waveform (Q wave) of the electromagnetic wave of the second frequency emitted from the antenna B is shown in FIG. 26B.

[0138] Next, a case where the frequencies and the phases of electromagnetic waves applied to a pair of antenna function portions are different is described. In the food composition control device shown in the circuit diagram in FIG. 26C, the first frequency (0811) applied to the antenna function portion having an antenna A is 50 kHz, and the phase is $\alpha = 0$. The second frequency (0812) applied to the antenna function portion having an antenna B is 47 kHz, and the phase is $\alpha = \pi/2$. The waveform obtained by adding the waveform (P wave) of the electromagnetic wave of the first frequency emitted from the antenna A and the waveform (Q wave) of the electromagnetic wave of the second frequency emitted from the antenna B is shown in FIG. 26D. When the

waveforms in FIG. 26B and FIG. 26D are compared, there is almost no effect on the pattern of the waveform but the phase is changed. However, the change in phase presumably gives no change to food.

5 <Example of Electromagnetic Fields Formed with
Electromagnetic Waves of Different Phases: Different
Frequencies (50 kHz and 30 kHz)>

[0139] FIG. 27 is a circuit diagram showing an example
of the food composition control device in the second
10 embodiment and a diagram showing an example of waveforms of
electromagnetic fields, which is another diagram for
explaining change in waveform of the electromagnetic field
when different frequencies and phases are applied to the
first frequency and the second frequency. First, a case
15 where the frequencies of electromagnetic waves applied to a
pair of antenna function portions are different is
described. In the food composition control device shown in
the circuit diagram in FIG. 27A, the first frequency (0911)
applied to the antenna function portion having an antenna A
20 is 50 kHz, the second frequency (0912) applied to the
antenna function portion having an antenna B is 30 kHz, and
the phase is $\alpha = 0$ for each. The waveform obtained by
adding the waveform (P wave) of the electromagnetic wave of
the first frequency emitted from the antenna A and the
25 waveform (Q wave) of the electromagnetic wave of the second
frequency emitted from the antenna B is shown in FIG. 27B.
[0140] Next, a case where the frequencies and the phases
of electromagnetic waves applied to a pair of antenna
function portions are different is described. In the food
30 composition control device shown in the circuit diagram in
FIG. 27C, the first frequency (0911) applied to the antenna
function portion having an antenna A is 50 kHz, and the
phase is $\alpha = 0$. The second frequency (0912) applied to the

antenna function portion having an antenna B is 30 kHz, and the phase is $\alpha = \pi/2$. The waveform obtained by adding the waveform (P wave) of the electromagnetic wave of the first frequency emitted from the antenna A and the waveform (Q wave) of the electromagnetic wave of the second frequency emitted from the antenna B is shown in FIG. 27D. When the waveforms in FIG. 27B and FIG. 27D are compared, they are similar in that the pattern of the waveform has regularity, but the pattern of the waveform is changed due to the changed phase.

[0141] Which frequency to select may be determined in accordance with the impedance when an electromagnetic field is formed for food. Presumably, as the energy consumption by vibrations of polymer organic substances included in food, alcohols with a relatively large molecular weight, and alcohol derivatives with a relatively large molecular weight is increased, the effect of controlling the food composition emerges to have a favorable effect on the food. It is therefore preferable to control the frequency and the phase such that the impedance has a relatively large value. However, since as many impedance peaks as the kinds of substances included in the food may appear, the impedance peaks may be found by changing the frequency, and radiation for a short time for each peak may be repeated. For this, the impedance characteristic may be first checked while the frequency is swept from the lower limit value to the upper limit, and an overall radiation plan may be made by scheduling based on the check result. It is also preferable that the search for impedance peaks and the radiation planning are performed automatically.

(Control of Timing of Stopping and Outputting Alternating Current Output)

[0142] FIG. 28A is a circuit diagram showing an example

of the food composition control device in the present embodiment and an image diagram of an electromagnetic field region formed for a certain period of time. The food composition control device shown in the circuit diagram in

5 FIG. 28A has a pair of antenna function portions. One antenna function portion of a pair of antenna function portions has an antenna A and receives alternating current from the first circuit portion, in which the timing of stopping and outputting alternating current output is

10 controlled by the first controller having the first timing controller configured to control the timing of stopping and outputting alternating current output. The other antenna function portion of a pair of antenna function portions has an antenna B and receives alternating current from the

15 second circuit portion, in which the timing of stopping and outputting alternating current output is controlled by the second controller having the second timing controller configured to control the timing of stopping and outputting alternating current output. Since the first controller and

20 the second controller have the first timing controller and the second timing controller, respectively, for example, alternating current can be applied alternately from the first circuit portion and the second circuit portion to a pair of antenna function portions, or applied

25 intermittently, or applied for a fixed time of a day.

[0143] As an example, a case where the first circuit portion and the second circuit portion apply alternating current to the antenna function portion having an antenna A and the antenna function portion having an antenna B,

30 respectively, alternately for 0.0001 second will be described with reference to FIG. 28A. A region (1019) of the electromagnetic field formed by the antenna function portion having the antenna A for 0.0001 second is shown by

a solid line, and a region (1020) of the electromagnetic field formed by the antenna function portion having the antenna B for 0.0001 second is shown by a broken line. For example, if alternating current is output for 0.0001 second alternately from the first circuit portion and the second circuit portion to a pair of antenna function portions, the region in which an electromagnetic field is formed is switched between the solid-line range and the dotted-line range every 0.0001 second. Another example will be described with reference to FIG. 28A. When the first controller and the second controller perform control of outputting alternating current for 0.0001 second from the first circuit portion and the second circuit portion to a pair of antenna function portions and then stopping the output for 0.0001 second, a state in which an electromagnetic field is formed in both of the solid-line region and the broken-line region for 0.0001 second and thereafter a state in which an electromagnetic field is not formed for 0.0001 second are alternately repeated. These two examples have an effect on a food composition, different from when alternating current is continuously output from the first circuit portion and the second circuit portion to a pair of antenna function portions.

[0144] FIG. 28B is an image diagram showing an example of the timing of stopping and outputting alternating current output in the food composition control device in the present embodiment. One antenna function portion of a pair of antenna function portions has an antenna A and receives alternating current from the first circuit portion, in which the timing of stopping and outputting alternating current output is controlled by the first controller having the first timing controller configured to control the timing of stopping and outputting alternating current

output. The other antenna function portion of a pair of antenna function portions has an antenna B and receives alternating current from the second circuit portion, in which the timing of stopping and outputting alternating
5 current output is controlled by the second controller having the second timing controller configured to control the timing of stopping and outputting alternating current output. The abscissa axis indicates the time and shows the time when the antennas A and B form electromagnetic fields
10 by solid lines.

[0145] In FIG. 28B(a), the antenna A forms an electromagnetic field for a certain time (t_0 to t_1) and thereafter stops forming an electromagnetic field for a certain time (t_1 to t_2). While the antenna A stops forming
15 an electromagnetic field (t_1 to t_2), the antenna B forms an electromagnetic field for a certain time (t_1 to t_2). Subsequently, while the antenna B stops forming an electromagnetic field for a certain time (t_2 to t_3), the antenna A forms an electromagnetic field (t_2 to t_3).
20 Similar control is subsequently repeated, and such an example is shown in FIG. 28B(a). By performing the control as shown in FIG. 28B(a), only the antenna A forms an electromagnetic field (α) and thereafter only the antenna B forms an electromagnetic field (β); this control α to β is
25 repeated.

[0146] In FIG. 28B(b), the antenna A forms an electromagnetic field for a certain time (t_0 to t_1) and thereafter stops forming an electromagnetic field for a certain time (t_1 to t_4). The antenna B forms an
30 electromagnetic field for a certain time (t_2 to t_3) and thereafter stops forming an electromagnetic field for a certain time (t_3 to t_6), and subsequently similar control is repeated. By performing the control as shown in FIG.

28B(b), only the antenna A forms an electromagnetic field (α), followed by a time during which neither antenna forms an electromagnetic field (β), and then only the antenna B forms an electromagnetic field (γ), followed by a time
5 during which neither antenna forms an electromagnetic field (Δ); this control α to Δ is repeated.

[0147] In the example shown in FIG. 28B(c), the antenna A continuously forms an electromagnetic field, the antenna B forms an electromagnetic field for a certain time (t_1 to t_2) and thereafter stops forming an electromagnetic field
10 for a certain time (t_2 to t_3), and subsequently similar control is repeated. By performing the control as shown in FIG. 28B(c), only the antenna A forms an electromagnetic field (α) and thereafter both of the antennas A and B form
15 an electromagnetic field (β); this control α to β is repeated.

[0148] In FIG. 28B(d), the antenna A forms an electromagnetic field for a certain time (t_0 to t_2), thereafter stops forming an electromagnetic field for a
20 certain time (t_2 to t_3), and forms an electromagnetic field again for a certain time (t_3 to t_6). The antenna B forms an electromagnetic field for a certain time (t_1 to t_4) and thereafter stops forming an electromagnetic field for a
certain time (t_4 to t_5), and subsequently similar control
25 is repeated. By performing the control as shown in FIG. 28B(d), only the antenna A forms an electromagnetic field (α), followed by a time during which both antennas form an electromagnetic field (β), and then after a time during
which neither antenna forms an electromagnetic field (γ),
30 there is a time during which both antennas form an electromagnetic field (Δ); this control α to Δ is repeated.

[0149] In FIG. 28B(e), the antenna A forms an electromagnetic field for a certain time (t_0 to t_2),

thereafter stops forming an electromagnetic field for a certain time (t_2 to t_4), and forms an electromagnetic field again for a certain time (t_4 to t_6). The antenna B forms an electromagnetic field for a certain time (t_1 to t_3) and
5 thereafter stops forming an electromagnetic field for a certain time (t_3 to t_5), and subsequently similar control is repeated. By performing the control as shown in FIG. 28B(e), only the antenna A forms an electromagnetic field (α), followed by a time during which both antennas form an
10 electromagnetic field (β), and then after a time during which only the antenna B forms an electromagnetic field (γ), there is a time during which neither antenna forms an electromagnetic field (Δ); this control α to Δ is repeated.

[0150] It is needless to say that the method of
15 controlling the timing of stopping and outputting alternating current output in the food composition control device in the present embodiment is not limited to these five examples shown in FIG. 28B. Controlling alternating current output in this manner can have an effect on the
20 food composition, different from when the first circuit portion and the second circuit portion continuously output alternating current to a pair of antenna function portions.

[0151] It is needless to say that the control of the food composition control device in the present embodiment
25 is not limited to the examples shown in FIG. 28A and FIG. 28B. In addition to the control of frequency or/and phase, the first controller and the second controller have the first timing controller and the second timing controller, respectively, to control the timing of stopping and
30 outputting alternating current output, thereby enabling various control of electromagnetic fields formed by the food composition control device in the present embodiment.
(Effect of Arrangement of Antennas)

[0152] FIG. 29A is a schematic diagram showing an example of arrangement of the antennas of a pair of antenna function portions. In FIG. 29A(a) to FIG. 29A(d), the antennas of one antenna function portion of a pair of antenna function portions are A and A', and the antennas of the other antenna function portion are B and B', in which a plan view is shown on the upper side and a perspective view is shown in the lower side. FIG. 29A(a) and FIG. 29A(b) show an example in which four flat plate-shaped antennas are used to form electromagnetic fields. In FIG. 29A(a), the antennas A and A' and the antennas B and B' are arranged to face each other. On the other hand, in FIG. 29A(b), the normal axes of the antennas A and A' and the antennas B and B' are orthogonal to each other. In FIG. 29A(c), two antennas A and B are used, each having an L-shape, and A and B face each other. In FIG. 29A(a) to FIG. 29A(d), the directions of electromagnetic waves forming electromagnetic fields are shown. For example, although the arrangement of the antennas is the same in FIG. 29A(a) and FIG. 29A(b), the directions of electromagnetic waves are different and the formed electromagnetic fields are also different. As shown in FIG. 29A(d), the arrangement of the antenna A and the antenna B is not limited to the position facing each other, and the antennas do not necessarily face each other. It is needless to say that the arrangement and shape of antennas is not limited to the examples in FIG. 28. In addition to the control of frequency and/or phase, the shape and arrangement of antennas allows electromagnetic waves forming electromagnetic fields to cross each other or to travel parallel to each other. In this way, the characteristics of electromagnetic waves forming electromagnetic fields can be controlled also by the arrangement of the antennas.

[0153] FIG. 29B is a schematic diagram showing an example of the arrangement of antennas of a pair of antenna function portions. The antennas of one antenna function portion of a pair of antenna function portions are A and A', and the antennas of the other antenna function portion are B and B', in which a plan view is shown on the upper side and a perspective view is shown on the lower side. In FIG. 29B(a), A and A' are disposed on the sides to face each other, and B and B' are disposed to face each other in the top-bottom direction. In FIG. 29B(a), the antennas of one antenna function portion of a pair of antenna function portions are disposed in proximity to the side surfaces, and the antennas of the other antenna function portion are disposed in proximity to the bottom surface. As shown in FIG. 29B(c), the antenna A of one antenna function portion of a pair of antenna function portions is in the shape of a letter C. The antenna B of the other antenna function portion is also in the shape of a letter C.

[0154] FIG. 29C is a schematic diagram showing an example of the arrangement of antennas of a pair of antenna function portions. In FIG. 29C(a) to FIG. 29C(d), the antenna of one antenna function portion of a pair of antenna function portions is A, and the antenna of the other antenna function portion is B, in which a plan view is shown on the upper side and a perspective view is shown on the lower side. The antennas A and B in FIG. 29C(a) have a shape formed by dividing an approximately spherical shape into four, and the antennas in FIG. 29C(b) have a shape formed by dividing an approximately spherical shape into two. In this manner, the antenna may have a spherical surface. The antennas in FIG. 29C(c) and FIG. 29C(d) have a shape formed by dividing a cylinder into two, in which FIG. 29C(c) shows an example in which a bottom surface is

not provided, and FIG. 29C(d) shows an example in which a bottom surface is provided. It is needless to say that the arrangement and shape of the antennas A and B is not limited to the examples in FIGs. 29B and 29C. Similar to
5 FIG. 29A, FIGs. 29B and 29C also indicate that the characteristics of electromagnetic waves forming electromagnetic fields can be controlled also by the arrangement of antennas.

(Mechanism by Which Electromagnetic Field Controls Food

10 Composition)

<Frying in Dynamic Electromagnetic Field in Single Frequency>

[0155] The inventor of the present invention has successfully developed a fryer by means of which food is
15 cooked in a space where electromagnetic waves in frequencies from 10 kilohertz to 150 kilohertz are generated between the opposed plate antennas, so that the eating quality of the cooked food can be made very high. A fryer 100 is provided by which food is cooked in dynamic
20 electromagnetic fields formed with a single frequency in a fry reservoir (first embodiment).

[0156] In the fryer 100 according to the first embodiment, the mechanism by which the cooked food is crispy on the surface and juicy inside is as follows.
25 Long-chain fatty acid salts such as sodium oleate that may be generated by heating and hydrolysis of food oil have a carboxyl chain functioning as hydrophilic group and a hydrocarbon chain moiety functioning as lipophilic group. In the first embodiment, the invention of a cooking method
30 using food oil including long-chain fatty acid salts is further provided. Long-chain fatty acid salts play a role of blending an oil component in food oil with a water component present on a surface of food put into the food

oil. In particular, when particulate water is present on a surface of food, the long-chain fatty acid salt aligns on the surface of water, and the electromagnetic waves applied at the electromagnetic waves-generating step allow the
5 long-chain fatty acid salt to vibrate in proximity to the surface of water.

[0157] For example, in the case of sodium laurate shown in FIG. 30, electromagnetic waves act on and vibrate the hydrophilic group moiety in the food oil.

10 [0158] Then, the hydrophilic group in contact with the particulate water vibrates to gradually make water particles finer. Because of this phenomenon, even if particulate water is present on a surface of food immediately after the food is applied into hot food oil,
15 the water is instantaneously formed into fine particles, and an oil splash phenomenon does not occur. In addition, the long-chain fatty acid salt aligns on the surface of the food, with the hydrophilic group on the food side and the lipophilic group on the food oil side, so that penetration
20 of food oil into the food can be prevented to some extent. Because of this, oiliness of food due to penetration of oil or ejection of water from the inside of the food can be prevented to some extent. With these actions in
25 combination, the cooked food has a crispy surface and is moist and juicy inside.

<Comparison Between First Embodiment and Second Embodiment>

[0159] The inventor of the present invention has found that improvement and enhancement of the eating quality and keeping freshness for a long time can be achieved by
30 forming an electromagnetic field suitable for each individual food with the frequency and the phase of alternating current applied to each of a pair of antenna function portions. In the fryer 100 in the first

embodiment, an electromagnetic field is formed with a single frequency, and a cooking method is also provided that includes the step of increasing/decreasing the frequency and the output of electromagnetic waves during the cooking process. However, as long as the frequency is single, the electromagnetic waves forming electromagnetic fields is unable to have a complicated waveform as in the present invention even by changing the frequency and the output during cooking.

10 [0160] Food contains a large amount of polar ingredients besides fatty acid salts such as sodium oleate. Food also contains a large amount of polar organic polymers. For example, water contained in large amounts in food is one of polar molecules. In the food composition control device of the present invention, an electromagnetic field suitable for each individual food is formed with the frequency and the phase of alternating current applied to each of a pair of antenna function portions, whereby the waveform of the electromagnetic waves forming electromagnetic fields is controlled to have a complicated shape, so that more polar substances in the food can be vibrated to exert a good effect on the food as shown by the third embodiment to the eleventh embodiment described later.

[0161] There are various cooking methods other than frying. Even when the cooking method is the same, the water content and the surface-active component contained vary with the food to be cooked, and electromagnetic fields for controlling the food composition suitable for each individual cooking method and food should vary. As described above, in the food composition control device in the present embodiment, the frequency, the phase, and the timing of stopping and outputting of alternating current output can be controlled, and an electromagnetic field

suitable for each individual cooking method and food can be formed. Accordingly, the effect on food is higher than by the fryer 100 shown in the first embodiment.

[0162] In the food composition control device of the
5 present invention, since the electromagnetic field formed by the food composition control device can mainly vibrate polar substances with a relatively high molecular weight, such as long-chain fatty acid salts and proteins, the vibration of such large molecules indirectly vibrates the
10 surrounding free water. Food contains polymers having a variety of vibration frequencies, and applying electromagnetic waves with various frequency components can increase the kinds of substances that vibrate naturally. Free water can exist in food in three states: solid (ice),
15 liquid, and gas (water vapor). In other words, free water is water that can undergo changes including vaporization, aggregation, sublimation, solidification, and melting. In the food composition control device of the present invention, vibration of large molecules and indirect
20 vibration of free water in the food enable the food control such as improvement and enhancement of the eating quality or keeping freshness of food for a long time.

[0163] Carbohydrate such as protein and starch contained in large amounts in food forms hydrogen bonding with water
25 and is easily hydrated. In the food composition control device of the present invention, protein, starch, etc. vibrate, therefore easily come into contact with water, and easily form hydrogen bonding, causing hydration. In the food composition control device of the present invention,
30 the hydration phenomenon promoted in this manner is thought to be one of reasons why improvement and enhancement of the eating quality and keeping freshness of food for a long time are achieved by controlling the food composition.

[0164] In general, when food is frozen, it is important to quick-freeze the food and suppress growth of ice crystals in order to prevent degradation of the food. It is requested to reduce the time passing through the
5 temperatures of around -1 to -5°C at which water in the food is frozen. This is because the growth of ice crystals destroys cell walls and cell membranes of vegetables and fish, and water or umami components (savory taste) elude from the destroyed part in defrosting, making the food
10 texture and the eating quality worse. Molecules can move freely in a liquid state but scarcely move when solidified into a solid state. On the other hand, bound water having hydrogen bonding to the ingredients such as protein in the food is not frozen. In the food composition control device
15 of the present invention, therefore, the ingredients in the food such as proteins presumably vibrate because of the electromagnetic field, even when the temperature of the food drops near the temperature at which water freezes. The free water in the food also keeps indirect vibration
20 and is less likely to freeze, causing a state close to supercooling, because water molecules still move even when the temperature of the food drops near the temperature at which water freezes. When water partially starts freezing, the entire food is rapidly frozen by this stimulus, so that
25 minute ice crystals are formed. Accordingly, the growth of ice crystals, which occurs when water in food gradually freezes, is less likely to occur, and degradation of the food due to freezing can be prevented

[0165] For example, when sherbet is made by freezing,
30 the part where ice crystals are grown may contain much water and lack taste, while the sherbet may taste strong at some other parts. However, when food is frozen using the food composition control device of the present invention,

unevenness of flavor does not occur in sherbet because of quick-freezing.

[0166] When cooked food such as gratin and noodles is frozen, water separates from sauce or noodles during
5 defrosting, and the eating quality, the food texture, and the appearance may be different from those before defrosting. However, when food is frozen using the food composition control device of the present invention, growth of ice crystals is suppressed in sauce or noodles because
10 of quick-freezing, so that drip loss during defrosting is suppressed and the eating quality can be kept as good as before freezing.

[0167] When food is defrosted, the temperature of the food rises, and ice in the food dissolves. When water
15 dissolves, heat (heat of dissolution) is released and therefore the temperature of the food is less likely to rise around -1 to -5°C slightly lower than the dissolution temperature. Water partially dissolved solidifies again to cause growth of ice crystals, which may deteriorate the
20 food. In the food composition control device of the present invention, even when ice partially dissolves into liquefied water, the liquefied water is indirectly vibrated by the effect of electromagnetic field and is not solidified again, and degradation of the food can be
25 prevented.

[0168] One of typical phenomena of food degradation is oxidation. For example, wine is easily oxidized and once opened, its taste and aroma are reduced over time. Alcohol, when oxidized, changes into aldehyde or carboxylic acid,
30 and the product of such oxidation is often a substance having high polarity and easily bound to water through hydrogen bonding. In the food composition control device of the present invention, since water indirectly vibrates

as described above, the oxidation product easily comes into contact with water and is bound to water through hydrogen bonding and easily hydrated. Even when wine tastes worse after opening, its degraded eating quality or aroma is less likely to be perceived, possibly because the oxidation product is hydrated and the oxidation product wrapped in water touches the tongue or nose. Alternatively, in the food composition control device of the present invention, the oxidation product may be reduced by the electromagnetic field.

[0169] When the food composition control device of the present invention is used for wine before opening, hydration and reduction of the oxidation product makes the wine smooth and controls the taste and the aroma as if the wine is an aged wine. The food composition control device of the present invention can remove bitterness or undesirable flavor of whisky or Japanese sake and make the flavor mellow.

[0170] The food composition control device of the present invention can form an electromagnetic field under a condition with the regulated temperature and humidity as described later and can control the food composition while food is cooked or stored. Besides wine, a variety of foods thus can be aged. For example, it can be used for aging of fermented food such as meat, cheese, and taste and can reduce the time taken for aging.

[0171] One of the reasons of degradation of food is dryness. For example, it is a well-known fact that if vegetable or sashimi (raw fish) dries, both food texture and taste are reduced. Fried food often tastes greasy over time. One of the reasons for this is probably that moisture separates from the ingredient of fried food and moves to the batter. In the food composition control

device of the present invention, as described above, the ingredients in food easily come into contact with water. This promotes hydration of water with a substance in the food that can cause a hydration phenomenon, such as ionic
5 compounds or hydrogen bonding compounds, and can increase bound water. Then, water less evaporates from the food, and inevitably, dryness of the food is suppressed. The effect of promoting hydration of the ingredients in the food in the food composition control device of the present
10 invention presumably increases the water retention ability of the ingredient of the fried food, so that water does not separate or move to the batter, and the fried food is less likely to become greasy.

[0172] On the other hand, some cooking methods require
15 water or taste to penetrate into food. In the food composition control device of the present invention, before rice or sticky rice is cooked, water is allowed to penetrate into rice or sticky rice in a food soaking tank as described later to make rice fluffy. In cooking of
20 cereals such as rice and sticky rice, starch contained much in cereals is hydrated into alpha starch (which requires heating). In the food composition control device of the present invention, hydration of starch and water seems to be promoted because the ingredients in food easily come
25 into contact with water. This probably facilitates gelatinization in the subsequent rice cooking and makes rice fluffy.

[0173] Stewing the ingredients of beef-on-rice bowls is described, by taking onions as an example. This cooking
30 method involves destroying cell walls and cell membranes of onions by heating and allowing umami components such as amino acids in the broth to soak into the softened onions. When the warmed state is kept after cooking, the cell walls

and cell membranes are destroyed by heating, so that the crunchiness of onions is lost as the warm state is kept for a long time. If the beef is kept warm, the water content in meat is reduced, making the meat tough. In the food composition control device of the present invention, umami components such as amino acids vibrate and easily penetrate without destructing the cell walls and cell membranes of onions, so that seasoning soaks into the ingredients while keeping the food texture. Even when keeping warm continues in the food composition control device of the present invention, the surface-active component such as long-chain fatty acid salts contained in the food is affected by the electromagnetic field, similarly to the effect by the fryer 100 in the first embodiment, so that the lipophilic group is easily arranged on the outside of the food and oil having an affinity to the lipophilic group easily forms a film around the food such as onions and meat in the broth. The food in the broth is as if it is coated with oil, which retains water and umami in the food and keeps the food texture and the eating quality.

[0174] The food composition control device of the present invention can have a cooking portion as described later and preferably further includes a water vapor supply portion that supplies water vapor or/and water spray to the cooking portion. In the food composition control device of the present invention, water vapor or/and water spray is supplied to the cooking portion, whereby gaseous or/and fine water particles can be supplied to the food or the cooking portion having the food thereon. This configuration is effective in particular for the cooking methods that require water supply for controlling the food compositions.

<Electrocapillary at Interface between Food Oil and

Physiological Saline Solution>

[0175] The inventor of the present invention has been continuously seeking for the reasons why electromagnetic fields have such excellent effects in controlling food compositions. Noting that the eating quality is improved when a dynamic electromagnetic field is formed in a frying tank, the research group including the inventor of the present invention has been conducting research on electrocapillary at the interface between food oil and physiological saline solution. Electrocappillary is a phenomenon in which when an electric field is applied to two phases that do not mix, the interfacial tension is changed. It has been found that in food oil that contains 10^{-3} mol/l of sodium oleate, the interfacial tension is reduced by 20% when an AC electric field of 50 kHz and 200 Vpp is applied (FIG. 7 in the first embodiment).

[0176] This suggests that applying an AC electric field exerts an effect on interfacial activity. Plant or animal-derived food contains water in the amount of 70% or so, and the cell membranes are formed of lipid bilayer membranes. It is estimated that the food composition can be controlled by applying an AC electric field to exert an effect on the interfacial activity of water in cells and cell membranes. For example, milk forms an o/W emulsion, and most food probably contains some surface-active component if not forming such emulsion. The food composition control device in the present embodiment can form electromagnetic fields with various patterns of waveforms and seems to act on the interfacial activity in the food to control the food.

(Description of Hardware Configuration)

[0177] FIG. 31 is a schematic diagram showing an example of the configuration of the food composition control device, in which the functional components described above are

implemented as hardware. Referring to this figure, the functions of the hardware components in the food composition control process will be described.

[0178] As shown in the figure, the food composition control device in the present embodiment includes a "CPU" (1321) that implements the first controller and the second controller as hardware, a "main memory" (1322), a "hard disk drive (HDD)" (1323), a "circuit interface" (1324), an "input/output (I/O)" (1325), and a "user interface" (1325). The main memory has a "first control program", a "second control program", "control data", and a "circuit driver". The food composition control device in the present embodiment can transmit/receive information, for example, through the I/O such as "keyboard" and "camera" and can accept an instruction signal associated with a food processing method such as freezing and heating and accept an instruction to specify the kind or the volume of food through operation of the user interface such as an operation panel of the food composition control device or a remote controller. The circuit interface can implement the "first circuit portion", the "second circuit portion", and the "antenna" as hardware. This circuit interface can be provided by wire or by radio.

[0179] A program is read on the "main memory", and the "CPU" refers to the read program to execute a variety of operation processing in accordance with the procedure specified by the program. A plurality of addresses are allocated to each of the "main memory" and the "HDD", and in the operation processing in the "CPU", the address is specified, data stored therein is accessed, whereby the operation processing using the data can be performed.

[0180] First of all, the CPU reads the first control program and the second control program from the HDD and

loads them on the main memory. For example, when information of food placed in the food composition control device is input through the user interface such as the operation panel of the food composition control device, the control data is referred to, the first control program and the second control program are executed, and the frequency or/and the phase of alternating current output from the first circuit portion and the second circuit portion are controlled through the circuit driver. Alternating current having a predetermined frequency or/and phase is then applied from the first circuit portion and the second circuit portion to the antenna function portion through the circuit interface. The CPU can control various conditions including voltage of alternating current and a period of time in which alternating current is applied, in addition to the control of frequency and phase of alternating current output from the first circuit portion and the second circuit portion.

[0181] Power from a power source is also supplied to the first circuit portion and the second circuit portion, so that the first circuit portion and the second circuit portion can output alternating current and apply alternating current to the antennas. The voltage supplied by the power source is, for example, 100 V, which is the voltage of a commercial power supply.

<Process Flow>

[0182] FIG. 32 is a flowchart showing an example of the process flow in the food composition control device in the present embodiment. The steps shown below may be steps executed by the hardware configuration of a computer as described above or may be process steps of a program recorded on a medium for controlling the first controller or/and the second controller.

[0183] As shown in this figure, first of all, at step S1431, the first controller applies an electromagnetic field of a first frequency to the food (first frequency applying step). At step S1432, the second controller
5 applies an electromagnetic field of a second frequency, which is a frequency different from the first frequency to the food (second frequency applying step). Here, the process order of step S1431 and step S1432 may be switched.
<Second Embodiment: Effects>

10 [0184] The food composition control device in the present embodiment can form electromagnetic waves forming an electromagnetic field in shapes more complicated than the conventional ones and therefore can enhance the effect of electromagnetic fields on food, compared with the
15 conventional technique, and have a good effect on the food composition. Specifically, improvement and enhancement of the eating quality or keeping food fresh for a long time can be achieved.

<<Third Embodiment>>

20 <Third Embodiment: Overview>

[0185] The food composition control device in the present embodiment is based on the second embodiment, includes a frying tank and a heating portion for heating the frying tank, and is characterized by performing food
25 composition control in frying food.

<Third Embodiment: Configuration>

[0186] FIG. 33A is a conceptual diagram showing an overview of the food composition control device in the present embodiment. The food composition control device in
30 the present embodiment further includes a frying tank (1541) and a heating portion (1542) for heating the frying tank. A pair of antenna function portions (1501, 1502) are disposed to form an electromagnetic field in the frying

tank. An antenna of one antenna function portion has a rectangular shape about 23 cm in the lengthwise direction and about 10 cm in the widthwise direction. Power for activating this antenna is 100 W. The antenna function portion thus configured is regarded as a general type and mainly used in description and testing in the following embodiments. Although power for activating may be 200 W or 300 W, 100 W is sufficient to fulfill the food composition function.

10 <Third Embodiment: Examples>

[0187] As shown in FIG. 33A, food oil was put into the frying tank, an electromagnetic field was formed by a pair of antenna function portions in the frying tank, and the food oil was heated by the heating portion to about 170°C.

15 Here, the frying tank has a width of 50 cm, a depth of 40 cm, and a height of 30 cm, and the antenna function portions that constitute a pair of antenna function portions (general type) are disposed about 1 cm apart from the side walls facing each other in the width direction of

20 the frying tank, and the distance between the antenna plate surfaces of the antenna function portions is about 48 cm. The antenna function portions are each disposed such that the lengthwise direction of the antenna function portion extends along the depth direction of the frying tank. Both

25 ends in the lengthwise direction of the antenna function portion are disposed about 5 cm apart from the side walls facing each other in the depth direction of the frying tank. Food oil fills the frying tank up to 25 cm in the height direction. In such a configuration, 50 g of silken tofu,

30 not drained, was put into the frying tank, but almost no oil splash occurred. After three minutes, silken tofu was removed from the frying tank. When similar cooking was performed without forming an electromagnetic field in the

frying tank, a big oil splash occurred when tofu was put in. The cross sections of the silken tofu after cooking were compared. The silken tofu with no electromagnetic field had a plurality of bubbles with diameters of 5 to 20 mm and
5 tasted dried out. On the other hand, the silken tofu cooked with the food composition control device in the present embodiment had no bubbles. The taste was less dried out and was juicy.

<Third Embodiment: Evaluation Test>

10 [0188] Using the food composition control device in the present embodiment, an electromagnetic field was formed in the frying tank in which target food was placed by the method described below. A sensory test of the food in which food composition was controlled was conducted for 10
15 subjects. In the sensory test, the subjects made evaluation in six levels: 5 points for "very good", 4 points for "good", 3 points for "rather good", 2 points for "rather bad", 1 point for "bad", and 0 point for "very bad". The subjects evaluated two items including taste and food
20 texture for each individual food, and the points were summed up (as used herein the sensory test refers to a test by summing up the points, unless otherwise specified). The maximum evaluation score per subject is 10 points (taste 5 points + food texture 5 points = 10 points) and there are
25 10 tests, so the maximum score is 100 and the minimum score is 0. (Method)

[0189] Alternating current of a first frequency and alternating current of a second frequency were applied to the food placed in the frying tank to control the food
30 composition. The first frequency and the second frequency were in a range of 5 kHz to 200 kHz, and an electromagnetic field was formed in the frying tank in actually 36 combinations shown in the table in FIG. 33B.

[0190] The test was also conducted for a case where one of the first frequency and the second frequency was 0 kHz, that is, alternating current was applied to either one antenna function portion, and for a case where both

5 frequencies were 0 kHz, that is, alternating current was not applied to either antenna function portion, in order to make a comparison with the effect brought by the food composition control according to the present embodiment.

[0191] The lower side in the table indicates the score
10 in the case where alternating current was applied with the first frequency of 100 kHz, the second frequency of 150 kHz, the phase of the first frequency $\alpha = 0$, and the phase of the second frequency $\alpha = \pi/2$. The numerical value in brackets indicates that the difference from the score in

15 the case where the first frequency was 100 kHz, the second frequency was 150 kHz, and both were applied in the same phase. The evaluation result is shown in the form of a graph for each second frequency applied, in which the abscissa axis indicates the value of first frequency, and
20 the ordinate axis indicates the evaluation result (0 point to 100 points).

(Food and Test Result)

[0192] This test was carried out with the general-type antenna function portions placed in the frying tank shown
25 in FIG. 33A in a similar manner. Silken tofu cut into 25 g of a substantially cubic shape was cooked for five minutes in oil at 170°C in the frying tank while alternating current was applied in each combination. As shown in FIG. 33B, the rating is high (65 points or higher) when both of
30 the first frequency and the second frequency are in a range of 10 kHz to 150 kHz (enclosed by a thick line in the table). The result when a phase difference is applied between the first frequency (100 kHz) and the second

frequency (150 kHz) is 85 points. The result with no phase difference is 84 points, and the difference is +1 point. This is applicable to the following tables showing the test results. The rating is slightly increased by applying a
5 phase difference.

[0193] The test described above was performed for frozen fried chicken instead of silken tofu. Specifically, no-fry chicken (not cooked) was cooked in oil at 170°C for five minutes in the frying tank. FIG. 33C shows the result of
10 the sensory test of the chicken. The rating is high when both of the first frequency and the second frequency are in a range of 10 kHz to 150 kHz. The result when a phase difference is applied between the first frequency and the second frequency is 82 points. The result with no phase
15 difference is 81 points, and the rating is slightly increased by applying a phase difference.

<Third Embodiment: Effects>

[0194] In the food composition control device in the present embodiment, even when raw food containing water is
20 put into the frying tank containing heated oil, oil splash scarcely occurs. The food composition control device can make the eating quality juicy and less dried out after cooking.

<<Fourth Embodiment>>

25 <Fourth Embodiment: Overview>

[0195] The food composition control device in the present embodiment is based on the second embodiment, further includes a food soaking tank capable of storing edible liquid for soaking or/and extracting food to allow
30 the edible liquid to soak into or/and extract the food, and is characterized by performing food composition control by allowing edible liquid to soak into food.

<Fourth Embodiment: Configuration>

[0196] FIG. 34A is a conceptual diagram showing an overview of the food composition control device in the present embodiment. The food composition control device in the present embodiment further includes a food soaking tank
5 (1643) capable of storing edible liquid for soaking or/and extracting food (1661) to allow the edible liquid (1662) to soak into or/and extract the food. A pair of antenna function portions (1601, 1602) are disposed to form an electromagnetic field in the food soaking tank.

10 [0197] The temperature for allowing edible liquid to soak into or extract food is not limited. When the food includes an ingredient that is easily denatured or volatilized by heating, processing at low temperature is preferable, whereas when heating facilitates penetration of
15 the ingredient in the edible liquid into the food, processing at high temperature is possible.

<Fourth Embodiment: Examples>

[0198] Uncooked rice was soaked in water in the food soaking tank and an electromagnetic field was formed in the
20 food soaking tank to reduce the time for soaking and make rice fluffy. Sticky rice was also made fluffy similarly to rice. It is known that when water is soaked into rice, higher water temperature can reduce the time for soaking. It is also said that soaking rice at low temperature
25 improves the eating quality. In the food composition control device in the present embodiment, even when rice is soaked in water at low temperature, the time for soaking can be reduced. When tsukemono (Japanese pickles) or pickles were preserved, for example, vegetable was soaked
30 in a pickle solution in the food soaking tank and an electromagnetic field was formed in the food soaking tank to allow seasoning to soak well into the vegetable and reduce the soaking time. For example, when meat or fish

was stewed in soup, meat or fish was soaked in soup containing umami components in the food soaking tank and an electromagnetic field was formed in the food soaking tank to allow the soup to soak well into the meat or fish and
5 reduce the time for stewing.

[0199] When fruit liquor was made, fruit was soaked in edible liquid such as liquor in the food soaking tank and an electromagnetic field was formed in the food soaking tank. The fruit in the edible liquid was then extracted
10 into the edible liquid for a short time, resulting in a mature fruit liquor. This process is effective also for tea and coffee. For example, green tea was soaked in hot water in the food soaking tank, and an electromagnetic field was formed in the food soaking tank. Green tea was
15 extracted for a short time with vivid color and good flavor. When coffee was extracted using the food composition control device in the present embodiment, for example, coffee was extracted in an amount smaller than usual but the taste and flavor was the same as usual, because the
20 amount of extract in hot water was increased.

<Fourth Embodiment: Evaluation Test>

[0200] A sensory test was conducted on "rice" similarly to the test performed in the third embodiment. The food soaking tank has a width of 50 cm, a depth of 40 cm, and a
25 height of 30 cm. The antenna function portions that constitute a pair of antenna function portions (general type) are disposed about 1 cm apart from the side walls facing each other in the width direction of the food soaking tank, and the distance between the antenna plate
30 surfaces of the antenna function portions is about 48 cm. The antenna function portions are each disposed such that the lengthwise direction of the antenna function portion extends along the depth direction of the food soaking tank.

Both ends in the lengthwise direction of the antenna function portion are disposed about 5 cm apart from the side walls facing each other in the depth direction of the food soaking tank. In such a configuration, 1 kg of Koshihikari was quickly washed, then drained in a strainer, and put into the food soaking tank. As edible liquid, 1 kg of water was added, and a first frequency and a second frequency were applied in a variety of combinations in a similar manner as in the third embodiment. After soaking for 10 minutes, the rice was drained in a strainer. "Rice" cooked with the same type of rice cooker under the same condition with the food composition controlled was individually evaluated. FIG. 34B shows the result of this sensory test. The rating is high when both of the first frequency and the second frequency are in a range of 10 kHz to 150 kHz. The result when a phase difference is applied between the first frequency and the second frequency is 83 points, one point up.

[0201] A sensory test similar to the test for "rice" above was conducted on "green tea". Ten grams of green tea in a nonwoven fabric bag and one liter of hot water at 95°C as edible liquid were put into the food soaking tank to make tea by soaking for one minute. FIG. 34C shows the result of this sensory test. The rating is high when both of the first frequency and the second frequency are in a range of 10 kHz to 150 kHz. The result when a phase difference is applied between the first frequency and the second frequency is 77 points, one point up.

[0202] A sensory test similar to the one described above was conducted on "green tea". Ten grams of green tea in a nonwoven fabric bag and two liters of hot water at 95°C as edible liquid were put into the food soaking tank to make tea by soaking for two minutes. FIG. 34D shows the result

of this sensory test. The rating is high when both of the first frequency and the second frequency are in a range of 10 kHz to 150 kHz. The result when a phase difference is applied between the first frequency and the second

5 frequency is 77 points, one point up.

[0203] Subsequently, a test to measure the amount of water absorption by soaking was conducted on "rice". The test environment was similar to the one in the sensory test for rice. One hundred grams of Koshihikari were quickly
10 washed, then drained in a strainer, and put into the food soaking tank. As edible liquid, 100 g of water was added, and after soaking for 10 minutes, rice was drained in a strainer and its weight was measured. A similar test was repeated three times, and a total value of the increased
15 weight was measured. This value was used as a score. The temperature of the food soaking tank was 15°C. FIG. 34E shows the result of this test. The amount of water absorption is a high value when both of the first frequency and the second frequency are in a range of 10 kHz to 150
20 kHz. The result when a phase difference is applied between the first frequency and the second frequency is 73 points, one point up.

[0204] A test for the amount of water absorption similar as described above was conducted on "soybeans". One
25 hundred grams of soybeans were put into the food soaking tank, and 100 g of consommé soup was put into the food soaking tank as edible liquid. After soaking for 30 minutes, the soybeans were drained in a strainer and the weight was measured. A similar test was repeated three
30 times, and a total value of the increased weight was measured. This value was used as a score. FIG. 34F shows the result of this test. Also in this test, the value is high when both of the first frequency and the second

frequency are in a range of 10 kHz to 150 kHz. The result when a phase difference is applied between the first frequency and the second frequency is 90 points, two points up.

5 <Fourth Embodiment: Effects>

[0205] The food composition control device in the present embodiment allows edible liquid to penetrate faster into the food soaked in the edible liquid. Since the edible liquid penetrates into the food and the ingredients
10 in the food dissolves into the edible liquid, the time taken to extract the ingredients in the food into the edible liquid can be reduced, and the amount of extract can be increased.

<<Fifth Embodiment>>

15 <Fifth Embodiment: Overview>

[0206] The food composition control device in the present embodiment is based on the second embodiment, further includes a high-temperature food cooking portion for heating food at high temperature, and is characterized
20 by performing food composition control by making food hot.

<Fifth Embodiment: Configuration>

[0207] FIG. 35A is a conceptual diagram showing an overview of the food composition control device in the present embodiment. The food composition control device in
25 the present embodiment further includes a high-temperature food cooking portion (1744) for heating food (1761a, 1761b, 1761c) at high temperature. A pair of antenna function portions (1701, 1702) are disposed to form an electromagnetic field in the high-temperature food cooking
30 portion.

[0208] The high-temperature food cooking portion of the food composition control device in the present embodiment can be used not only for cooking, for example, boiling,

baking, steaming, and frying, but also for preserving food, for example, storing cooked rice at a temperature of 60°C or higher and preventing degradation of starch and proliferation of microorganisms to keep the eating quality of cooked rice. The food composition control also includes keeping taste or soy sauce at high temperature and promoting the activity of microorganisms and ferment to mature the food. In the high-temperature food cooking portion, food is heated at high temperature. The temperature is normal temperature or higher and preferably 40°C or higher, although the temperature varies depending on the kinds of food and the purpose of food composition control.

<Fifth Embodiment: Examples>

[0209] FIG. 35A(a) shows an example in which one (1701) of a pair of antenna function portions also serves as a high-temperature food cooking portion (1744). When the antenna function portion also has the function of the high-temperature food cooking portion, it is preferably formed of iron or stainless steel. In this example, one antenna function portion is formed in the shape of a rectangular plate 50 cm in the lengthwise direction and 40 cm in the widthwise direction. One antenna function portion and the other antenna function portion face each other at a distance of about 4 cm from each other. Beef for steak (1761a) was placed on the high-temperature food cooking portion also serving as an antenna function portion, and while an electromagnetic field was formed, beef for steak was cooked for two minutes on each side. Without forming an electromagnetic field, beef for steak was cooked similarly, for comparison. The beef for steak cooked with an electromagnetic field formed was cooked through, while the beef for steak cooked without forming an

electromagnetic field was not cooked through. Other examples in which the antenna function portion also has the function of the high-temperature food cooking portion include, but not limited to, plates of hot plates, baking sheets or grills of ovens or toasters, pots of rice cookers, iron pans, and iron plates.

[0210] Referring to FIG. 35A(b), an example of cooking the ingredients of beef-on-rice bowls will be described. The container shown in the figure is a container that has a similar size as the frying tank shown in the third embodiment or the food soaking tank shown in the fourth embodiment, and a pair of general-type antenna function portions are disposed in the container. The manner of their arrangement is similar to the manner shown in the third embodiment or the fourth embodiment. Chopped onions (1761a), thinly sliced beef (1761b) cut into bite-size pieces, and broth for beef-on-rice bowls (1761c) were placed in the high-temperature food cooking portion (1744), and the food composition control device in the present embodiment was used to form an electromagnetic field, thereby reducing the stewing time taken to cook the ingredients of beef-on-rice bowls.

[0211] FIG. 35A(c) also shows an example, similar to FIG. 35A(a), in which one (1701) of a pair of antenna function portions serves as a high-temperature food cooking portion (1744). In this example, the antenna function portion shown in FIG. 35A(a) is disposed to cover the opening of the container shown in FIG. 35A(b). An example of heating precooked food is described using FIG. 35A(c). This is an example of continuing heating for precooked warm food and an example of the food composition control device for keeping food warm. When the ingredients of beef-on-rice bowls cooked by forming an electromagnetic field using the

food composition control device in the present embodiment were heated, the state after cooking remained the same even after two hours, the onions were still crunchy, and the beef kept tendered. When the simmered ingredients of beef-on-rice bowls were heated continuously for two hours without forming an electromagnetic field, the onions lost crunchiness and the beef became tough.

[0212] An example of heating precooked food is described using FIG. 35A(d). This is an example of continuing heating for precooked warm food and an example of the food composition control device for keeping food warm, similar to the example in FIG. 35A(c). This example has an opening in the horizontal direction, has several (three, in the figure) shelves inside, and is installed, for example, in a convenience store. As a configuration example, in a container having inside dimensions of 60 cm in width, 40 cm in depth, and 50 cm in height, a pair of general-type antenna function portions are disposed such that the plate surfaces of the antennas face each other in the width direction of the container with the lengthwise direction oriented vertically. When precooked fried food such as fried chicken, french fries, and fritter was heated with an electromagnetic field formed using the food composition control device in the present embodiment, the state after cooking remained almost the same even after two hours, and the food texture was not greasy and was crispy. When precooked fried food such as fried chicken, french fries, and fritter was heated continuously for two hours without forming an electromagnetic field, the food texture was greasy and no longer crispy. The food composition control device in the present embodiment can heat precooked food other than precooked fried food and can heat, for example, boxed meals. The food composition control device in the

present embodiment can be used as an apparatus for delivering food while keeping food warm when meals are served to inpatients in a hospital, for example.

<Fifth Embodiment: Evaluation Test>

5 [0213] A sensory test similar to the test performed in the third embodiment or the fourth embodiment was conducted on "beef" with the configuration shown in FIG. 35A(a). Two hundred grams of meat for steak were heated for two minutes on each side, in total, for four minutes. The temperature
10 of the high-temperature food cooking portion was set to 240°C. The first frequency was applied from the antenna function portion also serving as a high-temperature food cooking portion. FIG. 35B shows the result of this test. The rating is high when both of the first frequency and the
15 second frequency are in a range of 10 kHz to 150 kHz. The result when a phase difference is applied between the first frequency and the second frequency is 84 points, one point up.

[0214] With the configuration shown in FIG. 35A(d), a
20 sensory test was conducted on "french fries". Precooked french fries were placed on the high-temperature food cooking portion and kept warm at 60°C for 60 minutes. FIG. 35C shows the result of this sensory test. The rating is high when both of the first frequency and the second
25 frequency are in a range of 10 kHz to 150 kHz. The result when a phase difference is applied between the first frequency and the second frequency is 66 points, one point up.

[0215] With the configuration shown in FIG. 35A(d), a
30 sensory test was conducted on "fried chicken". Precooked fried chicken was placed on the high-temperature food cooking portion and kept warm at 60°C for 60 minutes. FIG. 35D shows the result of this sensory test. The rating is

high when both of the first frequency and the second frequency are in a range of 10 kHz to 150 kHz. The result when a phase difference is applied between the first frequency and the second frequency is 79 points, one point up.

<Fifth Embodiment: Effects>

[0216] With the food composition control device in the present embodiment, the food heated at high temperature in the high-temperature food cooking portion can be cooked for a short time. In addition, when precooked food is stored at high temperature in the high-temperature food cooking portion, the eating quality and the food texture immediately after cooking can be kept for a long time.

<<Sixth Embodiment>>

15 <Sixth Embodiment: Overview>

[0217] The food composition control device in the present embodiment is based on the second embodiment, further includes a room-temperature food cooking portion in which food is placed at room temperature, and is characterized by performing food composition control at room temperature.

<Sixth Embodiment: Configuration>

[0218] FIG. 36A is a conceptual diagram showing an overview of the food composition control device in the present embodiment. The food composition control device in the present embodiment further includes a room-temperature food cooking portion (1845) in which food (1861) is placed at room temperature. A pair of antenna function portions (1801, 1802) are disposed to form an electromagnetic field in the room-temperature food cooking portion. In the food composition control device in the present embodiment, room temperature is preferably temperature of 10°C or higher to 40°C or lower.

<Sixth Embodiment: Examples>

[0219] Wine a few days after opening and oxidized was placed in the room-temperature food cooking portion, and the room-temperature food cooking portion formed an
5 electromagnetic field for 10 minutes, whereby aroma and taste were improved. When wine immediately after opening was brought into contact with an electromagnetic field for 10 minutes, aroma and taste were improved, resulting in a wine having a flavor of aging wine. There is no difference
10 in effect between wine put into a decanter with no stopper and placed in the room-temperature food cooking portion and wine put into a bottle with a lid on and placed in the room-temperature food cooking portion. When unopened wine was stored in the room-temperature food cooking portion in
15 which an electromagnetic field was formed, aroma and taste were improved compared with unopened wine stored in a room. In addition to the room-temperature food cooking portion, the food composition control device in the present embodiment may further include a vapor supply portion to
20 supply water vapor or/and water spray to control the humidity as described later. When food such as wine is stored for a long time, it is preferable that humidity is controlled by the vapor supply portion.

<Sixth Embodiment: Evaluation Test>

25 [0220] A sensory test similar to the test performed in the third embodiment to the fifth embodiment was conducted on "wine". The container that forms the room-temperature food cooking portion has inner dimensions of 50 cm in width, 40 cm in depth, and 30 cm in height. The antenna function
30 portions that constitute a pair of antenna function portions (general type) are disposed about 1 cm apart from the side walls facing each other in the width direction of the container, and the distance between the antenna plate

surfaces of the antenna function portions is about 48 cm. The antenna function portions are each disposed such that the lengthwise direction of the antenna function portion extends along the depth direction of the container. Both
5 ends in the lengthwise direction of the antenna function portion are disposed about 5 cm apart from the side walls facing each other in the depth direction of the container. Wine 10 days after opening was placed substantially at the center of the container that forms the room-temperature
10 food cooking portion. After processing at 15°C for 10 minutes, the wine having the food composition controlled was evaluated in terms of two items: taste and aroma. FIG. 36B shows the result of this test. The rating is high when both of the first frequency and the second frequency are in
15 a range of 10 kHz to 150 kHz. The result when a phase difference is applied between the first frequency and the second frequency is 79 points, one point up.

[0221] Wine immediately after opening was also tested under a similar environment as in the test above.
20 Similarly, after processing at 15°C for 10 minutes, the wine having the food composition controlled was evaluated in terms of two items: taste and aroma. FIG. 36C shows the result of this test. The rating is high when both of the first frequency and the second frequency are in a range of
25 10 kHz to 150 kHz. The result when a phase difference is applied between the first frequency and the second frequency is 75 points, one point up.

<Sixth Embodiment: Effects>

[0222] With the food composition control device in the
30 present embodiment, the taste and aroma of food in contact with an electromagnetic field in the room-temperature food cooking portion can be enhanced or improved.

<<Seventh Embodiment>>

<Seventh Embodiment: Overview>

[0223] The food composition control device in the present embodiment is based on the second embodiment, further includes a refrigerated food cooking portion for refrigerating food and a refrigerating portion for refrigerating the refrigerated food cooking portion, and is characterized by performing composition control while storing food in the refrigerated food cooking portion.

<Seventh Embodiment: Configuration>

10 [0224] FIG. 37A is a conceptual diagram showing an overview of the food composition control device in the present embodiment. The food composition control device in the present embodiment further includes a refrigerated food cooking portion (1946) for refrigerating food (1961) and a
15 refrigerating portion (1947) for refrigerating the refrigerated food cooking portion. A pair of antenna function portions (1901, 1902) are disposed to form an electromagnetic field in the refrigerating layer. In the food composition control device in the present embodiment,
20 refrigerating is preferably at temperatures of 0°C or higher to 10°C or lower.

<Seventh Embodiment: Examples>

[0225] After the refrigerated food cooking portion is cooled by the refrigerating portion, lettuce was placed in
25 the refrigerated food cooking portion and refrigerated for seven days while an electromagnetic field was formed. The lettuce was not discolored and stayed fresh. Similarly, when lettuce was refrigerated for seven days without forming an electromagnetic field, the lettuce was withered
30 and discolored. The lettuce refrigerated in the food composition control device in the present embodiment was fresh and felt crunchy. On the other hand, the lettuce refrigerated without forming an electromagnetic field did

not taste fresh or crunchy even at a non-discolored portion.

[0226] After the refrigerated food cooking portion was cooled by the refrigerating portion, tuna fillet for sashimi was placed in the refrigerated food cooking portion and refrigerated at a temperature around zero degree for seven days while an electromagnetic field was formed. The tuna fillet was not discolored and stayed fresh. Similarly, when tuna fillet for sashimi was refrigerated for seven days without forming an electromagnetic field, the tuna fillet was darkly discolored. Tuna sashimi refrigerated in the food composition control device in the present embodiment tasted good and did not have a fishy smell. On the other hand, tuna sashimi refrigerated without forming an electromagnetic field did not taste good and had a fishy smell, even at a non-discolored portion. In this way, the food composition control device in the present embodiment can form an electromagnetic field at a temperature near zero degree, just above the temperature at which food is frozen, or at a temperature at which food is slightly frozen.

<Seventh Embodiment: Evaluation Test>

[0227] A sensory test similar to the test performed in the third embodiment to the sixth embodiment was conducted on "lettuce". The food composition control device is as shown in the conceptual diagram in FIG. 37A. Specifically, a container that forms the refrigerated food cooking portion has inner dimensions of 50 cm in width, 40 cm in depth, and 30 cm in height. The antenna function portions that constitute a pair of antenna function portions (general type) are disposed about 1 cm apart from the side walls facing each other in the width direction of the container, and the distance between the antenna plate surfaces of the antenna function portions is about 48 cm.

The antenna function portions are each disposed such that the lengthwise direction of the antenna function portion extends along the depth direction of the container. Both ends in the lengthwise direction of the antenna function portion are disposed about 5 cm apart from the side walls facing each other in the depth direction of the container. Lettuce was placed in the container of the refrigerated food cooking portion kept at temperatures of 5 to 7°C and processed for seven days. The lettuce was evaluated in terms of two items: taste and texture. FIG. 37B shows the result of this test. The rating is high when both of the first frequency and the second frequency are in a range of 10 kHz to 150 kHz. The result when a phase difference is applied between the first frequency and the second frequency is 80 points, one point up.

[0228] A test was conducted similarly on "tuna" using the refrigerated food cooking portion described above. Tuna fillet for sashimi (about 500 g) was placed in the container of the refrigerated food cooking portion kept at temperatures of 5 to 7°C and processed for seven days, and sashimi prepared from this fillet was evaluated in terms of two items: taste and color. FIG. 37C shows the result of this test. The rating is high when both of the first frequency and the second frequency are in a range of 10 kHz to 150 kHz. The result when a phase difference is applied between the first frequency and the second frequency is 80 points, one point up.

<Seventh Embodiment: Effects>

[0229] With the food composition control device in the present embodiment, the food stored in the refrigerated food cooking portion can be kept in a fresh state for a long time.

<<Eighth Embodiment>>

<Eighth Embodiment: Overview>

[0230] The food composition control device in the present embodiment is based on the second embodiment, further includes a low-temperature refrigerated food cooking portion for storing food by low-temperature refrigeration, and is characterized by performing composition control while storing food by low-temperature refrigeration.

<Eighth Embodiment: Configuration>

10 [0231] FIG. 38A is a conceptual diagram showing an overview of the food composition control device in the present embodiment. The food composition control device in the present embodiment further includes a low-temperature refrigerated food cooking portion (2048) for storing food
15 (2061) by low-temperature refrigeration. A pair of antenna function portions (2001, 2002) are disposed to form an electromagnetic field in the low-temperature refrigerated food cooking portion. Chilling often refers to a temperature range of near 0°C, ice temperature refers to a temperature range of near minus 1°C, and partial freezing refers to a temperature range of near minus 3°C. In the food composition control device in the present embodiment, low-temperature refrigeration is preferably at temperatures of minus 5°C or higher to 0°C or lower. In the food
20 composition control device in the present embodiment, storing by low-temperature refrigeration refers to keeping freshness in a temperature range in which food is not frozen.

<Eighth Embodiment: Examples>

30 [0232] About 2 kg of meat was placed in the low-temperature refrigerated food cooking portion for storage by low-temperature refrigeration (minus 2°C to 0°C) and stored for 30 days while an electromagnetic field was

formed. The meat was then cut into about 200 g of a steak. Similarly, beef stored in the low-temperature refrigerated food storing portion for 30 days without forming an electromagnetic field was cooked into to a steak. The steak made from beef stored in the food composition control device in the present embodiment had a concentrated flavor with no smell unique to meat, and the eating quality was excellent. On the other hand, a steak of beef refrigerated without forming an electromagnetic field did not taste good and had smell unique to meat.

<Eighth Embodiment: Evaluation Test>

[0233] A sensory test similar to the test performed in the third embodiment to the seventh embodiment was conducted on "beef". The food composition control device is as shown in a conceptual diagram FIG. 38A. Specifically, the container that forms the low-temperature refrigerated food cooking portion has inner dimensions of 50 cm in width, 40 cm in depth, and 30 cm in height. The antenna function portions that constitute a pair of antenna function portions (general type) are disposed about 1 cm apart from the side walls facing each other in the width direction of the container, and the distance between the antenna plate surfaces of the antenna function portions is about 48 cm. The antenna function portions are each disposed such that the lengthwise direction of the antenna function portion extends along the depth direction of the container. Both ends in the lengthwise direction of the antenna function portion are disposed about 5 cm apart from the side walls facing each other in the depth direction of the container. Two kilograms of a beef lump was placed in the low-temperature refrigerated food cooking portion kept at temperatures of minus 5 to minus 2°C and processed for 30 days. Two hundred grams prepared from the beef were

evaluated in terms of two items: taste and texture. FIG. 38B shows the result of this test. The rating is high when both of the first frequency and the second frequency are in a range of 10 kHz to 150 kHz. The result when a phase
5 difference is applied between the first frequency and the second frequency is 69 points, one point up.

<Eighth Embodiment: Effects>

[0234] The food composition control device in the present embodiment can improve umami components such as
10 glutamic acids in the food stored in the low-temperature refrigerated food cooking portion and can mature the food.

<<Ninth Embodiment>>

<Ninth Embodiment: Overview>

[0235] The food composition control device in the
15 present embodiment is based on the second embodiment, further includes a food placement portion for defrosting frozen food, and is characterized by performing composition control while defrosting the food.

<Ninth Embodiment: Configuration>

20 [0236] FIG. 39A is a conceptual diagram showing an overview of the food composition control device in the present embodiment. The food composition control device in the present embodiment further includes a food defrost cooking portion (2149) for defrosting frozen food such as
25 tuna fillet. A pair of antenna function portions (2101, 2102) are disposed to form an electromagnetic field in the food defrost cooking portion. The temperature at which food is defrosted in the food composition control device in the present embodiment is preferably, but not limited to,
30 15°C or lower. However, it is needless to say that some food can be defrosted at room temperature or high temperatures.

<Ninth Embodiment: Examples>

[0237] A packaged product containing four slices of 200 g frozen beef was obtained, and one slice of the beef was placed in the food defrost cooking portion for defrosting frozen food and defrosted while an electromagnetic field was formed for 10 minutes in the food defrost cooking portion. Another slice of four slices was left in a refrigerator overnight and defrosted. Each slice was cooked into a steak, and the eating quality was compared. No drip loss was observed in the beef defrosted in the food composition control device in the present embodiment, whereas drip loss during defrosting was observed in the beef defrosted in the refrigerator, and the beef was discolored. The steak of beef defrosted in the food composition control device in the present embodiment did not taste dried out and was juicy. On the other hand, the steak of beef defrosted in the refrigerator tasted dried out and was not juicy.

<Ninth Embodiment: Evaluation Test>

[0238] A sensory test similar to the test performed in the third embodiment to the eighth embodiment was conducted on "tuna". The food composition control device is as shown in the conceptual diagram in FIG. 39A. Specifically, the container that forms the food defrost cooking portion has inner dimensions of 50 cm in width, 40 cm in depth, and 30 cm in height. The antenna function portions that constitute a pair of antenna function portions (general type) are disposed about 1 cm apart from the side walls facing each other in the width direction of the container, and the distance between the antenna plate surfaces of the antenna function portions is about 48 cm. The antenna function portions are each disposed such that the lengthwise direction of the antenna function portion extends along the depth direction of the container. Both

ends in the lengthwise direction of the antenna function portion are disposed about 5 cm apart from the side walls facing each other in the depth direction of the container. Two hundred grams of frozen tuna fillet were placed in the food defrost cooking portion and processed for 10 minutes and defrosted. Sashimi prepared from the tuna fillet was evaluated in terms of two items: taste and texture. FIG. 39B shows the result of this test. The rating is high when both of the first frequency and the second frequency are in a range of 10 kHz to 150 kHz. The result when a phase difference is applied between the first frequency and the second frequency is 79 points, one point up.

<Ninth Embodiment: Effects>

[0239] The food composition control device in the present embodiment can reduce the time for defrosting food without causing uneven defrosting.

<<Tenth Embodiment>>

<Tenth Embodiment: Overview>

[0240] The food composition control device in the present embodiment is based on the third embodiment to the ninth embodiment, further includes a vapor supply portion for supplying water vapor or/and water spray in the cooking portions shown in the third embodiment to the ninth embodiment, and is characterized by performing composition control while replenishing water in food by supplying water vapor or/and water spray.

<Tenth Embodiment: Configuration>

[0241] FIG. 40A is a conceptual diagram showing an overview of the food composition control device in the present embodiment. The food composition control device in the present embodiment further includes a vapor supply portion (2250) for supplying water vapor or/and water spray in the cooking portion shown in the third embodiment to the

ninth embodiment. A pair of antenna function portions (2201, 2202) are disposed to form an electromagnetic field in a high-temperature food cooking portion (2244), which is one of the cooking portions. The temperature inside the food composition control device in the present embodiment is not limited. The food composition can be controlled at temperatures suitable for the cooking portions shown in the third embodiment to the ninth embodiment.

<Tenth Embodiment: Examples>

10 [0242] FIG. 40A is a conceptual diagram showing an overview of the food composition control device in the present embodiment. Referring to FIG. 40A, an example of keeping food warm with the high-temperature food cooking portion and the vapor supply portion will be described.

15 Frozen meat buns were placed in the high-temperature food cooking portion (2244) of the food composition control device in the present embodiment. When the frozen meat buns were cooked with an electromagnetic field while water vapor or water spray was supplied from the vapor supply portion (2250), the cooking time was reduced compared with cooking without forming an electromagnetic field.

[0243] An example of heating precooked food is described using FIG. 40A. This is an example of continuing heating for precooked warm food and an example of the food composition control device for keeping food warm. Cooked meat buns were placed on the high-temperature food cooking portion (2244) of the food composition control device, and the cooked meat buns were heated with an electromagnetic field while water vapor and water spray were supplied from the vapor supply portion (2250). Even after 30 minutes, the state immediately after cooking remained almost the same, the meat buns did not look watery or dried and tasted fluffy like immediately after cooking. On the other hand,

when the cooked meat buns were heated continuously for 30 minutes while water vapor and water spray were supplied from the vapor supply portion without forming an electromagnetic field, the meat buns looked watery and the texture was also watery. When the cooked meat buns were heated continuously for 30 minutes with an electromagnetic field and without supplying water vapor or water spray from the vapor supply portion, the meat buns looked dry and shrunk and had tough texture.

[0244] In this way, the food composition control device in the present embodiment can be used as a steamer or a steam convection oven. In the food composition control device in the present embodiment, the food composition control device having the room-temperature food cooking portion, the refrigerated food cooking portion, the low-temperature refrigerated food cooking portion, or the food defrost cooking portion, other than the high-temperature food cooking portion, may have the vapor supply portion for supplying water vapor or/and water spray to cook food by controlling the water content in the food.

<Tenth Embodiment: Evaluation Test>

[0245] A sensory test similar to the test performed in the third embodiment to the ninth embodiment was conducted on "meat buns". The food composition control device is as shown in the conceptual diagram in FIG. 40A. Specifically, the container that forms the high-temperature food cooking portion has inner dimensions of 50 cm in width, 40 cm in depth, and 30 cm in height. The antenna function portions that constitute a pair of antenna function portions (general type) are disposed about 1 cm apart from the side walls facing each other in the width direction of the container, and the distance between the antenna plate surfaces of the antenna function portions is about 48 cm.

The antenna function portions are each disposed such that the lengthwise direction of the antenna function portion extends along the depth direction of the container. Both ends in the lengthwise direction of the antenna function portion are disposed about 5 cm apart from the side walls facing each other in the depth direction of the container. The vapor supply portion is configured to supply water vapor or/and water into the container. The cooked meat buns were placed in the container of the high-temperature food cooking portion and kept warm for 30 minutes with water vapor and water spray supplied from the vapor supply portion. FIG. 40B shows the result of this test. The rating is high when both of the first frequency and the second frequency are in a range of 10 kHz to 150 kHz. The result when a phase difference is applied between the first frequency and the second frequency is 79 points, one point up.

<Tenth Embodiment: Effects>

[0246] Water vapor or/and water spray is supplied to the cooking portions shown in the third embodiment to the ninth embodiment to replenish water in the food or to control the humidity of the environment in which food is put, whereby the water content in the food can be controlled. This configuration can further enhance the effects of food control by the food composition control device of the present invention, such as enhancement and improvement of the eating quality or keeping food fresh for a long time.

<<Eleventh Embodiment>>

<Eleventh Embodiment: Overview>

[0247] The food composition control device in the present embodiment is based on the second embodiment, further includes a frozen food storing portion for storing food by freezing, and is characterized by performing

composition control while storing food by freezing.

<Eleventh Embodiment: Configuration>

[0248] FIG. 41A is a conceptual diagram showing an overview of the food composition control device in the present embodiment. The food composition control device in the present embodiment further includes a frozen food storing portion (2351) for storing food by freezing. A pair of antenna function portions (2301, 2302) are disposed to form an electromagnetic field in the frozen food storing portion. In the food composition control device in the present embodiment, freezing is preferably at temperatures of minus 60°C or higher to minus 5°C or lower. The frozen food storing portion of the food composition control device in the present embodiment can perform cooking, for example, making freeze-dried food by freeze-drying or mixing ice cream with fruits or nuts.

<Eleventh Embodiment: Examples>

[0249] About 200 g of beef was placed in the frozen food storing portion for freeze-storage and stored for 60 days while an electromagnetic field was formed. After defrosting, a steak was made. Similarly, beef stored in the frozen food storing portion without forming an electromagnetic field was cooked into a steak. Almost no drip loss occurred during defrosting in the beef stored in the food composition control device in the present embodiment, whereas drip loss occurred during defrosting in the beef defrosted without forming an electromagnetic field, and the beef was discolored. The steak of beef stored in the food composition control device in the present embodiment did not taste dried out and was juicy. On the other hand, the steak of beef stored without forming an electromagnetic field tasted dried out and was not juicy.

<Eleventh Embodiment: Evaluation Test>

[0250] A sensory test similar to the test performed in the third embodiment to the tenth embodiment was conducted on "beef". The food composition control device is as shown in the conceptual diagram in FIG. 41A. Specifically, the container that forms the frozen food storing portion has inner dimensions of 50 cm in width, 40 cm in depth, and 30 cm in height. The antenna function portions that constitute a pair of antenna function portions (general type) are disposed about 1 cm apart from the side walls facing each other in the width direction of the container, and the distance between the antenna plate surfaces of the antenna function portions is about 48 cm. The antenna function portions are each disposed such that the lengthwise direction of the antenna function portion extends along the depth direction of the container. Both ends in the lengthwise direction of the antenna function portion are disposed about 5 cm apart from the side walls facing each other in the depth direction of the container. Then, 200 g of beef for steak was placed in the frozen food storing portion for 60 days. The beef was defrosted to room temperature, cooked into a steak, and evaluated in terms of two items: taste and texture. FIG. 41B shows the result of this test. The rating is high when both of the first frequency and the second frequency are in a range of 10 kHz to 150 kHz. The result when a phase difference is applied between the first frequency and the second frequency is 82 points, one point up.

<Eleventh Embodiment: Effects>

[0251] The food composition control device in the present embodiment can suppress growth of ice crystals in the food stored in the frozen food storing portion and thus can prevent drip loss during defrosting due to growth of ice crystals. Accordingly, degradation of food stored by

freezing can be prevented, and the eating quality can be maintained.

<<Twelfth Embodiment>>

[0252] Japanese Patent No. 4637051 discloses a water
5 activating device in which the north pole and the south
pole of a pair of permanent magnets are disposed to face
each other with a water pipe interposed therebetween, and a
paramagnetic metal plate and a diamagnetic metal plate are
disposed in a direction at the right angle to the magnetic
10 line of force of the permanent magnets. The paramagnetic
metal plate is a nickel-plated copper plate or a nickel
single metal plate. The diamagnetic metal plate is a
silver-plated copper plate or a single metal plate of
copper or silver. The paramagnetic metal plate and the
15 diamagnetic metal plate are connected through a good
conductive wire to form a contact battery. The description,
the claims, and the drawings of Japanese Patent No. 4637051
are incorporated herein by reference.

[0253] A molecular arrangement adjusting unit, a
20 molecular arrangement adjusting device, and a
transportation method using the same according to a twelfth
embodiment adjust the arrangement of molecules of a liquid
with a simple structure and at low costs and can keep an
object such as food and beverages fresh.

25 [0254] FIG. 42 is a diagram showing the molecular
arrangement adjusting unit and the molecular arrangement
adjusting device according to the present embodiment.

[0255] The molecular arrangement adjusting unit 1 in the
present embodiment includes a power source 2 for generating
30 alternating current, a first electrode 3 coupled to one
electrode of the power source 2, a second electrode 4
coupled to the other electrode of the power source 2, and a
wire 5 coupling one electrode of the power source 2 with

the first electrode 3 and coupling the other electrode of the power source 2 with the second electrode 4.

[0256] An AC power source with an effective value of voltage of 100 V to 200 V and a frequency of about 5 kHz to 200 kHz may be used as the power source 2. Direct current from a DC power source may be converted into alternating current using an inverter or the like. The DC power source may be a 12V battery or a dry battery, for example. The power source 2 may adjust voltage, frequency, phase, and the like. A not-shown switch may be used for ON/OFF control of the power source 2. In addition, for example, a timer may be used to power on the power source 2 only for a certain time and subsequently power off the power source 2.

[0257] The first electrode 3 and the second electrode 4 are disposed with a space therebetween. The first electrode 3 and the second electrode 4 are formed of a conductive material such as metal or metal alloy. For example, when the first electrode 3 and the second electrode 4 are members such as copper plates or aluminum plates, they can be made thin and modified in shape and thus can be lightweight and installed in a small space.

[0258] The first electrode 3 and the second electrode 4 may have surfaces coated with an insulating material. The coating of an insulating material can prevent users of the fryer 1 from receiving an electric shock.

[0259] The wire 5 is a conductive material. For example, the conductive material used for the wire 5 may be metal such as copper or aluminum or metal alloy, or may be carbon. Preferably, the wire 5 is coated with an insulating material on its periphery.

[0260] The molecular arrangement adjusting unit 1 in the present embodiment is installed in a container 11 to configure the molecular arrangement adjusting device 10.

An object 3100 of which molecular arrangement is to be adjusted is installed in the container 11. The container 11 is preferably an insulating member. When the container 11 is a conductive member, the first electrode 3 and the second electrode 4 are installed in an insulated state. The container 11 in the present embodiment has a box 11a in which the object 3100 and the molecular arrangement adjusting unit 1 are installed and a lid 11b closing the opening of the box 11a.

[0261] The container 11 does not necessarily have the lid 11b and may only have the box 11a. The object 3100 and the molecular arrangement adjusting unit 1 may be installed in the lid 11b. One of the object 3100 and the molecular arrangement adjusting unit 1 may be installed in the box 11a, and the other may be installed in the lid 11b.

[0262] The molecular arrangement adjusting unit 1 activates the power source 2, for example, by a not-shown switch. An electric field is then generated between the first electrode 3 and the second electrode 4.

[0263] FIG. 43 is a diagram showing the arrangement of water molecules of an object in a normal state and the arrangement of water molecules H_2O of an object in an electric field generated between the first electrode 3 and the second electrode 4.

[0264] The object 3100 includes a liquid ingredient. For example, the object 3100 may be food such as meats, fish, and vegetables, beverages or plant/animal cells or oils and fats. The object 3100 in the present embodiment includes water molecules H_2O .

[0265] Water molecules H_2O are usually arranged irregularly, as shown in FIG. 43A. Hence, hydrogen atoms H take in active oxygen 111 or generate hydrogen bonds, so that the size of water molecules H_2O increases and water

molecules H_2O become inert. Oxidation of water molecules H_2O then starts.

[0266] By contrast, when an electric field is generated between the first electrode 3 and the second electrode 4,
5 water molecules H_2O tend to orient in a certain direction. This is because oxygen atoms O of water molecules H_2O that have strong force of attracting electrons become slightly minus and hydrogen atoms H that tend to release electrons become slightly positive, and they are apt to turn to the
10 direction of the electric field between the first electrode 3 and the second electrode 4.

[0267] Since the power source 2 generates alternating current, water molecules H_2O change directions alternately. Since the power source 2 in the present embodiment
15 generates alternating current of about 50 kHz, water molecules H_2O change directions about 50,000 times per second and appear to be vibrating. As this vibration is repeated, as shown in FIG. 43B, the hydrogen bonds of water molecules H_2O to active oxygen 111 or other ingredients are
20 cut off, and water molecules H_2O gradually become finely particulate and regularly arranged. The frequency of alternating current generated from the power source 2 may be in a range of 5 kHz to 200 kHz.

[0268] Water will now be described. Water can be
25 classified into "bound water" and "free water". Bound water is bound by hydrogen bonding to other ingredients and stable. By contrast, free water is freely movable and is fresh and not stale (see FIG. 43A). However, free water has molecules easily bonded to the other ingredients and is
30 easily rotten.

[0269] Water molecules H_2O regularly arranged by the molecular arrangement adjusting unit 1 in the present embodiment form a pearl-chain structure in which free water

is bound into a stable state like bound water. To be more specific, water molecules H_2O regularly arranged by the molecular arrangement adjusting unit 1 in the present embodiment are not bonded to other ingredients, although
5 they are free water, and can stay fresh and not stale.

[0270] The molecular arrangement adjusting device 10 including the molecular arrangement adjusting unit 1 in the present embodiment installed in the container 11 therefore can adjust the liquid molecule arrangement of the object
10 3100 and can keep freshness of the object 3100. For example, the molecular arrangement adjusting device 10 can be used as a transportation container to transport an object farther than now while keeping freshness. The container 11 may be, for example, styrene foam, and the
15 molecular arrangement adjusting unit 1 in the present embodiment may be attached to the existing styrene foam to form a transportation container.

[0271] Water molecules H_2O once regularly arranged by the molecular arrangement adjusting unit 1 in the present
20 embodiment are kept in the regularly arranged state for a few days. Therefore, even when the object 3100 is stored in another container after the liquid molecular arrangement in the cells of the object 3100 is adjusted in the molecular arrangement adjusting device 10 including the
25 molecular arrangement adjusting unit 1 in the present embodiment installed in the container 11, the freshness of the object 3100 can be kept. Even when the object 3100 is moved to and transported in another transportation container after the liquid molecular arrangement of the
30 object 3100 is adjusted in the molecular arrangement adjusting device 10 including the molecular arrangement adjusting unit 1 in the present embodiment installed in the container 11, the object 3100 can be transported farther

than now while keeping fresh.

[0272] FIG. 44 is a diagram showing an example including a temperature controller in the molecular arrangement adjusting unit in the present embodiment.

5 [0273] As shown in FIG. 44, the molecular arrangement adjusting unit 1 in the present embodiment may include a temperature controller 6 for controlling the ambient temperature. The temperature controller 6 can regulate the inside of the container 11 to a predetermined temperature.
10 For example, when the inside of the container 11 is set in a refrigerated state, the fresh state can be maintained for a long time. Food or beverage may be transported in a refrigerated state in the container 11, and its temperature may be increased during transportation to be ready for
15 eating or drinking on arrival.

[0274] FIG. 45 is a diagram showing the molecular arrangement adjusting device according to another embodiment. FIG. 45(a) is a diagram showing a cross section of the molecular arrangement adjusting device 10 in
20 another embodiment. FIG. 45(b) is a diagram showing a top view of the molecular arrangement adjusting device 10 in another embodiment.

[0275] The molecular arrangement adjusting device 10 in another embodiment shown in FIG. 45 is an example in which
25 the container 11 also serves as electrodes 3 and 4. The container 11 of the molecular arrangement adjusting device 10 is a box 11a in the shape of a tube with a bottom. The box 11a has a first electrode 3 on one side made of a conductive material such as metal or alloy, a second
30 electrode 4 on the other side made of a conductive material such as metal and alloy, and an insulating member 7 installed between the first electrode 3 and the second electrode 4. The first electrode 3 and the second

electrode 4 are separated from each other by the insulating member 7.

[0276] The molecular arrangement adjusting device 10 in another embodiment shown in FIG. 45 contains a liquid as a first object 3101 in the box 11a and contains a second object 3102 in the liquid. The molecular arrangement adjusting device 10 in the present embodiment can adjust the liquid molecular arrangement of the first object 3101 and the second object 3102 and keep the freshness of the first object 3101 and the second object 3102. Since the box 11a serves as the electrodes 3 and 4, the molecular arrangement adjusting device 10 can be compact and slim in appearance. In the molecular arrangement adjusting device 10 in another embodiment shown in FIG. 45, the electrodes 3 and 4 are provided only in the box 11a. However, a lid 11b may be further provided, and electrodes connected to the electrodes 3 and 4 may be provided in the lid 11b.

[0277] An experiment was conducted to compare an object 3100 stored by refrigeration using the molecular arrangement adjusting device 10 in the present embodiment with an object 3100 stored using a normal refrigerator. In the molecular arrangement adjusting device 10 in this example, the power source 2 generated alternating current of about 50 kHz. The refrigerator held a temperature of about 4°C for 10 days. Bean sprouts were used as the object 3100. The bean sprouts changed as listed in Table 1 below.

[Table 1]

Bean sprouts	Refrigerator	Molecular arrangement adjusting device
Before storage	223.03 g	215.31 g
After 10 days	185.56 g	207.46 g

Weight reduction ratio	16.80%	3.65%
Amount of drip loss	26.64 g	1.08 g

[0278] As listed in Table 1, 223.03 g of bean sprouts before storage decreased to 185.56 g after being stored in the refrigerator for 10 days. The weight reduction ratio is 16.80% and the amount of drip loss, which is escaping water, is 26.64 g.

[0279] By contrast, 215.31 g of bean sprouts before storage, stored in the molecular arrangement adjusting device 10, decreased to 207.46 g after 10 days. The weight reduction ratio is 3.65% and the amount of drip loss, which is escaping water, is only 1.08 g.

[0280] The molecular arrangement adjusting device 10 thus can keep the water in the bean sprouts for a long time and keep the bean sprouts not stale and fresh.

[0281] In the molecular arrangement adjusting device 10 in the next example, pea sprouts were used as the object 3100. The power source 2 generated alternating current of about 50 kHz. The refrigerator held a temperature of about 4°C for 35 days. The pea sprouts changed as listed in Table 2 below.

[Table 2]

Pea sprouts	Refrigerator	Molecular arrangement adjusting device
Before storage	380.47 g	377.56 g
After 35 days	323.87 g	347.08 g
Weight reduction ratio	15.00%	8.00%

[0282] As listed in Table 2, 380.47 g of pea sprouts before storage decreased to 323.87 g after 35 days in the

refrigerator. The weight reduction ratio is 15.00%.

[0283] By contrast, 377.56 g of pea sprouts before storage, stored in the molecular arrangement adjusting device 10, decreased to 347.08 g after 35 days. The weight
5 reduction ratio is 8.00%.

[0284] The molecular arrangement adjusting device 10 thus can keep the water in the pea sprouts for a long time and keep the pea sprouts not stale and fresh.

[0285] As described above, the molecular arrangement
10 adjusting unit 1 in the present embodiment includes a power source 2 for generating alternating current, a first electrode 3 coupled to one electrode of the power source 2, a second electrode 4 coupled to the other electrode of the power source 2, and a wire 5 coupling one electrode of the
15 power source 2 with the first electrode 3 and coupling the other electrode of the power source 2 with the second electrode 4. The molecular arrangement adjusting unit can adjust the arrangement of molecules of liquid with a simple structure and at low costs and can keep the freshness.

[0286] In the molecular arrangement adjusting unit 1 in
20 the present embodiment, the first electrode 3 and the second electrode 4 are sheet-like members. The molecular arrangement adjusting unit therefore can be made thin and modified in shape and can be lightweight and installed in a
25 small space.

[0287] The molecular arrangement adjusting unit 1 in the present embodiment includes the temperature controller 6 for controlling the ambient temperature. The molecular arrangement adjusting unit therefore can keep a fresh state
30 for a long term when the inside of the container 11 is refrigerated. Food or beverage may be transported in a refrigerated state in the container 11, and its temperature may be increased during transportation to be ready for

eating or drinking on arrival.

[0288] The molecular arrangement adjusting device 10 in the present embodiment includes the molecular arrangement adjusting unit 1 and the container 11 in which the object 3100 of which molecular arrangement is to be adjusted and the molecular arrangement adjusting unit 1 are installed. The molecular arrangement adjusting device 10 can adjust the arrangement of molecules of liquid with a simple structure and at low costs and can keep the freshness.

10 [0289] In the molecular arrangement adjusting device 10 in the present embodiment, the container 11 has a part serving as the first electrode 3 and another part serving as the second electrode 4, and the insulating member 7 is installed between the first electrode 3 and the second
15 electrode 4 to separate the first electrode 3 and the second electrode 4 from each other. The molecular arrangement adjusting device 10 therefore can be compact and slim in appearance. As used herein "the container 11 having a part serving as an electrode" means that a part of
20 the container 11 is, for example, metal and functions as an electrode, or that a copper plate or a plate-like or sheet-like member such as an aluminum foil is attached to a part of the container 11.

[0290] In the transportation method in the present
25 embodiment, the object 3100 of which molecular arrangement is to be adjusted is installed between the first electrode 3 and the second electrode 4 of the molecular arrangement adjusting device 10, and the object 3100 is transported while an electric field is generated between the first
30 electrode 3 and the second electrode 4. The transportation method using the molecular arrangement adjusting device 10 therefore can adjust the arrangement of molecules of liquid with a simple structure and at low costs and can transport

the object while keeping the freshness.

[0291] In the transportation method in the present embodiment, the object 3100 of which molecular arrangement is to be adjusted is installed between the first electrode
5 3 and the second electrode 4 of the molecular arrangement adjusting device 10, and an electric field is generated between the first electrode 3 and the second electrode 4. After the elapse of a predetermined period of time, the object 3100 is removed from the molecular arrangement
10 adjusting device 10, and the object 3100 is thereafter transported. Even when the object is moved to and transported in another transportation container, it can be transported farther than now while keeping the freshness.

[0292] Although the molecular arrangement adjusting unit,
15 the molecular arrangement adjusting device, and the molecular arrangement adjusting method have been described based on some examples, the present invention is not limited to those examples and is susceptible to various combinations and modifications.

20 <<Thirteenth Embodiment>>

[0293] A cooking method according to a thirteenth embodiment enables uniform cooking in a short time and improves the eating quality.

[0294] FIG. 46 is a diagram showing a fryer in the
25 present embodiment. The same configuration as in the twelfth embodiment is denoted by the same reference sign and a description thereof is omitted.

[0295] A fryer 4001 in the present embodiment includes a power source 2 for generating alternating current, a first
30 electrode 3 coupled to one electrode of the power source 2, a second electrode 4 coupled to the other electrode of the power source 2, a wire 5 coupling one electrode of the power source 2 with the first electrode 3 and coupling the

other electrode of the power source 2 with the second electrode 4, an oil reservoir 4006 for storing oil, a heating portion 4007 for heating oil stored in the oil reservoir 4006, a temperature measuring portion 4008 for
5 measuring the temperature of oil stored in the oil reservoir 4006, and a controller 4009 for controlling the power source 2 and the heating portion 4007.

[0296] The oil reservoir 4006 is a box-shaped member having an opening on the top. The oil reservoir 4006 is
10 preferably formed of a conductive material such as stainless steel less degraded. When the oil reservoir 4006 is formed of an insulating member, the first electrode 3 and the second electrode 4 are insulated. Food oil 200 is stored in the oil reservoir 4006. An ingredient 4100 such
15 as food is put into the heated food oil 200.

[0297] The heating portion 4007 heats the food oil 200 stored in the oil reservoir 4006. The structure of the heating portion 4007 may be a heating structure that feeds current to a heating coil, a heating structure that burns
20 gas, or a heating structure by electromagnetic induction. The heating portion 4007 may be installed in the inside of the oil reservoir 4006 or may be formed as a structure integrated with the oil reservoir 4006. The heating portion 4007 in the present embodiment is installed on the
25 outside of the oil reservoir 4006 and heats the food oil 200 in the oil reservoir 4006 to 120 degrees to 200 degrees centigrade.

[0298] The temperature measuring portion 4008 measures the temperature of the food oil 200 stored in the oil
30 reservoir 4006. At least a part of the temperature measuring portion 4008 that measures the temperature is installed in the food oil 200 stored in the oil reservoir 4006.

[0299] The controller 4009 controls the power source 2 and the heating portion 4007 in accordance with the kind of the ingredient 4100 and the temperature measured by the temperature measuring portion 4008. For example, the
5 controller 4009 controls the voltage or the frequency applied by the power source 2 to the first electrode 3 and the second electrode 4. The controller 4009 controls electric power generated by the heating portion 4007 or the flow rate of gas flowing through the heating portion 4007.

10 [0300] In this manner, the controller 4009 controls the power source 2 and the heating portion 4007 in accordance with the kind of the ingredient 4100 and the temperature measured by the temperature measuring portion 4008, whereby the food oil 200 is set to the temperature and the electric
15 field most suitable for cooking the ingredient 4100. Different ingredients 4100 therefore have individual excellent eating quality.

[0301] The fryer 4001 in the present embodiment may have a not-shown oxidation degree sensor that measures the
20 degree of oxidation of the food oil 200 stored in the oil reservoir 4006. When the fryer 4001 has an oxidation degree sensor, the controller 4009 may control the power source 2 and the heating portion 4007 in accordance with the degree of oxidation of the food oil 200 measured by the
25 oxidation degree sensor.

[0302] In this manner, the controller 4009 controls the power source 2 and the heating portion 4007 in accordance with the kinds of the ingredient 4100 and the degree of oxidation of the food oil 200 measured by the oxidation
30 degree sensor, whereby the food oil 200 is set to the temperature and the electric field most suitable for cooking the ingredient 4100. Different materials 4100 therefore have individual excellent eating quality.

[0303] A description will now be given to the water content in the ingredient 4100 in the electric field generated between the first electrode 3 and the second electrode 4 and the molecular arrangement of the food oil

5 200 when the power source 2 of the fryer 4001 is turned on.

[0304] The ingredient 4100 includes a liquid ingredient. For example, the ingredient 4100 may be food such as meat, fish, and vegetable. The ingredient 4100 in the present embodiment contains water molecules H_2O .

10 [0305] Water molecules H_2O regularly arranged by the fryer 4001 in the present embodiment form a pearl-chain structure in which free water is bound into a stable state like bound water. To be more specific, water molecules H_2O regularly arranged by the fryer 4001 in the present

15 embodiment are not bonded to other ingredients and are finely particulate, although they are free water, and can stay fresh and not stale.

[0306] FIG. 30 is a diagram showing the arrangement of long-chain fatty acid in food oil.

20 [0307] The food oil in the present embodiment includes fatty acid. The fatty acid is preferably a long-chain fatty acid or a medium-chain fatty acid.

[0308] The long-chain fatty acid is preferably those with 12 or more carbons. Examples of the long-chain fatty acid include lauric acid, myristic acid, pentadecylic acid, palmitic acid, palmitoleic acid, margaric acid, stearic acid, oleic acid, vaccenic acid, linoleic acid, α -linolenic acid, γ -linolenic acid, arachidic acid, arachidonic acid, eicosapentaenoic acid, and docosahexaenoic acid. The

25 medium-chain fatty acid is preferably those with 8 to 10 carbons. Examples of the medium-chain fatty acid include caprylic acid, capric acid, and lauric acid.

30

[0309] For example, the fatty acid has a carboxyl chain

moiety functioning as hydrophilic group and a hydrocarbon chain moiety functioning as lipophilic group and mixes the oil component of the food oil 200 with the water component present on the surface of the ingredient 4100 put into the food oil 200. For example, when particulate water is present on the surface of the ingredient 4100, the hydrophilic group of the fatty acid aligns on the surface of water.

[0310] When the food oil 200 stored in the oil reservoir 4006 of the fryer 4001 is heated to a predetermined temperature by the heating portion 4007, and the ingredient 4100 having particulate water on the surface is put with an electric field generated between the first electrode 3 and the second electrode 4, the particulate water on the surface of the ingredient 4100 and the hydrophilic group of the fatty acid of the food oil 200 vibrate similarly to the water molecules shown in FIG. 43. The molecules of particulate water on the surface of the ingredient 4100 become finely particulate. The hydrophilic group of the fatty acid aligns on the ingredient 4100 side.

[0311] Even when the ingredient 4100 having particulate water on the surface is put into the hot food oil 200, the water on the surface is instantaneously formed into fine particles, and oil does not splash. The hydrophilic group of the fatty acid arranged on the surface side of the ingredient 4100 reduces the food oil 200 penetrating into the inside of the ingredient 4100 and prevents the ingredient 4100 from becoming greasy and at the same time prevents ejection of water from the ingredient 4100. That is, the ingredient 4100 is cooked crispy on the surface and moist in the inside.

[0312] FIG. 47 is a diagram showing a cooking method in the present embodiment. FIG. 47A is a diagram showing an

ingredient put into food oil. FIG. 47B is a diagram showing an ingredient washed with water. FIG. 47C is a diagram showing baking of an ingredient. FIG. 47D is a diagram showing boiling of an ingredient. FIG. 47E is a
5 diagram showing steaming of an ingredient.

[0313] At step 1, as shown in FIG. 47A, the ingredient 4100 is fried in food oil 200 using the fryer 4001 in the present embodiment shown in FIG. 46 (ST1). Preparation is necessary before frying in the fryer 4001. In the cooking
10 method in the present embodiment, batter such as bread crumbs usually put on the ingredient 4100 is not used.

[0314] First of all, the first electrode 3 and the second electrode 4 are installed in the oil reservoir 4006. A predetermined amount of food oil 200 is then stored in
15 the oil reservoir 4006. The food oil 200 is stored such that the first electrode 3 and the second electrode 4 are at least partially submerged. Next, the power source 2 is turned on to form an electric field between the first electrode 3 and the second electrode 4. Subsequently, the
20 controller 4009 controls the voltage and the frequency of the power source 2 and the temperature of the heating portion 4007. The voltage and the frequency of the power source 2 and the temperature of the heating portion 4007 may be preset.

[0315] Next, the ingredient 4100 is put into the food oil 200 in the oil reservoir 4006. The ingredient 4100 is fried in the food oil 200 for a predetermined period of time. A not-shown timer may be installed to give an alarm when a predetermined period of time passes. The voltage
25 and the frequency of the power source 2 and the temperature of the heating portion 4007 may be set after the ingredient 4100 is put or may be set before and after the ingredient 4100 is put.
30

[0316] After the ingredient 4100 is fried in the food oil 200, at step 2, the ingredient 4100 is washed with water as shown in FIG. 47B (ST2). In washing, the fried ingredient 4100 is put into water 300 stored in a water reservoir 13. Alternatively, the ingredient 4100 may be exposed to running tap water and washed. After washing with water, water is preferably wiped off.

[0317] Typically, when the ingredient 4100 is fried in the food oil 200 and then immediately washed with water for a short time within five minutes or so, water reacts with the hot food oil 200 adhering to the ingredient 4100, and water splashes to cause a dangerous situation. The ingredient 4100 fried by the fryer 4001 in the present embodiment, however, is fried at a low temperature in a short time, and the ingredient 4100 is not greasy and can be washed immediately.

[0318] The ingredient 4100 fried by the fryer 4001 in the present embodiment is washed with water so that the oil is washed away. In this way, in the ingredient cooking method in the present embodiment, after the ingredient 4100 is fried in the food oil 200, the fried ingredient 4100 is washed with water immediately and water is wiped off, so that the ingredient 4100 is cooked in a similar state to being baked while it is cooked through evenly without producing smoke.

[0319] After washing with water, as shown in FIG. 47C, the ingredient 4100 may be baked for a short time, for example, in a grill or a frying pan. In this way, when the surface of the ingredient 4100 is additionally baked in a grill for a short time after washing with water, the ingredient 4100 is browned and cooked in the same way as being baked. Compared with typical baking in a grill or the like, the ingredient 4100 can be cooked through evenly

for a short time without producing smoke.

[0320] After washing with water, as shown in FIG. 47D, the ingredient 4100 may be boiled, for example, in a pan for a short time. In this way, when the ingredient 4100 is additionally boiled in a pan for a short time after washing with water, the ingredient 4100 is stewed and cooked in the same way as being simmered. Compared with typical simmering in a pan or the like, the ingredient 4100 can be cooked through evenly for a short time without unevenness in heating or losing its shape.

[0321] After washing with water, as shown in FIG. 47E, the ingredient 4100 may be steamed, for example, in a steamer for a short time. In this way, when the ingredient 4100 is additionally steamed in a steamer after washing with water, the ingredient 4100 is steamed and cooked in the same way as being steamed. Compared with typical steam cooking in a steamer or the like, the ingredient 4100 can be cooked through evenly for a short time without unevenness in heating or losing its shape.

[0322] These ingredient cooking methods can be entirely systemized and all the steps can be performed automatically through a production line. For example, the step of putting the ingredient 4100 into the fryer 4001 shown in FIG. 47A, the step of removing the fried ingredient, and the step of washing with water shown in FIG. 47B may be performed automatically through a production line. The baking step shown in FIG. 47C, the boiling step shown in FIG. 47D, and the steaming step shown in FIG. 47E may also be performed automatically through a production line.

[0323] FIG. 48 is a diagram showing a fryer and an oil reservoir in another embodiment. FIG. 48A is a diagram showing a cross section of the fryer and the oil reservoir in another embodiment. FIG. 48B is a diagram showing a top

view of the fryer and the oil reservoir in another embodiment.

[0324] A fryer 4010 in another embodiment shown in FIG. 48 is an example in which an oil reservoir 4011 also serves as electrodes 3 and 4. The oil reservoir 4011 is a box-shaped member in the shape of a tube with a bottom. The oil reservoir 4011 has a first electrode 3 on one side made of a conductive material such as metal or alloy, a second electrode 4 on the other side made of a conductive material such as metal and alloy, and an insulating member 12 installed between the first electrode 3 and the second electrode 4. The first electrode 3 and the second electrode 4 are separated from each other by the insulating member 12.

[0325] In the fryer 4010 and the oil reservoir 4011 in another embodiment shown in FIG. 48, food oil 200 is put into the oil reservoir 4011, and an ingredient 4100 is put into the food oil 200. In the fryer 4010 in this embodiment, since the oil reservoir 4011 also serves as the electrodes 3 and 4, the fryer 4010 can be compact and slim in appearance.

[0326] In the present embodiment shown in FIG. 46 and FIG. 48, the first electrode 3 and the second electrode 4 are used as vibration generating portions. The vibration generating portions in the present embodiment, however, may be those that generate electric waves or ultrasonic waves, rather than electrodes. The vibration generating portions in the present embodiment may use any frequency range. The vibration generating portions vibrate water and oil, so that an emulsion phenomenon occurs in which water and oil are emulsified, the affinity between water and oil increases, the interfacial tension decreases, and consequently, the size of water droplets becomes small.

Water on the surface of the ingredient becomes fine, and the ingredient is promptly covered with water skin. This prevents intrusion of oil into the ingredient and makes fried food with oil less absorbed.

5 [0327] Typically, when the ingredient 4100 is fried in the food oil 200 and then immediately washed with water for a short time within five minutes or so, water reacts with the hot food oil 200 adhering to the ingredient 4100, and water splashes to cause a dangerous situation. The
10 ingredient 4100 fried by the fryer 4001 in the present embodiment, however, is fried at a low temperature in a short time, and the ingredient 4100 is not greasy and therefore can be washed with water immediately.

[0328] The ingredient 4100 fried by the fryer 4001 in
15 the present embodiment is washed with water so that the oil is washed away. In this way, in the ingredient cooking method in the present embodiment, after the ingredient 4100 is fried in the food oil 200, the fried ingredient 4100 is washed with water immediately and water is wiped off, so
20 that the ingredient 4100 is heated in the same way as being baked while it is cooked through evenly without producing smoke.

[0329] In a conventional cooking method for fried food using oil, cooking at high temperature makes protein and
25 burnt bits bonded to each other and accelerates glycation. Moreover, protein and cells in the ingredient are destroyed, and the ingredient rapidly loses water and becomes tough. By contrast, when the vibration generating portions in the present embodiment are used, the ingredient can be cooked
30 at low temperature, and the ingredient can be cooked moist and tender without destroying protein.

[0330] Traditionally, grillers, iron plates, frying pans, charcoal, or ovens are used for bake cooking and produce

smoke. By contrast, the use of the vibration generating portions in the present embodiment can reduce smoking.

[0331] In conventional bake cooking using a griller, the ingredient is heated only on one side, and the ingredient
5 is not evenly baked. By contrast, when the vibration generating portions in the present embodiment are used, the ingredient is heated on all surfaces, thereby eliminating baking unevenness. Since the ingredient is heated on all surfaces, the time for cooking can be controlled, and the
10 evenly cooked state can be always achieved by setting the time for heating, for example, using a timer.

[0332] The ingredient cooking method in the present embodiment as described above uses the fryer 4001 including the power source 2 and the vibration generating portions 3
15 and 4 connected to the power source 2 to generate vibrations. The ingredient cooking method includes: storing oil in the oil reservoir 4006 in which the vibration generating portions 3 and 4 of the fryer 1 are installed; frying the ingredient 4100 in the oil in the oil
20 reservoir 4006 in which the vibration generating portions 3 and 4 generate vibrations; and thereafter washing the ingredient 4100 with water. The ingredient cooking method in the present embodiment therefore ensures even cooking at low temperature in a short time, thereby improving the
25 eating quality.

[0333] In the ingredient cooking method in the present embodiment, after the ingredient 4100 is washed with water, the ingredient 4100 is baked. The ingredient cooking method in the present embodiment therefore ensures even
30 cooking at low temperature in a short time and improves the eating quality in bake cooking.

[0334] In the ingredient cooking method in the present embodiment, after the ingredient 4100 is washed with water,

the ingredient 4100 is boiled. The ingredient cooking method in the present embodiment therefore ensures even cooking at low temperature in a short time and improves the eating quality in boil cooking.

5 [0335] In the ingredient cooking method in the present embodiment, after the ingredient 4100 is washed with water, the ingredient 4100 is steamed. The ingredient cooking method in the present embodiment therefore ensures even cooking at low temperature in a short time and improves the
10 eating quality in steam cooking.

[0336] In the ingredient cooking method in the present embodiment, the vibration generating portions 3 and 4 generate electric waves. The eating quality therefore can be improved inexpensively with a simple structure.

15 [0337] In the ingredient cooking method in the present embodiment, the oil reservoir 4011 has a part serving as the first electrode 3 and another part serving as the second electrode 4, and the insulating member 12 is installed between the first electrode 3 and the second
20 electrode 4 to separate the first electrode 3 and the second electrode 4 from each other. The fryer 4010 therefore can be compact and slim in appearance.

[0338] Although the ingredient cooking method has been described in the present embodiment based on some examples,
25 the present invention is not limited to those examples and is susceptible to various combinations and modifications.

[0339] The principal features of the present invention can be employed in various embodiments and variations without departing from the broad spirit and scope of the
30 invention. The embodiment described above is merely illustrative of an example of the present invention and does not limit the scope of the invention.

[0340] This application claims priority to Japanese Patent Application No. 2017-100354 filed on May 19, 2017, Japanese Patent Application No. 2017-126102 filed on June 28, 2017, and Japanese Patent Application No. 2017-153591
5 filed on August 8, 2017, the entire contents of which are incorporated herein by reference.

Reference Signs List

[0341] 1 molecular arrangement adjusting unit
10 (ingredient control device)
2 power source
3 first electrode (vibration generating portion)
4 second electrode (vibration generating portion)
5 wire
15 6 temperature controller
7, 12 insulating member
10 molecular arrangement adjusting device (ingredient control device)
11 container
20 11a box
11b lid
13 water reservoir
100, 4001, 4010 fryer (ingredient control device)
101, 4006, 4011 oil reservoir
25 102 opposed plate antenna (vibration generating portion)
103 drive portion
104, 1542, 4007 heating portion
111 base portion
30 112 vertical portion
113 terminal
200 food oil
300 water

0100, 0400 food composition control device
 (ingredient control device)

0101, 0401, 1501, 1601, 1701, 1801, 1901, 2001, 2101,
 2201 antenna function portion (first vibration generating
 5 portion)

0102, 0402, 1502, 1602, 1702, 1802, 1902, 2002, 2102,
 2202 antenna function portion (second vibration generating
 portion)

0103, 0403 first frequency

10 0104, 0404 second frequency

0105, 0405 first circuit portion

0106, 0406 second circuit portion

0107, 0407 first controller

0108, 0408 second controller

15 0209 antenna

0210 feeding point

0211, 0511, 0611, 0711, 0811, 0911 electromagnetic
 wave of first frequency

0212, 0512, 0612, 0712, 0812, 0912 electromagnetic
 20 wave of second frequency

0413 first frequency controller

0414 second frequency controller

0415 first phase controller

0416 second phase controller

25 0417 first timing controller

0418 second timing controller

1019 region of electromagnetic field

1020 region of electromagnetic field

1321 CPU

30 1322 main memory

1323 HDD

1324 circuit interface

1325 I/O

	1326	user interface
	1541	frying tank
	1643	food soaking tank
	1744, 2244	high-temperature food cooking portion
5	1845	room-temperature food cooking portion
	1946	refrigerated food cooking portion
	1947	refrigerating portion
	2048	low-temperature refrigerated food cooking
		portion
10	2149	food defrost cooking portion
	2250	vapor supply portion
	2351	frozen food storing portion
	1561, 1661, 1761, 1861, 1961, 2061, 2161, 2216	food
		(object)
15	1662	edible liquid
	4100	ingredient (object)

CLAIMS

1. An ingredient control device (100, 0100, 0400, 10, 4001, 4010) comprising at least one vibration generating portion (102, 0101, 0102, 0401, 0402, 3, 4) configured to
5 generate vibrations, wherein vibration is generated by the vibration generating portion to control an ingredient in an object disposed to face the vibration generating portion to decrease an interfacial tension between a water phase and an other phase.
- 10 2. The ingredient control device (100, 0100, 0400, 10, 4001, 4010) according to claim 1, wherein
the vibration generating portion (102, 0101, 0102, 0401, 0402, 3, 4) includes an electrode configured to
15 generate electromagnetic waves, and
a water activity of the object is controlled by generating electromagnetic waves by the electrode.
- 20 3. The ingredient control device (100, 0100, 0400, 10, 4001, 4010) according to claim 2, wherein electromagnetic waves are generated by the electrode to increase interfacial polarization between the water phase and the other phase of the object and thus decrease an interfacial tension between the water phase and the other phase and
25 bind water in the object into a pearl-chain structure.
4. The ingredient control device (0100, 0400) according to claim 1, 2, or 3, wherein
the vibration generating portion (102, 0101, 0102, 30 0401, 0402, 3, 4) includes a pair of vibration generating portions,
the ingredient control device (0100, 0400) further comprising:

a first circuit portion (0105, 0405) configured to apply alternating current of a first frequency to a first vibration generating portion (0101, 0401) of the pair of vibration generating portions; and

5 a second circuit portion (0106, 0406) configured to apply alternating current of a second frequency to a second vibration generating portion (0102, 0402) of the pair of vibration generating portions.

10 5. The ingredient control device (0400) according to claim 4, further comprising a frequency controller (0413, 0414) configured to control the first frequency and the second frequency to different frequencies.

15 6. The ingredient control device (0400) according to claim 4 or 5, wherein the first frequency and the second frequency are at least 10 kilohertz to at most 150 kilohertz.

20 7. The ingredient control device (0400) according to claim 4, 5, or 6, further comprising a phase controller (0415, 0416) configured to control a phase of the alternating current of the first frequency and the alternating current of the second frequency.

25

8. The ingredient control device (0100, 0400) according to any one of claims 4 to 7, further comprising:

a frying tank (1541); and

30 a heating portion (1542) configured to heat the frying tank, wherein

the vibration generating portions (1501, 1502) generate electromagnetic waves, and

the pair of vibration generating portions are disposed

to form an electromagnetic field in the frying tank.

9. The ingredient control device (0100, 0400) according to any one of claims 4 to 7, further comprising a food
5 soaking tank (1643) capable of storing edible liquid for soaking food (1661) to allow the edible liquid (1662) to soak into the food and/or to extract an ingredient from the food into the edible liquid, wherein
the vibration generating portions (1601, 1602)
10 generate electromagnetic waves, and
the pair of vibration generating portions (1601, 1602) are disposed to form an electromagnetic field in the food soaking tank.

15 10. The ingredient control device (0100, 0400) according to any one of claims 4 to 7, further comprising a high-temperature food cooking portion (1744) configured to heat food (1761a, 1761b, 1761c) as the object at high temperature, wherein
20 the vibration generating portions (1701, 1702) generate electromagnetic waves, and
the pair of vibration generating portions are disposed to form an electromagnetic field in the high-temperature food cooking portion.

25 11. The ingredient control device (0100, 0400) according to any one of claims 4 to 7, further comprising a room-temperature food cooking portion (1845) in which food (1861) as the object is placed at room temperature, wherein
30 the vibration generating portions (1801, 1802) generate electromagnetic waves, and
the pair of vibration generating portions are disposed to form an electromagnetic field in the room-temperature

food cooking portion.

12. The ingredient control device (0100, 0400) according to any one of claims 4 to 7, further comprising a
5 refrigerated food cooking portion (1946) configured to refrigerate food (1961) as the object, wherein
the vibration generating portions (1901, 1902) generate electromagnetic waves, and
the pair of vibration generating portions are disposed
10 to form an electromagnetic field in the refrigerated food cooking portion.

13. The ingredient control device (0100, 0400) according to any one of claims 4 to 7, further comprising a low-
15 temperature refrigerated food cooking portion (2048) configured to store food (2061) as the object by low-temperature refrigeration, wherein
the vibration generating portions (2001, 2002) generate electromagnetic waves, and
20 the pair of vibration generating portions are disposed to form an electromagnetic field in the low-temperature refrigerated food cooking portion.

14. The ingredient control device (0100, 0400) according to any one of claims 4 to 7, further comprising a food
25 defrost cooking portion (2149) for defrosting frozen food, wherein
the vibration generating portions (2101, 2102) generate electromagnetic waves, and
30 the pair of vibration generating portions are disposed to form an electromagnetic field in the food defrost cooking portion.

15. The ingredient control device (0100, 0400) according to any one of claims 10 to 14, further comprising a vapor supply portion (2250) configured to supply water vapor and/or water spray.

5

16. The ingredient control device (0100, 0400) according to any one of claims 4 to 7, further comprising a frozen food storing portion (2351) configured to store food as the object by freezing, wherein

10 the vibration generating portions (2301, 2302) generate electromagnetic waves, and

 the pair of vibration generating portions are disposed to form an electromagnetic field in the frozen food storing portion.

15

17. The ingredient control device (10, 4001, 4010) according to claim 1, wherein the vibration generating portion (102, 0101, 0102, 0401, 0402, 3, 4) includes a pair of vibration generating portions,

20 the ingredient control device (10, 4001, 4010) further comprising a power source (10) configured to generate alternating current, wherein

 a first vibration generating portion (3) of the pair of vibration generating portions is coupled to one
25 electrode of the power source, and

 a second vibration generating portion (4) of the pair of vibration generating portions is coupled to another electrode of the power source.

30 18. The ingredient control device (10, 4001, 4010) according to claim 17, wherein the vibration generating portions (3, 4) are sheet-like members.

19. The ingredient control device (10) according to claim 17 or 18, further comprising a temperature controller (6) configured to control ambient temperature.

5 20. The ingredient control device (10) according to claim 17, 18, or 19, further comprising a container (11) in which the object is disposed, wherein

the vibration generating portions (3, 4) are electrodes configured to generate electromagnetic waves,

10 the container has a part serving as one electrode of a pair of the electrodes and another part serving as another electrode of the pair of the electrodes, and

an insulating member (7) is installed between the pair of the electrodes to separate the pair of the electrodes
15 from each other.

21. An ingredient control method using an ingredient control device (100, 0100, 0400, 10, 4001, 4010) including at least one vibration generating portion (102, 0101, 0102,
20 0401, 0402, 3, 4) configured to generate vibrations,

the method comprising generating vibrations by the vibration generating portion to control an ingredient in an object disposed to face the vibration generating portion to decrease an interfacial tension between a water phase and
25 an other phase.

22. The ingredient control method according to claim 21, wherein

the vibration generating portion (102, 0101, 0102,
30 0401, 0402, 3, 4) includes an electrode configured to generate electromagnetic waves, and

a water activity of the object is controlled by generating electromagnetic waves by the electrode.

23. The ingredient control method according to claim 21 or 22, wherein electromagnetic waves are generated by the electrode to increase interfacial polarization between the water phase and the other phase of the object to decrease
5 an interfacial tension between the water phase and the other phase and bind water in the object into a pearl-chain structure.

24. The ingredient control method according to claim 22,
10 wherein a DC electric field is applied as an offset electric field to an AC electric field to increase interfacial polarization between the water phase and the other phase to decrease an interfacial tension between the water phase and the other phase and bind water in the
15 object into a pearl-chain structure.

25. The ingredient control method according to claim 24, wherein the DC electric field of approximately +100 V is applied as an offset electric field on the water phase side
20 relative to the other phase in the AC electric field to increase interfacial polarization between the water phase and the other phase of the object and thus decrease the interfacial tension between the water phase and the other phase and bind water in the object into a pearl-chain
25 structure.

26. The ingredient control method according to any one of claims 22 to 25, wherein the electromagnetic waves are low-frequency waves.
30

27. The ingredient control method according to any one of claims 22 to 25, wherein the electromagnetic waves have a frequency of 10 kHz to 500 kHz.

28. The ingredient control method according to any one of claims 22 to 27, wherein

the water in the object is divided into bound water and free water, and

5 the free water in the object is bound in a pearl-chain structure.

29. The ingredient control method according to claim 21, wherein

10 the vibration generating portion (102, 0101, 0102, 0401, 0402, 3, 4) includes a pair of vibration generating portions,

the vibration generating portions generate electromagnetic waves,

15 one (0101, 0401) of the pair of vibration generating portions applies an electromagnetic field of a first frequency to the object, and

the other (0102, 0402) of the pair of vibration generating portions applies an electromagnetic field of a
20 second frequency different from the first frequency to the object.

30. A transportation method using an ingredient control device (10) including at least one vibration generating
25 portion (3, 4) configured to generate vibrations, the method comprising:

installing an object disposed to face the vibration generating portion; and

30 transporting the object while generating vibrations by the vibration generating portion to control an ingredient in the object to decrease an interfacial tension between a water phase and an other phase.

31. A transportation method using an ingredient control device (10) including at least one vibration generating portion (3, 4) configured to generate vibrations, the method comprising:

5 installing an object disposed to face the vibration generating portion;

generating vibrations by the vibration generating portion to control an ingredient in the object to decrease an interfacial tension between a water phase and an other
10 phase;

removing the object from the ingredient control device after elapse of a predetermined period of time; and thereafter transporting the object.

15 32. A cooking method using an ingredient control device (4001, 4010) including at least one vibration generating portion (3, 4) configured to generate vibrations and an oil reservoir (4006, 4011) in which the vibration generating portion is installed, the method comprising:

20 storing oil in the oil reservoir;

frying an object in oil in the oil reservoir in which the vibration generating portion generates vibrations to control an ingredient in the object to decrease an interfacial tension between a water phase and an other

25 phase; and

thereafter washing the object with water.

33. The cooking method according to claim 32, wherein after the object is washed with water, the object is baked.

30

34. The cooking method according to claim 32, wherein after the object is washed with water, the object is boiled.

35. The cooking method according to claim 32, wherein after the object is washed with water, the object is steamed.

5 36. The cooking method according to any one of claims 32 to 35, wherein the vibration generating portion (3, 4) generates electromagnetic waves.

37. The cooking method according to any one of claims 32
10 to 36, wherein

the vibration generating portion (3, 4) is an electrode-configured to generate electromagnetic waves,
the oil reservoir is comprised of a pair of electrodes,

15 the oil reservoir has a part serving as one electrode of the pair of the electrodes and another part serving as the other electrode of the pair of the electrodes, and
an insulating member (12) is installed between the pair of the electrodes to separate the pair of the
20 electrodes from each other.

38. A program for a computer of an ingredient control device (0100, 0400) including a pair of vibration generating portions configured to generate electromagnetic
25 waves to control an ingredient in an object to decrease an interfacial tension between a water phase and an other phase, the program causing the computer to perform:

applying an electromagnetic field of a first frequency by one (0101, 0401) of the pair of vibration generating
30 portions to the object installed between the pair of vibration generating portions; and
applying an electromagnetic field of a second

frequency different from the first frequency by the other (0102, 0402) of the pair of vibration generating portions to the object installed between the pair of vibration generating portions.