

FIELD OF INVENTION

This invention relates to the enhanced, dynamic, efficient and economic production of high purity water in large quantity by utilizing, the sensible heat and latent heat present in waste flue gas / exhaust gases being released / dissipated into the atmosphere. Further this invention relates to the unique process of evaporation, saturation and evaporative - condensation using brackish / sea water and fossil fuel fired boiler flue gas or turbine exhaust gases being liberated / dissipated into the atmosphere or the hot gases that are generated during combustion of hydrocarbon gases, when they are flared into the atmosphere in a flare stack. The source of the waste heat as mentioned above can be from several sources, combustion of fossil fuel like Coal, Lignite, Natural gas, Coke oven gas etc., Sugarcane baggase burning and also the heat present in furnace exhaust gas and flared hydrocarbon gases. Waste heat present in the flue gases generated from the heat sources other than that mentioned above can also be used for the production of high purity water from sea / brackish water in large quantity.

BACKGROUND

Conventionally, good quality water from sea / brackish water is being produced with known process of REVERSE OSMOSIS, MULTI STAGE FLASH EVAPORATION or with the conventional EVAPORATION & CONDENSATION method. All these above methods require huge quantity of energy by way of electricity and / or thermal energy to evaporate / separate water from brackish / sea water. The FGEPS (FLARED, GAS EXHAUST, PNEUMATIC, SATURATION AND CONDENSATION) process and system envisages the effective utilization of the waste heat and

water vapor, (present in the fossil fuel fired boiler flue gas and turbine exhaust gases that are being liberated into the atmosphere, and also heat available in flared hydrocarbon gases being dissipated into the atmosphere). Waste heat present in the flue / exhaust gases generated from heat sources other than that mentioned above can also be used for the production of high purity water in large quantity as stated above by desalination of brackish / sea water.

OBJECT OF INVENTION

It is therefore the object of this invention to improve & dynamically enhance the performance of the process for the production of large quantity of high purity water at very low overall production cost. Maintaining a low operating cost as well as ensuring low initial investment achieves this.

The object of the present invention is to provide a method by which high purity water in large quantity can be obtained using waste heat as the main source of energy.

It is further object of the present invention to conceptualize /demonstrate a process and a system by which high purity water can be obtained by using the waste heat in flue gas / exhaust gas / flared hydrocarbon gas / furnace exhaust gas in combination with sea / brackish water.

It is still another object of the present invention to utilize the latent heat released by the water vapors present in the flue gas during phase change.

It is also the object of the invention to extract / separate water already present in the flue gas thus increasing the overall quantity of production of high purity water generated.

It is also the object of the invention that during the process of generating high purity water from brackish / sea water, to simultaneously scrub, clean and cool the flue gas / exhaust gas / furnace exhaust gases / hydrocarbon flared gas before they are dissipated into the atmosphere

It is the object of the invention to effectively and efficiently utilize the heat still present in the flue gas / exhaust gas being liberated into the atmosphere as waste heat so that the overall efficiency of the boiler / thermal power plant is greatly improved.

It is also the objective of the invention to mitigate corrosion (of heat exchanger tubes - due to the presence of acidic media in the flue gas / exhaust gas) by ensuring dilution of the acidic media itself through condensation of large volume of water from the flue gas / exhaust gas / furnace exhaust gases / hydrocarbon flared gas before they are dissipated into the atmosphere

It is also the objective of the invention to use the flue gas / exhaust gas / flared gas as a container to separate and hold water from sea / brackish water, since the flue gas / exhaust gas / hydrocarbon flared gas are almost immune to the corrosive and erosive nature of sea / brackish water.

It is also the objective of the invention to make the flue gas / exhaust gas / flared hydrocarbon gas more amenable for selective separation of Carbon dioxide gas present in it thus facilitating Carbon sequestration.

SUMMARY OF INVENTION

The FGEPSC (FLARED, GAS EXHAUST, PNEUMATIC, SATURATION AND CONDENSATION) process and system incorporates extraction of water from sea / brackish water using the sensible and latent heat present in

fossil fuel fired flue gas / exhaust gas, flared hydrocarbon gas and furnace exhaust. The heat and water vapor present in these gases and which are normally exhausted / dissipated into the atmosphere and usually / normally termed as "waste heat," shall be utilized as the main source of energy for desalination of seawater to generate high purity water. Normally the sea and atmospheric air are used as a heat sink to cool the hot flue gas / exhaust gases. In the envisaged system, most of the "waste heat" available in the hot flue gas / exhaust gas / furnace exhaust gases / hydrocarbon flared gas is effectively and efficiently used to extract water from sea / brackish water before the gases are dissipated into the atmosphere.

Further this process is environment friendly as suspended particulate matters and sulphur bearing chemical compounds present in the flue gas / exhaust gases / furnace exhaust gases / hydrocarbon flared gas are cleaned, trapped and settled before the gases dissipated into the atmosphere.

The object of this invention is to effectively utilize the sensible heat and latent heat present in flue gas / exhaust gases and which are normally liberated / dissipated into the atmosphere, (like the exhaust gas generated by a Natural gas fired turbine coupled to a Waste Heat Recovery Boiler, or flue gas generated by a fossil fuel fired steam boiler / hot water generator, or flared hydrocarbon gases or furnace exhaust gas) for the production of large quantity of high purity water from brackish / sea water at very low production cost, by maintaining a low operating cost and ensuring low initial investment.

BRIEF DESCRIPTION

The FGEPSC (FLARED, GAS EXHAUST, PNEUMATIC, SATURATION AND CONDENSATION) process and system envisages the effective and

efficient utilization of the heat and water vapor present in fossil fired flue gas / turbine exhaust gas / flared hydrocarbon gases / furnace exhaust which are normally dissipated / liberated into the atmosphere and are usually termed as “waste heat,” for desalination of sea / brackish water to generate high purity water in large quantity.

In thermal power plants using coal fired boilers, enormous quantity of flue gas (typically around 800 Metric Tons per Hour – 210 MW capacity power plant) is liberated / dissipated into the atmosphere. This flue gas contains water (typically, around 12% of the total quantity of flue gas) and the flue gas is also hot, (typically ranging from around 100 to 220 degrees Centigrade) and termed as waste heat. About 300 Tons per Hour of high purity water can be obtained from seawater by processing around 200 Tons per Hour of hot flue gas at around 160 °C.

In another embodiment, typically a 50 MW Natural gas fired turbine, generating electric power, around 200 Tons per hour of exhaust gas at around 500 degree C will be generated. This extremely hot exhaust gas from the gas turbine is routed to a waste heat recovery unit, to recover maximum heat in the form of high-pressure steam or hot water. The hot exhaust gas at around 115 degree Centigrade leaves the waste heat recovery unit and is dissipated into the atmosphere as “waste heat” through a stack. It is envisaged that by processing around 200 Tons per hour of this exhaust gas at around 115 degree Centigrade in the present Process and System, about 400 Tons per hour of high purity water can be generated from seawater.

In yet another embodiment of the present invention, hot waste gasses also termed as flared hydrocarbon gas (at around 1000 degree Centigrade) is made to pass through equipment (E & S unit), evaporation and scrubbing

unit, where brackish / sea water is sprayed into the stream of hot waste gasses. The hot waste gasses are sucked from the vicinity of the flare, ensuring there is no physical contact with the flare stack. Whenever required an external blower will provide sufficient atmospheric air to complete the combustion of partially / un-burnt chemical compounds in the waste flared gasses. The E&S unit is installed, engulfed within the duct carrying the waste gasses and is installed near the top of the duct where the hot waste gasses enters the duct. Please refer (Diagram – 2 and 3). Appropriate provision is made for moving the tip of the duct D-1 backward & forward, upward & downward, sideways swivel movement. All these movements can be

operated electrically, mechanical or hydraulically. It is envisaged that by processing around 200 Tons per hour of waste gasses (flared hydrocarbon gases) at around 1200 degree Centigrade in the present Process and System, about 900 Tons per Hour of high purity water can be generated from seawater.

Higher the temperatures of HOT flue gas / exhaust gas more water can be evaporated from seawater during direct scrubbing of the gases with seawater. Coal fired thermal power plant flue gas will have higher temperature (100 - 220 degree Centigrade) compared to Natural Gas fired combined cycle thermal power plant (110 - 120 degree Centigrade), flared hydro carbon gas and furnace exhaust temperature are very high (1000 - 1500 degree Centigrade).

Of the total quantity of high purity water that will be generated, more than 90% of the water will be of very high purity (typically water containing TDS - Total Dissolved Solids of less than 5 ppm - Parts Per Million).

The figures indicated hereinabove are indicative and will vary depending upon location, ambient conditions, quality and quantity of fossil fuel being fired, quality & quantity of combustible hydrocarbon gasses being flared, type and size of furnace. The quality, quantity and temperature of flue gas / exhaust gas as well as availability, quality and temperature of sea / brackish water are also important parameters governing the operation of the envisaged process and apparatus.

DETAILED PROCESS DESCRIPTION: (Refer Diagram: 1)

As per the present invention with the help of a blower B1, hot flue gas (around 160⁰C) in the case of Coal fired thermal power plant, hot waste gas (around 1000⁰C) in the case of flared hydrocarbon gases from flare stack and hot exhaust gas (around 110⁰C) from a Natural gas fired Combined Cycle Power Plant is made to pass through equipment (E & S unit), evaporation and scrubbing unit, where sea / brackish water is sprayed into the stream of hot flue gas / exhaust gas. Hot flue gas enters the unit through inlet No. 2 and seawater is sprayed through several nozzles No. 1a.

Seven different unit operations sequentially, consecutively & simultaneously take place inside this equipment (E & S unit)

- A1 is the mixing zone where thorough mixing of sea / brackish water and flue gas / exhaust gas is ensured by strategic placement of nozzles and by fine atomized spraying of the sea / brackish water into the gas.
- A2 is the quenching zone where the temperature of the hot flue gas is drastically lowered – from around 160⁰C to around 60⁰C in the case of Coal fired thermal power plant; and from around 1200⁰C to around 70⁰C in the case of waste gases from flare stack; and around 110⁰C

to near 65°C in the case of hot exhaust gas liberated by Natural gas fired Combined Cycle power Plant.

- A3 is the evaporation zone where some quantity of water from the sea / brackish water evaporates using the sensible heat that is present in the flue gas and combines / mixes with the gas itself.
- A4 is the neutralization zone where most of the acidic media present in the flue gas / exhaust gas is neutralized by the alkaline media present in the sea / brackish water.
- A5 is the saturation zone where it is ensured that the flue gas / exhaust gas is now fully saturated with water at the requisite temperature.
- A6 is the scrubbing zone where the suspended particulate matters present in the flue gas / exhaust gas is entrapped in the sea / brackish water making the flue gas relatively free of particulate matters.
- A7 is the separation zone where the moisture laden flue gas / exhaust gas is separated from the sea / brackish water now containing suspended particulate matters.

The sea / brackish water now containing suspended particulate matters leave the equipment (E & S unit) – Evaporation and Scrubbing unit through outlet No.: 3. The moisture laden flue gas passes through outlet No.: 4 sucked through the induced draft blower B1 to enter the Single Effect Evaporative - Condenser (SEEC unit). The number of effects in a Single Effect Evaporative-Condenser (SEEC unit) depends upon the temperature and volume of saturated flue gas / exhaust gases, entering it.

The warm moisture laden flue gas now enters the bank of tubes in the Single Effect Evaporative - Condenser (SEEC unit), through inlet No.: 5. Requisite

vacuum is maintained on the shell side of the Single Effect Evaporative - Condenser (SEEC unit), while cold sea / brackish water is sprayed on to the top of the tubes. The sea / brackish water enters the Single Effect Evaporative - Condenser (SEEC unit) through nozzles No.: 6a and after some water in the sea / brackish water evaporates due to the heat and vacuum, leaves the Single Effect Evaporative - Condenser (SEEC unit) through outlet No.: 7. The evaporated low pressure water vapor leaves the Single Effect Evaporative - Condenser (SEEC unit) through outlet No.: 8 on its way to the Mechanical Vapor Compressor (MVC unit), which is also maintaining the vacuum in the Three Stage Single Effect Evaporative - Condenser (SEEC unit). The cold flue gas now leaves the Three Stage Single Effect Evaporative - Condenser (SEEC unit) through outlet No.: 9 to enter the Stack S1 for dissipation into the atmosphere through outlet No.: 10. At the bottom of the stack S1, condensed water droplets in the flue gas is separated and removed as good quality water through outlet No.: 11.

The Mechanical Vapor Compressor (MVC unit) while maintaining the vacuum in the Single Effect Evaporative - Condenser (SEEC unit) also sucks the low-pressure vapor generated in it through inlet No.: 12. The Mechanical Vapor Compressor (MVC unit) then compresses the low-pressure vapor to raise its temperature before releasing the compressed vapor to the Multiple Effect Distillation (MED unit) through outlet No.: 14. The Mechanical Vapor Compressor (MVC unit) is operated with the help of an electric motor. The Mechanical Vapor Compression (MVC) units are only to increase / enhance the total quantity of high purity water generated. FGEPSC (FLARED, GAS EXHAUST, PNEUMATIC, SATURATION AND CONDENSATION) process and system can be operated without

installing Mechanical Vapor Compression (MVC) units. Depending on the required temperature and pressure of the compressed low-pressure vapors entering the Multiple Effect Distillation (MED unit), a number of Mechanical Vapor Compression (MVC) units may be placed in series for each stage of the Single Effect Evaporative - Condenser (SEEC unit). Higher the temperature and pressure of the compressed low-pressure vapors more quantity of high purity water will be generated by the Multiple Effect Distillation (MED unit)

The compressed low-pressure vapor now enters the bank of tubes in the first effect of the Multiple Effect Distillation (MED unit) through nozzle No.: 15, as a source of heat, wherein the low-pressure vapor condenses and is removed as high quality water. Requisite vacuum is maintained on the shell side of the Multiple Effect Distillation (MED unit), while cold sea / brackish water is sprayed on to the top of the tubes. The sea / brackish water enters the Multiple Effect Distillation (MED unit) through nozzles No.: 16a and after some water in the sea / brackish water evaporates due to the heat and vacuum leaves the Multiple Effect Distillation (MED unit) for re-circulation or disposal to sea through a common outlet No.: 17.

The evaporated low-pressure water vapor leaves the first effect of the Multiple Effect Distillation (MED unit) to enter the tube side of the second effect of the Multiple Effect Distillation (MED unit) as the source of heat. The process is repeated in a series of effects, which are being maintained under vacuum. In each effect sea / brackish water is sprayed on to the tubes forcing some water to evaporate due to the heat & vacuum while later condensing inside the tubes as high quality water.

All the condensed high quality water is collected and removed from the Multiple Effect Distillation (MED unit) through outlet No.: 20. A vacuum apparatus VS1 consisting of condensers and vacuum pump shall maintain the requisite vacuum in all the effects of the Multiple Effect Distillation (MED unit) by sucking the ultimate and final low-pressure vapors through inlet No.: 22. Cold seawater will enter the condenser through inlet No.: 18 as coolant and leave through outlet No.: 19 to be returned to the sea. The condensed water vapor will leave the condenser through outlet No.: 21.

Necessary instrumentation and control system shall be provided for safe operation. The temperature and volume of flue gas entering and leaving the system, the temperature and quantity of seawater entering and leaving the system, the pressure, temperature and volume of low-pressure and compressed low-pressure water vapor will be controlled and measured with appropriate measuring and controlling apparatus. The electrical energy consumed for normal operation of the system will be measured and recorded. Periodic chemical analysis of the sea / brackish water and flue gas / exhaust gases entering and leaving the system will be carried out with suitable measuring and analyzing apparatus.

SALIENT FEATURES OF THE INVENTION

- The invention offers a high & efficient utilization of waste heat, – (sensible heat and latent heat which is otherwise being dissipated into the atmosphere / sea), to generate large quantity of good quality water.

- The overall thermal efficiency of the (Coal / Natural gas fired) Thermal Power Plant is improved. Due to the additional & maximum utilization of the available heat still remaining in the flue gas, and presently being dissipated into the atmosphere as waste heat.
- Taking cognizant of the fact, that huge quantity of heat energy in the form of latent heat is available in the hot flue gas, presently being dissipated into the atmosphere. This is mainly due to the presence of large quantity of water vapor in the flue gas liberated by the Coal / Natural gas fired thermal power station.
- Apt utilization of the flue gas itself for separating water from seawater, knowing very well that the flue gas is almost inert and can withstand the erosive and corrosive nature of seawater.
- During the process of separation of water from seawater with the hot flue gas liberated by the coal fired boiler of a thermal power station, the flue gas itself gets cleaned & scrubbed, leading to a better & cleaner environment. Particulate matters are trapped in the scrubbing liquid (seawater); and the alkaline nature of seawater neutralizes the corrosive oxides of Sulphur.
- Scrubbing, cleaning and quenching of the hot flue gas makes it more amenable to selective separation of Carbon dioxide gas present in it, thus facilitating Carbon sequestration.

- Drastically drop the temperature of the highly corrosive hot flue gas, so that exotic material of construction (like Titanium / Monel / Inconel etc.) need **not** be recommended to withstand corrosion due to the presence of oxides of sulphur in the flue gas. Carbon steel vessels lined with Rubber / Plastics will suffice.
- The condensation of large quantity of water from the flue gas will ensure, dilution of the traces of un-scrubbed acidic media still present in the flue gas. (Traces of oxides of Sulphur that escaped seawater scrubbing). The dilution of acidic media by condensed water is so high that it makes the acidic media practically non-corrosive. Therefore the Heat Exchanger tubes can be made of Stainless steel or Aluminum
- Ensuring that the temperature of the motive steam, the main energy source for the Multiple Effect Distillation unit, is not raised above 70°C. This leads to low temperature evaporation and condensation in the Multiple Effect Distillation unit. Tending towards drastic reduction of scaling of heat exchanger tubes by salts present in the corrosive seawater. Thus Aluminum tubes can be recommended instead of expensive Titanium tubes.
- Taking full advantage of the fact that the cost of electric power for a Thermal Power plant is far lower compared to the cost of electric power otherwise made available commercially to the final consumer.

1. A process for the effective utilization of sensible and latent heat of waste heat, for desalination of sea / brackish water to generate high purity water, and characterized in that the waste heat sources are flue gas / exhaust gases from combustion of fossil fuel, heat present in furnace exhaust gas and flared hydrocarbon gases and burning of Sugarcane baggase comprising of the following steps of

guiding the flue gas / exhaust gases from the plant where it is generated to an Evaporating and Scrubbing E & S unit with the help of blowers (B1) and insulated ducts (2), spraying the scrubbing liquid i.e. sea / brackish water into E & S unit through several spraying nozzles (1a) and discharging the polluted scrubbing liquid from the E & S unit through outlet (3) for recycling or further treatment,

mixing the hot flue gas / exhaust gases with sea / brackish water in the E & S unit, quenching of heat and lowering of temperature of the flue gas / exhaust gases leading to evaporation of a quantity of water from the sea / brackish water due to the sensible heat present in the flue gas/ exhaust gases,

neutralizing the acidic media present in the flue gas/ exhaust gases with alkaline media present in the sea / brackish water,

maintaining complete saturation of the flue gas / exhaust gases with water vapor,

assisting in cleansing of the flue gas / exhaust gases by trapping the suspended particles in sea / brackish water,

separating the warm moisture laden flue gas / exhaust gases from the polluted sea / brackish water,

allowing the warm moisture laden flue gas to enter into a bank of tubes placed inside the Single Effect Evaporating Condensor(SEEC) unit, spraying Sea / brackish water through several nozzles (6A) on top of the tube bundles leading to cooling of the warm moisture laden flue gas / exhaust gases inside the tubes causing condensation of the water vapor and release of latent heat,

exchanging the released heat to evaporate water from seawater at low temperature by maintaining required vacuum on the shell side of the SEEC unit, thus generating low-pressure water vapor,

5 discharging the clean and cold flue gas / exhaust gases from the SEEC unit through duct (9) and dissipated into the atmosphere through stack (S1), releasing the concentrated sea / brackish water from the SEEC unit through outlet (7) for recycling or further treatment,

condensing the low-pressure vapors in the first effect of the Multiple Effect Distillation (MED) unit and the Vacuum System (VS),

10 allowing said low-pressure water vapors to enter into the tube banks placed inside the first effect of the MED unit through inlet (14) as a heat source,

15 spraying sea / brackish water through several nozzles (16A) over the tube bundles, to cool and condense the low-pressure water vapors inside the tubes, generating high purity water and forcing release of latent heat,

maintaining requisite vacuum on the shell side and releasing the heat to generate more low-pressure water vapors,

20 releasing the concentrated sea / brackish water from the MED unit through outlet(s) (20) for recycling or further treatment,

creating and maintaining the vacuum by the VS in the MED unit, mainly to remove non-condensable gases that may have entered the system through leakages and sea / brackish water.

25 2. The process as claimed in claim 1, wherein the sources of waste heat are flue gas/exhaust gas generated from heat energy plants, factories, power stations.

3. The process as claimed in claim 1, wherein the temperature of flue gas in case of coal fired thermal station is in the range of 100 - 220 degree C and water content of the flue gas is in the range of 10 – 15%.

30 4. The process as claimed in claim 1, wherein the temperature of the exhaust gas, emanating in case of Natural gas fired Combined Cycle Power plant consisting of a gas turbine, and a waste heat recovery boiler,

is in the range of 100 – 120 degree C and the exhaust gas having water content in the range of 20 – 25%.

5. The process as claimed in claim 1, wherein the temperature of flue gas in the case of hot waste gasses i.e. flared hydrocarbon gas and gases emanating from furnaces is in the range of 1000 – 1500 degree C.
6. The process as claimed in claim 5, wherein the hot waste gasses and flared hydrocarbon gases are sucked from the vicinity of the flare with no physical contact with the flare stack, sufficient atmospheric air to complete the combustion of partially / un-burnt organic chemical compounds still present in the waste gas (flared hydrocarbon gases) is provided by an external blower and E & S unit is installed, engulfed within the duct carrying the waste gas /flared hydrocarbon gases and is installed near the top of the duct where the hot waste gases (flared hydrocarbon gases) enters the duct.
7. The process as claimed in claim 1, wherein unit operation being carried out in the E&S unit is optionally carried out in packed columns, absorption columns spray chambers either individually or in combination.
8. The process as claimed in claim 1, wherein the released heat is exchanged to evaporate water from seawater at low temperature by maintaining required vacuum on the shell side of the SEEC unit, thus generating low- pressure water vapor.
9. The process as claimed in claim 1, wherein the low-pressure water vapors generated by the SEEC unit is routed to a Multiple Effect Distillation (MED) unit either directly or through Mechanical Vapor Compression (MVC) unit(s) or through Thermal Vapor Compression (TVC) unit(s).
10. The process as claimed in claim 1, wherein the MVC unit(s) and the TVC unit(s) raise the temperature and pressure of the low-pressure vapors generated by the SEEC unit, thus increasing / enhancing the quantity of high purity water that can be generated from sea / brackish water by the Multiple Effect Distillation (MED) unit, using the low-pressure water vapors as the heat source.

11. The process as claimed in claim 1, wherein the evaporated low-pressure vapor leaves first effect through outlet (17) of the MED unit to enter second effect of the MED unit through (16A) as heat source to evaporate water from seawater under vacuum and condenses as well to generate high purity water.
12. The process as claimed in claim 1, wherein the process of evaporative - condensation is repeated in a series of stages in case of SEEC unit and in a series of effects in MED unit.
13. The process as claimed in claim 1, wherein the flue gas / exhaust gas is simultaneously scrubbed, cleaned and cooled while extraction of the sensible heat and water vapor present in it, before being dissipated into the atmosphere.
14. The process as claimed in claim 1, wherein the carbon dioxide present in the flue gas becomes amenable to selective separation thus facilitating carbon sequestration.
15. The system for the utilization of sensible and latent heat of waste heat from various sources as claimed in claim 1 comprises of the following unit operation packages: blower B1 along with an evaporator and scrubbing (E & S) unit, single effect evaporative - condenser (SEEC) unit, mechanical vapor compressor (MVC) unit and multiple effect distillation (MED) unit.
16. The system as claimed in claim 15, wherein the E & S unit comprises zone A1 for mixing the flue gas/exhaust gas and seawater, A2 zone is the quenching zone, A3 is the evaporation zone, A4 is the neutralization zone A5 is the saturation zone A6 is the scrubbing zone and A7 is the separation zone.
17. The system as claimed in claim 15, wherein SEEC unit comprises a bank of tubes with inlet no 5 through which the moisture laden flue gas/exhaust gas enters the SEEC units, vacuum is maintained on the shell side of the SEEC unit and sea/brackish water is sprayed on the top of the tubes, the sea/brackish water enters the unit through inlet no 6a and leaves by outlet no 7.

18. The system as claimed in claim 15, wherein the MVC unit is operated with the help of an electric motor and maintains the vacuum and also sucks the low-pressure vapor through its inlet no 12, the low pressure vapor is then released to the MED unit through outlet no 14.
- 5 19. The system as claimed in claim 15, wherein the MED unit comprises of tubes and shell; inlets no 16a for seawater entry wherein vacuum is maintained on the shell side, and outlet no 17 from where high quality water is removed from MED; through outlet no. 20 the concentrated sea / brackish water from the (MED) unit is released through for recycling or
10 further treatment.
20. The system as claimed in claim 19, wherein the MED has a series of effects which are being maintained under vacuum by vacuum system VS1.