

CORRECTED VERSION

(19) World Intellectual Property Organization
International Bureau(43) International Publication Date
8 February 2001 (08.02.2001)

PCT

(10) International Publication Number
WO 01/09054 A1(51) International Patent Classification⁷: **C03C 25/10**,
C08J 5/08, H05K 1/03NC 27012 (US). **RICE, William, B.**; 2855 Gray Moss
Drive, Clemmons, NC 27012 (US).

(21) International Application Number: PCT/US00/20459

(74) Agents: **SIMINERIO, Andrew, C.**; PPG Industries, Inc.,
One PPG Place, Pittsburgh, PA 15272 et al. (US).

(22) International Filing Date: 28 July 2000 (28.07.2000)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:

60/146,605	30 July 1999 (30.07.1999)	US
60/146,337	30 July 1999 (30.07.1999)	US
60/146,862	3 August 1999 (03.08.1999)	US
PCT/US99/21442	8 October 1999 (08.10.1999)	US
PCT/US99/21443	8 October 1999 (08.10.1999)	US
60/183,562	18 February 2000 (18.02.2000)	US
09/527,034	16 March 2000 (16.03.2000)	US
09/548,379	12 April 2000 (12.04.2000)	US
09/668,916	11 May 2000 (11.05.2000)	US
09/620,526	20 July 2000 (20.07.2000)	US

(81) Designated States (*national*): AE, AL, AM, AT, AU, AZ,
BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK,
DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL,
IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU,
LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT,
RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA,
UG, UZ, VN, YU, ZA, ZW.(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian
patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European
patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,
IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG,
CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:

— With international search report.

(71) Applicant: **PPG INDUSTRIES OHIO, INC.** [US/US];
3800 West 143rd Street, Cleveland, OH 44111 (US).

(48) Date of publication of this corrected version:

19 April 2001

(72) Inventors: **NOVICH, Bruce, E.**; 1035 Highmont Road,
Pittsburgh, PA 15232 (US). **LAMMON-HILINSKI,**
Kami; 617-2 Center Avenue, Aspinwall, PA 15215 (US).
ROBERTSON, Walter, J.; 28 Shannopin Drive, Pitts-
burgh, PA 15202 (US). **WU, Xiang**; 1667 East Jamison
Place, Littleton, CO 80122 (US). **VELPARI, Vedagiri**;
230 Old Haymaker Road, Monroeville, PA 15146 (US).
LAWTON, Ernest, L.; 3432 Kilcash Drive, Clemmons,

(15) Information about Correction:

see PCT Gazette No. 16/2001 of 19 April 2001, Section II

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: IMPREGNATED GLASS FIBER STRANDS AND PRODUCTS INCLUDING THE SAME

(57) Abstract: The present invention provides an at least partially coated fiber strand comprising a plurality of fibers, the coating comprising an organic component and lamellar particles having a thermal conductivity of at least 1 Watt per meter K at a temperature of 300K. The present invention also provides an at least partially coated fiber strand comprising a plurality of fibers, the coating comprising an organic component and non-hydratable, lamellar particles. The present invention further provides an at least partially coated fiber strand comprising a plurality of fibers having a resin compatible coating composition on at least a portion of a surface of at least one of said fibers, the resin compatible coating composition comprising: (a) a plurality of discrete particles formed from materials selected from non-heat expandable organic materials, inorganic polymeric materials, non-heat expandable composite materials and mixtures thereof, the particles having an average particle size sufficient to allow strand wet out; (b) at least one lubricious material different from said plurality of discrete particles; and (c) at least one film-forming material. The present invention also provides an at least partially coated fiber strand comprising a plurality of glass fibers having a resin compatible coating composition on at least a portion of a surface of at least one of said glass fibers, the resin compatible coating composition comprising: (a) a plurality of lamellar, inorganic particles having a Mohs' hardness value which does not exceed the Mohs' hardness value of said glass fibers; and (b) at least one polymeric material. The present invention further provides an at least partially coated fiber strand comprising a plurality of glass fibers having a resin compatible coating composition on at least a portion of a surface of at least one of said glass fibers, the resin compatible coating composition comprising: (a) a plurality of hollow, non-heat expandable organic particles; and (b) at least one lubricious material different from the at least one hollow organic particle.



WO 01/09054 A1