

NATURAL GAS LIQUEFACTION BY A HIGH PRESSURE EXPANSION PROCESS**CROSS-REFERENCE TO RELATED APPLICATIONS**

[0001] This application claims the priority benefit of U.S. Provisional Application No. 62/565,725 filed September 29, 2017 entitled "Natural Gas Liquefaction by a High Pressure Expansion Process," the entirety of which is incorporated by reference herein.

[0002] This application is related to U.S. Provisional Application No. 62/565733, titled "Natural Gas Liquefaction by a High Pressure Expansion Process," being commonly owned and filed on an even date herewith, the disclosure of which is incorporated by reference herein in its entirety.

BACKGROUNDField of Disclosure

[0003] The disclosure relates generally to liquefied natural gas (LNG) production. More specifically, the disclosure relates to LNG production at high pressures.

Description of Related Art

[0004] This section is intended to introduce various aspects of the art, which may be associated with the present disclosure. This discussion is intended to provide a framework to facilitate a better understanding of particular aspects of the present disclosure. Accordingly, it should be understood that this section should be read in this light, and not necessarily as an admission of prior art.

[0005] Because of its clean burning qualities and convenience, natural gas has become widely used in recent years. Many sources of natural gas are located in remote areas, which are great distances from any commercial markets for the gas. Sometimes a pipeline is available for transporting produced natural gas to a commercial market. When pipeline transportation is not feasible, produced natural gas is often processed into liquefied natural gas (LNG) for transport to market.

[0006] In the design of an LNG plant, one of the most important considerations is the process for converting the natural gas feed stream into LNG. Currently, the most common liquefaction processes use some form of refrigeration system. Although many refrigeration cycles have been used to liquefy natural gas, the three types most commonly used in LNG plants today are: (1) the "cascade cycle," which uses multiple single component refrigerants in heat exchangers arranged progressively to reduce the temperature of the gas to a liquefaction temperature; (2) the "multi-component refrigeration cycle," which uses a multi-component

refrigerant in specially designed exchangers; and (3) the "expander cycle," which expands gas from feed gas pressure to a low pressure with a corresponding reduction in temperature. Most natural gas liquefaction cycles use variations or combinations of these three basic types.

[0007] The refrigerants used in liquefaction processes may comprise a mixture of components such as methane, ethane, propane, butane, and nitrogen in multi-component refrigeration cycles. The refrigerants may also be pure substances such as propane, ethylene, or nitrogen in "cascade cycles." Substantial volumes of these refrigerants with close control of composition are required. Further, such refrigerants may have to be imported and stored, which impose logistics requirements, especially for LNG production in remote locations. Alternatively, some of the components of the refrigerant may be prepared, typically by a distillation process integrated with the liquefaction process.

[0008] The use of gas expanders to provide the feed gas cooling, thereby eliminating or reducing the logistical problems of refrigerant handling, is seen in some instances as having advantages over refrigerant-based cooling. The expander system operates on the principle that the refrigerant gas can be allowed to expand through an expansion turbine, thereby performing work and reducing the temperature of the gas. The low temperature gas is then heat exchanged with the feed gas to provide the refrigeration needed. The power obtained from cooling expansions in gas expanders can be used to supply part of the main compression power used in the refrigeration cycle. The typical expander cycle for making LNG operates at the feed gas pressure, typically under about 6,895 kPa (1,000 psia). Supplemental cooling is typically needed to fully liquefy the feed gas and this may be provided by additional refrigerant systems, such as secondary cooling and/or sub-cooling loops. For example, U.S. Pat. No. 6,412,302 and U.S. Pat. No. 5,916,260 present expander cycles which describe the use of nitrogen as refrigerant in the sub-cooling loop.

[0009] Previously proposed expander cycles have all been less efficient thermodynamically, however, than the current natural gas liquefaction cycles based on refrigerant systems. Expander cycles have therefore not offered any installed cost advantage to date, and liquefaction cycles involving refrigerants are still the preferred option for natural gas liquefaction.

[0010] Because expander cycles result in a high recycle gas stream flow rate and high inefficiency for the primary cooling (warm) stage, gas expanders have typically been used to further cool feed gas after it has been pre-cooled to temperatures well below -20 °C using an external refrigerant in a closed cycle, for example. Thus, a common factor in most proposed expander cycles is the requirement for a second, external refrigeration cycle to pre-cool the gas

before the gas enters the expander. Such a combined external refrigeration cycle and expander cycle is sometimes referred to as a "hybrid cycle." While such refrigerant-based pre-cooling eliminates a major source of inefficiency in the use of expanders, it significantly reduces the benefits of the expander cycle, namely the elimination of external refrigerants.

5 [0011] U. S. Patent Application US2009/0217701 introduced the concept of using high pressure within the primary cooling loop to eliminate the need for external refrigerant and improve efficiency, at least comparable to that of refrigerant-based cycles currently in use. The high pressure expander process (HPXP), disclosed in U. S. Patent Application US2009/0217701, is an expander cycle which uses high pressure expanders in a manner
10 distinguishing from other expander cycles. A portion of the feed gas stream may be extracted and used as the refrigerant in either an open loop or closed loop refrigeration cycle to cool the feed gas stream below its critical temperature. Alternatively, a portion of LNG boil-off gas may be extracted and used as the refrigerant in a closed loop refrigeration cycle to cool the feed gas stream below its critical temperature. This refrigeration cycle is referred to as the primary
15 cooling loop. The primary cooling loop is followed by a sub-cooling loop which acts to further cool the feed gas. Within the primary cooling loop, the refrigerant is compressed to a pressure greater than 1,500 psia, or more preferably, to a pressure of approximately 3,000 psia. The refrigerant is then cooled against an ambient cooling medium (air or water) prior to being near isentropically expanded to provide the cold refrigerant needed to liquefy the feed gas.

20 [0012] Figure 1 depicts an example of a known HPXP liquefaction process **100**, and is similar to one or more processes disclosed in U. S. Patent Application US2009/0217701. In Figure 1, an expander loop **102** (i.e., an expander cycle) and a sub-cooling loop **104** are used. Feed gas stream **106** enters the HPXP liquefaction process at a pressure less than about 1,200 psia, or less than about 1,100 psia, or less than about 1,000 psia, or less than about 900 psia, or
25 less than about 800 psia, or less than about 700 psia, or less than about 600 psia. Typically, the pressure of feed gas stream **106** will be about 800 psia. Feed gas stream **106** generally comprises natural gas that has been treated to remove contaminants using processes and equipment that are well known in the art.

[0013] In the expander loop **102**, a compression unit **108** compresses a refrigerant stream
30 **109** (which may be a treated gas stream) to a pressure greater than or equal to about 1,500 psia, thus providing a compressed refrigerant stream **110**. Alternatively, the refrigerant stream **109** may be compressed to a pressure greater than or equal to about 1,600 psia, or greater than or equal to about 1,700 psia, or greater than or equal to about 1,800 psia, or greater than or equal to about 1,900 psia, or greater than or equal to about 2,000 psia, or greater than or equal to

about 2,500 psia, or greater than or equal to about 3,000 psia, thus providing compressed refrigerant stream **110**. After exiting compression unit **108**, compressed refrigerant stream **110** is passed to a cooler **112** where it is cooled by indirect heat exchange with a suitable cooling fluid to provide a compressed, cooled refrigerant stream **114**. Cooler **112** may be of the type that provides water or air as the cooling fluid, although any type of cooler can be used. The temperature of the compressed, cooled refrigerant stream **114** depends on the ambient conditions and the cooling medium used, and is typically from about 35 °F. to about 105 °F. Compressed, cooled refrigerant stream **114** is then passed to an expander **116** where it is expanded and consequently cooled to form an expanded refrigerant stream **118**. Expander **116** is a work-expansion device, such as a gas expander, which produces work that may be extracted and used for compression. Expanded refrigerant stream **118** is passed to a first heat exchanger **120**, and provides at least part of the refrigeration duty for first heat exchanger **120**. Upon exiting first heat exchanger **120**, expanded refrigerant stream **118** is fed to a compression unit **122** for pressurization to form refrigerant stream **109**.

[0014] Feed gas stream **106** flows through first heat exchanger **120** where it is cooled, at least in part, by indirect heat exchange with expanded refrigerant stream **118**. After exiting first heat exchanger **120**, the feed gas stream **106** is passed to a second heat exchanger **124**. The principal function of second heat exchanger **124** is to sub-cool the feed gas stream. Thus, in second heat exchanger **124** the feed gas stream **106** is sub-cooled by sub-cooling loop **104** (described below) to produce sub-cooled stream **126**. Sub-cooled stream **126** is then expanded to a lower pressure in expander **128** to form a liquid fraction and a remaining vapor fraction. Expander **128** may be any pressure reducing device, including, but not limited to a valve, control valve, Joule Thompson valve, Venturi device, liquid expander, hydraulic turbine, and the like. The sub-cooled stream **126**, which is now at a lower pressure and partially liquefied, is passed to a surge tank **130** where the liquefied fraction **132** is withdrawn from the process as an LNG stream **134**, which has a temperature corresponding to the bubble point pressure. The remaining vapor fraction (flash vapor) stream **136** may be used as fuel to power the compressor units.

[0015] In sub-cooling loop **104**, an expanded sub-cooling refrigerant stream **138** (preferably comprising nitrogen) is discharged from an expander **140** and drawn through second and first heat exchangers **124**, **120**. Expanded sub-cooling refrigerant stream **138** is then sent to a compression unit **142** where it is re-compressed to a higher pressure and warmed. After exiting compression unit **142**, the re-compressed sub-cooling refrigerant stream **144** is cooled in a cooler **146**, which can be of the same type as cooler **112**, although any type of cooler

may be used. After cooling, the re-compressed sub-cooling refrigerant stream is passed to first heat exchanger **120** where it is further cooled by indirect heat exchange with expanded refrigerant stream **118** and expanded sub-cooling refrigerant stream **138**. After exiting first heat exchanger **120**, the re-compressed and cooled sub-cooling refrigerant stream is expanded
5 through expander **140** to provide a cooled stream which is then passed through second heat exchanger **124** to sub-cool the portion of the feed gas stream to be finally expanded to produce LNG.

[0016] U. S. Patent Application US2010/0107684 disclosed an improvement to the performance of the HPXP through the discovery that adding external cooling to further cool
10 the compressed refrigerant to temperatures below ambient conditions provides significant advantages which in certain situations justifies the added equipment associated with external cooling. The HPXP embodiments described in the aforementioned patent applications perform comparably to alternative mixed external refrigerant LNG production processes such as single mixed refrigerant processes. However, there remains a need to further improve the efficiency
15 of the HPXP as well as overall train capacity. There remains a particular need to improve the efficiency of the HPXP in cases where the feed gas pressure is less than 1,200 psia.

[0017] U. S. Patent Application 2010/0186445 disclosed the incorporation of feed compression up to 4,500 psia to the HPXP. Compressing the feed gas prior to liquefying the gas in the HPXP's primary cooling loop has the advantage of increasing the overall process
20 efficiency. For a given production rate, this also has the advantage of significantly reducing the required flow rate of the refrigerant within the primary cooling loop which enables the use of compact equipment, which is particularly attractive for floating LNG applications. Furthermore, feed compression provides a means of increasing the LNG production of an HPXP train by more than 30% for a fixed amount of power going to the primary cooling and
25 sub-cooling loops. This flexibility in production rate is again particularly attractive for floating LNG applications where there are more restrictions than land based applications in matching the choice of refrigerant loop drivers with desired production rates. Although liquefying the feed gas at high pressures has advantages, it was found that for liquefaction pressures greater than 1,500 psia the choice of suitable cryogenic heat exchangers for the primary cooling and
30 sub-cooling loops were limited to options significantly high in cost, weight and with reduced fluid processing capabilities. For example, the use of printed circuit heat exchangers, which are capable of operating at pressures greater than 4,500 psia, was shown to significantly increase project cost compared to the more widely sourced brazed aluminum heat exchanger type where proven operating pressures are less than 1,500 psia. This significant increase in

cost may limit the practical application of feed compression to up to 1,500 psia. Thus, there remains a need to further improve the HPXP without requiring feed compression or feed compression greater than 1,500 psia. Additionally, there remains an additional need to allow the use of significant feed compression with HPXP without requiring the use of high-cost main cryogenic heat exchangers such as printed circuit heat exchangers.

SUMMARY

[0018] The present disclosure provides a method for liquefying a feed gas stream rich in methane using a system having first and second heat exchanger zones, where the method comprises the following steps: providing the feed gas stream at a pressure less than 1,200 psia; providing a compressed refrigerant stream with a pressure greater than or equal to 1,500 psia; cooling the compressed refrigerant stream by indirect heat exchange with an ambient temperature air or water, to produce a compressed, cooled refrigerant stream; directing the compressed, cooled refrigerant stream to the second heat exchanger zone to additionally cool the compressed, cooled refrigerant stream below ambient temperature to produce a compressed, additionally cooled refrigerant stream; expanding the compressed, additionally cooled refrigerant stream in at least one work producing expander, thereby producing an expanded, cooled refrigerant stream; passing the expanded, cooled refrigerant stream through the first heat exchanger zone to form a first warm refrigerant stream, wherein the first warm refrigerant stream has a temperature that is cooler, by at least 5 °F, than the highest fluid temperature within the first heat exchanger zone; passing the feed gas stream through the first heat exchanger zone to cool at least part of the feed gas stream by indirect heat exchange with the expanded, cooled refrigerant stream, thereby forming a liquefied gas stream; directing at least a portion of the first warm refrigerant stream to the second heat exchanger zone to cool by indirect heat exchange the compressed, cooled refrigerant stream, thereby forming a second warm refrigerant stream; and compressing the second warm refrigerant stream to produce the compressed refrigerant stream.

[0019] The present disclosure also provides a system for liquefying a feed gas stream rich in methane, the system having first and second heat exchanger zones. A feed gas stream at a pressure less than 1,200 psia is provided. A compressed refrigerant stream is provided with a pressure greater than or equal to 1,500 psia. A cooler is configured to cool the compressed refrigerant stream by indirect heat exchange with an ambient temperature air or water, to produce a compressed, cooled refrigerant stream. At least one heat exchanger is provided within the second heat exchanger zone, the compressed, cooled refrigerant stream being directed to the at least one heat exchanger within the second heat exchanger zone to additionally

cool the compressed, cooled refrigerant stream below ambient temperature and thereby produce a compressed, additionally cooled refrigerant stream. At least one work producing expander is arranged to expand the compressed, additionally cooled refrigerant stream, thereby producing an expanded, cooled refrigerant stream. At least one heat exchanger is provided within the first heat exchanger zone. The expanded, cooled refrigerant stream passes through the at least one heat exchanger in the first heat exchanger zone to form a first warm refrigerant stream, wherein the first warm refrigerant stream has a temperature that is cooler, by at least 5 °F, than the highest fluid temperature within the first heat exchanger zone. The feed gas stream passes through the first heat exchanger zone to cool at least part of the feed gas stream by indirect heat exchange with the expanded, cooled refrigerant stream, thereby forming a liquefied gas stream. At least a portion of the first warm refrigerant stream is directed to the second heat exchanger zone to cool by indirect heat exchange the compressed, cooled refrigerant stream, thereby forming a second warm refrigerant stream. A compressor is configured to compress the second warm refrigerant stream to produce the compressed refrigerant stream.

[0020] The present disclosure also provides a method for liquefying a feed gas stream rich in methane, where the method comprises the following steps: providing the feed gas stream at a pressure less than 1,200 psia; compressing the feed gas stream to a pressure of at least 1,500 psia to form a compressed gas stream; cooling the compressed gas stream by indirect heat exchange with an ambient temperature air or water, to form a cooled, compressed gas stream; expanding the cooled, compressed gas stream in at least one work producing expander to a pressure that is less than 2,000 psia and no greater than the pressure to which the gas stream was compressed, to thereby form a chilled gas stream; providing a compressed refrigerant stream with a pressure greater than or equal to 1,500 psia; cooling the compressed refrigerant stream by indirect heat exchange with an ambient temperature air or water, to produce a compressed, cooled refrigerant stream; directing the compressed, cooled refrigerant stream to a second heat exchanger zone, to additionally cool the compressed, cooled refrigerant stream below ambient temperature, to produce a compressed, additionally cooled refrigerant stream; expanding the compressed, additionally cooled refrigerant stream in at least one work producing expander, thereby producing an expanded, cooled refrigerant stream; passing the expanded, cooled refrigerant stream through a first heat exchanger zone to form a first warm refrigerant stream, whereby the first warm refrigerant stream has a temperature that is cooler, by at least 5 °F, than the highest fluid temperature within the first heat exchanger zone; passing the chilled gas stream through the first heat exchanger zone to cool at least part of the chilled

gas stream by indirect heat exchange with the expanded, cooled refrigerant, thereby forming a liquefied gas stream; directing the first warm refrigerant stream to the second heat exchanger zone to cool by indirect heat exchange the compressed, cooled refrigerant stream, thereby forming a second warm refrigerant stream; and compressing the second warm refrigerant stream to produce the compressed refrigerant stream.

[0021] The disclosure also provides a system for liquefying a feed gas stream rich in methane and having a pressure less than 1,200 psia. The system comprises: a compressor for compressing the feed gas stream to a pressure of at least 1,500 psia, to form a compressed gas stream; a cooler for cooling the compressed gas stream by indirect heat exchange with an ambient temperature air or water, to form a cooled, compressed gas stream; at least one work producing expander for expanding the cooled, compressed gas stream to a pressure that is less than 2,000 psia and no greater than the pressure to which the gas stream was compressed, to thereby form a chilled gas stream; a compressed refrigerant stream with a pressure greater than or equal to 1,500 psia; a refrigerant cooler for cooling the compressed refrigerant stream by indirect heat exchange with an ambient temperature air or water, to produce a compressed, cooled refrigerant stream; a heat exchanger zone through which the compressed, cooled refrigerant stream is directed to be additionally cooled below ambient temperature, to produce a compressed, additionally cooled refrigerant stream; an additional work producing expander for expanding the compressed, additionally cooled refrigerant stream, thereby producing an expanded, cooled refrigerant stream; an additional heat exchanger zone through which the expanded, cooled refrigerant stream is passed, to thereby form a first warm refrigerant stream, whereby the warm refrigerant stream has a temperature that is cooler, by at least 5 °F, than the highest fluid temperature within the first heat exchanger zone; wherein the chilled gas stream is passed through the additional heat exchanger zone to cool at least part of the chilled gas stream by indirect heat exchange with the expanded, cooled refrigerant, thereby forming a liquefied gas stream; wherein the first warm refrigerant stream is directed to the heat exchanger zone to cool by indirect heat exchange the compressed, cooled refrigerant stream, thereby forming a second warm refrigerant stream; and an additional compressor for compressing the second warm refrigerant stream to produce the compressed refrigerant stream.

[0022] The foregoing has broadly outlined the features of the present disclosure so that the detailed description that follows may be better understood. Additional features will also be described herein.

BRIEF DESCRIPTION OF THE DRAWINGS

[0023] These and other features, aspects and advantages of the disclosure will become

apparent from the following description, appending claims and the accompanying drawings, which are briefly described below.

[0024] Figure 1 is a schematic diagram of a system for LNG production according to known principles.

5 [0025] Figure 2 is a schematic diagram of a system for LNG production according to disclosed aspects.

[0026] Figure 3 is a schematic diagram of a system for LNG production according to disclosed aspects.

10 [0027] Figure 4 is a schematic diagram of a system for LNG production according to disclosed aspects.

[0028] Figure 5 is a schematic diagram of a system for LNG production according to disclosed aspects.

[0029] Figure 6 is a schematic diagram of a system for LNG production according to disclosed aspects.

15 [0030] Figure 7 is a schematic diagram of a system for LNG production according to disclosed aspects.

[0031] Figure 8 is a schematic diagram of a system for LNG production according to disclosed aspects.

20 [0032] Figure 9 is a schematic diagram of a system for LNG production according to disclosed aspects.

[0033] Figure 10 is a flowchart of a method according to aspects of the disclosure.

[0034] Figure 11 is a flowchart of a method according to aspects of the disclosure.

[0035] Figure 12 is a flowchart of a method according to aspects of the disclosure.

25 [0036] It should be noted that the figures are merely examples and no limitations on the scope of the present disclosure are intended thereby. Further, the figures are generally not drawn to scale, but are drafted for purposes of convenience and clarity in illustrating various aspects of the disclosure.

DETAILED DESCRIPTION

30 [0037] To promote an understanding of the principles of the disclosure, reference will now be made to the features illustrated in the drawings and specific language will be used to describe the same. It will nevertheless be understood that no limitation of the scope of the disclosure is thereby intended. Any alterations and further modifications, and any further applications of the principles of the disclosure as described herein are contemplated as would normally occur to one skilled in the art to which the disclosure relates. For the sake of clarity, some features

not relevant to the present disclosure may not be shown in the drawings.

[0038] At the outset, for ease of reference, certain terms used in this application and their meanings as used in this context are set forth. To the extent a term used herein is not defined below, it should be given the broadest definition persons in the pertinent art have given that term as reflected in at least one printed publication or issued patent. Further, the present techniques are not limited by the usage of the terms shown below, as all equivalents, synonyms, new developments, and terms or techniques that serve the same or a similar purpose are considered to be within the scope of the present claims.

[0039] As one of ordinary skill would appreciate, different persons may refer to the same feature or component by different names. This document does not intend to distinguish between components or features that differ in name only. The figures are not necessarily to scale. Certain features and components herein may be shown exaggerated in scale or in schematic form and some details of conventional elements may not be shown in the interest of clarity and conciseness. When referring to the figures described herein, the same reference numerals may be referenced in multiple figures for the sake of simplicity. In the following description and in the claims, the terms “including” and “comprising” are used in an open-ended fashion, and thus, should be interpreted to mean “including, but not limited to.”

[0040] The articles “the,” “a” and “an” are not necessarily limited to mean only one, but rather are inclusive and open ended so as to include, optionally, multiple such elements.

[0041] As used herein, the terms “approximately,” “about,” “substantially,” and similar terms are intended to have a broad meaning in harmony with the common and accepted usage by those of ordinary skill in the art to which the subject matter of this disclosure pertains. It should be understood by those of skill in the art who review this disclosure that these terms are intended to allow a description of certain features described and claimed without restricting the scope of these features to the precise numeral ranges provided. Accordingly, these terms should be interpreted as indicating that insubstantial or inconsequential modifications or alterations of the subject matter described and are considered to be within the scope of the disclosure. The term “near” is intended to mean within 2%, or within 5%, or within 10%, of a number or amount.

[0042] As used herein, the term “compression unit” means any one type or combination of similar or different types of compression equipment, and may include auxiliary equipment, known in the art for compressing a substance or mixture of substances. A “compression unit” may utilize one or more compression stages. Illustrative compressors may include, but are not limited to, positive displacement types, such as reciprocating and rotary compressors for

example, and dynamic types, such as centrifugal and axial flow compressors, for example.

[0043] "Exemplary" is used exclusively herein to mean "serving as an example, instance, or illustration." Any embodiment or aspect described herein as "exemplary" is not to be construed as preferred or advantageous over other embodiments.

5 [0044] The term "gas" is used interchangeably with "vapor," and is defined as a substance or mixture of substances in the gaseous state as distinguished from the liquid or solid state. Likewise, the term "liquid" means a substance or mixture of substances in the liquid state as distinguished from the gas or solid state.

[0045] As used herein, "heat exchange area" means any one type or combination of similar
10 or different types of equipment known in the art for facilitating heat transfer. Thus, a "heat exchange area" may be contained within a single piece of equipment, or it may comprise areas contained in a plurality of equipment pieces. Conversely, multiple heat exchange areas may be contained in a single piece of equipment.

[0046] A "hydrocarbon" is an organic compound that primarily includes the elements
15 hydrogen and carbon, although nitrogen, sulfur, oxygen, metals, or any number of other elements can be present in small amounts. As used herein, hydrocarbons generally refer to components found in natural gas, oil, or chemical processing facilities.

[0047] As used herein, the terms "loop" and "cycle" are used interchangeably.

[0048] As used herein, "natural gas" means a gaseous feedstock suitable for manufacturing
20 LNG, where the feedstock is a methane-rich gas containing methane (C1) as a major component. Natural gas may include gas obtained from a crude oil well (associated gas) or from a gas well (non-associated gas).

[0049] The disclosure describes a process/method and system for liquefying natural gas and other methane-rich gas streams to produce liquefied natural gas (LNG) and/or other
25 liquefied methane-rich gases. In one or more aspects of the disclosure, the primary cooling loop is segmented into two heat exchanger zones. Within the first heat exchanger zone, the primary cooling loop refrigerant is used to liquefy the feed gas. Within the second heat exchanger zone, all or a portion of the primary cooling loop refrigerant is used to cool the high pressure primary cooling loop refrigerant prior to expansion of the refrigerant. The first heat exchanger zone is
30 physically separate from second heat exchanger zone. Additionally, the heat exchanger type of the first heat exchanger zone is different from the heat exchanger type of the second heat exchanger zone. One advantage of having two separate heat exchanger zones is that the types of heat exchangers in the two zones can be different from each other. As a non-limiting example, the type of heat exchanger(s) used in the first exchanger zone may include a brazed

aluminum heat exchanger, and the type of heat exchanger(s) used in the second heat exchanger zone may be include a printed circuit heat exchanger. It is in the first exchanger zone where more the 90% of the heat transfer needed to liquefy the feed gas occurs. Using the less expensive brazed aluminum heat exchanger here reduces project cost. The significantly more expensive printed circuit heat exchanger may be used in the second heat exchanger zone because it can operate at the required 3,000 psia pressure of the high pressure refrigerant. The use of a printed circuit heat exchanger in the second heat exchanger zone does not significantly impact overall project cost since it is a relatively small heat exchanger. This is because the heat transfer duty within the second heat exchanger zone is significantly smaller than that of the first heat exchanger zone. Both heat exchanger zones may comprise multiple heat exchangers.

[0050] In an aspect, a method for liquefying a gas stream, particularly one rich in methane, includes: (a) providing the gas stream at a pressure less than 1,200 psia; (b) providing a compressed refrigerant with a pressure greater than or equal to 1,500 psia; (c) cooling the compressed refrigerant by indirect heat exchange with an ambient temperature air or water to produce a compressed, cooled refrigerant; (d) directing the compressed, cooled refrigerant to a second heat exchanger zone to additionally cool the compressed, cooled refrigerant below ambient temperature to produce a compressed, additionally cooled refrigerant; (e) expanding the compressed, additionally cooled refrigerant in at least one work producing expander thereby producing an expanded, cooled refrigerant; (f) passing the expanded, cooled refrigerant through a first heat exchanger zone to form a first warm refrigerant, whereby the first warm refrigerant has a temperature that is cooler, by at least 5 °F, than the highest fluid temperature within the first heat exchanger zone, and whereby the heat exchanger type of the first heat exchanger zone is different from the heat exchanger type of the second heat exchanger zone; (g) passing the gas stream through the first heat exchanger zone to cool at least part of the gas stream by indirect heat exchange with the expanded, cooled refrigerant, thereby forming a liquefied gas stream; (h) directing at least a portion of the first warm refrigerant to the second heat exchanger zone to cool by indirect heat exchange the compressed, cooled refrigerant thereby forming a second warm refrigerant; and (i) compressing the second warm refrigerant to produce the compressed refrigerant.

[0051] In another aspect, a method for liquefying a gas stream includes: (a) providing the gas stream at a pressure less than 1,200 psia; (b) compressing the gas stream to a pressure of at least 1,500 psia to form a compressed gas stream; (c) cooling the compressed gas stream by indirect heat exchange with an ambient temperature air or water to form a compressed, cooled

gas stream; (d) expanding the compressed, cooled gas stream in at least one work producing expander to a pressure that is less than 2,000 psia and no greater than the pressure to which the gas stream was compressed, to thereby form a chilled gas stream; (e) providing a compressed refrigerant with a pressure greater than or equal to 1,500 psia (f) cooling the compressed refrigerant by indirect heat exchange with an ambient temperature air or water to produce a compressed, cooled refrigerant (g) directing the compressed, cooled refrigerant to a second heat exchanger zone to additionally cool the compressed, cooled refrigerant below ambient temperature to produce a compressed, additionally cooled refrigerant; (h) expanding the compressed, additionally cooled refrigerant in at least one work producing expander thereby producing an expanded, cooled refrigerant; (i) passing the expanded, cooled refrigerant through a first heat exchanger zone to form a first warm refrigerant, whereby the first warm refrigerant has a temperature that is cooler, by at least 5 °F, than the highest fluid temperature within the first heat exchanger zone, and whereby the heat exchanger type of the first heat exchanger zone is different from the heat exchanger type of the second heat exchanger zone; (j) passing the chilled gas stream through the first heat exchanger zone to cool at least part of the chilled gas stream by indirect heat exchange with the expanded, cooled refrigerant, thereby forming a liquefied gas stream; (k) directing the first warm refrigerant to the second heat exchanger zone to cool by indirect heat exchange the compressed, cooled refrigerant, thereby forming a second warm refrigerant; and (l) compressing the second warm refrigerant to produce the compressed refrigerant.

[0052] In another aspect, a method for liquefying a gas stream includes: (a) providing the gas stream at a pressure less than 1,200 psia; (b) providing a refrigerant stream at near the same pressure of the gas stream; (c) mixing the gas stream with the refrigerant stream to form a second gas stream; (d) compressing the second gas stream to a pressure of at least 1,500 psia to form a compressed second gas stream; (e) cooling the compressed second gas stream by indirect heat exchange with an ambient temperature air or water to form a compressed, cooled second gas stream; (f) directing the compressed, cooled second gas stream to a second heat exchanger zone to additionally cool the compressed, cooled second gas stream below ambient temperature to produce a compressed, additionally cooled second gas stream; (g) expanding the compressed, additionally cooled second gas stream in at least one work producing expander to a pressure that is less than 2,000 psia and no greater than the pressure to which the second gas stream was compressed, to thereby form an expanded, cooled second gas stream; (h) separating the expanded, cooled second gas stream into a first expanded refrigerant and a chilled gas stream; (i) expanding the first expanded refrigerant in at least one work producing

expander, thereby producing a second expanded refrigerant; (j) passing the second expanded refrigerant through a first heat exchanger zone to form a first warm refrigerant, whereby the first warm refrigerant has a temperature that is cooler, by at least 5 °F, than the highest fluid temperature within the first heat exchanger zone, and whereby the heat exchanger type of the first heat exchanger zone is different from the heat exchanger type of the second heat exchanger zone; (k) passing the chilled gas stream through the first heat exchanger zone to cool at least part of the chilled gas stream by indirect heat exchange with the second expanded refrigerant, thereby forming a liquefied gas stream; (l) directing the first warm refrigerant to the second heat exchanger zone to cool by indirect heat exchange the compressed, cooled second gas stream, thereby forming a second warm refrigerant; and (m) compressing the second warm refrigerant to produce the refrigerant stream.

[0053] Aspects of the disclosure may include the additional steps of compressing the gas stream to a pressure no greater than 1,600 psia and then cooling the compressed gas stream by indirect heat exchange with an ambient temperature air or water prior to directing the gas stream to the first heat exchanger zone. Aspects of the disclosure may also include the additional steps of cooling the gas stream to a temperature below the ambient by indirect heat exchange within an external cooling unit prior to directing the gas stream to the first heat exchanger zone. Aspects of the disclosure may also include the additional steps of cooling the compressed, cooled refrigerant to a temperature below the ambient temperature by indirect heat exchange with an external cooling unit prior to directing the compressed, cooled refrigerant to the second heat exchanger zone. These described additional steps may be employed singularly or in combination with each other.

[0054] Aspects of the disclosure have several advantages over the known liquefaction processes, in which feed compression is required to significantly improve the efficiency of the HPXP. In contrast, the efficiency of the disclosed aspects is more than 16% greater than the efficiency for a comparable configuration according to known liquefaction processes. Aspects of the disclosure may have the additional advantage of allowing significant feed compression (greater than 1,500 psia) without requiring the use of high cost main cryogenic heat exchangers for the first heat exchanger zone. Feed compression by the disclosed method may provide a means of increasing the LNG production of an HPXP train by more than 25% for a fixed amount of power going to the primary cooling and sub-cooling loops. Aspects of the disclosure may also have the advantage of combining the compression service of the feed gas and some of that of the primary cooling loop to reduce equipment count. Such an embodiment provides a highly efficient and compact configuration suitable for small scale LNG applications.

[0055] Figure 2 is a schematic diagram that illustrates a liquefaction system **200** according to an aspect of the disclosure. The liquefaction system **200** includes a primary cooling loop **202**, which may also be called an expander loop. The liquefaction system also includes a sub-cooling loop **204**, which is a closed refrigeration loop preferably charged with nitrogen as the sub-cooling refrigerant. Within the primary cooling loop **202**, an expanded, cooled refrigerant stream **205** is directed to a first heat exchanger zone **201** where it exchanges heat with a feed gas stream **206** to form a first warm refrigerant stream **208**. A portion of the first warm refrigerant **208** is directed to a second heat exchanger zone **210** where, in one or more heat exchangers **210a**, it exchanges heat with a compressed, cooled refrigerant stream **212** to additionally cool the compressed, cooled refrigerant stream and form a second warm refrigerant stream **209** and a compressed, additionally cooled refrigerant stream **213**. The one or more heat exchangers **210a** may be of a printed circuit heat exchanger type, a shell and tube heat exchanger type, or a combination thereof. The heat exchanger types within the second heat exchanger zone may have a design pressure of greater than 1,500 psia, or more preferably, a design pressure of greater than 2,000 psia, or more preferably, a design pressure of greater than 3,000 psia.

[0056] The portion of the first warm refrigerant stream **208** directed to the second heat exchanger zone **210** has a temperature that is cooler by at least 5 °F, or more preferably, cooler by at least 10 °F, or more preferably, cooler by at least 15 °F, than the highest fluid temperature within the first heat exchanger zone **201**. The portion of the first warm refrigerant stream **208** that may remain within the first heat exchanger zone (as shown by reference number **208a**) further exchanges heat with the feed gas stream to form a third warm refrigerant stream **214**. The second warm refrigerant stream **209** from the second heat exchanger zone **210** may be combined with the third warm refrigerant stream **214** from the first heat exchanger zone **201** to produce a fourth warm refrigerant stream **216**. The fourth warm refrigerant stream is compressed in one or more compression units **218**, **220** to a pressure greater than 1,500 psia, or more preferably, to a pressure of approximately 3,000 psia, to form a compressed refrigerant stream **222**. The compressed refrigerant stream **222** is then cooled against an ambient cooling medium (air or water) in a cooler **224** to produce the compressed, cooled refrigerant stream **212**. Cooler **224** may be similar to cooler **112** as previously described. The compressed, additionally cooled refrigerant stream **213** is near isentropically expanded in an expander **226** to produce the expanded, cooled refrigerant stream **205**. Expander **226** may be a work-expansion device, such as a gas expander, which produces work that may be extracted and used for compression.

[0057] The first heat exchanger zone **201** may include a plurality of heat exchanger devices, and in the aspects shown in Figure 2, the first heat exchanger zone includes first and second main heat exchangers **232**, **234**, and a sub-cooling heat exchanger **236** exchange heat with the expanded, cooled refrigerant **205**. These heat exchangers may be of a brazed aluminum heat exchanger type, a plate fin heat exchanger type, a spiral wound heat exchanger type, or a combination thereof. Within the sub-cooling loop **204**, an expanded sub-cooling refrigerant stream **238** (preferably comprising nitrogen) is discharged from an expander **240** and drawn through sub-cooling heat exchanger **236** and second and first main heat exchangers **234**, **232**. Expanded sub-cooling refrigerant stream **238** is then sent to a compression unit **242** where it is re-compressed to a higher pressure and warmed. After exiting compression unit **242**, the re-compressed sub-cooling refrigerant stream **244** is cooled in a cooler **246**, which can be of the same type as cooler **224**, although any type of cooler may be used. After cooling, the re-compressed sub-cooling refrigerant stream is passed through first and second main heat exchangers **232**, **234** where it is further cooled by indirect heat exchange with part or all of the warm refrigerant stream **208** and expanded sub-cooling refrigerant stream **238**. After exiting first heat exchange area **201**, the re-compressed and cooled sub-cooling refrigerant stream is expanded through expander **240** to provide the expanded sub-cooled refrigerant stream **238** that is re-cycled through the first heat exchanger zone as described herein. In this manner, the feed gas stream **206** is cooled, liquefied and sub-cooled in the first heat exchanger zone **201** to produce a sub-cooled gas stream **248**. Sub-cooled gas stream **248** is then expanded to a lower pressure in expander **250** to form a liquid fraction and a remaining vapor fraction. Expander **250** may be any pressure reducing device, including but not limited to a valve, control valve, Joule Thompson valve, Venturi device, liquid expander, hydraulic turbine, and the like. The sub-cooled stream **248**, which is now at a lower pressure and partially liquefied, is passed to a surge tank **252** where the liquefied fraction **254** is withdrawn from the process as an LNG stream **256**, which has a temperature corresponding to the bubble point pressure. The remaining vapor fraction (flash vapor) stream **258** may be used as fuel to power the compressor units.

[0058] Figure 3 is a schematic diagram that illustrates a liquefaction system **300** according to another aspect of the disclosure. Liquefaction system **300** is similar to liquefaction system **200** and for the sake of brevity similarly depicted or numbered components may not be further described. Liquefaction system **300** includes a primary cooling loop **302** and a sub-cooling loop **304**. Liquefaction system **300** also includes first and second heat exchanger zones **301**, **310**. In contrast with liquefaction system **200**, all of the first warm refrigerant **308** is directed

to the second heat exchanger zone **310** where, in one or more heat exchangers **310a**, it exchanges heat with a compressed, cooled refrigerant stream **312** to form a second warm refrigerant **309**.

[0059] The first warm refrigerant stream **308** has a temperature that is cooler by at least 5 °F, or more preferably, cooler by at least 10 °F, or more preferably, cooler by at least 15 °F, than the highest fluid temperature within the first heat exchanger zone. The second warm refrigerant stream **309** may be compressed in one or more compressors **318**, **320** to a pressure greater than 1,500 psia, or more preferably, to a pressure of approximately 3,000 psia, to thereby form a compressed refrigerant stream **322**. The compressed refrigerant stream **322** is then cooled against an ambient cooling medium (air or water) to produce the compressed, cooled refrigerant stream **312** that is directed to the second heat exchanger zone **310**. The compressed, additionally cooled refrigerant stream **313** is near isentropically expanded in an expander **326** to produce the expanded, cooled refrigerant stream **305**.

[0060] The feed gas stream **306** is directed through the first heat exchange area **301** that includes a main heat exchanger **332** and a sub-cooling heat exchanger **336**. The number of main heat exchangers in first heat exchanger zone **301** may be reduced since all of the first warm refrigerant **308** is directed to the second heat exchanger zone **310**. Within the sub-cooling loop **304**, an expanded sub-cooling refrigerant stream **338** (preferably comprising nitrogen) is discharged from an expander **340** and drawn through sub-cooling heat exchanger **336** and main heat exchanger **332**. Expanded sub-cooling refrigerant stream **338** is then sent to a compression unit **342** where it is re-compressed to a higher pressure and warmed. After exiting compression unit **342**, the re-compressed sub-cooling refrigerant stream **344** is cooled in a cooler **346**, which can be of the same type as cooler **324**, although any type of cooler may be used. After cooling, the re-compressed sub-cooling refrigerant stream is passed through main heat exchanger **232** where it is further cooled by indirect heat exchange with part or all of the expanded, cooled refrigerant stream **305** and expanded sub-cooling refrigerant stream **338**. After exiting first heat exchange area **301**, the re-compressed and cooled sub-cooling refrigerant stream is expanded through expander **340** to provide the expanded sub-cooled refrigerant stream **338** that is re-cycled through the first heat exchange area as described herein. In this manner, the feed gas stream **306** is cooled, liquefied and sub-cooled in the first heat exchanger zone **301** to produce a sub-cooled gas stream **348**. Sub-cooled gas stream **348** is then expanded to a lower pressure in expander **350** to form a liquid fraction and a remaining vapor fraction. Expander **350** may be any pressure reducing device, including but not limited to a valve, control valve, Joule Thompson valve, Venturi device, liquid expander, hydraulic turbine, and the like. The

sub-cooled stream **348**, which is now at a lower pressure and partially liquefied, is passed to a surge tank **352** where the liquefied fraction **354** is withdrawn from the process as an LNG stream **356**, which has a temperature corresponding to the bubble point pressure. The remaining vapor fraction (flash vapor) stream **358** may be used as fuel to power the compressor units.

[0061] Figure 4 is a schematic diagram that illustrates a liquefaction system **400** according to another aspect of the disclosure. Liquefaction system **400** is similar to liquefaction system **200**, and for the sake of brevity similarly depicted or numbered components may not be further described. Liquefaction system **400** includes a primary cooling loop **402** and a sub-cooling loop **404**. Liquefaction system **400** also includes first and second heat exchanger zones **401**, **410**. In liquefaction system **400**, the sub-cooling loop **404** is an open refrigeration loop where a portion **449** of the expanded, sub-cooled gas stream **448** is recycled and used as the sub-cooling refrigerant stream. Specifically, the portion **449** of the expanded, sub-cooled gas stream is directed through the first heat exchanger zone **401** as previously described before being compressed in a compressor **442**, cooled in a cooler **446**, and re-inserted into the feed gas stream **406**. This sub-cooling refrigerant stream may be one stream, as shown, or may comprise multiple streams at different pressures: for example, a portion of the expanded, sub-cooling gas stream - not to exceed 50% thereof - may be diverted and pass through one or more pressure reduction valves to reduce its pressure to a range of about 30 to 300 psia, to thereby produce one or more reduced pressure gas streams. The reduced pressure gas streams may then be passed through the first heat exchanger zone as the sub-cooling refrigerant. Having multiple streams improves the efficiency of the sub-cooling process. Alternatively, this sub-cooling loop may be configured to be a closed refrigeration loop.

[0062] Figure 5 is a schematic diagram that illustrates a liquefaction system **500** according to another aspect of the disclosure. Liquefaction system **500** is similar to liquefaction system **200** and for the sake of brevity similarly depicted or numbered components may not be further described. Liquefaction system **500** includes a primary cooling loop **502** and a sub-cooling loop **504**. Liquefaction system **500** also includes first and second heat exchanger zones **501**, **510**. Liquefaction system **500** stream includes the additional steps of compressing the feed gas stream **506** in a compressor **560** and then, using a cooler **562**, cooling the compressed feed gas **561** with ambient air or water to produce a cooled, compressed feed gas stream **563**. Feed gas compression may be used to improve the overall efficiency of the liquefaction process and increase LNG production.

[0063] Figure 6 is a schematic diagram that illustrates a liquefaction system **600** according

to still another aspect of the disclosure. Liquefaction system **600** is similar to liquefaction system **300** and for the sake of brevity similarly depicted or numbered components may not be further described. Liquefaction system **600** includes a primary cooling loop **602** and a sub-cooling loop **604**. Liquefaction system **600** also includes first and second heat exchanger zones **601**, **610**. Liquefaction system **600** includes the additional step of chilling, in an external cooling unit **665**, the feed gas stream **606** to a temperature below the ambient temperature to produce a chilled gas stream **667**. The chilled gas stream **667** is then directed to the first heat exchanger zone **601** as previously described. Chilling the feed gas as shown in Figure 6 may be used to improve the overall efficiency of the liquefaction process and increase LNG production.

[0064] Figure 7 is a schematic diagram that illustrates a liquefaction system **700** according to another aspect of the disclosure. Liquefaction system **700** is similar to liquefaction system **200** and for the sake of brevity similarly depicted or numbered components may not be further described. Liquefaction system **700** includes a primary cooling loop **702** and a sub-cooling loop **704**. Liquefaction system **700** also includes first and second heat exchanger zones **701**, **710**. Liquefaction system **700** includes the additional step of chilling, using an external cooling unit **770**, the compressed, cooled refrigerant **712** in the primary cooling loop **702** to a temperature below the ambient temperature, to thereby produce a compressed, chilled refrigerant **772**. The compressed, chilled refrigerant **772** is then directed to the second heat exchanger zone **710** as previously described. Using an external cooling unit to further cool the compressed, cool refrigerant may be used to improve the overall efficiency of the process and increase LNG production.

[0065] Figure 8 is a schematic diagram that illustrates a liquefaction system **800** according to another aspect of the disclosure. Liquefaction system **800** is similar to liquefaction system **300** and for the sake of brevity similarly depicted or numbered components may not be further described. Liquefaction system **800** includes a primary cooling loop **802** and a sub-cooling loop **804**. Liquefaction system **800** also includes first and second heat exchanger zones **801**, **810**. In liquefaction system **800**, the feed gas stream **806** is compressed in a compressor **860** to a pressure of at least 1,500 psia to form a compressed gas stream **861**. Using an external cooling unit **862**, the compressed gas stream **861** is cooled by indirect heat exchange with an ambient temperature air or water to form a compressed, cooled gas stream **863**. The compressed, cooled gas stream **863** is expanded in at least one work producing expander **874** to a pressure that is less than 2,000 psia but no greater than the pressure to which the gas stream was compressed, to thereby form a chilled gas stream **876**. The chilled gas stream **876** is then

directed to the first heat exchanger zone **801** where a primary cooling refrigerant and a sub-cooling refrigerant are used to liquefy the chilled gas stream as previously described.

[0066] The sub-cooling loop **804** is a closed refrigeration loop preferably charged with nitrogen as the sub-cooling refrigerant stream. Within the primary cooling loop **802**, an expanded, cooled refrigerant stream **805** is directed to the first heat exchanger zone **801** where it exchanges heat with the chilled gas stream **876** to form a first warm refrigerant stream **808**. The first warm refrigerant stream **808** is directed to the second heat exchanger zone **810** where it exchanges heat with a compressed, cooled refrigerant stream **825** to additionally cool the compressed, cooled refrigerant stream **825**, thereby forming a second warm refrigerant stream **809** and a compressed, additionally cooled refrigerant stream **813**. The first warm refrigerant stream **808** has a temperature that is cooler by at least 5 °F, or more preferably, cooler by at least 10 °F, or more preferably, cooler by at least 15 °F, than the highest fluid temperature within the first heat exchanger zone **801**. Using one or more compressors **818**, **820**, the second warm refrigerant stream **809** is compressed to a pressure greater than 1,500 psia, or more preferably, to a pressure of approximately 3,000 psia, to form a compressed refrigerant stream **822**. The compressed refrigerant stream **822** is then cooled against an ambient cooling medium (air or water) in an external cooling unit **824** to produce the compressed, cooled refrigerant stream **825**. After being directed through the second heat exchanger area **810**, the compressed, additionally cooled refrigerant stream is near isentropically expanded in an expander **826** to produce the expanded, cooled refrigerant **805**. The chilled gas stream **876** is liquefied and sub-cooled in the first heat exchanger zone to produce a sub-cooled gas stream **848**, which is further processed as previously disclosed.

[0067] Figure 9 is a schematic diagram that illustrates a liquefaction system **900** according to yet another aspect of the disclosure. Liquefaction system **900** contains similar structure and components with previously disclosed liquefaction systems and for the sake of brevity similarly depicted or numbered components may not be further described. Liquefaction system **900** includes a primary cooling loop **902** and a sub-cooling loop **904**. Liquefaction system **900** also includes first and second heat exchanger zones **901**, **910**. In liquefaction system **900**, the feed gas stream **906** is mixed with a refrigerant stream **907** to produce a second feed gas stream **906a**. Using a compressor **960**, the second feed gas stream **906a** is compressed to a pressure greater than 1,500 psia, or more preferably, to a pressure of approximately 3,000 psia, to form a compressed second gas stream **961**. Using an external cooling unit **962**, the compressed second gas stream **961** is then cooled against an ambient cooling medium (air or water) to produce a compressed, cooled second gas stream **963**. The compressed, cooled second gas

stream **963** is directed to the second heat exchanger zone **910** where it exchanges heat with a first warm refrigerant stream **908**, to produce a compressed, additionally cooled second gas stream **913** and a second warm refrigerant stream **909**.

[0068] The compressed, additionally cooled second gas stream **913** is expanded in at least one work producing expander **926** to a pressure that is less than 2,000 psia, but no greater than the pressure to which the second gas stream **906a** was compressed, to thereby form an expanded, cooled second gas stream **980**. The expanded, cooled second gas stream **980** is separated into a first expanded refrigerant stream **905** and a chilled feed gas stream **906b**. The first expanded refrigerant stream **905** may be near isentropically expanded using an expander **982** to form a second expanded refrigerant stream **905a**. The chilled feed gas stream **906b** is directed to the first heat exchanger zone **901** where a primary cooling refrigerant (i.e., the second expanded refrigerant stream **905a**) and a sub-cooling refrigerant (from the sub-cooling loop **904**) are used to liquefy the chilled gas stream **906b**. The sub-cooling loop **904** may be a closed refrigeration loop, preferably charged with nitrogen as the sub-cooling refrigerant. Within the primary cooling loop **902**, the second expanded refrigerant stream **905a** is directed to the first heat exchanger zone **901** where it exchanges heat with the chilled feed gas stream **906b** to form the first warm refrigerant stream **908**. The first warm refrigerant stream **908** may have a temperature that is cooler by at least 5 °F, or more preferably, cooler by at least 10 °F, or more preferably, cooler by at least 15 °F, than the highest fluid temperature within the first heat exchanger zone **901**. The second warm refrigerant stream **909** is compressed in one or more compressors **918** and then cooled with an ambient cooling medium in an external cooling device **924** to produce the refrigerant stream **907**. The chilled feed gas stream **906b** is liquefied and sub-cooled in the first heat exchanger zone **901** to produce a sub-cooled gas stream **948**, which is processed as previously described to form LNG.

[0069] Aspects of the disclosure illustrated in Figure 9 demonstrate that the primary refrigerant stream may comprise part of the feed gas stream, which in a preferred aspect may be primarily or nearly all methane. Indeed, it may be advantageous for the refrigerant in the primary cooling loop of all the disclosed aspects (i.e., Figures 2 through 9) be comprised of at least 85% methane, or at least 90% methane, or at least 95% methane, or greater than 95% methane. This is because methane may be readily available in various parts of the disclosed processes, and the use of methane may eliminate the need to transport refrigerants to remote LNG processing locations. As a non-limiting example, the refrigerant in the primary cooling loop **202** in Figure 2 may be taken through line **206a** of the feed gas stream **206** if the feed gas is high enough in methane to meet the compositions as described above. Alternatively, part or

all of a boil-off gas stream **259** from an LNG storage tank **257** may be used to supply refrigerant for the primary cooling loop **202**. Furthermore, if the feed gas stream is sufficiently low in nitrogen, part or all of the end flash gas stream **258** (which would then be low in nitrogen) may be used to supply refrigerant for the primary cooling loop **202**. Lastly, any combination of line
5 **206a**, boil-off gas stream **259**, and end flash gas stream **258** may be used to provide or even occasionally replenish the refrigerant in the primary cooling loop **202**.

[0070] Figure 10 is a flowchart of a method **1000** for liquefying a feed gas stream rich in methane using a system having first and second heat exchanger zones, where the method comprises the following steps: **1002**, providing the feed gas stream at a pressure less than 1,200
10 psia; **1004**, providing a compressed refrigerant stream with a pressure greater than or equal to 1,500 psia; **1006**, cooling the compressed refrigerant stream by indirect heat exchange with an ambient temperature air or water, to produce a compressed, cooled refrigerant stream; **1008**, directing the compressed, cooled refrigerant stream to the second heat exchanger zone to additionally cool the compressed, cooled refrigerant stream below ambient temperature to
15 produce a compressed, additionally cooled refrigerant stream; **1010**, expanding the compressed, additionally cooled refrigerant stream in at least one work producing expander, thereby producing an expanded, cooled refrigerant stream; **1012**, passing the expanded, cooled refrigerant stream through the first heat exchanger zone to form a first warm refrigerant stream, wherein the first warm refrigerant stream has a temperature that is cooler, by at least 5 °F, than
20 the highest fluid temperature within the first heat exchanger zone; **1014**, passing the feed gas stream through the first heat exchanger zone to cool at least part of the feed gas stream by indirect heat exchange with the expanded, cooled refrigerant stream, thereby forming a liquefied gas stream; **1016** directing at least a portion of the first warm refrigerant stream to the second heat exchanger zone to cool by indirect heat exchange the compressed, cooled
25 refrigerant stream, thereby forming a second warm refrigerant stream; and **1018**, compressing the second warm refrigerant stream to produce the compressed refrigerant stream.

[0071] Figure 11 is a flowchart of a method **1100** for liquefying a feed gas stream rich in methane, where the method comprises the following steps: **1102**, providing the feed gas stream at a pressure less than 1,200 psia; **1104**, compressing the feed gas stream to a pressure of at
30 least 1,500 psia to form a compressed gas stream; **1106**, cooling the compressed gas stream by indirect heat exchange with an ambient temperature air or water, to form a cooled, compressed gas stream; **1108**, expanding the cooled, compressed gas stream in at least one work producing expander to a pressure that is less than 2,000 psia and no greater than the pressure to which the gas stream was compressed, to thereby form a chilled gas stream; **1110**, providing a compressed

refrigerant stream with a pressure greater than or equal to 1,500 psia; **1112**, cooling the compressed refrigerant stream by indirect heat exchange with an ambient temperature air or water, to produce a compressed, cooled refrigerant stream; **1114**, directing the compressed, cooled refrigerant stream to a second heat exchanger zone, to additionally cool the compressed, cooled refrigerant stream below ambient temperature, to produce a compressed, additionally cooled refrigerant stream; **1116**, expanding the compressed, additionally cooled refrigerant stream in at least one work producing expander, thereby producing an expanded, cooled refrigerant stream; **1118**, passing the expanded, cooled refrigerant stream through a first heat exchanger zone to form a first warm refrigerant stream, whereby the first warm refrigerant stream has a temperature that is cooler, by at least 5 °F, than the highest fluid temperature within the first heat exchanger zone; **1120**, passing the chilled gas stream through the first heat exchanger zone to cool at least part of the chilled gas stream by indirect heat exchange with the expanded, cooled refrigerant, thereby forming a liquefied gas stream; **1122**, directing the first warm refrigerant stream to the second heat exchanger zone to cool by indirect heat exchange the compressed, cooled refrigerant stream, thereby forming a second warm refrigerant stream; and **1124**, compressing the second warm refrigerant stream to produce the compressed refrigerant stream.

[0072] Figure 12 is a method **1200** for liquefying a feed gas stream rich in methane, where the method comprises the following steps: **1202**, providing the feed gas stream at a pressure less than 1,200 psia; **1204**, providing a refrigerant stream at near the same pressure of the feed gas stream; **1206**, mixing the feed gas stream with the refrigerant stream to form a second gas stream; **1208**, compressing the second gas stream to a pressure of at least 1,500 psia to form a compressed second gas stream; **1210**, cooling the compressed second gas stream by indirect heat exchange with ambient temperature air or water, to form a compressed, cooled second gas stream; **1212**, directing the compressed, cooled second gas stream to a second heat exchanger zone, to additionally cool the compressed, cooled second gas stream below ambient temperature, thereby producing a compressed, additionally cooled second gas stream; **1214**, expanding the compressed, additionally cooled second gas stream in at least one work producing expander to a pressure that is less than 2,000 psia and no greater than the pressure to which the second gas stream was compressed, to thereby form an expanded, cooled second gas stream; **1216**, separating the expanded, cooled second gas stream into a first expanded refrigerant stream and a chilled gas stream; **1218**, expanding the first expanded refrigerant stream in at least one work producing expander, thereby producing a second expanded refrigerant stream; **1220**, passing the second expanded refrigerant stream through a first heat

exchanger zone to form a first warm refrigerant stream such that the first warm refrigerant stream has a temperature that is cooler, by at least 5 °F, than the highest fluid temperature within the first heat exchanger zone; **1222**, passing the chilled gas stream through the first heat exchanger zone to cool at least part of the chilled gas stream by indirect heat exchange with the
5 second expanded refrigerant stream, thereby forming a liquefied gas stream; **1224**, directing the first warm refrigerant stream to the second heat exchanger zone to cool by indirect heat exchange the compressed, cooled second gas stream, thereby forming a second warm refrigerant stream; and **1226**, compressing the second warm refrigerant stream to produce the refrigerant stream.

10 **[0073]** The steps depicted in Figures 10-12 are provided for illustrative purposes only and a particular step may not be required to perform the disclosed methodology. Moreover, Figures 10-12 may not illustrate all the steps that may be performed. The claims, and only the claims, define the disclosed system and methodology.

[0074] The aspects described herein have several advantages over known technologies.
15 For example, the described technology may greatly reduce the size and cost of systems that treat sour natural gas.

[0075] It should be understood that the numerous changes, modifications, and alternatives to the preceding disclosure can be made without departing from the scope of the disclosure. The preceding description, therefore, is not meant to limit the scope of the disclosure. Rather,
20 the scope of the disclosure is to be determined only by the appended claims and their equivalents. It is also contemplated that structures and features in the present examples can be altered, rearranged, substituted, deleted, duplicated, combined, or added to each other.

CLAIMS

1. A method for liquefying a feed gas stream rich in methane using a system having first and second heat exchanger zones, wherein the first heat exchanger zone comprises a first and
5 a second main heat exchanger, where the method comprises:

(a) providing the feed gas stream at a pressure less than 1,200 psia;
(b) providing a compressed refrigerant stream with a pressure greater than or equal
to 1,500 psia;

(c) cooling the compressed refrigerant stream by indirect heat exchange with an
10 ambient temperature air or water, to produce a compressed, cooled refrigerant stream;

(d) directing the compressed, cooled refrigerant stream to the second heat
exchanger zone to additionally cool the compressed, cooled refrigerant stream below ambient
temperature to produce a compressed, additionally cooled refrigerant stream;

(e) expanding the compressed, additionally cooled refrigerant stream in at least one
15 work producing expander, thereby producing an expanded, cooled refrigerant stream;

(f) passing the expanded, cooled refrigerant stream through a second main heat
exchanger within the first heat exchanger zone to form a first warm refrigerant stream, wherein
the first warm refrigerant stream has a temperature that is cooler, by at least 5 °F, than the
highest fluid temperature within the first heat exchanger zone;

(g) passing the feed gas stream through the first heat exchanger zone to cool at least
20 part of the feed gas stream by indirect heat exchange with the expanded, cooled refrigerant
stream, thereby forming a liquefied gas stream;

(h) directing at least a portion of the first warm refrigerant stream to the second heat
exchanger zone to cool by indirect heat exchange the compressed, cooled refrigerant stream,
25 thereby forming a second warm refrigerant stream;

(i) passing a portion of the first warm refrigerant stream remaining within the first
heat exchanger zone through the first main heat exchanger to further exchange heat within the
first heat exchanger zone, thereby forming a third warm refrigerant stream;

(j) combining the second warm refrigerant stream with the third warm refrigerant
30 stream to form a fourth warm refrigerant stream; and

(k) compressing the fourth warm refrigerant stream to produce the compressed
refrigerant stream.

2. The method of claim 1, wherein the first warm refrigerant stream has a temperature that
is cooler, by at least 10 °F, than the highest fluid temperature within the first heat exchanger

zone.

3. The method of claim 1 or 2, further comprising:

further cooling the liquefied gas stream within the first heat exchanger zone using a sub-cooling refrigeration cycle comprising a sub-cooling refrigerant, to thereby form a sub-cooled gas stream.

4. The method of claim 3, further comprising:

expanding the sub-cooled gas stream in a hydraulic turbine to a pressure greater than or equal to 50 psia and less than or equal to 450 psia, to produce an expanded, sub-cooled gas stream.

5. The method of claim 3, wherein the sub-cooling refrigeration cycle comprises a closed loop gas phase refrigeration cycle using nitrogen gas as a refrigerant.

6. The method of claim 4, wherein the sub-cooling refrigeration cycle comprises:

withdrawing a portion not to exceed 50% of the expanded, sub-cooled gas stream and reducing its pressure in a pressure reduction valve to a range of about 30 to 300 psia to produce one or more reduced pressure gas streams; and

passing the one or more reduced pressure gas streams through the first heat exchanger zone as the sub-cooling refrigerant.

7. The method of claim 6, wherein the one or more reduced pressure gas streams comprise two or more reduced pressure gas streams having different pressures from each other.

8. The method of claim 6, further comprising:

compressing the sub-cooling refrigerant stream exiting the first heat exchanger zone; and

cooling the sub-cooling refrigerant stream by indirect heat exchange with an ambient temperature air or water and then adding the sub-cooling refrigerant to the gas stream.

9. The method of claim 4, wherein at least a portion of the expanded, sub-cooled gas stream is further expanded and then directed to a separation tank from which liquid natural gas is withdrawn and remaining gaseous vapors are withdrawn as a flash gas stream.

10. The method of any one of claims 1-9, further comprising:

prior to directing the feed gas stream to the first heat exchanger zone, compressing the feed gas stream to a pressure no greater 1,600 psia, and then cooling it by indirect heat exchange with an ambient temperature air or water.

11. The method of any one of claims 1-10, wherein the feed gas stream is cooled to a temperature below an ambient temperature by indirect heat exchange within an external cooling unit prior to directing the feed gas stream to the first heat exchanger zone.

12. The method of any one of claims 1-11, wherein the compressed, cooled refrigerant stream is cooled to a temperature below the ambient temperature by indirect heat exchange within an external cooling unit prior to directing the compressed, cooled refrigerant stream to the second heat exchanger zone.

5 13. A system for liquefying a feed gas stream rich in methane, the system having first and second heat exchanger zones and comprising:

a feed gas stream at a pressure less than 1,200 psia;

a compressed refrigerant stream with a pressure greater than or equal to 1,500 psia;

10 a cooler configured to cool the compressed refrigerant stream by indirect heat exchange with an ambient temperature air or water, to produce a compressed, cooled refrigerant stream;

at least one heat exchanger within the second heat exchanger zone, the compressed, cooled refrigerant stream being directed to the at least one heat exchanger within the second heat exchanger zone to additionally cool the compressed, cooled refrigerant stream below ambient temperature and thereby produce a compressed, additionally cooled refrigerant stream;

15 at least one work producing expander arranged to expand the compressed, additionally cooled refrigerant stream, thereby producing an expanded, cooled refrigerant stream;

at least a first and a second main heat exchanger within the first heat exchanger zone, the expanded, cooled refrigerant stream being passed through the second main heat exchanger in the first heat exchanger zone to form a first warm refrigerant stream, wherein the first warm refrigerant stream has a temperature that is cooler, by at least 5 °F, than the highest fluid temperature within the first heat exchanger zone;

wherein the feed gas stream is passed through the first heat exchanger zone to cool at least part of the feed gas stream by indirect heat exchange with the expanded, cooled refrigerant stream, thereby forming a liquefied gas stream;

25 wherein a portion of the first warm refrigerant stream is directed to the second heat exchanger zone to cool by indirect heat exchange the compressed, cooled refrigerant stream, thereby forming a second warm refrigerant stream;

30 wherein a portion of the first warm refrigerant stream remaining within the first heat exchanger zone further exchanges heat within the first main heat exchanger within the first heat exchanger zone to produce a third warm refrigerant stream;

wherein the second warm refrigerant stream is combined with the third warm refrigerant stream forming a fourth warm refrigerant; and

a compressor configured to compress the fourth warm refrigerant stream to produce the compressed refrigerant stream.

14. The system of claim 13, wherein the first warm refrigerant stream has a temperature that is cooler, by at least 10 °F, than the highest fluid temperature within the first heat exchanger zone.

15. The system of any one of claims 13-14, further comprising:

5 a sub-cooling refrigeration cycle comprising a sub-cooling refrigerant stream configured to further cool the liquefied gas stream within the first heat exchanger zone, to thereby form a sub-cooled gas stream.

16. The system of claim 15, further comprising:

10 an additional expander configured to expand the sub-cooled gas stream to a pressure greater than or equal to 50 psia and less than or equal to 450 psia, to produce an expanded, sub-cooled gas stream, wherein the additional expander comprises a hydraulic turbine.

17. The system of claim 15, wherein the sub-cooling refrigeration cycle comprises a closed loop gas phase refrigeration cycle using nitrogen gas as the sub-cooling refrigerant.

18. The system of claim 16, further comprising:

15 a pressure reduction valve configured to reduce the pressure of a portion, not to exceed 50%, of the expanded, sub-cooled gas stream, to a range of about 30 to 300 psia, thereby producing one or more reduced pressure gas streams;

wherein the one or more reduced pressure gas streams is passed through the first heat exchanger zone as the sub-cooling refrigerant.

20 19. The system of claim 18, wherein the one or more reduced pressure gas streams comprise two or more reduced pressure gas streams having different pressures from each other.

20. The system of claim 15, further comprising:

a sub-cooling compressor configured to compress the sub-cooling refrigerant stream exiting the first heat exchanger zone; and

25 an external cooling unit configured to cool the sub-cooling refrigerant stream by indirect heat exchange with an ambient temperature air or water.

21. The system of claim 16, further comprising:

an additional expander configured to further expand at least a portion of the expanded, sub-cooled gas stream; and

30 a separation tank to which the expanded, sub-cooled gas stream is directed after passing through the additional expander.

22. The system of any one of claims 13-21, further comprising:

an additional compressor configured to compress, prior to directing the feed gas stream to the first heat exchanger zone, the feed gas stream to a pressure no greater 1,600 psia; and

an external cooling unit configured to cool the feed gas stream by indirect heat exchange with an ambient temperature air or water.

23. The system of any one of claims 13-22, further comprising:

5 a second external cooling unit configured to cool the feed gas stream to a temperature below an ambient temperature by indirect heat exchange within an external cooling unit prior to directing the feed gas stream to the first heat exchanger zone.

24. The system of any one of claims 13-23, further comprising:

10 a third external cooling unit configured to cool the compressed, cooled refrigerant stream to a temperature below the ambient temperature by indirect heat exchange therein prior to directing the compressed, cooled refrigerant stream to the second heat exchanger zone.

25. The system of claim 21, wherein refrigerant in the primary cooling loop is supplied from one or more of

the feed gas stream,

15 a flash gas stream, obtained by withdrawal of gaseous vapours from the separation tank, following direction of the expanded, sub-cooled gas stream to the separation tank; and

boil-off gas from liquid natural gas, obtained by withdrawal of liquid natural gas from the separation tank, following direction of the expanded, sub-cooled gas stream to the separation tank.

26. The system of any one of claims 13-25, wherein at least one of the first and second
20 main heat exchanger within the first heat exchanger zone comprises a brazed aluminum heat exchanger.

27. The system of any one of claims 13-26, wherein at least one of the first and second main heat exchanger within the second heat exchanger zone comprises a printed circuit heat exchanger.

25