

(10)

Description

This invention relates to scroll type fluid displacement apparatus.

Scroll type fluid displacement apparatus are well known in the prior art. For example, US—A—801 182 discloses a device including two scroll members each having a circular end plate and a spiroidal or involute spiral element. These scroll members are maintained angularly and radially offset so that both spiral elements interfit to make a plurality of line contacts between both spiral curved surfaces of the spiral elements, to thereby seal off and define at least one pair of fluid pockets. The relative orbital motion of the two scroll members shifts the line contact along the spiral curved surfaces and, therefore, the fluid pockets change in volume. The volume of the fluid pockets increases or decreases dependent on the direction of the orbital motion. Therefore, the scroll type apparatus is applicable to compress, expand or pump fluids.

EP—A—009 350 and FR—A—2 195 270 discloses scroll type fluid displacement apparatus wherein one of the scroll members has one or more holes formed in its circular end plate. Associated with the or each hole is a valve. The arrangement in FR—A—2 195 270 is such that the valve or each valve opens if the pressure of fluid in the fluid pockets becomes excessive. In EP—A—009 350 the or each valve opens if the rotational speed of the orbiting scroll member is too high.

Scroll type fluid displacement apparatus is suited for use as a refrigerant compressor for an automobile air conditioner. In such air conditioners, generally, thermal control in the passenger compartment or control of the air conditioner is accomplished by intermittent operation of the compressor unit through a magnetic clutch which is connected to the compressor and activated by a signal from the thermostat disposed in a passenger compartment. If the temperature in the passenger compartment has been cooled down to a desired temperature, the refrigerating capacity of the air conditioner for supplemental cooling because of further temperature changes in the passenger compartment, or, for keeping the passenger compartment at the desired temperature, need not be of such large capacity. However, prior air conditioners do not have capacity control means. Therefore, after the passenger compartment has been cooled to the desired temperature, the only manner for controlling the output of the compressor is by intermittent operation of the compressor through the magnetic clutch which follows small changes of temperature in the passenger compartment by means of the thermostat. Whereby, the large load to drive the compressor is intermittently applied to the engine shaft which is connected to the compressor through the magnetic clutch for accomplishing the rotary movement of the compressor drive.

It is a primary object of this invention to provide an improvement in a scroll type compressor unit

which has a displacement volume changing means, whereby the load acting on the power source is reduced under certain conditions of car air conditioner operation.

According to the present invention there is provided a scroll type fluid displacement apparatus including a housing having a fluid inlet port and a low pressure fluid chamber communicating with said fluid inlet port, a fixed scroll member fixedly disposed relative to said housing and having a first end plate means from which a first wrap means extends into the interior of said housing, an orbiting scroll member having a second end plate means from which a second wrap means extends, one of said first and second end plate means having at least one hole which is associated with valve means, said first and second wrap means interfitting at an angular and radial offset to make a plurality of line contacts to define at least one pair of sealed-off fluid pockets, said fluid pockets being connected to said low pressure fluid chamber through said at least one hole at a time when said valve means is open, a driving mechanism including a rotatable drive shaft connected to said orbiting scroll member to effect orbital motion of said orbiting scroll member, and a rotation preventing mechanism connected to said orbiting scroll member to prevent the rotation of said orbiting scroll member during the orbital motion of said orbiting scroll member, whereby said fluid pockets move and their volumes change upon orbital motion of said orbiting scroll member, characterised in that said one of said first and second end plate means is provided with a pair of holes for connecting said pair of sealed-off fluid pockets with said low pressure fluid chamber during movement of said pair of sealed-off fluid pockets, said pair of holes are located at such a position that they are simultaneously crossed by the other wrap, said pair of holes are associated with valve means, and said valve means are positively controlled, whereby when the valve means are open fluid in the pair of fluid pockets is permitted to flow back into said low pressure chamber during movement of said pair of fluid pockets, effective compression only starts when said pair of holes have been crossed by the other wrap and the pair of fluid pockets are sealed off, and the displacement volume is thus controlled by operation of said valve means.

One embodiment of this invention is a scroll-type fluid compressor unit which includes a pair of scroll members. Each scroll member is comprised of end plate means and a wrap means extends from a side surface of the end plate means. Both wrap means interfit at an angular offset to make a plurality of line contacts and define at least one pair of sealed off fluid pockets between both wrap means. One of the scroll members undergoes orbital motion by the rotation of a drive shaft while the rotation of the one scroll member is prevented. The fluid pockets shift along the direction of the orbital motion whereby the fluid pockets change their volume.

One of the end plate means has two holes formed through it. The holes are so arranged that the wrap means of the other scroll member simultaneously crosses over the holes. A control means is disposed at the holes for controlling the opening and closing of these holes. The displacement volume of each fluid pocket is controlled to start the compression at an intermediate state by the opening and closing of these holes through the control means.

In another aspect of this invention, a fluid passage means for connecting between these two holes is provided. An aperture is formed on the fluid passage means to connect a passageway of the fluid passage means with a suction chamber, i.e., a low pressure area. The control means is disposed at the opening of the aperture to control communication between the two holes and the low pressure area. Therefore, the capacity of the compressor changes by changing the compression starting volume of the fluid pockets through the opening of the aperture, which in turn, can be controlled by external environment conditions, such as the temperature in the passenger compartment.

The invention will now be described, by way of example, with reference to the accompanying drawings, in which:—

Figs. 1a—1d are schematic views illustrating the movement of interfitting spiral elements to compress a fluid;

Fig. 2 is a vertical sectional view of a compressor unit of the scroll type according to an embodiment of this invention;

Fig. 3 is an exploded perspective view of a fixed scroll member in one embodiment of this invention;

Fig. 4 is an exploded perspective view of a modification of the embodiment of Fig. 3;

Fig. 5 is a schematic view illustrating an air conditioning control circuit; and

Figs. 6a—6d are schematic views illustrating the operation of volume changing means.

Before the preferred embodiments of this invention are described, the principle of operation of a scroll type compressor unit is described with reference to Figs. 1a—1d. The scroll type compressor unit is operated by moving a sealed off fluid pocket from a low pressure region to a high pressure region.

Figs. 1a—1d may be considered end views of a compressor wherein the end plate is removed and only spiral elements are shown. Two spiral elements 1 and 2 are angularly and radially offset and interfit with one another. As shown in Fig. 1a, the orbiting spiral element 1 and fixed spiral element 2 make four line contacts as shown at four points A—D. A pair of fluid pockets 3a and 3b are defined between line contacts D—C and line contacts A—B, as shown by the dotted regions. The pair of fluid pockets 3a and 3b are defined not only by the walls of both spiral elements 1 and 2 but also by the end plates from which these spiral elements extend. When orbiting spiral element 1 is moved in relation to fixed spiral element 2 in

such a manner that center O' of orbiting spiral element 1 revolves around the center O of fixed spiral element 2 with a radius of O—O' and the rotation of orbiting spiral element 1 is prevented, the location of the pair of fluid pockets 3a and 3b shifts angularly and radially towards the center of the interfitted spiral elements with the volume of each fluid pocket 3a and 3b being gradually reduced, as shown in Figs. 1a—1d. Therefore, the fluid in each pocket 3a, 3b is compressed.

The pair of fluid pockets 3a and 3b are connected to one another while passing the stage from Fig. 1c to Fig. 1d, and after rotation through a 360° angle as shown in Fig. 1a, both fluid pockets 3a and 3b are disposed at the center portion and are completely connected to one another to form a single pocket. The volume of the connected single pocket is further reduced by further revolution of 90°, as shown in Figs. 1b and 1c. During the course of rotation outer spaces which open in the state shown in Fig. 1b change as shown in Figs. 1c, 1d and 1a to form new sealed off pockets in which fluid is newly enclosed as shown in Fig. 1a.

Accordingly, if circular end plates are disposed on, and sealed to, the axial faces of spiral elements 1 and 2, respectively, and if one of the end plates is provided with a discharge port 4 at the center thereof as shown in the figures, fluid is taken into the fluid pockets at the radial outer portions and is discharged from the discharge port 4 after compression.

Referring to Fig. 2 a refrigerant compressor unit of the embodiment shown includes a compressor housing 10 comprising a cylindrical housing 11, a front end plate 12 disposed to a front end portion of cylindrical housing 11 and a rear end plate 13 disposed to a rear end portion of cylindrical housing 11. An opening is formed in front end plate 12 and a drive shaft 15 is rotatably supported by a bearing means, such as a ball bearing 14 disposed in the opening. Front end plate 12 has an annular sleeve portion 16 projecting from the front end surface thereof and surrounding drive shaft 15 to define a shaft seal cavity 17. A shaft seal assembly 18 is assembled on drive shaft 15 within shaft seal cavity 17. A pulley 19 is rotatably supported by a bearing means 20 which is disposed on the outer surface of sleeve portion 16. An electromagnetic annular coil 21 is fixed to the outer surface of sleeve portion 16 by a support plate 211 and is received in an annular cavity of pulley 19. An armature plate 22 is elastically supported on the outer end of drive shaft 15 which extends from sleeve portion 16. A magnetic clutch comprising pulley 19, magnetic coil 21 and armature plate 22 is thereby formed. Thus, drive shaft 15 is driven by an external drive power source, for example, an engine of a vehicle through a rotational force transmitting means such as the above mentioned magnetic clutch.

Front end plate 12 is fixed to the front end portion of cylindrical housing 11 by bolts (not shown), to thereby cover an opening of cylindrical

(12)

housing. A seal is formed about the opening by a seal member 23 disposed between facing surfaces of the front end plate 12 and the cylindrical housing 11. Rear end plate 13 is provided with an annular projection 131 to form a discharge passageway 24. The projection 131 extends inwardly whereby an inner chamber of rear end plate 13 is divided into a suction chamber 25 and discharge passageway 24 by projection 131. Rear end plate 13 has a fluid inlet port and a fluid outlet port, which respectively are connected to the suction chamber 25 and discharge passageway 24. Rear end plate 13 together with a circular end plate 261 of fixed scroll member 26 is fixed to rear end portion of cylindrical housing 11 by bolts (not shown). Circular end plate 261 of fixed scroll member 26 is disposed between cylindrical housing 11 and rear end plate 13 and is secured to cylindrical housing 11. The opening of the rear end portion of cylindrical housing 11 is thereby covered by circular end plate 261. Therefore, an inner chamber 111 is sealed to form a low pressure space in cylindrical housing 11.

Fixed scroll member 26 includes circular end plate 261 and a wrap means or spiral element 262 affixed to or extending from one side surface of circular plate 261. Spiral element 262 is disposed in inner chamber 111 of cylindrical housing 11. A hole or suction port (not shown) is formed through circular plate 261 which communicates between suction chamber 25 and inner chamber 111 of cylindrical housing 11. A hole or discharge port 263 is formed through circular plate 261 at a position near to the center of spiral element 262 and is connected to discharge passageway 24.

An orbiting scroll member 27 is also disposed in inner chamber 111. Orbiting scroll member 27 also comprises a circular end plate 271 and a wrap means or spiral element 272 affixed to or extending from one side surface of circular plate 271. The spiral elements 262, 272 interfit at an angular offset of 180° and a predetermined radial offset to make a plurality of line contacts and define at least one pair of sealed off fluid pockets between both spiral elements 262, 272. Orbiting scroll member 27 is connected to a driving mechanism and a rotation preventing/thrust bearing mechanism. These two mechanisms effect orbital motion by rotation of drive shaft 15 to thereby compress fluid in the fluid pockets as the fluid passes through the compressor unit.

Driving mechanism of orbiting scroll member 27 includes drive shaft 15 which is rotatably supported by front end plate 12 through ball bearing 14. Drive shaft 15 is formed with a disk portion 151 at its inner end portion. Disk portion 151 is rotatably supported by a bearing means, such as a ball bearing 28, which is disposed in a front end opening of cylindrical housing 11. A crank pin or drive pin projects axially from an end surface of disk portion 151 and is radially offset from the center of drive shaft 15. Circular plate 271 of orbiting scroll member 27 is provided with a tubular boss 273 projecting axially from an end

surface, which is opposite the side thereof from which spiral element 272 extends. A discoid or short axial bushing 29 is fitted into boss 273, and rotatably supported therein by a bearing means, such as a needle bearing 30. An eccentric hole (not shown) is formed in bushing 29 radially offset from the center of bushing 29. The drive pin is fitted into the eccentrically disposed hole. Bushing 29 is therefore driven by the revolution of the drive pin and permitted to rotate by needle bearing 30. Orbiting scroll member 27 is thereby allowed to undergo the orbital motion by the rotation of drive shaft 15 while the rotation of orbiting scroll member 27 is prevented by the rotation preventing mechanism 31.

Rotation preventing mechanism 31 is disposed around boss 273 and comprises an Oldham plate 311 and an Oldham ring 312. Oldham plate 311 is secured to a stepped portion of the inner surface of cylindrical housing 11 by pins 32. Oldham ring 312 is disposed in a hollow space between Oldham plate 311 and circular plate 271 of orbiting scroll member 27. Oldham plate 311 and Oldham ring 312 are connected by keys and keyways whereby Oldham ring 312 is slidable in a first radial direction. Oldham ring 312 and circular plate 271 are also connected by keys and keyways whereby orbiting scroll member 27 is slidable in a second radial direction which is perpendicular to the first radial direction.

Accordingly, orbiting scroll member 27 is slidable in one radial direction with Oldham ring 312, and is slidable in another radial direction independently. The second radial direction is perpendicular to the first radial direction. Therefore, orbiting scroll member 27 is prevented from rotating but is permitted to move in two radial directions perpendicular to one another.

Oldham ring 312 is provided with a plurality of holes or pockets, and a bearing means, such as balls 33, each having a diameter which is longer than the thickness of Oldham ring 312. The balls 33 are retained in pockets of Oldham ring 312. Balls 33 contact and roll on the surface of Oldham plate 311 and circular plate 271. Therefore, the thrust load from orbiting scroll member 27 is supported on Oldham plate 311 through balls 33.

When drive shaft 15 is rotated by the external drive power source through the magnetic clutch, the drive pin is eccentrically moved by the rotation of drive shaft 15. Eccentric bushing 29 is driven eccentrically because it follows the motion of the drive pin. Therefore, orbiting scroll member 27 is allowed to undergo the orbital motion, while the rotation of orbiting scroll member 27 is prevented by rotation preventing mechanism 31. The fluid, or refrigerant gas, introduced into suction chamber 25 is taken into a pair of fluid pockets from outer end of spiral elements 262, 272, and, as orbiting scroll member 27 orbits, fluid in the fluid pocket is moved to the center of the spiral element with a consequent reduction of volume. The compressed fluid is discharged into discharge passageway 24 from the fluid pocket of spiral element center through discharge port 263,

and therefrom discharged through the outlet port to an external fluid circuit, for example, a cooling circuit.

Two holes 34a and 34b are formed in circular plate 261 of fixed scroll member 26, the holes being so arranged that an axial end surface of spiral element 272 of orbiting scroll member 27 simultaneously crosses over the two holes. A control means 35a is disposed at one end opening of each hole 34a, 34b to control the opening and closing of each hole, as shown in Fig. 3.

A refrigerant circuit for an automobile air conditioner is illustrated in Fig. 5. The circuit includes a condenser 36, one end portion of which is connected to the fluid outlet port of the compressor 10, a receiver/dryer 37, an expansion valve 38 and an evaporator 39, one end portion of which is connected to the fluid inlet port of the compressor 10. The magnetic clutch MC is connected to a battery 42 which is controlled through a thermostat 43 disposed in the passenger compartment of the automobile.

Valve means 35 comprises a means for controlling the passage of fluids through the holes 34. Valve means 35 includes a magnetic solenoid valve means 35a and a detecting means 35b. In one embodiment of this invention, as shown in Fig. 5, detecting means 35b is disposed on the outlet portion of evaporator 39 for detecting outlet pressure of evaporator 39. Therefore, magnetic solenoid valve means 35a is controlled by the pressure difference of evaporator 39 through detecting means 35b. Because the pressure of the evaporator outlet depends on the air temperature which passes through the evaporator for heat exchange, the outlet pressure is dependent on the air temperature. Usually, the outlet pressure of the evaporator lowers as the temperature in the evaporator lowers. Such a condition generally occurs when the temperature in the passenger compartment has been lowered to a desired temperature level and only a small or gradual elevation of the temperature occurs, because the temperature of the air passing through the evaporator is relatively low. To hold the car interior temperature at the desired level, operation of the compressor at its full capacity is not required and also it is not desirable because such operation places a high load on the engine. The opening of holes 34a, 34b allow the compression capacity of the compressor to be lowered to thereby lower the load on the engine under such a condition.

Referring to Fig. 1 and Fig. 6, the operation of a displacement volume changing means for fluid pockets will be described.

When the terminal end portion of both spiral elements 262, 272 are fitted against opposite sidewalls of the other spiral element by the orbital motion of orbiting scroll member 26, a pair of fluid pockets 3a, 3b are sealed off and formed at the same time, as shown in Fig. 1a. If the two holes 34a, 34b are closed by magnetic valve means 35a, the compression is normally

operated, as described above referring to Figs. 1a—1d.

When detecting means 35b detects a pressure in the fluid circuit below the desired pressure, magnetic valve means 35a is operated to open holes 34a, 34b. Therefore, the fluid which has been taken into the sealed off fluid pocket is leaked from the sealed off fluid pockets 3a, 3b to suction chamber 25 of rear end plate 13, as shown in Fig. 6a. This leaking state continues until the axial end surface of spiral element 271 of orbiting scroll member 27 passes over the holes 34a, 34b, as shown in Fig. 6b. Whereby, the actual compressing stroke of fluid pockets 3a, 3b starts after spiral element 272 of orbiting scroll member 27 crosses over two holes 34a, 34b. The volume of the fluid pockets 3a, 3b at the time when the pockets are sealed from the suction chamber 25 and compression actually begins is thereby reduced. In this manner, the capacity of the compressor is reduced.

A theoretical displacement volume V , of scroll type compressor is given by:

$$V = H \text{ RoP} (2\phi - 3\pi)$$

where H is height of spiral element, P is pitch of spiral element, ϕ is final involute angle of spiral element, i.e., the complete angular extent of the spiral element from its innermost tip to its outermost tip, and Ro is given by $\text{Ro} = \text{Rg} \cdot \pi - t$, where Rg is a radius of the generating circle of the involute spiral, and t is thickness of spiral element.

Thus, for example, when the outermost involute angle ϕ_1 is 6π and the involute angle where the compression starts when valves are open ϕ_2 is 4π the displacement volume V_2 is reduced by 44.4% from the maximum displacement volume V_1 .

$$\frac{V_2}{V_1} = \frac{2\phi_2 - 3\pi}{2\phi_1 - 3\pi} = \frac{5\pi}{9\pi} = 0.556$$

According to this construction, the capacity of the compressor unit can be easily changed because of changes in the external environment, i.e., changes in the passenger compartment temperature, and load on engine can thereby be reduced. This occurs because the fluid in the sealed off fluid pocket is leaked through the holes by operation of the magnetic valve means which is controlled by the changes in the external environment. For example, when the temperature of the fluid passing through evaporator 39 is low due to cool air passing through the evaporator, the pressure of the fluid at the outlet of the evaporator will be lowered and this pressure reduction will be sensed by the detecting means 35b.

Fig. 4 illustrates a modified construction of a mechanism for changing the volume in the fluid pockets. In this construction, a fluid passage means 41 connects the two holes 34a, 34b. Fluid

passage means 41 comprises a passage plate 411 within which is formed a fluid passageway 412 at one of its side surfaces. An aperture 413 is formed on the plate 411 for connecting fluid passageway 412 with suction chamber 25 of rear end plate 13. A valve means, such as a single magnetic solenoid valve means 35a is disposed on the aperture 413 for controlling the opening and closing of aperture 413. Therefore, a single valve means can modulate the displacement volume compared to the two valve means required for the first embodiment. Alternatively, the fluid passageway may be formed in circular plate 261 of fixed scroll member 26. Such a fluid passageway is illustrated by dotted lines in Fig. 3. It will be understood that one of holes 34a and 34b is closed at the end shown opening into the rear surface of the circular plate 261 whilst the corresponding valve is omitted.

Our co-pending EP-A-43702 discloses a scroll type fluid displacement apparatus in which two holes are formed in an end plate of one of the scroll members and a tubular passage connects the holes together. The arrangement is such that two fluid pockets are connected together via the holes and the passage during movement of the orbiting scroll member through a certain orbiting angle. This serves to minimize differences in pressure between the fluid pockets.

Claims

1. A scroll type fluid displacement apparatus including a housing (10) having a fluid inlet port and a low pressure fluid chamber (25) communicating with said fluid inlet port, a fixed scroll member (26) fixedly disposed relative to said housing (10) and having a first end plate means (261) from which a first wrap means extends into the interior of said housing (10), an orbiting scroll member (27) having a second end plate means (271) from which a second wrap means (272) extends, one of said first and second end plate means having at least one hole which is associated with valve means, said first and second wrap means (262, 272) interfitting at an angular and radial offset to make a plurality of line contacts to define at least one pair of sealed-off fluid pockets, said fluid pocket being connected to said low pressure fluid chamber (25) through said at least one hole at a time when said valve means is open, a driving mechanism including a rotatable drive shaft (15) connected to said orbiting scroll member (27) to effect orbital motion of said orbiting scroll member (27), and a rotation preventing mechanism (31) connected to said orbiting scroll member (27) to prevent the rotation of said orbiting scroll member (27) during the orbital motion of said orbiting scroll member (27), whereby said fluid pockets move and their volumes change upon orbital motion of said orbiting scroll member (27), characterised in that said one of said first and second end plate means (261, 271) is provided with a pair of holes (34) for connecting said pair of sealed-off fluid pockets

with said low pressure fluid chamber (25) during movement of said pair of sealed-off fluid pockets, said pair of holes (34) are located at such a position that they are simultaneously crossed by the other wrap, said pair of holes (34) are associated with valve means (35), and said valve means (35) are positively controlled, whereby when the valve means (35) are open fluid in the pair of fluid pockets is permitted to flow back into said low pressure chamber (25) during movement of said pair of fluid pockets, effective compression only starts when said pair of holes (34) have been crossed by the other wrap and the pair of fluid pockets are sealed off, and the displacement volume is thus controlled by operation of said valve means (35).

2. An apparatus as claimed in claim 1, characterised in that said holes (34) are formed in said first end plate means (261) of said fixed scroll member (26).

3. An apparatus as claimed in claim 1, characterised in that fluid passage means (41) is disposed between said holes (34) for connecting together the pair of fluid pockets, said fluid passage means (41) is formed with an aperture (413) for communication with said low pressure fluid chamber (25), and said valve means (35) is disposed at said aperture (413) for controlling the opening and closing of said aperture (413).

4. An apparatus as claimed in claim 3, characterised in that said fluid passage means (41) comprises a passage plate (411) within which is formed a fluid passageway (412).

5. An apparatus as claimed in claim 3, characterised in that said fluid passage means (41) comprises a fluid passageway (412) which is formed in said end plate means (261) of said fixed scroll member (26).

6. An apparatus as claimed in any one of the preceding claims, characterised in that said valve means (35) comprises magnetic solenoid valve means.

Patentansprüche

1. Spiralfliuidverdrängervorrichtung mit einem Gehäuse (10), das eine erste Fluideinlaßöffnung und eine Niederdruckfluidkammer (25), die in Verbindung mit der Fluideinlaßöffnung steht, aufweist, einem befestigten Spiralteil (26), das relativ zu dem Gehäuse (10) feststehend angeordnet ist, und eine erste Endplatteneinrichtung (261), aus der ein erstes gewundenes Teil in das Innere des Gehäuses (10) herausragt, aufweist, einem umlaufenden Spiralteil (27), das eine zweite Endplatteneinrichtung (271), aus der ein zweites gewundenes Teil (272) herausragt, besitzt, wobei die eine der ersten und zweiten Endplatteneinrichtungen mindestens eine Bohrung, die mit einer Ventileinrichtung verbunden ist, aufweist, das erste und zweite gewundene Teil (262, 272) in einem winkelmäßigen und radialen Abstand zueinander eingepaßt sind, um eine Mehrzahl von Linienberührungsstellen zu besitzen, die mindestens ein Paar von

passage means 41 comprises a passage plate 411 within which is formed a fluid passageway 412 at one of its side surfaces. An aperture 413 is formed on the plate 411 for connecting fluid passageway 412 with suction chamber 25 of rear end plate 13. A valve means, such as a single magnetic solenoid valve means 35a is disposed on the aperture 413 for controlling the opening and closing of aperture 413. Therefore, a single valve means can modulate the displacement volume compared to the two valve means required for the first embodiment. Alternatively, the fluid passageway may be formed in circular plate 261 of fixed scroll member 26. Such a fluid passageway is illustrated by dotted lines in Fig. 3. It will be understood that one of holes 34a and 34b is closed at the end shown opening into the rear surface of the circular plate 261 whilst the corresponding valve is omitted.

Our co-pending EP-A-43702 discloses a scroll type fluid displacement apparatus in which two holes are formed in an end plate of one of the scroll members and a tubular passage connects the holes together. The arrangement is such that two fluid pockets are connected together via the holes and the passage during movement of the orbiting scroll member through a certain orbiting angle. This serves to minimize differences in pressure between the fluid pockets.

Claims

1. A scroll type fluid displacement apparatus including a housing (10) having a fluid inlet port and a low pressure fluid chamber (25) communicating with said fluid inlet port, a fixed scroll member (26) fixedly disposed relative to said housing (10) and having a first end plate means (261) from which a first wrap means extends into the interior of said housing (10), an orbiting scroll member (27) having a second end plate means (271) from which a second wrap means (272) extends, one of said first and second end plate means having at least one hole which is associated with valve means, said first and second wrap means (262, 272) interfitting at an angular and radial offset to make a plurality of line contacts to define at least one pair of sealed-off fluid pockets, said fluid pocket being connected to said low pressure fluid chamber (25) through said at least one hole at a time when said valve means is open, a driving mechanism including a rotatable drive shaft (15) connected to said orbiting scroll member (27) to effect orbital motion of said orbiting scroll member (27), and a rotation preventing mechanism (31) connected to said orbiting scroll member (27) to prevent the rotation of said orbiting scroll member (27) during the orbital motion of said orbiting scroll member (27), whereby said fluid pockets move and their volumes change upon orbital motion of said orbiting scroll member (27), characterised in that said one of said first and second end plate means (261, 271) is provided with a pair of holes (34) for connecting said pair of sealed-off fluid pockets

with said low pressure fluid chamber (25) during movement of said pair of sealed-off fluid pockets, said pair of holes (34) are located at such a position that they are simultaneously crossed by the other wrap, said pair of holes (34) are associated with valve means (35), and said valve means (35) are positively controlled, whereby when the valve means (35) are open fluid in the pair of fluid pockets is permitted to flow back into said low pressure chamber (25) during movement of said pair of fluid pockets, effective compression only starts when said pair of holes (34) have been crossed by the other wrap and the pair of fluid pockets are sealed off, and the displacement volume is thus controlled by operation of said valve means (35).

2. An apparatus as claimed in claim 1, characterised in that said holes (34) are formed in said first end plate means (261) of said fixed scroll member (26).

3. An apparatus as claimed in claim 1, characterised in that fluid passage means (41) is disposed between said holes (34) for connecting together the pair of fluid pockets, said fluid passage means (41) is formed with an aperture (413) for communication with said low pressure fluid chamber (25), and said valve means (35) is disposed at said aperture (413) for controlling the opening and closing of said aperture (413).

4. An apparatus as claimed in claim 3, characterised in that said fluid passage means (41) comprises a passage plate (411) within which is formed a fluid passageway (412).

5. An apparatus as claimed in claim 3, characterised in that said fluid passage means (41) comprises a fluid passageway (412) which is formed in said end plate means (261) of said fixed scroll member (26).

6. An apparatus as claimed in any one of the preceding claims, characterised in that said valve means (35) comprises magnetic solenoid valve means.

Patentansprüche

1. Spiralfliuidverdrängervorrichtung mit einem Gehäuse (10), das eine erste Fluideinlaßöffnung und eine Niederdruckfluidkammer (25), die in Verbindung mit der Fluideinlaßöffnung steht, aufweist, einem befestigten Spiralteil (26), das relativ zu dem Gehäuse (10) feststehend angeordnet ist, und eine erste Endplatteneinrichtung (261), aus der ein erstes gewundenes Teil in das Innere des Gehäuses (10) herausragt, aufweist, einem umlaufenden Spiralteil (27), das eine zweite Endplatteneinrichtung (271), aus der ein zweites gewundenes Teil (272) herausragt, besitzt, wobei die eine der ersten und zweiten Endplatteneinrichtungen mindestens eine Bohrung, die mit einer Ventileinrichtung verbunden ist, aufweist, das erste und zweite gewundene Teil (262, 272) in einem winkelmäßigen und radialen Abstand zueinander eingepaßt sind, um eine Mehrzahl von Linienberührungsstellen zu besitzen, die mindestens ein Paar von



gegeneinander abgedichteten Fluidtaschen bilden, und die Fluidtasche mit der Niederdruckfluidkammer (25) über mindestens eine Bohrung zu einem Zeitpunkt, wenn die Ventileinrichtung geöffnet ist, verbunden ist, einer Antriebseinrichtung, die eine drehbar Antriebswelle (15), die mit dem umlaufenden Spiralteil (27) verbunden ist, um eine umlaufende Bewegung des umlaufenden Spiralteils (27) zu bewirken, und eine Drehverhinderungseinrichtung (31), die mit dem umlaufenden Spiralteil (27) verbunden ist, um die Drehung des umlaufenden Spiralteils (27) während der umlaufenden Bewegung des umlaufenden Spiralteils (27) zu verhindern, aufweist, wodurch sich die Fluidtaschen bewegen und sich deren Volumen durch die umlaufende Bewegung des umlaufenden Spiralteils (27) ändert, dadurch gekennzeichnet, daß die eine der ersten und zweiten Endplatteneinrichtungen (261, 271) mit einem Paar Bohrungen (34) zur Verbindung des Paares der gegeneinander abgedichteten Fluidtaschen mit der Niederdruckfluidkammer (25) während der Bewegung des Paares der gegeneinander abgedichteten Fluidtaschen versehen ist, das Paar Bohrungen (34) in einer solchen Position angeordnet ist, daß diese gleichzeitig von dem anderen gewundenen Teil überkreuzt werden, das Paar Bohrungen (34) mit der Ventileinrichtung (35) in Verbindung steht, und die Ventileinrichtung (35) gesteuert wird, wodurch während der Bewegung des Paares der Fluidtaschen bei geöffneter Ventileinrichtung (35) das Fluid in dem Paar der Fluidtaschen zurück in die Niederdruckkammer (25) fließt, eine wirkungsvolle Verdichtung nur dann beginnt, wenn das Paar der Bohrungen (34) von dem anderen gewundenen Teil überquert wurde und damit das Paar der Fluidtaschen abgedichtet ist, und das Verdrängervolumen auf diese Weise durch den Betrieb der Ventileinrichtung (35) gesteuert wird.

2. Vorrichtung nach Anspruch 1, dadurch gekennzeichnet, daß die Bohrungen (34) in der ersten Endplatteneinrichtung (261) des feststehenden Spiralteils (26) gebildet sind.

3. Vorrichtung nach Anspruch 1, dadurch gekennzeichnet, daß eine Fluiddurchlaßeinrichtung (41) zwischen den Bohrungen (34) angeordnet ist, um das Paar der Fluidtaschen miteinander zu verbinden, die Fluiddurchlaßeinrichtung (41) mit einer Öffnung (413) zur Verbindung mit der Niederdruckfluidkammer (25) gebildet ist, und die Ventileinrichtung (35) an der Öffnung (413) zur Steuerung des Öffnens und Schließens der Öffnung (413) angeordnet ist.

4. Vorrichtung nach Anspruch 3, dadurch gekennzeichnet, daß die Fluiddurchlaßeinrichtung (41) eine Durchlaßplatte (411), in der ein Fluiddurchlaß (412) gebildet ist, aufweist.

5. Vorrichtung nach Anspruch 3, dadurch gekennzeichnet, daß die Fluiddurchlaßeinrichtung (41) einen Fluiddurchlaß (412), der in der Endplatteneinrichtung (261) des feststehenden Spiralteils (26) gebildet ist, aufweist.

6. Vorrichtung nach einem der Ansprüche 1 bis

5, dadurch gekennzeichnet, daß die Ventileinrichtung (35) eine Magnetspulenventileinrichtung aufweist.

5 Revendications

1. Appareil de déplacement de fluide, du type à volutes imbriquées, comprenant un carter (10) muni d'un orifice d'entrée de fluide et d'une chambre de fluide basse pression (25) communiquant avec cet orifice d'entrée de fluide, un élément de volute fixe 26 monté de façon fixe par rapport au carter (10) et comportant des premiers moyens de plaque d'extrémité (261) d'où partent des premiers moyens d'enroulement pénétrant à l'intérieur du carter (10), un élément de volute orbital (27) comportant des seconds moyens de plaque d'extrémité (271) d'où partent des seconds moyens d'enroulement (272), l'une des premiers et seconds moyens de plaque d'extrémité comportant au moins un trou associé à des moyens de soupape, les premiers et seconds moyens d'enroulement (262, 272) s'emboîtant avec un décalage angulaire et radial pour former un certain nombre de lignes de contact permettant de définir au moins une pair de poches à fluide étanches, ces poches à fluide étant reliées à la chambre de fluide basse pression (25) par ce trou au moins unique, au moment où les moyens de soupape sont ouverts, un mécanisme d'entraînement comprenant un arbre d'entraînement en rotation (15) relié à l'élément de volute orbital (27) pour produire la mouvement orbital de cet élément de volute orbital (27), et un mécanisme antirotation (31) relié à l'élément de volute orbital (27) pour empêcher la rotation de cet élément de volute orbital (27) pendant le mouvement orbital de cet élément de volute orbital (27), ce qui permet de déplacer les poches à fluide et de faire varier leur volume par suite du mouvement orbital de l'élément de volute orbital (27) appareil caractérisé en ce que celui ci-dessus des premiers et seconds moyen de plaque d'extrémité (261, 271) est muni d'une paire de trous (34) destinés à relier la paire de poches à fluide étanche à la chambre de fluide basse pression (25) pendant le mouvement de cette pair de poches à fluide étanches, en ce que les trous de la paire de trous (34) sont placés dans une autre position telle qu'ils soient simultanément coupés par l'autre enroulement, en ce que cette paire de trous (34) est associée à des moyens de soupape (35), et en ce que ces moyens de soupape (35) sont efficacement commandés, de sorte que lorsque les moyens de soupape (35) sont ouverts, le fluide contenu dans la paire de poches à fluide peut revenir en arrière dans le chambre basse pression (25) pendant le mouvement de la paire de poches à fluide, la compression effective ne commençant que lorsque les trous de la paire de trous (34) ont été coupés par l'autre enroulement, et lorsque l'étanchéité des poches à fluide est assurée, le volume de déplacement étant ainsi commandé



par le fonctionnement des moyens de soupape (35).

2. Appareil selon la revendication 1, caractérisé en ce que les trous (34) sont formés dans les premiers moyens de plaque d'extrémité (261) de l'élément de volute fixe (26).

3. Appareil selon la revendication 1, caractérisé en ce que des moyens de passage de fluide (41) sont disposés entre les trous (34) pour relier ensemble la paire de poches à fluide, ces moyens de passage de fluide (41) étant munis d'une ouverture (413) destinée à assurer la communication avec la chambre de fluide basse pression (25), et en ce que les moyens de soupape (35) sont disposés à l'endroit de cette ouverture (413) pour commander l'ouverture et la fermeture de cette ouverture (413).

4. Appareil selon la revendication 3, caractérisé en ce que les moyens de passage de fluide (41) sont constitués par une plaque de passage (411) dans laquelle est formé un passage de fluide (412).

5. Appareil selon la revendication 3, caractérisé en ce que les moyens de passage de fluide (41) sont constitués par un passage de fluide (412) formé dans les moyens de plaque d'extrémité (261) de l'élément de volute fixe (26).

6. Appareil selon l'une quelconque des revendications précédentes, caractérisé en ce que les moyens de soupape (35) sont constitués par des moyens de soupape magnétiques à solénoïde.

20

25

30

35

40

45

50

55

60

65

8



* C L M S *