7. Composition according to any of the preceding claims, comprising at least one additive selected from the group of fragrants, thickeners, gelling agents and free flowing agents.

8. Composition according to any of the preceding claims, wherein the composition is an aerosol.

9. Composition according to claim 8, wherein the aerosol comprises at least 50 wt. % gas, preferably 70 to 99 wt. %, in particular 75 to 95 wt. %, based on total weight of the aerosol.

10. Aerosol container, comprising an aerosol according to claim 8 or 9.

11. Container provided with a roller applicator, wherein the container comprises a composition according to any of the claims 1-7.

12. Method for preparing a composition according to any of the claims 1-7, comprising combining a burnt aluminium salt with the carrier liquid.

13. Method according to claim 12, wherein the burnt aluminium salt is obtained by heating hydrated aluminium salt to a temperature above 60 °C, in particular above 150 °C, preferably in the range of 200-300 °C.

7. Composition according to any of the preceding claims, comprising at least one additive selected from the group of fragrants, thickeners, gelling agents and free flowing agents.

8. Composition according to any of the preceding claims, wherein the composition is an aerosol.

9. Composition according to claim 8, wherein the aerosol comprises at least 50 wt. % gas, preferably 70 to 99 wt. %, in particular 75 to 95 wt. %, based on total weight of the aerosol.

10. Aerosol container, comprising an aerosol according to claim 8 or 9.

11. Container provided with a roller applicator, wherein the container comprises a composition according to any of the claims 1-7.

12. Method for preparing a composition according to any of the claims 1-7, comprising combining a burnt aluminium sulphate salt with the carrier liquid.

13. Method according to claim 12, wherein the burnt aluminium sulphate salt is obtained by heating hydrated aluminium salt to a temperature above 60 °C, in particular above 150 °C, preferably in the range of 200-300 °C.