

Description

This invention relates to a light source according to the preamble of Claim 1. Such a light source is known from US—A—3 058 468. The invention may be applied to the lighting of a stage or theatre.

In conventional lighting systems, individual light sources are typically hung from trusses or fixed structural members mounted in front of the stage, at the sides of the stage or over the stage. The light sources are adjusted to direct the light beam to a desired location on the stage and are then secured in that position by tightening bolts or other fasteners. A large sealed beam lamp of 1000 to 1500 watts run from a 110 volt AC line is typically employed to create the light. In addition to generating visible light, such lamps, generally noted as par lamps, generate a significant amount of infrared heat.

In a typical stage lighting plan, the light sources are employed in either of two fashions. Certain light sources may be used as a wash or general stage illumination. The remainder of the light sources are used as spots for highlighting specific positions on the stage, such as an actor's face.

The light beams emanating from each light source may be coloured by the use of a coloured celluloid gel. The gel is positioned within a frame which is slid into a receiver positioned at the end of the light source so that the beam passes through the coloured gel. The gel functions to absorb the incident light other than the colour desired. The absorbed light is transformed into heat which warps and discolours the gel, so the gel needs replacement, as often as once every show.

It is known from US Patent Specification No: 3883243 to provide a photographic enlarger having three dichroic filters for producing light of a predetermined colour and density. However, the filters are mounted with their major surfaces perpendicular to an incident light beam, i.e. perpendicular to an optical axis passing through a lamp mounted in an elliptical reflector. A mechanism is provided for rotating any one of the filters into the path of the incident light beam, e.g. so that the filter either wholly or partly intercepts the incident light beam. Such an arrangement is adapted to the photographic application of the enlarger, in order to provide accurate control of the desired colour saturation.

The present invention provides a light source comprising an elongate hollow frame, a lamp positioned adjacent one end of the frame for producing light, a plurality of dichroic filters and means associated with each of said filters for pivoting said filters, said means permitting pivotal motion of more than one of said filters simultaneously across the path of the incident light, characterised in that each of said filters transmits a respective and different dominant colour and is pivotally mounted, within the frame, for motion into said light path; motor means, associated with each of said filters, are provided

for pivoting said filters from a position aligned with the light path, wherein the filters do not significantly interfere with the incident light, to a position transverse to the light path whereby said filters can be individually and selectively pivoted, between said positions, to vary the angle of incidence of the light on the selectively pivoted filter whilst enabling the light from the lamp to pass around the sides of said filter so that both the hue and saturation of the colour of the light produced by the light source can be varied in dependence on the pivotal positions of said filters.

A preferred embodiment of the invention will now be described with reference to the accompanying drawings, in which:

Figure 1 is a perspective view of a lighting system;

Figure 2a is a vertical cross-sectional view of a light source according to an embodiment of the invention; and

Figure 2b is a horizontal cross-sectional view of the light source shown in Figure 2a.

Figure 1 illustrates a lighting system 10 which may be used to light a stage or other forum where directable light is desired. For example, the lighting system 10 may be used to light a rock concert or a theatrical performance. As explained in more detail in copending Application No. 82301043.4 (EP—A—0060068) from which this application is divided, the lighting system 10 includes a remote control panel 12 for controlling the light sources 14 mounted on a truss 16 above, in front, or to the side of the stage to be lit. Each light source 14 may be positioned and the light being produced thereby varied in colour, intensity and beam divergence from the remote control panel 12. If the performance being lit includes a number of scenes, or individual lighting changes generally termed as cues, the remote control panel 12 includes a memory for recalling the position, colour, intensity and beam divergence of each light source 14 for each separate cue and the remote control panel 12 will automatically set up an entire cue by the activation of a single control on the control panel 12. Each function described above is accomplished with only a single two conductor data link or single cable 18 interconnecting the control panel 12 and truss 16 and a power cable 20.

Referring to Figures 2a and 2b, a light source 30 is illustrated in more detail as an example of one of the lights 14 shown in Figure 1. The light source 30 includes a rigid frame 32 having an aperture 34 formed in one end thereof for passage of the light beam 36. The frame 32 and components therein are pivotally mounted to the truss 16 by a gimbal mechanism 38.

The gimbal mechanism 38 pivotally supports the frame 32 for motion in two mutually perpendicular planes. The frame 32 may move in a horizontal plane or pan across a stage and in a vertical plane or tilt. The gimbal mechanism 38 also includes motor for independently panning and tilting the frame 32 in discrete increments in

response to signals generated by the remote control panel 12. The motors permit the light beam 36 to be aimed at any desired location on the stage. In the preferred embodiment servo motors are used in gimbal mechanism 38.

A lamp 50 is positioned within frame 32 adjacent one end thereof. The lamp 50 produces white light, or light across substantially the entire visible spectrum. In the preferred embodiment, the lamp 50 may comprise a common projection lamp as used in movie projectors and the like having a 110 volt AC input with a power consumption of approximately 350 watts. This type of lamp has the advantage of very low infrared radiation generation, thereby avoiding the generation of excess heat within the light 30. An elliptic mirror 52 is positioned about the lamp 50 to reflect light incident thereon to converge at a focus 54, the light diverges and enters a collimating lens 56 which collimates light incident thereon to form the light beam 36.

Dichroic filters 58 and 60 are pivotally mounted to the frame 32 on either side of focus 54. Two additional dichroic filters 62 and 64 are pivotally mounted to frame 32 on the side of collimating lens 56 opposite focus 54. Dichroic filters are available commercially, such as those sold by the Technical Products Division of Optical Coating Laboratory, Inc. of P.O. Box 1599, Santa Rosa, California. A dichroic filter is a multiple layered optical film having a glass, pyrex or quartz base. The alternate layers have low and high indexes of refraction, respectively. Dichroic filters work on an interference principle, separating two colours out of a white light source, one colour being transmitted and the other colour, the complement of that transmitted, being reflected. The transmitted colour depends upon the type of material used in the layers and its refractive index, the thickness of each layer, the number of layers and the angle of incidence of the white light source striking the surface of the filter. By varying the angle of incidence of white light on a given filter, a preselected range of colour spectrum may be produced.

The dichroic filters 58-64 are preferably formed of multiple thin layers of material and may have a circular, rectangular or other shape. The filters therefore have a thickness of a relatively small dimension and a relatively large surface for incidence of light. Dichroic filter 58 is mounted for pivotal motion about an axis X-X by shaft 66. As can be seen with reference to 2b, the axis X-X extends through the centre of the light path. Dichroic filters 60, 62 and 64 are similarly mounted for pivotal motion about axis Y-Y, Z-Z and V-V, respectively, about shafts 68, 70 and 72, respectively. Each dichroic filter may be pivoted about its associated shaft by means of a servo motor 74, 76, 78 or 80.

When the dichroic filters are aligned with the light path, as shown in Figure 2b, no influence on the colour is created and the filters do not significantly interfere with the light path. Therefore, a white light beam is created for use as a spot or

other desired use. As a given dichroic filter is pivoted so that the angle of incidence of the light, θ , increases above 0, the filter moves across the light path and transmits a coloured beam with the colour dependent on the angle θ . The four filters may be chosen to transmit four dominant colours. Filters 58 may transmit blue, filter 60 green, filter 62 red and filter 64 yellow. However, each individual filter will transmit a range of spectrum as θ is varied. At low values of θ , white light spills around the edges of the filters, diluting the transmitted beam to produce pastel or un-saturated shades of colour as the beam is passed through an integrating lens 100 described hereinafter to homogenize the light beam. In the preferred embodiment, the blue and green filters are positioned furthest from lamp 50 to form dichroic filters 62 and 64. This permits desirable pastel or unsaturated shades of colour to be produced when low values of θ are present. The permutations of colour in the light beam 36 in passing light through a filter or multiple filters are theoretically infinite, dependent only on the relative position of the filters. In one application of the present invention, 4,000 permutations of colour are possible.

A douser unit 90 is positioned within the frame 32. The douser unit 90 acts to permit the light beam 36 to pass therethrough when open but substantially cuts off the light beam 36 when closed. It therefore acts like a shutter to block light from passing from the light 30, but permits the light beam to be almost instantaneously restored by opening the douser unit. In the preferred embodiment, the douser unit 90 is in the form of a mechanical shutter. The shutter is controlled by a solenoid 92 which may be activated to either close or open the shutter to control the light beam. The shutter is designed so that the shutter is closed upon deactivation of the solenoid. This feature prevents a light beam from emanating from a light when the light is malfunctioning, or the data transmitted to the light is in error to prevent improper lighting.

In close proximity with douser unit 90 is a dimmer unit 94. The dimmer unit 94 dims or decreases the intensity of light beam 36 to vary the mood or impact of the light on the stage. The dimmer unit 94 is controlled by a servo motor 96.

An integrating lens 100 is provided to mix the light passing through the dichroic filters to insure a uniform colour. The integrating lens 100 is formed of a large number of small spherical lens 102 mounted on a flat transparent surface which acts to homogenize any light passing there-through. Finally, light beam 36 passes through a focusing lens 104 prior to exiting frame 32 through aperture 34 to light a desired location on a stage.

The light 30 may include a cooling fan 106 mounted in the lower base thereof. The cooling fan 106 forces outside air into the lower portion of the light to cool the electric components such as receiver 166 and servo drive 168. A portion of the airflow is directed through nozzles 107 at the lamp

50 to cool the lamp directly. The remainder of the air passes forward to a slot 108 adjacent the douser and dimmer units and passes to the upper portion of the light 30 to cool the lenses and dichroic filters. The air passing through slot 108 and issuing from the nozzles 107 exits through a grating 109 at the rear of light source 30 adjacent the elliptic mirror 52.

Reference is made to copending European Patent Application No. 82301043.4, from which this application is divided, (EP-A-0060068) for further details of the way in which the light source 30 is controlled by the system 10 of Figure 1.

Claims

1. A light source comprising an elongate hollow frame (32), a lamp (50) positioned adjacent one end of the frame (32) for producing light, a plurality of dichroic filters (58-64) and means (74-80) associated with each of said filters (58-64) for pivoting said filters (58-64), said means (74-80) permitting pivotal motion of more than one of said filters (58-64) simultaneously across the path of the incident light, characterised in that each of said filters (58-64) transmits a respective and different and dominant colour and is pivotally mounted, within the frame (32), for pivotal motion into said light path; motor means (74-80), associated with each of said filters (58-64), are provided for pivoting said filters (58-64) from a position aligned with the light path, wherein the filters (58-64) do not significantly interfere with the incident light, to a position transverse to the light path whereby said filters (58-64) can be individually and selectively pivoted, between said positions, to vary the angle of incidence of the light on the selectively pivoted filter whilst enabling the light from the lamp (50) to pass around the sides of said filter so that both the hue and saturation of the colour of the light produced by the light source can be varied in dependence on the pivotal positions of said filters (58-64).

2. A light source according to claim 1 wherein each of said filters (58-64) is mounted for pivotal motion about an axis passing through the centre of the light path.

3. A light source according to claim 1 wherein integrating means (100) is provided for a homogenizing the light passing through said filters (58-64) with the light passing around said filters (58-64) in order to produce a uniformly coloured light beam.

4. A light source according to claim 1 wherein said plurality of filters (58-64) comprises four dichroic filters which respectively transmit the dominant colours blue, green, yellow and red.

5. A light source according to claim 4 wherein the filters (58-60) which transmit blue and green light are positioned further from the lamp (50) than the filters (62-64) which transmit yellow and red light.

6. A light source according to any of the preceding claims wherein an elliptical reflector

(52) is positioned behind the lamp (50) for focusing the light at a point between the first two of said filters (58-60), and a collimating lens (56) is provided between said first two filters (58-60) and the second two of said filters (62-64) for providing said collimated beam of light on the light path through said second two filters (62-64).

Patentansprüche

1. Lichtquelle mit einem langgestreckten hohlen Rahmen (32), einer Lampe (50), die neben einem Ende des Rahmens (32) angeordnet ist, um Licht zu erzeugen, einer Vielzahl von dichroitischen Filtern (58-64) und Einrichtungen (74-80), die jedem der Filter (58-64) zugeordnet sind, um die Filter (58-64) zu schwenken, wobei die Einrichtungen (74-80) eine Schwenkbewegung von mehr als einem der Filter (58-64) gleichzeitig quer zum Weg des einfallenden Lichtes erlauben, dadurch gekennzeichnet, daß jedes der Filter (58-64) eine jeweilige andere und vorherrschende Farbe durchläßt und schwenkbar im Rahmen (32) zum Ausführen einer Schwenkbewegung in den Lichtweg angebracht ist, Motor-einrichtungen (74-80) vorgesehen sind, die jedem der Filter (58-64) zugeordnet sind, um die Filter (58-64) aus einer Position, die mit dem Lichtweg in einer Linie ausgerichtet ist und in der die Filter (58-64) das einfallende Licht nicht merklich stören, in eine Position zu schwenken, die quer zum Lichtweg liegt, wodurch die Filter (58-64) einzeln und wahlweise zwischen diesen Positionen geschwenkt werden können, um den Einfallswinkel des Lichtes auf das wahlweise geschwenkte Filter zu variieren, während das Licht von der Lampe (50) um die Seiten des Filters herum gehen kann, so daß sowohl der Farbton als auch die Sättigung der Farbe des durch die Lichtquelle erzeugten Lichtes in Abhängigkeit von den Schwenkpositionen der Filter (58-64) variiert werden können.

2. Lichtquelle nach Anspruch 1, bei der jedes der Filter (58-64) um eine Achse schwenkbeweglich angebracht ist, die durch die Mitte des Lichtweges geht.

3. Lichtquelle nach Anspruch 1, bei der Integriereinrichtungen (100) vorgesehen sind, um das durch die Filter (58-64) gehende Licht mit dem Licht zu homogenisieren, das um die Filter (58-64) geht, damit ein Lichtstrahl mit gleichmäßiger Farbe erzeugt wird.

4. Lichtquelle nach Anspruch 1, bei der die Vielzahl der Filter (58-64) vier dichroidische Filter umfaßt, die jeweils die vorherrschenden Farben blau, grün, gelb und rot durchlassen.

5. Lichtquelle nach Anspruch 4, bei der die Filter (58-60), die blaues und grünes Licht durchlassen, weiter von der Lampe (50) als die Filter (62-64) entfernt angeordnet sind, die gelbes und rotes Licht durchlassen.

6. Lichtquelle nach einem der vorhergehenden Ansprüche, bei der ein elliptischer Reflektor (52) hinter der Lampe (50) angeordnet ist, um das

50 to cool the lamp directly. The remainder of the air passes forward to a slot 108 adjacent the douser and dimmer units and passes to the upper portion of the light 30 to cool the lenses and dichroic filters. The air passing through slot 108 and issuing from the nozzles 107 exits through a grating 109 at the rear of light source 30 adjacent the elliptic mirror 52.

Reference is made to copending European Patent Application No. 82301043.4, from which this application is divided, (EP-A-0060068) for further details of the way in which the light source 30 is controlled by the system 10 of Figure 1.

Claims

1. A light source comprising an elongate hollow frame (32), a lamp (50) positioned adjacent one end of the frame (32) for producing light, a plurality of dichroic filters (58-64) and means (74-80) associated with each of said filters (58-64) for pivoting said filters (58-64), said means (74-80) permitting pivotal motion of more than one of said filters (58-64) simultaneously across the path of the incident light, characterised in that each of said filters (58-64) transmits a respective and different and dominant colour and is pivotally mounted, within the frame (32), for pivotal motion into said light path; motor means (74-80), associated with each of said filters (58-64), are provided for pivoting said filters (58-64) from a position aligned with the light path, wherein the filters (58-64) do not significantly interfere with the incident light, to a position transverse to the light path whereby said filters (58-64) can be individually and selectively pivoted, between said positions, to vary the angle of incidence of the light on the selectively pivoted filter whilst enabling the light from the lamp (50) to pass around the sides of said filter so that both the hue and saturation of the colour of the light produced by the light source can be varied in dependence on the pivotal positions of said filters (58-64).

2. A light source according to claim 1 wherein each of said filters (58-64) is mounted for pivotal motion about an axis passing through the centre of the light path.

3. A light source according to claim 1 wherein integrating means (100) is provided for a homogenizing the light passing through said filters (58-64) with the light passing around said filters (58-64) in order to produce a uniformly coloured light beam.

4. A light source according to claim 1 wherein said plurality of filters (58-64) comprises four dichroic filters which respectively transmit the dominant colours blue, green, yellow and red.

5. A light source according to claim 4 wherein the filters (58-60) which transmit blue and green light are positioned further from the lamp (50) than the filters (62-64) which transmit yellow and red light.

6. A light source according to any of the preceding claims wherein an elliptical reflector

(52) is positioned behind the lamp (50) for focusing the light at a point between the first two of said filters (58-60), and a collimating lens (56) is provided between said first two filters (58-60) and the second two of said filters (62-64) for providing said collimated beam of light on the light path through said second two filters (62-64).

Patentansprüche

1. Lichtquelle mit einem langgestreckten hohlen Rahmen (32), einer Lampe (50), die neben einem Ende des Rahmens (32) angeordnet ist, um Licht zu erzeugen, einer Vielzahl von dichroitischen Filtern (58-64) und Einrichtungen (74-80), die jedem der Filter (58-64) zugeordnet sind, um die Filter (58-64) zu schwenken, wobei die Einrichtungen (74-80) eine Schwenkbewegung von mehr als einem der Filter (58-64) gleichzeitig quer zum Weg des einfallenden Lichtes erlauben, dadurch gekennzeichnet, daß jedes der Filter (58-64) eine jeweilige andere und vorherrschende Farbe durchläßt und schwenkbar im Rahmen (32) zum Ausführen einer Schwenkbewegung in den Lichtweg angebracht ist, Motor-einrichtungen (74-80) vorgesehen sind, die jedem der Filter (58-64) zugeordnet sind, um die Filter (58-64) aus einer Position, die mit dem Lichtweg in einer Linie ausgerichtet ist und in der die Filter (58-64) das einfallende Licht nicht merklich stören, in eine Position zu schwenken, die quer zum Lichtweg liegt, wodurch die Filter (58-64) einzeln und wahlweise zwischen diesen Positionen geschwenkt werden können, um den Einfallswinkel des Lichtes auf das wahlweise geschwenkte Filter zu variieren, während das Licht von der Lampe (50) um die Seiten des Filters herum gehen kann, so daß sowohl der Farbton als auch die Sättigung der Farbe des durch die Lichtquelle erzeugten Lichtes in Abhängigkeit von den Schwenkpositionen der Filter (58-64) variiert werden können.

2. Lichtquelle nach Anspruch 1, bei der jedes der Filter (58-64) um eine Achse schwenkbeweglich angebracht ist, die durch die Mitte des Lichtweges geht.

3. Lichtquelle nach Anspruch 1, bei der Integriereinrichtungen (100) vorgesehen sind, um das durch die Filter (58-64) gehende Licht mit dem Licht zu homogenisieren, das um die Filter (58-64) geht, damit ein Lichtstrahl mit gleichmäßiger Farbe erzeugt wird.

4. Lichtquelle nach Anspruch 1, bei der die Vielzahl der Filter (58-64) vier dichroidische Filter umfaßt, die jeweils die vorherrschenden Farben blau, grün, gelb und rot durchlassen.

5. Lichtquelle nach Anspruch 4, bei der die Filter (58-60), die blaues und grünes Licht durchlassen, weiter von der Lampe (50) als die Filter (62-64) entfernt angeordnet sind, die gelbes und rotes Licht durchlassen.

6. Lichtquelle nach einem der vorhergehenden Ansprüche, bei der ein elliptischer Reflektor (52) hinter der Lampe (50) angeordnet ist, um das



Licht an einem Punkt zwischen den ersten beiden Filtern (58—60) zu fokussieren und eine Kollimatorlinse (56) zwischen den ersten beiden Filtern (58—60) und den zweiten beiden Filtern (62, 64) vorgesehen ist, um einen kollimierten Lichtstrahl auf dem Lichtweg durch die zweiten beiden Filter (62—64) zu liefern.

Revendications

1. Source lumineuse comprenant un châssis (32) creux allongé, une lampe (50) positionnée à proximité de l'une des extrémités du châssis (32) destinée à produire une lumière, plusieurs filtres dichroïques (58 à 64) et des moyens (74 à 80) associés à chacun des filtres (58, 64) pour faire pivoter les filtres (58, 64), lesdits moyens (74, 80) permettant un mouvement de pivotement de plus d'un filtre (58—64) en même temps à travers le trajet de la lumière incidente, caractérisée en ce que chacun des filtres (58—64) transmet une couleur dominante différente respective et est monté de manière pivotante dans le châssis (32) pour un mouvement de pivotement dans le trajet de la lumière; des moyens moteurs (74, 80) associés à chacun des filtres (58, 64), sont prévus pour faire pivoter les filtres (58, 64) depuis une position alignée avec le trajet de la lumière, dans lequel les filtres (58, 64) n'interfèrent pas de manière significative avec la lumière incidente, jusqu'à une position transversale par rapport au trajet de la lumière et les filtres (58—64) peuvent ainsi être pivotés de manière individuelle et sélective entre lesdites positions, pour faire varier l'angle d'incidence de la lumière sur le filtre pivoté de manière sélective tout en permettant à la lumière émise par la lampe (50) de passer autour des bords du filtre de façon telle que à la

fois la teinte et la saturation de la couleur de la lumière produite par la source lumineuse peuvent varier en fonction des positions pivotées des filtres (58—64).

2. Source lumineuse selon la revendication 1 caractérisée en ce que chacun des filtres (58—64) est monté pour un mouvement pivotant autour d'un axe (60) passant par le centre géométrique du trajet de la lumière.

3. Source lumineuse selon la revendication 1 caractérisée en ce que des moyens intégrateurs (100) sont prévus pour une homogénéisation de la lumière passant à travers les filtres (58—64) avec la lumière passant autour des filtres (58—64) dans le but de produire un rayon lumineux coloré de manière uniforme.

4. Source lumineuse selon la revendication 1 caractérisée en ce que lesdits plusieurs filtres (58—64) comportent quatre filtres dichroïques qui respectivement transmettent les couleurs dominantes bleu, vert, jaune et rouge.

5. Source lumineuse selon la revendication 4 caractérisée en ce que les filtres (58—60) qui transmettent la lumière bleue et la lumière verte sont positionnés plus loin de la lampe (50) que les filtres (62—64) qui transmettent la lumière jaune et la lumière rouge.

6. Source lumineuse selon l'une quelconque des revendications précédentes, caractérisée en ce que un miroir elliptique (52) est positionné derrière la lampe (50) pour focaliser la lumière en un point situé entre les deux premiers filtres (58—60), et une lentille collimatrice (56) est prévue entre lesdits deux premiers filtres (58—60) et les deux filtres suivants (62—64) pour amener le rayon de lumière collimaté sur le trajet lumineux à travers les deux filtres suivants (62—64).

