

Electrical connector

This invention relates to electrical connectors and particularly to an electrical connector suitable for facilitating the wiring or harnesses on panel boards.

GB—A—1,497,494 (5058) describes an electrical connector comprising an insulating housing formed with a compartment opening to a rear, wire receiving face and receiving an electrical contact having at one end a wire-receiving slot comprising a narrow wire-connecting portion opening to a wire-admitting mouth at the face, through which mouth an insulated wire can be forced transversely of its axis into the wire-connecting portion so that the edges of the wire-connecting portion penetrate the insulation to establish electrical connection to the wire core, the compartment wall being integrally formed with a resilient finger extending adjacent the slot to trap the wire in the slot.

A disadvantage of the known connector is that the resilient finger extends longitudinally of the wire-receiving slot and terminates intermediate the ends of the wire-connecting portion. Whilst the finger will assist in retaining the wire in the wire-connecting portion subsequent to connection it will not trap the wire in the wire-admitting mouth prior to connection.

In a connector according to the invention, the resilient finger extends across the wire-admitting mouth of the slot to trap a wire in the wire-admitting mouth prior to insertion in the wire-connecting portion of the slot.

When several such connectors are mounted on a panel board a wiring technician can lace the wires to the desired configuration using the finger to retain each wire securely in a preloaded condition in the wire admitting mouth of each slot. The wiring configuration can subsequently be checked before connection and without risk of dislodgement of the wires during handling of the panel board.

It is also known to provide additional wire locating combs adjacent the connectors to enable wires to be aligned approximately with contacts prior to connection but the disadvantages are that not only is additional apparatus required but the wires are often only approximately aligned, further alignment being necessary during wire insertion. The wires are also often subject to dislodgement during lacing the harness or subsequent handling of the panel board.

Specific examples of electrical connectors constituting lamp holders according to the invention will now be described with reference to the accompanying drawings in which:—

Figure 1 is a perspective view of a first example of connector with a contact exploded from the connector housing for clarity;

Figure 2 is a perspective view of the con-

necter mounted on a panel board;

Figure 3 is a cross-sectional view along lines III—III of Figure 2;

Figure 4 is a perspective view of several examples of electrical connectors according to the invention mounted in various positions on a panel board.

The first example of electrical connector includes a box-like housing 11 moulded in one-piece of plastics material with a laterally extending mounting foot 12 and formed with a through cavity divided by a transverse wall 13 into two contact receiving compartments 14 and 15 respectively at a rear, wire-connecting, face 16. The cavity provides a lamp receiving compartment 17 at a front face 18 of the housing.

Flexible fingers 19 and 21 extend rearwardly from opposite sides of the rear face.

Electrical contacts of the connector are each stamped and formed from a single piece of sheet metal stock and each comprise a channel-section body portion 22, from one axial end of the side walls of which extend a pair of opposed resilient contact arms 23 adapted to grip between them the base of a conventional lamp 28 electrically to connect to lamp wire 29 extending along the lamp base. A wire receiving slot 24 extends through the channel base into the side walls at the axially opposite wire connecting end of the body and comprises narrow wire connecting portion 26 communicating with a relatively wide wire-admitting mouth 25. A locking tooth or detent 27 is pushed out from each side wall.

The contacts are assembled in respective back-to-back relation with the flexible fingers extending parallel to the contact axis bridging the respective slot mouths. When several connectors are secured to the rear face of a panel board 31 adjacent windows 32, wires are laced around the connectors as desired, inserted under the fingers as shown in Figure 2, by flexing the fingers away from the slot mouths and thereby trapped in alignment with the mouths of respective contacts. The wires are reliably held in place by the fingers during handling of the panel boards prior to connection enabling inspection of the harness configuration without risk of dislocation of the wires. After inspection, the wires are forced into the narrow wire connecting portions 26 of the slots using a simple tool. It should be noted that in some applications, the fingers themselves may advantageously be used to transmit a portion of the insertion force.

Figure 4 illustrates a resultant harness using different examples of connectors.

A particular application of the invention is in wiring illuminated panel boards of electronic games machines and panel boards of other illuminated displays.



15

3

0032 615

4

Claims

1. An electrical connector comprising an insulating housing (11) formed with a compartment (14 or 15) opening to a rear, wire receiving face (16) and receiving an electrical contact having at one end a wire-receiving slot (24) comprising a narrow wire-connecting portion (26) opening to a wire-admitting mouth (25) at the face, through which mouth an insulated wire can be forced transversely of its axis into the wire-connecting portion so that the edges of the wire-connecting portion penetrate the insulation to establish electrical connection to the wire core, the compartment wall being integrally formed with a resilient finger (19 or 21) extending adjacent the slot to trap the wire in the slot, characterised in that the resilient finger (19 or 21) extends across the wire-admitting mouth (25) of the slot (24) to trap a wire in the wire admitting mouth (25) prior to insertion in the wire-connecting portion (26) of the slot (24).

2. An electrical connector according to Claim 1, characterised in that the contact comprises a channel section body (22), wire connecting portions (26) being formed in each side wall and communicating through a common mouth (25) extending through the channel base, a pair of resilient contact arms (23) extending axially in opposed relation from respective side walls at the other end of the body (22).

3. An electrical connector according to Claim 2, characterised in that the housing (11) includes a further similar compartment (14 or 15) receiving a further similar electrical contact, the two contacts being arranged in back-to-back relation, the compartments communicating at a front face to provide a lamp-receiving compartment into which the respective resilient pairs of arms (23) extend in alignment with each other to receive and effect connection to the respective wires (29) on the base of a wedge-base lamp (28).

Revendications

1. Connecteur électrique comprenant un boîtier isolant (11) formé avec un compartiment (14 ou 15) s'ouvrant vers une face arrière (16) de réception de fils et recevant un contact électrique ayant, à une extrémité, une fente (24) de réception de fil comprenant une partie étroite (26) de connexion de fil s'ouvrant vers une embouchure (25) d'admission de fil située à la face, embouchure à travers laquelle un fil isolé peut être forcé transversalement à son axe dans la partie de connexion du fil afin que les bords de la partie de connexion de fil pénètrent dans l'isolation pour établir une connexion électrique avec l'âme du fil, la paroi du compartiment étant réalisée d'une seule pièce avec un doigt élastique (19 ou 21) s'étendant à proximité immédiate de la fente pour retenir le fil dans la fente, caractérisé en ce que le doigt élastique

(19 ou 21) s'étend en travers de l'embouchure (25) d'admission de fil de la fente (24) pour retenir un fil dans l'embouchure (25) d'admission de fil avant l'insertion dans la partie (26) de connexion de fil de la fente (24).

2. Connecteur électrique selon la revendication 1, caractérisé en ce que le contact comprend un corps (22) de section en gouttière, des parties (26) de connexion de fils étant formées dans chaque paroi latérale et communiquant par l'intermédiaire d'une embouchure commune (25) s'étendant à travers la base de la gouttière, deux lames élastiques (23) de contact s'étendant axialement, en opposition, à partir de parois latérales respectives, à l'autre extrémité du corps (22).

3. Connecteur électrique selon la revendication 2, caractérisé en ce que le boîtier (11) comprend un autre compartiment similaire (14 ou 15) recevant un autre contact électrique similaire, les deux contacts étant agencés dos à dos, les compartiments communiquant à une face avant pour former un compartiment de réception d'une lampe dans lequel les paires élastiques respectives de lames (23) s'étendent en alignement l'une avec l'autre pour recevoir et réaliser une connexion sur les fils respectifs (29) situés sur la base d'une lampe (28) à base en forme de coin.

Patentansprüche

1. Elektrischer Verbinder mit einem Isoliergehäuse (11), das mit einem sich zu einer rückwärtigen Drahtaufnahmeseite (16) öffnenden Abteil (14) oder (15) ausgebildet ist und einen elektrischen Kontakt aufnimmt, der an einem Ende einen Drahtaufnahmeschlitz (24) aufweist, der einenschmalen Drahtanschlußbereich (26) besitzt, der in eine Drahteinführöffnung (25) an der Vorderseite mündet, durch die ein isolierter Draht quer zu seiner Achse in den Drahtanschlußbereich hineingezwängt werden kann, so daß die Kanten des Drahtanschlußbereichs die Isolierung durchdringen und eine elektrische Verbindung mit dem Kern des Drahts herstellen, wobei die Abteilmwandung einstückig mit einem federnd nachgiebigen Finger (19) oder (21) ausgebildet ist, der sich angrenzend an den Schlitz erstreckt, um den Draht in dem Schlitz einzuschließen, dadurch gekennzeichnet, daß sich der federnd nachgiebige Finger (19 oder 21) über die Drahteinführöffnung (25) des Schlitzes (24) erstreckt, um einen Draht vor dem Einführen in den Drahtanschlußbereich (26) des Schlitzes (24) in der Drahteinführöffnung (25) einzuschließen.

2. Elektrischer Verbinder nach Anspruch 1, dadurch gekennzeichnet, daß der Kontakt einen Körper (22) mit rinnenartigem Querschnitt aufweist, daß in jeder Seitenwand Drahtanschlußbereiche (26) ausgebildet sind und über eine durch die Rinnen-Basis verlaufende, gemeinsame Mündung (25) miteinander in Verbindung stehen, und daß sich ein Paar federnd



16

5

0032 615

6

nachgiebiger Kontaktarme (23) axial in entgegengesetztem Verhältnis von den jeweiligen Seitenwänden am anderen Ende des Körpers (22) wegerstrecken.

3. Elektrischer Verbinder nach Anspruch 2, dadurch gekennzeichnet, daß das Gehäuse (11) ein weiteres ähnliches Abteil (14) oder (15) aufweist, das einen weiteren ähnlichen elektrischen Kontakt aufnimmt, daß die beiden Kontakte Rücken an Rücken angeordnet sind, und

daß die Abteilungen an einer Vorderseite miteinander in Verbindung stehen, um ein Lampenaufnahme-Abteil zu schaffen, in das sich die jeweiligen federnd nachgiebigen Paare von Armen (23) in gegenseitiger Fluchtung hineinerstrecken, um die jeweiligen Drähte (29) am Sockel einer Keilsockel-Lampe (28) aufzunehmen und eine Verbindung mit diesem herzustellen.

5

10

15

20

25

30

35

40

45

50

55

60

65

4