

## FOUR-DIMENSIONAL FLYABLE AREA DISPLAY SYSTEM FOR AIRCRAFT

### Field

5           The present disclosure relates generally to aircraft and, in particular, to displaying information used to operate aircraft. Still more particularly, the present disclosure relates to a method and apparatus for displaying flyable areas for an aircraft.

### Background

10           Information used to fly an aircraft may be displayed on a display system in the aircraft. This display system may be, for example, a navigation display or an  
15   electronic flight bag (EFB) display. An aeronautical chart showing terrain around the aircraft may be displayed on the navigation display.

          Additionally, other information also may be displayed on the navigation display. This information may  
20   include, for example, without limitation, information about air traffic, flight paths of air traffic, and other suitable information.

          The operator may use this information along with other information from other sources to operate the  
25   aircraft. For example, the operator may use fuel usage or estimates of fuel usage from a flight management system along with information about weather and traffic shown on the navigation display to determine whether sufficient reserve fuel is present to reach a target airport or whether  
30   the foreseen workload due to traffic is acceptable and manageable by the flight crew. If reserve fuel levels are not sufficient, the operator may use the navigation display to identify alternative airports that can be reached with a desired level of reserve fuel.

Further, the navigation display may also be used by the operator to identify weather conditions that may require changes to the flight plan for the aircraft. For example, weather conditions may make landing at a target  
5 airport in the flight plan unfeasible. As a result, the operator may use the navigation display along with the weather conditions on the display to identify an alternate airport for landing.

Further, the navigation display may also be used  
10 by the operator to identify areas where a reduced workload can be estimated for operating the aircraft as desired. For example, when one crew member is impaired, the remaining crew member needs to fly the aircraft to the next airport and may want to avoid flying through congested airspace.

15 In another example, when equipment in the aircraft does not operate as desired, the flight crew focuses their mental workload on assessing and addressing the current situation of the aircraft. In this case, the flight crew may also desire avoiding congested airspace.

20 Various conditions change dynamically during the flight of an aircraft. These conditions include, for example, without limitation, weather, traffic, flight paths of traffic, and other conditions. With these changes in conditions occurring during the flight of the aircraft, an  
25 operator of the aircraft uses the information from the navigation display and the flight management system to determine whether changes in the operation of the aircraft should occur. Identifying the changes in the conditions and determining whether changes in the operation of the aircraft  
30 should occur are tasks that require time and attention of the operator.

For example, with rapidly-changing weather conditions, identifying a desirable, safe route to a target airport may be more difficult than desired due to the need

to process and manage various types of information about the environment around the aircraft. In other words, the operator monitors and makes calculations as to whether the target airport can be reached with the desired reserve fuel levels, or the operator identifies an alternative airport if the target airport cannot be reached. With dynamically-changing conditions, this may be more difficult or time-consuming than desired.

Therefore, it would be desirable to have a method and apparatus that takes into account at least some of the issues discussed above as well as possibly other issues.

#### **SUMMARY**

In one illustrative embodiment, a method for displaying information for an aircraft is present. Information is identified for the aircraft. An aeronautical chart is displayed on a display system. An envelope is displayed in the aeronautical chart based on the information. The envelope defines a space flyable by the aircraft that meets a number of objectives.

In another illustrative embodiment, a navigation system comprises a display system and a flight information identifier. The flight information identifier is configured to identify information for an aircraft. The flight information identifier is further configured to display an aeronautical chart on the display system. The flight information identifier is further configured to display an envelope in the aeronautical chart based on the information. The envelope defines a space flyable by the aircraft that meets a number of objectives.

According to an aspect of the present invention there is provided a method for displaying information for an aircraft, the method comprising: identifying the information for the aircraft; displaying an aeronautical chart on a

display system; and displaying an envelope in the aeronautical chart based on the information, wherein the envelope defines a space flyable by the aircraft that meets a number of objectives.

5            Optionally the envelope is displayed in either two dimensions or three dimensions.

            Optionally the method is further comprising the step of displaying an indication of undesirable space outside of the envelope. Preferably the indication of  
10 undesirable space is a graphical indicator that obscures a portion of the aeronautical chart outside of the envelope.

            Optionally the method is further comprising the step of displaying an indication of desired space within the envelope.

15            Optionally the method further comprises the step of repeating displaying the envelope in the aeronautical chart based on the information in response to the information changing, wherein the envelope defines the space flyable by the aircraft that meets the number of objectives.

20            Optionally the aeronautical chart is selected from at least one of a vertical view and a top view.

            Optionally the information for the aircraft is selected from at least one of an aircraft state, environmental information, and a flight plan.

25            Optionally the step of identifying the information associated with the aircraft; displaying the aeronautical chart; and displaying the envelope in the aeronautical chart based on the information, wherein the envelope defines the space flyable by the aircraft that meets the number of  
30 objectives is performed in a computer system in the aircraft or at a ground location.

            Optionally the number of objectives comprises at least one of a risk objective, an optimization objective, and a legal objective.

Optionally the method is further comprising the steps; generating a four-dimensional cube comprised of a plurality of cubes; and marking the plurality of cubes with an indication of a type of space based on the information, wherein, the step of displaying the envelope comprises: displaying the envelope using the four-dimensional cube with the type of space marked for the plurality of cubes in the four-dimensional cube.

According to another aspect of the present invention there is provided a navigation system comprising: a display system; and a flight information identifier configured to identify information for an aircraft; display an aeronautical chart on the display system; and display an envelope in the aeronautical chart based on the information, wherein the envelope defines a space flyable by the aircraft that meets a number of objectives.

Optionally the envelope is displayed in one of two dimensions and three dimensions.

Optionally the flight information identifier is configured to display an indication of undesirable space outside of the envelope. Preferably the indication of undesirable space is a graphical indicator that obscures a portion of the aeronautical chart outside of the envelope.

Optionally the flight information identifier is configured to display an indication of desired space within the envelope.

Optionally the flight information identifier is further configured to repeat displaying the envelope in the aeronautical chart based on the information in response to the information changing, wherein the envelope defines the space flyable by the aircraft that meets the number of objectives.

Optionally the aeronautical chart is selected from at least one of a vertical view and a top view.

Optionally the flight information identifier is further configured to generate a four-dimensional cube comprised of a plurality of cubes and mark the plurality of cubes with an indication of a type of space based on the information, and wherein in being configured to display the envelope in the aeronautical chart based on the information, the flight information identifier is configured to display the envelope using the four-dimensional cube with the type of space marked for the plurality of cubes in the four-dimensional cube.

The features and functions can be achieved independently in various embodiments of the present disclosure or may be combined in yet other embodiments in which further details can be seen with reference to the following description and drawings.

#### **BRIEF DESCRIPTION OF THE DRAWINGS**

The novel features believed characteristic of the illustrative embodiments are set forth in the appended claims. The illustrative embodiments, however, as well as a preferred mode of use, further objectives, and advantages thereof will best be understood by reference to the following detailed description of an illustrative embodiment of the present disclosure when read in conjunction with the accompanying drawings, wherein:

**Figure 1** is an illustration of a block diagram of an aircraft information environment in accordance with an illustrative embodiment;

**Figure 2** is an illustration of a block diagram of a graphical user interface in accordance with an illustrative embodiment;

**Figure 3** is an illustration of an envelope displayed in an aeronautical chart in a graphical user interface in accordance with an illustrative embodiment;

**Figure 4** is another illustration of an envelope displayed in an aeronautical chart in a graphical user interface in accordance with an illustrative embodiment;

**Figure 5** is yet another illustration of an envelope displayed in an aeronautical chart in a graphical user interface in accordance with an illustrative embodiment;

**Figure 6** is an illustration of a block diagram of a flight information identifier in accordance with an illustrative embodiment;

**Figure 7** is an illustration of cubes in a four-dimensional space in accordance with an illustrative embodiment;

**Figure 8** is an illustration of a flowchart of a process for displaying information for an aircraft in accordance with an illustrative embodiment;

**Figure 9** is an illustration of a flowchart of a process for processing information for an aircraft to identify an envelope in accordance with an illustrative embodiment; and

**Figure 10** is an illustration of a data processing system in accordance with an illustrative embodiment.

## **DETAILED DESCRIPTION**

The illustrative embodiments recognize and take into account one or more different considerations. For example, the different illustrative embodiments recognize and take into account that currently, an operator may need to look at different sources for information to operate the aircraft. The different illustrative embodiments recognize and take into account that additional information may be displayed on a navigation display with the aeronautical charts to provide an operator of the aircraft additional situational awareness. The different illustrative

embodiments recognize and take into account that by displaying more information on a navigation display, the operator does not need to look at as many displays, paper charts, or other sources in operating the aircraft.

5           The different illustrative embodiments recognize and take into account that the current manner in which information is displayed on a navigation display may not reduce the effort and time needed for the operator to make decisions regarding operation of the aircraft as much as  
10 desired. For example, the display of additional information may increase the clutter on the navigation display. This increase in clutter may make it more difficult for the operator to identify needed information for determining whether changes in the operation of the aircraft should  
15 occur.

          Thus, one or more illustrative embodiments provide a method and apparatus for displaying information for an aircraft. In one illustrative embodiment, information associated with the aircraft is identified. An aeronautical  
20 chart is displayed on a display system. An envelope is displayed in the aeronautical chart based on the information identified. The envelope defines a space flyable by the aircraft that meets a number of objectives. As used herein, "a number of", when used with reference to items, means one  
25 or more items. For example, a number of objectives is one or more objectives.

          The display of the envelope may be made in a number of different ways. In one illustrative example, information in an area outside of the envelope may be grayed  
30 or blacked out to indicate that that area is a non-flyable area or an area that does not meet the number of objectives. In other words, the areas that do not meet the number of objectives are not shown. The objectives may be areas that are unreachable or restricted.

Turning now to **Figure 1**, an illustration of a block diagram of an aircraft information environment is depicted in accordance with an illustrative embodiment. As depicted, aircraft information environment **100** includes aircraft **102**. Aircraft **102** may take various forms. For example, aircraft **102** may be, without limitation, an airplane, a helicopter, a commercial airplane, a private airplane, a military jet, or other suitable types of aircraft.

In these illustrative examples, flight information identifier **104** may be used to provide information to operate aircraft **102**. In these illustrative examples, flight information identifier **104** may be implemented in software, hardware, or a combination of the two. When implemented in software, flight information identifier **104** may be embodied in program code that is run by a processor unit, such as a processor unit in computer system **106**. Computer system **106** comprises a number of computers. When more than one computer is present, those computers may be in communication with each other through a communications system, such as a network.

Display system **108** is in communication with computer system **106**. In these illustrative examples, display system **108** is hardware that is configured to display information. Display system **108** comprises a number of display devices.

In these illustrative examples, flight information identifier **104** may receive information **110** for aircraft **102**. Information **110** may be received in systems **112** in aircraft **102**. Systems **112** may include, for example, without limitation, at least one of an inertial measurement system, a global positioning system receiver, a flight management system, a sensor system, an electronic centralized aircraft

monitor, an automatic dependent surveillance broadcast (ADS-B) system, and other suitable types of systems.

As used herein, the phrase "at least one of", when used with a list of items, means different combinations of one or more of the listed items may be used and only one of each item in the list may be needed. For example, "at least one of item A, item B, and item C" may include, without limitation, item A or item A and item B. This example also may include item A, item B, and item C, or item B and item C. In other examples, "at least one of" may be, for example, without limitation, two of item A, one of item B, and 10 of item C; four of item B and seven of item C; and other suitable combinations.

In these illustrative examples, information **110** for aircraft **102** may include at least one of information about aircraft **102**, information that affects the operation of aircraft **102**, and other suitable information that may be used to operate aircraft **102**. In these illustrative examples, information **110** may be, for example, at least one of aircraft state **114**, environmental information **116**, flight plan **117**, and other suitable types of information. In these illustrative examples, aircraft state **114** may include information, such as, for example, position, airspeed, fuel use, temperature, pressure, predicted fuel use, altitude, vertical speed, and other suitable types of information about aircraft **102**.

Environmental information **116** may take a number of different forms. Environmental information **116** may include, for example, weather information **115** and traffic information **119**. Weather information **115** in environmental information **116** may include at least one of temperature, precipitation, wind, turbulence, weather conditions, visibility, and other suitable information. Further, weather information **115** also may include projected information, such as, for example,

without limitation, projected weather, projected precipitation, projected winds, and other suitable information.

5 Traffic information **119** may include at least one of locations of air traffic, commercial airways, and other suitable information. Further, traffic information **119** also may include, for example, projected positions for other aircraft for different times. This information may be information about aircraft **102** in its current position or  
10 along a flight path for aircraft **102** based on flight plan **117**.

Flight plan **117** includes information about the flight of aircraft **102** from one location to another location. This information may include, for example, a  
15 route, segments making up the route, waypoints, predicted fuel use, altitude, airspeed, and other suitable information. Other suitable information may include, for example, legal restrictions, notices to airmen, airspace restrictions, such as no-fly zones, and the like.

20 In these illustrative examples, flight information identifier **104** uses information **110** for aircraft **102** to identify envelope **118** for aircraft **102**. Envelope **118** is space **120** that may be flyable by aircraft **102** that meets number of objectives **122**. In other words, envelope **118** is  
25 where aircraft **102** may fly in a manner that meets number of objectives **122**. Space **120** may be two dimensional or three dimensional, depending on the particular implementation.

In these illustrative examples, number of objectives **122** may be various types of objectives, depending  
30 on the particular implementation. Number of objectives **122** may include at least one of risk objective **124**, optimization objective **126**, legal objective **127**, and other types of objectives.

Risk objective **124** may be any objective relating to the amount of risk involved in the operation of aircraft **102**. For example, risk objective **124** may be a requirement or constraint that aircraft **102** has a required level of fuel reserves to reach a target airport. In another illustrative example, risk objective **124** also may be avoiding turbulence that is greater than some desired level of turbulence for aircraft **102**. As yet another example, risk objective **124** may be avoiding airspace in which a cloud of ash is present. Of course, other sets of risk objectives may be used for risk objective **124**.

In still another illustrative example, risk objective **124** may be avoiding a projected flight path of another aircraft by some established amount of distance. Risk objective **124** also may include avoiding terrain by some established amount of distance.

Optimization objective **126** may also take a number of different forms. For example, optimization objective **126** may be to reach a target airport within a desired amount of time, fly with a desired fuel use rate, and other suitable objectives that may be optimizations for the operation of aircraft **102**.

Legal objective **127** may be set by a government agency, such as the Federal Aviation Administration. An example of legal objective **127** may be an airspace restriction, a requirement to fly over designated waypoints, a no-fly zone, altitude restrictions, and other objectives.

In these illustrative examples, flight information identifier **104** displays aeronautical chart **128** on display system **108**. Aeronautical chart **128** is a map that is used in navigating aircraft **102**. In these illustrative examples, aeronautical chart **128** is information that is displayed on display system **108** rather than a paper chart. Aeronautical chart **128** may include information about items, such as, for

example, without limitation, terrain elevations, airports, communications frequencies, navigation aids, rivers, cities, airspace boundaries, and other suitable information for use in navigating aircraft **102**.

5           The display of aeronautical chart **128** may be based on the location of aircraft **102**. Different aeronautical charts are displayed on display system **108**, depending on the location and altitude of aircraft **102**. In some illustrative examples, aeronautical chart **128** may be displayed as a  
10 "moving map" on display system **108**.

          In this illustrative example, aeronautical chart **128** is displayed on graphical user interface **130** in display system **108**. In these illustrative examples, envelope **118** is displayed on aeronautical chart **128** as defining space **120**  
15 flyable by aircraft **102** that meets number of objectives **122**.

          As a result, operator **132** may obtain situational awareness information about aircraft **102** in a manner that allows aircraft **102** to meet or exceed number of objectives **122**. The display of envelope **118** in aeronautical chart **128**  
20 may be used to reduce the amount of information that is displayed in aeronautical chart **128** for operator **132** to view. By reducing the information to an identification of space **120** flyable by aircraft **102**, operator **132** may more easily make decisions about the operation of aircraft **102**.

25           The reduction information may be, for example, leaving out information not needed by operator **132**. For example, the information may be reduced by not showing or obscuring an area outside of envelope **118**. Other information within envelope **118** would remain visible.

30           In other illustrative examples, the areas outside of envelope **118** may still be displayed. In this example, envelope **118** is displayed in a manner to draw attention to the area within envelope **118**. As a result, the amount of information displayed may not be reduced, but an

identification of information needed by operator **132** is made through the display of envelope **118**.

5 In this manner, operator **132** may need to perform less calculations or analyses to operate aircraft **102**. As a result, operator **132** may be less fatigued and may have more time to perform other tasks. Additionally, with the identification of space **120** flyable by aircraft **102**, errors in calculations by operator **132** may be reduced.

10 For example, an operator may be optimistic about the range that an aircraft can fly. In one illustrative example, an operator may make calculations with results indicating that a target airport may be just out of fuel range. In some cases, the operator may be optimistic about how much fuel may actually be needed to reach the target airport and may still attempt to reach the target airport. 15 In this instance, the aircraft may be out of fuel before reaching the target airport or may not have a desired amount of fuel reserves in case the aircraft encounters poor weather conditions.

20 When changes in information **110** occur during flight of aircraft **102**, those changes may be taken into account by operator **132** more quickly than with currently used systems. In this manner, risk in the operation of aircraft **102** also may be reduced.

25 In these illustrative examples, flight information identifier **104** in computer system **106** may be located in aircraft **102** with operator **132** being a pilot or other suitable operator of aircraft **102**. For example, flight information identifier **104** may be located in a flight management system, an electronic flight bag, or another 30 suitable device in computer system **106**.

In other illustrative examples, flight information identifier **104** may be located in platform **134**. Platform **134** is in a location remote to aircraft **102**. Platform **134** may

be, for example, a building for an airline operations center, a building for an air traffic control service, or some other suitable platform. In other words, computer system **106** with flight information identifier **104** may be  
5 located at a ground location.

When flight information identifier **104** is located in aircraft **102** with operator **132** being a pilot, flight information identifier **104** may operate during some or all of the flight of aircraft **102** to provide information to  
10 operator **132** for use in operating aircraft **102**. Further, in some cases, operator **132** may make projections or changes to flight plans or other parameters for aircraft **102** to determine whether envelope **118** changes with respect to the ability of aircraft **102** to meet number of objectives **122**.

15 In other words, operator **132** may be able to use flight information identifier **104** to perform "what-if" scenarios. For example, operator **132** may change parameters, such as a selection of aircraft types for aircraft **102**. The different types of aircraft may have different reserve fuel  
20 levels required for landing. Further, different types of aircraft also have different cost indexes. As a result, operator **132** may perform planning, which may include selecting a type of aircraft for aircraft **102**.

Additionally, operator **132** may use flight  
25 information identifier **104** before flight of aircraft **102** in planning a flight plan for aircraft **102**. In yet other illustrative examples, when platform **134** is a building at an airline operations center, operator **132** may provide instructions to aircraft **102**. Further, the analysis of  
30 information may be performed for other aircraft in the fleet of aircraft for the airline during the flight of those aircraft. The analysis may be used to make changes in the operation of those aircraft as needed based on envelopes developed for those aircraft meeting desired objectives.

Additionally, the airline may use information in a projected envelope to promote efficiency and maintain on-time departures and arrivals. In other words, an airline may use this information to slightly reroute an aircraft in the  
5 fleet to reach a desired destination on time.

The illustration of aircraft information environment **100** in **Figure 1** is not meant to imply physical or architectural limitations to the manner in which an illustrative embodiment may be implemented. Other  
10 components in addition to or in place of the ones illustrated may be used. Some components may be unnecessary. Also, the blocks are presented to illustrate some functional components. One or more of these blocks may be combined, divided, or combined and divided into different  
15 blocks when implemented in an illustrative embodiment.

Although platform **134** has been described as a building for an airline operations center and a building for an air traffic control surface, platform **134** may take other forms. For example, platform **134** may be a ship, a  
20 spacecraft, or some other suitable type of platform.

Further, computer system **106** has been described as being located in aircraft **102** or in platform **134**. In yet other illustrative examples, computer system **106** may be distributed between aircraft **102** and platform **134** in which  
25 computers in computer system **106** are in communication with each other. In some illustrative examples, computer system **106** may be located in platform **134**, while display system **108** is located in aircraft **102**.

Turning now to **Figure 2**, an illustration of a  
30 block diagram of a graphical user interface is depicted in accordance with an illustrative embodiment. In this depicted example, aeronautical chart **128** may be two-dimensional chart **200**, three-dimensional chart **202**, or some combination thereof.

Further, aeronautical chart **128**, when taking the form of two-dimensional chart **200**, may be displayed as top view **204**, vertical view **206**, or some combination thereof. Top view **204** is a view from the top of aircraft **102** in  
5 **Figure 1** to the ground. Vertical view **206** is a view in the direction that aircraft **102** travels. In particular, vertical view **206** may be a view from the surface of the Earth upward. Vertical view **206** may also be referred to as a vertical situational display.

10 In these illustrative examples, envelope **118** is displayed in graphical user interface **130** in aeronautical chart **128**. As depicted, envelope **118** defines a space in which aircraft **102** is able to meet number of objectives **122** in **Figure 1**. For example, if number of objectives **122** is a  
15 range based on a desired level of fuel reserves, envelope **118** illustrates space in which aircraft **102** may fly and meet that objective.

As depicted, envelope **118** may include neutral space **208** and desirable space **210**. Neutral space **208** is any  
20 space that aircraft **102** may fly to meet number of objectives **122**.

Additionally, desirable space **210** may be any space within envelope **118** that aircraft **102** may fly that may exceed number of objectives **122** by some threshold. For  
25 example, desirable space **210** may be areas where tailwinds are present. Flying in desirable space **210** with tailwinds may increase fuel efficiency to a level greater than required to meet an objective for fuel efficiency by some threshold. The threshold may be selected in different ways,  
30 depending on the implementation. For example, the threshold may be a numerical value, a percentage, a function that calculates a value, or some other suitable form.

Additionally, space outside of envelope **118** is undesirable space **212** in these illustrative examples.

Undesirable space **212** is space in which aircraft **102** should avoid during flight.

In these illustrative examples, neutral space **208**, desirable space **210**, envelope **118**, and undesirable space **212** may be identified in aeronautical chart **128** using number of graphical indicators **214**. Number of graphical indicators **214** may take various forms. For example, without limitation, number of graphical indicators **214** may be at least one of a line, color, shading, cross-hatching, graphic, text, animated graphics, and other suitable types of graphical indicators.

For example, envelope **118** may be defined using a line. Neutral space **208** within envelope **118** may be defined using first color **216**, desirable space **210** may be defined using second color **218**, and undesirable space **212** may be defined using third color **220**.

For example, first color **216** may be blue, and second color **218** may be green. Third color **220** may be selected to obscure or block out a view of terrain or other information on aeronautical chart **128** that is outside of envelope **118**. In one illustrative example, third color **220** may be black or gray.

In these illustrative examples, envelope **118** may change dynamically as information **110** in **Figure 1** changes. As a result, operator **132** does not need to perform new calculations each time information **110** changes in operating aircraft **102**. Instead, operator **132** may view envelope **118** displayed in aeronautical chart **128** to more quickly make decisions on operating aircraft **102**.

The illustration of graphical user interface **130** in **Figure 2** is not meant to imply physical or architectural limitations to the manner in which graphical user interface **130** may display information. For example, although neutral space **208**, desirable space **210**, and undesirable space **212**

have been described as being displayed using colors, other types of graphical indicators may be used in addition to or in place of color. For example, undesirable space **212** may be displayed using third color **220** and cross-hatching.

5 Desirable space **210** may be displayed using second color **218** in which intensity of second color **218** alternates in a flashing manner.

10 In other illustrative examples, shading may be used in a particular color to indicate certain sections within a space. For example, a lighter shade of first color **216** may be used to show when the aircraft is in a space close to undesirable space **212** or a particular condition, such as rain, has begun in a section of neutral space **208**. In this illustrative example, aircraft **102** may still be able  
15 to fly through this section of neutral space **208**, but considerations must be made for the change in weather condition.

In still other illustrative examples, envelope **118** may not distinguish between different types of space. For  
20 example, envelope **118** may only have neutral space **208**. In still other illustrative examples, one or more desirable space in addition to desirable space **210** may be displayed.

These additional desirable spaces may be of different types than desirable space **210**. For example,  
25 desirable space **210** may indicate a desirable space in which tailwinds are present for increased fuel efficiency. Another desirable space may be present that indicates a lack of turbulence for increased comfort of passengers. When more than one type of desirable space is present, these  
30 spaces may overlap each other. This overlap may be indicated with additional graphical indicators to indicate the overlap. For example, flashing colors, animation, or graphical indicators may be used to show the area of overlap

may provide an increased ability to meet or exceed number of objectives **122**.

With reference now to **Figure 3**, an illustration of an envelope displayed in an aeronautical chart in a graphical user interface is depicted in accordance with an illustrative embodiment. In this illustrative example, graphical user interface **300** is an example of an implementation for graphical user interface **130** displayed in display system **108** in **Figure 1**. Aeronautical chart **302** is displayed in graphical user interface **300**. In this illustrative example, aeronautical chart **302** is a moving map.

As depicted, route **304** for an aircraft is displayed on aeronautical chart **302**. Icon **306** is displayed on aeronautical chart **302** in a location corresponding to a location of the aircraft.

Envelope **308** is displayed in aeronautical chart **302**. In this two-dimensional display, undesirable space **310** is an area outside of envelope **308** and is obscured in this illustrative example. In this illustrative example, envelope **308** is displayed using first color **312** and second color **314**. First color **312** identifies neutral space **316** in envelope **308**.

Neutral space **316** in envelope **308** is an area in which a number of objectives can be met. Second color **314** identifies desirable space **318** in envelope **308**. Desirable space **318** identified by second color **314** is an area in which a number of objectives can be met or exceeded by the aircraft flying through desirable space **318**. In this illustrative example, desirable space **318** is an area in which tailwinds are present. When the aircraft flies through desirable space **318** in envelope **308**, the aircraft may reach a target airport more quickly and may be able to fly with greater fuel efficiency.

In this illustrative example, undesirable space **310** is displayed using third color **320**. In this illustrative example, third color **320** may be selected to obscure information in undesirable space **310** on aeronautical chart **302**. In other words, undesirable space **310** may be blacked out or obscured from the view of the operator. Of course, an operator may change the color or remove the color to see information in undesirable space **310**, depending on the particular implementation.

With reference now to **Figure 4**, another illustration of an envelope displayed in an aeronautical chart in a graphical user interface is depicted in accordance with an illustrative embodiment. In this example, desirable space **318** is no longer displayed within envelope **308**. In this example, only neutral space **316** is present. This change in the display of envelope **308** may occur in response to a change in information. For example, when desirable space **318** in **Figure 3** represents a presence of tailwinds, if tailwinds change or are no longer present during the operation of the aircraft, desirable space **318** is no longer displayed within envelope **308**.

Turning now to **Figure 5**, yet another illustration of an envelope displayed in an aeronautical chart in a graphical user interface is depicted in accordance with an illustrative embodiment. In this illustrative example, information for the aircraft has changed during the flight of the aircraft.

In this particular example, the change in information results in a change in the shape of envelope **308**. Further, desirable space **318** also has changed in shape and location as compared to the illustration of envelope **308** in **Figures 3** and **4**.

In this manner, changes in information that affect the flight of the aircraft result in changes in the display

of envelope **308**. Further, the illustration of envelope **308** in **Figures 3-5** is not meant to imply physical or architectural limitations to the manner in which an illustrative embodiment may be implemented. In these  
5 illustrative examples, envelope **308** is displayed as a flight envelope. In other words, envelope **308** illustrates flyable space for an aircraft based on route **304** in a flight plan for the aircraft. In other illustrative examples, envelope **308** may be displayed as a range envelope. In this example,  
10 envelope **308** may be displayed to indicate areas flyable by the aircraft without regard to a particular route or flight plan.

With reference now to **Figure 6**, an illustration of a block diagram of flight information identifier **104** is  
15 depicted in accordance with an illustrative embodiment. As depicted, flight information identifier **104** comprises information retrieval system **600**, situation system **602**, and situation display **604**.

In these illustrative examples, systems **112** in  
20 aircraft **102** in **Figure 1** comprise automatic dependent surveillance broadcast (ADS-B) system **610**, weather information system **612**, and electronic centralized aircraft monitor (ECAM) **614**. Of course, systems **112** may include other systems in addition to or in place of the ones  
25 illustrated in this particular example.

As depicted, inertial measurement system **606** may generate information, such as position, speed, altitude, and other information for aircraft state **114** in **Figure 1** in information **110**. Flight management system **608** may provide  
30 flight plan **117**, a cost index, and other suitable information for aircraft state **114** for aircraft **102**. Automatic dependent surveillance broadcast system **610** may provide information, such as aircraft traffic, traffic

intent, predicted aircraft traffic, and other suitable information.

Weather information system **612** may provide current weather information as well as predicted or forecasted  
5 weather information. Electronic centralized aircraft monitor **614** may provide information, such as, for example, current fuel use, predicted fuel use, and other information.

Information retrieval system **600** is configured to obtain information **110** from systems **112** in these depicted  
10 examples. Information retrieval system **600** is configured to retrieve and process information **110**. In these illustrative examples, information **110** received from systems **112** may be time-tagged. In other words, information **110** may include timestamps. Information retrieval system **600** correlates the  
15 information based on the timestamps.

Further, when predicted information is unavailable, information retrieval system **600** also may provide predictions for various types of information. For example, if electronic centralized aircraft monitor **614** does  
20 not provide an estimated fuel use, information retrieval system **600** may predict fuel use based on past information about current fuel use.

Further, information retrieval system **600** places information **110** in a format useable by situation system **602**.  
25 For example, information retrieval system **600** may use a format with five fields. These fields may be system, time, variable, and projected error. The system identifies a system in systems **112** from which the information in information **110** was received. Time represents the time at  
30 which the information in information **110** was received from the system identified. The variable identifies the parameter. The value is the value of the parameter. Projected error is the estimated error for the value.

For example, information received from inertial measurement system **606** may be as follows: INS, 17:00:00, ALT, 7500m, and 20m. In this example, INS represents inertial measurement system **606**. 17:00:00 is the timestamp  
5 for the information. ALT represents altitude. 7500m is the altitude identified, and 20m is the projected error for the value. Of course, other numbers and types of fields may be used, depending on the particular implementation.

Situation system **602** is configured to identify  
10 envelope **118** based on number of objectives **122** selected for aircraft **102** in **Figure 1**. In particular, situation system **602** may represent the space around aircraft **102** as four-dimensional space **618**. Four-dimensional space **618** is a data structure that identifies space **120** in **Figure 1** in which  
15 aircraft **102** may fly at different points in time. In these illustrative examples, four-dimensional space **618** may be the shape of a cube. In this example, four-dimensional space **618** may take the form of a four-dimensional cube.

In these illustrative examples, four-dimensional  
20 space **618** may be divided into cubes **620**. Each cube in cubes **620** may be marked in a manner that defines envelope **118**. For example, each cube in cubes **620** may be marked to indicate type of space **622**. Type of space **622** may be, for example, selected from one of neutral space **624**, desirable  
25 space **626**, undesirable space **628**, or as some other suitable type of space. Type of space **622** for cubes **620** may be marked based on whether an objective in number of objectives **122** can be met by aircraft **102** flying within a particular cube in cubes **620**.

30 Type of space **622** for cubes **620** also may be marked based on whether an objective in number of objectives **122** can be exceeded by some threshold. Cubes **620** that meet the objective but do not exceed the objective by some threshold are marked as neutral space. Cubes **620** that exceed the

number of objectives by the threshold are marked as desirable space.

If any objective cannot be met in number of objectives **122**, the cube may then be marked as undesirable.

5 The use of neutral space, desirable space, and undesirable space may be suited for when flight information identifier **104** is used in aircraft **102** by operator **132** in **Figure 1**. In this manner, clutter or too much information may be avoided in displaying envelope **118** to operator **132**.

10 Of course, a higher granularity may be present for cubes **620**, depending on the particular implementation. For example, particular types of objectives that are met or exceeded by a threshold may be identified for different points in time. This increased amount of information may be  
15 suitable for when flight information identifier **104** is used on platform **134** in **Figure 1**. Situation display **604** is configured to generate graphical user interface **130** with envelope **118** displayed in aeronautical chart **128** in **Figure 1**. Aeronautical chart **128** may be displayed in two-  
20 dimensions or three-dimensions.

With reference now to **Figure 7**, an illustration of cubes in a four-dimensional space is depicted in accordance with an illustrative embodiment. In this illustrative example, cubes **700** are shown as a pictorial illustration of  
25 cubes **620** for four-dimensional space **618** in **Figure 6**.

In this illustrative example, axis **702** represents altitude, axis **704** represents latitude, and axis **706** represents longitude. Each of cubes **700** contains an indication of whether the space in a particular cube is a  
30 neutral space, a desirable space, or an undesirable space. In these illustrative examples, the indication is made for different points in time. For example, cube **708** may include an indication that this space is a neutral space at one point in time but is an undesirable space in another point

in time. As a result, the state of the cube may change over time.

Of course, in other illustrative examples, each cube may include more-detailed information for different points in time. For example, cube **708** may identify levels of traffic for different points in time in addition to whether the space is neutral, desirable, or undesirable.

With reference now to **Figure 8**, an illustration of a flowchart of a process for displaying information for an aircraft is depicted in accordance with an illustrative embodiment. The process illustrated in **Figure 8** may be used in aircraft information environment **100** in **Figure 1**. In particular, the process may be implemented in flight information identifier **104** in **Figure 1**. This process may be implemented in hardware, software, or a combination of the two.

The process begins by identifying information for an aircraft (operation **800**). The process then identifies an aeronautical chart based on a location of the aircraft (operation **802**).

The process then identifies an envelope that defines a space flyable by the aircraft that meets a number of objectives (operation **804**). In operation **804**, the envelope may be identified using a four-dimensional cube. In one illustrative example, the plurality of cubes may be marked with an indication of a type of space based on the information identified for the aircraft.

The aeronautical chart is displayed on a graphical user interface in a display system (operation **806**). The envelope is displayed in the aeronautical chart (operation **808**), with the process then returning to operation **800**. In operation **808**, the envelope may be displayed using the four-dimensional cube with the type of space marked for the plurality of cubes in the four-dimensional cube. Further,

the envelope may be displayed by obscuring or blacking out the areas of the aeronautical chart that are outside of the envelope. In this manner, information areas in which the aircraft should not operate are not shown for consideration  
5 by the operator. Of course, the operator may opt to see the information if desired. By returning to operation **800**, the process may identify changes to information for the aircraft and update the envelope as needed.

This process may be implemented in an aircraft  
10 during operation of the aircraft. Further, the process also may be used by an operator at a platform that is remote to the aircraft while the aircraft is flying. In still other illustrative examples, the process may be used for planning purposes prior to the flight of the aircraft. Although  
15 information may change during actual flight, performing "what-if" scenarios during a planning process may be useful for selecting types of aircraft for use or for selecting routes and other items.

Turning now to **Figure 9**, an illustration of a  
20 flowchart of a process for processing information for an aircraft to identify an envelope is depicted in accordance with an illustrative embodiment. This process may be implemented in flight information identifier **104** in **Figure 1** and, in particular, in situation system **602** in flight  
25 information identifier **104** in **Figure 6**.

The process begins by identifying cubes for a four-dimensional space (operation **900**). The four-dimensional space may be selected in a number of different ways. For example, the four-dimensional space may be a  
30 space around a route for a flight plan of an aircraft. In another illustrative example, the four-dimensional space may be a selected distance from the current location of the aircraft. The cubes in the four-dimensional space may have different sizes, depending on the particular implementation.

The process selects an unprocessed cube from the cubes in the four-dimensional space (operation **902**). Each cube may have a plurality of entries in which each entry corresponds to a different point in time. A determination  
5 is made as to whether a route of an aircraft from a flight plan intersects the selected cube (operation **904**).

If the route intersects the selected cube, an entry in the cube that corresponds to the time that the aircraft intersects the selected cube is identified  
10 (operation **906**). The process then marks the entry to indicate whether the space in the selected cube is neutral, desirable, or undesirable for that point in time (operation **908**).

With reference again to operation **904**, if the  
15 route does not intersect the selected cube, an identification of the minimum amount of time needed to intersect the cube when deviating from the route is made (operation **910**). The entry for that point in time is identified for the selected cube (operation **912**). The  
20 process then proceeds to operation **908** as described above.

Thereafter, a determination is made as to whether additional unprocessed cubes are present in the four-dimensional space (operation **914**). If additional unprocessed cubes are present, the process returns to  
25 operation **902**. Otherwise, the process terminates.

Turning now to **Figure 10**, an illustration of a data processing system is depicted in accordance with an illustrative embodiment. Data processing system **1000** may be used to implement one or more computers in computer system  
30 **106** in aircraft information environment **100** in **Figure 1**. In this illustrative example, data processing system **1000** includes communications framework **1002**, which provides communications between processor unit **1004**, memory **1006**, persistent storage **1008**, communications unit **1010**,

input/output (I/O) unit **1012**, and display **1014**. In this example, communications framework **1002** may take the form of a bus system.

5 Processor unit **1004** serves to execute instructions for software that may be loaded into memory **1006**. Processor unit **1004** may be a number of processors, a multi-processor core, or some other type of processor, depending on the particular implementation.

10 Memory **1006** and persistent storage **1008** are examples of storage devices **1016**. A storage device is any piece of hardware that is capable of storing information, such as, for example, without limitation, data, program code in functional form, and/or other suitable information either on a temporary basis and/or a permanent basis. Storage  
15 devices **1016** may also be referred to as computer readable storage devices in these illustrative examples. Memory **1006**, in these examples, may be, for example, a random access memory or any other suitable volatile or non-volatile storage device. Persistent storage **1008** may take various  
20 forms, depending on the particular implementation.

For example, persistent storage **1008** may contain one or more components or devices. For example, persistent storage **1008** may be a hard drive, a flash memory, a rewritable optical disk, a rewritable magnetic tape, or some  
25 combination of the above. The media used by persistent storage **1008** also may be removable. For example, a removable hard drive may be used for persistent storage **1008**.

30 Communications unit **1010**, in these illustrative examples, provides for communications with other data processing systems or devices. In these illustrative examples, communications unit **1010** is a network interface card.

Input/output unit **1012** allows for input and output of data with other devices that may be connected to data processing system **1000**. For example, input/output unit **1012** may provide a connection for user input through a keyboard,  
5 a mouse, and/or some other suitable input device. Further, input/output unit **1012** may send output to a printer. Display **1014** provides a mechanism to display information to a user.

Instructions for the operating system,  
10 applications, and/or programs may be located in storage devices **1016**, which are in communication with processor unit **1004** through communications framework **1002**. The processes of the different embodiments may be performed by processor unit **1004** using computer-implemented instructions, which may  
15 be located in a memory, such as memory **1006**.

These instructions are referred to as program code, computer usable program code, or computer readable program code that may be read and executed by a processor in processor unit **1004**. The program code in the different  
20 embodiments may be embodied on different physical or computer readable storage media, such as memory **1006** or persistent storage **1008**.

Program code **1018** is located in a functional form on computer readable media **1020** that is selectively  
25 removable and may be loaded onto or transferred to data processing system **1000** for execution by processor unit **1004**. Program code **1018** and computer readable media **1020** form computer program product **1022** in these illustrative examples. In one example, computer readable media **1020** may  
30 be computer readable storage media **1024** or computer readable signal media **1026**.

In these illustrative examples, computer readable storage media **1024** is a physical or tangible storage device

used to store program code **1018** rather than a medium that propagates or transmits program code **1018**.

Alternatively, program code **1018** may be transferred to data processing system **1000** using computer readable signal media **1026**. Computer readable signal media **1026** may be, for example, a propagated data signal containing program code **1018**. For example, computer readable signal media **1026** may be an electromagnetic signal, an optical signal, and/or any other suitable type of signal. These signals may be transmitted over communications links, such as wireless communications links, optical fiber cable, coaxial cable, a wire, and/or any other suitable type of communications link.

The different components illustrated for data processing system **1000** are not meant to provide architectural limitations to the manner in which different embodiments may be implemented. The different illustrative embodiments may be implemented in a data processing system including components in addition to and/or in place of those illustrated for data processing system **1000**. Other components shown in **Figure 10** can be varied from the illustrative examples shown. The different embodiments may be implemented using any hardware device or system capable of running program code **1018**.

Thus, one or more of the different illustrative embodiments provide a method and apparatus for displaying information for operating an aircraft. In particular, one or more illustrative embodiments may display an envelope on an aeronautical chart on a display system. The envelope identifies a space in which the aircraft may fly that meets a number of objectives.

These objectives may include risk objectives, performance objectives, optimization objectives, and other suitable types of objectives. With the use of one or more

illustrative embodiments, the display of the envelope may reduce the need for an operator of an aircraft to consult numerous different sources of information to operate the aircraft. For example, an operator may avoid looking at  
5 paper charts, an electronic flight bag, and other sources to determine where the aircraft may fly to meet an objective.

Further, with one or more illustrative embodiments, clutter from too much information being displayed also may be avoided. The use of the envelope may  
10 allow an operator to quickly identify the space in which an aircraft may fly. This may be in contrast to the display of weather reports, aircraft state information, or other information on an aeronautical chart on a navigation display. As a result, an operator does not need to find and  
15 analyze information to determine where an aircraft may fly.

The description of the different illustrative embodiments has been presented for purposes of illustration and description and is not intended to be exhaustive or limited to the embodiments in the form disclosed. Many  
20 modifications and variations will be apparent to those of ordinary skill in the art. Further, different illustrative embodiments may provide different features as compared to other illustrative embodiments. The embodiment or embodiments selected are chosen and described in order to  
25 best explain the principles of the embodiments, the practical application, and to enable others of ordinary skill in the art to understand the disclosure for various embodiments with various modifications as are suited to the particular use contemplated.

What is claimed is:

5

1. A method for displaying information (110) for an aircraft (102), the method comprising:  
identifying the information (110) for the aircraft (102);

10 displaying an aeronautical chart (128) on a display system (108); and

displaying an envelope (118) in the aeronautical chart (128) based on the information (110), wherein the envelope (118) defines a space (120) flyable by the aircraft (102)  
15 that meets a number of objectives (122).

2. The method of claim 1, wherein the envelope (118) is displayed in one of two-dimensions and three-dimensions.

20 3. The method of claim 1 further comprising:  
displaying an indication of undesirable space (212) outside of the envelope (118).

4. The method of claim 3, wherein the indication of  
25 undesirable space (212) is a graphical indicator that obscures a portion of the aeronautical chart (128) outside of the envelope (118).

5. The method of claim 1 further comprising:  
30 displaying an indication of desired space (120) within the envelope (118).

6. The method of claim 1 further comprising:

repeating displaying the envelope (118) in the  
aeronautical chart (128) based on the information (110) in  
response to the information (110) changing, wherein the  
envelope (118) defines the space (120) flyable by the  
5 aircraft (102) that meets the number of objectives (122).

7. The method of claim 1, wherein the aeronautical chart  
(128) is selected from at least one of a vertical view (206)  
and a top view (204).

10

8. The method of claim 1, wherein the information (110)  
for the aircraft (102) is selected from at least one of an  
aircraft state (114), environmental information (116), and a  
flight plan (117).

15

9. The method of claim 1, wherein identifying the  
information (110) associated with the aircraft (102);  
displaying the aeronautical chart (128); and displaying the  
envelope (118) in the aeronautical chart (128) based on the  
20 information (110), wherein the envelope (118) defines the  
space (120) flyable by the aircraft (102) that meets the  
number of objectives (122) is performed in a computer system  
(106) in the aircraft (102).

25 10. The method of claim 1, wherein identifying the  
information (110) associated with the aircraft (102);  
displaying the aeronautical chart (128); and displaying the  
envelope (118) in the aeronautical chart (128) based on the  
information (110), wherein the envelope (118) defines the  
30 space (120) flyable by the aircraft (102) that meets the  
number of objectives (122) is performed in a computer system  
(106) at a ground location.

11. The method of claim 1, wherein the number of objectives (122) comprises at least one of a risk objective (124), an optimization objective (126), and a legal objective (127).

5

12. The method of claim 1 further comprising:  
generating a four-dimensional cube comprised of a plurality of cubes; and

10 marking the plurality of cubes with an indication of a type of space (120) based on the information (110),  
wherein, the step of displaying the envelope (118) comprises:

displaying the envelope (118) using the four-dimensional cube with the type of space (120) marked for the plurality  
15 of cubes in the four-dimensional cube.

13. A navigation system comprising:

a display system (108); and

a flight information (110) identifier configured to  
20 identify information (110) for an aircraft (102); display an aeronautical chart (128) on the display system (108); and display an envelope (118) in the aeronautical chart (128) based on the information (110), wherein the envelope (118) defines a space (120) flyable by the aircraft (102) that  
25 meets a number of objectives (122).

14. The navigation system of claim 13, wherein the envelope (118) is displayed in one of two-dimensions and three-dimensions.

30

15. The navigation system of claim 13, wherein the flight information (110) identifier is configured to display an indication of undesirable space (212) outside of the envelope (118).

16. The navigation system of claim 15, wherein the indication of undesirable space (212) is a graphical indicator that obscures a portion of the aeronautical chart (128) outside of the envelope (118).

17. The navigation system of claim 13, wherein the flight information (110) identifier is configured to display an indication of desired space (120) within the envelope (118).

18. The navigation system of claim 13, wherein the flight information (110) identifier is further configured to repeat displaying the envelope (118) in the aeronautical chart (128) based on the information (110) in response to the information (110) changing, wherein the envelope (118) defines the space (120) flyable by the aircraft (102) that meets the number of objectives (122).

19. The navigation system of claim 13, wherein the aeronautical chart (128) is selected from at least one of a vertical view (206) and a top view (204).

20. The navigation system of claim 13, wherein the flight information (110) identifier is further configured to generate a four-dimensional cube comprised of a plurality of cubes and mark the plurality of cubes with an indication of a type of space (120) based on the information (110), and wherein in being configured to display the envelope (118) in the aeronautical chart (128) based on the information (110), the flight information (110) identifier is configured to display the envelope (118) using the four-dimensional cube with the type of space (120) marked for the plurality of cubes in the four-dimensional cube.