

-1-

DUCTED OPPOSING BONDED FIN HEAT SINK BLOWER
MULTI-MICROPROCESSOR COOLING SYSTEM

BACKGROUND OF THE INVENTION

Field of the Invention

The present invention relates to a heat sink cooling system for an integrated circuit package in an enclosed computer system.

Description of Related Art

Integrated circuits (ICs) are typically housed within a plastic or ceramic package. The packages have leads or surface pads that are soldered to a printed circuit board. The circuit board and package are often located within a computer chassis which contains a fan that removes the heat generated by the IC.

It is desirable to have a high rate of heat transfer from the IC package in order to maintain the junction temperatures of the integrated circuit within safe operating limits. Excessive IC junction temperatures may affect the performance of the circuit and cause a permanent degradation of the IC. Heat sinks are sometimes mounted to the top surface of the package housing to increase the thermal performance of the package. Conventional heat sinks typically have a plurality of fins that extend from a bottom base portion. The fins increase the surface area of the heat sink and the heat transfer rate of the package.

Microprocessors are a type of IC which often require a heat sink. For high performance microprocessors employed in an enclosed computer system, a high heat transfer rate is particularly important since the interior operating environment of typical computers is 10°C to 25°C above that of the air exterior to the enclosed computer system.

Several methods have been employed for cooling such high performance microprocessors. A common method of cooling such a microprocessor is by the use of a fan heat sink, in which an axial fan is attached to the heat sink atop the microprocessor in order to blow air

-2-

across the heat sink to remove the heat dissipated by the microprocessor. To date, the best fan heat sinks are not thermally efficient enough to cool the higher powered new microprocessors.

One method of increasing the fan heat sink's efficiency, or lowering its thermal resistance, is to increase the speed of rotation of the fan prop, thereby forcing more air through the heat sink. The problem with this method is that at higher speeds of rotation, the fan consumes more power, further heating the fan motor bearings. Reliability of the fan heat sinks is a key concern for these high performance microprocessors. One failure mechanism of these small fans is a breakdown of the lubrication used in the bearings, which results at higher operating temperatures. Fan heat sinks have a drawback that they often require a system fan to move the heated air dissipated by the fan heat sink and to prevent recirculation of the heated air back to the fan heat sink.

Additionally, fan heat sinks have the drawback of having to operate in the elevated-temperature environment of the enclosed computer system. Subsequently, the fan heat sinks can encounter reliability problems due to operation at the elevated temperatures. Fan heat sinks also pose assembling problems since both a heat sink and a fan must be attached to each microprocessor.

Another approach is the use of passive heat sinks in combination with an axial system fan, but the large surface area requirements result in heat sink volumes that are too large for the typical computer chassis design.

Another approach involves the use of a liquid coolant to move the dissipated heat away from the microprocessor. Liquid cooling, however, is the least desirable and most expensive approach.

Accordingly, it would be advantageous to provide a reliable heat sink cooling system design. It would also be advantageous to provide a heat sink design which physically decouples the air mover (fan) from the heat sink.

-3-

It would also be advantageous to provide a cheap, easily constructed heat sink to efficiently dissipate the heat generated by the microprocessors.

SUMMARY OF THE INVENTION

A device and method is described herein for cooling an integrated circuit package—in particular, a microprocessor. The device and method are particularly useful for cooling high performance microprocessors, which can dissipate over 30W of heat.

A microprocessor with a heat sink attached atop operates within a computer chassis. A blower, which has an air intake from a source external to the computer chassis, provides an air stream at its output. A first air duct is coupled to the blower, and a first ducted heat sink is coupled to the first air duct. The air stream flows through the first air duct and through the first ducted heat sink, thereby cooling the attached microprocessor.

A second air duct can be connected to the first ducted heat sink for directing the air stream to a second ducted heat sink in order to cool a second microprocessor attached to the second ducted heat sink. Although the air stream is slightly preheated from the heat dissipated from the first microprocessor, the air stream is still able to dissipate heat from the second microprocessor.

A ducted heat sink is required for the cooling system previously described. An opposing bonded fin heat sink is easily constructed using two extruded heat sinks. The two extruded heat sinks are attached such that the fins of one of the heat sinks are interleaved with the fins of the other heat sink. In the described embodiment, the heat sinks are attached by thermally conductive epoxy. Other methods of attachment include soldering, welding, or simply friction contact.

The cooling system can be employed to cool modular add-in cards, motherboards, and other electronic components in addition to microprocessors.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a block diagram of the ducted opposing bonded fin heat sink cooling system 100.

Fig. 2 is an alternative block diagram of the ducted opposing bonded fin heat sink cooling system 100.

Fig. 3A is a diagram of a ducted opposing bonded fin heat sink 300 before attachment.

Fig. 3B is a representation of a ducted opposing bonded fin heat sink 300 after attachment.

Fig. 4 is a representation of a cooling design for channeling air to two microprocessors as well as other electronic components.

Fig. 5 is a representation showing how the air channel of Fig. 4 can be coupled to a blower 510.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Figures 1 through 5 of the drawings disclose various embodiments of the present invention for purposes of illustration only. One skilled in the art will readily recognize from the following discussion that alternative embodiments of the structures and methods illustrated herein may be employed without departing from the principles of the invention. The following description may include specific numbers and quantities associated with the device and methods described herein. It should be apparent to one skilled in the art that these numbers and quantities are utilized herein for illustrative purposes.

Fig. 1 shows a block diagram of the ducted opposing bonded fin heat sink cooling system 100. The cooling system 100 is comprised of three main elements: a blower 110, a first air duct 120, and a first ducted heat sink 130. The blower 110 has an air intake 135 which allows the blower to receive air from a source external to the computer chassis 180. The blower 110 is coupled to the first air duct 120. The first air duct 120 is coupled to the first ducted heat sink 130. The cooling system can additionally include a second air duct 140 and a second ducted heat sink 150. The second air duct 140 couples the first ducted heat sink 130 to the second ducted heat sink 150.

The first ducted heat sink 130 is attached to a first microprocessor 160. The first ducted heat sink 130 dissipates heat from the first microprocessor 160. Similarly, the second ducted heat sink 150 is attached to a second microprocessor 170. The second ducted heat sink 150 dissipates heat from the second microprocessor 170.

In the described embodiment, the blower 110 is located in the interior of the computer chassis 180. A vent 190 in the computer chassis 180 allows air from the exterior of the computer chassis 180 to enter the blower 110. Alternatively, referring to Fig. 2, an intake air duct 205 can be employed to couple the air intake 135 of the blower 110 to an air source exterior to the computer chassis 180. Although the

-7-

blower 110 could also be located exterior to the computer chassis 180, this is less desirable for noise and safety reasons.

In any case, the blower 110 can receive air from the exterior of the computer chassis 180 and provides an air stream which flows through the first air duct 120, through the first ducted heat sink 130, through the second air duct 140, and through the second ducted heat sink 150.

It should be noted that the blower 110, the first air duct 120, the first ducted heat sink 130, the second air duct 140, and the second ducted heat sink 150 may all be detachable as required to meet assembly and manufacturing constraints as well as normal consumer modifications to the computer system.

It should also be noted that the cooling system must be designed such that the second microprocessor 170 has proper cooling since the air stream used to dissipate the heat of the second microprocessor 170 has been slightly preheated from the heat dissipated from the first microprocessor 160.

In the described embodiment, the blower 110 provides the static air pressure required to force air from the exterior of the system through the air intake duct and eventually through the ducted heat sinks 130 and 150 on the two microprocessors 160 and 170, which are cooled in series. The static pressure produced by the blower 110 is approximately three times that produced by axial fans. The blower 110 produces enough static pressure to generate high air velocities through the narrow heat sink channels. The resulting cooling system is very efficient. The air flow volume from the blower 110 is constrained such that all the air from the blower 110 is forced through the ducted heat sinks 130 and 150.

Axial fans are not capable of producing the required static pressure for generating such high air flow volumes. In current axial fan cooled systems, only a small amount of air from the system fan goes through the microprocessor heat sinks. This is even the case when the microprocessors are located directly in front of the axial fan near the motor. Thus, in the axial fan approach, only a small

-8-

percentage of the air actually goes through the microprocessor's heat sinks, as opposed to the ducted heat sink approach using a blower 110 where all the air is forced through the ducted heat sinks 130 and 150 by the blower 110.

Additionally, the blower 110 may be thermally controlled so as to increase air flow when more cooling is required and decrease air flow when less cooling is required.

Reference is now made to Fig. 3A, which is a diagram of a ducted opposing bonded fin heat sink 300. The opposing bonded fin heat sink 300 is comprised of two identical extruded heat sinks 305 and 310. Each of the extruded heat sinks 305 and 310 are comprised of a base portion 312 and a plurality of fins 314 projecting transverse to the base portion 312.

The extruded heat sink 305 is inverted and rotated 180° from the extruded heat sink 310. The two extruded heat sinks 305 and 310 are then glued together with a thermally conductive epoxy. The presence of grooves 315 in each of the extruded heat sinks 305 and 310 allows for the placement of the fins of the opposite extruded heat sink. Figure 3B shows extruded heat sinks 305 and 310 attached together.

Heat sinks typically require a large surface area to dissipate the heat from a microprocessor. For high efficiency, the air gaps between the fins must be very tall and narrow, as viewed from the end of the heat sink. An aspect ratio is the ratio of the air gap height to the air gap width for a given heat sink channel. Typically, the maximum aspect ratio for an extruded heat sink is 4 to 1. The requirements of high-power dissipating microprocessor heat sinks is about 10 to 1. By attaching the two extruded heat sinks 305 and 310 as described above, an effective aspect ratio of the opposing bonded heat sink 300 is created of approximately 10 to 1.

The opposing bonded heat sink 300 has the advantage of being cheap and easy to manufacture compared to other heat sinks with a comparable aspect ratio. To attain this same aspect ratio using conventional heat sink designs would require machining or individually gluing fin plates into a base plate at a cost of two to three

-9-

times more per heat sink. In addition, these complex heat sinks would still require a shroud over the top in order to duct air flow through the heat sink. Conversely, the opposing bonded heat sink 300 has the advantage of automatically providing a duct (or a series of ducts) so that air flow from the blower 110 flows through the opposing bonded heat sink 300. A side benefit of the opposing bonded heat sink 300 is that the top surface can be used for labels.

Reference is now made to Fig. 4, which is a representation of a cooling design for channeling air to two microprocessors 415 and 420 as well as other electronic components. The above described cooling system can be employed to cool modular add-in cards, motherboards, and other electronic components in addition to microprocessors.

The connecting duct lengths, cross sectional area, and implementation details can vary depending on the system's design and microprocessor placement. Many variations of this invention can be realized using these basic ingredients of modifying and reorienting the air ducts. For example, in some cases, the system's axial fan can be directly replaced by the blower, thus minimizing the cost of the cooling system.

Fig. 4 shows the creation of an air channel by using a molded plastic cover 410. This molded plastic cover 410 encloses two microprocessors 415 and 420 along with two ducted heat sinks 425 and 430 as well as other electronic components.

Fig. 5 is a representation showing how the air channel of Fig. 4 can be coupled to a blower 510 in order to cool the two microprocessors 415 and 420 as well as the other electronic components within the molded plastic cover 410.

From the above description, it will be apparent that the invention disclosed herein provides a novel and advantageous heat sink cooling system. The foregoing discussion discloses and describes exemplary methods and embodiments of the present invention. As will be understood by those familiar with the art, the invention may be embodied in other specific forms without departing from its spirit or essential characteristics, and thus, the described embodiment is not

-10-

restrictive of the scope of the invention. The following claims are indicative of the scope of the invention. All variations which come within the meaning and range of equivalency of the claims are to be embraced within their scope.

This Sheet Has Been Replaced



-12-

coupled to said first extruded heat sink to create a ducted heat sink with one or more ducts running through the ducted heat sink.

6. The cooling system of Claim 5 wherein said integrated circuit package is a microprocessor.

7. The cooling system of Claim 6 further comprising:
a second heat sink connected to a second microprocessor;
and
a second air duct connecting said first heat sink to said second heat sink.

8. The cooling system of Claim 1 wherein said integrated circuit package is a microprocessor.

9. The cooling system of Claim 8 further comprising:
a second heat sink connected to a second microprocessor;
and
a second air duct connecting said first heat sink to said second heat sink.

10. The cooling system of Claim 1 wherein said first heat sink is an opposing bonded heat sink comprised of:

a first extruded heat sink comprising a first base portion and a plurality of fins projecting transverse to said first base portion; and
a second extruded heat sink comprising a second base portion and a plurality of fins projecting transverse to said second base portion, said second extruded heat sink coupled to said first extruded heat sink to create a ducted heat sink with one or more ducts running through the ducted heat sink.




-11-

CLAIMS


WHAT IS CLAIMED IS:

1. In an enclosed computer system which has an integrated circuit package, a cooling system comprising:
 - a blower with an air intake from the exterior of said enclosed computer system for providing an air flow;
 - a first heat sink attached to said integrated circuit package;
 - and
 - a first air duct coupling said blower to said heat sink.
2. The cooling system of Claim 1 further comprising an intake air duct, one end of which is coupled to the exterior of said computer system and the other end of which is coupled to said blower for providing said air intake from the exterior of said computer system.
3. The cooling system of Claim 2 wherein said integrated circuit package is a microprocessor.
4. The cooling system of Claim 3 further comprising:
 - a second heat sink connected to a second microprocessor;
 - and
 - a second air duct connecting said first heat sink to said second heat sink.
5. The cooling system of Claim 2 wherein said first heat sink is an opposing bonded heat sink comprised of:
 - a first extruded heat sink comprising a first base portion and a plurality of fins projecting transverse to said first base portion; and
 - a second extruded heat sink comprising a second base portion and a plurality of fins projecting transverse to said second base portion, said second extruded heat sink



-14-

17. The cooling system of Claim 16 wherein said integrated circuit package is a microprocessor.
18. The cooling system of Claim 17 further comprising:
 - a second heat sink means connected to a second microprocessor; and
 - a second air channel means connecting said first heat sink means to said second heat sink means.
19. The cooling system of Claim 16 wherein said heat sink means is an opposing bonded heat sink means comprised of:
 - a first extruded heat sink means comprising a first base portion and a plurality of fins projecting transverse to said first base portion; and
 - a second extruded heat sink means comprising a second base portion and a plurality of fins projecting transverse to said second base portion, said second extruded heat sink means coupled to said first extruded heat sink means to create a ducted heat sink means with one or more ducts running through the ducted heat sink means.
20. The cooling system of Claim 19 wherein said integrated circuit package is a microprocessor.
21. The cooling system of Claim 20 further comprising:
 - a second heat sink means connected to a second microprocessor; and
 - a second air channel means connecting said first heat sink means to said second heat sink means.
22. The cooling system of Claim 15 wherein said integrated circuit package is a microprocessor.
23. The cooling system of Claim 22 further comprising:



-13-

11. The cooling system of Claim 10 wherein said integrated circuit package is a microprocessor.
12. The cooling system of Claim 11 further comprising:
 - a second heat sink connected to a second microprocessor;
 - and
 - a second air duct connecting said first heat sink to said second heat sink.
13. The cooling system of Claim 1 wherein said blower is thermally controlled to increase the air flow when said integrated circuit package requires more cooling and decrease the air flow when said integrated circuit package requires less cooling.
14. The cooling system of Claim 1 wherein said first heat sink is a ducted heat sink having one or more ducts for allowing air to flow through the ducted heat sink.
15. In an enclosed computer system which has an integrated circuit package, a cooling system comprising:
 - a blowing means with an air intake from the exterior of said enclosed computer system for providing an air flow;
 - a first heat sink means attached to said integrated circuit package; and
 - an air channel means connecting said blowing means to said heat sink means.
16. The cooling system of Claim 15 further comprising an intake air channel means, one end of which is coupled to the exterior of said computer system and the other end of which is coupled to said blowing means for providing said air intake from the exterior of said computer system.


This Sheet Has Been Replaced



-16-



29. An opposing bonded heat sink comprised of:
- a first extruded heat sink comprising a first base portion and a first plurality of fins projecting transverse to said first base portion; and
 - a second extruded heat sink comprising a second base portion and a second plurality of fins projecting transverse to said second base portion, said second extruded heat sink coupled to said first extruded heat sink to create a ducted heat sink with one or more ducts running through the ducted heat sink.
30. The opposing bonded heat sink of Claim 29 wherein said first base portion of the first extruded heat sink includes a first plurality of grooves, said first plurality of grooves providing a receptacle for a portion of the second plurality of fins of the second extruded heat sink, and said second base portion of the second extruded heat sink includes a second plurality of grooves providing a receptacle for a portion of the first plurality of fins of the first extruded heat sink.
31. In a computer system enclosed in a computer chassis, said computer system including a blower, a first air duct, and a first heat sink attached to one or more integrated circuit packages, a cooling method comprising the step of:
- a) employing said blower for providing an air stream originating from a source external to said computer chassis through said first air duct to said first heat sink.
32. The cooling method of claim 31 wherein the first heat sink is a ducted heat sink having ducts running through it, and the air stream flows through said ducted heat sink.
33. The cooling method of Claim 32 further comprising the steps of:



-15-

a second heat sink means connected to a second microprocessor; and
a second air channel means connecting said first heat sink means to said second heat sink means.

24. The cooling system of Claim 15 wherein said heat sink means is an opposing bonded heat sink means comprised of:

a first extruded heat sink means comprising a first base portion and a plurality of fins projecting transverse to said first base portion; and
a second extruded heat sink means comprising a second base portion and a plurality of fins projecting transverse to said second base portion, said second extruded heat sink means coupled to said first extruded heat sink means to create a ducted heat sink means with one or more ducts running through the ducted heat sink means.

25. The cooling system of Claim 24 wherein said integrated circuit package is a microprocessor.

26. The cooling system of Claim 25 further comprising:

a second heat sink means connected to a second microprocessor; and
a second air channel means connecting said first heat sink means to said second heat sink means.

27. The cooling system of Claim 15 wherein said blowing means is thermally controlled to increase the air flow when said integrated circuit package requires more cooling and decrease the air flow when said integrated circuit package requires less cooling.

28. The cooling system of Claim 15 wherein said first heat sink means is a ducted heat sink means having one or more ducts for allowing air to flow through the ducted heat sink means.



This Sheet Has Been Replaced



-17-

- b) providing said air stream through a second air duct; and
- c) providing said air stream through a second ducted heat sink.

34. In a computer system enclosed in a computer chassis, said computer system including a blowing means, a first air channel means, and a first heat sink means attached to one or more integrated circuit packages, a cooling method comprising the step of:

- a) employing said blowing means for providing an air stream originating from a source external to said computer chassis through said first air channel means to said first heat sink means.

35. The cooling method of claim 34 wherein the first heat sink means is a ducted heat sink means having ducts running through it, and the air stream flows through said ducted heat sink means.

36. The cooling method of Claim 35 further comprising the steps of:

- b) providing said air stream through a second air channel means; and
- c) providing said air stream through a second ducted heat sink means.

37. A method of combining a first extruded heat sink having a plurality of fins projecting from a base portion and a second extruded heat sink having a plurality of fins projecting from a different base portion, said method comprising the step of:

- using an attachment means to attach the first extruded heat sink to the second extruded heat sink to form a combined heat sink such that one or more ducts are created running through the combined heat sink.



THIS SHEET HAS BEEN
REPLACED





-18-

38. The method of claim 37 wherein the attachment means is performed by a thermally conductive glue.


1/4

**FIGURE 1****FIGURE 2**

2/4

**FIGURE 3A****FIGURE 3B**

3/4

**FIGURE 4**

4/ 4




FIGURE 5

**REPLACEMENT SHEET**Date : **06 SEP 1997**

-1-


CLAIMS**REPLACEMENT SHEETS SG**

- ☐ Description : paged to paged
☒ Claim(s) : paged **1** to paged **7**
☐ Drawing(s) : paged to paged
☒ Abstract : paged **8** to paged **.....**

DATE OF RECEIPT **6-9-97****WHAT IS CLAIMED IS:**

1. A cooling system for cooling an electrical component of a computer system comprising:
 - (1) a blower;
 - (2) a first opposing bonded heat sink coupled to the electrical component, the first opposing bonded heat sink comprising
 - (A) a first extruded heat sink comprising a first base portion and a first plurality of fins projecting transverse to the first base portion; and
 - (B) a second extruded heat sink comprising a second base portion and a second plurality of fins projecting transverse to the second base portion, the second extruded heat sink coupled to the first extruded heat sink such that the first and the second pluralities of fins interlock to form one or more ducts running through the first opposing bonded heat sink, wherein a heat sink face including the one or more ducts defines a heat sink surface area; and
 - (3) a first air duct coupling the blower to the one or more ducts of the first opposing bonded heat sink, the first air duct providing an air flow path therein, wherein the first air duct has a cross sectional area in a plane perpendicular to the air


AMENDED SHEET




-2-

flow path, wherein the cross sectional area is substantially the same throughout the first air duct, and wherein the cross sectional area is substantially the same as the heat sink surface area.

2. The cooling system of claim 1 wherein the electrical component is a processor.
3. The cooling system of claim 1 wherein the electrical component is an integrated circuit.
4. The cooling system of claim 1 further comprising:
an intake air duct connecting an air intake of the blower to the next exterior of the computer system.
5. The cooling system of claim 1 further comprising:
an intake air duct connecting an air intake of the blower to the exterior of the computer system, wherein the intake air duct connects to the exterior of the computer system at a base area of the computer system.
6. The cooling system of Claim 1 wherein the blower is coupled to provide an air flow in a direction perpendicular to the one or more ducts of the first opposing bonded heat sink, and wherein the blower, the first air duct and the first opposing bonded heat sink are coupled in an L-shaped configuration.
7. The cooling system of claim 1 further comprising:





-3-

(4) a second opposing bonded heat sink connected to a second processor, the second opposing bonded heat sink comprising

(A) a third extruded heat sink comprising a third base portion and a third plurality of fins projecting transverse to the third base portion;

(B) a fourth extruded heat sink comprising a fourth base portion and a fourth plurality of fins projecting transverse to the fourth base portion, the fourth extruded heat sink coupled to the third extruded heat sink such that the third and the fourth pluralities of fins interlock to form a second plurality of ducts running through the second opposing bonded heat sink; and

(5) a second air duct connecting the first opposing bonded heat sink to the second opposing heat sink.

8. A cooling system for a computer including a processor comprising:


(1) a blower;

(2) a first opposing bonded heat sink coupled to the processor, the first opposing bonded heat sink comprising

(A) a first extruded heat sink comprising a first base portion and a first plurality of fins projecting transverse to the first base portion;

(B) a second extruded heat sink comprising a second base portion and a second plurality of fins projecting transverse to the second base portion, the second extruded heat sink coupled to the first extruded heat sink such that the first and the second pluralities of fins interlock to form

AMENDED SHEET



-4-

one or more ducts running through the first opposing bonded heat sink, wherein a heat sink face including the one or more ducts defines a heat sink surface area; and

(3) a first air duct connecting the blower to the one or more ducts of the first opposing bonded heat sink, the first air duct providing an air flow path therein, wherein the first air duct has a cross sectional area in a plane perpendicular to the air flow path at, wherein the cross sectional area is substantially the same through the first air duct, wherein the cross sectional area is substantially the same as the heat sink surface area, and wherein the air flow path is directionally redirected within the first air duct by approximately ninety degrees.


9. The cooling system of claim 8 further comprising:

(4) a second opposing bonded heat sink connected to a second processor, the second opposing bonded heat sink comprising

(A) a third extruded heat sink comprising a third base portion and a third plurality of fins projecting transverse to the third base portion;

(B) a fourth extruded heat sink comprising a fourth base portion and a fourth plurality of fins projecting transverse to the fourth base portion, the fourth extruded heat sink coupled to the third extruded heat sink such that the third and the fourth pluralities of fins interlock to form a second plurality of ducts funning through the second opposing bonded heat sink; and

AMENDED SHEET



-5-

(5) a second air duct connecting the first opposing bonded heat sink to the second opposing bonded heat sink.

10. A cooling system for a computer system including a processor comprising:

(1) a blower means;


(2) a first opposing bonded heat sink means coupled to the processor, the first opposing bonded heat sink means comprising two extruded heat sinks, each of the extruded heat sinks being a single unit comprising a base portion and a plurality of fins projecting transverse to the base portion, wherein the plurality of fins of each of the extruded heat sinks interlock, wherein a heat sink face including the one or more ducts defines a heat sink surface area; and

11) A cooling system for a computer system including a processor comprising:

(1) a blower means;

(2) a first opposing bonded heat sink means coupled to the processor, the first opposing bonded heat sink means comprising two extruded heat sinks; each of the extruded heat sinks being a single unit comprising a base portion and a plurality of fins projecting transverse to the base portion, wherein the plurality of fins of each of the extruded heat sinks interlock, wherein a heat sink face including the one or more ducts defines a heat sink surface area; and

AMENDED SHEET



-6-

(3) a first air duct coupling the blower means to the first opposing bonded heat sink means, the first air duct means providing an air flow path therein, wherein the first air duct means has a cross sectional area in a plane perpendicular to the air flow path, wherein the cross sectional area is substantially the same throughout the first air duct means, and wherein the cross sectional area is substantially the same as the heat sink surface area.

12) The cooling system of claim 11 further comprising:


an intake air duct means for coupling an air intake of the blower means to the exterior of the computer system.


13) The cooling system of claim 11 further comprising:

an intake air duct means for coupling an air intake of the blower means to the exterior of the computer system, wherein the intake air duct means connects to the exterior of the computer system at a base area of the computer system.

14) In a cooling system enclosed in a computer chassis, the cooling system comprising a blower, an air duct, and a ducted heat sink attached to an integrated circuit package, the ducted heat sink having a plurality of ducts running through it, a cooling method comprising the steps of:

(a) employing the blower to draw air in from a source external to the computer chassis to create an air stream;






-7-

(b) providing the air stream through the air duct, wherein the air duct has a cross sectional area in a plane perpendicular to the air stream, wherein the cross sectional area is substantially the same throughout the air ducts, wherein the air stream has a first direction upon entering the air duct and the air stream has a second direction upon exiting the air duct wherein the first direction is substantially perpendicular to the second direction; and


(c) providing the air stream into the plurality of ducts of the ducted heat sink.



DUCTED OPPOSING BONDED FIN HEAT SINK BLOWER
MULTI-MICROPROCESSOR COOLING SYSTEM

ABSTRACT OF THE DISCLOSURE

A device and method for cooling an integrated circuit package—in particular, a microprocessor—within an enclosed computer system. The device comprises a blower, a first heat sink attached to the microprocessor, and a first air duct coupling the blower to the first heat sink. The blower has an air intake from the exterior of the computer system. The blower generates an air stream which flows through the first air duct to the first heat sink for cooling the first microprocessor. A second air duct connected to the first heat sink may be used to subsequently direct the air stream to a second heat sink for cooling a second microprocessor. An efficient ducted heat sink for use in this cooling system can be easily constructed by attaching two extruded heat sinks.




AMENDED SHEET



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H05K 7/20	A1	(11) International Publication Number: WO 96/01035 (43) International Publication Date: 11 January 1996 (11.01.96)
(21) International Application Number: PCT/US95/06769 (22) International Filing Date: 25 May 1995 (25.05.95) (30) Priority Data: 08/269,431 30 June 1994 (30.06.94) ✓ US (71) Applicant: INTEL CORPORATION [US/US]; 2200 Mission College Boulevard, Santa Clara, CA 95052 (US). (72) Inventor: NELSON, Daryl, J.; 1184 N.W. 175th Place, Beaverton, OR 97006 (US). (74) Agents: SALTER, James, H. et al.; Blakely, Sokoloff, Taylor & Zafman, 7th floor, 12400 Wilshire Boulevard, Los Angeles, CA 90025-1026 (US).	(81) Designated States: AM, AT, AT (Utility model), AU, BB, BG, BR, BY, CA, CH, CN, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), EE, ES, FI, FI (Utility model), GB, GE, HU, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LT, LU, LV, MD, MG, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), TJ, TM, TT, UA, UG, UZ, VN, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG), ARIPO patent (KE, MW, SD, SZ, UG). Published With international search report. <div style="font-size: 2em; font-family: cursive;">SG 9612195-9</div>	

(54) Title: DUCTED OPPOSING BONDED FIN HEAT SINK BLOWER MULTI-MICROPROCESSOR COOLING SYSTEM



(57) Abstract

A device and method for cooling an integrated circuit package - in particular, a microprocessor - within an enclosed computer system. The device comprises a blower (110), a first heat sink (130) attached to the microprocessor, and a first air duct (120) coupling the blower (110) to the first heat sink (130). The blower (110) has an air intake (135) from the exterior of the computer system. The blower (110) generates an air stream which flows through the first air duct (120) to the first heat sink (130) for cooling the first microprocessor (160). A second air duct (140) connected to the first heat sink (130) may be used to subsequently direct the air stream to a second heat sink (150) for cooling a second microprocessor (170). An efficient duct heat sink for use in this cooling system (100) can be easily constructed by attaching two extruded heat sinks.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

9612193-9