

Valve Assembly

The present invention relates to a valve assembly for use with, for example radiators or other liquid holding containers or reservoirs (hereinafter in the specification and claims simply called "reservoirs")
5 integrated or to be integrated into a piped liquid system.

WO 91/09248 discloses a two part radiator valve assembly for use in closing off a water supply to enable a radiator to be removed. The valve assembly has two mutually opposed valves, each of which comprises a casing in which a through passage is defined, the passages having at contiguous
10 ends internally circumferential valve seats against which respective movable conical valve members are spring biased by respective closing springs, the valve members engaging each other when the valves are placed together to urge the valve members away from the respective valve seats to open the valves. A bayonet coupling sleeve extending between the valve casings to hold the valves
15 together. The casing of the upper of the two valves has an extension accommodating a flow regulating control valve at its distal end, the extension having a branch to be connected to a radiator. Release of the bayonet coupling sleeve allows the valves to separate, automatically closing both valves under the action of the respective closing springs.

A problem with the abovementioned known valve assembly is that the flow rate of liquid through the
20 aligned through passages of the valves causes a resultant force to act on the valve members. At sufficiently high flow rates, such biasing force may be sufficient to displace the valve members from their neutral, mutually open position, against the biasing force of the closing spring of the upstream valve member until the downstream valve member is brought into engagement with its valve seat, closing off flow through the valve assembly.

25

An object of the present invention is to obviate or mitigate this disadvantage.

According to the present invention there is provided a valve assembly comprising mutually opposed first and second valves, each of which comprises a casing in which a through passage is defined, the
30 through passages having, at contiguous ends, internally circumferential valve seats against which respective movable valve members are biased, the respective valve members of the first and second valves engaging one another when the first and second valves are brought together to urge the valve members away from their respective seats to open the first and second valves, a coupling member being provided for holding the first and second valves together wherein means are provided for
35 limiting the travel of the valve member of at least one of the first and second valves away from its valve seat to prevent the valve member of the other of the first and second valves from engaging its valve seat when the first and second valves are together, thus preventing said other of the first and second valves from closing due to the flow of fluid through the valve assembly.

40 Preferably the casing of the first valve includes an extension accommodating a flow regulating control valve at its distal end, the extension having a branch to be connected to a reservoir. The

control valve may be manually operable. Alternatively, the control valve may be thermostatically controlled.

Preferably the upstream valve of the first and second valves in the normal direction of flow, in use,
5 through the valve assembly, is provided with means for limiting the travel of said upstream valve to prevent closure of the downstream valve due to the flow of fluid through the valve assembly.

In one embodiment, the travel limiting means comprises the respective biasing means of the at least one of the first and second valves. The biasing means may comprise a coil spring, wherein the
10 dimensions of the spring are selected such that the spring becomes coil bound at said limit of travel of the associated valve member.

Preferably said coil spring acts between a face of the associated valve member and a spring seat located within the respective through passage of said at least one of the first and second valves.
15 Preferably at least one flow passage is provided through or around the spring seat to allow fluid to flow through the valve assembly when the spring is coil bound. In one embodiment, the spring seat comprises an elongate member extending between the inner sides of the through passage. Preferably said elongate member is provided with a through hole for receiving a spring supporting extension the respective valve member. The spring seat may be retained in place with the
20 associated through passage by means of a retaining member located within the through passage. The retaining member may comprise a circlip or a threaded member.

Where the first valve is provided with a return spring adapted to define a travel limiting means, the spring seat may be retained in place by a valve seat of the flow regulating control valve, said valve
25 seat being removably mounted within the through passage of the first valve to allow insertion and removal of the spring seat. The valve seat of the flow regulating valve may be threadedly retained within the through passage or may be retained in place by a suitable retaining means, such as a circlip.

30 Preferably, the coupling member is a collar which is rotatable and axially fast or substantially so around the casing of one of the first and second valves. One of the casing of the other of said first and second valves and the inner face of the outer end of the collar having two or more bayonets extending radially therefrom to engage with slots provided in the other of the inner face of the outer end of the collar or the casing of the other of the first and second valves.

35

An embodiment of the present invention will now be described, by way of example, with reference to the accompanying drawings, in which:-

Figure 1 is a vertical cross-sectional view of a valve assembly according to the present invention, the
40 assembly having a manually-operable flow regulating control valve; and

Figure 2 is a transverse cross sectional view of the valve assembly of Figure 1 on line A-A.

Referring to Fig. 1 of the drawings, a valve assembly includes two mutually opposed elongate valves 10 in a lengthwise relationship. Each valve 10 comprises a tubular casing 12 in which a through passage 14 is defined. The passage 14 of each valve has at one end, i.e. the end to which the other valve 10 is to be connected, an internally circumferential valve seat 16 against which a movable valve member 18 is spring biased by a return spring 22.

The valve member 18 of each valve is a poppet valve which is conical in shape and may be of rubber or other suitable synthetic plastics material. Each valve member 18 has a spigot device 20 centrally thereof with part of the spigot device 20 projecting outwardly of said one end to extend under the influence of the respective return spring 22 beyond the contiguous end of the casing 12. Each return spring comprises a helical compression spring 22 located within the respective through passage acting between the respective valve member 18 and a spring seat.

The contiguous ends of the valves 10 are coupled together by a coupling member providing each contiguous end with a seal gland, namely an external groove 38 into which an O-ring 40 is positioned. The coupling member comprises a collar 42 mounted around the lower valve casing 12.

The collar 42 has an internally extending flange 50 which abuts a peripheral stop 52 on the casing 12 and has a free rotational movement but a restricted axial movement between said stop 52 and abutment against a circlip 54 provided in a peripheral groove on the outside of the casing 12 as shown. The collar 42 holds the two valves 10 together, and is locked by two or more spaced bayonet connections engaging with a respective bayonet 58. The lower valve 10 and collar 42 serves as a female part of the assembly and the upper valve as the male part of the assembly.

In the lower of the two valves as shown in Fig. 1, the return spring 22 extends between the rear of the member 18 and an annular retaining plate 24, defining said spring seat, which is held in position against a collar 26, integral with the casing 12, by a circlip 28. The other end of the spigot 20 extends, as shown, through the hole in the plate 24 when the valve member 18 is out of its seat. The other end of the casing 12 of the lower valve 10 terminates with an external screw thread 32 to allow the valve assembly to be integrated into a piped liquid system.

The casing 12 of the upper valve 10 as shown in Fig. 1, is extended to accommodate a flow regulating control valve 30 at its other end. The extension 44 terminates with an internal screw-thread into which a manually-operable control valve 30 is fitted. A valve member 34 of the control valve 30 can be manually screwed into abutment with a valve seat 36 provided internally of the respective casing 12. The extension 44 has a branch 46 having an external screw thread 48 to allow the assembly to be connected to a reservoir. When the control valve 30 is in a closed position, i.e. with the member 34 in abutment in the seat 36, the through passage 14 in the respective casing 12 is closed off.

The return spring 22 of the upper valve 10 extends between the rear of the valve member 18 and a spring seat 50 located within the through passage 14 and retained in place by the valve seat 36 of the flow regulating control valve 30. Thus the return spring 22 of the upper valve 10 operates
5 independently of the flow regulating control valve 30.

The dimensions of the return springs 22 are selected so that the springs become coil bound to limit the travel of the respective valve member 18 away from its valve seat 16. As shown in Figure 1, when the valves 10 are coupled together, the valve members 18 adopt a neutral open position, with
10 each valve member urged to an open position by the action of the opposing valve member against the biasing force of the respective return spring 22.

The return spring 22 of each of the upper and lower valves 10 limits further movement of the respective valve member 18 away from its valve seat 16, preventing the opposing valve member 18
15 from being pushed into contact with its respective valve seat 16, thus limiting the movement of the valve members 18 away from their neutral open position and preventing either of the valve members 18 from closing the through passage under the action of fluid flowing through the aligned through passages 14.

20 This invention is advantageous in that it allows for ready removal of reservoirs without the hitherto disadvantages. Also in a domestic situation, several pipes for fitment for radiator (s) be provided whereby the positioning of the radiator (s) be altered to suit the housewife's requirements in furnishings and decoration. In an industrial situation, the reservoirs may contain other liquids such as milk, beverages or chemicals. Also, for a water system, a water storage tank may constitute the
25 reservoir.

While in the preferred embodiment, the return springs of the valves are utilised to limit the travel of the valve members away from their respective seats, other travel limiting means are envisaged. For example, radially inwardly projecting stop members may be provided on the inner sides of the
30 respective valve casings 12 for limiting the travel of the valve members.

The invention is not limited to the embodiment(s) described herein but can be amended or modified without departing from the scope of the present invention.

Claims

1. A valve assembly comprising mutually opposed first and second valves, each of which comprises a casing in which a through passage is defined, the through passages having, at contiguous ends,
5 internally circumferential valve seats against which respective movable valve members are biased, the respective valve members of the first and second valves engaging one another when the first and second valves are brought together to urge the valve members away from their respective seats to open the first and second valves, a coupling member being provided for holding the first and second valves together wherein means are provided for limiting the travel of the valve member of at
10 least one of the first and second valves away from its valve seat to prevent the valve member of the other of the first and second valves from engaging its valve seat when the first and second valves are together, thus preventing said other of the first and second valves from closing due to the flow of fluid through the valve assembly.
- 15 2. A valve assembly as claimed in claim 1, wherein the casing of the first valve includes an extension accommodating a flow regulating control valve at its distal end, the extension having a branch to be connected to a reservoir.
3. A valve assembly as claimed in claim 2, wherein the control valve is manually operable.
20
4. A valve assembly as claimed in claim 2, wherein the control valve is thermostatically controlled.
5. A valve assembly as claimed in any preceding claims, wherein the upstream valve of the first and second valves in the normal direction of flow, in use, through the valve assembly, is provided with
25 means for limiting the travel of said upstream valve to prevent closure of the downstream valve due to the flow of fluid through the valve assembly.
6. A valve assembly as claimed in claim 5, wherein the travel limiting means comprises the respective biasing means of the at least one of the first and second valves.
30
7. A valve assembly as claimed in claim 6, wherein the biasing means comprises a coil spring, wherein the dimensions of the spring are selected such that the spring becomes coil bound at said limit of travel of the associated valve member.
- 35 8. A valve assembly as claimed in claim 7, wherein said coil spring acts between a face of the associated valve member and a spring seat located within the respective through passage of said at least one of the first and second valves.
9. A valve assembly as claimed in claim 8, wherein at least one flow passage is provided through or
40 around the spring seat to allow fluid to flow through the valve assembly when the spring is coil bound.

10. A valve assembly as claimed in claim 8 or claim 9, wherein the spring seat comprises an elongate member extending between the inner sides of the through passage.
- 5 11. A valve assembly as claimed in claim 10, wherein said elongate member is provided with a through hole for receiving a spring supporting extension the respective valve member.
12. A valve assembly as claimed in any of claims 8 to 11, wherein the spring seat is retained in place with the associated through passage by means of a retaining member located within the
10 through passage.
13. A valve assembly as claimed in claim 12, wherein the retaining member comprises a circlip or a threaded member.
- 15 14. A valve assembly as claimed in claim 12, wherein the first valve is provided with a return spring adapted to define a travel limiting means, the spring seat being retained in place by a valve seat of the flow regulating control valve, said valve seat being removably mounted within the through passage of the first valve to allow insertion and removal of the spring seat.
- 20 15. A valve assembly as claimed in claim 15, wherein the valve seat of the flow regulating valve is threadedly retained within the through passage or is retained in place by a suitable retaining means, such as a circlip.
16. A valve assembly as claimed in any preceding claims, wherein the coupling member is a collar
25 which is mounted to be rotatable and axially fast or substantially so around the casing of one of the first and second valves.
17. A valve assembly as claimed in claim 16, wherein one of the casing of the other of said first and second valves and the inner face of the outer end of the collar is provided with two or more bayonets
30 extending radially therefrom to engage with slots provided in the other of the inner face of the outer end of the collar or the casing of the other of the first and second valves.