

Description

The invention relates to a clamping contact element for the electrical connection of conductors, provided with a spring arm. The invention further relates to an edge connector made up of a plurality of such clamping contact elements, for the connection of several parallel conductors. A connection device of this type is known from U.S. Patent Specification 4,379,608.

For a number of years now, for connections in electronic equipment in particular, or for the inter-connection of electronic units, it has been common practice to use flexible conductor film, for example made by etching a copper layer applied to a polyester film serving as a carrier, to produce an assembly of several flexible (parallel) conductors.

A special group of applications is formed by connections of flexible conductor film with the glass substrates of liquid crystal or LED (light Emitting Diode) display panels. Here, an electrical connection generally has to be produced between a number of parallel conducting strips on the substrate and the respective conductors of the flexible film.

Liquid crystal and LED display panels are currently designed in the most varied forms and for the most varied functions, for example as instrument panels in aeroplanes, cars and ships, as alphanumeric displays in telecommunication equipment etc. On the substrate of such a panel, one or more different functions are then accommodated, for example speedometer, tachometer, altimeter, indication and warning tests etc. This means that such a substrate is provided on its edges with a relatively large number of contact strips. When such a substrate is connected to plug contacts soldered on a printed circuit board, the substrate can no longer be replaced without breaking the soldered connection of one or more plug contacts provided along the edges.

This problem can be avoided by providing the connections with the substrate by means of flexible conductor film. Flexible conductor film can also be etched as a printed circuit and thus also provides attractive possibilities for producing therewith the various externally required connections between the substrate and the equipment for controlling the various functions.

In the edge connector known from the above-mentioned U.S. Patent Specification 4,379,608, an electrical connection between the contact strips or conductors on a glass substrate and the parallel conductors of flexible film is obtained by mechanically pressing the flexible conductor film on the substrate under external spring force. The quality of this connection is largely dependent on the construction elements, which have to ensure that the conductors of the film are accurately positioned

relative to the contact strips on the substrate. Since the glass substrates generally possess fairly sharp edges, the thin conductors of the film can easily be damaged. This applies even more in the case of connectors in which the flexible conductor film has to be folded over an edge of the substrate.

Other connections in which conducting flexible strips, so-called Zebra strips, are fitted as an intermediate between the contact strips of the display panel and, for example, a printed circuit board, and where under external mechanical pressure the Zebra strips produce an electrical connection between the display panel and the printed circuit board, do not permit rapid and simple fitting. Besides, various separate auxiliaries such as contact frames, compression means and the like are necessary for positioning of the Zebra strips.

The object of the invention is to eliminate the above disadvantages and produce a clamping contact element and an edge connector of the type referred to in the preamble, in particular for the connection of a flexible conductor film with the rigid substrate of a liquid crystal or LED display panel, in which the flexible conductor film can be taken without contact friction into the edge connector, and can be positioned therein in a simple manner, and with which a reliable connection can subsequently be produced, without external mechanical compression means, between the contact strips on the rigid substrate and the respective conductors of the flexible film.

To this end, provision is made according to the invention for a clamping contact element which is approximately E-shaped in structure and has at least three contact arms projecting from a base part, in succession a fixed arm, a first spring arm and a second spring arm, in such a way that between the fixed and first spring arm a first insertion opening and between the first and second spring arm a second insertion opening are formed, whereby through insertion of a rigid substrate into the first insertion opening the first spring arm is pressed away and exerts a pressure force on a flexible thin conductor which has been previously inserted without contact friction into the second insertion opening, in such a way that an electrical connection is achieved between the flexible thin conductor and a conductor provided on said rigid substrate.

A preferred embodiment of the invention is characterized in that the second spring arm is of a shape which is bent backward from the insertion side, and the first spring arm is a meandering shape with at least one pressure face in the first and another pressure face in the second insertion opening.

A further preferred embodiment of the invention is characterized in that following on the second

spring arm another fixed arm is disposed in such a way that between the second spring arm and the other fixed arm a third insertion opening is formed for insertion of a second rigid substrate by means of which the second spring arm is pressed away and exerts a pressure force on the previously inserted flexible thin conductor in the direction of the first spring arm.

Yet another preferred embodiment of the invention is characterized in that the first and second spring arms are each of a shape which is bent over from the insertion side towards each other and backwards.

Again another preferred embodiment of the invention is characterized in that the fixed arm near its end has a V-shaped notch facing the particular insertion opening, in such a way that when the corresponding rigid substrate is inserted at an angle with the fixed arm until its insertion edge lies in the V-shaped notch, it is introduced with low contact friction with lever action on the adjacent spring arm parallel to the fixed arm. The fixed arm is preferably provided with a stop including a flat side against which the conductor or a conductor carrier introduced into the first insertion opening lies in the resting position.

In addition to a connection between, for example, a contact strip on a substrate and a conductor on a flexible film, it may also be necessary to connect the clamping contact element directly to, for example, signal wires or a printed circuit board. The clamping contact element according to the invention is to this end provided with moulded-on means for the electrical connection of the clamping contact element to external connection means.

For the connection of several parallel thin conductors of preferably a flexible film with several parallel contact strips on a rigid substrate, provision is made according to the invention for an edge connector comprising a plurality of clamping contact elements accommodated in rows in a common housing of insulating material, for the connection of a flexible conductor film comprising parallel conductors and a plurality of parallel conductors provided on a rigid substrate and lying in one plane, wherein the clamping contact elements are disposed in such a way that a row of first and, where applicable, a row of third insertion openings are formed for the insertion of a first and, where applicable, a second substrate respectively and wherein the second insertion openings form a row for the insertion of the flexible conductor film, while the electrically separate clamping contact elements achieve an electrical connection between the conductors contacted with the same clamping contact element.

A disadvantage of the edge connector known from the U.S. Patent Specification 4,379,608 is in

the positioning and retaining in a particular position of the flexible conductor film in such a way that a reliable and absolute contact is made between a conductor of the flexible conductor film and, for example, a contact strip on the rigid substrate. Since an object of the invention relates to the production of means for positioning the flexible conductor film in the row of second insertion openings, a preferred embodiment of the edge connector according to the invention is characterized in that the means for positioning the flexible conductor film are formed by rectangular recesses one disposed on each short side of the common housing, each recess being by means of a groove-shaped connection channel spatially connected on the inside to a groove-shaped opening which is positioned essentially transversely to the rows of insertion openings and which is accessible from the insertion side, and in that the flexible conductor film has an end portion with on either side of the film a projecting resilient, bendable projection which can flap outwards into a respective recess after its insertion into the respective groove-shaped opening, and are each held in that position by a rear face of the short side of the housing which projects sideways relative to the recess, as a result of which the parallel conductors of the flexible conductor film are positioned between the respective second insertion openings and the film in its entirety is held in position in the common housing.

Another preferred embodiment of the edge connector is characterized to that end in that the common housing of the edge connector has on the insertion side defined insertion openings for insertion of the flexible conductor film, a first and, where applicable, a second rigid substrate respectively into the respective rows of insertion openings.

Yet another preferred embodiment of the edge connector is characterized in that the rear face of the short side of the common housing which projects sideways relative to the recess has at the level of the row of second insertion openings a V-shaped notch facing the recess, in such a way that the projections of the conductor film are each positioned in such a notch.

The common housing can also be provided with locking means for locking the external connection means on the housing.

The edge connector according to the invention can also be advantageously used as a connector for the insertion without contact friction and the connection of parallel thin conductors, in particular a flexible conductor film, but this is on condition that the clamping contact elements of the edge connector are provided with moulded-on means for contacting these contact elements with external connection means. Into the row of first and third insertion openings, a first and second rigid sub-

strate of insulating material must then be introduced respectively, which produces an electrical connection between a conductor in one of the clamping contact elements of, for example, a flexible conductor film and an external conductor contacted with said clamping contact element.

The clamping contact element can be advantageously punched from a piece of electrically conducting sheet material, while the common housing is preferably of cast insulating material. This means that the clamping contact units according to the invention can be mass-produced in a cheap and simple manner.

The invention will now be explained in greater detail with reference to the embodiments shown in the drawings.

Fig. 1 is a perspective view of the structure of a preferred embodiment of a clamping contact element according to the invention;

Fig. 2 shows a side view of another preferred embodiment of a clamping contact element according to the invention;

Fig. 3 shows a side view of yet another preferred embodiment of a clamping contact element according to the invention;

Fig. 4 shows a perspective view of the structure of the clamping contact element of Fig. 1, with backward projecting pins for contacting the clamping contact element with external connection means;

Fig. 5 is a perspective view of the structure of the clamping contact element of Fig. 1, provided with one or more plug contacts for contacting the clamping contact element with external connection means;

Fig. 6 is a perspective view in partial section of the structure of a preferred embodiment of an edge connector according to the invention, in which the clamping contact elements according to Fig. 4 are used, and shows the pre-worked end of the flexible conductor film;

Fig. 7 shows a perspective view of the edge connector according to Fig. 6 with a flexible conductor film retained therein and the substrate to be inserted;

Fig. 8 shows another embodiment of an edge connector according to the invention, with notches provided therein for accommodation of the projections of the flexible conductor film;

Fig. 9 shows a perspective view of a preferred embodiment of an edge connector according to the invention, viewed from the insertion side, with defined insertion openings for a rigid substrate and a flexible conductor film;

Fig. 10 shows a perspective view of the edge connector according to Fig. 9 viewed from the rear side; and

Fig. 11 shows an example of an application of various embodiments of an edge connector accord-

ing to the invention.

The embodiment of the clamping contact element 1 according to the invention shown in Fig. 1 shows the fixed arm 2, the first spring arm 3 and the second spring arm 4, which are connected to a base part and are arranged virtually in an E-shape. The contact face 5 of the fixed arm 2 and the top pressure face 6 of the first spring arm 3 form the first insertion opening 9, while the bottom pressure face 7 of the first spring arm 3 and the contact face 8 of the second spring arm 4 form a second insertion opening 10. The two contact faces 5, 8 are electrically connected to each other by means of the fixed arm 2, the second spring arm 4 and the base part of the clamping contact element. The insertion openings 9, 10 are on the insertion side of the clamping contact element 1. The second spring arm 4 has a shape which is bent backwards from the insertion opening 10. The first spring arm 3 meanders in shape, in such a way that the end on the side with the insertion openings is bent slanting downwards, while the top pressure face 6 is on a peak and the bottom pressure face 7 is on a dip, positioned towards the rear, of the meander shape. The peak following this dip, viewed from the insertion openings, is connected to the base part of the clamping contact element 1.

Through the insertion of a rigid substrate into the first insertion opening 9, the first spring arm 3 will be moved downwards, as a result of which, by means of its bottom pressure face 7, it exerts a pressure force on a thin conductor inserted into the second insertion opening 10. Depending on the movement of the first spring arm 3, the second spring arm 4 can also undergo a downward movement. In order to prevent this arm from being bent too much, a downward-directed boss 14 can be formed on the side of the second flexible arm 4 facing away from the contact face 8.

The opening between the bottom pressure face 7 of the first spring arm and the contact face 8 of the second spring arm is of such dimensions that a conductor can be inserted between them without contact friction when the first insertion opening is free. This is particularly important for a flexible conductor or a flexible conducting strip, since these cannot withstand pressure forces in the lengthwise direction. The bare side of this conductor or these conducting strips is thereby brought into contact with the contact face 8 of the second spring arm 4. The bare side of a conductor or conducting strip of a substrate to be inserted into the first insertion opening 9 must be brought into contact with the contact face 5 of the fixed arm 2. The first spring arm 3 must thereby ensure sufficient contact pressure for a reliable electrical connection between the contact faces and the respective conductors.

As can be seen from Fig. 1, the fixed arm 2 is

provided with a downward-facing stop 11. A conductor or conductor-carrying substrate inserted into the first contact opening 9 will in the resting position lie against the flat side 12 of the stop 11.

The upward-projecting boss 13 on the top side of the fixed arm 2 of the clamping contact element serves to hold the clamping contact element in a casing of, for example, plastic material which may be provided around the clamping contact element.

Fig. 2 shows a side view of the clamping contact element of Fig. 1, but in this embodiment the fixed arm 2 has near its end a V-shaped notch 5' facing the insertion opening 9.

The substrate to be introduced into the insertion opening 9 is inserted at an angle with the fixed arm 2, until its insertion edge lies in the V-shaped notch 5' as shown by the dotted line in Fig. 2. If the substrate is then brought parallel to the fixed arm 2, the lever action exerted in this way moves the first spring arm 3 downwards and the substrate can be inserted further with low contact friction into the first insertion opening up to the stop 11.

The push-on force of the clamping contact element is considerably smaller than that with the clamping contact element according to Fig. 1, because the spring force of the first spring arm is now virtually overcome by means of a lever action by the substrate to be inserted. The clamping contact according to this embodiment is provided on the top side with a boss 13' to retain the clamping contact element in a casing of, for example, plastic material which may be provided around the clamping contact element. Depending on the shape of said casing, a boss 13 like that in the embodiment of Fig. 1 can be provided instead of a boss 13', or - vice versa - the clamping contact element of Fig. 1 can be provided with a boss 13' instead of 13.

Fig. 3 shows an embodiment of a clamping contact element 1, with a first and second fixed arm 2 and 2' respectively, projecting from a base part. The second fixed arm 2' together with the second spring arm 4 forms a third insertion opening 9'.

These first and second spring arms 3, 4 are in a form bent towards each other and backwards from the insertion side. Here, both the second spring arm 4 can be provided with a contact face 8 and the first spring arm 3 with a contact face 8'. The two spring arms form the second insertion opening 10. The bosses 14 can be provided in order to prevent buckling of these two spring arms. On the side facing the respective fixed arm, the spring arms have pressure lobes 6' and 7' in the first 9 and third insertion opening 9' respectively.

Through the introduction of a first rigid substrate into the first insertion opening 9 and a second rigid substrate into the third insertion opening

9', the contact faces 8' and 8 of the spring arms are pressed towards each other, so that a thin conductor previously inserted without contact friction into the second insertion opening 10 is electrically connected to the clamping contact element 1 and the conductors to be contacted with it.

Like the clamping contact elements in Figs. 1 and 2, this clamping contact element can also be provided with bosses 13 or 13' to retain the clamping contact element in a casing of, for example, plastic material.

In addition to the form shown in Fig. 3, the fixed arms can also be designed without the V-shaped notches 5', as in the case of the fixed arm of the clamping contact element shown in Fig. 1.

As has already been said above, the clamping contact element can also be provided with means for direct electrical connection of the clamping contact element to, for example, signal wires, plug connections, printed circuit boards etc. Fig. 4 shows an embodiment to this end for the contact element according to Fig. 1, in which backward-projecting pins 15 of electrically conducting material are moulded onto the base part. Plug sockets can be pushed over the pins 15, or the pins can be, for example, soldered to a printed circuit board.

Fig. 5 shows an embodiment of the clamping contact element according to Fig. 1, which on the base part is provided with two moulded-on plug contacts 16, 17 of electrically conducting material. The conductors introduced into the contact channels 18, 19 are brought into direct electrical connection with the clamping contact element 1 by means of these plug contacts 16, 17.

Formed on the plug contacts are two resilient hooks 20 facing each other. These hooks 20 can mate with the parts which are to be fitted over the plug contacts and which contain the signal wire(s) which have to be electrically connected to the clamping contact element 1, in such a way that these parts are retained over the plug contacts.

The two plug contacts 16, 17 need not be the same shape or of the same dimensions. This makes it possible to connect signal wires of different diameters.

It will be clear that the embodiments of the clamping contact elements according to Figs. 2 and 3 can also be provided with pins 15 or plug contacts 16, 17 in the same way as the clamping contact element of Fig. 1.

The individual clamping contact elements can be combined parallel to one another and electrically separate from one another to form an edge connector, in such a way that a row of first insertion openings and parallel thereunder rows of second insertion openings or third insertion openings are formed, all for the accommodation of several parallel conductors, as shown in the partially

cutaway embodiment of the edge connector in Fig. 6. Here, clamping contact elements such as those of Fig. 4 are accommodated in parallel groove-shaped recesses 22 in a common housing 21 of electrically insulating material. The pins 15 project outwards on the rear side of the common housing 21, in other words the side opposite the insertion openings. It is, of course, also possible to use the clamping contact elements according to the preferred embodiment of Figs. 2 or 3, with or without pins 15 or plug contacts 16, 17.

The distance between the individual clamping contact elements corresponds to the pitch distance of 0.635 mm or more, common for this type of application, for clamping contact elements without means for connection of external conductors to be contacted, or 1.27 mm or more for clamping contact elements with moulded-on pins, and 2.54 mm or more for clamping contact elements with moulded-on plug contacts.

On the front, the housing 21 is open for inserting a flexible conductor film 30 with parallel conductors into the row of second insertion openings and, for example, a rigid conductor-carrying substrate 33 on which are disposed a number of parallel contact strips 34, as shown in Fig. 7, into the row of first insertion openings.

In order to permit correct positioning of the contact strips 32 of the flexible conductor film 30 between the second insertion openings 10 of the respective clamping contact elements 1, provision is made on each narrow side of the common housing 21 for a recess 27 which lies inwards relative to this narrow side and which is spatially connected by means of an internal groove-shaped connection channel 26 to a groove-shaped opening 23, which is positioned transversely to the row of first and second insertion openings and is formed by the narrow side 24 of the common housing 21 and a partition 25 which is placed parallel thereto but at a distance therefrom in the inward direction.

The flexible conductor film 30 is provided on the front with resilient, bendable projections 31 projecting on either side and with respective dimensions A, B. The film is introduced without contact friction into the second insertion openings by bending the projections 31 downwards into a position transverse to the plane of the film 30, as shown by dotted lines in Fig. 6, and by taking them in this position into the groove-shaped opening 23. If the film is taken further into the common housing 21, the projections by means of the connection channels 26 reach the recesses 27, in which they can spring back into their original position (see Fig. 7). To this end, the dimensions A, B of the recesses 27 correspond to the dimensions of the projections 31. The projections 31 are locked in this position by the rear faces 29 of the narrow sides 24

projecting sideways relative to the recesses 27. The film is retained in this way positioned in the correct manner between the row of second insertion openings in the common housing 21. The film can be removed again simply by bending downwards the projections 31 extending sideways in the recesses 27 while the contacts are open and removing them through the conductor channels 26 from the housing.

During both the insertion and the removal of the parallel conductor film, no friction force is exerted on the conducting strips, because the row of second insertion openings is then open. The chance of damage to the generally very thin contact strips is thus very small.

Fig. 8 shows an edge connector similar to that of Fig. 6 or 7, but on the two rear faces 29 projecting sideways relative to the recesses 27 provision is made at the level of the second insertion openings for a V-shaped notch 48 facing the recesses, one side 49 of said notch being parallel to a surface of the inserted flexible conductor film or the rigid substrate.

After insertion of the flexible conductor film, the projections 31 of the film will fall into said notches, which will prevent sideways movements of the film in the row of second insertion openings. The reliability of the connections is thereby greatly increased.

Fig. 9 shows a further embodiment of an edge connector 50 according to the invention. Disposed on the insertion side are now defined openings 51, 52 for the rigid substrate and the flexible conductor film respectively. It is now out of the question for the thicker substrate to be fed inadvertently into the row of second insertion openings 52, which could lead to faulty contacts and damage to the spring arms.

As can be seen from Fig. 10, the rear side of the common housing is open. The clamping contact elements are fitted from the open rear side into the parallel groove-shaped recesses 22 of the housing. By means of the boss 13' they are then retained in the parallel groove-shaped recesses 22, after fitting, by the recesses 53 provided on the top side of the common housing.

In contrast to the edge connector 21 with the open insertion side, this embodiment has the advantage that during fitting of external connection means, for example via the pins 15, the clamping contact elements cannot be pressed out of the housing at the front. For strengthening, reinforcement walls 54 can be provided in the common housing parallel to the clamping contacts.

Fig. 11 shows an example of an application of the edge connectors according to the invention. A liquid crystal display panel 35 is provided along all its edges with several parallel contact strips. The

flexible printed circuit 36 contains several pre-worked projections 37 which by means of an edge connector according to the invention have to be connected to the respective contact strips on the liquid crystal display panel 35.

Various embodiments of the edge connectors according to the invention are shown here. The edge connector 38 is provided with clamping contact elements according to Fig. 1 and serves purely to connect the flexible circuit 36 with the panel 35.

The edge connector 39 is made up of clamping contact elements according to Fig. 4. Pushed over the backward-projecting pins 15 is a standard socket connector 40 which is normally commercially available and is for contacting, for example by means of a flat ribbon cable 41, the contact elements or contact strips on the printed circuit 36 and the panel 35. The housing of the edge connector 39 is provided with two resilient hook-shaped locking projections 42 for locking the connector part 40 on the housing 39, as illustrated by the mounted assembly 43.

The edge connector 44 is designed with clamping contact elements according to the embodiment of Fig. 5. From the openings on the rear side of the means 45 retained by the locking hooks 20 the signal wires 46, 47 electrically connected by means of the plug contacts 16, 17 to the clamping contact elements are taken to the outside. As can be seen, the signal wires 46 are thicker than the signal wires 47, which corresponds to different dimensions of the plug contacts 16, 17. It will be clear that the display panel 35 can consist of a rigid printed circuit board, which may or may not be provided with electronic components.

A major advantage of the invention is that the sharp edges along the display panel cannot cause damage to the thin contact strips of the flexible conductor film, because the panel and the film are not brought into direct contact with each other, but are in contact through separate insertion openings of the respective clamping contact elements and the sequence of insertion.

It goes without saying that the invention is not limited to the embodiments discussed and shown above in the figures, but that modifications and additions are possible without going beyond the scope of the invention as defined by the appended claims.

Claims

1. Clamping contact element for the electrical connection of conductors, provided with a spring arm, characterized in that the clamping contact element (1) is approximately E-shaped in structure and has at least three contact arms projecting from a base part, in succession a

fixed arm (2), a first spring arm (3) and a second spring arm (4), in such a way that between the fixed and first spring arm a first insertion opening (9) and between the first and second spring arm a second insertion opening (10) are formed, whereby through insertion of a rigid substrate into the first insertion opening the first spring arm (3) is pressed away and exerts a pressure force on a flexible thin conductor which has been previously inserted without contact friction into the second insertion opening, in such a way that an electrical connection is achieved between the flexible thin conductor and a conductor provided on said rigid substrate.

2. Clamping contact element according to claim 1, characterized in that the second spring arm (4) is of a shape which is bent backward from the insertion side, and the first spring arm (3) is a meandering shape with at least one pressure face in the first and another pressure face in the second insertion opening.

3. Clamping contact element according to claim 1, characterized in that following the second spring arm (4) another fixed arm (2') is disposed in such a way that between the second spring arm (4) and the other fixed arm (2') a third insertion opening (9') is formed for insertion of a second rigid substrate by means of which the second spring arm (4) is pressed away and exerts a pressure force on the previously inserted flexible thin conductor towards the first spring arm (3).

4. Clamping contact element according to claim 3, characterized in that the first and second spring arms (3, 4) are each of a shape which is bent towards each other and backwards from the insertion side.

5. Clamping contact element according to claim 1 or 3, characterized in that the fixed arm (2 and 2') near its end has a V-shaped notch (5') facing the corresponding insertion opening, in such a way that when the corresponding rigid substrate is inserted at an angle to the fixed arm until its insertion edge lies in the V-shaped notch, it is introduced with low contact friction with lever action on the adjacent spring arm parallel to the fixed arm.

6. Clamping contact element according to claim 1 or 3, characterized in that the fixed arm (2 or 2') has a stop (11) including a flat side (12) against which the first or second substrate inserted into the first or third insertion opening

flexible printed circuit 36 contains several pre-worked projections 37 which by means of an edge connector according to the invention have to be connected to the respective contact strips on the liquid crystal display panel 35.

Various embodiments of the edge connectors according to the invention are shown here. The edge connector 38 is provided with clamping contact elements according to Fig. 1 and serves purely to connect the flexible circuit 36 with the panel 35.

The edge connector 39 is made up of clamping contact elements according to Fig. 4. Pushed over the backward-projecting pins 15 is a standard socket connector 40 which is normally commercially available and is for contacting, for example by means of a flat ribbon cable 41, the contact elements or contact strips on the printed circuit 36 and the panel 35. The housing of the edge connector 39 is provided with two resilient hook-shaped locking projections 42 for locking the connector part 40 on the housing 39, as illustrated by the mounted assembly 43.

The edge connector 44 is designed with clamping contact elements according to the embodiment of Fig. 5. From the openings on the rear side of the means 45 retained by the locking hooks 20 the signal wires 46, 47 electrically connected by means of the plug contacts 16, 17 to the clamping contact elements are taken to the outside. As can be seen, the signal wires 46 are thicker than the signal wires 47, which corresponds to different dimensions of the plug contacts 16, 17. It will be clear that the display panel 35 can consist of a rigid printed circuit board, which may or may not be provided with electronic components.

A major advantage of the invention is that the sharp edges along the display panel cannot cause damage to the thin contact strips of the flexible conductor film, because the panel and the film are not brought into direct contact with each other, but are in contact through separate insertion openings of the respective clamping contact elements and the sequence of insertion.

It goes without saying that the invention is not limited to the embodiments discussed and shown above in the figures, but that modifications and additions are possible without going beyond the scope of the invention as defined by the appended claims.

Claims

1. Clamping contact element for the electrical connection of conductors, provided with a spring arm, characterized in that the clamping contact element (1) is approximately E-shaped in structure and has at least three contact arms projecting from a base part, in succession a

fixed arm (2), a first spring arm (3) and a second spring arm (4), in such a way that between the fixed and first spring arm a first insertion opening (9) and between the first and second spring arm a second insertion opening (10) are formed, whereby through insertion of a rigid substrate into the first insertion opening the first spring arm (3) is pressed away and exerts a pressure force on a flexible thin conductor which has been previously inserted without contact friction into the second insertion opening, in such a way that an electrical connection is achieved between the flexible thin conductor and a conductor provided on said rigid substrate.

2. Clamping contact element according to claim 1, characterized in that the second spring arm (4) is of a shape which is bent backward from the insertion side, and the first spring arm (3) is a meandering shape with at least one pressure face in the first and another pressure face in the second insertion opening.

3. Clamping contact element according to claim 1, characterized in that following the second spring arm (4) another fixed arm (2') is disposed in such a way that between the second spring arm (4) and the other fixed arm (2') a third insertion opening (9') is formed for insertion of a second rigid substrate by means of which the second spring arm (4) is pressed away and exerts a pressure force on the previously inserted flexible thin conductor towards the first spring arm (3).

4. Clamping contact element according to claim 3, characterized in that the first and second spring arms (3, 4) are each of a shape which is bent towards each other and backwards from the insertion side.

5. Clamping contact element according to claim 1 or 3, characterized in that the fixed arm (2 and 2') near its end has a V-shaped notch (5') facing the corresponding insertion opening, in such a way that when the corresponding rigid substrate is inserted at an angle to the fixed arm until its insertion edge lies in the V-shaped notch, it is introduced with low contact friction with lever action on the adjacent spring arm parallel to the fixed arm.

6. Clamping contact element according to claim 1 or 3, characterized in that the fixed arm (2 or 2') has a stop (11) including a flat side (12) against which the first or second substrate inserted into the first or third insertion opening

respectively lies in the resting position.

7. Clamping contact element according to one of the preceding claims, characterized in that the clamping contact element is provided with moulded-on means (16, 17) for the connection of one or more conductors to be contacted. 5
8. Clamping contact element according to claim 7, characterized in that the moulded-on means are provided on the base part of the clamping contact element and consist of one or more backward-projecting pins (15) made of electrically conducting material. 10
9. Clamping contact element according to claim 7, characterized in that the moulded-on means are provided on the base part of the clamping contact element and consist of one or more plug contacts (16, 17) made of electrically conducting material and having the same or different dimensions. 15
10. Clamping contact element according to claim 9, characterized in that the clamping contact element on the base part is provided with locking means for retaining the external connection means. 20
11. Clamping contact element according to claim 10, characterized in that the locking means consist of two backward-projecting resilient hooks (20) facing each other. 25
12. Clamping contact element according to one of the preceding claims, characterized in that the clamping contact element is formed from a piece of electrically conducting material. 30
13. Edge connector comprising a plurality of clamping contact elements according to one of the preceding claims, accommodated in rows in a common housing (21) of insulating material, for the connection of a flexible conductor film (30) comprising parallel conductors and a plurality of parallel conductors (34) provided on a rigid substrate (33) and lying in one plane, wherein the clamping contact elements are disposed in such a way that a row of first and, where applicable, a row of third insertion openings are formed for the insertion of a first and, where applicable, a second substrate respectively and wherein the second insertion openings form a row for the insertion of the flexible conductor film, while the electrically separate clamping contact elements achieve an electrical connection between the conductors contacted with the same clamping contact ele-

ment.

14. Edge connector according to claim 13, characterized in that means are provided for positioning of the flexible conductor film introduced into the row of second insertion openings.
15. Edge connector according to claim 14, characterized in that the means for positioning the flexible conductor film (30) are formed by rectangular recesses (27) one disposed on each short side of the common housing, each recess being by means of a groove-shaped connection channel (26) spatially connected on the inside to a groove-shaped opening (23) which is positioned essentially transversely to the rows of insertion openings and which is accessible from the insertion side, and in that the flexible conductor film (30) has an end portion with on either side of the film a projecting resilient, bendable projection (31) which can flap outwards into a respective recess (27) after its insertion into the respective groove-shaped opening (23), and are each held in that position by a rear face (29) of the short side of the housing which projects sideways relative to the recess (27), as a result of which the parallel conductors of the flexible conductor film (30) are positioned between the respective second insertion openings and the film (30) in its entirety is held in position in the common housing.
16. Edge connector according to claim 15, characterized in that the common housing of the edge connector has on the insertion side defined insertion openings (51, 52) for insertion of the flexible conductor film, a first and, where applicable, a second rigid substrate respectively into the respective rows of insertion openings.
17. Edge connector according to claim 15 and 16, characterized in that the rear face (29) of the short side of the common housing which projects sideways relative to the recess (27) has at the level of the row of second insertion openings a V-shaped notch (48) facing the recess, in such a way that the projections (31) of the conductor film are each positioned in such a notch.
18. Edge connector according to claim 13 to 17, characterized in that the common housing is provided with locking means for locking the external connection means (40) on the housing.

19. Edge connector according to claim 18, characterized in that the locking means are formed by two resilient hook-shaped locking projections (42) which are disposed on the shirt sides of the common housing and mate with the external connection means (40).

Revendications

1. Elément de contact par serrage, pour le raccordement électrique de conducteurs, pourvu d'un bras ressort, caractérisé en ce que la structure de l'élément de contact par serrage (1) a la forme approximative d'un E et présente au moins trois bras de contact faisant saillie à partir d'une partie de base, dans l'ordre un bras fixe (2), un premier bras ressort (3) et un second bras ressort (4), de façon telle qu'entre le bras fixe et le premier bras ressort soit formée une première ouverture d'insertion (9) et qu'entre le premier et le second bras ressort soit formée une seconde ouverture d'insertion (10), de façon que, par l'insertion d'un substrat rigide dans la première ouverture d'insertion, le premier bras ressort (3) soit pressé à distance et exerce une force de pression sur un conducteur mince flexible qui a été auparavant inséré sans friction de contact dans la seconde ouverture d'insertion, de façon telle que le raccordement électrique soit réalisé entre le conducteur mince flexible et un conducteur présent sur ledit substrat rigide.
2. Elément de contact par serrage selon la revendication 1, caractérisé en ce que le second bras ressort (4) a une forme incurvée vers l'arrière du côté d'insertion, et que le premier bras ressort (3) est d'une forme en méandre avec au moins une face de pression dans la première ouverture d'insertion et une autre face de pression dans la seconde ouverture d'insertion.
3. Elément de contact par serrage selon la revendication 1, caractérisé en ce qu'à la suite du second bras ressort (4), un autre bras fixe (2') est disposé de façon telle qu'entre le second bras ressort (4) et l'autre bras fixe (2') soit formée une troisième ouverture d'insertion (9'), pour l'insertion d'un second substrat rigide, au moyen duquel le second bras ressort (4) est repoussé et exerce une force de pression sur le conducteur mince flexible inséré auparavant, en direction du premier bras ressort (3).
4. Elément de contact par serrage selon la revendication 3, caractérisé en ce que les premier et second bras ressorts (3, 4) sont chacun de

forme incurvée et dirigés l'un vers l'autre et vers l'arrière de la face d'insertion.

5. Elément de contact par serrage selon la revendication 1 ou 3, caractérisé en ce que le bras fixe (2 et 2') présente à proximité de son extrémité une encoche en V (5') faisant face à l'ouverture d'insertion correspondante, de façon telle que lorsque le substrat rigide correspondant est inséré selon un certain angle par rapport au bras fixe, jusqu'à ce que son bord d'insertion repose dans l'encoche en V, il soit introduit avec faible friction de contact due à l'action de levier du bras ressort adjacent parallèle au bras fixe.
6. Elément de contact par serrage selon la revendication 1 ou 3, caractérisé en ce que le bras fixe (2 ou 2') présente une butée (11) comprenant une face plane (12), contre laquelle le premier ou le second substrat inséré dans la première ou la seconde ouverture d'insertion repose chacun en une position de repos.
7. Elément de contact par serrage selon l'une des revendications précédentes, caractérisé en ce que l'élément de contact par serrage est doté de moyens monoblocs surmoulés (16, 17) pour la liaison d'un ou de plusieurs conducteurs à mettre en contact.
8. Elément de contact par serrage selon la revendication 7, caractérisé en ce que les moyens monoblocs surmoulés sont présents sur la partie de base de l'élément de contact par serrage et consistent en une ou plusieurs broches (15) faisant saillie vers l'arrière et constituées en un matériau conducteur de l'électricité.
9. Elément de contact par serrage selon la revendication 7, caractérisé en ce que les moyens monoblocs surmoulés sont présents sur la partie de base de l'élément de contact par serrage et consistent en un ou plusieurs contact de prise (16, 17) constitués d'un matériau conducteur de l'électricité et présentant des dimensions identiques ou différentes.
10. Elément de contact par serrage selon la revendication 9, caractérisé en ce que l'élément de contact par serrage présent sur la partie de base est pourvu de moyen de verrouillage pour maintenir le moyen de liaison extérieur.
11. Elément de contact par serrage selon la revendication 10, caractérisé en ce que le moyen de verrouillage consiste en deux crochets élastiques (20) faisant saillie en arrière et se faisant



face.

12. Elément de contact par serrage selon l'une des revendications précédentes, caractérisé en ce que l'élément de contact par serrage est formé à partir d'une pièce de matériau conducteur de l'électricité.
13. Connecteur de bord comprenant une pluralité d'éléments de contact par serrage selon l'une des revendications précédentes, disposés en rangée dans un boîtier commun (21) en matériau isolant, pour le raccordement d'un film conducteur flexible (30) comprenant des conducteurs parallèles et d'une pluralité de conducteurs parallèles (34) prévus coplanaires sur un substrat rigide (33), dans lequel les éléments de contact par serrage sont disposés de façon telle qu'une rangée de premières et, si cela est réalisable, une rangée de troisièmes ouvertures d'insertion sont formées pour l'insertion pour l'un et l'autre d'un premier et, si cela est réalisable, d'un second substrat, et dans lequel les secondes ouvertures d'insertion forment une rangée pour l'insertion du film conducteur flexible, tandis que les éléments de contact par serrage séparés électriquement réalisent une connexion électrique entre les conducteurs mis en contact avec le même élément de contact par serrage.
14. Connecteur de bord selon la revendication 13, caractérisé en ce que des moyens sont prévus pour positionner le film conducteur flexible introduit dans la rangée de secondes ouvertures d'insertion.
15. Connecteur de bord selon la revendication 14, caractérisé en ce que les moyens de positionnement du film conducteur flexible (30) sont formés par des cavités rectangulaires (27) chacune disposées sur chaque côté court du boîtier commun, chaque cavité étant reliée spatialement à l'intérieur à une ouverture en forme de gorge (23), au moyen d'un canal de connexion en forme de gorge (25) situé essentiellement transversalement aux rangées et étant accessible de l'intérieure d'insertion, et en ce que le film conducteur flexible (30) présente une partie d'extrémité avec, de chaque côté du film, une saillie flexible élastique (31) qui peut se rabattre vers l'extérieur, dans une cavité respective (27) après son insertion dans l'ouverture respective en forme de gorge (23), et chaque saillie étant maintenue en cette position par une face arrière (29) du côté court du boîtier, qui fait saillie sur le côté par rapport à la cavité (27), le résultat étant que les

conducteurs parallèles du film conducteur flexible (30) sont positionnés entre les secondes ouvertures d'insertion respectives et que le film (30) dans sa totalité est maintenu en position dans le boîtier commun.

16. Connecteur de bord selon la revendication 15, caractérisé en ce que le boîtier commun du connecteur de bord présente, sur la face d'insertion, des ouvertures d'insertion (51,52) définies pour l'insertion du film conducteur flexible, un premier et un second substrats rigides en correspondance avec les rangées d'ouvertures d'insertion mentionnées.
17. Connecteur de bord selon la revendication 15 et 16, caractérisé en ce que la face arrière (29) du côté court du boîtier commun qui fait saillie sur le côté par rapport à la cavité (27) présente, au niveau de la rangée des secondes ouvertures d'insertion, une encoche en V (48) faisant face à la cavité, de façon telle que les saillies (31) du film conducteur soient chacune positionnées dans une telle encoche.
18. Connecteur de bord selon les revendications 13 à 17, caractérisé en ce que le boîtier commun est prévu avec des moyens de verrouillage pour verrouiller le moyen de connexion extérieur (40) sur le boîtier.
19. Connecteur de bord selon la revendication 18, caractérisé en ce que les moyens de verrouillage sont formés par deux saillies élastiques de verrouillage (42) en forme de crochet, disposées sur les côtés courts du boîtier commun et s'adaptant au moyen de connexion extérieur (40).

40 Ansprüche

1. Klemmkontaktelement für die elektrische Verbindung von Leitern, das mit einem Federarm versehen ist, dadurch gekennzeichnet, daß das Klemmkontaktelement (1) etwa E-förmig ausgelegt ist und wenigstens drei Kontaktarme, die von einem Basistell vorstehen, in einer Aufeinanderfolge einen festen Arm (2), einen ersten Federarm (3) und einen zweiten Federarm (4) derart hat, daß zwischen dem festen und dem ersten Federarm eine erste Einführungsöffnung (9) und zwischen dem ersten und dem zweiten Federarm eine zweite Einführungsöffnung (10) gebildet werden, wobei durch das Einführen eines starren Substrats in die erste Einführungsöffnung der erste Federarm (3) weggedrückt wird und eine Druckkraft auf einen flexiblen, dünnen Leiter ausübt, der



zuvor ohne Kontaktreibung in die zweite Einführöffnung derart eingesetzt wurde, daß eine elektrische Verbindung zwischen dem flexiblen dünnen Leiter und einem an dem starren Substrat vorgesehenen Leiter erzielt wird.

2. Klemmkontaktelement nach Anspruch 1, dadurch gekennzeichnet, daß der zweite Federarm (4) eine Gestalt hat, die ausgehend von der Einführungsseite nach rückwärts gebogen ist, und daß der erste Federarm (3) eine gewundene Gestalt mit wenigstens einer Druckfläche in der ersten und einer weiteren Druckfläche in der zweiten Einführöffnung hat.
3. Klemmkontaktelement nach Anspruch 1, dadurch gekennzeichnet, daß im Anschluß an den zweiten Federarm (4) ein weiterer fester Arm (2') derart angeordnet ist, daß zwischen dem zweiten Federarm (4) und dem weiteren festen Arm (2') eine dritte Einführungsöffnung (9') zum Einführen eines zweiten starren Substrats gebildet wird, mittels dem der zweite Federarm (4) weggedrückt wird und eine Druckkraft auf den zuvor eingeführten, flexiblen, dünnen Leiter in Richtung auf den ersten Federarm (3) ausübt.
4. Klemmkontaktelement nach Anspruch 3, dadurch gekennzeichnet, daß die ersten und zweiten Federarme (3, 4) jeweils eine solche Gestalt haben, daß sie in Richtung aufeinander und von der Einführungsseite nach rückwärts gebogen sind.
5. Klemmkontaktelement nach Anspruch 1 oder 3, dadurch gekennzeichnet, daß der feste Arm (2 und 2') in der Nähe seines Endes eine V-förmige Ausnehmung (5') hat, die der zugeordneten Einführungsöffnung derart zugewandt ist, daß, wenn das zugeordnete starre Substrat unter einem Winkel zu dem festen Arm eingeführt wird, bis der Einführungsrand in der V-förmigen Ausnehmung liegt, dieses mit geringer Kontaktreibung unter Hebelwirkung an dem benachbarten Federarm parallel zum festen Arm eingeführt wird.
6. Klemmkontaktelement nach Anspruch 1 oder 3, dadurch gekennzeichnet, daß der feste Arm (2 oder 2') einen Anschlag (11) hat, der eine flache Seite (12) hat, gegen die das erste oder zweite in die erste oder dritte Einführungsöffnung jeweils eingeführte Substrat in der Ruhestellung anliegt.
7. Klemmkontaktelement nach einem der vorangehenden Ansprüche, dadurch gekennzeichnet,

net, daß das Klemmkontaktelement mit einer angeformten Einrichtung (16, 17) zum Verbinden mit einem oder mehreren zu kontaktierenden Leitern versehen ist.

8. Klemmkontaktelement nach Anspruch 7, dadurch gekennzeichnet, daß die angeformte Einrichtung an dem Basisteil des Klemmkontaktelements vorgesehen ist und ein oder mehrere nach rückwärts vorspringende Stifte (15) hat, die aus einem elektrisch leitenden Material bestehen.
9. Klemmkontaktelement nach Anspruch 7, dadurch gekennzeichnet, daß die angeformte Einrichtung an dem Basisteil des Klemmkontaktelements vorgesehen ist und ein oder mehrere Steckerkontakte (16, 17) aufweist, die aus einem elektrisch leitenden Material hergestellt sind, und die gleiche oder unterschiedliche Abmessungen haben.
10. Klemmkontaktelement nach Anspruch 9, dadurch gekennzeichnet, daß das Klemmkontaktelement auf dem Basisteil mit einer Sperreinrichtung zum Festlegen der externen Anschlußeinrichtung versehen ist.
11. Klemmkontaktelement nach Anspruch 10, dadurch gekennzeichnet, daß die Sperreinrichtung zwei nach rückwärts vorspringende Federhaken (20) aufweist, die einander zugewandt sind.
12. Klemmkontaktelement nach einem der vorangehenden Ansprüche, dadurch gekennzeichnet, daß das Klemmkontaktelement aus einem Stück eines elektrisch leitenden Materials ausgebildet ist.
13. Randverbinder, der eine Mehrzahl von Klemmkontaktelementen nach einem der vorangehenden Ansprüche aufweist, die in Reihen in einem gemeinsamen Gehäuse (21) aus isolierendem Material für den Anschluß einer flexiblen Leiterfolie (30) untergebracht ist, die parallele Leiter aufweist, und eine Mehrzahl von parallelen Leitern (34) aufweist, die an einem starren Substrat (33) vorgesehen sind und in einer Ebene liegen, wobei die Klemmkontaktelemente derart angeordnet sind, daß eine Reihe von ersten, wenn vorhanden eine Reihe von dritten Einführöffnungen, zum Einführen eines ersten, wenn vorhanden eines zweiten Substrats, jeweils gebildet werden und bei dem die zweiten Einführöffnungen eine Reihe zum Einführen der flexiblen Leiterfolie bildet, während die elektrisch gesonderten Klemmkontaktele-



mente eine elektrische Verbindung zwischen den Leitern erzielen, die in Kontakt mit ein und demselben Klemmkontaktelement sind.

14. Randverbinder nach Anspruch 13, dadurch gekennzeichnet, daß Einrichtungen zum Positionieren der flexiblen Leiterfolie vorgesehen sind, die in die Reihe von zweiten Einführöffnungen eingeführt wird. 6
15. Randverbinder nach Anspruch 14, dadurch gekennzeichnet, daß die Positioniereinrichtung für die flexible Leiterfolie (30) von viereckförmigen Ausnehmungen (27) gebildet wird, von denen eine auf jeder kurzen Seite des gemeinsamen Gehäuses angeordnet ist, jede Ausnehmung mit Hilfe eines ausnehmungsförmigen Verbindungskanals (26) räumlich an der Innenseite mit einer nutzförmig ausgebildeten Öffnung (23) verbunden ist, die im wesentlichen quer zu den Reihen der Einführöffnungen angeordnet ist, und die für die Einführseite zugänglich ist, und daß die flexible Leiterfolie (30) einen Endabschnitt mit einem vorspringenden, federnd nachgiebigen, biegbaren Vorsprung (31) an jeder Seite hat, die nach außen in eine zugeordnete Ausnehmung (27) nach dem Einführen in die zugeordnete, nutzförmige Öffnung (23) auslenken kann, und die jeweils in der Position durch eine hintere Fläche (29) der kurzen Seite des Gehäuses gehalten ist, die relativ zu der Ausnehmung (27) zur Seite hin vorsteht, wobei als Folge die parallelen Leiter der flexiblen Leiterfolie (30) zwischen den zugeordneten zweiten Einführöffnungen und der Folie (30) in ihrer Gesamtheit an Ort und Stelle in dem gemeinsamen Gehäuse angeordnet gehalten sind. 10
15
20
25
30
35
16. Randverbinder nach Anspruch 15, dadurch gekennzeichnet, daß das gemeinsame Gehäuse des Randverbinders auf der Einführseite ausgebildete Einführöffnungen (51, 52) zum Einführen der flexiblen Leiterfolie, eines ersten und gegebenenfalls eines zweiten starren Substrats jeweils in die zugeordneten Reihen von Einführöffnungen hat. 40
45
17. Randverbinder nach Anspruch 15 und 16, dadurch gekennzeichnet, daß die Rückfläche (29) der kurzen Seite des gemeinsamen Gehäuses, die seitlich relativ zu der Ausnehmung (27) vorsteht, in der Höhe der Reihe der zweiten Einführöffnungen eine V-förmige Ausnehmung (48) hat, die der Ausnehmung derart zugewandt ist, daß die Vorsprünge (31) der Leiterfolie jeweils in einer solchen Ausnehmung positioniert sind. 50
55

18. Randverbinder nach einem der Ansprüche 13 bis 17, dadurch gekennzeichnet, daß das gemeinsame Gehäuse mit einer Sperreinrichtung zum Festlegen einer äußeren Anschlußeinrichtung (40) an dem Gehäuse versehen ist.
19. Randverbinder nach Anspruch 18, dadurch gekennzeichnet, daß die Sperreinrichtung von zwei federnd nachgiebigen, hakenförmigen Sperrvorsprüngen (42) gebildet werden, die auf den kürzeren Seiten des gemeinsamen Gehäuses angeordnet sind und passend zu der externen Anschlußeinrichtung (40) ausgelegt sind.

