

DESCRIPTION

TWO-PART HAIR DYE OR BLEACH COMPOSITION

TECHNICAL FIELD

5 [0001]

The present invention relates to a two-part hair cosmetic for hair dyeing or bleaching which includes first and second agents of which a two-part hair dye or bleach composition is constituted and a squeeze container filled
10 with a mixed solution thereof.

BACKGROUND ART

[0002]

Examples of discharge containers containing liquid contents and discharging such contents therefrom include a
15 squeeze container. Squeeze containers can be classified as squeeze containers provided with a nozzle cap, squeeze containers provided with a squeeze foamer and the like, according to the kind of cap attached to the container body.

20 [0003]

To complete a product using such a squeeze container, it is necessary to select from among various kinds of materials, shapes and the like depending on the physical properties of the contents and the intended use and the
25 like, and then draw up a design based on the discharge amount per one discharge, the discharge mode, i.e.,

whether the contents are discharged as a liquid or a foam, the discharge frequency and the like. Such selection and design requires a large amount of work and in new product development often entails great difficulties, even if
5 carried out with the cooperation of people skilled in the art of containers and in the art of the contents.

[0004]

For example, a face wash cosmetic is used approximately several times per day in an amount of about
10 1 g each time. Thus, the conditions required for a container containing a face wash cosmetic are that it can be left for a period of several months to several years with its contents inside, and the discharge mode can be a liquid or in a fine foam. Accordingly, it is necessary to
15 select the optimum materials for those conditions and draw up a design based thereon.

[0005]

On the other hand, two-part hair dye or bleach compositions are constituted of a first agent containing
20 an alkaline agent and a second agent containing hydrogen peroxide. Such compositions have to be used by thoroughly mixing the first and second agents just before use. In addition, all of the composition needs to be used up immediately after mixing. Furthermore, a mixed solution
25 of the first and second agents has to be applied on the hair and then left for about 30 minutes, during which time

the mixed solution must not drip. Therefore, to apply the mixed solution on the hair in a liquid state as is, the mixed solution needs to be in the form of a gel or a cream having a viscosity of at least several thousand mPa.s.

5 Considering the ease of applying on the hair and problems such as corrosion of the container by the composition, a squeeze container provided with a nozzle cap is generally used for containing such a form of a two-part hair dye or bleach composition.

10 [0006]

However, to carry out dyeing or bleaching without any unevenness using a gel- or cream-formed two-part hair dye or bleach composition, since the mixed solution has a high viscosity as mentioned above, not only skill is
15 required, but the hair must be "pre-blocked" (braiding the hair into sections at the front, sides and rear of the head). Thus, a lot of time and effort is required to carry out such dyeing or bleaching.

[0007]

20 In recent years, to resolve this problem, two-part hair dye or bleach compositions have been proposed which contain a foaming agent in at least one of the first or second agents (Patent Documents 1 and 2). If the mixed solution of these first and second agents is applied on
25 the hair by discharging it in a foam by a foamer container, dyeing or bleaching can be carried out simply without any

trouble.

Patent Document 1: JP-A-2004-339216

Patent Document 2: JP-A-2006-124279

5 DISCLOSURE OF THE INVENTION

PROBLEMS TO BE SOLVED BY THE INVENTION

[0008]

Patent Documents 1 and 2 disclose known pump foamer
containers, squeeze containers and the like as foamer
10 containers which discharge in a foam a mixed solution of
first and second agents of a two-agent type composition
for hair dyeing or bleaching.

[0009]

However, there is a need for further investigation
15 into a foamer container which is capable of smoothly
repeating the discharge operation of a mixed solution of
first and second agents, which does not allow dripping
even if a foamy mixed solution is left for about 30
minutes after being applied on the hair, and yet which can
20 carry out dyeing or bleaching without any unevenness.

MEANS FOR SOLVING THE PROBLEMS

[0010]

The present inventors discovered that when
discharging a mixed solution of first and second agents of
25 a two-part hair dye or bleach composition in a foam from a
squeeze container, factors such as the ratio between the

liquid amount of the mixed solution filled in the squeeze container and the inner volume of the container body, and the cross-sectional profile and cross-sectional area of the container body, have a large effect on foam quality. Furthermore, the present inventors discovered that foam quality could be controlled by setting these factors in specific ranges, and that dyeing or bleaching could even be carried out without any drips or color unevenness. As a result of this discovery, the present inventors completed the present invention.

[0011]

Specifically, a first aspect of the present invention provides a two-part hair cosmetic for hair dyeing or bleaching which includes a two-part hair dye or bleach composition having a first agent containing an alkaline agent and a second agent containing hydrogen peroxide, and a squeeze container for discharging in a foam a mixed solution of the first and second agents, wherein

at least one of the first or second agents contains a foaming agent,

the mixed solution of the first and second agents has a viscosity (25°C) of from 1 mPa·s to 100 mPa·s,

the squeeze container has a container body and a squeeze foamer,

the squeeze foamer has a gas-liquid mixing chamber

for causing the mixed solution to foam by mixing air in the container body with the mixed solution, foam homogenizing means for homogenizing foam of the mixed solution which has been made to foam in the gas-liquid mixing chamber, and a discharge outlet for discharging the homogenized foam, and

a ratio between a total volume of the first and second agents and an inner volume of the container body (total volume/inner volume) is in the range of from 0.30 to 0.60.

[0012]

A second aspect of the present invention provides a two-part hair cosmetic for hair dyeing or bleaching which includes a two-part hair dye or bleach composition having a first agent containing an alkaline agent and a second agent containing hydrogen peroxide and a squeeze container for discharging in a foam a mixed solution of the first and second agents, wherein

at least one of the first or second agents contains a foaming agent,

the mixed solution of the first and second agents has a viscosity (25°C) of from 1 mPa·s to 100 mPa·s,

the squeeze container has a container body and a squeeze foamer,

the squeeze foamer has a gas-liquid mixing chamber for causing the mixed solution to foam by mixing air in

the container body with the mixed solution, foam
homogenizing means for homogenizing foam of the mixed
solution which has been made to foam in the gas-liquid
mixing chamber, and a discharge outlet for discharging the
5 homogenized foam,

a ratio between a total volume of the first and
second agents and an inner volume of the container body
(total volume/inner volume) is in the range of from 0.30
to 0.70, and

10 a torso outer shape of the container body has a
cross-section with a ratio of minor axis to major axis at
a middle portion in a height direction of the container
body of from 0.50 to 1.0.

[0013]

15 A third aspect of the present invention provides a
two-part hair cosmetic for hair dyeing or bleaching which
includes a two-part hair dye to bleach composition having
a first agent containing an alkaline agent and a second
agent containing hydrogen peroxide and a squeeze container
20 for discharging in a foam a mixed solution of the first
and second agents, wherein

at least one of the first or second agents contains
a foaming agent,

the mixed solution of the first and second agents
25 has a viscosity (25°C) of from 1 mPa·s to 100 mPa·s,

the squeeze container has a container body and a

squeeze foamer,

the squeeze foamer has a gas-liquid mixing chamber for causing the mixed solution to foam by mixing air in the container body with the mixed solution, foam

5 homogenizing means for homogenizing foam of the mixed solution which has been made to foam in the gas-liquid mixing chamber, and a discharge outlet for discharging the homogenized foam,

a ratio between a total volume of the first and
10 second agents and an inner volume of the container body (total volume/inner volume) is in the range of from 0.30 to 0.70, and

a torso outer shape of the container body has a cross-section with an area at a middle portion in a height
15 direction of the container body of from 12 cm² to 30 cm².

EFFECT OF THE INVENTION

[0014]

According to the first aspect of the present invention, the mixed solution of the first and second
20 agents includes a foaming agent and has a specific viscosity; a squeeze container provided with a specific squeeze foamer is used; and the ratio between the total volume of the first and second agents and the inner volume of the container body (total volume/inner volume) is in
25 the range of from 0.30 to 0.60. As a result, the foam quality of the mixed solution when repeated squeezing is

carried out can be made very fine from start to finish of the squeezing; and an excellent hair dyeing performance can be achieved, such as the enablement of dyeing or bleaching without any drips or unevenness. Furthermore, the number of squeeze repetitions from start to finish of the squeezing corresponding to the required total discharge amount on the hair can be reduced by discharging approximately 3 g or more of foam, which is suitable to be taken on one hand, in a single squeeze. Therefore, the hand can be prevented from becoming tired even when applying foam of the mixed solution over all of the hair.

[0015]

According to the second aspect of the present invention, the same mixed solution and squeeze foamer as in the first aspect of the present invention are used; and a torso outer shape of the container body has a cross-section with a ratio of minor axis to major axis at a middle portion in a height direction of the container body of from 0.50 to 1.0. As a result, the foam quality of the mixed solution discharged from the squeeze container can be made finer, and an excellent hair dyeing performance can be achieved, such as the enablement of dyeing or bleaching without any drips or unevenness. Furthermore, approximately 3 g or more of foam, which is suitable to be taken on one hand, in a single squeeze, can be discharged, and the recovery properties of the squeezed container can

be improved. Therefore, it is easier to carry out repeated squeezing continuously with a stable foam quality.

[0016]

According to the third aspect of the present invention, the same mixed solution and squeeze foamer as in the first aspect of the present invention are provided; and a torso outer shape of the container body has a cross-section with an area at a middle portion in a height direction of the container body of from 12 cm² to 30 cm². As a result, the foam quality of the mixed solution discharged from the squeeze container can be made finer, and an excellent hair dyeing performance can be achieved, such as the enablement of dyeing or bleaching without any drips or unevenness. Furthermore, it is easier to grip the container body, easy to increase the amount discharged from a single squeeze, and easy to discharge approximately 3 g or more of foam, which is suitable to be taken on one hand in a single squeeze. Therefore, the hand can be prevented from becoming tired even when applying foam of the mixed solution over all of the hair.

BRIEF DESCRIPTION OF THE DRAWINGS

[0017]

Fig. 1A is a schematic view of the two-part cosmetic for hair dyeing or bleaching of the first aspect of the present invention prior to the mixing of the first and

second agents;

Fig. 1B is a schematic view of the two-part hair cosmetic for hair dyeing or bleaching of the first aspect of the present invention after the first and second agents
5 have been mixed;

Fig. 2 is a cross-sectional view of a squeeze container;

Fig. 3 is a cross-sectional view of the squeeze container when being squeezed;

10 Fig. 4 is an explanatory diagram of the cross-section of the squeeze container;

Fig. 5 is a schematic view of the squeeze container in an inclined state;

15 Fig. 6 is an explanatory diagram of the two-part cosmetic for hair dyeing or bleaching provided with a nozzle; and

Fig. 7 is a schematic view of the squeeze container after the first and second agents have been mixed.

DESCRIPTION OF THE REFERENCE NUMERALS

20 [0018]

- 1 two-part hair cosmetic for hair dyeing or bleaching
- 2 first container
- 3 second container
- 4 container body of second container or container body
- 25 of squeeze container
- 5 squeeze foamer

- 6, 6B squeeze container
- 7 cap member
- 8 head member
- 10 mixing device
- 5 11 gas-liquid mixing chamber
- 12 air induct path
- 13 dip tube
- 14 foam homogenizing means
- 15 liquid path
- 10 16 liquid path
- 17 discharge outlet
- 18 foam homogenizing means
- 19 gap
- 20 check valve
- 15 21 discharge nozzle
- A1 first agent
- A2 second agent
- A3 mixed solution
- La minor axis
- 20 Lb major axis
- Lx axis perpendicular to aperture face of discharge outlet
- Ly vertical direction
- S cross-section of container body

25

MODE FOR CARRYING OUT THE INVENTION

[0019]

The present invention will now be described in more detail while referring to the drawings. It is noted that in the drawings, like reference numerals represent the same or similar structural elements.

[0020]

Fig. 1A is a schematic view showing one embodiment of the two-part hair cosmetic for hair dyeing or bleaching of the first aspect of the present invention and illustrating the state prior to the mixing of the first and second agents. Fig. 1B illustrates the state after the first and second agents have been mixed.

[0021]

As illustrated in Fig. 1A, this two-part hair cosmetic 1 for hair dyeing or bleaching includes a first agent A1 filled in a first container 2, a second agent A2 filled in a second container 3, and a squeeze foamer 5. The container body 4 of the second container 3 also serves as the container body of the squeeze container. As illustrated in Fig. 1B, a squeeze container 6 is constituted of the container body 4 and the squeeze foamer 5. Here, the squeeze container is preferably such a container as causes a mixed solution to foam by mixing the mixed solution with air in the same container body. Examples of such a squeeze container include a container like the squeeze container 6 illustrated in Fig. 1B, which

discharges its contents while in an upright manner (for example, "S1 Squeeze Foamer", manufactured by Daiwa Can Company). Further examples include a container such as the squeeze container 6B illustrated in Fig. 7, which is provided with a check valve (not shown) in the discharge path of the liquid so that it can discharge its contents either in an upright or inverted manner, since when the container is standing upright the portion which is the air induct path becomes the liquid induct path when inverted, while the dip tube which is the liquid induct path when the container is standing upright becomes the air induct path when inverted (for example, "Squeeze Foamer RF-270" manufactured by Toyo Seikan Kaisha, Ltd.). From the perspective of the discharge performance of the foam, a squeeze container which can discharge its contents in an upright manner like as illustrated in Fig. 1B is preferred.

[0022]

The concept of the "two-pair hair dye or bleach composition " in the present invention includes hair dye or bleach compositions which contain a first agent and a second agent and which are used by mixing these agents at the time of use. In the case of a hair dye composition, the first agent A1 contains an alkaline agent and a dye, and the second agent A2 contains hydrogen peroxide.

Furthermore, in the case of a hair bleach composition, the first agent A1 contains an alkaline agent but not a dye,

and the second agent A2 contains hydrogen peroxide. In addition, in the case of hair dye compositions as well as hair bleach compositions, this concept also includes embodiments wherein a third agent containing a persulfate
5 is used. In such a case, the first, second, and third agents are used by mixing them together.

[0023]

The hair cosmetic 1 for hair dyeing or bleaching of the first aspect of the present invention includes a
10 foaming agent in at least one of the first agent A1 or the second agent A2 of the two-part hair dye or bleach composition, with the mixed solution A3 being adjusted to have a certain viscosity, wherein a specific container is used as the squeeze container 6, and a specific ratio
15 between the initial filled amount of the mixed solution A3 and the inner volume of the container body 4 is set. As a result, the foam quality and discharge properties of the mixed solution A3 discharged in a foam from the squeeze container are improved from start to finish of the
20 squeezing.

[0024]

Here, as the alkaline agent contained in the first agent A1, ammonia, an alkanolamine such as monoethanolamine, sodium hydroxide, and potassium
25 hydroxide can be used. Furthermore, a buffer may be appropriately added, for example, an ammonium salt such as

ammonium hydrogencarbonate and ammonium chloride, and a carbonate such as potassium carbonate and sodium hydrogencarbonate.

[0025]

5 The concentration of the alkaline agent can be appropriately set so that the pH in the mixed solution A3 of the first agent A1 and the second agent A2 is from 8 to 12, and preferably from 9 to 11.

[0026]

10 On the other hand, the concentration of the hydrogen peroxide in the second agent A2 is preferably in the range of from 1 mass% to 9 mass%, and more preferably in the range of from 3 mass% to 6 mass%. The hydrogen peroxide concentration in the mixed solution of the first agent A1
15 and the second agent A2 is preferably in the range of from 1 mass% to 6 mass%, and more preferably in the range of from 2 mass% to 5 mass%. Furthermore, to suppress decomposition of the hydrogen peroxide, the pH of the
20 second agent A2 is preferably in the range of from 2 to 6, and more preferably in the range of from 2.5 to 4.

[0027]

Both the first agent A1 and the second agent A2 preferably have water as their main solvent.

[0028]

25 At least one of the first agent A1 or the second agent A2 used in the present invention contains a foaming

agent. This enables the mixed solution A3 of the first agent A1 and the second agent A2 to easily foam by discharging the mixed solution A3 from the squeeze container 6. Furthermore, the produced foam has a longer
5 life. Although the foaming agent may be anything so long as it has foaming properties, a surfactant is preferable. Examples of the surfactant include nonionic surfactants, anionic surfactants, cationic surfactants, ampholytic surfactants, semipolar surfactants, and the like. Among
10 these, the use of an anionic surfactant is preferred, and using together with an ampholytic surfactant as well is more preferred. Examples of the anionic surfactant include an alkylsulfate, polyoxyethylenealkylethersulfate and the like. Examples of the ampholytic surfactant which
15 can be used include fatty acid amidopropyl betaine, alkyldimethylamine oxide, alkylcarboxymethyl hydroxyethyl imidazolinium betaine, alkyldimethylaminoacetic acid betaine and sulfobetaine.

[0029]

20 Furthermore, generally, considering that the first agent A1 in many cases contains ammonia or a carbonate and has a high ionic strength, to solubilize the dye or to improve the sense of feel, the first agent A1 preferably contains a nonionic surfactant, such as a
25 polyoxyethylenealkylether, an alkylpolyglucoside, and an alkylalkanolamide. Among these, an alkylpolyglucoside or

polyoxyethylenealkylether are preferred. More specifically, preferred examples of the alkylpolyglucoside have 8 to 14 carbon atoms on the alkyl group and an average degree of condensation of the glucoside of 1 to 2.

- 5 Furthermore, preferred examples of the polyoxyethylenealkylether have 10 to 18 carbon atoms on the alkyl group and an average degree of polymerization of the polyoxyethylene of 5 to 40.

[0030]

- 10 Furthermore, the second agent A2 may also contain a nonionic surfactant, such as a polyoxyethylenealkylether, an alkylpolyglucoside, and an alkylalkanolamide, and a cationic surfactant, such as alkyltrimethylammonium chloride and dialkyldimethylammonium chloride in order to
15 improve the sense of feel.

[0031]

- If the two-part hair dye or bleach composition is for hair dyeing, the dye contained in the first agent A1 may be an oxidation dye or a direct dye. Examples of the
20 oxidation dye include: dye precursors, such as para-phenylenediamine, para-aminophenol, toluene-2,5-diamine, N,N-bis(2-hydroxyethyl)para-phenylenediamine, 2-(2-hydroxyethyl)para-phenylenediamine, 4-amino-3-methylphenol, 6-amino-3-methylphenol, ortho-aminophenol and 1-
25 hydroxyethyl-4,5-diaminopyrazole; couplers, such as resorcin, 2-methylresorcin, meta-aminophenol, para-amino-

ortho-cresol, 5-(2-hydroxyethylamino)-2-methylphenol, meta-phenylenediamine, 2,4-diaminophenoxyethanol, and 1-naphthol; and the like. Examples of the direct dye include para-nitro-ortho-phenylenediamine, para-nitro-
5 meta-phenylenediamine, basic yellow 87, basic orange 31, basic red 12, basic red 51, basic blue 99, acid orange 7, and the like.

[0032]

It is preferred that at least one of the first agent
10 A1 or the second agent A2 contains a higher alcohol, since this improves the life of the foam of the mixed solution discharged from the squeeze container 6, and suppresses drips from forming when the foam collapses after being applied on the hair. The higher alcohol preferably has 14
15 to 24 carbon atoms. Examples thereof include myristyl alcohol, cetyl alcohol, stearyl alcohol, behenyl alcohol, isostearyl alcohol, oleyl alcohol, and the like. These can be used as a combination of two kinds or more.
Furthermore, these can be contained, based on the whole
20 composition for hair dyeing after the first and second agents have been mixed, in an amount of 0.01 mass% to 3 mass%, preferably 0.1 mass% to 2 mass%, more preferably 0.2 mass% to 1 mass% and even more preferably 0.3 mass% to 0.8 mass%.

25 [0033]

In addition, the first agent A1 and the second agent

A2 may contain various additives as required. For example, to prevent the scalp from being irritated by an irritant component, such as hydrogen peroxide, which becomes more concentrated due to moisture evaporation after the mixed solution A3 of the first agent A1 and the second agent A2 is applied on the hair, addition of a nonvolatile, hydrophilic solvent, such as a polyol or lower alkyl ether thereof thereto are preferred. Furthermore, to give a conditioning effect to the hair, an ampholytic or cationic polymer, or a silicone and the like are also preferably added. Also they may appropriately contain a perfume material, an ultraviolet ray absorbent, a metal sequestering agent such as edetic acid, an antiseptic, a germicide such as methyl paraoxybenzoate, a stabilizing agent such as dibutylhydroxytoluene, 1-hydroxyethane-1,1-diphosphonic acid and sulfuric acid oxyquinoline, an organic solvent such as ethanol, benzyl alcohol and benzyloxy ethanol, a water-soluble polymer compound such as and hydroxyethylcellulose, a moisturizer, and the like.

20 [0034]

Furthermore, the viscosity (25°C) of the first agent A1 is preferably in the range of from 1 mPa·s to 50 mPa·s, more preferably in the range of from 3 mPa·s to 40 mPa·s, and even more preferably in the range of from 5 mPa·s to 30 mPa·s. The viscosity (25°C) of the second agent A2 is preferably in the range of from 1 mPa·s to 300 mPa·s, more

preferably in the range of from 3 mPa·s to 200 mPa·s, and even more preferably in the range of from 5 mPa·s to 100 mPa·s. The viscosity (25°C) of the mixed solution A3 of the first agent A1 and the second agent A2 is in the range of from 1 mPa·s to 100 mPa·s, preferably in the range of from 3 mPa·s to 50 mPa·s, and more preferably in the range of from 5 mPa·s to 30 mPa·s. It is noted that these viscosity values are found using a B-type rotary viscometer (Model TV-10) with the No. 1 rotor manufactured by Tokimec Inc., after rotating the rotor for 1 minute. Measurement is carried out at a rotation speed of 60 rpm when the measuring target has a viscosity of 100 mPa·s or less, 30 rpm when the measuring target has a viscosity of from 100 mPa·s to 200 mPa·s, and 12 rpm when the measuring target has a viscosity of 200 mPa·s to 500 mPa·s. The viscosities of the first agent, second agent and mixed solution are taken as the values measured in a 25°C thermostat bath. Furthermore, in the case of the mixed solution, the value measured immediately after mixing is used, and any temperature change due to heat of reaction is ignored. By setting the viscosity of the mixed solution in the above range, the mixed solution can be homogenously mixed without producing a foam in the container body. Furthermore, homogenous foam discharged from the squeeze foamer can be obtained which are easily applied on the hair, react well with the hair, and which

do not easily form drips after being applied on the hair.

[0035]

Adjustment of the viscosities of the first agent A1, second agent A2 and their mixed solution A3 to within the above ranges can be carried out by adding a water-soluble solvent such as ethanol to the first agent A1 and the second agent A2, or by appropriately adjusting the kind or added amount of the above-described surfactant, polyol or higher alcohol.

10 [0036]

Further, the squeeze container 6 for causing the two-part hair dye or bleach composition to foam has the same basic structure as a known squeeze container disclosed in, for example, JP-A-1995-215352. As illustrated in Fig. 2, the squeeze container 6 is composed of a flexible container body 4 and a squeeze foamer 5. The squeeze foamer 5 is composed of a cap member 7 attached to an aperture of the container body 4, and a head member 8 which sits over the cap member 7.

20 [0037]

A mixing device 10 is fitted to the cap member 7 so as to hang down from the cap member 7. In the interior of the mixing device 10 are provided a gas-liquid mixing chamber 11, and an air induct path 12 through which the interior space in the container body 4 and the gas-liquid mixing chamber 11 are in communication with each other.

Furthermore, in the mixing device 10, a dip tube 13 is fitted which extends into the container body 4. A net is attached to the ceiling of the gas-liquid mixing chamber 11 as foam homogenizing means 14, and the head member 8 side of the foam homogenizing means 14 serves as a liquid path 15.

[0038]

On the other hand, on the head member 8 are provided a liquid path 16 connecting to the liquid path 15 of the cap member 7, and a discharge outlet 17 connecting to the liquid path 16. Furthermore, a net is provided in the liquid path 16 in the vicinity of the discharge outlet 17 as foam homogenizing means 18.

[0039]

In the present invention, the foam homogenizing means 14 and 18 of the gas-liquid mixing chamber and the discharge outlet are not limited to a net. A porous material such as a sponge or a sintered body may also be used.

[0040]

One method for using such a two-part hair cosmetic for hair dyeing or bleaching is to, during use, first transfer the whole amount of the first agent A1 filled in the first container 2 to the container body 4 of the second container 3 filled with the second agent A2 to prepare the mixed solution A3. Accordingly, the total

volume of the first and second agents becomes the initial filled amount of the mixed solution A3 in the container body 4. In the present invention, this mixing is carried out so that the mixing of the first agent A1 and the
5 second agent A2 produces as little foam as possible, or so that no foam are produced. Here, "not producing foam" or "no foam is produced" are a concept which excludes the intentional production of foam, but includes cases where a small amount of foam is unintentionally produced when the
10 mixing is carried out like in the specific examples illustrated below. As long as a foam is not produced during the mixing, there are no restrictions on the mixing method. Examples of such methods include mixing carried out by shaking a test tube, or by moving the container
15 body 4 from a roughly upright state to an inverted through sideways state, and then once again returning to a roughly upright state. More specifically, the lid of the second container 3 is put on the container body 4 containing the first agent A1 and the second agent A2, and the cycle of
20 moving the container body 4 from a roughly upright state to an inverted through sideways state, and then once again returning to a roughly upright state, may be carried out 1 to 30 times, preferably 1.5 to 20 times, and more preferably 2 to 10 times, in 10 seconds. The operation of
25 moving from a roughly upright state to an inverted though sideways state, and then once again returning to a roughly

upright state is carried out 1 to 15 times, preferably 2 to 10 times, and even more preferably 3 to 7 times. A uniform mixed solution A3 can be easily obtained without a foam being produced even if the container body 4 is slowly shaken in this manner, since the first agent A1 and the second agent A2 used in the present invention have a much lower viscosity than a gel or cream type agent.

[0041]

As illustrated in Fig. 1B or Fig. 7, after the first agent A1 and the second agent A2 have been mixed, the squeeze foamer 5 is attached to the container body 4. It is noted that the mixing of the first agent A1 and the second agent A2 may also be carried out by transferring the whole amount of the first agent A1 to the container body 4 of the second container filled with the second agent A2, then attaching the squeeze foamer 5 to the container body 4 in place of the lid of the second container 3, and slowly shaking the container body 4 by a mixing method like that of shaking a test tube.

[0042]

The foam of the thus-discharged mixed solution A3 is applied on the hair using a hand or a comb. Furthermore, this discharging is repeated until a required amount has been discharged. Hair dyeing or bleaching can be carried out by subsequently leaving the foam on the hair for a given amount of time and then washing off.

[0043]

Here, in the two-part hair cosmetic 1 for hair dyeing or bleaching of the first aspect of the present invention, the ratio between the total volume of the first agent A1 and the second agent A2 (i.e., the initial filled amount of the mixed solution A3; hereinafter the same) and the inner volume of the container body 4 (total volume/inner volume) is characterized by being in the range of from 0.30 to 0.60. Therefore, for example, when the liquid amount of the mixed solution A3 is 100 mL, a container body 4 having an inner volume of 167 to 333 mL is used. This ratio between the initial filled amount of the mixed solution A3 and the inner volume of the container body 4 is preferably in the range of from 0.40 to 0.60, more preferably in the range of from 0.35 to 0.55, even more preferably in the range of from 0.40 to 0.50 and even more preferably in the range of from 0.45 to 0.50. By setting the ratio between the initial filled amount of the mixed solution A3 and the inner volume of the container body 4 in such a specific range, the foam of the mixed solution A3 discharged from the discharge outlet 17 can have a very fine foam quality and better foam life right from the start of squeezing, and drips after the foam have been applied on the hair can be suppressed. More specifically, by setting the ratio between the initial filled amount of the mixed solution A3 and the

inner volume of the container body 4 to 0.30 to 0.60, as illustrated in Fig. 3, when discharging the foam the gas-liquid mixing ratio, which acts as an index for foam quality, can be stabilized without the air induct path 12 of the gas-liquid mixing chamber 11 being blocked by mixed solution A3 in the container body 4 from the start of squeezing even if the container body 4 is squeezed until both opposing sides thereof come into contact with each other. Therefore, when applying on the hair, drips are less likely to form and color unevenness is less likely to occur.

[0044]

This gas-liquid mixing ratio is a value obtained by measuring the mass and volume of the discharged product at 25°C in the following manner. Specifically, 20 g is discharged from a squeeze container 6 containing 80 g of the mixed solution A3 into a 1,000 mL graduated cylinder. The gas-liquid mixing ratio (mL/g) is found by measuring the total volume of the foam and the liquid 1 minute after the initial discharge, and then dividing the total volume (mL) of the measured foam and liquid by 20 g. However, when measuring the effects of the ratio between the total volume of the first agent A1 and the second agent A2 and the inner volume of the container body 4, the value is found by measuring the initial filled amount.

[0045]

The two-part hair cosmetic for hair dyeing or bleaching of the second aspect of the present invention has, in the two-part hair cosmetic for hair dyeing or bleaching of the first aspect of the present invention, a ratio between the total volume of the first agent A1 and the second agent A2 and the inner volume of the container body 4 (total volume/inner volume) of from 0.30 to 0.70, preferably from 0.35 to 0.60, more preferably from 0.40 to 0.55, and even more preferably from 0.45 to 0.50.

Furthermore, as illustrated in Fig. 4, the torso outer shape of the container body 4 has a cross-section S with a ratio a/b of minor axis L_a to major axis L_b at a middle portion in a height direction of the container body 4 of from 0.5 to 1.0. Here, "middle portion in a height direction of the container body 4" refers to the middle portion of the height L_h (height from the bottom of the container body 4 to the lower edge of a cap member 7 of the squeeze foamer 5) of the container body 4.

[0046]

The ratio a/b of minor axis L_a to major axis L_b of the cross-section S is preferably in the range of from 0.60 to 0.90, and more preferably in the range of from 0.70 to 0.80. The cross-section S of the container body 4 is preferably an ellipse rather than a circle.

[0047]

The ratio a/b of minor axis L_a to major axis L_b

affects the thrust required to squeeze the container body 4 and the liquid amount which is discharged by squeezing. By setting this ratio a/b of minor axis L_a to major axis L_b to 0.5 to 1.0, a sufficient foam amount can be discharged by squeezing with a smaller thrust without having to squeeze the container body 4 until both opposing sides thereof come into contact with each other. This also allows the recovery properties of the squeezed container body 4 to be improved.

10 [0048]

More specifically, when discharging 3 g or more of the mixed solution A3, which is suitable to be taken on one hand, in a single squeeze from the container body 4, the thrust required to squeeze the container body 4 can be set to 5 kgf or less.

[0049]

Here, the thrust is a value measured in the following manner. Specifically, the thrust is the measured value at 25°C, with a filled amount of mixed solution A3 of 80 g, of the maximum load at which the middle portion of the height L_h (height from the bottom of the container body 4 to the lower edge of a cap member 7 of the squeeze foamer 5) of the container body 4 is squeezed at 15 mm/sec up to a distance $1/2$ of the minor axis in the minor axis direction from both opposing sides of the container body 4 with a rod-like member. This rod-

like member is 15 mm in diameter, is made of stainless steel, and has a tip with a height of 5 mm in a roughly dome shape. However, when measuring the effects of the ratio between the total volume of the first agent A1 and the second agent A2 and the inner volume of the container body 4, the value is found by measuring the initial filled amount.

[0050]

Furthermore, regarding the foam amount discharged by one squeeze, the mixed solution A3 can easily be set to 2 g or more, which is suitable for providing in one hand, and more preferably 3 g or more. Therefore, even when applying the mixed solution over all of the hair, the number of squeezes required to discharge that mixed solution can be set at about 30 times or less, so that the hand doing the squeezing does not get tired. Furthermore, when the discharged foam is applied on the hair, drips are less likely to form and color unevenness is less likely to occur.

[0051]

The two-part hair cosmetic for hair dyeing or bleaching of the third aspect of the present invention has, in the two-part hair cosmetic for hair dyeing or bleaching of the first aspect of the present invention, a ratio between the total volume of the first agent A1 and the second agent A2 and the inner volume of the container body

4 (total volume/inner volume) of from 0.30 to 0.70, preferably from 0.35 to 0.60, more preferably from 0.40 to 0.55, and even more preferably from 0.45 to 0.50.

Furthermore, the torso outer shape of the container body 4 has an area at a middle portion in a height direction of the container body 4 of from 12 cm² to 30 cm², preferably from 17 cm² to 25 cm², and more preferably from 19 cm² to 23 cm².

[0052]

10 The area of the cross-section S affects how easily the container body 4 is to grip, the thrust required to squeeze the container body 4, and the liquid amount which is discharged by squeezing. Thus, by setting this area in the above-described range, the liquid amount of the mixed solution A3 discharged by one squeeze can easily be set to 15 2 g or more, and more preferably 3 g or more, without having to squeeze the container body 4 until both opposing sides thereof come into contact with each other.

[0053]

20 Therefore, even when applying the mixed solution over all of the hair, the number of squeezes required to discharge that mixed solution can be set at about 30 times or less, so that the hand doing the squeezing does not get tired. Furthermore, when the discharged foam is applied 25 on the hair, drips are less likely to form and color unevenness is less likely to occur.

[0054]

The compositions of the two-part hair cosmetic for hair dyeing or bleaching of the above first, second and third aspects of the present invention may be
5 appropriately combined.

[0055]

Furthermore, in all of the first, second and third two-part hair cosmetics for hair dyeing or bleaching, to reduce the thrust required to squeeze the container body 4
10 and to improve the recovery properties of the squeezed container body 4, the container body 4 is preferably formed from a polyolefin resin, such as polypropylene (PP), high density polyethylene (HDPE), medium density polyethylene (MDPE), low density polyethylene (LDPE) and
15 linear low density polyethylene (LLDPE). Among them, polypropylene (PP) is preferable. Furthermore, in the case of forming the container body 4 from such a polyolefin resin, the "2/3 power coefficient", which is the ratio between the resin weight w (g) of the container
20 body 4 and the 2/3 power of the inner volume V of the container body 4 ($w/V^{2/3}$), is preferably set at a range of from 0.40 to 0.60, and more preferably at a range of from 0.45 to 0.55. Thus, if the inner volume of the container body 4 is 210 mL, the resin weight is preferably in the
25 range of from 14 g to 20 g, and more preferably in the range of from 16 g to 18 g. As a result, the thrust

required for squeezing can be reduced, recovery properties can be improved, and continuous squeezing can be repeatedly carried out.

[0056]

- 5 In addition, in all of the first, second and third two-part hair cosmetics for hair dyeing or bleaching, to even further improve the foam quality of the foam of the mixed solution A3 discharged from the squeeze container 6, it is preferred to set the ratio between the aperture area of the narrowest portion of the air induct path 12 and the flow path cross-sectional area of the dip tube 13 (aperture area of the narrowest portion/flow path cross-sectional area) to from 0.05 to 0.25, more preferably from 0.055 to 0.20, and even more preferably from 0.060 to 0.10.
- 10 If a plurality of air induct paths 12 of the squeeze foamer 5 are formed, the ratio between the total of those aperture areas of the narrowest portions and the flow path cross-sectional area of the dip tube 13 is set in the above range. From the perspectives of ease of molding and foam quality, the number of air induct paths 12 is preferably in the range of from 1 to 8, more preferably in the range of from 2 to 6 and even more preferably 3 or 4. Furthermore, if there are variations in the cross-sectional area of the dip tube 13 flow path, the flow path cross-sectional area of the narrowest portion is used in the calculation of the above ratio.
- 15
- 20
- 25

[0057]

As a result of the above features, the gas-liquid mixing ratio is reduced and the proportion of liquid in the foam is increased, whereby the tendency of drips to form can be prevented. Furthermore, deterioration in dyeing performance, such as a reduction in the application efficiency of the mixed solution A3 on the hair (liquor ratio) caused by individual bubbles becoming larger and turning into foam having a rough texture, so-called "crab bubbles", due to the gas-liquid mixing ratio becoming too high, and even dripping or color unevenness, can be prevented.

[0058]

In addition, the roughness of the net forming the foam homogenizing means 14 on the gas-liquid mixing chamber 11 side is preferably a 50 to 220 mesh, more preferably a 90 to 195 mesh, and even more preferably a 130 to 170 mesh. The roughness of the net forming the foam homogenizing means 18 on the discharge outlet 17 side is preferably a 150 to 280 mesh, more preferably a 165 to 250 mesh, and even more preferably a 180 to 220 mesh. Here, "mesh" refers to the number of holes per 1 inch.

[0059]

Furthermore, as illustrated in Fig. 5, if a user excessively tilts the squeeze container 6 upon discharging the mixed solution A3 as foam, so that the mixed solution

A3 in the container body 4 blocks the air induct path 12 of the squeeze foamer 5, the mixed solution A3 cannot be discharged in a foam even if the container body 4 is squeezed. Therefore, a container structure which does not allow the squeeze container 6 to be tilted in this way when being squeezed by a user is preferable.

[0060]

Therefore, as illustrated in Fig. 6(a), the tip of the discharge outlet 17 is preferably made to have an angle θ , formed between the axis Lx perpendicular to the aperture face of the discharge outlet 17 and the vertical direction Ly when the squeeze container 6 is stood upright, of 80° to 10° by either attaching a downward-facing discharge nozzle 21 or by integrally forming such a discharge nozzle 21 with the head portion 8. This angle θ is more preferably 65° to 20° , and especially preferably 50° to 30° . As illustrated in Fig. 6(b), because a user usually does not tilt the axis Lx perpendicular to the aperture face of the discharge outlet 17 more than the orientation of the vertical direction, by forming such a discharge outlet 17, the air induct path 12 can be prevented from being covered by the mixed solution A3 when the user tilts the container body 4.

25 EXAMPLES

[0061]

The following examples were all carried out at room temperature (25°C).

[0062]

Test Example 1

- 5 (1) Preparation of Two-part hair Cosmetic for Hair Dyeing

The first and second agents of the two-agent type composition for hair dyeing having the blended compositions shown in Tables 1 and 2 were prepared. The
10 viscosity and pH of each of the first and second agents were measured. Also measured were the viscosity and pH of mixed solutions in a 4:6 mass ratio of the first and second agents. Viscosity was measured using a B-type rotary viscometer with the No. 1 rotor by rotating at 30
15 rpm for 1 minute. The pH was measured using a pH meter (F-52, electrode 9611-10D, manufactured by Horiba, Ltd.). These results are shown in Table 3.

[0063]

On the other hand, the squeeze container 6 of Fig.
20 1B was constituted of a flexible container body 4 and a squeeze foamer ("S1 Squeeze Foamer" manufactured by Daiwa Can Company) to serve as a squeeze container for use in Test Example 1. This flexible container body 4 was made from polypropylene (PP), and had a resin weight of 17 g
25 and an interior volume of 210 mL. The $2/3$ power coefficient α calculated from this resin weight and

interior volume ($\alpha = w/V^{2/3}$) was 0.46. The cross-sectional profile at a height 55 mm from the bottom, which corresponds to the middle in the height direction of the container body 4, was an ellipse (61 mm major axis, 44 mm minor axis, 21 cm² area). The ratio L_a/L_b of minor axis L_a to major axis L_b was 0.72.

[0064]

Furthermore, as the homogenizing means in the squeeze foamer 5, a 150 mesh net was provided on the gas-liquid mixing chamber 11 side and a 200 mesh net was provided on the discharge outlet 17 side. The aperture area (total of 3 locations) of the narrowest portion of the air induct path 12 in the squeeze foamer was 0.27 mm², and the ratio between this aperture area and the flow path cross-sectional area of the dip tube 13 was 0.086.

[0065]

(2) Discharge Properties Evaluation

The above-described squeeze container was charged with 40 g of the first agent and 60 g of the second agent. Shaking was then carried out by moving the container body from a roughly upright state to an inverted state, and then once again returning to a roughly upright state at a rate of 3 times in 10 seconds. This shaking was carried out 5 times. As a result of this shaking, the mixed solution of the first and second agents was mixed without producing a foam. A squeeze foamer was then attached.

[0066]

Next, the squeeze container was stood upright, and then squeezed 30 mm by the same method as the below-described thrust measurement for about 2 seconds per
5 squeeze to discharge the foamy mixed solution. The (a) discharge amount per squeeze was evaluated in the following manner, and (b) the gas-liquid mixing ratio was measured in the following manner to evaluate the foam quality of the discharged foam.

10 Furthermore, the (c) thrust and the (d) recovery properties during squeezing were evaluated as follows.

These results are shown in Table 4.

[0067]

(a) Discharge Amount Per Squeeze

15 The mass of the mixed solution discharged by repeatedly squeezing 3 times from the initial time was measured to determine the discharge amount (g) per squeeze. Evaluation was carried out using this value as follows.

"AA": 3 g or more

20 "A": 2 g or more to less than 3 g

"B": 1 g or more to less than 2 g

"C": less than 1 g

[0068]

(b) Gas-liquid Mixing Ratio

25 20 g was discharged from the squeeze container into a 1,000 mL graduated cylinder. The gas-liquid mixing

ratio (mL/g) was found by dividing the total volume (mL) of the foam and the liquid 1 minute after the initial discharge by 20 g. Using this value, the evaluation was carried out as follows.

- 5 "AA": 20 mL/g or more to less than 30 mL/g
 - "A": 15 mL/g or more to less than 20 mL/g, or 30 mL/g or more to less than 40 mL/g
 - "B": 10 mL/g or more to less than 15 mL/g, or 40 mL/g or more to less than 50 mL/g
 - 10 "C": less than 10 mL/g, or 50 mL/g or more
- [0069]

The evaluated criteria were determined from the perspectives of the amount placed on the hand, and the liquor ratio when coated on the hair. However, cases where the volume of liquid immediately after discharging 20 g was 3 mL or more were all evaluated as "C" since such cases would be problematic as the liquid would trickle down when taken in the hand.

[0070]

20 (c) Thrust

A foam of the mixed solution was discharged by squeezing at 25°C. The middle portion (position 55 mm from the bottom of the container body 4) of a height L_h of the container body 4 was squeezed 15 mm/sec to a distance 1/2 of the minor axis in the minor axis direction from both opposing sides of the container body 4 with a rod-

like member made of stainless steel having a tip with a diameter of 15 mm and a height of 5 mm in a roughly dome shape. The maximum load at the first squeeze was measured. From this measured value, evaluation was carried out as

5 follows.

"AA": less than 5 Kgf

"A": 5 Kgf or more to less than 5.5 Kgf

"B": 5.5 Kgf or more to less than 6 Kgf

"C": 6 Kgf or more

10 [0071]

(d) Recovery properties

After the measurement of (c) was carried out, the time taken for the container body to return to its original shape when the load was released was measured.

15 "AA": less than 0.5 seconds

"A": 0.5 seconds or more to less than 1 second

"B": 1 second or more to less than 3 seconds

"C": 3 seconds or more (an operation to help the container body to return to its original shape was required, such as

20 applying pressure in the major axis direction)

[0072]

Test Examples 1-2 to 1-6

The initial filled amount in the container of the mixed solution (mass ratio of the first and second agents
25 of 4:6) was changed as shown in Table 4 while keeping the same ratio. Then, including each of the evaluations in

Test Example 1, the above-described discharge properties were evaluated in the initial state. The results are shown in Table 4.

[0073]

5 [Table 1]

First agent blend component	Blend amount (mass%)
Meta-aminophenol	0.03
Toluene-2,5-diamine	0.18
Resorcin	0.07
5-Amino-ortho-cresol	0.04
2,4-Diaminophenoxyethanol hydrochloride	0.06
Strong ammonia water	6.0
Ammonium hydrogencarbonate	10.5
Decylpoly(1.4)glucoside	6.16
Polyoxyethylene(2) lauryl ether sodium sulfate	2.7
Polyoxyethylene(9) tridecyl ether	0.5
Polyoxyethylene(23) lauryl ether	2.0
Myristyl alcohol	0.2
Propylene glycol	4.0
Ethanol	10.0
Dimethyldiallylammonium chloride/acrylic acid copolymer	0.4
Dimethyldiallylammonium chloride/acrylamide copolymer	0.5
Royal jelly extract	0.01
L-arginine	0.01
Ascorbic acid	0.4
Sodium sulfite anhydride	0.5
Tetrasodium edetate dihydrate	0.1
Perfume	0.95
Purified water	Balance
Viscosity (mPa·s)	14
pH	9.1

[0074]

[Table 2]

Second agent blend component	Blend amount (mass%)
Hydrogen peroxide water (35%)	16.3
Polyoxyethylene(2) lauryl ether sodium sulfate	0.6
Cetanol	0.48
Myristyl alcohol	0.28
Oxyquinoline sulfate	0.04
Hydroxyethane diphosphonic acid	0.08
Sodium hydroxide solution	(*1)
Purified water	Balance
Viscosity (mPa·s)	15

(*1): the amount required for adjusting pH to 3.5

5 [0075]

[Table 3]

Mixed solution viscosity (mPa·s)	7
Mixed solution pH	9.0

[0076]

[Table 4]

[illegible]

[0077]

From Table 4, it can be seen that for Test Examples 1 to 1-5, which had a ratio between the initial filled volume of the mixed solution and the inner volume of the container body of from 0.30 to 0.70, foam quality could be stabilized, whereas for Test Example 1-6, which had a ratio larger than this, the foam quality was looser and the thrust was higher.

[0078]

10 Test Examples 2 to 2-5

Evaluation of the discharge properties was carried in the same manner as in Test Example 1, except that the used container body of the squeeze container had a different ratio between the minor axis and major axis of the torso cross-section as shown in Table 5, and that the evaluation was carried out at the point where the mixed solution in the container body was 80 g. The results are shown in Table 5.

[0079]

20 From Table 5, it can be seen that for Test Examples 2 to 2-4, in which the ratio between minor axis and major axis was in the range of from 0.50 to 1.0, the recovery properties were better than those for Test Example 2-5, in which the ratio was lower.

[0080]

[Table 5]

	Test Ex. 2	Test Ex. 2-2	Test Ex. 2-3	Test Ex. 2-4	Test Ex. 2-5
Container body material	PP	←	←	←	←
Container body resin weight	17	←	←	←	←
Container body inner volume (mL)	210	←	←	←	←
2/3 Power coefficient ($w/V^{2/3}$)	0.47	←	←	←	←
Minor axis Ia of the torso cross-section of the container body (mm)	42	46	37	52	33
Major axis Ib of the torso cross-section of the container body (mm)	64	58	72	52	82
Ratio Ia/Ib of minor axis to major axis	0.65	0.80	0.52	1.0	0.40
Area of the torso cross-section of the container body (cm ²)	21	←	←	←	←
Homogenizing means (net on the gas-liquid mixing chamber side)	150	←	←	←	←
roughness (mesh)	200	←	←	←	←
Homogenizing means (net on the nozzle side) roughness (mesh)	0.086	←	←	←	←
Air aperture area/Liquid flow path cross-sectional area	0.27	←	←	←	←
Air collector aperture area (mm ²)	100	←	←	←	←
Initial filled amount of the mixed solution (mL)	0.48	←	←	←	←
Ratio between the initial filled amount of the mixed solution and the inner volume of the container body					
Discharge properties	AA	A	A	B	B
Discharge amount per squeeze	3.2 g	2.9 g	2.7 g	1.6 g	1.8 g
Gas-liquid mixing ratio	AA	AA	AA	AA	AA
	22 mL/g	22 mL/g	22 mL/g	22 mL/g	22 mL/g
Thrust	AA	A	AA	A	AA
	4.9 Kgf	5.3 Kgf	4.8 Kgf	5.5 Kgf	4.5 Kgf
Recovery properties	AA	AA	A	AA	B
	Within 0.5 seconds	Within 0.5 seconds	0.9 seconds	Within 0.5 seconds	2 seconds

[0081]

Test Examples 3 to 3-6

Evaluation of the discharge properties was carried in the same manner as in Test Example 1, except that the
5 used container body of the squeeze container had a different torso cross-sectional area as shown in Table 6, and that the evaluation was carried out at the point where the mixed solution in the container body was 80 g. The results are shown in Table 6.

10 [0082]

From Table 6, it can be seen that for Test Examples 3 to 3-4, in which the torso cross-sectional area of the container body was in the range of from 12 cm² to 30 cm², the discharge amount of 1 squeeze was larger than for both
15 Test Example 3-5, in which the cross-sectional area was smaller, and Test Example 3-6, in which the cross-sectional area was larger.

[0083]

Test Examples 4 to 4-6

Evaluation of the discharge properties was carried in the same manner as in Test Example 1, except that the used container body of the squeeze container had a different ratio between the aperture area of the narrowest portion of the air induct path and the dip tube as shown in Table 7, and that the evaluation was carried out at the point where the mixed solution in the container body was 80 g. The results are shown in Table 7.

[0085]

From Table 7, it can be seen that good foam quality could be obtained for Test Examples 4 to 4-4, in which this ratio was in the range of 0.05 to 0.25.

[0086]

In contrast, it can be seen that if this ratio is small as in Test Example 4-5, although the discharge amount increases, the foam is looser, while if this ratio is large as in Test Example 4-6, the volume of the liquid when measuring the gas-liquid mixing ratio is 3 mL or more, so that the discharge amount is reduced.

[0087]

[Table 7]

	Test Ex. 4	Test Ex. 4-2	Test Ex. 4-3	Test Ex. 4-4	Test Ex. 4-5	Test Ex. 4-6
Container body material	PP	←	←	←	←	←
Container body resin weight	17	←	←	←	←	←
Container body inner volume (mL)	210	←	←	←	←	←
2/3 Power coefficient ($w/\sqrt{2/3}$)	0.47	←	←	←	←	←
Minor axis Ia of the torso cross-section of the container body (mm)	44	←	←	←	←	←
Major axis Ib of the torso cross-section of the container body (mm)	61	←	←	←	←	←
Ratio Ia/Ib of minor axis to major axis	0.72	←	←	←	←	←
Area of the torso cross-section of the container body (cm ²)	21	←	←	←	←	←
Homogenizing means (net on the gas-liquid mixing chamber side) roughness (mesh)	150	←	←	←	←	←
Homogenizing means (net on the nozzle side) roughness (mesh)	200	←	←	←	←	←
Air aperture area/Liquid flow path cross-sectional area	0.07	0.09	0.05	0.24	0.04	0.3
Air collector aperture area (mm ²)	0.27	←	←	←	←	←
Initial filled amount of the mixed solution (mL)	100	←	←	←	←	←
Ratio between the initial filled amount of the mixed solution and the inner volume of the container body	0.48	←	←	←	←	←
Discharge properties						
Discharge amount per squeeze	AA 3.5 g	AA 3.1 g	AA 3.8 g	A 2.1 g	AA 3.9 g	C 0.9 g
Gas-liquid mixing ratio	AA 20 mL/g	AA 23 mL/g	A 17 mL/g	AA 25 mL/g	C 9 mL/g	Liquid, 3 mL or more C
Recovery properties	AA Within 0.5 seconds	AA Within 0.5 seconds	AA Within 0.5 seconds	AA Within 0.5 seconds	AA Within 0.5 seconds	AA Within 0.5 seconds

[0088]

Test Examples 5 to 5-6

Evaluation of the discharge properties was carried in the same manner as in Test Example 1, except that the
5 used $2/3$ power coefficient α calculated from the resin weight and the inner volume of the container body ($\alpha = w/V^{2/3}$) was different as shown in Table 8, and that the evaluation was carried out at the point where the mixed solution in the container body was 80 g. The results are
10 shown in Table 8.

[0089]

From Table 8, it can be seen that for Test Examples 5 to 5-4, in which the $2/3$ power coefficient was in the range of from 0.40 to 0.60, the discharging could be
15 carried out with a low thrust and with good recovery properties.

[0090]

In contrast, it can be seen that if this ratio is low due to a low resin weight of the container body as in
20 Test Example 5-5, although the thrust is small, recovery does not take place easily, while if this ratio is large due to a large resin weight as in Test Example 5-6, although recovery takes place easily, a large thrust is required.

[0091]

[Table 8]

	Test Ex. 5	Test Ex. 5-2	Test Ex. 5-3	Test Ex. 5-4	Test Ex. 5-5	Test Ex. 5-6
Container body material	PP	←	←	←	←	←
Container body resin weight	16	19	15	20	11	25
Container body inner volume (mL)	210	←	←	←	←	←
2/3 Power coefficient ($w/V^{2/3}$)	0.46	0.54	0.42	0.58	0.30	0.70
Minor axis La of the torso cross-section of the container body (mm)	44	←	←	←	←	←
Major axis Lb of the torso cross-section of the container body (mm)	60	←	←	←	←	←
Ratio La/Lb of minor axis to major axis	0.72	←	←	←	←	←
Area of the torso cross-section of the container body (cm ²)	21	←	←	←	←	←
Homogenizing means (net on the gas-liquid mixing chamber side) roughness (mesh)	150	←	←	←	←	←
Homogenizing means (net on the nozzle side) roughness (mesh)	200	←	←	←	←	←
Air aperture area/Liquid flow path cross-sectional area	0.086	←	←	←	←	←
Air collector aperture area (mm ²)	0.27	←	←	←	←	←
Initial filled amount of the mixed solution (mL)	100	←	←	←	←	←
Ratio between the initial filled amount of the mixed solution and the inner volume of the container body	0.48	←	←	←	←	←
Discharge properties						
Discharge amount per squeeze	AA 3.2 g	AA 3.2 g	AA 3.2 g	AA 3.2 g	AA 3.2 g	AA 3.2 g
Gas-liquid mixing ratio	AA 22 mL/g	AA 22 mL/g	AA 22 mL/g	AA 22 mL/g	AA 22 mL/g	AA 22 mL/g
Thrust	AA 4.9 Kgf	AA 5.39 Kgf	AA 4.4 Kgf	AA 5.59 Kgf	AA 4.0 Kgf	AA 7.0 Kgf
Recovery properties	AA Within 0.5 seconds	AA Within 0.5 seconds	A 1 second	AA Within 0.5 seconds	C Did not return	AA Within 0.5 seconds

INDUSTRIAL APPLICABILITY

[0092]

The two-part hair cosmetic for hair dyeing or bleaching of the present invention can be applied for hair
5 dyeing or bleaching.

CLAIMS

1. A two-part hair cosmetic for hair dyeing or bleaching, comprising a two-part hair dye or bleach composition comprising a first agent containing an alkaline agent and a second agent containing hydrogen peroxide, and a squeeze container for discharging in a foam a mixed solution of the first and second agents, wherein
- at least one of the first or second agents contains a foaming agent,
- the mixed solution of the first and second agents has a viscosity (25°C) of from 1 mPa·s to 100 mPa·s,
- the squeeze container has a container body and a squeeze foamer,
- the squeeze foamer has a gas-liquid mixing chamber for causing the mixed solution to foam by mixing air in the container body with the mixed solution, foam homogenizing means for homogenizing foam of the mixed solution which has been made to foam in the gas-liquid mixing chamber, and a discharge outlet for discharging the homogenized foam, and
- a ratio between a total volume of the first and second agents and an inner volume of the container body (total volume/inner volume) is in a range of from 0.30 to 0.60.

2. A two-part hair cosmetic for hair dyeing or bleaching, comprising a two-part hair dye or bleach composition comprising a first agent containing an
5 alkaline agent and a second agent containing hydrogen peroxide and a squeeze container for discharging in a foam a mixed solution of the first and second agents, wherein
at least one of the first or second agents contains a foaming agent,

10 the mixed solution of the first and second agents has a viscosity (25°C) of from 1 mPa·s to 100 mPa·s,

the squeeze container has a container body and a squeeze foamer,

the squeeze foamer has a gas-liquid mixing chamber
15 for causing the mixed solution to foam by mixing air in the container body with the mixed solution, foam homogenizing means for homogenizing foam of the mixed solution which has been made to foam in the gas-liquid mixing chamber, and a discharge outlet for discharging the
20 homogenized foam,

a ratio between a total volume of the first and second agents and an inner volume of the container body (total volume/inner volume) is in a range of from 0.30 to 0.70, and

25 a torso outer shape of the container body has a cross-section with a ratio of minor axis to major axis at

a middle portion in a height direction of the container body of from 0.50 to 1.0.

3. A two-part hair cosmetic for hair dyeing or
5 bleaching, comprising a two-part hair dye or bleach composition comprising a first agent containing an alkaline agent and a second agent containing hydrogen peroxide and a squeeze container for discharging in a foam a mixed solution of the first and second agents, wherein
10 at least one of the first or second agents contains a foaming agent,

the mixed solution of the first and second agents has a viscosity (25°C) of from 1 mPa·s to 100 mPa·s,

the squeeze container has a container body and a
15 squeeze foamer,

the squeeze foamer has a gas-liquid mixing chamber for causing the mixed solution to foam by mixing air in the container body with the mixed solution, foam homogenizing means for homogenizing foam of the mixed
20 solution which has been made to foam in the gas-liquid mixing chamber, and a discharge outlet for discharging the homogenized foam,

a ratio between a total volume of the first and second agents and an inner volume of the container body
25 (total volume/inner volume) is in a range of from 0.30 to 0.70, and

a torso outer shape of the container body has a cross-section with an area at a middle portion in a height direction of the container body of from 12 cm² to 30 cm².

5 4. The two-part hair cosmetic for hair dyeing or bleaching according to any of claims 1 to 3, wherein the container body is formed from a polyolefin resin, and a ratio between a resin weight w (g) of the container body and $2/3$ power of an inner volume V of the container body
10 ($w/V^{2/3}$), is in a range of from 0.40 to 0.60.

 5. The two-part hair cosmetic for hair dyeing or bleaching according to any of claims 1 to 3, wherein the squeeze foamer comprises an air induct path which allows
15 an interior space and a gas-liquid mixing chamber of the container body to be in communication with each other, and a dip tube which extends from the gas-liquid mixing chamber to the container body bottom side, and wherein a ratio between an aperture area of the narrowest portion of
20 the air induct path and a flow path cross-sectional area of the dip tube (aperture area of the narrowest portion/flow path cross-sectional area) is in a range of from 0.05 to 0.25.

25 6. The two-part hair cosmetic for hair dyeing or bleaching according to any of claims 1 to 3, wherein the

discharge outlet is formed such that an angle formed between an axis perpendicular to an aperture face of the discharge outlet and a vertical direction when the squeeze container is stood upright is set in a range of from 10° to 80°.