

System and Method for Uplink Grant-Free Transmission Scheme

[0001]

TECHNICAL FIELD

5 [0002] The present invention relates to a system and method for wireless communications, and, in particular embodiments, to a system and method for uplink grant-free transmission scheme.

BACKGROUND

10 [0003] In a typical wireless network such as long-term evolution (LTE) network, the selection of shared data channels for uplink (UL) is scheduling/grant based, and the scheduling and grant mechanisms are controlled by a base station (BS) in a network. A user equipment (UE) sends an UL scheduling request to the base station. When the BS receives the scheduling request, the BS sends an UL grant to the UE indicating its UL resource allocation. The UE then transmits data on the granted resource.

15 [0004] An issue with this approach is that the signaling resource overhead for the scheduling/grant mechanism can be quite large, especially in cases where the data transmitted is small. For example, for small packet transmissions of around 20 bytes each, the resources used by the scheduling/grant mechanism could be around 30%, or even 50%, of the packet's size. Another issue with this approach is the scheduling/grant procedure causes an initial delay in data
20 transmission. Even when the resources are available, there is a minimum 7-8ms delay in a typical wireless network between a scheduling request being sent and the first uplink data transmission.

SUMMARY OF THE INVENTION

[0005] These and other problems are generally solved or circumvented, and technical advantages are generally achieved, by preferred embodiments of the present invention which provide a system and method for uplink grant-free transmission scheme.

[0006] In accordance with an aspect of the present invention, a method includes
5 implementing, by a BS, a grant-free uplink transmission scheme. The grant-free uplink transmission scheme defines a first contention transmission unit (CTU) access region in a time-frequency domain, defines a plurality of CTUs, defines a default CTU mapping scheme by mapping at least some of the plurality of CTUs to the first CTU access region, and defines a default user equipment (UE) mapping scheme by defining rules for mapping a plurality of UEs
10 to the plurality of CTUs.

[0007] In accordance with another aspect of the present invention, a base station (BS) includes a processor, and a computer readable storage medium storing programming for execution by the processor, the programming including instructions to implement a grant-free uplink transmission scheme, receive an uplink transmission from a user equipment (UE), attempt
15 to decode the uplink transmission blindly, and indicate to the UE whether the attempt to decode the uplink transmission blindly was successful. The grant-free uplink transmission scheme defines a plurality of contention transmission units (CTUs), defines one or more CTU access regions in a time-frequency domain, creates a default CTU mapping scheme by mapping the plurality of CTUs to the one or more CTU access regions, and creates a default UE mapping
20 scheme by defining rules for mapping a plurality of UEs to the plurality of CTUs.

[0008] In accordance with another aspect of the present invention, a method for a grant-free transmission scheme includes implementing, by a user equipment (UE), a default contention transmission unit (CTU) mapping scheme by determining an appropriate CTU for uplink transmission in accordance with a UE mapping rule and the default CTU mapping scheme, and
25 transmitting an uplink transmission, to a base station (BS), on the appropriate CTU.

[0009] In accordance with yet another aspect of the present invention, a user equipment (UE) includes a processor, and a computer readable storage medium storing programming for execution by the processor, the programming including instructions to implement a default contention transmission unit (CTU) mapping scheme by determining an appropriate CTU for
5 uplink transmission in accordance with a UE mapping rule and the default CTU mapping scheme, and transmitting, to a base station (BS), an uplink transmission on the appropriate CTU, determine whether a collision has occurred based on an indication by the BS, and re-transmit, to the BS, the uplink transmission using an asynchronous hybrid automatic repeat request (HARQ) mechanism when the UE determines a collision has occurred.

10

BRIEF DESCRIPTION OF THE DRAWINGS

[0010] For a more complete understanding of the present invention, and the advantages thereof, reference is now made to the following descriptions taken in conjunction with the accompanying drawings, in which:

15 [0011] Figure 1 is a block diagram illustrating a network in accordance with various embodiments;

[0012] Figure 2 is a diagram illustrating an example configuration of various contention transmission unit (CTU) access regions in accordance with various embodiments;

[0013] Figure 3 is a diagram illustrating an example mapping of CTUs to CTU access
20 regions in accordance with various embodiments;

[0014] Figure 4 is a diagram illustrating an example CTU index numbering in accordance with various embodiments;

[0015] Figures 5A and 5B are diagrams illustrating an example UE mapping and remapping in accordance with various embodiments;

[0016] Figure 6 is a block diagram of a joint signature and data detection using message passing algorithm method with an active UE detector in accordance with various embodiments;

[0017] Figures 7A and 7B are flow diagrams of base station (BS) activity in accordance with various embodiments;

[0018] Figures 8A and 8B are flow diagrams of user equipment (UE) activity in accordance with various embodiments; and

[0019] Figure 9 is a block diagram illustrating a computing platform that may be used for implementing, for example, the devices and methods described herein, in accordance with an embodiment.

DETAILED DESCRIPTION OF ILLUSTRATIVE EMBODIMENTS

[0020] The making and using of embodiments are discussed in detail below. It should be appreciated, however, that the present invention provides many applicable inventive concepts that can be embodied in a wide variety of specific contexts. The specific embodiments discussed are merely illustrative of specific ways to make and use the invention, and do not limit the scope of the invention.

[0021] Various embodiments are described with respect to a specific context, namely a LTE wireless communication network. Various embodiments may also be applied, however, to other wireless networks such as a worldwide interoperability for microwave access (WiMAX) network.

[0022] Figure 1 illustrates a block diagram of a network 100 according to various embodiments. A base station (BS) 102 manages uplink and downlink communications for various UEs 104-114 within its coverage area 116. BS 102 may alternatively be referred to as a cell tower, an eNodeB, an access network, and the like. BS 102 may support transmissions for multiple cellular carriers concurrently. BS 102 implements a grant-free uplink transmission

scheme, wherein contention transmission unit (CTU) access regions are defined so that UEs 104-114 may contend for and access uplink resources without a request/grant mechanism. The grant-free uplink transmission scheme may be defined by the BS, or it may be set in a wireless standard (e.g., 3GPP). UEs 104-114 may be mapped to various CTU access regions to avoid collision (i.e., when two or more UEs attempt to transmit data on the same uplink resource). However, if collision occurs, UEs 104-114 may resolve collisions using an asynchronous HARQ (hybrid automatic repeat request) method. BS 102 blindly (i.e., without explicit signaling) detects active UEs and decodes received uplink transmissions.

[0023] Under this scheme, UEs 104-114 may send uplink transmissions without the BS allocating resources to request/grant mechanisms. Therefore, total network overhead resources are saved. Furthermore, this system allows for time savings during uplink by bypassing the request/grant scheme. Although only one BS 102 and six UEs 104-114 are illustrated in Figure 1, a typical network may include multiple BS each covering transmissions from a varying multitude of UEs in its geographic coverage area.

[0024] Network 100 uses various high level signaling mechanisms to enable and configure grant-free transmissions. UEs 104-114 capable of grant-free transmissions signal this capability to BS 102. This allows BS 102 to support both grant-free transmissions and traditional signal/grant transmissions (e.g., for older UE models) simultaneously. The relevant UEs may signal this capability by, for example, RRC (radio resource control) signaling defined in the 3GPP (third generation partnership project) standard. A new field may be added to the UE capability list in RRC signaling to indicate whether the UE supports grant-free transmissions. Alternatively, one or more existing fields can be modified or inferred from in order to indicate grant-free support.

[0025] BS 102 also uses high-level mechanisms (e.g., a broadcast channel or a slow signaling channel) to notify UEs 104-114 of information necessary to enable and configure a

grant-free transmission scheme. For example, BS 102 may signal that it supports grant-free transmissions, its search space and access codes for CTU access regions, a maximum size of a signature set (i.e., the total number of signatures defined), a modulation and coding scheme (MCS) setting, and the like. Furthermore, BS 102 may update this information from time to time using, for example, a slow signaling channel (e.g., a signaling channel that only occurs in the order of hundreds of milliseconds instead of occurring in every TTI).

[0026] BS 102 implements a grant-free uplink transmission scheme. The grant-free transmission uplink scheme defines CTU access regions to enable grant-free transmissions by UE 104-114. A CTU is a basic resource, predefined by network 100, for contention transmissions. Each CTU may be a combination of time, frequency, code-domain, and/or pilot elements. Code-domain elements may be CDMA (code division multiple access) codes, LDS (low-density signature) signatures, SCMA (sparse code multiple access) codebooks, and the like. These possible code-domain elements are referred to generically as “signatures” hereinafter. Multiple UEs may contend for the same CTU. The size of a CTU is preset by the network and may take into account an expected transmission size, the amount of desired padding, and/or MCS levels.

[0027] A CTU access region is a time-frequency region where contention transmission occurs. The grant-free uplink transmission scheme may define multiple CTU access regions for network 100. The grant-free transmission uplink scheme may be defined by BS 102 via high level signaling (e.g., through a broadcast channel) or it may be pre-defined by a standard and implemented in UEs (e.g., in a UE’s firmware). The regions may exist in one or more frequency bands (intra-band or inter-band) and may occupy the entire uplink transmission bandwidth or a portion of the total transmission bandwidth of BS 102 or a carrier supported by BS 102. A CTU access region that occupies only a portion of the bandwidth allows BS 102 to simultaneously support uplink transmissions under a traditional request/grant scheme (e.g., for older UE models that cannot support grant-free transmissions). Furthermore, BS 102 may utilize unused CTUs for

scheduled transmissions under a request/grant scheme, or BS 102 may adjust the size of CTU access regions if portions of the access regions are not used for a period of time. Furthermore, the CTU access regions may frequency hop periodically. BS 102 may signal these changes in CTU access region size and frequency to UEs 104-114 through a slow signaling channel.

[0028] Figure 2 illustrates an example configuration for various CTU access regions defined by BS 102. In Figure 2, BS 102 supports transmissions for three carriers each operating at frequencies F_1 , F_2 and F_3 with bandwidth BW_1 , BW_2 and BW_3 . Figure 2 illustrates example CTU access regions 200 defined in all three carriers using different configurations. The configurations shown in Figure 2 are for illustrative purposes only, and alternative CTU access region configurations may be defined in various embodiments.

[0029] Multiple CTU access regions (e.g., as illustrated in Figure 2) allow each CTU access region to be categorized differently to provide different types of service to varying UE types. For example, the CTU access regions may be categorized to support different quality of service (QoS) levels, different UE configurations (e.g., in situations of carrier aggregation), different UE subscribed levels of service, different UE geometries, or a combination thereof. Furthermore, each CTU access region may be configured to support a different number of UEs. The size of each CTU access region may vary depending on the expected number of UEs using the region. For example, the size of a CTU access region may be based the history of loading in the CTU access region (such as the number of UEs), UE collision probability estimations, and/or measured UE collisions over a period of time.

[0030] Figure 3 illustrates an example CTU resource definition in various CTU access regions. Figure 3 illustrates four CTU access regions 302-308. The available bandwidth is divided into time-frequency regions for CTU access region 302-308, with each access region 302-308 occupying a predefined number of resource blocks (e.g., access region 302 occupies

RBs 1-4) of bandwidth. In Figure 3, CTUs are mapped identically to access regions 302-308, but varying views of this mapping are shown for illustrative purposes.

[0031] In Figure 3, each CTU access region is capable of supporting up to thirty-six UEs contending for the thirty-six CTUs defined in each region. Each CTU is a combination of time, frequency, signature, and pilot. Each access region 302-308 occupies a distinct frequency-time region. These frequency-time regions are further broken down to each support six signatures (S_1 - S_6) and six pilots mapped to each signature to create thirty-six total pilots (P_1 - P_{36}). A pilot/signature decorrelator at BS 102 is used to detect and decode individual UE signals and transmissions.

[0032] Therefore, under this scheme different UEs conduct uplink transmissions on the same signature. Various embodiments support signature collisions (i.e., when several UEs simultaneously access the same frequency-time resources by using the same signature). In the known art, it was previously believed that signature collisions irreparably degrade UE performance and should be absolutely avoided. However, it has been observed that while signature collisions may degrade UE performance, the transmitted information can still be decoded by BS 102 using various decoding schemes (e.g., a JMPA scheme as described in detail in subsequent paragraphs). Furthermore, it has also been observed that signature collisions between two UEs (e.g., UEs 104 and 106) do not affect the performance of other UEs (e.g., UEs 108-114). Therefore, signature collisions are not detrimental to overall system performance. Various embodiments map multiple potential UEs to the same frequency-time-signature resource so that, at each contention transmission, the system may be fully loaded.

[0033] In contrast, pilot collisions may not be supported. Similar to signature collision, pilot collision refers to cases when multiple UEs simultaneously access the same frequency-time-signature resources by using the same pilot sequence. However, unlike signature collisions, pilot collisions may lead to irreparable results in a grant-free transmission scheme. This is due to BS

102 being unable to decode a UE's transmission information in pilot collision scenarios because BS 102's is unable to estimate the individual channels of UEs using the same pilot. For example, assume two UEs (UE 104 and 106) have the same pilot and their channels are h_1 and h_2 , then BS 102 can only estimate a channel of quality of $h_1 + h_2$ for both UEs 104 and 106. Thus, the transmitted information will not be decoded correctly. Various embodiments may define a number of unique pilots (e.g. thirty-six pilots per access region in Figure 3) depending on the number of UEs supported in the system. The specific numbers given in Figure 3 are for illustrative purposes only, and the specific configuration of the CTU access regions and CTUs may vary depending on the network.

[0034] Various embodiments enable grant-free transmissions through the inclusion of mechanisms for collision avoidance through UE to CTU mapping/re-mapping and collision resolution through asynchronous HARQ. For a UE to successfully perform uplink transmissions in a grant-free scheme, the UE must determine a CTU on which data can be sent. A UE determines the CTU it should use for transmissions based on predefined mapping rules known by both the UE (e.g., UEs 104-114) and the base stations (e.g., BS 102) in a network (e.g., network 100). These mapping rules may be implicit (i.e., default) rules pre-defined for the UE (e.g. in an applicable standard or in the firmware of the UE) and/or explicit rules defined by a BS using high level signaling. For example, different mapping rules (as referred to as mapping configurations) are pre-defined in a wireless standard, such as 3GPP, and the index of the applicable mapping configuration is signaled to a UE by the BS.

[0035] The grant-free uplink transmission scheme assigns a unique, identifying CTU index, I_{CTU} , to each CTU in the CTU access regions. UEs determine which CTUs to transmit on based on mapping rules for choosing an appropriate CTU index. The mapping of CTU indexes may be distributed uniformly over the available resources taking into account the size of the CTU regions over the time-frequency domain and the desire to reduce BS decoding complexity. The

size of the CTU regions is taken into account so that UEs are not mapped to the same subset of available time-frequency resources.

[0036] For example, Figure 4 illustrates such a distribution of CTU indexes over the CTU access regions. Each signature-pilot grid 402-408 corresponds to a time-frequency access region 302-308 from Figure 3. As shown in Figure 4, indexes are distributed in the following order: time, frequency, signature, and then pilot. For example, index 0 is mapped to a first time and a first frequency. Index 1 is then mapped to a second time in the first frequency. Index 2 is mapped to the first time in a second frequency, and index 3 is mapped to the second time in the second frequency. Only when all the time-frequency combinations are exhausted is the next index (index 4) mapped to a different signature in the first time and first frequency. In this manner all 144 CTU indexes (i.e., four access regions multiplied by thirty-six pilots per region) are mapped to distribute UEs over the region and reduce the chance of signature and pilot collision. Various alternative embodiments may use different mapping rules for CTU index mapping.

[0037] The inclusion of default mapping rules allows a UE to automatically transmit data on the mapped CTU as soon as it enters a BS's coverage area without additional signaling. These default mapping rules may be based on a UE's dedicated connection signature (DCS), its DCS index assigned by a BS, the total number of CTUs, and/or other parameters such as subframe number. For example, a UE i may map to a CTU resource index, I_{CTU} based on a default formula:

$$I_{CTU} = DSC_i \bmod N_{CTU}$$

wherein N_{CTU} represents the total number of available CTU indexes (e.g., 144 in the examples given in Figures 3-4) and DSC_i is the DSC index of UE i .

[0038] A UE's DCS index may be assigned to the UE by a BS via high level signaling (e.g., through a broadcast, multicast, or unicast channel). Furthermore, this DCS index number may be used in conjunction with CTU index mapping to evenly distribute UEs across the CTU access regions. For example, when a UE enters a BS's (e.g., BS 102) coverage area, the BS may receive

notice of the UE entering its area. BS 102 may assign a DCS index (hence the DSC) to the UE. For example, the first UE is assigned $DCS_1 = 0$, the second UE is assigned $DCS_2 = 1$, the third UE is assigned $DCS_3 = 2$, and so on. When the UE maps to a CTU resource based on a default mapping formula (e.g., $I_{CTU} = DSC_i \bmod N_{CTU}$), the UEs will be assigned indexes based on their DCS index and the total number of CTUs. By combining this mapping formula with the appropriate CTU index mapping (e.g., Figure 4), the UEs may be distributed evenly across the CTU access regions. That is, the first UE will be mapped to index 0, the second UE will be mapped to index 1, etc.

[0039] A subset of UEs may be re-mapped periodically by the network to reduce collisions. UEs may be remapped in cases when UEs exchange packets frequently in a data session (referred to as active UEs). These active UEs may experience higher probabilities of collision when they are unevenly distributed across the available CTU access regions. For example, Figure 5A illustrates various UEs 502-516 mapped to four CTU access regions 518-524 under default mapping rules. In Figure 5A, UEs 502, 504, 514, and 516 are active UEs mapped to two of the four available CTU access regions, increasing their probability for collision. A BS associated with the UEs (e.g., BS 102) determines that the default mapping is causing too many collisions and remaps certain UEs (e.g., UE 504 and 514) to the other CTU access regions as shown in Figure 5B. BS 102 may detect the high level of collisions through high level signaling from the UEs or through repeated failed attempts to decode transmitted information (i.e., as previously discussed, pilot collisions cause failed attempts to decode transmission data). Alternatively, active UEs may be initially mapped to the same CTU in an access region. When the BS determines collisions are occurring due to this mapping, the active UEs may be re-mapped to different CTUs in the same access region. The various UEs 502-516 may revert to default mapping rules either implicitly when the UEs are no longer active or explicitly through network signaling. In alternative embodiments, this type of temporary re-mapping may also be

used to provide certain UEs with dedicated resources for very time-sensitive transmissions when requested by the UE or configured by the network.

[0040] By implementing the described UE mapping strategies, the number of initial collisions in a CTU access region may be controlled. However, collisions may still occur and must be resolved. When transmissions are successful, the UE will be notified by the BS through, for example, an ACK (acknowledgement) signal. The BS only sends the ACK signal when transmissions are successful. Therefore, if a UE does not receive an ACK signal within a predetermined time period, the UE determines that collision has occurred. Alternatively, the BS may receive an NACK (negative acknowledgement) signal when the transmission fails. The UE assumes transmission was successful unless it receives a NACK.

[0041] When collisions occur, they are resolved using asynchronous HARQ methods. Asynchronous HARQ methods differ from synchronous HARQ methods in that the UE does not attempt to retransmit on the same CTU when collision occurs. Rather the UE may choose a different CTU to retransmit on. For example, a random backoff procedure may be implemented. Each UE picks a backoff time period (e.g., a next TTI) randomly within a contention window to retransmit data. At the next TTI, the UE transmits data. The contention window size is a system parameter that may be signaled to the UE using high-level signaling.

[0042] When BS 102 receives transmitted information, it blindly decodes the transmitted information (referred to as blindly because BS 102 does not know which UE transmitted the information or which UEs are active in a network). For example, BS 102 may use JMPA (joint signature and data detection using MPA (message passing algorithm)) methods to blindly decode the transmitted information. Generally, MPA methods rely on channel knowledge and user-specific information to detect and decode data. JMPA initially assume all possible users might be active. It then iteratively detects the active users and simultaneously tries to detect their transmitted data. At the end of the iteration, among the all possible user pool, a list of active

users and their detected data are provided by JMPA. A detailed description of a JMPA system and method may be found in U.S. Provisional Application No. 61/737,601, filed on December 14, 2012, entitled “System and Method for Low Density Spreading Modulation Detection,” which application is hereby incorporated herein by reference.

[0043] An issue with this JMPA approach is that the original user pool might be very large to start with. It may make the complexity of the JMPA process impractically high. Figure 6 illustrates a block diagram of a JMPA detector 602, channel estimator 604, with an active UE detector 606 to simplify the potentially high complexity of the JMPA process. A list of all potential UEs is fed into JMPA detector 602, channel estimator 604, and active UE detector 606. Active UE detector 606 uses the list of all potential UEs and received transmission data (e.g., all transmissions received by the BS from the CTU access regions) to generate a smaller list of potential active UEs. For example, as previously discussed multiple pilots may be correlated with each signature. Therefore, if active UE detector 606 determines a signature is not active, all corresponding pilots (i.e., CTU indexes/potential UEs) correlated with the inactive signature are also inactive. These pilots are removed from the list of potential UEs. If active UE detector 606 determines a pilot is inactive, it is taken off the list as well. In this manner, active UE detector 606 may decrease the list of potential active UEs for channel estimator 604 and JMPA detector 602, simplifying the decoding process. Furthermore, JMPA detector 602 may feed an updated list of potentially active UEs back to active UE detector 606. For example, JMPA detector 602 may determine that a second signature is inactive; this information is fed back to active UE detector 606 so that the corresponding pilots related to the second signature may be eliminated from the list of potential UEs.

[0044] Typically, uplink transmission performance depends on the number of the active signatures. A fewer number of overlaid signatures correlates to better expected performance from a MPA detector, such as the JMPA detector. This idea can be used to implicitly control the uplink quality. Based on long-term traffic statistics and the number of the potential active users,

the network can statistically control the average number of the users transmitting within the same CTU access region. For example, different numbers of UEs can be grouped together to access different CTU access regions. The network can also limit the number of pilots and/or signatures in a CTU access region. If the channel quality of the UEs is historically good, more interference within a CTU access region may be tolerated (i.e., more of these UEs can be configured to access a CTU access region allow for more pilots and/or signatures to be defined). This long-term link-adaptation mechanism is controlled by the network through the defining of CTU access regions and the mapping of UEs to access regions.

[0045] Figures 7A illustrates a flow diagram of network activity (e.g., through BS 102) according to various embodiments. In step 702, BS 102 defines CTU access regions. In step 704, BS 102 maps various CTU indexes to the CTU access region. Each CTU index corresponds to a CTU a UE (e.g., UE 104) may perform grant-free transmissions on. In step 706, BS 102 uses high-level signaling (e.g., through a broadcast channel) to send information enabling grant-free transmissions. This high-level signaling includes information on the defined CTU access regions, number of CTUs in the access regions and/or CTU index map. The high-level signaling may also include assigned DCS index information, and the like.

[0046] Steps 702-706 illustrate BS 102 defining and implementing a grant-free uplink transmission scheme. Alternatively, BS 102 may perform none or a subset of steps 702-706 because certain steps are pre-configured for BS 102 by a standard. For example, a standard may eliminate step 702 by pre-defining CTU access regions. BS 102 need only perform steps 704 and 706 (i.e., mapping CTU indexes to the CTU access regions and transmitting information). In another example, a standard defines the grant-free uplink transmission scheme and BS 102 need only implement the grant-free uplink transmission scheme.

[0047] In step 708, BS 102 receives an uplink transmission from UE 104. In step 710, the BS decodes the uplink transmission information blindly using, for example, a JMPA and active

UE detector method. In step 712, BS 102 determines whether the decoding was successful. If not, BS 102 assumes that collision has occurred, and waits to receive another uplink transmission. BS 102 also indicates to UE 104 whether the decoding was successful. BS 102 may do this by sending an ACK signal only if the transmission is successfully decoded. Alternatively, BS 102 may send a NACK signal if the transmission was not successfully decoded.

[0048] In an alternative embodiment illustrated in Figure 7B, if decoding was not successful in step 712, BS 102 determines if the number of failed decodings (i.e., collisions) is above a certain configurable threshold. If not, BS 102 waits for the next transmission. If the number of failures meets a certain threshold, BS 102 uses this information and overall conditions (e.g. distribution of active UEs in the CTUs) to make decision on remapping the UEs to other CTU indexes in the same or a different CTU access region in step 718. BS 102 then returns to step 706 to send the remapped CTU information via high-level signaling (e.g., broadcast, multicast, or unicast) to the UEs in its coverage area.

[0049] Figure 8A illustrates a flow diagram of UE activity in accordance with various embodiments. In step 802, UE (e.g., UE 104) enters a BS's coverage area. In step 804, UE 104 receives high-level signaling information from the BS. This high level signaling information includes CTU access region definitions, total number of CTUs, default mapping rules, and the like. Alternatively, UE 104 may be preconfigured with default mapping rules. In step 806, UE 104 determines an appropriate CTU to conduct uplink transmissions on (e.g., UE 104 may determine an appropriate CTU index using default mapping rules).

[0050] In Step 808, UE 104 transmits information on the appropriate CTU. In step 810, UE 104 determines whether collision has occurred based on an indication from the BS. For example, the UE may wait a predetermined amount of time for an ACK signal. If an ACK signal is received, then in step 812, the uplink procedure is concluded and UE 104 moves on to its next task. If no ACK signal is received, UE 104 determines that collision has occurred, and moves to

step 814. In step 814, UE 104 resolves the collision using an asynchronous HARQ method.

Alternatively, UE 104 assumes no collision has occurred unless it receives a NACK. If a NACK is received, the UE then continues with the collision resolution procedure.

[0051] In an alternative embodiment illustrated in Figure 8B, if UE 104 determines collision
5 has occurred, UE 104 then determines if the number of collisions exceed a certain threshold in
step 816. If not, then UE 104 returns to step 814 and resolves the collision using an
asynchronous HARQ method. If the threshold is met, then in step 818, UE 104 may request
remapping of CTUs by the BS. UE 104 then returns to step 804 and waits to receive the
remapping information from the BS and proceed with the uplink procedure. In another
10 embodiment, step 818 is optional and UEs do not send a request for remapping. The decision
whether to remap UEs is made by the BS based on aggregate information on the collisions of
UEs in the CTUs. UE 104 may continue to try to resolve the collision using an asynchronous
HARQ method.

[0052] Figure 9 is a block diagram of a processing system that may be used for
15 implementing the devices and methods disclosed herein. Specific devices may utilize all of the
components shown, or only a subset of the components and levels of integration may vary from
device to device. Furthermore, a device may contain multiple instances of a component, such as
multiple processing units, processors, memories, transmitters, receivers, etc. The processing
system may comprise a processing unit equipped with one or more input/output devices, such as
20 a speaker, microphone, mouse, touchscreen, keypad, keyboard, printer, display, and the like. The
processing unit may include a central processing unit (CPU), memory, a mass storage device, a
video adapter, and an I/O interface connected to a bus.

[0053] The bus may be one or more of any type of several bus architectures including a
memory bus or memory controller, a peripheral bus, video bus, or the like. The CPU may
25 comprise any type of electronic data processor. The memory may comprise any type of system
memory such as static random access memory (SRAM), dynamic random access memory

(DRAM), synchronous DRAM (SDRAM), read-only memory (ROM), a combination thereof, or the like. In an embodiment, the memory may include ROM for use at boot-up, and DRAM for program and data storage for use while executing programs.

[0054] The mass storage device may comprise any type of storage device configured to store data, programs, and other information and to make the data, programs, and other information accessible via the bus. The mass storage device may comprise, for example, one or more of a solid state drive, hard disk drive, a magnetic disk drive, an optical disk drive, or the like.

[0055] The video adapter and the I/O interface provide interfaces to couple external input and output devices to the processing unit. As illustrated, examples of input and output devices include the display coupled to the video adapter and the mouse/keyboard/printer coupled to the I/O interface. Other devices may be coupled to the processing unit, and additional or fewer interface cards may be utilized. For example, a serial interface card (not shown) may be used to provide a serial interface for a printer.

[0056] The processing unit also includes one or more network interfaces, which may comprise wired links, such as an Ethernet cable or the like, and/or wireless links to access nodes or different networks. The network interface allows the processing unit to communicate with remote units via the networks. For example, the network interface may provide wireless communication via one or more transmitters/transmit antennas and one or more receivers/receive antennas. In an embodiment, the processing unit is coupled to a local-area network or a wide-area network for data processing and communications with remote devices, such as other processing units, the Internet, remote storage facilities, or the like.

[0057] While this invention has been described with reference to illustrative embodiments, this description is not intended to be construed in a limiting sense. Various modifications and combinations of the illustrative embodiments, as well as other embodiments of the invention,

will be apparent to persons skilled in the art upon reference to the description. It is therefore intended that the appended claims encompass any such modifications or embodiments.

WHAT IS CLAIMED IS:

1. A method, comprising:

 sending, by a base station (BS), information indicating a first contention transmission unit (CTU) in a high-level signaling to a user equipment (UE);

 receiving, by the BS, a first uplink data transmission from the UE without allocating resources to the UE according to a request/grant mechanism, wherein the first uplink data transmission is transmitted using the first CTU of a plurality of CTUs in a first time frequency region, and the first CTU being a combination of time, frequency and pilot; and

 decoding, by the BS, the first uplink data transmission.
2. The method of claim 1, wherein the first CTU has a pre-defined mapping relationship with the UE.
3. The method of claim 1, before receiving the first uplink transmission, further comprising: sending, by the BS, message indicating to enable and configure grant-free transmissions in a high level signaling.
4. The method of claim 1, wherein the first time frequency region being used for contention transmissions by a plurality of UEs.
5. The method of claim 1, before receiving the first uplink transmission, further comprising: sending, by the BS, a first CTU index to the UE, wherein the first CTU index uniquely identifies the first CTU in the plurality of CTUs.
6. The method of claim 1, wherein each of the plurality of CTUs is assigned a unique and identifying CTU index.

7. The method of claim 1, further comprising:

sending, by the BS, an uplink grant indicating an unused second CTU in the plurality of CTUs to a second UE for grant scheme transmissions of the second UE when receiving a scheduling request from the second UE.

8. The method of claim 1, wherein the plurality of CTUs are categorized according to types of services to be provided by the BS.

9. The method of claim 1, wherein a size of a time-frequency region occupied by the plurality of CTUs is determined according to a number of UEs to be served by the BS.

10. The method of claim 1, wherein each of the plurality of CTUs is a combination of time, frequency, pilot and signature.

11. A base station, BS, comprising:

a processor; and

a computer readable storage medium storing programming for execution by the processor, the programming including instruction to:

send information indicating a first contention transmission unit (CTU) in a high-level signaling to a user equipment (UE);

receive a first uplink data transmission from the UE without allocating resources to the UE according to a request/grant mechanism, wherein the first uplink data transmission is transmitted using the first CTU of a plurality of CTUs in a first time frequency region, the first CTU being a combination of time, frequency and pilot; and

decode the first uplink data transmission.

12. The BS of claim 11, wherein the first CTU has a pre-defined mapping relationship with the UE.

13. The BS of claim 11, the BS further comprising instruction to: send message indicating to enable and configure grant-free transmissions in a high level signaling the UE.

14. The BS of claim 11, wherein the first time frequency region being used for contention transmissions by a plurality of UEs.

15. The BS of claim 11, the BS further comprising instruction to: send a first CTU index to the UE, wherein the first CTU index uniquely identifies the first CTU in the plurality of CTUs.

16. The BS of claim 11, wherein each of the plurality of CTUs is assigned a unique and identifying CTU index.

17. The BS of claim 11, the BS further comprising instruction to: send an uplink grant indicating an unused second CTU in the plurality of CTUs to a second UE for grant scheme transmissions of the second UE when receiving a scheduling request from the second UE.

18. The BS of claim 11, wherein the plurality of CTUs are categorized according to types of services to be provided by the BS.

19. The BS of claim 11, wherein a size of a time-frequency region occupied by the plurality of CTUs is determined according to a number of UEs to be served by the BS.

20. The BS of claim 11, wherein each of the plurality of CTUs is a combination of time, frequency, pilot and signature.

21. A method, comprising:

receiving, by an user equipment (UE), information indicating a first contention transmission unit (CTU) in a high-level signaling;

sending, by the UE, a first uplink data transmission to a base station (BS), without receiving resources from the BS according to a request/grant mechanism, wherein the first uplink data transmission is transmitted using the first CTU of a plurality of CTUs in a first time frequency region, and the first CTU being a combination of time, frequency and pilot.

22. The method of claim 21, wherein the first CTU has a pre-defined mapping relationship with the UE.

23. The method of claim 21, before sending the first uplink transmission, further comprising:

receiving, by the UE, message indicating to enable and configure grant-free transmissions in a high level signaling.

24. The method of claim 21, wherein the first time frequency region being used for contention transmissions by a plurality of UEs.

25. The method of claim 21, further comprising: receiving, by the UE, a first CTU index from the BS, wherein the first CTU index uniquely identifies the first CTU in the plurality of CTUs.

26. The method of claim 21, wherein each of the plurality of CTUs is assigned a unique and identifying CTU index.

27. The method of claim 21, wherein the plurality of CTUs are categorized according to types of services to be provided by the BS.

28. The method of claim 21, wherein a size of a time-frequency region occupied by the plurality of CTUs is determined according to a number of UEs to be served by the BS.

29. The method of claim 21, wherein each of the plurality of CTUs is a combination of time, frequency, pilot and signature.

30. A user equipment (UE), comprising:

a processor and

a computer readable storage medium storing programming for execution by the processor, the programming including instruction to:

receive information indicating a first contention transmission unit (CTU) in a high-level signaling; and

send a first uplink data transmission to a base station (BS), without receiving resources from the BS according to a request/grant mechanism, wherein the first uplink data transmission is transmitted using the first CTU of a plurality of CTUs in a first time frequency region, and the first CTU being a combination of time, frequency and pilot.

31. The UE of claim 30, wherein the first CTU has a pre-defined mapping relationship with the UE.

32. The UE of claim 30, the UE further comprising instruction to: receive message indicating to enable and configure grant-free transmissions in a high level signaling.

33. The UE of claim 30, wherein the first time frequency region being used for contention transmissions by a plurality of UEs.

34. The UE of claim 30, the UE further comprising instruction to: receive a first CTU index from the BS, wherein the first CTU index uniquely identifies the first CTU in the plurality of CTUs.

35. The UE of claim 30, wherein each of the plurality of CTUs is assigned a unique and identifying CTU index.

36. The UE of claim 30, wherein the plurality of CTUs are categorized according to types of services to be provided by the BS.

37. The UE of claim 30, wherein a size of a time-frequency region occupied by the plurality of CTUs is determined according to a number of UEs to be served by the BS.

38. The UE of claim 30, wherein each of the plurality of CTUs is a combination of time, frequency, pilot and signature.