

## Device for magnetic field therapy

### Specification

5

### Field of the invention

10 The invention relates to a device for magnetic field therapy.

### Background of the invention

15 Methods for magnetic field therapy and associated devices for performing same are known.

A method for magnetic field therapy in which the therapeutic effect relies on the effect of nuclear magnetic resonance is described in European patent document  
20 EP 1 089 792 B1 (patent holder Axel Muntermann).

This method uses a device in which a substantially static magnetic field is superimposed by an alternating magnetic field perpendicular thereto.  
25

A requirement for achieving nuclear magnetic resonance is that at least the static magnetic field in the treatment zone has a field strength as homogenous as possible, since  
30 otherwise nuclear magnetic resonance only occurs in a part of the treatment zone.

In practice, for generating alternating magnetic fields a Helmholtz coil is used, for example, i.e. an arrangement of two annular or cylindrical coils spaced from each other.

5 A disadvantage of such a coil arrangement or an annular coil in general is that the patient has to lie down in the coil during treatment. This is not comfortable, in particular for older or adipose persons. Moreover, the annular arrangement extending around the patient may cause  
10 claustrophobia.

When treating animals the handling of an annular coil is also impractical, since the animal has to be driven in, e.g. on a carriage, and so would have to be fixed in many  
15 cases, or since the air coil required for treatment has to be slid onto the joint to be treated or the area to be treated.

20 Object of the invention

An object of the invention, therefore, is to at least mitigate the shortcomings of the prior art mentioned above.

25 In particular, an object of the invention is to provide a device for magnetic field therapy with improved handling properties. In the same time, it is desired to maintain a treatment volume as large as possible.

30 Another object of the invention is to provide a device for magnetic field therapy which is easily manufactured and which is suitable for use in therapy forms that are based

on the effect of nuclear magnetic resonance due to a good homogeneity of the field.

Moreover, it is an object of the invention to ameliorate  
5 the accessibility of the treatment zone for the patients.

Yet another object of the invention is to maintain the treatment zone of a device for magnetic field therapy, with the exception of a couch surface, as open as possible, and  
10 accessible from all sides.

#### Summary of the invention

15 This object of the invention is already achieved by a device for magnetic field therapy according to the independent claim.

Preferred embodiments and modifications of the invention  
20 are set forth in the respective dependent claims.

The invention relates to a device for magnetic field therapy, in particular the invention relates to a device which is adapted to achieve nuclear magnetic resonances in  
25 the tissue to be treated.

The device comprises a base which is preferably arranged horizontally and is particularly formed as a couch surface for a patient or a body part of a patient.  
30

Furthermore, the device comprises two angled and/or curved side parts which are disposed at the sides of the base and

preferably extend in vertical direction from the sides of the base.

Each of the side parts includes a coil having a central  
5 axis that extends transversely, preferably substantially perpendicular to the respective side part.

The arrangement of the coils in the side parts allows a construction of the device such that the device opens  
10 upwardly.

Moreover, by integrating a pair of coils in the side parts, a magnetic field with fairly good homogeneity can be generated. Since the magnetic field extends substantially  
15 linearly from one of the side parts to the other one, quite a large treatment volume may be provided in which nuclear magnetic resonances are achieved. So, the coils are provided as some kind of Helmholtz coil pair.

20 Preferably, the entire device is approximately U-shaped.

In contrast to known devices for magnetic field therapy that use annular or cylindrical coils, the invention provides accessibility of the treatment zone from above. So  
25 the patient do not has to be driven into the coil arrangement but can lie back by his own and can enter the treatment zone in this manner with at least one body part.

When treating animals, the simplified accessibility also  
30 provides for a significantly easier treatment. So, e.g., a dog or a small animal can be introduced into the treatment zone from above and can additionally be supervised during

treatment and does not have to be strapped down or otherwise fixed on a couch.

5 Further, the device comprises a first means for generating a magnetic field, wherein the magnetic field generated by this first means is transverse, preferably substantially perpendicular to the field generated by the coils.

10 By combining a substantially static field with a superimposed alternating field nuclear magnetic resonances can be produced in the tissue to be treated.

15 In a preferred embodiment of the invention the first means for generating a magnetic field comprises at least one coil which has a substantially flat cross-section and is disposed in or below the base.

20 In this embodiment, the magnetic field generated by the first magnetic field generating means is not generated by a permanent magnet but also by means of a coil.

Preferably, a flat cylindrical or annular coil laid flat in the base is used.

25 It will be understood, however, that parts of a coil system even may protrude up and into the side parts.

30 In one embodiment of the invention, the substantially static magnetic field is generated by the flat lying coil, while the alternating magnetic field substantially perpendicular thereto is generated by the coils integrated in the side parts. In an alternative embodiment in which the alternating field is generated by the first magnetic

field generating means, an advantage of the device is the good homogeneity of the field between the side parts.

5 A combination of permanent magnets and coils for generating the substantially static magnetic field is also contemplated within the scope of the invention.

10 Preferably, the device for magnetic field therapy opens opposite to the base, i.e. in particular upwards, to provide for easier access. The coil systems described can be mounted in a closed casing with or without openings.

15 In another preferred embodiment the side parts each have a recess, wherein the respective coil extends around the recess.

This embodiment allows a construction in which the side parts substantially only form a frame to receive the coil.

20 One purpose of the recess is that the treatment zone is not perceived as a narrow tunnel by the patient, as is the case with known annular designs.

25 On the other hand, light may enter through the recesses so that there will be light also in the treatment zone.

In a modification of the invention a lighting device is provided which is used to marked the treatment zone by a light field.

30

In a preferred embodiment of the invention, light sources can be switched on as a positioning aid to properly position a patient, preferably by a switch/button

arrangement mounted outside. Moreover, it is envisaged to provide for a therapy accompanying light that can be switched on in the treatment zone. Another light means which is for example coupled to at least one other separate coil which is inductively powered through the fields of the means for generating a magnetic field, can be used to indicate the operability of the device for magnetic field therapy.

10 In a preferred embodiment, the recesses are substantially rectangular. The side parts also have a substantially rectangular shape, as seen in a side view. Such a construction allows to provide a substantially rectangular treatment zone with a good use of space.

15 In a preferred embodiment of the invention, the recesses occupy more than 50%, preferably more than 60% of the area of the side parts.

20 In a modification of the invention, the side parts are curved within the plane of the coil.

Thus, the coil which is formed as a cylindrical or annular coil and extends within the frame of the side parts is curved along with the side part so providing for a better use of space.

In particular, an approximately circular shape of the side parts is contemplated, as seen in a front view.

30 The coils preferably used for the various treatment tasks have a diameter from 10 cm to 1 m, more preferably from 50 cm to 90 cm, wherein the base of the device for magnetic

field therapy has a length from 20 to 120 cm, preferably from 40 to 80 cm.

5 The coils in the side parts can be used both for generating a substantially static field and for generating an alternating magnetic field.

10 In case of use for a static field, the good homogeneity of the field is of particular advantage, since the frequency of the alternating field required to achieve nuclear magnetic resonance depends on the strength of the static field.

15 But even with a coil laid flat in the base a field of sufficient homogeneity can be produced. In particular, the static field can be swept, which is to generate a field with a sufficient minimum field strength which is varied such that by altering the static field it is ensured that during sweeping the resonance condition is produced in  
20 every portion of the treatment zone, at least for a short time.

A similar result may be obtained by sweeping the frequency of the alternating magnetic field.

25

The base and side parts with the respective coils are preferably formed as a unitary module, particularly formed from a plastic material. For example, in a particularly simple way the coils can be integrated in an injection  
30 molded casing, and especially can be coated with a plastic material, plastic foam or another dielectric material in an injection mold.

In a modification of the invention, the device for magnetic field therapy additionally comprises a carriage which is disposed on the base and includes a couch surface, and which can be displaced relative to the base. Thus, by  
5 translating the carriage it is possible to move the treatment zone relative to the patient and to treat several portions of the body.

In an alternative embodiment of the invention, a module  
10 formed by the base and the side parts is constructed to be movable relative to the level of a seat. In this embodiment of the invention, the base is arranged substantially vertically and can be moved upwards and downwards along the body of the patient who sits on the seat. This embodiment  
15 of the invention is especially suitable for a treatment in the head or upper body zone. It is particularly useful for skin treatment in the facial area.

In a modification of the invention, the module is adapted  
20 to be pivotable and so can be tilted from an exactly vertical position to be optimally adjustable in function of the seating position and the zone of the body to be treated.

25

#### Brief description of the drawings

The invention will now be described in detail with reference to exemplary embodiments schematically  
30 illustrated in the drawings of Figs. 1 to 5.

Fig. 1 schematically shows a perspective view of an exemplary embodiment of the invention;

- Fig. 2 shows the exemplary embodiment illustrated in Fig. 1, the arrangement of coils being schematically illustrated;
- Fig. 3 schematically shows the arrangement of coils;
- 5 Fig. 4 shows another exemplary embodiment of a device for magnetic field therapy that includes an adjustable couch;
- Fig. 5 shows another exemplary embodiment of the invention; and
- 10 Fig. 6 shows another exemplary embodiment of the invention in which a seat is provided.

#### Detailed description of the drawings

15

Fig. 1 schematically illustrates a device 1 for magnetic field therapy.

Device 1 for magnetic field therapy comprises a base 2, which for example serves as a rest for a body part to be treated.

Two side parts 3 and 4 extend from base 2.

25 Side parts 3 and 4 have a curved shape, as seen in a front view, and have an approximately circular segment shaped or U-shaped cross-section.

Furthermore, the two side parts 3 and 4 form a frame and so each have a recess 6, 7.

30

Device 1 for magnetic field therapy is open opposite base 2 thereby providing for significantly better accessibility

of the treatment zone 5 provided between side parts 3, 4 and base 2, as compared to known devices for magnetic field therapy.

- 5 A first means for generating an magnetic field (not shown) is provided in base 2.

Fig. 2 shows the embodiment of a device 1 for magnetic field therapy according to Fig. 1, this view schematically  
10 showing a coil 12 integrated in base 2 which provides a first means for generating a magnetic field.

Another coil 11 is provided in the right-hand side part 4 which can also be used to produce a magnetic field.

15

The coil in side part 3 is not shown, but it can be seen that a magnetic field can be generated by means of the coils in side part 3 and side part 4 which is substantially perpendicular to the magnetic field generated by coil 12.

20

Coils 11, 12 can be powered via a control device that is independent from a power supply system, in particular a device that includes an accumulator (not shown).

- 25 In this manner, nuclear magnetic resonances can be generated in the skin area to be treated (not shown) within the treatment zone 5.

Through recesses 6 and 7, the treatment zone 5 can be  
30 marked using a light (not shown).

Fig. 3 schematically illustrates the coil arrangement.

A first magnetic field is produced by coil 12 incorporated in the base, with field lines that substantially extend along the y-axis within the treatment zone.

- 5 Coils 10 and 11 are used to produce a field perpendicular thereto which has field lines that extend substantially along the x-axis. Thus, coils 10 and 11 form a second means for generating a magnetic field.
- 10 The field generated by coils 10 and 11 is very homogeneous, due to the arrangement being very similar to a Helmholtz coil. Thus, for producing nuclear magnetic resonances in the tissue to be treated it is advantageous to produce a substantially static magnetic field using coils 10 and 11,
- 15 and to produce an alternating field perpendicular thereto using coil 12 which results in the spins folding down.

- Fig. 4 schematically illustrates another embodiment of the invention. In this embodiment, the device 1 for magnetic field therapy illustrated in Fig. 1 and Fig. 2 is equipped
- 20 with a couch moveable along the base of the device. By moving couch 13 relative to the device 1 for magnetic field therapy, the treatment zone 5 may be slightly displaced, if a patient lies on the couch (not shown), and in this way
- 25 several zones of the body may be treated successively.

Referring to Fig. 5 another exemplary embodiment of the invention will be described in detail.

- 30 The figure likewise illustrates a device 1 for magnetic field therapy, wherein in this exemplary embodiment side parts 3, 4 do not have any recesses, rather they are closed. Otherwise, the basic form of the device 1 for

magnetic field therapy corresponds to that of the device illustrated in Fig. 1.

5 Additionally, an arrangement of switches 14 is illustrated in the drawing which can be used for example to operate the device or to switch on and off lights 15. Lights 15 are preferably provided as LED lights. In this exemplary embodiment three lights are provided on each side to mark the treatment zone 5.

10

Furthermore, the device 1 for magnetic field therapy comprises operation indicators 16 from which it can be seen if the device works. Operation indicators 16 may e.g. comprise an LED which is connected to another coil (not shown), wherein in case of correct operation the LED is inductively powered through the coil.

15

Fig. 6 shows an alternative embodiment of the invention in which the device 1 for magnetic field therapy comprises a seat 17 on which the patient may sit down. For enhancing comfort, the device additionally comprises a backrest 18, an armrest 20, and a neck cushion 19.

20

A module 21, which comprises a base and side parts 3, 4 is disposed substantially vertically.

25

Module 21 is preferably adjustable, at least in height, so that the device 1 for magnetic field therapy can be adjusted to different sizes of patients or to treat different skin portions.

30

It will be understood that the invention is not limited to a combination of features described above, rather a person

skilled in the art will combine any features as far as appropriate.

List of reference numerals

|    |    |                                   |
|----|----|-----------------------------------|
|    | 1  | device for magnetic field therapy |
| 5  | 2  | base                              |
|    | 3  | side part                         |
|    | 4  | side part                         |
|    | 5  | treatment zone                    |
|    | 6  | recess                            |
| 10 | 7  | recess                            |
|    | 10 | coil                              |
|    | 11 | coil                              |
|    | 12 | coil                              |
|    | 13 | couch                             |
| 15 | 14 | switch                            |
|    | 15 | light                             |
|    | 16 | operation indicator               |
|    | 17 | seat                              |
|    | 18 | backrest                          |
| 20 | 19 | cushion                           |
|    | 20 | armrest                           |
|    | 21 | module                            |

Claims:

1. A device for magnetic field therapy, comprising:  
5 a base with a first means for generating a magnetic field;  
and two angled side parts extending vertically from the sides of the base;  
wherein each of the side parts includes a coil with a  
10 central axis that extends perpendicular to the respective side part; and  
wherein a magnetic field produced by said coils is perpendicular to a magnetic field produced by said first means for generating a magnetic field, at least  
15 in portions thereof.
2. The device for magnetic field therapy according to the preceding claim, characterized in that the magnetic field produced by the coils extends substantially  
20 linearly from one of the side parts to the other side part, at least in portions thereof.
3. The device for magnetic field therapy according to any of the preceding claims, characterized in that the  
25 angled side parts extend vertically from the sides of the base.
4. The device for magnetic field therapy according to any of the preceding claims, characterized in that the  
30 central axis of the coils extends perpendicular to the respective side part.

5. The device for magnetic field therapy according to any of the preceding claims, characterized in that the first means for generating a magnetic field comprises at least one coil arranged in or below the base and having a substantially flat cross-section.  
5
6. The device for magnetic field therapy according to any of the preceding claims, characterized in that the first means for generating a magnetic field comprises another coil with a central axis that extends substantially perpendicular to the base.  
10
7. The device for magnetic field therapy according to any of the preceding claims, characterized in that the device for magnetic field therapy opens opposite the base.  
15
8. The device for magnetic field therapy according to any of the preceding claims, characterized in that the side parts each have a recess.  
20
9. The device for magnetic field therapy according to the preceding claim, characterized in that the recesses are of rectangular shape.  
25
10. The device for magnetic field therapy according to any of the two preceding claims, characterized in that the recesses occupy 50 %, preferably more than 60 % of the area of the side parts.  
30
11. The device for magnetic field therapy according to any of the preceding claims, characterized in that the side

parts are curved.

12. The device for magnetic field therapy according to any  
of the preceding claims, characterized in that the side  
5 parts are of a frame-type construction.
13. The device for magnetic field therapy according to any  
of the preceding claims, characterized in that the  
coils have a diameter from 10 cm to 1 m, preferably  
10 from 50 cm to 90 cm.
14. The device for magnetic field therapy according to any  
of the preceding claims, characterized in that the base  
has a length from 20 to 120 cm, preferably from 40 to  
15 80 cm.
15. The device for magnetic field therapy according to any  
of the preceding claims, characterized in that the  
coils or the first means for generating a magnetic  
20 field are adapted to generate an alternating magnetic  
field.
16. The device for magnetic field therapy according to any  
of the preceding claims, characterized in that the  
25 first means for generating a magnetic field or the  
coils are adapted to generate a substantially static  
field.
17. The device for magnetic field therapy according to any  
30 of the preceding claims, characterized in that the base  
with the first means for generating a magnetic field  
and the side parts with the coils are formed as a

unitary module.

18. The device for magnetic field therapy according to any  
of the preceding claims, characterized in that the base  
5 and the side parts are made from a dielectric material,  
in particular a plastic material, and preferably are  
formed as a plastic injection-molded part.
19. The device for magnetic field therapy according to any  
10 of the preceding claims, characterized in that the  
device is adapted to produce nuclear magnetic  
resonances in the tissue to be treated.
20. The device for magnetic field therapy according to any  
15 of the preceding claims, further comprising a carriage  
arranged on the base and having a couch surface,  
wherein said carriage is adapted to be moveable  
relative to the base.
- 20 21. The device for magnetic field therapy according to any  
of the preceding claims, characterized in that the base  
is arranged horizontally.
22. The device for magnetic field therapy according to any  
25 of claims 1 to 19, further comprising a module formed  
by said base and said side parts which is displaceable  
relative to the level of a seat.
23. The device for magnetic field therapy according to the  
30 preceding claim, characterized in that the module is  
adapted to be pivotable.