

CORRECTED VERSION

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
11 January 2007 (11.01.2007)

PCT

(10) International Publication Number
WO 2007/005981 A1

(51) International Patent Classification:
H01R 13/20 (2006.01)

(21) International Application Number:

PCT/US2006/026235

(22) International Filing Date: 5 July 2006 (05.07.2006)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/696,684 5 July 2005 (05.07.2005) US

(71) Applicant (for all designated States except US): **EMERSON ELECTRIC CO.** [US/US]; 8000 West Florissant Avenue, St. Louis, Missouri 63136 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **PATEREK, Franz Dieter** [DE/NL]; 2e Blockweg 3, NL-7681 GH Vroomshoop (NL). **KOLKMAN, Albertus Jan Hendrik** [NL/NL]; Verbindingsweg 7, NL-7751 BA Dalen (NL). **SCHUCKMANN, Scott** [US/US]; 5917 Hidden Oaks Ct., Maineville, Ohio 45039 (US).


(74) Agents: **UTYKANSKI, David P.** et al.; Harness, Dickey & Pierce, P.L.C., P.O. Box 828, Bloomfield Hills, MI 48303 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LV, LY, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: ELECTRIC POWER TERMINAL FEED-THROUGH



(57) Abstract: A power terminal feed-through incorporates a metallic body through which extend one or more current conducting pins that are hermetically sealed to the metallic body by a glass-to-metal seal. The metallic body includes an annular lip with a protrusion. During welding installation of the power terminal feed-through, the protrusion serves to assist in the welding process, better controlling the location and definition of the weld between the metallic body and a housing, and to focus the welding heat at the protrusion, thereby protecting the glass-to-metal seal. The glass-to-metal seal can be a single glass insert through which the current conducting pins extend, thereby reducing the pin circle diameter and the overall size of the power terminal feed-through.

WO 2007/005981 A1



Declaration under Rule 4.17:

— *of inventorship (Rule 4.17(iv))*

Published:

— *with international search report*

(48) Date of publication of this corrected version:

8 March 2007

(15) Information about Correction:

see PCT Gazette No. 10/2007 of 8 March 2007

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.