

METHODS AND DEVICES FOR VERIFYING VALIDITY OF TOKEN

RECORDED ON BLOCKCHAIN

TECHNICAL FIELD

[0001] The specification relates generally to computer technologies, and more particularly, to methods and devices for verifying validity of token recorded on blockchain.

BACKGROUND

[0002] Conventionally, a fungible asset is generally composed of units that can be interchanged, and a non-fungible asset may not be interchanged because it has unique properties. Both types of assets may exist in the digital world, and may be bought and sold like their physical counterparts.

[0003] A non-fungible token (NFT) may be a unit of data utilized to certify that an asset is unique and not interchangeable (i.e., the asset is non-fungible). NFTs may be utilized to certify items such as artworks, photos, videos, audio files, transactions, records, and other types of non-fungible assets. For example, while traditional works of art such as paintings and the like are one of a kind, digital artworks can be easily and repeatedly duplicated. Using NFTs, a digital artwork (or other types of assets) may be “tokenized” to create a digital certificate of ownership to certify that the digital artwork is unique and not interchangeable.

[0004] NFTs may be bought and sold, and may be stored on a digital ledger, which may be implemented using a blockchain system. Blockchain systems, also known as distributed ledger systems (DLSs) or consensus systems, may enable participating parties to store data securely and immutably. Blockchain systems may

include any DLSSs, without referencing any particular use case, and may be used for public, private, and consortium blockchain networks. A public blockchain network is open for all entities to use the system and participate in the consensus process. A private blockchain network is provided for a particular entity, which centrally controls read and write permissions. A consortium blockchain network is provided for a select group of entities, which control the consensus process, and includes an access control layer.

[0005] A blockchain system is implemented using a peer-to-peer (P2P) network, in which the nodes communicate directly with each other, e.g., without the need of a fixed, central server. Each node in the P2P network may initiate communication with another node in the P2P network. A blockchain system maintains one or more blockchains. A blockchain is a data structure for storing data, such as transactions, that may prevent tampering and manipulation of the data by malicious parties.

[0006] Users of a blockchain system may utilize the blockchain system to record various types of information, including, e.g., NFTs. Currently, many NFT applications have been made available on various blockchain platforms, including, e.g., Ethereum, Binance Smart Chain, and the like. Many types of NFTs have been minted and traded on these blockchain platforms, including, e.g., artworks, music, domain names, trading cards, collectibles, and the like. Other types of assets, including invoices and purchase orders, may also be represented using non-fungible tokens and traded on such blockchain platforms. However, little work has been done with respect to protecting the privacy of the NFTs recorded on blockchains.

SUMMARY

[0007] In one aspect, a computer-implemented method for generating a privacy-preserving token includes calculating a privacy-preserving representation of a set of attributes associated with the token, wherein calculating the privacy-preserving representation comprises calculating a Merkle tree root hash based on a value associated with each attribute of the set of attributes, wherein the value associated with each attribute of the set of attributes has a corresponding hash stored on a leaf node of the Merkle tree; and recording the privacy-preserving representation of the set of attributes on a blockchain system as metadata of the token.

[0008] In another aspect, a computer-implemented method for verifying validity of a privacy-preserving token, wherein a privacy-preserving representation of a set of attributes is calculated by calculating a Merkle tree root hash based on a value associated with each attribute of the set of attributes and is recorded on a blockchain system as metadata of the token, and the value associated with each attribute of the set of attributes has a corresponding hash stored on a leaf node of the Merkle tree is disclosed. The method includes: identifying hashes stored on a plurality of nodes of the Merkle tree that can be utilized to calculate the Merkle tree root hash; and providing the identified hashes stored on the plurality of nodes of the Merkle tree to a verifier, to facilitate a verification of the validity of the token without revealing the value associated with each attribute of the set of attributes.

[0009] In still another aspect, a computer-implemented method for verifying validity of a privacy-preserving token, wherein a privacy-preserving representation of a set of attributes is calculated by calculating a Merkle tree root hash based on a value associated with each attribute of the set of attributes and is recorded on a blockchain system as metadata of the token, and the value associated with each attribute of the

set of attributes has a corresponding hash stored on a leaf node of the Merkle tree is disclosed. The method includes: receiving hashes stored on a plurality of nodes of the Merkle tree that can be utilized to calculate the Merkle tree root hash; calculating a root hash based on the hashes received; obtaining the token recorded on the blockchain system; and verifying the validity of the token based on the calculated root hash without knowing the value associated with each attribute of the set of attributes.

BRIEF DESCRIPTION OF THE DRAWINGS

[0010] The accompanying drawings, which are incorporated in and constitute a part of this specification, illustrate embodiments. In the following description, which refers to the drawings, the same numbers in different drawings represent the same or similar elements unless otherwise represented.

[0011] FIG. 1 is a schematic diagram of a blockchain system, according to an embodiment.

[0012] FIG. 2 is a schematic diagram of a computing device for implementing a node in a blockchain system, according to an embodiment.

[0013] FIG. 3 is a schematic diagram depicting an implementation of a Merkle tree, according to an embodiment.

[0014] FIG. 4 is a schematic diagram depicting a Merkle tree with hash values stored therein, according to an embodiment.

[0015] FIG. 5 is a schematic diagram depicting a Merkle tree with hash values stored therein, according to an embodiment.

[0016] FIG. 6 is a schematic diagram depicting a Merkle tree with hash values stored therein, according to an embodiment.

[0017] FIG. 7 is a flow chart of a method for verifying validity of a token, according to an embodiment.

[0018] FIG. 8 is a flow chart of a method for verifying validity of a token, according to an embodiment.

[0019] FIG. 9 is a block diagram of an apparatus for verifying validity of a token, according to an embodiment.

DETAILED DESCRIPTION

[0020] Embodiments of the specification provide methods and devices for verifying validity of tokens. The methods and devices may calculate a privacy-preserving representation by calculating a Merkle tree root hash based on values associated with a set of attributes, where the value associated with each attribute of the set of attributes may have a corresponding hash stored on a leaf node of the Merkle tree. The methods and devices may record the privacy-preserving representation on a blockchain as metadata of a token. The methods and devices may also provide the hashes stored on the Merkle tree that correspond to the values associated with the set of attributes to a verifier to facilitate a verification of the validity of the token without revealing any values associated with the set of attributes.

[0021] Embodiments disclosed in the specification have one or more technical effects. In some embodiments, the methods and devices may calculate the privacy-preserving representation by calculating a Merkle tree root hash based on values associated with a set of attributes, where the value associated with each attribute of the set of attributes may have a corresponding hash stored on a leaf node of the Merkle tree. This allows the methods and devices to account for each attribute of the set of attributes when calculating the privacy-preserving representation. In some

embodiments, the methods and devices may record the privacy-preserving representation on a blockchain as metadata of a token. This allows the methods and devices to record the metadata of the token securely and immutably without exposing any private information about the token on the blockchain. In some embodiments, the methods and devices may provide the hashes stored on the Merkle tree that correspond to the values associated with the set of attributes to a verifier to facilitate a verification of the validity of the token without revealing any values associated with the set of attributes. This allows the methods and devices to provide a mechanism that not only protects the privacy of the token, but also safeguards correctness of the token recorded on the blockchain.

[0022] A blockchain is a data structure that stores data, e.g., transactions, in a way that may prevent tampering and manipulation of the data by malicious parties. The transactions stored in this manner may be immutable and subsequently verified. A blockchain includes one or more blocks. Each block is linked to a previous block immediately before it in the blockchain by including a cryptographic hash of the previous block. Each block also may include a timestamp, its own cryptographic hash, and one or more transactions. The transactions, which generally have already been verified by the nodes of the blockchain system, may be hashed and encoded into a data structure, such as a Merkle tree. In a Merkle tree, data at leaf nodes of the tree is hashed, and all hashes in each branch of the tree may be concatenated at a root of the branch. This process continues up the tree to the root of the entire tree, which stores a hash that is representative of all data in the tree. A hash purporting to be of a transaction stored in the tree can be quickly verified by determining whether it is consistent with the structure of the tree.

[0023] A blockchain system includes a network of computing nodes that

manage, update, and maintain one or more blockchains. The network may be a public blockchain network, a private blockchain network, or a consortium blockchain network. For example, numerous entities, such as hundreds, thousands, or even millions of entities, can operate in a public blockchain network, and each of the entities operates at least one node in the public blockchain network. Accordingly, the public blockchain network can be considered a public network with respect to the participating entities. Sometimes, a majority of entities (nodes) must sign every block for the block to be valid and added to the blockchain of the blockchain network. Examples of public blockchain networks include particular peer-to-peer payment networks that leverage a distributed ledger, referred to as blockchain.

[0024] In general, a public blockchain network may support public transactions. A public transaction is shared with all of the nodes in the public blockchain network, and is stored in a global blockchain. A global blockchain is a blockchain replicated across all nodes, and all nodes are in perfect state consensus with respect to the global blockchain. To achieve consensus (e.g., agreement to the addition of a block to a blockchain), a consensus protocol is implemented in the public blockchain network. Examples of consensus protocols include proof-of-work (POW) (e.g., implemented in the some crypto-currency networks), proof-of-stake (POS), and proof-of-authority (POA).

[0025] In general, a private blockchain network may be provided for a particular entity, which centrally controls read and write permissions. The entity controls which nodes are able to participate in the blockchain network. Consequently, private blockchain networks are generally referred to as permissioned networks that place restrictions on who is allowed to participate in the network, and on their level of participation (e.g., only in certain transactions). Various types of access control

mechanisms can be used (e.g., existing participants vote on adding new entities, a regulatory authority can control admission).

[0026] In general, a consortium blockchain network may be private among the participating entities. In a consortium blockchain network, the consensus process is controlled by an authorized set of nodes, one or more nodes being operated by a respective entity (e.g., a financial institution, insurance company). For example, a consortium of ten (10) entities (e.g., financial institutions, insurance companies) can operate a consortium blockchain network, each of which operates at least one node in the consortium blockchain network. Accordingly, the consortium blockchain network can be considered a private network with respect to the participating entities. In some examples, each entity (node) must sign every block in order for the block to be valid, and added to the blockchain. In some examples, at least a sub-set of entities (nodes) (e.g., at least 7 entities) must sign every block in order for the block to be valid, and added to the blockchain.

[0027] FIG. 1 illustrates a schematic diagram of a blockchain system 100, according to an embodiment. Referring to FIG. 1, the blockchain system 100 may include a plurality of nodes, e.g., nodes 102-110, configured to operate on a blockchain 120. The nodes 102-110 may form a network 112, such as a peer-to-peer (P2P) network. Each of the nodes 102-110 may be a computing device, such as a computer or a computer system, configured to store a copy of the blockchain 120, or may be software running on the computing device, such as a process or an application. Each of the nodes 102-110 may have a unique identifier.

[0028] The blockchain 120 may include a growing list of records in the form of data blocks, such as blocks B1-B5 in FIG. 1. Each of the blocks B1-B5 may include a timestamp, a cryptographic hash of a previous block, and data of the present block,

which may be transactions such as monetary transactions. For example, as illustrated in FIG. 1, block B5 may include a timestamp, a cryptographic hash of block B4, and transaction data of block B5. Also, for example, a hashing operation may be performed on the previous block to generate the cryptographic hash of the previous block. The hashing operation may convert inputs of various lengths into cryptographic outputs of a fixed length through a hash algorithm, such as SHA-256.

[0029] The nodes 102-110 may be configured to perform an operation on the blockchain 120. For example, when a node, e.g., the node 102, wants to store new data onto the blockchain 120, that node may generate a new block to be added to the blockchain 120 and broadcast the new block to other nodes, e.g., the nodes 104-110, in the network 112. Based on legitimacy of the new block, e.g., validity of its signature and transactions, the other nodes may determine to accept the new block, such that the node 102 and the other nodes may add the new block to their respective copies of the blockchain 120. As this process repeats, more and more blocks of data may be added to the blockchain 120.

[0030] FIG. 2 illustrates a schematic diagram of a computing device 200 for implementing a node, e.g., the node 102 (FIG. 1), in a blockchain system, according to an embodiment. Referring to FIG. 2, the computing device 200 may include a communication interface 202, a processor 204, and a memory 206.

[0031] The communication interface 202 may facilitate communications between the computing device 200 and devices implementing other nodes, e.g., nodes 104-110 (FIG. 1), in the network. In some embodiments, the communication interface 202 is configured to support one or more communication standards, such as an Internet standard or protocol, an Integrated Services Digital Network (ISDN) standard, etc. In some embodiments, the communication interface 202 may include one or more

of a Local Area Network (LAN) card, a cable modem, a satellite modem, a data bus, a cable, a wireless communication channel, a radio-based communication channel, a cellular communication channel, an Internet Protocol (IP) based communication device, or other communication devices for wired and/or wireless communications. In some embodiments, the communication interface 202 may be based on public cloud infrastructure, private cloud infrastructure, hybrid public/private cloud infrastructure.

[0032] The processor 204 may include one or more dedicated processing units, application-specific integrated circuits (ASICs), field-programmable gate arrays (FPGAs), or various other types of processors or processing units. The processor 204 is coupled with the memory 206 and is configured to execute instructions stored in the memory 206.

[0033] The memory 206 may store processor-executable instructions and data, such as a copy of the blockchain 120 (FIG. 1). The memory 206 may include any type of volatile or non-volatile memory devices, or a combination thereof, such as a static random-access memory (SRAM), an electrically erasable programmable read-only memory (EEPROM), an erasable programmable read-only memory (EPROM), a programmable read-only memory (PROM), a read-only memory (ROM), a magnetic memory, a flash memory, or a magnetic or optical disk. When the instructions in the memory 206 are executed by the processor 204, the computing device 200 may perform an operation on the blockchain 120.

[0034] Users of a blockchain system, e.g., the blockchain system 100, may utilize the blockchain system 100 to record various types of information. For example, in some embodiments, users may utilize the blockchain system 100 to record information regarding assets owned, managed, or traded by them. The assets may include, e.g., artworks, music, domain names, trading cards, collectibles, invoices,

purchase orders, monetary assets, personal properties, real properties, intellectual properties, contracts, and the like.

[0035] In some embodiments, information regarding an asset may be represented by an identifier and a metadata field recorded on the blockchain system 100. The identifier and the metadata field may form a unit of data represented as, e.g., $\{ID:Metadata\}$, referred to as a token. In some embodiments, the *Metadata* may include a set of attributes and their corresponding values. For example, if the asset represented is an artwork, the attributes may include, e.g., the name of the artist who created the artwork, the date of creation, a thumbprint of the artwork, an InterPlanetary File System (IPFS) link of the artwork, and the like. In another example, if the asset represented is an invoice or a purchase order, the attributes may include, e.g., the identity of the buyer, the identity of the seller, an amount of the invoice or the purchase, the goods or services purchased, and the like. In some embodiments, the asset represented may be unique and not interchangeable (i.e., a non-fungible asset). In such embodiments, the token representing the asset may be referred to as a non-fungible token (NFT).

[0036] There may be instances where a user, e.g., the owner of an NFT, may want to protect the plaintext values of the attributes or otherwise keep the plaintext values of the attributes hidden from other users of the blockchain system 100. In some embodiments, to protect the plaintext values of the attributes, the owner may encrypt the plaintext values of the attributes (e.g., using the owner's public key) so that only encrypted attribute values are recorded in the *Metadata* field of the NFT. However, if the owner later sells the NFT to a buyer, the buyer may not be able to decrypt the encrypted attribute values without obtaining the secret key from the owner. Also, for security reasons, the owner may not be willing to share its secret key with the buyer.

Furthermore, as the NFT continues to be bought and sold to subsequent buyers, it may become difficult to keep track of the keys required to decrypt the encrypted attribute values.

[0037] In some embodiments, instead of encrypting the attribute values, the owner may calculate a privacy-preserving representation of the attribute values and record the privacy-preserving representation of the attribute values as the *Metadata* of the NFT. For example, if the privacy-preserving representation of the attribute values is denoted as *PPR*, the owner may record the NFT as $\{ID: PPR\}$.

[0038] In some embodiments, the owner may calculate the privacy-preserving representation of the attribute values by calculating a Merkle tree root hash according to a function. In some embodiments, the function may include a Merkle tree root hash function defined based on the attribute values. A Merkle tree refers to a tree where every leaf node is labelled with a cryptographic hash of a data block, and every non-leaf node is labelled with a cryptographic hash of the labels of its child nodes. For illustrative purposes, a Merkle tree is depicted in FIG. 3, where leaf nodes 302-308 are labelled with cryptographic hashes of data blocks L1-L4, respectively. Also, for illustrative purposes, non-leaf nodes 310-314 are labelled with cryptographic hashes of the labels of their child nodes. Therefore, the non-leaf node 310 is labelled with the cryptographic hash of the labels of its child nodes, Hash 0-0 and Hash 0-1. Similarly, the non-leaf node 312 is labelled with the cryptographic hash of the labels of its child nodes, Hash 1-0 and Hash 1-1, and the non-leaf node 314 (which is also the Merkle tree root in this example) is labelled with the cryptographic hash of the labels of its child nodes, Hash 0 and Hash 1. In some embodiments, the owner may store the Merkle tree in a storage device. The storage device used for storing the Merkle tree may be implemented in various manners. In some embodiments, the owner may store

the Merkle tree in a local data storage device. In some embodiments, the owner may store the Merkle tree on one or more cloud-based storage devices, distributed storage devices, or the like.

[0039] In some embodiments, to calculate the privacy-preserving representation of the attribute values, the owner may calculate the hashes of the attribute values and store the calculated hashes on the leaf nodes of a Merkle tree. For illustrative purposes, suppose the attribute values can be represented generally as:

$$\left\{ \begin{array}{l} attribute_1: value_1 \\ attribute_2: value_2, \\ \vdots \\ attribute_N: value_N \end{array} \right\},$$

where $\{attribute_i: value_i\}$ represents the value $value_i$ of a particular attribute $attribute_i$, then the Merkle tree with the calculated hashes stored therein may be depicted as shown in FIG. 4.

[0040] For example, as shown in FIG. 4, the values of the Merkle tree leaf nodes may be calculated based on the hashes of the different attribute-value pairs, $attribute_1: value_1$ through $attribute_N: value_N$. The values of the non-leaf nodes may be calculated as the hashes of their corresponding child nodes. Also shown in FIG. 4 is a cryptographic nonce (e.g., an arbitrary number) that may be used in some embodiments to randomize the root hash. Randomizing the root hash in this manner may help prevent other users from guessing the values of the attributes through trial and error.

[0041] For illustrative purposes, suppose the owner wants to record an NFT that represents a non-fungible asset on the blockchain system 100, and further suppose that the asset is associated with three attributes (e.g., the name of the artist who created the artwork, the date of creation, and a thumbprint of the artwork). FIG. 5 is a

schematic diagram depicting a Merkle tree with hashes of the three attributes plus a nonce stored therein. As shown in FIG. 5, values of the leaf nodes, denoted as Hash 1, Hash 2, and Hash 3, are calculated based on the hashes of the different attribute-value pairs $attribute_1: value_1$ through $attribute_3: value_3$. The value of the remaining leaf node, denoted as Hash 4, is calculated based on the hash of the nonce. The values of the non-leaf nodes are calculated as hashes of their respective child nodes. Accordingly, the value of the root node, which may be referred to as the Merkle tree root hash, can be calculated. Similarly, FIG. 6 is a schematic diagram depicting a Merkle tree with hashes of six attributes plus a nonce stored therein, and the values of the non-leaf nodes depicted in FIG. 6, including the value of the root node, may be calculated accordingly, as described above.

[0042] In some embodiments, once the Merkle tree root hash is calculated, the owner may use the Merkle tree root hash as the privacy-preserving representation of the attribute values and record the privacy-preserving representation of the attribute values as the *Metadata* of the NFT on the blockchain system 100. In this manner, the owner may keep the plaintext values of the attributes private, and the other users of the blockchain system 100 may not be able to obtain the plaintext values of the attributes by reading the *Metadata* of the NFT recorded on the blockchain system 100, thus preserving the privacy of the NFT.

[0043] Furthermore, recording the privacy-preserving representation of the attribute values as the *Metadata* of the NFT may also support verification of the validity of the NFT without revealing any plaintext values of the attributes, as described below.

[0044] In some embodiments, the owner may provide the hashes stored on the Merkle tree that correspond to the values associated with the set of attributes to a

verifier to facilitate a verification of the validity of the token without revealing any values associated with the set of attributes. For example, if the NFT represents an artwork, which is associated with attributes including, e.g., the name of the artist who created the artwork, the date of creation, a thumbprint of the artwork, and an IPFS link of the artwork, then the owner may provide the hashes that correspond to the values associated with these attributes to the verifier (e.g., a buyer of the NFT or a third party). If the owner provides the verifier with hashes for a different set of attributes (e.g., if the owner fails to provide a hash that corresponds to the name of the artist who created the artwork, or if the owner provides a different number of hashes than expected), then the verifier may consider the NFT to be invalid and therefore refuse to accept the NFT.

[0045] In some embodiments, if the owner used a nonce to calculate the privacy-preserving representation, the owner may also provide the hash of the nonce to the verifier. The verifier may verify whether the owner calculated the privacy-preserving representation recorded in the *Metadata* field of the NFT correctly based on the hashes provided by the owner. For example, the verifier may independently create a Merkle tree that stores the owner-provided hashes (including hashes that correspond to the values associated with the set of attributes and the hash that corresponds to the nonce, if the nonce is used to calculate the privacy-preserving representation). In some embodiments, both the owner and the verifier may create their respective Merkle trees in a deterministic manner. For example, both the owner and the verifier may create their respective Merkle trees as binary Merkle trees with leaf nodes organized in a particular manner (e.g., alphabetically according to the attribute names). In this manner, the verifier may calculate a Merkle tree root hash based on the Merkle tree created by the verifier, and the Merkle tree root hash calculated by the verifier should match the Merkle tree root hash calculated by the

owner.

[0046] In some embodiments, the verifier may determine whether the Merkle tree root hash calculated by the verifier matches the Merkle tree root hash calculated by the owner based on the privacy-preserving representation recorded in the *Metadata* field of the NFT. For example, the verifier may retrieve the privacy-preserving representation recorded in the *Metadata* field of the NFT from the blockchain system 100 and compare the retrieved privacy-preserving representation against the verifier-calculated Merkle tree root hash. If the retrieved privacy-preserving representation matches the verifier-calculated Merkle tree root hash, then the verifier may accept the validity of the NFT. On the other hand, if the retrieved privacy-preserving representation does not match the verifier-calculated Merkle tree root hash, the verifier may refuse to accept the validity of the NFT and refuse to carry out any transactions associated with that NFT.

[0047] In some embodiments, the verifier may be a user of the blockchain system 100. In some embodiments, the verifier may be a trusted party (e.g., an administrator or an agency trusted by users of the blockchain system 100). In some embodiments, the owner may provide the hashes to the verifier through an off-chain communication channel, which may include various types of wired or wireless communication channels, such as the Internet, electronic mails, file transfer applications, text messages, and the like. Upon receiving the hashes from the owner, the verifier may invoke a verification program that takes the hashes as input and performs the verification process described above (including calculating a Merkle tree root hash and comparing the calculated Merkle tree root hash with the privacy-preserving representation recorded on the blockchain system 100). In some embodiments, the verification program invoked by the verifier may be carried out on a

computing device that does not participate in the blockchain system 100. In some embodiments, the verifier may invoke one or more smart contracts executing on the blockchain system 100 to perform the verification.

[0048] Smart contracts are computer protocols implemented in the form of computer code that are incorporated into the blockchain, to facilitate, verify, or enforce the negotiation or performance of agreed terms or conditions. For example, users of the blockchain system 100 may program agreed terms into a smart contract using a programming language, such as C++, Java, Solidity, Python, etc., and when the terms are met, the smart contract may be automatically executed on the blockchain system 100. Also for example, the smart contract may include a plurality of subroutines or functions, each of which may be a sequence of program instructions that performs a specific task. The smart contract may be operational code that is fully or partially executed without human interaction. In some embodiments, the blockchain system 100, through one or more smart contracts executing on the blockchain system 100, may receive as input the hashes provided by the owner. In this manner, the blockchain system 100, through one or more smart contracts executing thereon, may perform the verification process described above.

[0049] FIG. 7 illustrates a flow chart of a method 700 for verifying validity of a token, according to an embodiment. For illustrative purposes, a Blockchain, e.g., the blockchain 120 (FIG. 1), is depicted in FIG. 7. The Blockchain may be implemented to support various types of users, or parties, including, e.g., individuals, businesses, banks, financial institutions, as well as other types of companies, organizations, and the like. For illustrative purposes, a user, referred to as an Owner, is depicted in FIG. 7, and the operations of the Owner described below are performed by a computing device of the Owner.

[0050] At step 702, the Owner may create (or “mint”) a token representing an asset owned by the Owner. As described above, in some embodiments, the asset may be represented by a token that includes an identifier and a metadata field, $\{ID: Metadata\}$. In some embodiments, the asset represented may be unique and not interchangeable (i.e., a non-fungible asset). In such embodiments, the token representing the asset may be referred to as a non-fungible token (NFT).

[0051] At step 704, the Owner may calculate the *Metadata* of the token. As described above, the Owner may calculate a privacy-preserving representation of a set of attributes and record the privacy-preserving representation as the *Metadata* of the token. In some embodiments, the Owner may calculate the privacy-preserving representation by calculating a Merkle tree root hash according to a function, and the function may be defined based on a value associated with each attribute of the set of attributes. In some embodiments, the function may include a Merkle tree root hash function that calculates a Merkle tree root hash based on the value associated with each attribute of the set of attributes, and in some embodiments, the value associated with each attribute of the set of attributes may have a corresponding hash stored on a leaf node of the Merkle tree. Furthermore, in some embodiments, the function may also be defined based on a cryptographic nonce. In some embodiments, the cryptographic nonce may have a corresponding hash stored on a node of the Merkle tree.

[0052] At step 706, the Owner may record the token on the Blockchain. As described above, in some embodiments, the Owner may record the privacy-preserving representation of the set of attributes on the Blockchain as the *Metadata* of the token. In some embodiments, the Owner may encrypt the *ID* of the recorded token. In some embodiments, the encryption of the *ID* may be optional and is not required.

[0053] At step 708, the Owner may provide, e.g., by wired or wireless transmission, the hashes stored on the Merkle tree that correspond to the values associated with the set of attributes to a verifier to facilitate a verification of the validity of the token without revealing any values associated with the set of attributes. As described above, in some embodiments, the Verifier may be a user of the Blockchain or a trusted party, and in some embodiments, the Verifier may choose to invoke a verification program or a smart contract deployed in the Blockchain to verify the validity of the token. While specific implementations may vary, the Verifier may, at step 710, obtain the token recorded on the Blockchain and carry out the verification process described above at step 712.

[0054] In some embodiments, the verification process may include, e.g., calculating a Merkle tree root hash and comparing the calculated Merkle tree root hash with the metadata of the token obtained from the Blockchain. In some embodiments, if the Merkle tree root hash calculated by the Verifier matches the metadata of the token, then the verifier may accept the NFT as valid. On the other hand, if the Merkle tree root hash calculated by the Verifier does not match the metadata of the token, the Verifier may refuse to accept the validity of the NFT because the mismatch may indicate that the Owner is not the true owner of the NFT or that the Owner has attempted to change one or more hashes recorded on the Merkle tree after the Owner has recorded the token on the Blockchain. In either case, if the Merkle tree root hash calculated by the Verifier does not match the metadata of the token, the Verifier may refuse to carry out any transactions associated with that NFT.

[0055] FIG. 8 illustrates a flow chart of a method 800 for verifying validity of a token, according to an embodiment. The method 800 may be performed by a computing device communicating with a blockchain system, e.g., the blockchain

system 100 (FIG. 1). The blockchain system may include a plurality of nodes, e.g., nodes 102-110, configured to operate on a blockchain 120. The blockchain 120 may be implemented as the Blockchain in the examples described above. The computing device may or may not be a node of the blockchain system.

[0056] In some embodiments, a user (e.g., the creator or the author of an asset) may generate a privacy-preserving token based on steps 802 and 804. At step 802, the user may utilize the computing device (e.g., the computing device 200) to calculate a privacy-preserving representation of a set of attributes by calculating a Merkle tree root hash based on a value associated with each attribute of the set of attributes. In some embodiments, the user may calculate the privacy-preserving representation according to a function defined based on the value associated with each attribute of the set of attributes. In some embodiments, the function may include a Merkle tree root hash function that calculates a Merkle tree root hash based on the value associated with each attribute of the set of attributes, and in some embodiments, the value associated with each attribute of the set of attributes may have a corresponding hash stored on a leaf node of the Merkle tree. Furthermore, in some embodiments, the function may be further defined based on a cryptographic nonce. In some embodiments, the cryptographic nonce may have a corresponding hash stored on a node of the Merkle tree.

[0057] At step 804, the user may record the privacy-preserving representation of the set of attributes on the blockchain system. In some embodiments, the user may utilize the computing device to submit the privacy-preserving representation of the set of attributes to the blockchain system for recordation. Upon receiving the privacy-preserving representation submitted by the user, the blockchain system may record the privacy-preserving representation on a blockchain of the blockchain system. In

some embodiments, the blockchain system may record the privacy-preserving representation as metadata of the token. In some embodiments, the blockchain system may also record an identifier of the token, and in some embodiments, the identifier of the token may be encrypted.

[0058] At step 806, the user may identify hashes stored on a plurality of nodes of the Merkle tree that can be utilized to calculate the Merkle tree root hash. In some embodiments, the identified hashes may include the hash stored on the leaf node of the Merkle tree that corresponds to the value associated with each attribute of the set of attributes. In some embodiments, the identified hashes may include certain non-leaf nodes of the Merkle tree. For example, the identified hashes may include Hashes D and E depicted in FIG. 6. In another example, the identified hashes may include Hashes A, B, and E depicted in FIG. 6. It is to be understood that the nodes depicted in FIG. 6 are merely referenced as examples and are not meant to be limiting. It is contemplated that the user may identify the hashes in various manners as long as the hashes identified can be utilized to calculate the Merkle tree root hash.

[0059] At step 808, the user may provide, e.g., via wired or wireless transmission, the identified hashes stored on the plurality of nodes of the Merkle tree that can be utilized to calculate the Merkle tree root hash to a verifier to facilitate a verification of the validity of the token without revealing any values associated with the set of attributes. In some embodiments, the user who performs the steps 806 and 808 may be the same as the user who performed the steps 802 and 804. For example, in some embodiments, the user may be the creator of the asset, and the user may perform the steps 806 and 808 after recording the metadata of the token on the blockchain system. Alternatively, in some embodiments, the user who performs the steps 806 and 808 may be different from the user who performed the steps 802 and

804. For example, the creator of the asset may have transferred the ownership of the token to a different owner. Therefore, in some embodiments, the steps 802 and 804 may be performed by the creator of the asset, and the steps 806 and 808 may be performed by the owner of the asset, who may or may not be the same as the creator.

[0060] In some embodiments, the verifier may be a user of the blockchain system or a trusted party. In some embodiments, the verifier may be a smart contract deployed in the blockchain system that can be utilized to verify the validity of the token. At step 810, the verifier may receive the hashes stored on the plurality of nodes of the Merkle tree that can be utilized to calculate the Merkle tree root hash, and at step 812, the verifier may calculate a root hash based on the hashes received. At step 814, the verifier may obtain the token recorded on the blockchain system, and at step 816, the verifier may verify the validity of the token based on the calculated root hash (i.e., the Merkle tree root hash calculated based on the hashes received) without knowing the value associated with each attribute of the set of attributes. In some embodiments, if the verifier determines that the Merkle tree root hash calculated based on the hashes received matches the metadata of the token recorded on the blockchain system, the verifier may accept the token as valid. On the other hand, if the verifier determines that that the Merkle tree root hash calculated based on the hashes received does not match the metadata of the token recorded on the blockchain system, the verifier may refuse to accept the validity of the token and refuse to carry out any transactions associated with that token.

[0061] FIG. 9 is a block diagram of an apparatus 900 for verifying validity of a token, according to an embodiment. The apparatus 900 may be an implementation of a software process, and may correspond to the method 800 (FIG. 8). Referring to FIG. 9, the apparatus 900 may include a calculation module 902, a recording module

904, and an interface module 906.

[0062] The calculation module 902 may calculate a privacy-preserving representation of a set of attributes, as described above, and provide the calculated privacy-preserving representation to the recording module 904. The recording module 904 may communicate with a data storage system, e.g., a blockchain system, to record the privacy-preserving representation of the set of attributes on the data storage system. The interface module 906 may provide information to a verifier to facilitate a verification of the validity of the token without revealing any values associated with the set of attributes, as described above.

[0063] Each of the above-described modules may be implemented as software, or hardware, or a combination of software and hardware. For example, each of the above described modules may be implemented using a processor executing instructions stored in a memory. Also, for example, each the above described modules may be implemented with one or more application specific integrated circuits (ASICs), digital signal processors (DSPs), digital signal processing devices (DSPDs), programmable logic devices (PLDs), field programmable gate arrays (FPGAs), controllers, micro-controllers, microprocessors, or other electronic components, for performing the described methods. Further for example, each of the above described modules may be implemented by using a computer chip or an entity, or implemented by using a product having a certain function. In one embodiment, the apparatus 900 may be a computer, and the computer may be a personal computer, a laptop computer, a cellular phone, a camera phone, a smartphone, a personal digital assistant, a media player, a navigation device, an email receiving and sending device, a game console, a tablet computer, a wearable device, or any combination of these devices.

[0064] For an implementation process of functions and roles of each module in the apparatus 900, references can be made to corresponding steps in the above-described methods. Details are omitted here for simplicity.

[0065] In some embodiments, a computer program product may include a non-transitory computer-readable storage medium having computer-readable program instructions thereon for causing a processor to carry out the above-described methods.

[0066] The computer-readable storage medium may be a tangible device that can store instructions for use by an instruction execution device. The computer-readable storage medium may be, for example, but is not limited to, an electronic storage device, a magnetic storage device, an optical storage device, an electromagnetic storage device, a semiconductor storage device, or any suitable combination of the foregoing. A non-exhaustive list of more specific examples of the computer-readable storage medium includes the following: a portable computer diskette, a hard disk, a random access memory (RAM), a read-only memory (ROM), an erasable programmable read-only memory (EPROM), a static random access memory (SRAM), a portable compact disc read-only memory (CD-ROM), a digital versatile disk (DVD), a memory stick, a floppy disk, a mechanically encoded device such as punch-cards or raised structures in a groove having instructions recorded thereon, and any suitable combination of the foregoing.

[0067] The computer-readable program instructions for carrying out the above-described methods may be assembler instructions, instruction-set-architecture (ISA) instructions, machine instructions, machine dependent instructions, microcode, firmware instructions, state-setting data, or source code or object code written in any combination of one or more programming languages, including an object oriented

programming language, and conventional procedural programming languages. The computer-readable program instructions may execute entirely on a computing device as a stand-alone software package, or partly on a first computing device and partly on a second computing device remote from the first computing device. In the latter scenario, the second, remote computing device may be connected to the first computing device through any type of network, including a local area network (LAN) or a wide area network (WAN).

[0068] The computer-readable program instructions may be provided to a processor of a general-purpose or special-purpose computer, or other programmable data processing apparatus to produce a machine, such that the instructions, which execute via the processor of the computer or other programmable data processing apparatus, create means for implementing the above-described methods.

[0069] The flow charts and diagrams in the figures illustrate the architecture, functionality, and operation of possible implementations of devices, methods, and computer program products according to various embodiments of the specification. In this regard, a block in the flow charts or diagrams may represent a software program, segment, or portion of code, which comprises one or more executable instructions for implementing specific functions. It should also be noted that, in some alternative implementations, the functions noted in the blocks may occur out of the order noted in the figures. For example, two blocks shown in succession may, in fact, be executed substantially concurrently, or the blocks may sometimes be executed in the reverse order, depending upon the functionality involved. It will also be noted that each block of the diagrams and/or flow charts, and combinations of blocks in the diagrams and flow charts, may be implemented by special purpose hardware-based systems that perform the specified functions or acts, or combinations of special purpose hardware

and computer instructions.

[0070] It is appreciated that certain features of the specification, which are, for clarity, described in the context of separate embodiments, may also be provided in combination in a single embodiment. Conversely, various features of the specification, which are, for brevity, described in the context of a single embodiment, may also be provided separately or in any suitable subcombination or as suitable in any other described embodiment of the specification. Certain features described in the context of various embodiments are not essential features of those embodiments, unless noted as such.

[0071] Although the specification has been described in conjunction with specific embodiments, many alternatives, modifications and variations will be apparent to those skilled in the art. Accordingly, the following claims embrace all such alternatives, modifications and variations that fall within the terms of the claims.

What Is Claimed Is:

1. A computer-implemented method for generating a privacy-preserving token, the method comprising:

calculating a privacy-preserving representation of a set of attributes associated with the token, wherein calculating the privacy-preserving representation comprises calculating a Merkle tree root hash based on a value associated with each attribute of the set of attributes, wherein the value associated with each attribute of the set of attributes has a corresponding hash stored on a leaf node of the Merkle tree; and

recording the privacy-preserving representation of the set of attributes on a blockchain system as metadata of the token.

2. A computer-implemented method for verifying validity of a privacy-preserving token, wherein a privacy-preserving representation of a set of attributes is calculated by calculating a Merkle tree root hash based on a value associated with each attribute of the set of attributes and is recorded on a blockchain system as metadata of the token, and the value associated with each attribute of the set of attributes has a corresponding hash stored on a leaf node of the Merkle tree, the method comprising:

identifying hashes stored on a plurality of nodes of the Merkle tree that can be utilized to calculate the Merkle tree root hash; and

providing the identified hashes stored on the plurality of nodes of the Merkle tree to a verifier, to facilitate a verification of the validity of the token without revealing the value associated with each attribute of the set of attributes.

3. A computer-implemented method for verifying validity of a privacy-preserving token, wherein a privacy-preserving representation of a set of attributes is calculated by calculating a Merkle tree root hash based on a value associated with each attribute of the set of attributes and is recorded on a blockchain system as metadata of the token, and the value associated with each attribute of the set of attributes has a corresponding hash stored on a leaf node of the Merkle tree, the method comprising:

receiving hashes stored on a plurality of nodes of the Merkle tree that can be utilized to calculate the Merkle tree root hash;

calculating a root hash based on the hashes received;

obtaining the token recorded on the blockchain system; and

verifying the validity of the token based on the calculated root hash without knowing the value associated with each attribute of the set of attributes.

4. The method of any preceding claim, wherein the token comprises: a token identifier and the metadata of the token.

5. The method of any preceding claim, wherein the token is a non-fungible token.

6. The method of any preceding claim, wherein the privacy-preserving representation is calculated by calculating the Merkle tree root hash based on a cryptographic nonce.

7. The method of claim 6, wherein a hash corresponding to the cryptographic nonce is stored on a node of the Merkle tree.

8. The method of any preceding claim, wherein the hashes stored on the plurality of nodes of the Merkle tree that can be utilized to calculate the Merkle tree root hash comprise the hash stored on the leaf node of the Merkle tree that corresponds to the value associated with each attribute of the set of attributes.
9. The method of any preceding claim, wherein a smart contract is deployed in the blockchain system to verify the validity of the token.
10. The method of claim 3, wherein the verifying the validity of the token comprises:
comparing the calculated root hash based on the hashes received with the metadata of the token recorded on the blockchain system.
11. The method of claim 10, wherein the verifying the validity of the token further comprising:
accepting the token as valid in response to a determination that the calculated root hash matches the metadata of the token recorded on the blockchain system.
12. A device for processing a token, comprising:
one or more processors; and
one or more computer-readable memories coupled to the one or more processors and having instructions stored thereon that are executable by the one or more processors to perform the method of any of claims 1 to 11.
13. An apparatus for processing a token, the apparatus comprising a plurality of modules for performing the method of any of claims 1 to 11.

14. A non-transitory computer-readable medium having stored therein instructions that, when executed by a processor of a device, cause the device to perform the method of any of claims 1 to 11.