

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
4 November 2004 (04.11.2004)

PCT

(10) International Publication Number
WO 2004/094290 A3

(51) International Patent Classification⁷: **B66B 13/26**,
E05F 15/00

Christopher [GB/GB]; September Cottage, Murrell Hill
Lane, Binfield, Berkshire RG12 5DA (GB).

(21) International Application Number:
PCT/GB2004/001764

(74) Agents: **MOIR, Michael, Christopher** et al.; Mathys &
Squire, 100 Gray's Inn Road, London WC1X 8AL (GB).

(22) International Filing Date: 26 April 2004 (26.04.2004)

(81) Designated States (*unless otherwise indicated, for every
kind of national protection available*): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0309310.1 24 April 2003 (24.04.2003) GB

(71) Applicant (*for all designated States except US*): **MEMCO
LIMITED** [GB/GB]; Memco House, Waldeck Road,
Maidenhead, Berks SL6 8BZ (GB).

(84) Designated States (*unless otherwise indicated, for every
kind of regional protection available*): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),


(72) Inventor; and

(75) Inventor/Applicant (*for US only*): **PLATT, Terence,**

[Continued on next page]

(54) Title: MULTIFUNCTION EDGE DEVICE FOR POWERED DOORS

(57) Abstract: An edge device for an elevator door includes an
elongate array of infrared transmitters and/or receivers and a proximate
elongate array of illuminable elements, both arrays extending for a
substantial part of the length of the door. The illuminable elements are
adapted to be illuminated when the door is in motion. The two arrays
are disposed in a common carrier structure, being either vertically
interleaved or extending vertically in parallel with each other.





European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

(88) Date of publication of the international search report:
10 February 2005

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.