

Description

Technical Field

The present invention generally relates to a photographic optical system in accordance with the generic part of claim 1 and to a camera in which such a photographic optical system is used. Such a system is for example known from DE-A- 33 36 265.

This application is related to the commonly assigned application filed on even date herewith, international publication No. WO 87/07036, entitled "Zoom Lens Drive System for lens shutter type of Camera", the disclosure of which is expressly incorporated by reference herein.

One primary object of the present invention is to provide a photographic optical system having a rotatable cam ring with at least one groove therein and having at least one axially movable lens barrel, in this system light is prevented from entering the interior of the cam ring.

Another object is to provide a lens shutter type camera with a light intercepting assembly which minimizes light from entering a photographic optical assembly lens system.

DISCLOSURE OF INVENTION

A photographic optical system is provided which has a cam ring with at least one groove therein. The cam ring is rotatable in a constant axial position and a light blocking mechanism is used, the mechanism comprises at least one light intercepting member positioned about the periphery of the cam ring. The light intercepting member comprises means for covering each of the cam ring grooves and for preventing light from entering the interior of the cam ring.

In a photographic optical system having a cam ring rotatable in a constant axial position and at least one movable lens barrel movable along an optical axis of the photographing optical system in response to rotation of the cam ring, a light interception member is provided which is positioned in a space between a front end of a cam ring support member and a front cover having an opening through which the lens barrel is adapted to move.

In an other aspect of the present invention a camera is provided which has a photographic optical system with a rotatable cam ring and with a light blocking mechanism.

Other objects, features and advantages of the present invention will hereinafter be described.

BRIEF DESCRIPTION OF DRAWINGS

The above and other objects, features, and advantages of the present invention will be described in greater detail with respect to the accompanying draw-

ings, in which like reference numerals represent similar elements throughout the several views, and wherein:

Fig. 1 is an exploded perspective view of a photographic optical system in accordance with the present invention;

Fig. 2 is a schematic perspective view of an embodiment of a lens shutter type of camera having a photographic optical system formed in accordance with the present invention, and an exploded perspective view of a light intercepting mechanism positioned adjacent to a cam ring;

Fig. 3 is a longitudinal sectional view of a photographic optical system in a camera formed in accordance with the present invention;

Fig. 4 is a perspective view of a light intercepting ring;

Fig. 5 is a sectional view taken along line XXXVII-XXXVII of Fig. 4;

Fig. 6 is a sectional view of a second embodiment of a light intercepting ring formed in accordance with the present invention which is similar to the view of Fig. 5;

Fig. 7 is a front elevational view of a camera formed in accordance with the present invention.

BEST MODE FOR CARRYING OUT THE INVENTION

The present invention will now be described below in greater detail, with specific reference to the accompanying drawings which illustrate a variety of embodiments and features of the present invention.

The description will be generally provided in accordance with the following general sub headings:

- A. The Overall Camera Construction for a Lens Shutter Type of Camera
- B. Light Interception Assembly And Mechanism.

A. Overall Camera Construction for a Lens Shutter Type of Camera

The overall construction of a lens shutter type of camera formed in accordance with the present invention is well illustrated in Figs. 1, 2, 3 and 7. A lens shutter type of camera formed in accordance with the present invention essentially comprises a photographic optical system like a zoom lens barrel block 1. Additionally it comprises a finder and strobe block 2 (hereinafter referred to as a finder block), a light emitter 3 and a light receiver 4 forming a portion of a distance measuring, i.e., AF, device, and a zooming motor 5 which is used for the zooming operation of the photographing optical system. All of these elements are secured to a base 6 which forms an immovable portion of the camera body.

Base 6 includes, as is best illustrated in Fig. 3, a lens barrel supporting plate portion 6a which lies in a

plane which is perpendicular to the optical axis of the lens; and a horizontal supporting plate portion 6 is provided which extends at right angles from the lens barrel support plate portion 6a. Support plate portion 6 extends beyond the side edge of plate 6a, in order to support finder assembly 8 and strobe assembly 9. The base further comprises motor supporting plate portions 6 which are positioned perpendicularly with respect to the horizontal support plate portion 6. Lens barrel block 1 is supported on lens barrel support plate portion 6a, which has a central opening (unreferenced) for receiving the lens barrel block. A zooming motor 5 is attached to motor support plate portions 6 and is located above the central portion of lens barrel block 1. Preferably, only a single such motor (e.g., a DC motor) is used to drivingly engage all of the movable elements of the system. A distance measuring device includes a light emitter 3 and a light receiver 4, which are secured to the horizontal support plate portion of base 6, and which are located on opposite sides of zooming motor 5.

Finder block 2 is secured to the right hand portion of horizontal support plate portion 6, as viewed from the front of the camera.

Lens barrel block 1 is adapted to be actuated by zooming motor 5, and the construction of this block will be described hereinbelow with more specific reference to Figs. 1-3. A rear securing plate 11 is mounted to lens barrel support plate portion 6a of base 6 by fastening screws 10, as is best illustrated in Fig. 3. Rear securing plate 11 includes four guide rods 12 which are attached to and through bores in the rear portion of the guide plate and which are located about the optical axis of the photographing optical system and parallel to this axis. A front securing plate 13 is secured to the front ends of guide rods 12; these guide rods and plates are the main securing elements for lens barrel block 1.

A rotatable cam ring 14 is positioned between front and rear securing plates 13 and 11, respectively; a sector gear 15 is provided about a substantial portion (but preferably not the entire 360°) of the outer periphery of cam ring 14; this gear can be attached to the cam ring by conventional means, e.g., via set screws 15a, as seen in Fig. 3; this gear is adapted to engage, either directly or indirectly, a first pinion 7 (Fig. 2) which is positioned between the gear train support plate and the motor support plate portion. Gear 15 can be a sector gear which will cover a predetermined range of rotational movement of cam ring 14. The cam ring is itself provided with zooming cam grooves 20 and 21 (see Fig. 1) which are used to engage the front and rear lens element groups, respectively.

A roller 17, as illustrated in both Figs. 1 and 3, is positioned within zooming cam groove 20; this roller is attached to a front lens group frame 16. A roller 19 of rear lens group frame 18 is positioned within zoom-

ing cam groove 21, again as illustrated in Figs. 1 and 3. Front lens group frame 16 and rear lens group frame 18 are movably guided by guide rods 12, and a decorative frame 22 and shutter block 23 are secured to the front lens group frame 16 via set screws 22a, as best seen in the exploded view of Fig. 1, as well as in the cross-sectional view of Fig. 3.

The front lens frame 24 which supports front lens element group L1 is engaged by shutter block 23 via helicoid 25, which is shown in Fig. 1. Front lens frame 24 includes an arm 24a which engages lens feeding lever 23a of shutter block 23 (see Fig. 3), so that when lens feeding lever 23a rotates in a circumferential direction in order to rotate front lens frame 24, the front lens frame will move along the direction of the optical axis of the photographing optical system under the guidance of helicoid 25. Rear lens element group L2 is directly attached to rear lens group frame 18, as seen in Fig. 3. One desired configuration of lens groups L1 and L2, as illustrated in Fig. 3, are disclosed in commonly assigned U.S. Patent Application Serial No. 935,982, filed on November 28, 1986, the disclosure of which is expressly incorporated by reference herein.

The structure of shutter block 23 is known per se. This shutter block rotates lens feeding lever 23a over a predetermined angular displacement in accordance with a detection signal which is received by the shutter block from the distance measuring device, as described hereinafter, via a pulse motor which is incorporated within the camera body and which is adapted to open shutter sector 23b, which has been closed for a predetermined time, and to thereafter return lens feeding lever 23a into its original position after the shutter has again closed. This type of shutter block is disclosed, e.g., in unexamined Japanese Published Patent Application (KOKAI) No. 60-235,126, dated November 21, 1985, the disclosure of which is expressly incorporated by reference herein. The present camera utilizes such a shutter block in the fundamental way disclosed therein.

Finder block 2 includes finder assembly 8 and strobe assembly 9. The finder device and the strobe device are adapted to vary, respectively, the field of finder view and the illumination angle, i.e., the intensity of the strobe, in accordance with variance in the focal length of the lens barrel block 1. Zooming motor 5 is used as a power source both for finder control and strobe control; only a single motor need therefore be used.

As seen in Fig. 2, sector gear 15 of cam ring 14 is engaged by a second pinion 50 which is different from the first pinion 7 referred to previously. Shaft 51, to which pinion 50 is attached, extends rearwardly towards the rear portion of base 6, and is provided with a reduction gear train 52 adjacent a rear end of the shaft. The reduction gear train includes a final gear 52a which meshes with a rack 53a of movable cam

plate 53. This substantially flat cam plate 53 is slidable in right and left hand lateral directions, as viewed in Fig. 1, and includes a downwardly bent portion 53b at its rear end, as best shown in Fig. 2. Rack 53a is formed on the lower end of bent portion 53b of cam plate 53. Reduction gear train 52 is adapted to reduce rotation of gear 15 in order to restrict or limit the lateral movement of cam plate 53. The cam plate is provided with a variable power cam groove 55 for guiding movement of finder device 8, a parallax correction cam groove 56, and a strobe cam groove 57 for guiding movement of strobe device 9.

The lens system used in finder optical assembly 8 essentially comprises a subject lens group L3, an eyepiece group L4, and a movable variable power lens group L5, and further comprises a deflection prism P1 which is used when the camera is placed into the macro or close-up mode.

Variable power lens group L5 makes the image picture size, which is adapted to vary in accordance with the variable power operation of lens barrel block 1, be coincident with the field of view in finder device 8. Deflection prism P1 will enter the optical path of the finder lens system only in the macro mode, in order to adjust parallax which otherwise occurs in such mode. Specifically, parallax which inevitably occurs when using lens shutter type of cameras will increase as the subject whose picture is being taken approaches the camera; and, accordingly, a large parallax would normally result in the macro mode. In order to solve this problem and reduce the large parallax which otherwise occurs in the macro mode, deflection prism P1 is provided in the form of a wedge with a thicker lower end and a thinner upper end. Deflection prism P1, when located along the optical axis of the finder optical system, serves to deflect rays downwardly in order to take a picture of a subject which is located extremely close to the camera.

Strobe assembly 9 restricts or limits the illumination angle when the focal length of the photographing lens is large, namely, as the zoom lens is fed forwardly; and the strobe assembly 9 is moved to increase the illumination angle in the macro mode, in order to decrease the amount of light which reaches the subject. In the embodiment illustrated, strobe device 9 includes a fixed Fresnel Lens L6, a movable concave reflector 59, and a xenon lamp 58 which can be moved along the direction of the optical axis of the strobe. Alternately, a simple strobe could be used in which the illumination angle would be fixed. Although such a strobe arrangement is possible, it is preferable to move the lamp in the optical axis direction in accordance with movement of the zoom lens in order to optimize the quantity of light given to a subject during photography, dependent upon the position occupied by the photographing optical system in the zoom lens.

8. Light Interception Assembly and Mechanism

The light interception mechanisms are best illustrated in Figs. 2,3 and 4-6 of the present application.

In a lens shutter type of camera as described herein, the front and rear lens element groups can be independently moved along the photographing optical axis direction in order to effect a lens zooming operation. Since a gap exists between the front lens group frame 16 and the rear lens group frame 18, and since cam ring 14, which includes through cam grooves 20 and 21 for actuating movement of lens frames 16 and 18, is located about the outer peripheries of the lens frames, the possibility exists that undesirable light rays would otherwise penetrate into the photographic optical system of the camera through the gap between the front and rear lens group frames and through the cam grooves 20 and 21. Further, since front lens group frame 22 moves through opening 201 of front cover 200 (see Fig. 3), rays of light can also enter the camera via opening 201. The front cover 200 covers the front face of lens barrel block 1 and supports lenses L3 and L6 of the finder as well as strobe block 2. Opening 201 is formed along and defined by an inner flange 202 of front cover 200, so that the movable decorative frame 22, i.e., which includes the front group lens frame 16, will move through opening 201 when the camera is in its zooming operation. An annular space 203 having a relatively small width W is provided between inner flange 202 and front stationary plate 13. The front stationary plate is substantially annular in configuration.

In order to prevent rays of light from penetrating into the camera, as noted above, a light intercepting mechanism has been provided. Specifically, a light intercepting assembly 210 which comprises a plurality of sections is provided about the outer periphery of cam ring 14 and is adapted to cover through or continuous cam grooves 20 and 21 in order to intercept rays of light and prevent them from entering the interior of lens barrel block 1. In the embodiment illustrated in Fig. 2, intercepting assembly 210 comprises a gear ring 15, a flexible code plate 90 which is adjacent to gear member 15 along one side of the gear member, and a light intercepting tape 211 which extends on the opposite side of the gear member 15. In other words, the annular gear member is located between the flexible code plate 90 which is wrapped about lens barrel block 1 over cam grooves 20 and 21, and the light tape 211, which is also flexible and which is wrapped about the lens barrel block so that it covers cam grooves 20 and 21.

Code plate 90 is provided to detect the angular position of cam ring 14 in order to automatically detect a change in the focal length of the zoom lens, a change of the F number which will vary in accordance with the changing focal length of the zoom lens, the

extreme wide angle position of the zoom lens, the extreme telephoto position of the zoom lens, the collapsed position of the zoom lens, the extreme macro position of the zoom lens, e.g., in order to effect a variety of controls which are disclosed in detail hereinafter with respect to the mechanism for detecting the position of the zoom lens and for deciphering information relating to the position of the zoom lens.

A not shown Brush includes independent (bristles) terminals which can be connected to the code plate 90. When each of the terminals is electrically connected to the conductive lands 93 of code plate 90, a signal "0" is issued, and when each of the terminals are not electrically connected to conductive lands 93, a signal "1" is issued. The angular position of cam ring 14 can be detected by the combination of signals "0" and "1". A plurality of dummy terminals 94 are formed in conductive lands 93. The purpose of the dummy terminals, which are formed from the same material as conductive lands 93, is that the flexible code plate bent about the cam ring, and in order to improve the physical strength of the plate and still provide an area without electrical contact the dummy terminals were so positioned to increase flexibility while preserving strength. Additionally, these dummy terminals provide (non-conductive) lands upon which the terminals of the brush can ride as the cam ring is rotated.

Code plate 90 is formed from a flexible material having a light intercepting property. Intercepting tape 211 comprises a flexible material also having such a property, e.g., a dull-finish black paper. The code plate and the intercepting (paper) tape are applied to the cylindrical outer surface of cam ring 14, along opposite sides of gear member 15, in order to cover the major portions of zooming cam grooves 20 and 21. Gear 15 is preferably superimposed or overlapped over the side edges of the code plate and the intercepting tape in order to ensure the interception of rays of light, as illustrated in Fig. 3.

An annular light intercepting member 220 which forms an additional portion of the light intercepting assembly is provided in annular space 203, which is defined by the space between front stationary plate 13, which rotatably supports the front portion of cam ring 14, and front cover 200, as best seen in Fig. 3.

Annular light intercepting member 220 which is positioned within annular space 203 comprises an elastic annular body 221, e.g., rubber, and an annular reinforcing plate 222, so that the light intercepting member 220 will have the overall configuration of a substantially flat annular ring, as best illustrated in Figs. 4 and 5. The thickness w of light intercepting member 220 is slightly less than the width W of annular space 203, so that the light intercepting member 220 can move over a small distance within space 203, along the direction of the photographing optical axis.

Elastic body 221 of light intercepting member 220

is provided, along its inner periphery, with a light intercepting lip 223 having a small width which slidably contacts the outer periphery of decorative frame 220. Reinforcing plate 222 can be secured to elastic body 221, e.g., by partially imbedding the elastic body 221 into connecting recesses, holes or apertures 224 formed in reinforcing plate 222, which plate is made, e.g., of metal or synthetic resin. The inner lip 223 is extremely flexible and is capable of moving in either direction axially of a lens barrier block about which it is positioned. The lip can thus play a minor role in reducing rebound of the barrier block after it ceases movement in a first axial direction.

Fig. 6 illustrates a second embodiment of the annular ring illustrated in Figs. 4 and 5, in which two spaced light intercepting lips 223 (rather than merely one) are formed on the inner periphery of annular light intercepting member 220 in order to increase the light interception effect of the apparatus. These lips are spaced from each other in a parallel fashion and form a generally annular U-shaped, inwardly directed annular flange for the light intercepting member. Elastic body 221 is used to cover the outer periphery of reinforcing plate 222 in such structure.

Alternately, it would be possible to replace annular light intercepting member 220 with a conventional O-ring structure, which would be the simplest manner of intercepting light and preventing it from reaching undesired areas within the camera.

With such a light intercepting mechanism, undesirable light rays will not enter the camera lens system through the circumference of the front lens group frame 16 and/or the rear lens group frame 18, nor through the front annular opening between the lens barrel and camera cover.

Claims

1. A photographic optical system (1) having a cam ring (14) with at least one groove (20, 21) therein, said cam ring (14) being rotatable at a constant axial position, said system (1) further having at least one movable lens barrel (22, 23, 24, 25, L1) movable along an optical axis of said photographic system (1) in association with rotation of said cam ring (14) around said optical axis, characterised in that said system (1) has at least one light intercepting member (210) positioned about the periphery of said cam ring (14), said member (210) comprising means (211, 90) for covering each said camming groove (20, 21) and for preventing light from entering the interior of said cam ring (14).
2. A system in accordance with claim 1, wherein said light intercepting member (210) further comprises a flexible code plate (90) wrapped about



extreme wide angle position of the zoom lens, the extreme telephoto position of the zoom lens, the collapsed position of the zoom lens, the extreme macro position of the zoom lens, e.g., in order to effect a variety of controls which are disclosed in detail hereinafter with respect to the mechanism for detecting the position of the zoom lens and for deciphering information relating to the position of the zoom lens.

A not shown Brush includes independent (bristles) terminals which can be connected to the code plate 90. When each of the terminals is electrically connected to the conductive lands 93 of code plate 90, a signal "0" is issued, and when each of the terminals are not electrically connected to conductive lands 93, a signal "1" is issued. The angular position of cam ring 14 can be detected by the combination of signals "0" and "1". A plurality of dummy terminals 94 are formed in conductive lands 93. The purpose of the dummy terminals, which are formed from the same material as conductive lands 93, is that the flexible code plate bent about the cam ring, and in order to improve the physical strength of the plate and still provide an area without electrical contact the dummy terminals were so positioned to increase flexibility while preserving strength. Additionally, these dummy terminals provide (non-conductive) lands upon which the terminals of the brush can ride as the cam ring is rotated.

Code plate 90 is formed from a flexible material having a light intercepting property. Intercepting tape 211 comprises a flexible material also having such a property, e.g., a dull-finish black paper. The code plate and the intercepting (paper) tape are applied to the cylindrical outer surface of cam ring 14, along opposite sides of gear member 15, in order to cover the major portions of zooming cam grooves 20 and 21. Gear 15 is preferably superimposed or overlapped over the side edges of the code plate and the intercepting tape in order to ensure the interception of rays of light, as illustrated in Fig. 3.

An annular light intercepting member 220 which forms an additional portion of the light intercepting assembly is provided in annular space 203, which is defined by the space between front stationary plate 13, which rotatably supports the front portion of cam ring 14, and front cover 200, as best seen in Fig. 3.

Annular light intercepting member 220 which is positioned within annular space 203 comprises an elastic annular body 221, e.g., rubber, and an annular reinforcing plate 222, so that the light intercepting member 220 will have the overall configuration of a substantially flat annular ring, as best illustrated in Figs. 4 and 5. The thickness w of light intercepting member 220 is slightly less than the width W of annular space 203, so that the light intercepting member 220 can move over a small distance within space 203, along the direction of the photographing optical axis.

Elastic body 221 of light intercepting member 220

is provided, along its inner periphery, with a light intercepting lip 223 having a small width which slidably contacts the outer periphery of decorative frame 220. Reinforcing plate 222 can be secured to elastic body 221, e.g., by partially imbedding the elastic body 221 into connecting recesses, holes or apertures 224 formed in reinforcing plate 222, which plate is made, e.g., of metal or synthetic resin. The inner lip 223 is extremely flexible and is capable of moving in either direction axially of a lens barrier block about which it is positioned. The lip can thus play a minor role in reducing rebound of the barrier block after it ceases movement in a first axial direction.

Fig. 6 illustrates a second embodiment of the annular ring illustrated in Figs. 4 and 5, in which two spaced light intercepting lips 223 (rather than merely one) are formed on the inner periphery of annular light intercepting member 220 in order to increase the light interception effect of the apparatus. These lips are spaced from each other in a parallel fashion and form a generally annular U-shaped, inwardly directed annular flange for the light intercepting member. Elastic body 221 is used to cover the outer periphery of reinforcing plate 222 in such structure.

Alternately, it would be possible to replace annular light intercepting member 220 with a conventional O-ring structure, which would be the simplest manner of intercepting light and preventing it from reaching undesired areas within the camera.

With such a light intercepting mechanism, undesirable light rays will not enter the camera lens system through the circumference of the front lens group frame 16 and/or the rear lens group frame 18, nor through the front annular opening between the lens barrel and camera cover.

Claims

1. A photographic optical system (1) having a cam ring (14) with at least one groove (20, 21) therein, said cam ring (14) being rotatable at a constant axial position, said system (1) further having at least one movable lens barrel (22, 23, 24, 25, L1) movable along an optical axis of said photographic system (1) in association with rotation of said cam ring (14) around said optical axis, characterised in that said system (1) has at least one light intercepting member (210) positioned about the periphery of said cam ring (14), said member (210) comprising means (211, 90) for covering each said camming groove (20, 21) and for preventing light from entering the interior of said cam ring (14).
2. A system in accordance with claim 1, wherein said light intercepting member (210) further comprises a flexible code plate (90) wrapped about



one peripheral portion of said cam ring (14), a light intercepting tape (211) positioned about a second peripheral portion of said cam ring (14), and an annular gear (15) positioned about a third peripheral portion of said cam ring (14).

3. A system in accordance with claim 2, wherein said gear (15) is positioned between said code plate (90) and said intercepting tape (211).
4. A system in accordance with one of claims 1 to 3, wherein said cam ring (14) includes a plurality of grooves (20, 21).
5. A system in accordance with claim 1, wherein said light-intercepting member (210) is independent of, and positioned about, said cam ring (14).
6. A system in accordance with claim 1, wherein said light-intercepting member (210) comprises a flexible code plate (90).
7. A system in accordance with one of the preceding claims, wherein at least one light intercepting member (220) is positioned in a space (203) between a front end of a cam ring support (13) and a front cover (200) having an opening (201) through which said lens barrel (22, 23, 24, 25, L1) is adapted to move.
8. A system in accordance with one of the preceding claims, characterised in that said system (1) is a zooming optical assembly with variable focal length.
9. A camera comprising a photographic optical system (1) as claimed in any of the preceding claims.
10. A camera in accordance with claim 9, wherein the photographic optical system is automatically focussed in accordance with the distance of a subject from a film plane in said camera.

Patentansprüche

1. Fotografisches optisches System (1) mit einem mindestens eine Nockenrinne (20, 21) habenden Nockenring (14), der in einer konstanten axialen Stellung drehbar ist, mit mindestens einem beweglichen Objektivtubus (22, 23, 24, 25, L1), der in Abhängigkeit von der Drehung des Nockenringes (14) um die optische Achse entlang der optischen Achse des fotografischen optischen Systems (1) bewegbar ist, dadurch gekennzeichnet, daß das Objektiv (1) mindestens ein über der Mantelfläche des Nockenringes (14) angeordnetes Lichtabfangteil (210) hat, wobei dieses Licht-

abfangteil (210) aus Mitteln (211, 90) zum Abdecken jeder der Nockenrillen (20, 21) und zum Verhüten von Lichteinfall in das Innere des Nockenringes (14) besteht.

2. Ein System nach Anspruch 1, wobei das Lichtabfangteil (210) außerdem aus einer flexiblen, um einen Teil des Außenmantels des Nockenringes (14) gewickelten Codeplatte (90) besteht, aus einem auf einem zweiten Teil des Außenmantels des Nockenringes (14) angeordneten Lichtabfangband (211) und aus einem auf einem dritten Teil des Außenmantels des Nockenringes (14) angeordneten ringförmigen Zahnrad (15).
3. System nach Anspruch 2, wobei das Zahnrad (15) zwischen der Codeplatte (90) und dem Abfangband (211) angeordnet ist.
4. System nach einem der Ansprüche 1 bis 3, wobei der Nockenring (14) eine Vielzahl von Nockenrillen (20, 21) hat.
5. System nach Anspruch 1, wobei das Lichtabfangteil (210) unabhängig von dem Nockenring (14) ist und um diesen herum angeordnet ist.
6. System nach Anspruch 1, wobei das Lichtabfangteil (210) eine flexible Codeplatte (90) einschließt.
7. System nach einem der vorhergehenden Ansprüche, wobei mindestens ein Lichtabfangteil (220) in einem Zwischenraum (203) angeordnet ist zwischen einem vorderen Rand eines Nockenringträgers (13) und einer Frontabdeckung (200) mit einer Öffnung (201), durch die der Objektivtubus (22, 23, 24, 25, L1) hindurch bewegbar ist.
8. System nach einem der vorhergehenden Ansprüche, dadurch gekennzeichnet, daß das System (1) eine Variooptikanordnung mit variabler Brennweite ist.

9. Kamera mit einem fotografischen optischen System (1) wie in einem der vorhergehenden Ansprüche beansprucht.

10. Kamera nach Anspruch 9, wobei das fotografische optische System (1) automatisch in Abhängigkeit von dem Abstand eines Gegenstandes von einer Filmebene in der Kamera scharfeingestellt wird.

Revendications

1. Système optique de photographie (1) comportant



- une bague à cames (14) contenant au moins une rainure (20, 21), ladite bague à cames (14) étant mobile en rotation au droit d'une position axiale constante, ledit système (1) comprenant en outre au moins un barillet d'objectif mobile (22, 23, 24, 25, L1), mobile suivant l'axe optique dudit système de photographie (1), en association avec la rotation de ladite bague à cames (14) autour dudit axe optique, caractérisé en ce que ledit système (1) comporte au moins un élément d'interception de lumière (210) placé autour de la périphérie de ladite bague à cames (14), ledit élément (210) comprenant un moyen (211, 90) pour recouvrir chacune desdites rainures de came (20, 21) et pour empêcher la lumière de pénétrer à l'intérieur de ladite bague à cames (14).
2. Système selon la revendication 1, dans lequel ledit élément d'interception de lumière (210) comprend en outre une plaque de codage flexible (90) enroulée autour d'une partie périphérique de ladite bague à cames (14), une bande d'interception de lumière (211) placée autour d'une deuxième partie périphérique de ladite bague à cames (14), et un engrenage annulaire (15) placé autour d'une troisième partie de ladite bague à cames (14).
 3. Système selon la revendication 2, dans lequel ledit engrenage (15) est placé entre ladite plaque de codage (90) et ladite bande d'interception (211).
 4. Système selon l'une quelconque des revendications 1 à 3, dans lequel ladite bague à cames (14) comprend plusieurs rainures (20, 21).
 5. Système selon la revendication 1, dans lequel ledit élément d'interception de lumière (210) est indépendant de ladite bague à cames (14) et est placé autour de celle-ci.
 6. Système selon la revendication 1, dans lequel ledit élément d'interception de lumière (210) comprend une plaque de codage flexible (90).
 7. Système selon l'une quelconque des revendications précédentes, dans lequel au moins un élément d'interception de lumière (220) est placé dans un espace (203) entre l'extrémité avant d'un support de bague à cames (13) et un couvercle avant (200) comportant une ouverture (201) à travers laquelle ledit barillet d'objectif (22, 23, 24, 25, L1) est prévu pour se déplacer.
 8. Système selon l'une quelconque des revendications précédentes, caractérisé en ce que ledit système (1) est un ensemble optique de change-

ment de plan avec distance focale variable.

9. Appareil photo comprenant un système optique de photographie (1) selon l'une quelconque des revendications précédentes.
10. Appareil photo selon la revendication 9, dans lequel le système optique de photographie est mis au point automatiquement en fonction de la distance d'un objet par rapport à un plan de film dudit appareil photo.